UNCLASSIFIED

AD NUMBER
AD077567
LIMITATION CHANGES
TO: **Approved for public release; distribution is unlimited.**
FROM: **Distribution authorized to U.S. Gov't. agencies and their contractors; Administrative/Operational Use; AUG 1955. Other requests shall be referred to Ballistic Research Labs., Aberdeen Proving Ground, MD.**
AUTHORITY
BRL ltr, 22 Apr 1981

THIS PAGE IS UNCLASSIFIED

BRL
TN-1038
c.1A
REFERENCE COPY

[redacted]

CLASSIFIED

Code 304

UNCLASSIFIED

CATALOGED BY ASTIA
AS AD No. 77[illegible]

BRL

REFERENCE COPY
DOES NOT CIRCULATE
OCT 1996

TECHNICAL NOTE No. 1038

The Flight Mechanics Of Spinning Shell At Large Angles Of Initial Yaw (U)

NOTICE
This document is the property of the United States Government. It is furnished for the duration of the contract and shall be returned when no longer required, or upon recall by ASTIA to the following address: Armed Services Technical Information Agency, Document Service Center, Knott Building, Dayton 2, Ohio.

C. L. POOR

TECHNICAL LIBRARY
AMXBR-LB (Bldg. 305)
ABERDEEN PROVING GROUND, MD. 21005

[redacted]

DEPARTMENT OF THE ARMY PROJECT No. 5B03-07-002
ORDNANCE RESEARCH AND DEVELOPMENT PROJECT No. TB3-0426 (AIR)

BALLISTIC RESEARCH LABORATORIES

ABERDEEN PROVING GROUND, MARYLAND

56AA 1605
JAN 30 1956
UNCLASSIFIED

[redacted]

Retain or destroy per AR 380-5 and SR 345-215-5 or comparable AF or Navy Regulations. Contractors should consult their government contracting officers regarding procedures to be followed. DO NOT RETURN

The Ballistic Research Laboratories Technical Note is designed for use within the laboratories or for issuing available information, when the occasion demands speed.

The contents of this paper are of the nature of advance information and may be extended or otherwise revised.

This document contains information affecting the National Defense of the United States within the meaning of the Espionage Laws, Title 18 U.S.C. Sections 793 and 794. The transmission or the revelation of its contents in any manner to an unauthorized person is prohibited by law.

[redacted]

UNCLASSIFIED

BALLISTIC RESEARCH LABORATORIES

TECHNICAL NOTE NO. 1038

AUGUST 1955

THE FLIGHT MECHANICS OF SPINNING SHELL AT LARGE ANGLES OF INITIAL YAW (U)

C. L. Poor

This Note is essentially the same as the paper presented at the Tripartite Conference in Canada, October 1954.

TECHNICAL LIBRARY
AMXBR-LB (Bldg. 305)
ABERDEEN PROVING GROUND, MD. 21005

Department of the Army Project No. 5B03-07-002
Ordnance Research and Development Project No. TB3-0426(Air)

ABERDEEN PROVING GROUND, MARYLAND

UNCLASSIFIED

~~50AA 1005~~

[redacted]

~~8333~~

INTRODUCTION

The advent of supersonic flight, and the increasing certainty that supersonic speeds will be routine for both fighter and bomber aircraft within the next few years, have brought the problem of describing the motion of bullets launched with large initial yaw from a difficult low priority research investigation to an equally difficult problem of the utmost current engineering importance.

The practical problem can be simply stated - to describe the trajectories of bullets fired from aircraft with sufficient accuracy to permit the design of adequate fire control equipment. The trajectory data must be available to the fire control designer about two years before the equipment is to be ready. The airplanes are not available, so the predictions must be based on model tests and ground firings, for the most part.

In this paper we discuss the steps being taken at the Ballistic Research Laboratories to attempt to obtain the basic information needed to predict the paths of bullets launched cross-wind from aircraft whose speeds will be comparable to that of the bullets. The general plan of the research is described, together with some of the preliminary results, and some novel experimental techniques are reported.

FLIGHT CONDITIONS TO BE EXPECTED

Aircraft currently under development, to be armed with machine guns now undergoing test, are expected to fly at Mach numbers of the order of 2 and at altitudes of the order of 60,000 ft. Ammunition designed for these guns yields muzzle velocities of approximately 3,000 ft/sec. Figure 1 shows the initial yaw of the bullet as function of the gun angles off the airplane center line for a typical World War II bomber, and for a Mach No. 2 bomber, typical of the performance expected in the immediate future. The increasing severity of the launch conditions with the future airplane is what makes the problem. Figure 2 gives the aerodynamicist's view of the problem; it shows the initial yaw as function

of bullet Mach No. for the 30mm shell T306E10, for flight conditions specified by the U. S. Air Force.

With initial yaws as large as shown, there is no reason to believe that calculations based on the linearized theory of motion of shell (Ref. 1, 2, 3) should be adequate. Although the experimental firings of Simon and Sterne, (Ref. 2) gave a gratifying agreement with the predictions of linear theory, these firings in 1942 were conducted at an air speed of some 270 mph. The more recent firings off the rocket sled at the U. S. Naval Ordnance Test Station, Inyokern, (Ref. 4) are markedly at variance with the predictions of the linearized theory. Here the sled velocity was about 1,100 ft/sec, giving substantial initial yaws.

THE SOURCES OF AERODYNAMIC DATA ON SHELL

The principal sources of accurate aerodynamic data on shell are free flight aerodynamic ranges using the spark photography techniques developed during World War II by Charters at BRL, and supersonic wind tunnels. Both techniques have limitations which affect their application to the problem at hand.

The free flight ranges have been developed into instruments of great precision, capable of yielding the path of the center of gravity of shell to an accuracy of about 0.01 inch, with timing accuracy of about one millionth of a second. From the photographs, the attitude of the shell can be determined within about 3 minutes of arc. With this sort of accuracy, it is possible to determine the drag of a bullet with about three significant figures, and to get two significant figure accuracy on the normal force coefficient by measuring the amplitude of the swerving motion, which amplitude is of the order of one caliber. However, this accuracy depends on a curve-fitting process - the motion of the shell is assumed to be that predicted by the linearized theory. If the aerodynamic force system is significantly non-linear, even though a good fit may be obtained with the assumed linear force system, the forces themselves may be grossly in error. This error shows up through a dependence of the results on initial conditions, as a scatter

in the results, not predictable from round to round. Due to the reduction procedures which must be used to obtain high precision, the ranges are blind to non-linearities.

Thus, unless the correct initial conditions are used, the range data say nothing about the trajectories to be expected with high initial yaws. For small yaws, where the linear theory may be expected to hold, they are by far the most accurate measuring device available to the exterior ballistician, but for the present problem the inability to launch shell with large initial yaw and zero yawing velocity makes them essentially useless by themselves.

The wind tunnel, on the other hand, is not bothered by non-linearities. Data have been available for many years on the variation of lift, drag, and pitching moment on bodies of revolution, through a range of angle of incidence large enough to exhibit large non-linear effects. The first static tests on the aerodynamics of shell at large yaw made in the BRL supersonic wind tunnel were carried out in 1947 (Ref. 5, 6). Walchner, at Gottingen, (Ref. 7) had carried out systematic measurements on the lift, drag, and moment characteristics of shell during World War II, although he covered a relatively limited range of angles of attack and Reynolds' No.

Until recently, however, little progress had been made in the development of techniques for the measurement of dynamic properties like the damping in pitch, and relatively little effort had been expended on measurement of the Magnus force and moment, the forces due to spin.

Data of the sort which has been available from the ranges and wind tunnels are shown in Figures 3 through 9. These are the results of recent measurements on the 30mm shell T306E10, whose outline is shown in the spark photograph, Figure 10.

AN ATTACK ON THE LARGE YAW PROBLEM

In principal, at least, it should always be possible to compute the motion of a rigid body through the air, given the initial conditions, and given enough information about the aerodynamic force system to compute the instantaneous linear and angular accelerations. Thus, with large scale electronic computers to do the computing for us, the problem reduces to an

aerodynamic one - the specification of the force system. This force system could be expected to depend on the following quantities, representative of the instantaneous condition of flight: Mach number, Air Density, Yaw Angle, Rate of Change of Yaw Angle, Axial Spin, Yawing Acceleration, Transverse Acceleration, Axial Acceleration.

Since an eight parameter non-linear specification of each of the six quantities required to establish the instantaneous force system seems to suggest a lifetime of experimentation, and since we can't measure some of the proposed dependences anyhow, we look for a simplified representation, which we hope will prove sufficient. The simplifications are based in part on reasonably good experimental grounds, and in part on theoretical estimates of the relative magnitudes involved. The simplified force system we are assuming can be represented as follows:

$$\begin{aligned}
\text{Lift} &= f_1(\text{Ma, Re, } \delta)\rho V^2 \\
\text{Drag} &= f_2(\text{Ma, Re, } \delta)\rho V^2 \\
\text{Pitching Moment} &= f_3(\text{Ma, Re, } \delta)\rho V^2 \\
\text{Damping Moment} &= f_4(\text{Ma, Re, } \delta)\rho V \dot{\delta} \\
\text{Damping Force} &= f_5(\text{Ma, Re, } \delta)\rho V \dot{\delta} \\
\text{Magnus Force} &= f_6(\text{Ma, Re, } \delta, \nu)\rho V^2 \\
\text{Magnus Moment} &= f_7(\text{Ma, Re, } \delta, \nu)\rho V^2 \\
\text{Axial Torque} &= f_8(\text{Ma, Re, } \nu)\rho V^2
\end{aligned}$$

Where ρ = Air Density $\qquad \dot{\delta}$ = Yawing Velocity

V = Velocity $\qquad \nu$ = Dimensionless Spin

δ = Yaw Angle $\qquad$ Ma = Mach No.

Re = Reynolds' No.

The assumption that the lift, drag, and pitching moments do not depend on spin is based on limited wind tunnel experiments on models with turbulent boundary layers. Happily, we have not been able to measure any effect of spin on these components, so, at least the dependence is small enough so that it can be neglected for the moment. Neglect of dependence of any of the force or moment components on linear or angular accelerations appears permissible, since these accelerations

are in general very small, and since estimates based on linear aerodynamic theory suggest the associated aerodynamic forces can safely be neglected. Neglect of Magnus forces and moments depending on the angular velocity normal to the shell axis is on rather shaky ground - the crude estimates we have made suggest these forces and moments should be small compared to the pitching moment and lift, and small compared to the Magnus force and moment in most cases. In any event, we have never been able to detect the effects of such forces and moments in the spark photography range experiments, and we cannot at this time measure them in the wind tunnel. Thus we will neglect them unless forced to include them by failure to predict correct trajectories with the present force and moment system.

If we can accept this force system as adequate, we should be able to define it completely using the wind tunnel, using rotating models for Magnus force and moment determination, and non-rotating oscillating models to measure the damping in pitch.

Once the force system is specified for the range of conditions expected in flight, yaw histories and trajectories will be computed using large-scale electronic computers available at BRL. Some of these trajectories, with initial conditions appropriate to airplane launch conditions, will make up the firing tables. Others will be used to test the assumptions about the force system.

To test our assumptions we plan to use the spark photography ranges. In the ranges we cannot get large initial yaws, but we can easily obtain large initial yawing velocities by well-known techniques. The yaw histories, jump, and swerving motions will be different from those corresponding to the airplane case, but we will have large amplitude yawing motions, and great accuracy of experimental trajectory determination. If the force system assumed is inadequate, the inadequacy should be revealed by comparison between the computed motions for the range initial conditions, and the measured motions. Additional checks are planned by firings from the Inyokern track, where we should be able to get test trajectories with the correct initial conditions but limited to sea level densities. As a final check, some very limited firings from a specially instrumented

fighter airplane are contemplated, with correct initial conditions at operational altitudes.

WIND TUNNEL TECHNIQUES FOR MAGNUS MOMENT AND DAMPING IN PITCH

Personnel of the Supersonic Wind Tunnels Branch of the BRL's Exterior Ballistics Laboratory have developed what appear to be adequate techniques for the measurement of the Magnus force and moment on spinning shell models, and of the damping in pitch for non-spinning models. While no reports have as yet been published on this work, due to the very preliminary nature of the results, it seems worthwhile to make some mention of the techniques and exhibit preliminary results at this meeting.

The spinning model tests involve the use of a shell model driven by an air turbine, at speeds up to 40,000 rpm or higher, mounted on a 4-component strain gage balance. Figure 11 is a sketch of a typical installation, and Figure 12 shows a representative Magnus moment curve. Good results depend on very steady air flow in the wind tunnel, and great care in avoiding interactions in the balance system.

The damping in pitch measurements have been made using special struts supporting the model at the desired center of rotation by crossed flexure hinges, allowing one rotational degree of freedom, as shown in Figure 13. The inherent static instability of the model is overcome by proper choice of flexure stiffness, and the decay of small amplitude pitching oscillations induced by a remotely controlled tripping device is observed by recording the signal output from calibrated strain gages mounted on the flexures. Typical results are shown in Figure 14. With this technique accuracy of the order $\pm 10\%$ in the damping coefficient is obtainable, provided the tunnel flow is very steady, and provided very accurate measurements of the damping due to the flexures under load are available.

SUMMARY

The work at the Ballistic Research Laboratories on large yaw characteristics of shell has been shown to depend heavily on wind tunnel measurements and machine computations. Checks are to be obtained with free flight experiments. The program has advanced past the preliminary technique development stage, and systematic measurements on two shell are now underway. No final trajectory checks have as yet been made.

C. L. POOR


INITIAL YAW, δ_o, AS A FUNCTION OF ANGLE OFF THE BOW, θ
V_q = (AIRPLANE SPEED)/(MUZZLE VELOCITY)
V_q = 0.7
MACH No.2 BOMBER
V_q = 0.2
WORLD WAR 2 BOMBERS
δ_o Degrees
50
40
30
20
10
0
10
20
30
40
50
60
70
80
90
100
110
120
130
140
150
160
170
180
θ Degrees

Figure 1


Max α, Max. RPM and Max Normal
Load for the 30 mm Aircraft Bullet
Normal Load at αMax.
for 2" Model Tail
Gun only – Po = atm.
RPM
2" Model
αMax. 180° Traverse
αMax
Tail gun only
αMax. – ω RPM × 10⁻³ – N lbs at Po = atm
70
60
50
40
30
20
10
0
0
1.0
2.0
3.0
4.0
5.0
Mach No of Bullet

Figure 2


Confidential
Wind Tunnel
Range
K_{D_0}
.25
.20
.15
.10
.05
0
.5
1.0
1.5
2.0
2.5
3.0
3.5
4.0
4.5
Mach Number
DRAG DATA FOR 30 MM PROJECTILE

Figure 3



PITCH DATA FOR 30 MM PROJECTILE

Ma = 2.00 Figure 4 Re = .62 x 10^6


DRAG COEFFICIENT
VS
MACH NUMBER
30 MM SHELL HE T 306 E 10
$Q = \sqrt{1 + M^2 K_{D_o}} = .8414 + .2598 M$
.0003 STD. DEV.
K_{D_o}
.24
.20
.16
.12
.08
.04
.4
.8
1.2
1.6
2.0
2.4
2.8
3.2
3.6
MACH NUMBER

Figure 5


LIFT COEFFICIENT
VS
MACH NUMBER
30 MM SHELL HE T 306 E 10
K_L
1.2
0.8
0.4
.4
.8
1.2
1.6
2.0
2.4
MACH NUMBER

Figure 6


MOMENT COEFFICIENT
VS
MACH NUMBER
30 MM SHELL HE T 306 E10
K_M
0.8
0.4
0
.4
.8
1.2
1.6
2.0
2.4
MACH NUMBER

Figure 7


YAW DAMPING MOMENT COEFFICIENT
VS
MACH NUMBER
30 MM SHELL HE T 306 E 10
K_H
1
0
-1
.4
.8
1.2
1.6
2.0
2.4
2.8
MACH NUMBER
WITH ARMING FUSE BALL REMOVED

Figure 8


MAGNUS TORQUE COEFFICIENTS
VS
MACH NUMBER
30 MM SHELL HE T-306 E 10
K_T
.2
0
-.2
.4
.8
1.2
1.6
2.0
2.4
2.8
MACH NUMBER

Figure 9



ARMY---OS---ABERDEEN PROVING GROUND, MD--



WIND TUNNEL MAGNUS INSTRUMENTATION

Figure 11


Confidential
Magnus Moment Coefficient, ℓ_T, about C.g.
.01
-.01
-10
0
10
20
30
40
Magnus Force C.P. Calibers from Base
C.G.
1.0
0
Angle of Attack, α, degrees
Magnus Force Coefficient, ℓ_F
.01
-.01
MAGNUS DATA FOR 30 MM BULLET
Ma = 2.00
$\frac{\omega d}{V}$ = .407
Re = .94 x 10^6

Figure 12



DAMPING IN PITCH MODEL

Figure 13


30 MM
DAMPING COEFFICIENT, K_H VS. MACH NUMBER
2.0
1.0
0
K_H
DAMPING COEFFICIENT
1.0
1.5
2.0
2.5
3.0
3.5
4.0
MACH NUMBER

Figure 14

DISTRIBUTION LIST

No. of Copies	Organization
	Chief of Ordnance Department of the Army Washington 25, D. C. Attn: ORDTB - Bal Sec
10	British Joint Services Mission 1800 K Street, N. W. Washington 6, D. C. Attn: Mr. John Izzard, Reports Officer
4	Canadian Army Staff 2450 Massachusetts Ave. Washington 8, D. C.
3	Chief, Bureau of Ordnance Department of the Navy Washington 25, D. C. Attn: Re3d
2	Commander Naval Proving Ground Dahlgren, Virginia
2	Commander Naval Ordnance Laboratory White Oak Silver Spring 19, Md.
1	Superintendent Naval Postgraduate School Monterey, California
2	Commander Naval Ordnance Test Station China Lake, California Attn: Technical Library, W. R. Haseltine
4	Commander Wright Air Development Center Wright-Patterson Air Force Base, Ohio Attn: WCLGH, Mr. F. Burgess WCLG, Mr. John Lawarre WCLGR-4, Mr. Orin Gard WCLGE-1
5	Commander Air Force Armament Center Eglin Air Force Base, Fla. Attn: ACOT
1	Director Air University Library Maxwell Air Force Base, Ala.
1	Commander Air Research and Development Command P. O. Box 1395 Baltimore, Maryland
1	Chief of Staff U. S. Air Force Washington 25, D. C. Attn: AFDRD
1	Commander Air Force Fighter Weapons School Nellis Air Force Base, Nevada
5	Director Armed Services Technical Information Agency Documents Service Center Knott Building Dayton 2, Ohio Attn: DSC - SA
1	A. C. Spark Plug Division General Motors Corporation 1925 E. Kenilworth Place Milwaukee, Wisconsin Attn: Mr. H. Davis
1	Aircraft Armaments, Inc. P. O. Box 126 Cockeysville, Maryland
	THRU: Deputy District Chief Baltimore Regional Office of the Phila. Ordnance District Main Post Office Baltimore 1, Maryland

DISTRIBUTION LIST

No. of Copies	Organization
1	Arma Corporation 254 36th Street Brooklyn, New York THRU: New York Procurement District 111 East 16th Street New York 3, New York
1	Air Force Plant Representative Officer Consolidated-Vultee Aircraft Corporation P. O. Box 371 Fort Worth, Texas
1	Crosley Division AVCO Manufacturing Corp. 2630 Glendale Milford Rd. P. O. Box 116 Evandale, Ohio THRU: Dayton Air Procurement District Bldg. 70 - Area "C" Wright-Patterson Air Force Base, Ohio
1	Douglas Aircraft Company 3000 Ocean Park Blvd. Santa Monica, California THRU: Air Force Plant Representative Douglas Aircraft Company Santa Monica, California
1	Emerson Electric Manufacturing Co. 8100 Florissant Avenue St. Louis 2, Missouri THRU: Contracting Officer St. Louis Air Procurement District Southern Illinois Sub-Office 1114 Market Street St. Louis 21, Missouri
1	The Franklin Institute 20th and Parkway Philadelphia 3, Pennsylvania THRU: District Chief Phila. Ordnance District 128 N. Broad Street Philadelphia 2, Pa.
1	Air Force Plant Representative General Electric Company Room 327, Building 22 1 River Road Schenectady 5, New York
1	General Mills, Inc. 1620 Central Avenue Minneapolis 13, Minnesota THRU: Milwaukee Air Procurement District 770 N. Planketon Avenue Milwaukee, Wisconsin
1	Glenn L. Martin Company Baltimore 3, Maryland Attn: Mrs. Mary Ezzo THRU: Air Force Plant Representative Glenn L. Martin Company Baltimore 3, Maryland
1	Hughes Aircraft Company Florence Ave. at Teal St. Culver City, California THRU: Air Force Plant Representative, WEAPD Hughes Aircraft Company- Florence Ave. at Teal St. Culver City, California
1	Air Force Plant Representative Lockheed Aircraft Corporation P. O. Box 371 Fort Worth, Texas

DISTRIBUTION LIST

No. of Copies	Organization
1	McDonnell Aircraft Corp. P. O. Box 516 Municipal Airport St. Louis 3, Missouri THRU: St. Louis Procurement District 1114 Market Street St. Louis 1, Missouri
1	Air Force Development Field Representative Massachusetts Institute of Technology 68 Albany Street Cambridge 39, Massachusetts Attn: Lt. Col. C. N. DeGennora
2	Air Force Plant Representative North American Aviation, Inc. Los Angeles International Airport Los Angeles 45, California
1	North American Aviation, Inc. 12214 Lakewood Boulevard Downey, California Attn: Mr. Jim Elms THRU: San Francisco Air Procurement District 1515 Clay Street Oakland 12, California
2	Air Force Plant Reppesentative Northrop Aircraft, Inc. Department 3483 Ogden Air Material Area Hawthorne, California Attn: Mr. D. C. Olmore
1	Sperry Gyroscope Company Great Neck Long Island, New York Attn: John M. Geiger, Federal Dept. for MA-4 Fire Control System THRU: Air Force Plant Representative Sperry Gyroscope Co., EAPD Great Neck, Long Island, N.Y.
2	University of Texas Box 8036 University Station Austin 12, Texas THRU: Dallas Air Procurement District Wilson Building Room 338 Dallas 1, Texas
1	United Shoe Machinery Corp. Balch Street Beverly, Massachusetts THRU: Boston Air Procurement District Boston Air Base Boston 10, Massachusetts
1	Westinghouse Electric Corp. Air Armaments Division Friendship Airport Baltimore, Maryland THRU: Air Force Quality Control Representative Westinghouse Electric Corp. Friendship International Airport Baltimore, Maryland
1	Dr. L. H. Thomas Watson Scientific Computing Lab. 612 West 116th Street New York 27, New York