THIS REPORT HAS BEEN DELIMITED
AND CLEARED FOR PUBLIC RELEASE
UNDER DOD DIRECTIVE 5200.20 AND
NO RESTRICTIONS ARE IMPOSED UPON
ITS USE AND DISCLOSURE.

DISTRIBUTION STATEMENT A

APPROVED FOR PUBLIC RELEASE;
DISTRIBUTION UNLIMITED.

DISCLAIMER NOTICE



THIS DOCUMENT IS BEST QUALITY AVAILABLE. THE COPY FURNISHED TO DTIC CONTAINED A SIGNIFICANT NUMBER OF PAGES WHICH DO NOT REPRODUCE LEGIBLY.

UNCLASSIFIED

144903

Armed Services Technical Information Agency
Reproduced by
DOCUMENT SERVICE CENTER
KNOTT BUILDING, DAYTON, 2, OHIO

FOR
MICRO-CARD
CONTROL ONLY

1 OF 1

NOTICE: WHEN GOVERNMENT OR OTHER DRAWINGS, SPECIFICATIONS OR OTHER DATA ARE USED FOR ANY PURPOSE OTHER THAN IN CONNECTION WITH A DEFINITELY RELATED GOVERNMENT PROCUREMENT OPERATION, THE U. S. GOVERNMENT THEREBY INCURS NO RESPONSIBILITY, NOR ANY OBLIGATION WHATSOEVER; AND THE FACT THAT THE GOVERNMENT MAY HAVE FORMULATED, FURNISHED, OR IN ANY WAY SUPPLIED THE SAID DRAWINGS, SPECIFICATIONS, OR OTHER DATA IS NOT TO BE REGARDED BY IMPLICATION OR OTHERWISE AS IN ANY MANNER LICENSING THE HOLDER OR ANY OTHER PERSON OR CORPORATION, OR CONVEYING ANY RIGHTS OR PERMISSION TO MANUFACTURE, USE OR SELL ANY PATENTED INVENTION THAT MAY IN ANY WAY BE RELATED THERETO.

UNCLASSIFIED

AD No. 144903
ASTIA FILE COPY

FC

NAVY DEPARTMENT

DAVID TAYLOR MODEL BASIN

HYDROMECHANICS

AERODYNAMICS

STRUCTURAL MECHANICS

APPLIED MATHEMATICS

THE IDEAL EFFICIENCY OF OPTIMUM PROPELLERS HAVING FINITE HUBS AND FINITE NUMBERS OF BLADES

by

CDR. J. W. Shultz, Jr., USN

[illegible] WITHIN
RESTRICTIONS OF DISSEMINATION

HYDRODYNAMICS LABORATORY

RESEARCH AND DEVELOPMENT REPORT

July 1957 Report No. 1148

PRCC-TRB-[illegible] (11-56)

THE IDEAL EFFICIENCY OF OPTIMUM PROPELLERS HAVING FINITE HUBS AND FINITE NUMBERS OF BLADES

by

CDR. J. W. Shultz, Jr., USN

HYDRODYNAMICS LABORATORY
RESEARCH AND DEVELOPMENT REPORT

July 1957 Report No. 1148

Table of Contents

		Page
Notation		iii
Abstract		1
Introduction		1
Method of Computation		2
Presentation of Results		4
References		5
Appendix	A: Tables of $C_{T_i} - \eta_i - 1/\lambda_i$	6
	B: Curves of $C_{T_i} - \eta_i - \lambda$	11

Notation

C_{T_i}	Ideal (non-viscous) thrust coefficient
h	Subscript denoting finite hub
$K^{(Z)}_{mn}$	Integral defined by equation (2)
r	Section radius
R	Propeller tip radius
$X = \frac{r}{R}$	Nondimensional section radius
X_h	Non-dimensional hub radius
Z	Number of Blades
β_i	Hydrodynamic pitch angle
η_i	Ideal efficiency
λ	Advance coefficient
λ_i	Induced advance coefficient ($= \frac{\lambda}{\eta_i} = X \tan \beta_i$)
κ	$= \kappa(\lambda_i, Z, X, X_h)$ "Goldstein Factor" or "Circulation Distribution Factor" from reference (8)

Abstract

The ideal (non-viscous) thrust coefficient C_{T_i} related to a range of ideal efficiencies (η_i) and a range of advance coefficients (λ) is calculated for propellers having 3,4,5 and 6 blades and having hubs whose diameters are 0.2, 0.3 and 0.4 of the propeller diameter.

Introduction

The relationships between ideal (non-viscous) thrust coefficient C_{T_i}, ideal efficiency η_i and advance coefficient λ for propellers having a finite number of blades but zero hub diameter were determined by Kramer[1] after suitably transforming equations (8) and (11) of Lösch[2] for finite blade number. The results obtained were based on Goldstein's[3] solution of the potential problem, recalculated by Lock,[4] and Yeatman[4] and Kramer, himself, and extended by Kramer for large values of λ_i .

When Lerbs[5] published a propeller design method using "induction factors," it became possible to compare theoretically the circulation distributions for lightly and moderately loaded propellers. When, as a result of

---

[1] References are listed on page 5

this comparison, it was seen that the condition of normality for lightly loaded propellers could be applied to moderately loaded propellers with good accuracy, "it was then deemed necessary to determine the Goldstein Factor by more accurate methods than had previously been used, particularly for sections near the tip and for large advance ratios."[6] This was done by Tachmindji and Milam.[6]

Noting the increasing use of propellers with relatively large hubs, Tachmindji[7] formulated and solved the potential problem for propellers with finite hub diameters. Numerical evaluations are presented by Tachmindji and Milam.[8]

Herein are given relationships between ideal (nonviscous) thrust coefficient C_{T_i}, ideal efficiency η_i (=0.50, 0.60, 0.70, 0.80, 0.85, 0.90, 0.95, 0.97, 0.99) and $\lambda = \lambda_i \eta_i$. Kramer's work is thus extended for propellers having finite hubs.

Method of Computation

The basic equation for the computation is Kramer's equation (1.1) (notation is changed to agree with that in use at the David Taylor Model Basin):

$$C_{T_i} = \frac{8(1-\eta_i)}{\eta_i} K_{31}^{(Z)} + \frac{8(1-\eta_i)^2}{\eta_i^2} K_{52}^{(Z)} \qquad (1)$$

$$K_{mn}^{(Z)} = \int_{X_h}^{1} \frac{\kappa X^m}{(\lambda_i^2 + X^2)^n} \, dX \qquad (2)$$

where C_{T_i} = ideal thrust coefficient

η_i = ideal efficiency

$\kappa = \kappa\ (\lambda_i, Z, X, X_h)$ = "Goldstein Function" or "Circulation Distribution Factor" from reference (8)

$\lambda_i = X \tan \beta_i = \frac{\lambda}{\eta_i}$

β_i = hydrodynamic pitch angle

λ = advance ratio

Z = number of blades

X = $\frac{r}{R}$ nondimensional section radius

X_h = $\frac{\text{hub diameter}}{\text{propeller diameter}}$

h = subscript denoting finite hub

The integrations of $K_{mn}^{(Z)}$ were performed using a desk computer and Simpson's first and second rules.

Presentation of Results

Curves relating C_{T_i}, η_i and λ for 3, 4, 5 and 6 bladed propellers having 0.2, 0.3 and 0.4 hub diameter ratios are given in Figures 1-4 Appendix B. In addition, curves taken from Kramer's curves for zero hub and 4 bladed are plotted on Figure 2 in order to show a comparison with propellers having finite hubs.

For more convenient use in interpolating for values of λ_i and X_h between those given, Tables 1-4, Appendix A, give values of C_{T_i} as a function of Z, λ_i, η_i and X_h.

The results presented are considered accurate within one in the third significant figure throughout the range covered.

References

1. Kramer, K. N., "Induzierte Wirkungsgrade von Best-Luftschrauben endlicher Blattzahl," Luftfahrtforschung, Vol. 15, no. 7, July 6, 1938.

2. Losch, F., "Über die Berechnung des induzierten Wirkungsgrades stark belasteter Luftschrauben unendlicher Blattzahl," Luftfahrtforschung, Vol. 15, no. 7, July 6, 1938.

3. Goldstein, S., "On the Vortex Theory of Screw Propellers," Proceedings Royal Society, Vol. 123A, 1929.

4. Lock, C. N. H., and Yeatman, D. M., "Tables for Use in an Improved Method of Airscrew Strip Theory Calculation," R. and M. No. 1674, British A.R.C., 1935.

5. Lerbs, H. W., "Moderately Loaded Propellers with a Finite Number of Blades and an Arbitrary Distribution of Circulation," Trans. SNAME, 1952.

6. Tachmindji, A. J., and Milam, A. B., "The Calculation of Goldstein Factors for Three, Four, Five and Six Bladed Propellers," DTMB Report No. 1034, March 1956.

7. Tachmindji, A. J., "The Potential Problem of the Optimum Propeller with Finite Hub", DTMB Report No. 1051, August 1956, and International Shipbuilding Progress, November 1956.

8. Tachmindji, A. J., and Milam, A. B., "The Calculation of the Circulation Distribution for Propellers with Finite Hub Having Three, Four, Five and Six Blades," DTMB Report No. 1141, June 1957.

Appendix A

Tables of C_{T_i} - η_i - $1/\lambda_i$ for 3,4,5 and 6 bladed propellers

Table I

Ideal Thrust Coefficient, C_{T_i}, for THREE-BLADED Propellers

η \ $1/\lambda_i$	3.0	3.5	4.0	4.5	5.0	5.5	6.0
			$x_h = 0.2$				
0.50	3.3514	3.8587	4.2842	4.6338	4.9356	5.1848	5.3954
0.60	1.9089	2.1860	2.4177	2.6104	2.7715	2.9066	3.0208
0.70	1.0777	1.2278	1.3529	1.4567	1.5434	1.6160	1.6774
0.80	0.5632	0.6386	0.7011	0.7529	0.7961	0.8322	0.8627
0.85	0.3786	0.4282	0.4693	0.5033	0.5316	0.5553	0.5753
0.90	0.2278	0.2570	0.2812	0.3011	0.3178	0.3317	0.3434
0.95	0.1034	0.1164	0.1271	0.1360	0.1433	0.1495	0.1547
0.97	0.0598	0.0672	0.0734	0.0784	0.0827	0.0862	0.0892
0.99	0.0192	0.0216	0.0236	0.0252	0.0265	0.0276	0.0286
			$x_h = 0.3$				
0.50	3.0441	3.5161	3.9152	4.2510	4.5316	4.7690	4.9696
0.60	1.7296	1.9876	2.2053	2.3882	2.5409	2.6700	2.7792
0.70	0.9742	1.1140	1.2318	1.3306	1.4130	1.4826	1.5414
0.80	0.5080	0.5782	0.6372	0.6866	0.7278	0.7626	0.7919
0.85	0.3411	0.3873	0.4261	0.4586	0.4857	0.5085	0.5278
0.90	0.2050	0.2322	0.2551	0.2742	0.2901	0.3035	0.3149
0.95	0.0929	0.1051	0.1152	0.1237	0.1308	0.1367	0.1418
0.97	0.0537	0.0607	0.0665	0.0714	0.0754	0.0788	0.0817
0.99	0.0173	0.0195	0.0213	0.0229	0.0242	0.0252	0.0262
			$x_h = 0.4$				
0.50	2.6321	3.0563	3.4218	3.7291	3.9965	4.2214	4.4142
0.60	1.4917	1.7240	1.9239	2.0918	2.2380	2.3608	2.4662
0.70	0.8381	0.9643	1.0727	1.1637	1.2429	1.3095	1.3665
0.80	0.4361	0.4995	0.5540	0.5996	0.6394	0.6728	0.7014
0.85	0.2924	0.3343	0.3702	0.4002	0.4264	0.4484	0.4673
0.90	0.1755	0.2002	0.2214	0.2391	0.2546	0.2675	0.2786
0.95	0.0795	0.0905	0.0999	0.1078	0.1147	0.1204	0.1254
0.97	0.0459	0.0522	0.0576	0.0622	0.0661	0.0694	0.0722
0.99	0.0148	0.0168	0.0185	0.0199	0.0212	0.0222	0.0231

Table II

Ideal Thrust Coefficient, C_{T_i}, for FOUR-BLADED Propellers

η_i / λ_i	3.0	3.5	4.0	4.5	5.0	5.5	6.0
			$x_h = 0.2$				
0.50	3.7639	4.2684	4.6787	5.0142	5.2882	5.5150	5.7034
0.60	2.1434	2.4176	2.6401	2.8214	2.9693	3.0915	3.1931
0.70	1.2098	1.3577	1.4772	1.5743	1.6534	1.7188	1.7730
0.80	0.6322	0.7060	0.7655	0.8136	0.8528	0.8851	0.9119
0.85	0.4249	0.4734	0.5124	0.5439	0.5695	0.5906	0.6081
0.90	0.2596	0.2841	0.3069	0.3254	0.3404	0.3528	0.3630
0.95	0.1160	0.1278	0.1388	0.1469	0.1535	0.1590	0.1635
0.97	0.0671	0.0743	0.0801	0.0848	0.0885	0.0917	0.0942
0.99	0.0216	0.0239	0.0257	0.0272	0.0284	0.0294	0.0302
			$x_h = 0.3$				
0.50	3.4914	3.9646	4.3505	4.6647	4.9212	5.1331	5.3117
0.60	1.9836	2.2410	2.4504	2.6206	2.7594	2.8739	2.9706
0.70	1.1172	1.2560	1.3686	1.4600	1.5344	1.5959	1.6477
0.80	0.5826	0.6519	0.7080	0.7534	0.7903	0.8208	0.8465
0.85	0.3912	0.4367	0.4735	0.5032	0.5274	0.5474	0.5642
0.90	0.2351	0.2618	0.2834	0.3009	0.3150	0.3267	0.3366
0.95	0.1066	0.1184	0.1280	0.1357	0.1420	0.1472	0.1515
0.97	0.0616	0.0684	0.0739	0.0783	0.0819	0.0848	0.0873
0.99	0.0198	0.0220	0.0237	0.0251	0.0262	0.0272	0.0280
			$x_h = 0.4$				
0.50	3.0981	3.5309	3.8893	4.1823	4.4244	4.6256	4.7967
0.60	1.7598	1.9917	2.1868	2.3461	2.4776	2.5869	2.6799
0.70	0.9865	1.1140	1.2193	1.3052	1.3760	1.4349	1.4850
0.80	0.5133	0.5771	0.6297	0.6725	0.7078	0.7372	0.7622
0.85	0.3442	0.3862	0.4208	0.4489	0.4721	0.4914	0.5078
0.90	0.2066	0.2313	0.2516	0.2682	0.2818	0.2931	0.3028
0.95	0.0936	0.1046	0.1136	0.1209	0.1270	0.1320	0.1362
0.97	0.0541	0.0604	0.0655	0.0697	0.0732	0.0760	0.0785
0.99	0.0174	0.0194	0.0210	0.0224	0.0235	0.0244	0.0252

Table III

Ideal Thrust Coefficient, C_{T_i}, for FIVE-BLADED Propellers

x_h \ λ_i	3.0	3.5	4.0	4.5	5.0	5.5	6.0
			$x_h = 0.2$				
0.50	4.0250	4.5214	4.9182	5.2370	5.4954	5.7070	5.8817
0.60	2.2915	2.5606	2.7748	2.9465	3.0855	3.1991	3.2928
0.70	1.2932	1.4377	1.5524	1.6440	1.7181	1.7785	1.8283
0.80	0.6756	0.7475	0.8043	0.8496	0.8861	0.9158	0.9403
0.85	0.4540	0.5012	0.5383	0.5679	0.5917	0.6111	0.6271
0.90	0.2731	0.3007	0.3225	0.3398	0.3537	0.3650	0.3743
0.95	0.1239	0.1362	0.1458	0.1534	0.1595	0.1645	0.1686
0.97	0.0716	0.0786	0.0841	0.0885	0.0920	0.0948	0.0972
0.99	0.0230	0.0253	0.0270	0.0284	0.0295	0.0304	0.0311
			$x_h = 0.3$				
0.50	3.7814	4.2462	4.6164	4.9124	5.1510	5.3456	5.5054
0.60	2.1482	2.4001	2.6001	2.7597	2.8881	2.9929	3.0788
0.70	1.2098	1.3451	1.4522	1.5375	1.6060	1.6619	1.7077
0.80	0.6309	0.6981	0.7512	0.7934	0.8272	0.8547	0.8773
0.85	0.4236	0.4676	0.5024	0.5299	0.5520	0.5700	0.5847
0.90	0.2545	0.2804	0.3007	0.3168	0.3297	0.3402	0.3488
0.95	0.1154	0.1268	0.1358	0.1429	0.1486	0.1533	0.1570
0.97	0.0667	0.0732	0.0784	0.0824	0.0857	0.0883	0.0905
0.99	0.0214	0.0235	0.0252	0.0264	0.0275	0.0283	0.0290
			$x_h = 0.4$				
0.50	3.4165	3.8451	4.1876	4.4638	4.6862	4.8678	5.0180
0.60	1.9362	2.1689	2.3545	2.5040	2.6242	2.7223	2.8035
0.70	1.0879	1.2132	1.3128	1.3930	1.4574	1.5100	1.5535
0.80	0.5660	0.6284	0.6780	0.7178	0.7497	0.7758	0.7973
0.85	0.3796	0.4206	0.4530	0.4791	0.5000	0.5171	.5312
0.90	0.2279	0.2519	0.2710	0.2862	0.2985	0.3085	0.3168
0.95	0.1032	0.1139	0.1223	0.1290	0.1345	0.1389	0.1425
0.97	0.0596	0.0572	0.0705	0.0744	0.0775	0.0800	0.0821
0.99	0.0192	0.0211	0.0226	0.0239	0.0248	0.0256	0.0263

Table IV

Ideal Thrust Coefficient, C_{T_i}, for SIX-BLADED Propellers

x_h \ λ	3.0	3.5	4.0	4.5	5.0	5.5	6.0
			$x_h = 0.2$				
0.50	4.2048	4.6913	5.0764	5.3830	5.6296	5.8298	5.9942
0.60	2.3934	2.6564	2.8639	3.0285	3.1607	3.2679	3.3558
0.70	1.3505	1.4914	1.6021	1.6897	1.7599	1.8167	1.8632
0.80	0.7054	0.7753	0.8300	0.8731	0.9076	0.9354	0.9582
0.85	0.4740	0.5198	0.5555	0.5836	0.6061	0.6242	0.6390
0.90	0.2851	0.3119	0.3328	0.3492	0.3622	0.3728	0.3814
0.95	0.1294	0.1412	0.1504	0.1576	0.1634	0.1680	0.1718
0.97	0.0748	0.0816	0.0868	0.0909	0.0942	0.0969	0.0990
0.99	0.0240	0.0262	0.0279	0.0292	0.0302	0.0310	0.0317
			$x_h = 0.3$				
0.50	3.9806	4.4350	4.7912	5.0731	5.2981	5.4794	5.6269
0.60	2.2612	2.5067	2.6985	2.8499	2.9706	3.0678	3.1467
0.70	1.2734	1.4048	1.5071	1.5878	1.6519	1.7035	1.7453
0.80	0.6640	0.7291	0.7796	0.8193	0.8508	0.8761	0.8967
0.85	0.4458	0.4884	0.5214	0.5472	0.5678	0.5843	0.5976
0.90	0.2678	0.2928	0.3121	0.3272	0.3392	0.3488	0.3565
0.95	0.1214	0.1325	0.1410	0.1476	0.1529	0.1571	0.1605
0.97	0.0702	0.0765	0.0813	0.0851	0.0881	0.0906	0.0925
0.99	0.0226	0.0246	0.0261	0.0273	0.0283	0.0290	0.0296
			$x_h = 0.4$				
0.50	3.6407	4.0993	4.3880	4.6473	4.8542	5.0212	5.1583
0.60	2.0633	2.2897	2.4671	2.6069	2.7183	2.8081	2.8819
0.70	1.1593	1.2807	1.3756	1.4502	1.5097	1.5576	1.5969
0.80	0.6031	0.6634	0.7104	0.7473	0.7766	0.8002	0.8196
0.85	0.4045	0.4440	0.4747	0.4988	0.5180	0.5334	0.5460
0.90	0.2428	0.2659	0.2839	0.2980	0.3092	0.3182	0.3256
0.95	0.1100	0.1202	0.1281	0.1344	0.1393	0.1433	0.1465
0.97	0.0635	0.0694	0.0739	0.0775	0.0803	0.0826	0.0844
0.99	0.0204	0.0223	0.0237	0.0248	0.0257	0.0265	0.0270

Appendix B

Curves of C_{T_i} - η_i - λ for 3,4,5 and 6 bladed propellers



FIG 1 C_{T_1} - η_1 - λ Relationship for THREE-BLADED Propellers



FIG 2 C_{T_1} - η_1 - λ Relationship for FOUR-BLADED Propellers



FIG 8 c_{T_1} - η_1 - λ Relationship for FIVE-BLADED Propellers



FIG 6 C_{T_1} - η_1 - λ Relationship for SIX-BLADED Propellers

INITIAL DISTRIBUTION

Copies

8 Chief, BuShips, Library (Code 312)
  5 Technical Library
  1 Tech. Asst. to Chief (Code 106)
  1 Prelim Des (Code 420)
  1 Prop & Shafting (Code 554)

1 CHONR, Fluid Mech Br (Code 438)

1 CO, USNCTS, Pasadena, Calif.

1 DIR, ORL, Penn. St. Univ, University Park, Pa.

1 ETT, SIT, Attn: Prof. Korvin-Kroukovsky

1 Head, Dept. NAME, MIT, Cambridge, Mass.

1 Dr. H. A. Schade, Dir. of Engin Res., Col. of Engin, Univ of Calif, Berkeley, Cal.

1 Dr. K. H. Schoenherr, Dean, Faculty of Engin, Univ of Notre Dame, Notre Dame, Ind..

1 Supt, Admiralty Experiment Works, Haslar, Gosport, Hants, England

1 Supt, Ship Div, Natl Phys Lab, Teddington, Middlesex, England

1 DIR, Bassin d'Essais des Carenes, Paris XVe, France

1 DIR, Statens Skipsmodeltanken, Tyholdt, Trondheim, Norway

1 DIR, Statens Skeppsprovingsanstalt, Gothenburg, Sweden

1 DIR, Skeppsprovnings Laboratoriet, Kungl Tekniska, Stockholm 70, Sweden

1 DIR, Canal de Experienceas Hidrodinamicas, El Pardo, Madrid, Spain

1 DIR, Netherlands Scheepsbouwkundig Proefstation, Wageningen, Holland

INITIAL DISTRIBUTION

1 DIR, Vasca Nazionale Perle Experienze, via Della Vasca Navale 89, Rome - SEDE, Italy

1 DIR, Hamburg Model Basin, Hamburg 33, Germany

1 DIR, Institute for Schiffbau, Berliner Tor 21, Hamburg, Germany

1 British Shipbldg Res Assoc, Chesterfield Gardens, London W1, England

1 Prof. L. C. Burrill, Dept of Nav Arch, Kings College, Univ of Durham, Newcastle upon Tyne, England

1 Karlstads Mekaniska Werkstad, Kristinehamm, Sweden

1 Prof. Dr. F. Horn, Laehr St 28, Berlin-Zelendorf, Germany

1 Prof. Dr. H. Amtsberg, Tech Univ, Berlin, Germany

David Taylor Model Basin. Rept. 1148.
THE IDEAL EFFICIENCY OF OPTIMUM PROPELLERS HAVING FINITE HUBS AND FINITE NUMBERS OF BLADES, by J.W. Shultz, Jr. July 1957. iii, 18p. tables, graphs, refs. (Research and development report) UNCLASSIFIED

The ideal (non-viscous) thrust coefficient C_{T_i} related to a range of ideal efficiencies (η_i) and a range of advance coefficients (λ) is calculated for propellers having 3, 4, 5, and 6 blades and having hubs whose diameters are 0.2, 0.3, and 0.4 of the propeller diameter.

1. Propellers (Marine) – Thrust – Mathematical analysis
2. Propeller blades (Marine)
3. Propeller hubs
I. Shultz, John W.

David Taylor Model Basin. Rept. 1148.
THE IDEAL EFFICIENCY OF OPTIMUM PROPELLERS HAVING FINITE HUBS AND FINITE NUMBERS OF BLADES, by J.W. Shultz, Jr. July 1957. iii, 18p. tables, graphs, refs. (Research and development report) UNCLASSIFIED

The ideal (non-viscous) thrust coefficient C_{T_i} related to a range of ideal efficiencies (η_i) and a range of advance coefficients (λ) is calculated for propellers having 3, 4, 5, and 6 blades and having hubs whose diameters are 0.2, 0.3, and 0.4 of the propeller diameter.

1. Propellers (Marine) – Thrust – Mathematical analysis
2. Propeller blades (Marine)
3. Propeller hubs
I. Shultz, John W.

David Taylor Model Basin. Rept. 1148.
THE IDEAL EFFICIENCY OF OPTIMUM PROPELLERS HAVING FINITE HUBS AND FINITE NUMBERS OF BLADES, by J.W. Shultz, Jr. July 1957. iii, 18p. tables, graphs, refs. (Research and development report) UNCLASSIFIED

The ideal (non-viscous) thrust coefficient C_{T_i} related to a range of ideal efficiencies (η_i) and a range of advance coefficients (λ) is calculated for propellers having 3, 4, 5, and 6 blades and having hubs whose diameters are 0.2, 0.3, and 0.4 of the propeller diameter.

1. Propellers (Marine) – Thrust – Mathematical analysis
2. Propeller blades (Marine)
3. Propeller hubs
I. Shultz, John W.

David Taylor Model Basin. Rept. 1148.
THE IDEAL EFFICIENCY OF OPTIMUM PROPELLERS HAVING FINITE HUBS AND FINITE NUMBERS OF BLADES, by J.W. Shultz, Jr. July 1957. iii, 18p. tables, graphs, refs. (Research and development report) UNCLASSIFIED

The ideal (non-viscous) thrust coefficient C_{T_i} related to a range of ideal efficiencies (η_i) and a range of advance coefficients (λ) is calculated for propellers having 3, 4, 5, and 6 blades and having hubs whose diameters are 0.2, 0.3, and 0.4 of the propeller diameter.

1. Propellers (Marine) – Thrust – Mathematical analysis
2. Propeller blades (Marine)
3. Propeller hubs
I. Shultz, John W.

David Taylor Model Basin. Rept. 1148.
THE IDEAL EFFICIENCY OF OPTIMUM PROPELLERS HAVING FINITE HUBS AND FINITE NUMBERS OF BLADES, by J.W. Shultz, Jr. July 1957. iii, 18p. tables, graphs, refs. (Research and development report) UNCLASSIFIED

The ideal (non-viscous) thrust coefficient C_{T_i} related to a range of ideal efficiencies (η_i) and a range of advance coefficients (λ) is calculated for propellers having 3, 4, 5, and 6 blades and having hubs whose diameters are 0.2, 0.3, and 0.4 of the propeller diameter.

1. Propellers (Marine) - Thrust - Mathematical analysis
2. Propeller blades (Marine)
3. Propeller hubs
I. Shultz, John W.

David Taylor Model Basin. Rept. 1148.
THE IDEAL EFFICIENCY OF OPTIMUM PROPELLERS HAVING FINITE HUBS AND FINITE NUMBERS OF BLADES, by J.W. Shultz, Jr. July 1957. iii, 18p. tables, graphs, refs. (Research and development report) UNCLASSIFIED

The ideal (non-viscous) thrust coefficient C_{T_i} related to a range of ideal efficiencies (η_i) and a range of advance coefficients (λ) is calculated for propellers having 3, 4, 5, and 6 blades and having hubs whose diameters are 0.2, 0.3, and 0.4 of the propeller diameter.

1. Propellers (Marine) - Thrust - Mathematical analysis
2. Propeller blades (Marine)
3. Propeller hubs
I. Shultz, John W.

David Taylor Model Basin. Rept. 1148.
THE IDEAL EFFICIENCY OF OPTIMUM PROPELLERS HAVING FINITE HUBS AND FINITE NUMBERS OF BLADES, by J.W. Shultz, Jr. July 1957. iii, 18p. tables, graphs, refs. (Research and development report) UNCLASSIFIED

The ideal (non-viscous) thrust coefficient C_{T_i} related to a range of ideal efficiencies (η_i) and a range of advance coefficients (λ) is calculated for propellers having 3, 4, 5, and 6 blades and having hubs whose diameters are 0.2, 0.3, and 0.4 of the propeller diameter.

1. Propellers (Marine) - Thrust - Mathematical analysis
2. Propeller blades (Marine)
3. Propeller hubs
I. Shultz, John W.

David Taylor Model Basin. Rept. 1148.
THE IDEAL EFFICIENCY OF OPTIMUM PROPELLERS HAVING FINITE HUBS AND FINITE NUMBERS OF BLADES, by J.W. Shultz, Jr. July 1957. iii, 18p. tables, graphs, refs. (Research and development report) UNCLASSIFIED

The ideal (non-viscous) thrust coefficient C_{T_i} related to a range of ideal efficiencies (η_i) and a range of advance coefficients (λ) is calculated for propellers having 3, 4, 5, and 6 blades and having hubs whose diameters are 0.2, 0.3, and 0.4 of the propeller diameter.

1. Propellers (Marine) - Thrust - Mathematical analysis
2. Propeller blades (Marine)
3. Propeller hubs
I. Shultz, John W.