

485869

BRLR 1314

BRL

AD

REPORT NO. 1314

EQUATIONS OF MOTION FOR A MODIFIED POINT MASS TRAJECTORY

by

Robert F. Lieske
Mary L. Reiter

March 1966

Distribution of this document is unlimited.

U. S. ARMY MATERIEL COMMAND
BALLISTIC RESEARCH LABORATORIES
ABERDEEN PROVING GROUND, MARYLAND

485869

Destroy this report when it is no longer needed.
Do not return it to the originator.

The findings in this report are not to be construed as
an official Department of the Army position, unless
so designated by other authorized documents.

THIS REPORT HAS BEEN DELIMITED
AND CLEARED FOR PUBLIC RELEASE
UNDER DOD DIRECTIVE 5200.20 AND
NO RESTRICTIONS ARE IMPOSED UPON
ITS USE AND DISCLOSURE

DISTRIBUTION STATEMENT A

APPROVED FOR PUBLIC RELEASE;
DISTRIBUTION UNLIMITED.

BALLISTIC RESEARCH LABORATORIES

REPORT NO. 1314

MARCH 1966

Distribution of this document is unlimited.

EQUATIONS OF MOTION
FOR A
MODIFIED POINT MASS
TRAJECTORY

Robert F. Lieske
Mary L. Reiter

Computing Laboratory

RDT & E Project No. 1P523801A87

ABERDEEN PROVING GROUND, MARYLAND

BALLISTIC RESEARCH LABORATORIES

REPORT NO. 1314

RFLieske/MLReiter/vm
Aberdeen Proving Ground, Md.
March 1966

EQUATIONS OF MOTION
FOR A
MODIFIED POINT MASS
TRAJECTORY

ABSTRACT

A modified point mass mathematical model which incorporates an estimate of the yaw of repose, has been developed to represent the flight of a spin stabilized, dynamically stable, artillery shell. This improved mathematical model has the desirable feature of representing the effects of the significant variables of yaw of repose and axial spin along the trajectory.

PREVIOUS PAGE WAS BLANK THEREFORE WAS NOT FILMED

TABLE OF CONTENTS

	Page
Abstract	3
Table of Symbols	7
Introduction	11
Basic Laws of Motion of a Rigid Body	12
Estimate for Yaw of Repose	13
Utilization	19
Conclusions	22
References	23
Distribution List	25

TABLE OF SYMBOLS

Term	Definition	Units
A	Axial moment of inertia	lb-ft ²
AZ	Azimuth of line of fire (clockwise from north)	mil
B	Transverse moment of inertia	lb-ft ²
C _s	Ballistic coefficient for standard mass	lb/in ²
d	Reference diameter of projectile	ft
\vec{E}	Position of projectile with respect to spherical Earth surface	ft
\vec{g}	Acceleration due to gravity	ft/sec ²
g _o	Acceleration due to gravity (surface)	ft/sec ²
\vec{H}	Total angular momentum	lb-ft ² -rad/sec
\vec{I}	Unit vector in the direction of \vec{v}	_____
K _A	Spin damping moment coefficient	_____
K _{D_o}	Drag force coefficient	_____
K _{D_α}	Yaw drag force coefficient	_____
K _F	Magnus force coefficient	_____
K _H	Damping moment coefficient	_____
K _L	Lift force coefficient	_____
K _M	Overturning moment coefficient	_____
K _S	Pitching force coefficient	_____
K _T	Magnus moment coefficient	_____

Term	Definition	Units
l	Lift factor	_____
L	Latitude of launch	deg
M	Mach number	_____
m	Projectile mass	lb
m_s	Standard projectile mass	lb
N	Axial spin	rad/sec
Q	Yaw drag factor	_____
r	Distance between center of Earth and projectile	ft
R	Effective radius of Earth	ft
t	Time	sec
\underline{u}	Velocity of projectile with respect to ground	ft/sec
\underline{v}	Velocity of the projectile with respect to air	ft/sec
\underline{w}	Velocity of the air with respect to ground	ft/sec
\underline{x}	Unit vector along the longitudinal axis of the projectile	_____
\underline{X}	Position of the projectile with respect to a ground-fixed coordinate system	ft
α	Angle of yaw of projectile	rad
α_e	Approximation for yaw of repose	rad
$\underline{\Delta}$	Coriolis acceleration due to rotation of the Earth	ft/sec ²
ρ	Air density as a function of E_2 (where E_2 is a component of \underline{E})	lb/ft ³

Term	Definition	Units
Ω	Angular velocity of the Earth	rad/sec
.	First derivative with respect to time	—/sec
..	Second derivative with respect to time	—/sec ²

PREVIOUS PAGE WAS BLANK THEREFORE WAS NOT FILMED

INTRODUCTION

The mathematical model for rigid body trajectory simulation, as reported in BRL Report No. 1244, closely matches the results of physical experiments of spin-stabilized projectiles over a spectrum of test conditions. However, its usefulness, as in most rigid body simulations, is hindered by the time required to numerically solve the system of differential equations. This report describes the derivation of a mathematical model which will not be as time consuming to solve as the rigid body system, but which will represent as closely as possible the center of gravity motion of the projectile by utilizing a force system, axial spin and an estimate of the yaw of repose.

BASIC LAWS OF MOTION OF A RIGID BODY

The frame of reference for all vectors to be presented is a ground-fixed, right-handed Cartesian coordinate system with unit vectors $(\underline{1}, \underline{2}, \underline{3})$. Assume the $\underline{2}$ axis to be parallel to the vector \underline{g} , and \underline{g} to have the same direction as $\underline{1} \times \underline{3} = -\underline{2}$.

Assume that the body can be considered a solid of revolution. Then spin-stabilized projectiles can be oriented by choosing a unit vector \underline{x} along the axis of symmetry, pointing from tail to nose. N is the magnitude of angular velocity parallel to \underline{x} . N is positive if it results from a rotation causing a right-handed screw to advance in the direction of \underline{x} .

The following set of simultaneous differential equations of motion for a spin-stabilized projectile is developed in BRL Report 1244.

The equation of motion of the center of mass is:

$$(1.1) \quad \dot{\underline{u}} = \frac{-\rho d^2}{m} (K_{D_0} + a^2 K_{D_a}) \underline{v} \underline{v} + \frac{\rho d^2}{m} K_L [\underline{v} \times (\underline{x} \times \underline{v})]$$

$$\frac{-\rho d^3}{m} K_S \underline{v} \dot{\underline{x}} + \frac{\rho d^3 K_F N}{m} (\underline{x} \times \underline{v}) + \underline{g} + \underline{\Lambda}$$

The total angular momentum of the body can be expressed as the sum of two vectors in the ground-fixed coordinate system:

- (a) The angular momentum about \underline{x} .
- (b) The total angular momentum about an axis perpendicular to \underline{x} .

The angular momentum about \underline{x} can be represented by the vector $A N \underline{x}$ and the angular momentum about an axis perpendicular to \underline{x} by the vector $B (\underline{x} \times \dot{\underline{x}})$.

Let \underline{H} denote the total angular momentum of the body. The vector representation of \underline{H} is:

$$(1.2) \quad \underline{H} = A N \underline{x} + B (\underline{x} \times \dot{\underline{x}})$$

The vector rate of change of angular momentum is the sum of the applied moments.

$$(1.3) \quad \dot{\underline{H}} = A \dot{N} \underline{x} + A N \dot{\underline{x}} + B (\underline{x} \times \ddot{\underline{x}}) =$$

$$\rho d^3 K_M v (\underline{v} \times \underline{x}) - \rho d^4 K_H v (\underline{x} \times \dot{\underline{x}})$$

$$+ \rho d^4 K_T N [\underline{x} \times (\underline{x} \times \underline{v})] - \rho d^4 K_A N v \underline{x}$$

ESTIMATE FOR YAW OF REPOSE

An estimate for the yaw of repose will be derived from the rigid body system of differential equations of motion for the purpose of representing the effects of yaw.

The following conditions are assumed:

- (1) The projectile can be represented sufficiently well as a body of revolution.
- (2) The projectile is dynamically stable.
- (3) Initial yaw is assumed small, i. e., it has no significant effect on the trajectory.

Examination of equation (1.1) shows the magnitude $|\underline{x} \times \underline{v}|$ as being present in the lift term and the Magnus term, the lift term being more significant. Examination of equation (1.3) shows its presence also in the corresponding terms of $\dot{\underline{H}}$.

If $\underline{i} = \underline{v}/v$, then $|\underline{x} \times \underline{i}| = \sin \alpha$. To a first order approximation,

this is a ; however, for computational purposes it is a more desirable quantity than a . To get the proper orientation of this quantity, the following vector will be defined:

$$(2.1) \quad \underline{a}_e \equiv \underline{I} \times (\underline{x} \times \underline{I}) = \underline{x} - \cos a \underline{I}$$

Obviously, $\underline{a}_e \cdot \underline{I} = 0$. \underline{a}_e represents vector yaw * directed from \underline{I} toward \underline{x} . The effect of \underline{a}_e on the trajectory is generally small under the assumptions stated. Furthermore, it will be assumed that $\dot{\underline{a}}_e$ is negligible. This implies \dot{a} is small; moreover, the following approximations are warranted:

$$(2.2) \quad \dot{\underline{x}} = \cos a \dot{\underline{I}}$$

$$(2.3) \quad \ddot{\underline{x}} = \cos a \ddot{\underline{I}}$$

The separation of $\dot{\underline{H}}$ into components parallel and perpendicular to \underline{x} yields:

$$(2.4) \quad A\dot{N} = -\rho d^4 K_A N v$$

$$(2.5) \quad AN\dot{\underline{x}} + B(\underline{x} \times \ddot{\underline{x}}) = \rho d^3 K_M v(\underline{v} \times \underline{x}) \\ - \rho d^4 K_H v(\underline{x} \times \dot{\underline{x}}) + \rho d^4 K_T N [\underline{x} \times (\underline{x} \times \underline{v})]$$

To determine \underline{a}_e , first replace \underline{x} and its derivatives in (1.1) and (2.5) using equations (2.1), (2.2) and (2.3).

* NOTE: $|\underline{a}_e| \neq a$. However, as mentioned earlier, in magnitude $|\underline{a}_e|$ is a first-order approximation for yaw. \underline{a}_e is in the plane determined by \underline{x} and \underline{I} , in the direction from \underline{I} toward \underline{x} . Hence, \underline{a}_e will be referred to as vector yaw.

The resulting equations are:

$$(2.6) \quad \dot{\underline{u}} = \frac{-\rho d^2 (K_{D_o} + a^2 K_{D_a}) v^2 \underline{I}}{m} + \frac{\rho d^2 K_L v^2 \underline{a}_e}{m} - \frac{\rho d^3 K_S v \cos a \dot{\underline{I}}}{m} \\ + \frac{\rho d^3 K_F N v (\underline{a}_e \times \underline{I}) + \underline{g} + \underline{\Lambda}}{m}$$

$$(2.7) \quad AN \cos a \dot{\underline{I}} + B \cos a (\underline{a}_e \times \ddot{\underline{I}}) + B \cos^2 a (\underline{I} \times \ddot{\underline{I}}) \\ = \rho d^3 K_M v^2 (\underline{I} \times \underline{a}_e) + \rho d^4 K_T N v [\cos a (\underline{a}_e + \cos a \underline{I}) - \underline{I}] \\ - \rho d^4 K_H v \cos a [(\underline{a}_e + \cos a \underline{I}) \times \dot{\underline{I}}]$$

Cross multiplication by \underline{I} of both sides of equations (2.6) and (2.7) and, with $\underline{\Lambda}$ negligible in comparison to \underline{g} , the simultaneous solution of the resulting equations gives the following for \underline{a}_e .

$$(2.8) \quad \underline{a}_e = \left\{ m \rho d^4 K_T N v \cos a [\underline{I} \times (\dot{\underline{u}} - \underline{g} + \frac{\rho d^3 K_S v \cos a \dot{\underline{I}}}{m})] \right. \\ \left. + \rho d^2 K_L v^2 [-AN \cos a (\underline{I} \times \dot{\underline{I}}) + B \cos^2 a [\underline{I} \times (\ddot{\underline{I}} \times \underline{I})] \right. \\ \left. + \rho d^4 K_H v \cos^2 a \dot{\underline{I}} \right\} / \left\{ \rho^2 d^7 K_F K_T N^2 v^2 \cos a \right. \\ \left. + \rho d^2 K_L v^2 [\rho d^3 K_M v^2 + B \cos a \underline{I} \cdot \ddot{\underline{I}}] \right\}$$

For further substitution into (2.8) the following are required:

$$(2.9) \quad \underline{\dot{I}} = \underline{v} / v$$

$$(2.10) \quad \underline{\dot{I}} = [\underline{\dot{v}} - (\underline{\dot{v}} \cdot \underline{I}) \underline{I}] / v = [\underline{I} \times (\underline{\dot{v}} \times \underline{I})] / v$$

$$(2.11) \quad \underline{\ddot{I}} = -2 (\underline{\dot{v}} \cdot \underline{I}) \underline{\dot{v}} / v^2 + 3 (\underline{\dot{v}} \cdot \underline{I})^2 \underline{I} / v^2 \\ + \underline{\ddot{v}} / v - (\underline{\dot{v}} \cdot \underline{\dot{v}}) \underline{I} / v^2 - (\underline{\ddot{v}} \cdot \underline{I}) \underline{I} / v$$

$$(2.12) \quad \underline{\ddot{v}} / v - (\underline{\ddot{v}} \cdot \underline{I}) \underline{I} / v = [\underline{I} \times (\underline{\ddot{v}} \times \underline{I})] / v$$

(2.12) will be considered negligible since $\underline{\ddot{v}}$ can be approximated by $\underline{\ddot{u}}$, and $\underline{\ddot{u}}$ is essentially parallel to \underline{I} .

With this assumption,

$$(2.13) \quad \underline{c}_e = \{ -AK_L N \cos a (\underline{v} \times \underline{\dot{v}}) + md^2 K_T N \cos a [\underline{v} \times (\underline{\dot{u}} - \underline{g}) \\ + \rho d^3 K_S \cos a \underline{\dot{v}} / m] - K_L [\underline{\dot{v}} - (\underline{\dot{v}} \cdot \underline{I}) \underline{I}] \\ [2B \cos^2 a (\underline{\dot{v}} \cdot \underline{I}) - \rho d^4 K_H \cos^2 a v^2] \} / \\ \{ \rho d^3 K_L K_M v^4 + \rho d^5 K_F K_T N^2 \cos a v^2 \\ + K_L B \cos a [(\underline{\dot{v}} \cdot \underline{I})^2 - (\underline{\dot{v}} \cdot \underline{\dot{v}})] \}$$

In the denominator of equation (2.13) the v^4 term predominates ; therefore, $K_L B \cos a [(\underline{\dot{v}} \cdot \underline{I})^2 - (\underline{\dot{v}} \cdot \underline{\dot{v}})]$ will be considered negligible.

The ratio of this term to the remaining terms in the denominator is of the order of (g^2/v^4) . In the numerator, $[\underline{\dot{v}} - (\underline{\dot{v}} \cdot \underline{I}) \underline{I}]$ is the component of $\underline{\dot{v}}$ perpendicular to the projectile flight in the air coordinate system.

For most spin stabilized trajectories $|\dot{\underline{v}} - (\dot{\underline{v}} \cdot \underline{I}) \underline{I}|$ is no more than the magnitude of \underline{g} ; hence, consider

$$(2.14) \quad \left| K_L [\dot{\underline{v}} - (\dot{\underline{v}} \cdot \underline{I}) \underline{I}] [2B \cos^2 \alpha (\dot{\underline{v}} \cdot \underline{I}) - \rho d^4 K_H \cos^2 \alpha v^2] \right| \approx$$

$$\left| K_L \underline{g} [2B \cos^2 \alpha (\dot{\underline{v}} \cdot \underline{I}) - \rho d^4 K_H \cos^2 \alpha v^2] \right|$$

For artillery shells, this term is generally bounded by

$$(2.15) \quad K_L |g| \left| 2B \cos^2 \alpha (10g) \right| = \left| 20K_L B g_0^2 \right|$$

Now

$$(2.16) \quad \left| -AK_L N(\underline{v} \times \underline{\dot{u}}) + md^2 K_T N[\underline{v} \times (\underline{\dot{u}} - \underline{g})] \right| \approx$$

$$Nv \left| \{-AK_L + md^2 K_T\} K_L \frac{\rho d^2}{m} v^2 + AK_L g_0 \sin \phi \right|$$

$$\text{where } \cos \phi = \frac{\underline{g} \cdot \underline{v}}{g v}$$

For artillery shells, it is usually true that

$$(2.17) \quad \left| \{-AK_L + md^2 K_T\} K_L \frac{\rho d^2}{m} v^2 \right| \ll \left| AK_L g_0 \sin \phi \right|$$

Comparison of (2.15) and (2.17) shows that the ratio of (2.14) to (2.16) is less than the order of $(20g_0 / Nv)$. For high spin, (2.14) will be considered negligible.

Let

$$(2.18) \quad \underline{v} = \underline{u} - \underline{w}$$

$$(2.19) \quad \dot{\underline{v}} = \dot{\underline{u}} - \dot{\underline{w}}$$

If the effects of the pitching force (K_S term) and $\dot{\underline{w}}$ are assumed insignificant, and $\cos \alpha$ can be approximated by 1, equation (2.13) is reduced to

$$(2.20) \quad \underline{a}_e = \frac{-AK_L N (\underline{v} \times \dot{\underline{u}}) + md^2 K_T N [\underline{v} \times (\dot{\underline{u}} - \underline{g})]}{\rho d^3 K_L K_M v^4 + \rho d^5 K_F K_T N^2 v^2}$$

UTILIZATION

The primary goal of the development of \underline{a}_e was the acquisition of a mathematical model which would incorporate the effects of yaw, but would not require the computing time of a complete rigid body simulation. The following representation was devised to incorporate \underline{a}_e in a modified point-mass mathematical model. This representation includes auxiliary equations necessary for the numerical solution of the differential equation of motion of the center of mass.

The equation of motion of the center of mass is:

$$(3.1)* \quad \underline{\dot{u}} = - \frac{\rho m_s}{144 C_s m} \{ K_{D_o} + K_{D_a} [Q \alpha_e]^2 \} v \underline{v}$$

$$+ \frac{\rho d^2}{m} K_L v^2 l \underline{a}_e + \underline{g} + \underline{\Lambda}$$

$$+ \frac{\rho d^3}{m} K_F N Q (\underline{a}_e \times \underline{v})$$

where: C_s = ballistic coefficient for standard mass

l = lift factor

m = projectile mass

m_s = standard projectile mass

Q = yaw drag factor

*Note: If Q and l are set to zero (0) in equation (3.1), this system reduces to the classical point mass equations of motion.

The axial spin is:

$$(3.2) \quad N = - \int_0^t \frac{\rho d^4}{A} K_A N v$$

The approximation for the yaw of repose is:

$$(3.3) \quad \underline{a}_e = (a_b - a_a) (\underline{v} \times \underline{\dot{u}}) - a_b (\underline{v} \times \underline{g})$$

$$\text{where: } a_a = \frac{AK_L N}{\rho d^3 K_L K_M v^4 + \rho d^5 K_F K_T N^2 v^2}$$

$$a_b = \frac{m K_T N}{\rho d K_L K_M v^4 + \rho d^3 K_F K_T N^2 v^2}$$

The velocity of the projectile with respect to air is:

$$(3.4) \quad \underline{v} = \underline{u} - \underline{w}$$

The position of the projectile with respect to ground-fixed Cartesian coordinate system is:

$$(3.5) \quad \underline{X} = \int_0^t \underline{u} dt$$

The approximation for the position of the projectile with respect to spherical Earth surface is:

$$(3.6) \quad \underline{E} = \begin{bmatrix} X_1 \\ X_2 + R - (R^2 - X_1^2)^{1/2} \\ X_3 \end{bmatrix}$$

where R = effective radius of Earth.

The approximation of the force of gravity is:

$$(3.7) \quad \vec{g} = -g_0 \frac{R^2}{r^3} \begin{bmatrix} X_1 \\ X_2 + R \\ X_3 \end{bmatrix}$$

$$r = [X_1^2 + (X_2 + R)^2 + X_3^2]^{1/2}$$

where g_0 = value of gravity at point of launch

r = distance between center of Earth and projectile

The Coriolis acceleration due to rotation of the Earth is:

$$(3.8) \quad \vec{\Lambda} = \begin{bmatrix} -\lambda_1 u_2 - \lambda_2 u_3 \\ \lambda_1 u_1 + \lambda_3 u_3 \\ \lambda_2 u_1 - \lambda_3 u_2 \end{bmatrix}$$

For the northern hemisphere, the λ 's are defined by the following equations. [For the southern hemisphere replace L by $(-L)$.]

$$\lambda_1 = 2 \Omega \cos L \sin AZ$$

$$\lambda_2 = 2 \Omega \sin L$$

$$\lambda_3 = 2 \Omega \cos L \cos AZ$$

where: Ω = Angular velocity of the Earth (radians/sec)

L = Latitude of launch point

AZ = Azimuth of fire measured clockwise from north

The orientation of yaw (Ψ) is the angle between the plane containing both \vec{v} and \vec{a}_e and a vertical plane containing \vec{v} . It is measured clockwise from the vertical plane. If desired, Ψ is given by the expression:

$$(3.9) \quad \Psi = \tan^{-1} \left[\frac{(v_1^a e_3 - v_3^a e_1) v}{(v_1^a e_2 - v_2^a e_1) v_1 - (v_2^a e_3 - v_3^a e_2) v_3} \right]$$

The dimensionless aerodynamic coefficients are functions of many dimensionless power products, including the dimensionless shape parameters, Reynolds number and Mach number. Aerodynamic coefficients are defined with reference to a specific set of shape parameters and may be expressed as functions of Mach number.

CONCLUSIONS

A modified, point-mass mathematical model has been developed which incorporates an estimate of the yaw of repose. This improved mathematical model has the desirable feature of representing the effects of the significant variables of yaw of repose and axial spin along the trajectory. By the incorporation of this yaw of repose, the factors (ballistic coefficient, yaw drag factor and lift factor) used to match empirical results have been found to vary little from theoretically determined values over the spectrum of conditions.

In comparisons between the rigid body mathematical model, the most complete representation available, and point-mass representation, the modified point-mass model accounted for better than 90 percent of the discrepancies in the time-dependent variables range, height and deflection. These comparisons were made for spin-stabilized artillery rounds currently being used by the U. S. Army. The modified point-mass model solution required only approximately twice the computation time of the point-mass solution while the rigid body solution requires about one hundred to one thousand times that of the point-mass solution.

REFERENCES

1. Lieske, R. F., and McCoy, R. L., Equations of Motion of a Rigid Projectile, BRL Report No. 1244, March 1964.
2. McShane, E. J., Kelley, J. L., and Reno, F., Exterior Ballistics. University of Denver Press, 1953.

DOCUMENT CONTROL DATA - R&D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY (Corporate author) U.S. Army Ballistic Research Laboratories Aberdeen Proving Ground, Maryland		2a. REPORT SECURITY CLASSIFICATION Unclassified	
		2b. GROUP	
3. REPORT TITLE EQUATIONS OF MOTION FOR A MODIFIED POINT MASS TRAJECTORY			
4. DESCRIPTIVE NOTES (Type of report and inclusive dates)			
5. AUTHOR(S) (Last name, first name, initial) Lieske, Robert F. and Reiter, Mary L.			
6. REPORT DATE March 1966		7a. TOTAL NO. OF PAGES 26	7b. NO. OF REFS 2
8a. CONTRACT OR GRANT NO.		9a. ORIGINATOR'S REPORT NUMBER(S)	
b. PROJECT NO. RDT&E 1P523801A287		Report No. 1314	
c.		9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)	
d.			
10. AVAILABILITY/LIMITATION NOTICES Distribution of this document is unlimited.			
11. SUPPLEMENTARY NOTES		12. SPONSORING MILITARY ACTIVITY U.S. Army Materiel Command Washington, D.C.	
13. ABSTRACT A modified point mass mathematical model, which incorporates an estimate of the yaw of repose, has been developed to represent the flight of a spin stabilized, dynamically stable, artillery shell. This improved mathematical model has the desirable feature of representing the effects of the significant variables of yaw of repose and axial spin along the trajectory.			

14. KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
Equations of motion Point mass mathematical model Estimate of the yaw of repose Axial spin						

INSTRUCTIONS

1. **ORIGINATING ACTIVITY:** Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (*corporate author*) issuing the report.

2a. **REPORT SECURITY CLASSIFICATION:** Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. **GROUP:** Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. **REPORT TITLE:** Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. **DESCRIPTIVE NOTES:** If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. **AUTHOR(S):** Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. **REPORT DATE:** Enter the date of the report as day, month, year; or month, year. If more than one date appears on the report, use date of publication.

7a. **TOTAL NUMBER OF PAGES:** The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. **NUMBER OF REFERENCES:** Enter the total number of references cited in the report.

8a. **CONTRACT OR GRANT NUMBER:** If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. **PROJECT NUMBER:** Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. **ORIGINATOR'S REPORT NUMBER(S):** Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. **OTHER REPORT NUMBER(S):** If the report has been assigned any other report numbers (*either by the originator or by the sponsor*), also enter this number(s).

10. **AVAILABILITY/LIMITATION NOTICES:** Enter any limitations on further dissemination of the report, other than those imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. **SUPPLEMENTARY NOTES:** Use for additional explanatory notes.

12. **SPONSORING MILITARY ACTIVITY:** Enter the name of the departmental project office or laboratory sponsoring (*paying for*) the research and development. Include address.

13. **ABSTRACT:** Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. **KEY WORDS:** Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.