UNCLASSIFIED

AD-A270 585

SECURITY CLASSIFICATION OF THIS PAGE

J
0188

REPORT DOCUMENTATION PAGE

1a REPORT SECURITY CLASSIFICATION UNCLASSIFIED			1b RESTRICTIVE MARKINGS None		
2a SECURITY CLASSIFICATION AUTHORITY N/A			3 DISTRIBUTION AVAILABILITY OF REPORT Distribution Statement A. Approved for public release; distribution is unlimited.		
2b DECLASSIFICATION/DOWNGRADING SCHEDULE N/A					
4 PERFORMING ORGANIZATION REPORT NUMBER(S) DOD POP HM TR/AYD 93-014			5 MONITORING ORGANIZATION REPORT NUMBER(S)		
6a NAME OF PERFORMING ORGANIZATION Packaging Division		6b OFFICE SYMBOL (if applicable) SMCAR-AEP	7a NAME OF MONITORING ORGANIZATION		
6c ADDRESS (City, State, and ZIP Code) US Army ARDEC Picatinny Arsenal, NJ 07806-5000			7b ADDRESS (City, State, and ZIP Code)		
8a NAME OF FUNDING/SPONSORING ORGANIZATION		8b OFFICE SYMBOL (if applicable)	9 PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER		
8c ADDRESS (City, State, and ZIP Code)			10 SOURCE OF FUNDING NUMBERS		
			PROGRAM ELEMENT NO	PROJECT NO	TASK NO
			WORK UNIT ACCESSION NO		
11 TITLE (Include Security Classification) Performance-Oriented Packaging (POP) Testing of Cartridge, 81mm: Practice, Short Range, M880 for 81mm Mortar Packed in a Wood Wirebound Box. (U)					
12 PERSONAL AUTHOR(S) Yuen H. Lam, Mechanical Engineer					
13a TYPE OF REPORT Final		13b TIME COVERED FROM _____ TO _____		14 DATE OF REPORT (Year, Month, Day) 93-09-20	
				15 PAGE COUNT 4	
16 SUPPLEMENTARY NOTATION					
17 COSATI CODES			18 SUBJECT TERMS (Continue on reverse if necessary and identify by block number)		
FIELD	GROUP	SUB-GROUP	Performance-Oriented Packaging (POP) Cartridge, M880 Mortar, 81mm 12944141 Short Range (SR) Practice		
19 ABSTRACT (Continue on reverse if necessary and identify by block number) This report details test results conducted on the Cartridge, 81mm: Practice, Short Range (SR), M880 for 81mm Mortar packaged in a wood wirebound box per drawing 12944141. The tests were conducted in accordance with the requirements of 49 CFR part 107 Subpart M (18.600 et. al.). The packaging is submitted for Performance-Oriented Packaging (POP) certification.					
20 DISTRIBUTION/AVAILABILITY OF ABSTRACT ☒ UNCLASSIFIED/UNLIMITED ☐ SAME AS RPT ☐ DTIC USERS					
22a NAME OF RESPONSIBLE INDIVIDUAL Mr. Yuen H. Lam			22b TELEPHONE (Include Area Code) (201) 724-2228		22c OFFICE SYMBOL SMCAR-AEP

93-23005

578

DD Form 1473, JUN 86

Previous editions are obsolete
Statement A, unlimitedSECURITY CLASSIFICATION OF THIS PAGE
UNCLASSIFIED

93 10 1 197

I. Report Number: DOD POP HM TR/AYD 93-014

II. Title: Performance-Oriented Packaging (POP) Testing of
Cartridge, 81mm: Practice, Short Range, M880 for 81mm
Mortar Packed in a Wood Wirebound Box

Drawing Number: 12944141

Author: Yuen H. Lam

Performing Activity: U.S. Army Armament Research, Development
and Engineering Center (ARDEC)

Address: Department of the Army
Commander, U.S. Army ARDEC
Attn: SMCAR-AEP
Picatinny Arsenal, N.J. 07806-5000

Date: September 1993

Distribution Statement A.

Approved for public release; distribution is unlimited.

DTIC QUALITY

Accession For	
DTIC GRA&I	☒
DTIC TAB	☐
Unannounced	☐
Justification	
Distribution	
Availability Codes	
A-1	

1. Data:

Container:

Type: Box, Wirebound
UN Code: 4C1
Specification: MIL-B-46506
Drawing Number: 12944141
Material: Wood
Maximum net mass: 31 kg (68 lbs)
Dimensions: 45.7 cm X 43.2 cm X 22.9 cm
(18 in X 17 in X 9 in)
Gross Weight: 34.5 kg (76 lbs)

Product:

Name: Cartridge, 81mm: Practice, Short Range, M880
Drawing Number: 12944202
Cage Code: 19200
United Nations Proper Shipping Name:
Cartridges for Weapons, Inert Projectile
United Nations Identification Number: 0012
United Nations Packaging Group: II
Physical State: Solid
Number of Cartridges per Container: 8
National Stock Number (NSN): 1315-01-216-7071
DOD Identification Code: C876

2. Reference Material:

- a. Federal Register, "49 CFR Part 107-179"
- b. United Nations, "Transport of Dangerous Goods"

3. Background:

This report details Performance-Oriented Packaging (POP) tests conducted on 81mm M880 Short Range Practice Cartridge for 81mm mortar packed in a wood wirebound container in accordance with drawing 12944141. Each cartridge weighs approximately 6.8 lb. A package contains 8 cartridges. The POP tests were conducted using packages containing additional weights to insure container integrity. The weight of the packed out tested container was 86 lbs (39 kg). Tests were performed according to POP test regulations.

4. Test:

The following POP tests were performed at ambient temperature:

a. Vibration Test (178.608)

Procedure:

Three wirebound boxes were vibrated on a vibrating platform unrestrained for a one-hour period. The double-amplitude (peak-to-peak displacement) was one inch and the frequency was 270 cycles per minute. The frequency was sufficient to allow the package to become completely airborne and enable a 1/16" piece of strapping material to be slid underneath the package during vibration.

Results:

After the tests, the wirebound boxes experienced no structural damage; there was no spillage of contents; the passing criteria was met.

b. Drop Test (178.603)

Procedure:

One of the packages that had been previously vibrated was reused for the five orientation drop tests: flat on the bottom, flat on the top, flat on the long side, flat on the short side, and on the corner. The height for all five drops was 4.0 ft (1.22 m).

Results:

There was no visible damage on the first four drops. On the fifth drop (on the corner), one of the long cleats on the end of wirebound box adjacent to the impact corner broke. However, no spillage occurred and the box was in a safely handled condition. In order to insure the test result to be accurate, a new wirebound box was tested. After the drop, the impact corner received only minor damage. Overall, the container was in a sound condition. All contents remained inside the container and the package was capable of being safely handled without danger of spillage. It was determined that the passing criteria was met.

c. Stacking Test (178.606)

Procedure:

The second wirebound box that had been previously vibrated was reused for the stacking test. A dead load of 1,726 lbs was applied to the top of the container for a 48 hour period. This simulated a stack height of 16 ft (21 layers) of identical packages.

Results:

During the test, the container supported the load adequately. No structural damage was observed on the container after the test. The passing criteria was exceeded.

5. Based on the above POP testing, the following POP symbol has been applied to fiberboard containers in accordance with drawing 12944141.

4C1/Y39/S/**
USA/DOD/AYD

Insert the last two digits
of year packed.