AFRL-RH-WP-TP-2012-0020

Airborne Human Odorants: Detection, Dispersion and Characterization

**Kai Zhao
George Preti**

Monell Chemical Senses Center

**MARCH 2012
Interim Report**

Distribution A. Approved for public release; distribution unlimited.

See additional restrictions described on inside pages

**AIR FORCE RESEARCH LABORATORY
711TH HUMAN PERFORMANCE WING,
HUMAN EFFECTIVENESS DIRECTORATE,
WRIGHT-PATTERSON AIR FORCE BASE, OH 45433
AIR FORCE MATERIEL COMMAND
UNITED STATES AIR FORCE**

NOTICE AND SIGNATURE PAGE

Using Government drawings, specifications, or other data included in this document for any purpose other than Government procurement does not in any way obligate the U.S. Government. The fact that the Government formulated or supplied the drawings, specifications, or other data does not license the holder or any other person or corporation; or convey any rights or permission to manufacture, use, or sell any patented invention that may relate to them.

This report is the result of contracted fundamental research deemed exempt from public affairs security and policy review in accordance with SAF/AQR memorandum dated 10 Dec 08 and AFRL/CA policy clarification memorandum dated 16 Jan 09. This report is available to the general public, including foreign nationals. Copies may be obtained from the Defense Technical Information Center (DTIC) (<http://www.dtic.mil>).

AFRL-RH-WP-TP-2012-0020 HAS BEEN REVIEWED AND IS APPROVED FOR PUBLICATION IN ACCORDANCE WITH ASSIGNED DISTRIBUTION STATEMENT.

//signature//

Claude Grigsby, Work Unit Manager
Human Signature Branch

//signature//

LOUISE A. CARTER, PhD
Chief, Forecasting Division
Human Effectiveness Directorate
711th Human Performance Wing
Air Force Research Laboratory

This report is published in the interest of scientific and technical information exchange, and its publication does not constitute the Government's approval or disapproval of its ideas or findings.

REPORT DOCUMENTATION PAGE				Form Approved OMB No. 0704-0188	
<p>The public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.</p>					
1. REPORT DATE (DD-MM-YY) March 2012		2. REPORT TYPE Interim		3. DATES COVERED (From - To) 1 Sept 2011 – 31 Dec 2011	
4. TITLE AND SUBTITLE Airborne Human Odorants: Detection, Dispersion and Characterization				5a. CONTRACT NUMBER IN-HOUSE	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER 0602202F	
6. AUTHOR(S) Kai Zhao, George Preti				5d. PROJECT NUMBER 7184	
				5e. TASK NUMBER C	
				5f. WORK UNIT NUMBER 7184C002	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Monell Chemical Senses Center 3500 Market Street Philadelphia PA 19104				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) Air Force Materiel Command Air Force Research Laboratory 711 th Human Performance Wing Human Effectiveness Directorate Forecasting Division Human Signature Branch Wright-Patterson AFB, OH 45433				10. SPONSORING/MONITORING AGENCY ACRONYM(S) 711 HPW/RHXB	
				11. SPONSORING/MONITORING AGENCY REPORT NUMBER(S) AFRL-RH-WP-TP-2012-0020	
12. DISTRIBUTION/AVAILABILITY STATEMENT Distribution A. Approved for public release; distribution unlimited.					
13. SUPPLEMENTARY NOTES Report contains color.					
14. ABSTRACT This project concentrates on characterizing how VOCs emitted by humans interact and propagate in the environment. In humans, the axillae are a unique source of human odor. In addition to a high density of eccrine glands, the axillae contain large numbers of sebaceous and apocrine glands. The interactions between the cutaneous microflora and skin secretions lead to a complex mix of odorants, several of which are unique to humans. We have begun our investigation of how human-derived odorants emanate into the vapor phase. Our instrumentation has been calibrated for several odorants and how their vapor phase concentration changes with time in a small sealed system. In addition, we have created, a computational model for how human axillary odorants may emanate from the axillae into a room (experimental chamber) under known experimental conditions.					
15. SUBJECT TERMS Mass transport, volatile organic compounds, vapor pressure, chemical reactivity, chemical degradation, chemical diffusion, plume and inverse modeling					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT: SAR	18. NUMBER OF PAGES 13	19a. NAME OF RESPONSIBLE PERSON (Monitor) Curt Grigsby 19b. TELEPHONE NUMBER (Include Area Code) n/a
a. REPORT Unclassified	b. ABSTRACT Unclassified	c. THIS PAGE Unclassified			

THIS PAGE IS INTENTIONALLY LEFT BLANK

LIST OF FIGURES

Figure 1. Dimethylsulfone (DMS) Calibration curve for dimethylsulfone, a mammalian metabolite reflective of metabolism of sulfur-containing amino acids.	2
Figure 2. Vapor phase concentration of dimethylsulfone with time, in a small fixed volume.	2
Figure 2.1. Diagram of the computational replication of the chamber. Each air inlet contains two parallel slits of $\frac{1}{2}$ " wide and $\frac{3}{4}$ " apart.	3
Figure 2.2. (a) Planes across z axis. Negative Y velocity means the flow towards floor, which is apparent on the two of planes that cut right along inlet slits. (b) air flow vector plots of the right most plane of (a), where the two air inlet slit were shown. Vectors show recirculation of air along the walls and between two air inlets. (c) flow vector in the middle plane of (a) which cut across outlet, shows how air flow peel out from the circulation and form the exhaust air stream. (d) streamlines of a few particles released from the two inlets on the right side. Only a few of the tracked particles exit the room from the exhaust within the time frame.	4
Figure 2.3. (a) planes across x axis and cut across three inlets. (b) air flow vector plots of the middle plane in (b), which shows intense recirculation of air between the inlet and wall.	5
Figure 2.4. Simulated release of 100 ppm odor vapor source	5
Figure 2.5 a) 9 virtual sites monitoring room b) Room regions containing high odor concentrations	6

THIS PAGE IS INTENTIONALLY LEFT BLANK

Airborne Human Odorants: Detection, Dispersion and Characterization

Kai Zhao, Ph.D. and George Preti, Ph.D.
Monell Chemical Senses Center
3500 Market Street, Philadelphia, PA 19104

Progress report for September 1, 2011 to December 31, 2011

The volatilization and dispersion of human VOCs depends on several factors: 1) the molecular properties such as saturated vapor pressure, Henry law constant, air/octane partition coefficient, etc. The human odorants we have chosen for study are emitted from the body in axillary sweat which is a complex mixture of water, protein, lipids and other small, VOCs. All of these properties and interactions are unknown, however, we will assume initially, that these odorants, because of their highly oxidized structures (e.g. they are acids) will remain stable in the vapor phase. With this assumption we have focused on how these compounds disperse through air movement caused either by active ventilations or by natural convections (diffusion). We have employed diverse experimental approaches to begin this research.

To allow the quantification of various human odorants we first calibrated the gas chromatography-mass spectrometry system that will be employed to quantify odorants collected from various headspaces.

Experiment 1: a.) Calibration of GC-MS system was performed by injecting small quantities of known concentrations of each compound under study (in chloroform or other appropriate solvent). To date, the instrument has been calibrated for the following compounds: dimethylsulfone, E-3-methyl-2-hexenoic acid (3M2H), 6-heptenoic acid, and 7-octenoic acid. Completion of calibration curves for these compounds has allowed us to quantify the amount of these VOCs found in headspaces of sealed systems of known volumes.

A typical calibration curve is shown in **Figure 1** for, dimethylsulfone.

Figure 2 shows how the concentration changes in the vapor phase, over time, in a fixed (0.50 L) volume.

Figure 1. Dimethylsulfone (DMS) Calibration curve for dimethylsulfone, a mammalian metabolite reflective of metabolism of sulfur-containing amino acids.

Figure 2. Vapor phase concentration of dimethylsulfone with time, in a small fixed volume.

Experiment 2) Quantifying human signature odorant propagation in an environmental chamber (250 sq foot).

We have setup computational models of the Monell Center's environmental chamber where our indoor experiments will be conducted, to hopefully assist future experimental design, e.g. placement of odor monitor sites, expected standoff time, etc.

Method: The dimension of the chamber and the locations of the fresh air inlets and exhaust (three inlet on the ceiling and one exhaust at the lower side wall) were precisely replicated in silico (**Figure 2.1**). A widely acceptable mathematical method, the finite volume method, was used to simulate room air movement and odor propagation. This method works by dividing the air space into many small and simple volumes, e.g. tetrahedral, polyhedron, prism, etc. The final model for our room contains about 3 million volumes (elements). Within each volume, the nonlinear and higher order fluid dynamic equations can then be approximated with linear equations, thus greatly simplify the computational task. Obviously, it is likely that with more and finer elements, the linear approximation would be closer to the real solution. Thus, we have compared simulation results in models with 400k, 1million and 3 million elements, and concluded the results reached convergency at 3 million elements, that is further more elements does not improve the numerical accuracy significantly. There are also different mathematical schemes to linearize the fluid dynamic equations based on various flow conditions, e.g. laminar, turbulent, etc. The renormalization group K-eps turbulence model, which has been previously reported to perform best for indoor airflow than other two-equation turbulence models (Chen, 1995 and Posner et al 2003), is applied here to capture airflow.

Figure 2.1. Diagram of the computational replication of the chamber. Each air inlet contains two parallel slits of 1/2" wide and 3/4" apart.

The initial simulation is conducted under an air exchange rate of 6 ACH (air exchange per hour), which is about mid range for ASHRAE (American Society of Heating, Refrigerating and Air-Conditioning Engineers) Guideline-2001 (4-12 ACH). Room is assumed to be in constant temperature of 25 C.

Results: The following graphs (**Figure 2.2** and **Figure 2.3**) show the air velocity (m/s) in three parallel planes cut across the three axes (x, y, z).

Figure 2.2. (a) Planes across z axis. Negative Y velocity means the flow towards floor, which is apparent on the two of planes that cut right along inlet slits. (b) air flow vector plots of the right most plane of (a), where the two air inlet slit were shown. Vectors show recirculation of air along the walls and between two air inlets. (c) flow vector in the middle

plane of (a) which cut across outlet, shows how air flow peel out from the circulation and form the exhaust air stream. (d) streamlines of a few particles released from the two inlets on the right side. Only a few of the tracked particles exit the room from the exhaust within the time frame.

Figure 2.3. (a) planes across x axis and cut across three inlets. (b) air flow vector plots of the middle plane in (b), which shows intense recirculation of air between the inlet and wall.

We further simulated in **Figure 2.4** the situation where a pseudo odor vapor source of 100ppm is released with constant rate of 100ml/s in the middle of the room, approximately 1.5m from the floor, roughly at the height of the chest or arm pit. In the future, an odor evaporation profile obtained from experimental 1, will be used to capture realistic human signature body odor releases.

Figure 2.4. Simulated release of 100 ppm odor vapor source

The overall averaged room air concentration rise to plateau after at least 1000 s under the current room ventilation. If assuming perfect mixing condition, the concentration in

the room should rise to 0.263 ppm in theory, which was never reached. Thus, a significant portion of the fresh air was not well mixed with the room air before they exit the room.

9 virtual sites were setup to monitor the room odor concentration spreading in the middle z plane that cut across the outlet (see **figure 2.5a**). Compared to the average room concentration, various room regions contain high odor concentrations that are not well mixed with fresh air or with rest of the room air (**Figure 2.5 b**). The highest concentration level is at PC2, which is right above the source; the 2nd highest is PA1 near outlet; the 3rd highest PC1; and the 4th PA3. From the above air flow patterns and attached video, we can see that the source point is located in or near an air pocket of a vortex (by accident), thus for the first 250 seconds or so, the odor propagation is very much contained within that pocket, after which it then spreads/jumps into a second bigger pocket of air/vortex that is located near the outlet. That is why we see PC2, which is located in the first pocket, rises sharply and quickly, whereas, PA1, PC1, PA3, which are located in the second pocket, rise with a bump after 250 seconds. The attached video shows odor propagation at 3 planes across at source point. PC3, which is right below the source point, is only the 5th highest, much lower than PC2, probably because it is outside the first pocket and endured more washout from the inlet.

Figure 2.5 a) 9 virtual sites monitoring room b) Room regions containing high odor concentrations

Summary

The above simulation indicate that even within a well ventilated room, the propagation of odor can be very non-uniform and depend heavily on the location of source, monitor sites and their relationship to the ventilation inlet and outlet. The standoff distance and time may vary significantly depending on these locations. In our trial case, for a location moderately away from the source (~half room size), a considerable delay (~ 250 s) may be expected before encountering the bulk odor. For some locations (the half room away from the source and outlet, PB 1,2,3 in our setup), the concentration of odor may never reach ~40% of expected -under well mixing assumption- level.

Future Work:

We plan release a target odor in the chamber as we've simulated to validate the computational results.

Chen, Q. 1995. Comparison of different k-eps models for indoor air flow computations. Numerical heat transfer Part B, Fundamentals, 28(3), 353-369.

Posner, J.D., Buchanan, C.R., and Dunn-Rankin, D. 2003. Measurement and prediction of indoor air flow in a model room. Energy and buildings 35 (5): 515-526.