iNET Preamble Detector Performance in the Presence of Multipath Interference

June 2014

Final Report

Tom Young
SET Executing Agent
412 TENG/ENI
(661) 277-1071
Email: tommy.young.1@us.af.mil

Approved for public release; distribution is unlimited.

Controlling Office: 412 TENG/ENI, Edwards AFB, CA 93524

Test Resource Management Center (TRMC)
Test & Evaluation/ Science & Technology (T&E/S&T)
Spectrum Efficient Technology (SET)

Qualified requestors may obtain copies of this report from the Defense Technical Information Center, 8725 John J. Kingman Road, Suite 0944, Ft. Belvoir, VA 22060-6218. Department of Defense contractors must be established for DTIC services, or have a "need to know" certified by cognizant military agency for their project or contract.

When U.S. Government drawings, specifications, or any other data are used for any purpose other than a definitely related government procurement operation, the government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the government may have formulated, furnished or in any way supplied the said drawings, specifications, or any other data is not to be regarded by implication or otherwise, as in any manner licensing the holder or any other person or corporation or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

Do not return this copy; retain or destroy.

DESTRUCTION NOTICE

For classified documents, follow the procedures in DoD 5220.22.M, *National Industrial Security Manual (NISPM)*, section 5-705, or DoD 5200.01 Vol. 1-4, *DoD Information Security Program*. For unclassified limited documents (ie., documents not approved for public release), destroy by any method that will prevent disclosure of contents or reconstruction of the document.

DISTRIBUTION LIST

Onsite Distribution

Number of Copies

	<u>E-Mail</u>	<u>Digital</u>	<u>Paper</u>
Attn. Tom Young, SET Executing Agent 412 TENG/ENI 61 N. Wolfe Ave. Bldg 1632 Edwards, AFB, CA 93524	0	2	2
Attn: Michael Rice Department of Electrical & Computer Engineering 459 Clyde Building Brigham Young University Provo, UT 84602 mdr@byu.edu	1	0	0
Attn: Erik Perrins University Of Kansas Center For Research 2385 Irving Hill RD Lawrence KS 66045-7563 esp@ku.edu	1	0	0
Andrew McMurdie Department of Electrical & Computer Engineering 459 Clyde Building Brigham Young University Provo, UT 84602 amcmurdie@gmail.com	1	0	0
Edwards AFB Technical Research Libaray Attn: Darrell Shiplett 307 East Popson Ave, Bldg 1400 Edwards AFB CA 93524	0	2	2

Offsite Distribution

Defense Technical Information Center DTIC/O 8725 John J Kingman Road, Suite 0944 Ft Belvoir, VA 22060-6218	1	0	0
U.S. ARMY PEO STRI Acquisition Center Email to: kaitlin.lockett@us.army.mil Attn: Kaitlin F. Lockett 12350 Research Parkway Orlando, FL 32826	1	0	0

REPORT DOCUMENTATION PAGE				Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.					
1. REPORT DATE (DD-MM-YYYY) 25-06-2014		2. REPORT TYPE Technical Paper		3. DATES COVERED (From - To) 3/13 -- 3/16	
4. TITLE AND SUBTITLE iNET Preamble Detector Performance in the Presence of Multipath Interference				5a. CONTRACT NUMBER: W900KK-13-C-0026	
				5b. GRANT NUMBER: N/A	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S) Andrew McMurdie, Michael Rice, Erik Perrins				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Department of Electrical & Computer Engineering, 459 Clyde Building Brigham Young University, Provo, UT 84602 University Of Kansas Center For Research, 2385 Irving Hill RD, Lawrence KS 66045-7563				8. PERFORMING ORGANIZATION REPORT NUMBER 412TW-PA-14319	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) Test Resource Management Center Test and Evaluation/ Science and Technology 4800 Mark Center Drive, Suite 07J22, Alexandria, VA 22350				10. SPONSOR/MONITOR'S ACRONYM(S) N/A	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S) SET 2014-0050	
12. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release A: distribution is unlimited.					
13. SUPPLEMENTARY NOTES CA: Air Force Flight Test Center Edwards AFB CA CC: 012100					
14. ABSTRACT Multiple preamble detectors are presented and applied to an SOQPSK-TG modulated signal in simulation. Multipath interference, additive white Gaussian noise, and frequency offsets are applied to the signal before detection is attempted. Simulation results are compared. A non-coherent post-detection integration (NCPDI) detector considered in this paper demonstrates the best detection performance for a reduced complexity.					
15. SUBJECT TERMS Preamble-Assisted Equalization for Aeronautical Telemetry (PAQ), Spectrum, Aeronautical telemetry, algorithm, bandwidth, Integrated Networked Enhanced Telemetry (iNET), Shaped Offset Quadrature Phase Shift Keying Test Group (SOQPSK-TG), bit error rate (BER), Orthogonal Frequency Division Multiplexing (OFDM), non-coherent post-detection integration (NCPDI)					
16. SECURITY CLASSIFICATION OF: Unclassified			17. LIMITATION OF ABSTRACT None	18. NUMBER OF PAGES 10	19a. NAME OF RESPONSIBLE PERSON 412 TENG/EN (Tech Pubs)
a. REPORT Unclassified	b. ABSTRACT Unclassified	c. THIS PAGE Unclassified			19b. TELEPHONE NUMBER (include area code) 661-277-8615

iNET PREAMBLE DETECTOR PERFORMANCE IN THE PRESENCE OF MULTIPATH INTERFERENCE

Andrew McMurdie
Brigham Young University

Michael Rice
Faculty Advisor
Brigham Young University

Eric Perrins
University of Kansas

ABSTRACT

Multiple preamble detectors are presented and applied to an SOQPSK-TG modulated signal in simulation. Multipath interference, additive white Gaussian noise, and frequency offsets are applied to the signal before detection is attempted. Simulation results are compared. A non-coherent post-detection integration (NCPDI) detector considered in this paper demonstrates the best detection performance for a reduced complexity.

INTRODUCTION

This paper will consider data-aided synchronization and equalization for aeronautical telemetry. The integrated Network Enhanced Telemetry (iNet) standard [1] describes a packet-based mode of data transfer, useful for telemetry downlinks. The standard defines each packet as consisting of three fields: a preamble, an attached sync marker (ASM), and data bits in the form of an LDPC codeword.

Data-aided synchronizers and equalizers operate by comparing a copy of a preamble (a known sequence) to the received copy. The frequency, phase, and timing offset can be estimated in the synchronizer. Previous work on this idea using iNET formatted SOQPSK-TG is shown in [2]. The comparison is used in the equalizer to estimate the impulse response of the channel in discrete time, which is then used to compute the optimum equalizer coefficients. See [3] for a more detailed example of this.

The first challenge in either operation lies in determining the starting location of the preamble for each packet within the received signal. Whatever detector is employed to find the preamble must be robust enough to detect it reliably given unknown channels and frequency offsets. The detected preamble can then be used in the synchronizers or equalizers.

This paper will focus on preamble detection in SOQPSK-TG modulated data streams in the iNET format.

SIGNAL MODEL

The transmitted signal, $s(t)$, uses an SOQPSK-TG modulated carrier. Details on SOQPSK-TG are shown in [4] and [5]. Post-modulation, the signal is convolved with a frequency selective channel. In addition, a frequency offset and additive white Gaussian noise is added. The received signal is of the form

$$r[n] = \left[\sum_{k=-N_1}^{N_2} h[k] s[n-k] \right] e^{j\omega_0 n} + w[n] \quad (1)$$

where $h[n]$ is the impulse response of the unknown channel with support on $-N_1 \leq n \leq N_2$, $s[n]$ are the received samples of the SOQPSK-TG signal, ω_0 is the unknown frequency offset, and $w[n]$ are samples of a zero-mean complex-valued white Gaussian noise process.

The bit pattern of the preamble must also be considered and chosen. From analysis in [6], the chosen sequence is CD98HEX repeated eight times. This pattern was chosen because the repetition allowed fast acquisition in burst-mode transmissions.

THE MAXIMUM LIKELIHOOD PREAMBLE DETECTOR

Barker [7] showed that preamble detection (also called “frame synchronization”) was possible by maximizing a simple correlation function. Massey expounded on this by deriving the maximum likelihood (ML) preamble detector searching for binary data in Gaussian noise [8]. Gansman *et al.* addressed unknown carrier frequency and phase in the received signal [9]. Choi and Lee, who derived several ML functions examined in this paper, developed an ML detector that has a “double correlation” structure [10]. The Choi and Lee functions provide better performance over a wider frequency offset than the Gansman preamble detector [9].

Pedone *et al.* [11] showed a preamble detector from a series of balanced generalized post detection integration (B-GPDI) operations. Their work used a non-coherent combination of coherent partial correlations (also called “integrations”). This paper will utilize this structure, called non-coherent post detection integration (NCPDI) to derive two lower-complexity preamble detectors to be examined.

SIMPLE PREAMBLE DETECTOR

The basic preamble detector structure in the literature consists of a correlation function that compares a known and stored copy of the preamble to the received samples. For this paper, let $p[n]$, $0 \leq n < L_p$ be the stored copy of the preamble of length $L_p - 1$. In the AWGN case (where no frequency-selective channel or frequency offset is applied), the received signal takes the form $r[n] = s[n] + w[n]$. The correlation function is calculated as

$$L_0[u] = \left| \sum_{n=u}^{u+L_p-1} r[n]p^*[n-u] \right| \quad (2)$$

This function is evaluated once for each received sample. Over each packet length, the maximum value of L_0 , called i_{max} , is chosen as the starting location of the preamble. If the true location of the preamble for a given packet is at sample i , then the preamble detector has correctly decided the starting location of the preamble if $i_{max} = i$.

This detector has the advantage of being moderately simple in complexity. It required $4L_p + 2$ real-valued multiplications and a single square root operation.

CHOI-LEE PREAMBLE DETECTORS

In real telemetry, assuming an AWGN environment is inadequate to achieve good performance. The added interference of the frequency offset causes the simple preamble detector in (2) to fail; the frequency offset introduces destructive cancellation in the summation.

The Choi and Lee described “double correlation” functions exhibit good performance despite unknown channel and frequency offset.

The first function (called $L_1(u)$ in [10]) has the form

$$L_{CL-1a}[u] = \sum_{i=1}^{L_p-1} \left\{ \left| \sum_{k=i}^{L_p-1} r^*[u+k]p[k]r[u+k-i]p^*[k-i] \right| - \sum_{k=u+i}^{u+L_p-1} |r[k]||r[k-i]| \right\} \quad (3)$$

This function is computationally complex. It requires $\frac{1}{2}[13L_p(L_p - 1) + 4L_p]$ real-valued multiplications and $2L_p - 1$ square root operations for each index u .

If unknown frequency-selective multipath interference is also applied to the transmitted signal, the correction term in (3) can be omitted, resulting in the second Choi-Lee detector function:

$$L_{CL-1b}[u] = \sum_{i=1}^{L_p-1} \left\{ \left| \sum_{k=i}^{L_p-1} r^*[u+k]p[k]r[u+k-i]p^*[k-i] \right| \right\} \quad (4)$$

This function needs only $6L_p(L_p-1)$ real-valued multiplications, and L_p-1 square root operations.

Choi and Lee proposed two other functions that result from using only the $i = 1$ terms in (3) and (4) to produce, respectively:

$$L_{\text{CL-2}}[u] = \left| \sum_{k=1}^{L_p-1} r^*[u+k]p[k]r[u+k-1]p^*[k-1] \right| - \sum_{k=u+1}^{u+L_p-1} |r[k]| |r[k-1]| \quad (5)$$

and

$$L_{\text{CL-3}}[u] = \left| \sum_{k=1}^{L_p-1} r^*[u+k]p[k]r[u+k-1]p^*[k-1] \right| \quad (6)$$

The $L_{\text{CL-2}}$ function requires $15L_p-13$ real-valued multiplications and L_p+1 square root operations for each index u . The $L_{\text{CL-3}}$ function requires $12(L_p-1)$ real-valued multiplications and a single square root operation for each index u .

For all of these functions, as in the AWGN case, the maximum value is found over the length of a packet. This is the decided location of the preamble.

NCPDI PREAMBLE DETECTORS

An inherent disadvantage of the Choi and Lee detectors is the overwhelming computational complexity required for each sample value u . Running these detectors in real-time is a difficult proposition at best; it is desirable to find a reduced-complexity detector that will achieve good performance even in unknown multipath interference and frequency offset environments.

We adapt the non-coherent post-detection integration (NCPDI) detector developed in [11]. We first write the correlation interval as $L_p = L_{\text{PDI}}L_{\text{coh}}$ to separate the correlation into two sections: coherent correlations of length L_{coh} , and L_{PDI} non-coherent sums of the L_{coh} combinations. This is written as

$$L_{\text{NCPDI}}[u] = \sum_{k=0}^{L_{\text{PDI}}-1} \left| \sum_{m=kL_{\text{coh}}}^{(k+1)L_{\text{coh}}-1} r[u+m]p^*[m] \right|^2 \quad (7)$$

Taking advantage of the chosen preamble structure, we set $L_{\text{coh}} = 32$. This is the length of the repeating sequence in the preamble (at 2 samples per bit). Choosing this value then forces $L_{\text{PDI}} = 8$. Further taking advantage of the fact that $p[n]$ is the form of the modulated bit pattern repeated eight times, let $q[n]$ be the SOQPSK-TG modulated samples of a single repeating section of the preamble (corresponding to the bits CD98HEX), with length L_q . With some variable manipulation, we can write the function as

$$L_{\text{NCPDI-1}}[u] = \sum_{k=0}^7 \left| \sum_{l=0}^{L_q-1} r[u + kL_q + l]q^*[l] \right|^2 \quad (8)$$

This function requires $4L_q + 16$ real-valued multiplications and zero square root operations for each index u .

A simplified version of this detector quantizes the possible values of $q[n]$ to ± 1 , $\pm j$, and $\frac{1}{\sqrt{2}}(\pm 1 \pm j)$. This function, denoted $L_{\text{NCPDI-2}}$, requires only 32 real-valued multiplications and zero square root operations for each index u .

PERFORMANCE

At $N = 2$ samples per bit and using the preamble structure shown above, Table 1 lists the proposed functions and their computational requirements for each index u . As was desired, the NCPDI detectors have a significantly reduced computational complexity.

Table 1: Computational Complexity of the Candidate Preamble Detectors
For a Sample Rate of $N = 2$ Samples/Bit

$L[u]$	# Real-Value Mults.	# Square-Roots
$L_0[u]$	1,026	1
$L_{\text{CL-1a}}[u]$	424,832	511
$L_{\text{CL-1b}}[u]$	391,680	255
$L_{\text{CL-2}}[u]$	3,827	257
$L_{\text{CL-3}}[u]$	3,060	1
$L_{\text{NCPDI-1}}[u]$	1,040	0
$L_{\text{NCPDI-2}}[u]$	32	0

All of these functions were tested in simulation, and performance was gauged by the mean and variance of $i - i_{\max}$. Simulations were performed with three different channel impulse responses, all of which were captured during channel sounding experiments at Edwards AFB, California [12]. See Figure 1 for the frequency responses of the channels. The simulations were run with a bit rate of 10.3125 Mbits/s, using SOQPSK-TG modulation at a sample rate of $N = 2$ two samples/bit. Frequency offsets of $\Delta f = 0$ Hz and $\Delta f = 50$ KHz were applied.

As shown in figures 2a - 2f, the detectors using $L_{\text{CL-1a}}$, $L_{\text{CL-1b}}$, $L_{\text{NCPDI-1}}$ and $L_{\text{NCPDI-2}}$ exhibited great performance in all test scenarios. The mean error for the detectors using these functions was very nearly zero, even in the high frequency offset environments.

Some caution must be exercised when examining the variance results. Because many of the index errors were zero the number of errors from which the variance estimate is determined is small,

causing the estimate to be somewhat unreliable. This is especially true for the L_{CL-1a} and L_{CL-1b} based detectors, who had nearly zero errors across the board.

However, we can draw general conclusions from the results. The L_{CL-1a} and L_{CL-1b} based detectors had the best performance, followed closely by the $L_{NCPDI-1}$ and $L_{NCPDI-2}$ based detectors. The L_{CL-2} and L_{CL-3} detectors came third in performance, although their error variances were quite different from channel to channel.

The correction term found in $L_{NCPDI-1}$ and L_{CL-2} had a curious effect on the detector performance. Depending on the channel, it either improved or degraded system performance when compared to the L_{CL-1b} and L_{CL-3} detector systems. It appears that the varying ISI from channel to channel coupled with the correction term causes detector performance to vary, as well.

As expected, the simple detector based on L_0 showed good performance when the frequency offset $\Delta f = 0$ Hz, but had terrible performance when the frequency offset $\Delta f = 50$ KHz.

CONCLUSIONS

We have shown that of the candidate functions listed, the reduced complexity NCPDI detector provides the best tradeoff between performance and computational complexity. It is also shown that preamble detectors based on SOQPSK-TG samples can have good performance, despite an unknown frequency offset and unknown ISI.

ACKNOWLEDGMENTS

This work was funded by the Test Resource Management Center (TRMC) Test and Evaluation Science and Technology (T&E/S&T) Program through the U.S. Army Program Executive Office for Simulation, Training and Instrumentation (PEO STRI) under contract W900KK-13-C-0026 (PAQ).

REFERENCES

- [1] integrated Network Enhanced Telemetry (iNET) Radio Access Network Standards Working Group, "Radio access network (ran) standard, version 0.7.9." [Online]. Available: <https://www.tena-sda.org/display/INET/iNET+Platform+Interface+Standards>
- [2] M. Rice and E. Perrins, "On frequency offset estimation using the iNET preamble in frequency selective fading channels," submitted to the 2014 IEEE Military Communications Conference.

- [3] M. Rice, M. S. Afran, M. Saquib, A. Cole-Rhodes, and F. Moazzami, "On the performance of equalization techniques for aeronautical telemetry," submitted to *IEEE Transactions on Aerospace & Electronic Systems*, 2014.
- [4] E. Perrins and M. Rice, "Reduced-complexity approach to iterative detection of coded SO-QPSK," *IEEE Transactions on Communications*, vol. 55, no. 7, pp. 1354–1362, July 2007.
- [5] T. Nelson, E. Perrins, and M. Rice, "Near optimal common detection techniques for shaped offset QPSK and Fehers QPSK," *IEEE Transactions on Communications*, vol. 56, no. 5, pp. 724–735, May 2008.
- [6] B. Erkmen, A. Tkacenko, and C. Okino, "Preamble design for symbol timing estimation from SOQPSK-TG waveforms," *Proceedings of the International Telemetry Conference*, October 2009.
- [7] R. Barker, *Group synchronization of binary digital systems*. London: Butterworth, 1953.
- [8] J. Massey, "Optimum frame synchronization," *IEEE Transactions on Communications*, vol. 20, no. 2, pp. 115–119, April 1972.
- [9] J. Gansman, M. Fitz, and J. Krogmeier, "Optimum and suboptimum frame synchronization for pilot-symbol-assisted modulation," *IEEE Transactions on Communications*, vol. 45, no. 10, pp. 1327–1337, October 1997.
- [10] Z. Choi and Y. Lee, "Frame synchronization in the presence of frequency offset," *IEEE Transactions on Communications*, vol. 50, no. 7, pp. 1062–1065, July 2002.
- [11] R. Pedone, M. Villanti, A. Vanelli-Coralli, G. Corazza, and P. Mathiopoulos, "Frame synchronization in frequency uncertainty," *IEEE Transactions on Communications*, vol. 58, no. 4, pp. 1235–1246, April 2010.
- [12] M. Rice and M. Jensen, "A comparison of L-band and C-band multipath propagation at Edwards AFB," *Proceedings of the International Telemetry Conference*, October 2011.

Figure 1: The example channels from channel sounding experiments at Edwards AFB: (top) a length-9 channel from the flight line; (middle) a length-19 channel from take-off; (bottom) a length-5 channel from low-elevation angle "up and away" flight.

(a) Error means for simulations with channel 1

(b) Error variances for simulations with channel 1

(c) Error means for simulations with channel 2

(d) Error variances for simulations with channel 2

(e) Error means for simulations with channel 3

(f) Error variances for simulations with channel 3

Figure 2: All simulation results. See figure 3 for plot legend.

Figure 3: Plot legend for figures 2a - 2f.