REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188		
<p>Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.</p>					
1. REPORT DATE (DD-MM-YYYY) July 2014		2. REPORT TYPE Briefing Charts		3. DATES COVERED (From - To) July 2014- August 2014	
4. TITLE AND SUBTITLE Numerical and experimental investigation of confined turbulent multiple transverse jets			5a. CONTRACT NUMBER In-House		
			5b. GRANT NUMBER		
			5c. PROGRAM ELEMENT NUMBER		
6. AUTHOR(S) F. Davoudzadeh, D. Forliti			5d. PROJECT NUMBER		
			5e. TASK NUMBER		
			5f. WORK UNIT NUMBER Q09Z		
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Air Force Research Laboratory (AFMC) AFRL/RQRC 10 E. Saturn Blvd Edwards AFB CA 93524-7680			8. PERFORMING ORGANIZATION REPORT NO.		
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) Air Force Research Laboratory (AFMC) AFRL/RQR 5 Pollux Drive. Edwards AFB CA 93524-7048			10. SPONSOR/MONITOR'S ACRONYM(S)		
			11. SPONSOR/MONITOR'S REPORT NUMBER(S) AFRL-RQ-ED-VG-2014-221		
12. DISTRIBUTION / AVAILABILITY STATEMENT Distribution A: Approved for Public Release; Distribution Unlimited					
13. SUPPLEMENTARY NOTES Briefing Charts presented at Joint Propulsion Conference, Cleveland Ohio, 28 July 2014. PA#14386					
14. ABSTRACT The flow and mixing properties of confined transverse jets are relevant to a myriad of combustion devices ranging from propulsion to energy generation and chemical processing. The current effort focuses on understanding the mixing process between a transverse jet mixing in a confined system. The current study involves the simulation of a single confined transverse jet configuration under matched conditions of a companion experiment. The main flow Reynolds number considered is in the range of 25000 - 53000 and the jet-to-main flow momentum flux ratio is varied from 3.2 -14.3. The momentum and scalar mixing is investigated through the solution of the Reynolds-Averaged Navier Stokes (RANS) equations. The mean scalar mixing characteristics are compared to experimental data. The turbulence model that is used is the low Reynolds number k- ϵ model. Due to demonstrated symmetry, only a one-half section of the geometry is considered. All numerical simulations capture salient flow structures such as the counter-rotating vortex pair (CRVP). The current investigation shows the numerical simulations predict the experimental data with a good degree of accuracy.					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON
a. REPORT	b. ABSTRACT	c. THIS PAGE			19b. TELEPHONE NO (include area code)
Unclassified	Unclassified	Unclassified	SAR	38	Nils Sedano 661-275-5972

Numerical and Experimental Investigation of Confined Turbulent Multiple Transverse Jets

29 July 2014

Presented to: AIAA Propulsion and Energy, Cleveland, Ohio

Farhad Davoudzadeh, Ph.D. – Air Force Research Laboratory

David Forliti, Ph.D. - Sierra Lobo, Inc.

Distribution A: Approved for public release; distribution unlimited

Outline

- **Objectives**
- **Jet in Crossflow characteristics**
- **ONERA Air-to-air Experimental configuration and Computational Setup**
- **AFRL's water-to-water Experimental configuration and Computational Setup**
- **Simulation matrix, computational results**
- **Comparative Analysis Results**
- **Summary & planned work**

Objectives

- **Investigate mixing characteristics of propellants in combustors**
- **CFD support for the in-house Themis project**
- **Provide numerical data for theoretical developments**

Project Themis

- **In-house combustion device research within the Combustion Devices Branch (RQRC) of AFRL**
- **Focuses on investigation of LOX/Hydrocarbon high pressure combustion devices through:**
 - **Theory development**
 - **Modeling and simulation**
 - **Subscale experimentation at reacting and inert conditions:**
 - **Design & test a 10k lbf combustor for liquid propellants**
 - Requires good mixing of variable density propellants
 - Temperature uniformity
 - Concentration uniformity

**Jet in
Crossflow**

Staged Combustion Cycle Rocket Engine

Staged Combustion cycle

Temperature Distribution
On the Turbine Blades

Jet in Cross Flow Characteristics

Complex flow with multiple engineering applications:

- Gas turbine combustors
- Film cooling of turbine blades
- Air pollution
- Chimney emissions
- Industrial burners
- Chemical mixing
- Wastewater discharges

Jet in Cross Flow Characteristics

Adapted from Fric and Roshko (1994)

Previous Numerical Work at AFRL: Air-to-Air Experimental Configuration

Conduct a validation study for a baseline case:

- Experimental data available
- Unity density ratio
- Multiple confined transverse jets
- Single phase/component

ONERA experimental/LES studies of an eight jet mixing chamber

Previous Numerical Work at AFRL: Air-to-Air Experimental Configuration

Air-to-Air Numerical and Experimental Comparisons

Axial velocity profile, $x = 2d$

Axial velocity profile, $x = 5d$

Axial velocity Contours, $x = 2d$

Axial velocity contours, $x = 5d$

Air-to-Air Experimental Data Versus Computational Results: Jet Concentration Profiles

Axial
locations
($d = \text{inj. dia.}$)

$X = 2d$:

$X = 5d$:

$X = 10d$:

AFRL Water-to-Water Experimental setup

Boundary conditions:

Inlets: Velocities, species, K ,
(Fully devp'd turb. profiles)

Outlet: Static Pressure, K , ϵ

Operating liquid: Water

Schematic of the experimental setup

Experimental setup

Simulation matrix

Considerations:

- Turning of outlet Flow
- Jets 2, 3, 5, and 6 not coplanar with exit pipe
- Turbulence Schmidt #
- Gravity effects

- **Simulation Matrix:**
 - Single injector without plenum outlet
 - Smaller computational domain, less computational resources needed
 - Single jet + plenum
 - Multiple jets: 2, 4, 6
 - Momentum flux ratios: 3.2, 8.2, 14.3, 20.3, 28.3, 36.5, 47.3

Grid Distribution Around the Jet

(Total cells: 3 million Hex Cells)

Grid Distribution Around the Outlet (Total cells: 3 million Hex Cells)

Hybrid Grid Around the Outlet:

Geometry for the Single jet without the Outlet Plenum

Computational setup and Solution Procedure

- **Equations Solved:**
 - Momentum Eqs.
 - Continuity
 - Turbulent Kinetic Energy (TKE)
 - Turbulent Dissipation Rate (TDR)
 - Species
- **Boundary Conditions:**
 - *Inlet BCs:* Velocities, K , ε
 - Inlet BCs are inlet profiles obtained from separate fully developed pipe flow simulations
 - *Exit BC:* Static Pressure
- **Discretization:** Second Order Upwind for all the equations
- **Turbulence Model:** Low Reynolds number K - ε (K - ω , and other variants of K - ε with various options were also tried)
- **Material Type:** Liquid water

Computational setup and Solution Procedure

... Continued

- **Number of Grid Points:**

- Simulation performed on one half of the geometry utilizing the geometry symmetry
- Two grids generated:
 - Single jet without plenum: 2.2 million all hex cells
 - Single jet with plenum: 3 million mostly hex cells
 - Wall $y^+ < 1$
- Fine grids allowed use of the low Reynolds number K- ϵ turbulence model integrating the solution to the wall

Solution Convergence History

Convergence History of Equations' Residuals

Convergence History of Mass Flow Rate at the Exit

Geometry for the Single jet without Outlet Plenum

Jet mass fraction, $J = 14.3$

Axial Velocity & TKE at: Inlet, Measurement Plane, and at Exit (J = 20.3)

Axial velocity

Turbulent Kinetic Energy

Note the Fully Developed Turbulent Inlet Profile

Vortex Core and X-component of Vorticity Distributions at the Measurement Plane and at Exit Plane (J = 20.3)

Jet Mass Fraction Distributions & Penetration for Different Momentum Flux Ratios (J) Continued . . .

Jet Mass Fraction Distributions & Penetration for Different Momentum Flux Ratios (J)

Computed X-vorticity & Jet Mass Fraction Distributions at the $x/D = 3$

$J = 3.2$

$J = 8.2$

$J = 14.3$

$J = 20.3$

$J = 28.3$

X-vorticity

Jet mass fraction

Computed and Measured Jet Mass Fractions

Continued . . .

Momentum flux

ratio

3.2:

8.2:

14.3:

Jet

Exp. data

CFD results

CFD vs Exp.

Computed and Measured Jet Mass Fractions

Momentum flux

ratio

20.3:

Exp. data

CFD results

CFD vs Exp.

28.3:

Computed and Measured Jet Mass Fractions (Momentum Flux Ratio = 8.2)

Jet direction

Computational & Experimental Jets

- Turbulence Schmidt number
- Computational domain does not include the plenum and the exhaust pipe
- Experimental Jet is not coplanar with exit pipe
- Fluid issuing through experimental jet has to rotate & turn to exit
- Fluid issuing through computational jet has to only turn to exit

Summary & Future Work

- A series of experiments and RANS simulations are performed to investigate JICF induced-mixing for an iso-density liquid (water).
- RANS simulations, using Fluent, captures the flow features such as the CRVs, and show reasonable predictions with the measured concentration data.
- Experimental data shows asymmetry in the wake
- Extensive computations planned:
 - Various momentum flux ratios
 - Multiple jets (2, 4, 6)
 - Plenum effect
 - Turbulent Schmidt number

Computed and Measured Jet Mass Fractions

Experimental data versus computational results: Axial Velocity Contours

Axial
locations
($d = \text{inj. dia.}$)

$X = 2d$:

Experiment

Fluent

STAR-CCM+

CFD⁺⁺

LES (ONERA)

$X = 5d$:

$X = 10d$:

Experimental data versus computational results: Axial Velocity Profiles

Axial
locations
($d = \text{inj. dia.}$)

$X = 2d$:

LES (ONERA)

Fluent

STAR-CCM+

CFD⁺⁺

$X = 5d$:

$X = 10d$:

Experimental data versus computational results:

Experiment

Fluent

Star-ccm+

CFD⁺⁺

LES (ONERA)

Axial Velocity Contours and Radial Profiles at $x = 2d$

Experimental data versus computational results:

Experiment

Fluent

Star-ccm+

CFD⁺⁺

LES (ONERA)

Axial Velocity Contours and Radial Profiles at $x = 5d$

Experimental data versus computational results:

Experiment

Fluent

Star-ccm+

CFD⁺⁺

LES (ONERA)

Axial Velocity Contours and Radial Profiles at $x = 10d$