

UNCLASSIFIED

AD 411808

DEFENSE DOCUMENTATION CENTER

FOR

SCIENTIFIC AND TECHNICAL INFORMATION

CAMERON STATION, ALEXANDRIA, VIRGINIA



UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell or patented invention that may in any way be related thereto.

63-4-4

411808

411808

MEMORANDUM
RM-2887-PR
JANUARY 1962

AD No.

DDC FILE COPY

MINIMUM-WEIGHT DESIGN
FOR MOVING LOADS

Oliver A. Gross and William Prager

DDC
SEP 9 1963
TISIA A

PREPARED FOR:

UNITED STATES AIR FORCE PROJECT RAND

The RAND Corporation
SANTA MONICA • CALIFORNIA

\$2.60

RAND PUBLICATION
MINIMUM-WEIGHT DESIGN
FOR MOVING LOADS

Oliver A. Gross and William Prager

RM-2887-PR

January 1962

in brief

This report derives a mathematical model that describes the minimum-weight design of a horizontal beam under an invariable, concentrated, vertical load moving slowly from one end to the other. Beams of this type, although possibly impractical in earthbound structures, may someday become interesting for applications in a weightless environment such as that of a space station.

④ #2160 ⑤ 739 200

AFRDP-R
Received

JAN 26 1962

④ MEMORANDUM
RM-2887-PR

⑪ January 1962,

⑦ NA

⑧ NA

⑨ NA

⑫ 16p.

⑬ NA

⑭ NA

⑮ NA

⑯ NA

⑰ 22

⑱ NA G.C.

⑥ MINIMUM-WEIGHT DESIGN
FOR MOVING LOADS,

⑩ by Oliver A. Gross and William Prager

This research is sponsored by the United States Air Force under Project RAND ^⑬ Contract No. AF 49(638)-700 → monitored by the Directorate of Development Planning, Deputy Chief of Staff, Research and Technology, Hq USAF. Views or conclusions contained in this Memorandum should not be interpreted as representing the official opinion or policy of the United States Air Force. Permission to quote from or reproduce portions of this Memorandum must be obtained from The RAND Corporation.

PREFACE

Plastic design of structures has received considerable attention in recent years. To the authors' knowledge, the present Project RAND memorandum is an innovation in this field and also in the domain of linear programming - in the former because the beam design is to withstand a one-parameter family of load conditions rather than a single load distribution, and in the latter because the program involves a continuum rather than a finite number of variables.

The basic mathematical treatment of the continuous version of the problems presented in this paper is contained in RM-2993 PR, "A Linear Program of Prager's: Notes on Linear Programming and Extensions - Part 60," now in the process of publication. In the present paper, which is to be submitted for presentation at the Fourth U. S. National Congress of Applied Mechanics at Berkeley, California, June, 1962, the mathematical model is derived from physical considerations and solved in a form readily accessible to the structural engineer.

It might be added that beams of the type considered in this paper may be impractical (i.e., expensive to manufacture) for earth-bound structures. They are, however, important for theoretical reasons since they represent, in a sense, the ultimate in weight design. It is of course conceivable that such designs might become more important in the future as actual components of nonearth-bound structures such as space stations.

SUMMARY

↘ The main problem considered and solved ~~in this paper~~ is the minimum-weight design of a horizontal I-beam of constant web and variable flange thickness. The beam is simply supported at one end and built in at the other and is designed to withstand (in plastic flow) a concentrated vertical load of fixed intensity moving slowly from one end to the other.

To introduce ~~the reader to~~ the general techniques employed, a few discrete versions of the problem are first presented and solved as linear-programming problems. ↑

CONTENTS

PREFACE	11
SUMMARY	111
Section	
1. INTRODUCTION	1
2. DISCRETE POSITIONS OF THE LOAD	3
3. CONTINUOUSLY VARYING POSITION OF THE LOAD ...	10
REFERENCES	16

MINIMUM-WEIGHT DESIGN FOR MOVING LOADS

1. INTRODUCTION

Plastic design of continuous beams and frames for minimum weight has been extensively studied in recent years. Almost without exception, earlier studies dealt with structures of given over-all dimensions (widths of bays and heights of stories) that are subjected to a single system of concentrated loads judged to be the most dangerous combination of the groups of loads that the structure has to carry. For practical reasons, the beams and columns of steel frames are usually prismatic, so that the designer disposes of only a finite number of design parameters (the yield moments of the beams and columns). If, within the range of practical structural sections, the unit weight of a section can be approximated by a linear function of its yield moment, designing for minimum weight can then be formulated as a problem in linear programming (see, for instance, [1]*, p. 84 ff.).

While designs with beams or columns of continuously varying cross section would not, in general, be practical, they are worth investigating because they furnish the theoretical minimum of the structural weight, against which practical designs may be checked.

*Numbers in brackets indicate items in the list of references at the end of the paper.

The minimum-weight design of a beam with continuously varying cross section subjected to a single system of loads has been discussed by Heyman [2]. Consider, for instance, a sandwich beam with a core of given constant height h and breadth b , and flanges of constant breadth b and variable thickness t . Since the designer controls only the thickness t , the variable part of the structural weight is proportional to the integral of t extended along the beam. Using a theorem of Drucker and Shield [3], Heyman has shown that the absolute minimum-weight design of such a beam can be based on a deflected shape for which the curvature has constant absolute value. Figure 1 shows deflections of this kind for a beam that is simply supported at one end ($x = 0$) and built in at the other end ($x = l$). The curvature is found to change sign at $x = l/\sqrt{2}$. Accordingly, the bending moment must vanish at $x = l/\sqrt{2}$. Since the indeterminacy of the beam is removed by this condition, the bending moments can be obtained from the design loads without reference to the cross-sectional dimensions of the beam. The flange thickness at each cross section is then determined from the bending moment at this section in such a way that the yield limit of the flange material is reached at all sections when the beam is subjected to the design loads.

As this example shows, an absolute minimum-weight design for a single system of loads is essentially a statically

determinate design. This feature, which greatly facilitates the design, is likely to be absent when a structure has to be designed for more than one system of loads. To illustrate the arguments that arise in the solution of problems of this kind, the sandwich beam in Fig. 1 will be designed for a moving load of constant intensity P that may act at any section of the beam. Calling for the determination of the flange thickness at each station x , this problem involves an infinity of design parameters or, what amounts to the same, a design function $t(x)$. Since there are as yet no general methods of solving continuous problems of this kind, a discrete analog will be discussed in Sec. 2 as a guide to the solution of the continuous problem, which will be given in Sec. 3.

2. DISCRETE POSITIONS OF THE LOAD

The general features of the desired design can be explored in the following way. Dividing the span l of the beam into n equal segments, suppose that only the partition points are eligible as points of application of the load, and that the flange thickness t is a segmentwise linear function of the distance x measured along the beam. This kind of design is specified by the n values of t at the points $x = l/n, 2l/n, \dots, (n-1)l/n, l$, the flange thickness being zero at the simply supported end $x = 0$. It is to be expected that the desired design with continuously varying flange thickness

results as $n \rightarrow \infty$.

If h denotes the constant height and b the constant breadth of the core, and s_0 the tensile or compressive yield stress of the flange, and if the flange thickness t is treated as small in comparison to h , the yield moment is

$$(2.1) \quad Y = s_0 bht.$$

For a unit length of the beam, the variable part of the structural weight, that is, the weight of the flanges, is proportional to the flange thickness t and hence to the yield moment (2.1).

For $n = 2$, a design of the considered type is specified by the yield moments Y_1 and Y_2 at the center of the beam and the built-in end. Only one position of the load and one yield mechanism need to be investigated. With the deflections and hinge rotations shown in Fig. 2, the condition that the energy dissipated in the plastic hinges equals the work of the load takes the form

$$(2.2) \quad 2Y_1 + Y_2 = Pl/2.$$

Since the yield moment vanishes at the simply supported end, the average values of the limiting moment in the two halves of the span are $Y_1/2$ and $(Y_1 + Y_2)/2$, so that the variable part of the structural weight is proportional to

$$(2.3) \quad W = (2Y_1 + Y_2)l/4.$$

The yield moments Y_1 and Y_2 of a minimum-weight design must satisfy (2.2). Substitution of this equation into (2.3) shows the variable part of the structural weight to be proportional to

$$(2.4) \quad W = Pl^2/8.$$

Thus there exist infinitely many minimum-weight designs for $n = 2$.

For a greater value of n , a yield mechanism is defined by the locations of its two plastic hinges, say $x = hl/n$ and $x = kl/n$ with $k > h$. From the deflections and hinge rotations indicated in Fig. 3, the condition that the energy dissipation in the plastic hinges must not exceed the work of the load becomes

$$(2.5) \quad kY_h + hY_k \geq Ph(k-h)l/n.$$

The variable part of the structural weight is proportional to

$$(2.6) \quad W = (Y_1 + Y_2 + \dots + Y_{n-1} + 0.5 Y_n)l/n.$$

For $n = 4$, for instance, the (nonnegative) yield moments of the minimum-weight design must minimize the linear form

$$(2.7) \quad W = (Y_1 + Y_2 + Y_3 + 0.5 Y_4)l/4,$$




FIG. 1




FIG. 2




FIG. 3

while satisfying the inequalities

$$\begin{aligned}
 (2.8) \quad & 2Y_1 + Y_2 && \geq Pl/4, \\
 & 3Y_1 &+ Y_3 && \geq Pl/2, \\
 & 4Y_1 &&+ Y_4 && \geq 3Pl/4, \\
 & & 3Y_2 + 2Y_3 && \geq Pl/2, \\
 & & 4Y_2 &+ 2Y_4 && \geq Pl, \\
 & & & 4Y_3 + 3Y_4 && \geq 3Pl/4,
 \end{aligned}$$

which are obtained from (2.5) by letting h and k vary from 1 to 4 subject to the condition that $k > h$.

In general, the n yield moments of the minimum-weight design must minimize a linear form, which represents the variable part of the structural weight, while satisfying $n(n-1)/2$ inequality constraints. Expressed in structural terms, the essential features of the solution of this linear-programming problem are as follows (see, for instance, [4]). The yield moments of the minimum-weight design fulfill n of the $n(n-1)/2$ constraints as equations rather than inequalities. Each of these equations corresponds to a yield mechanism that becomes critical for some position of the moving load; it states that the energy dissipated in the plastic hinges of this mechanism must equal the work of the load if the mechanism is to be critical. The n equations can be linearly combined with nonnegative factors in such a manner that the coefficient of each yield moment in the

linear combination equals the coefficient of this yield moment in the expression for the variable part of the structural weight.

For $n = 4$, the use of the equality sign in the second, fourth, fifth, and sixth relations (2.8) furnishes the yield moments

$$(2.9) \quad Y_1 = 5Pl/32, Y_2 = 7Pl/48, Y_3 = Pl/32, Y_4 = 5Pl/24,$$

which are readily seen to satisfy the remaining two relations (2.8). Moreover, when the four equations corresponding to critical yield mechanisms are combined with the factors $l/12$, $l/24$, $l/32$, $l/48$, the coefficient of each yield moment in the linear combination is found to equal the coefficient of this yield moment in (2.7). The yield moments (2.9) therefore represent the minimum-weight design.

In Fig. 4, the line OABCD represents the variation of the yield moment along the beam; and OA'B'C'D' is the image of this line, by symmetry with respect to the x-axis. For the considered positions of the load at $x = l/4$, $x = l/2$, and $x = 3l/4$, the bending moments are represented by the lines OAC'E, OBC'D', and OCD', respectively. For none of these load positions does the absolute value of the bending moment at any section of the beam exceed the yield moment at this section, while for each load position the absolute value of the bending moment attains the yield moment in at




FIG. 4

least two sections.

With the yield moments (2.9), (2.7) furnishes
 (2.10)
$$W = 7Pl^2/64.$$

3. CONTINUOUSLY VARYING POSITION OF THE LOAD

The solution of the discrete problem in Sec. 2 suggests that for continuously varying position of the load the yield moments of the minimum weight design are represented by arcs such as OABC and CD in Fig. 5. Denoting the abscissa of C by x_1 , suppose that the load acts at the section $x = x_0 \leq x_1$ and that a plastic hinge forms at this section. The bending moment at this section then equals the yield moment $Y(x_0)$, and the reaction at the simply supported end equals

$$(3.1) \quad R(x_0) = Y(x_0)/x_0.$$

To the left of the load, the bending moments are given by

$$(3.2) \quad M(x; x_0) = x R(x_0) = x Y(x_0)/x_0, \quad 0 \leq x \leq x_0$$

(line OB in Fig. 5). If the arc OABC is concave with respect to the x -axis, these bending moments nowhere exceed the yield moment. To the right of the load, the bending moments are given by

$$(3.3) \quad M(x; x_0) = x R(x_0) - (x - x_0)P, \quad x_0 \leq x \leq \ell$$

(line BE in Fig. 5). Since there must be a yield mechanism




FIG. 5

corresponding to the considered position of the load, the absolute value of the bending moment must attain the yield moment at some abscissa $x = x_2 \geq x_1$ without exceeding the yield moment at any other abscissa. In other words, the line BE must be tangent to the image C'D' of the arc CD with respect to the x-axis. Thus, one obtains

$$(3.4) \quad Y(x) + M(x; x_0) \geq 0, \quad x_1 \leq x \leq l,$$

with equality for one value of x. With the use of (3.1) and (3.3), one finds

$$(3.5) \quad Y(x) \geq (x - x_0)P - x Y(x_0)/x_0, \quad x_1 \leq x \leq l.$$

To find the abscissa of the point of contact E of the line BE and the arc C'D', equate the derivative of the right-hand side of (3.5) to zero and replace x by x_2 . Thus, x_2 is given by

$$(3.6) \quad x_2 = - \frac{P}{[Y(x_0)/x_0]'}, \quad 0 \leq x_0 \leq x_1,$$

where the prime denotes differentiation with respect to x_0 . With this value of x_2 , the yield moment $Y(x_2)$ is found by setting $x = x_2$ and using the equality sign in (3.5). As x_0 varies from 0 to x_1 , the point of contact E moves from C' to D' as indicated in Fig. 5. Accordingly, the arc C'D' is uniquely determined by the arc OABC.

The variable part of the structural weight is propor-

tional to

$$(3.7) \quad W = \int_0^{x_1} Y(x) dx + \int_{x_1}^{\ell} Y(x) dx.$$

Let $Y(x_0)$ be an arbitrarily defined positive concave function in $0 \leq x_0 \leq x_1$ that vanishes for $x_0 = 0$, and $x = f(x_0)$ an arbitrary increasing function that maps the interval $(0, x_1)$ onto (x_1, ℓ) . When the second integral in (3.7) is transformed by the use of the inequality (3.5) and the change of variable $x = f(x_0)$, the relation

$$(3.8) \quad W \geq \int_0^{x_1} [Y(x_0) (1 - \frac{ff'}{x_0}) + (f - x_0)f'P] dx_0$$

is obtained. To render the lower bound (3.8) for the structural weight independent of the choice of $Y(x_0)$, set

$$(3.9) \quad ff' = x_0,$$

or

$$(3.10) \quad f = \sqrt{x_0^2 + c^2},$$

where c is a constant of integration.

Since f is to map the interval $(0, x_1)$ onto (x_1, ℓ) , f satisfies

$$(3.11) \quad f(0) = x_1, \quad f(x_1) = \ell.$$

It follows from (3.10) and (3.11) that

$$(3.12) \quad c = x_1 = \ell/\sqrt{2}.$$

and

$$(3.13) \quad f = \sqrt{x_0^2 + x_1^2}.$$

In view of (3.9) and (3.13), the inequality (3.8) reduces to

$$(3.14) \quad W \geq \frac{1}{4}(1 - \sqrt{2} + \log(1 + \sqrt{2}))Pl^2 = 0.1168Pl^2.$$

To obtain the function $Y(x_0)$ for which W equals this lower bound, identify the function (3.14) with the right-hand side of (3.6) to obtain

$$(3.15) \quad \left(\frac{Y(x_0)}{x_0}\right)' = -\frac{P}{\sqrt{x_0^2 + x_1^2}},$$

or

$$(3.16) \quad Y(x_0) = Px_0 \left\{ k - \log \left[(x_0 + \sqrt{x_0^2 + x_1^2})/l \right] \right\}, \quad 0 \leq x_0 \leq x_1,$$

where k is a constant of integration. To determine this constant, note that $Y(x_1)$ evaluated from (3.16) must equal $Y(x_1)$ obtained by substituting $x_0 = 0$ and $x = x_1$ into (3.5) and using the equality sign in this relation. Thus, the value of k is

$$k = \frac{1}{2} \left(1 + \log \frac{1 + \sqrt{2}}{2} \right).$$

With $f = x_2$, it follows from (3.13) that

$$(3.18) \quad x_0 = \sqrt{x_2^2 - x_1^2},$$

and from (3.5) and (3.16) that

$$(3.19) \quad Y(x_2) = P \left\{ x_2 \sqrt{x_2^2 - x_1^2} - x_2 \sqrt{x_2^2 - x_1^2} k - \log \left[(x_2 + \sqrt{x_2^2 - x_1^2})/l \right] \right\}, \quad x_1 \leq x_2 \leq l,$$

where k is given by (3.17). The arcs OABC and CD in Fig. 5 represent the functions (3.16) and (3.19).

It is interesting to note that the abscissa x_1 defined by (3.12) is identical with the abscissa at which the curvature in Fig. 1 changes sign. An analogous identity was found to exist for the doubly built-in beam, which was treated along similar lines, but no general reason for this has been discovered.

REFERENCES

1. W. Prager, Introduction to Plasticity, Addison-Wesley Publishing Co., Reading, Mass., 1959.
2. J. Heyman, "On the Absolute Minimum Weight Design of Framed Structures," Quarterly Journal of Mechanics and Applied Mathematics, Vol. 12 (1959), pp. 314-324.
3. D. C. Drucker and R. T. Shield, "Design for Minimum Weight," Proceedings of the 9th International Congress of Applied Mechanics (Brussels, 1950), Vol. 5 (Brussels, 1957), pp. 212-222.
4. J. D. Foulkes, "The Minimum-weight Design of Structural Frames," Proceedings of the Royal Society, Ser. A, Vol. 223 (1954), pp. 482-494.