$\frac{\text{UNCLASSIFIED}}{\text{AD}}$

DEFENSE DOCUMENTATION CENTER

FOR

SCIENTIFIC AND TECHNICAL INFORMATION

CAMERON STATION. ALEXANDRIA. VIRGINIA



UNCLASSIFIED



NOLTR 63-33

5 May 1963

A PROPOSAL FOR THE STUDY OF COLLISIONAL PROCESSES LEADING TO ELECTRONIC EXCITATION AND IONIZATION BEHIND SHOCKWAVES

This report presents the proposal to study the fundamental collisional processes which lead to ionization and electronic excitation behind strong shockwaves by means of alkali metal vapors.

The knowledge gained, both experimentally and theoretically, will be helpful in the understanding of the much more complex collisional processes occurring in air around re-entry bodies.

The proposal was accepted for support under the Foundational Research Program at the Naval Ordnance Laboratory and work on this program is currently being performed under NOL Task Number FR-64.

> R. E. ODENING Captain, USN Commander

> a. E. Seigel A. E. SEIGEL By direction

11

CONTENTS

		Page
BACKGROUND		. 1
INTRODUCTION .		. 1
PREVIOUS INVEST	IGATIONS AND AVAILABLE TEST	
FACILITIES .		. 2
NEW APPROACH .		. 3
PROPOSED TEST F	ACILITY	. 4
MEASUREMENTS .		. 7
FUTURE PLANS .		. 7

ILLUSTRATIONS

Figu	re																								Page
1	•			•						•					•	•					•		•		8
2	•	•		•	•	٠	•	•	•	•		•	•		•		•			٠	•		•	•	9
3	•		•	•		•	•	•	•	•		•		•		•	•	•	•	•	•	•	•	•	10
4	٠	٠	•	•	•	•	•	•	٠	٠	•	٠	•	•	•	•	•	•	•	٠	٠	•	٠	•	11

REFERENCES

(1)	Pomerantz, J. and Piacesi, R., "The Equilibrium
	Composition and Thermodynamic Properties of Sodium
	Vapor from 400° to 10,000°K," NOLTR 62-170
	(in publication)

- (2) Encyclopedia of Physics, Vol. XXII, Gas Discharges II
- (3) Burhorn, F., Maecker, H., and Peters, T., Z. Physik 131, 28(1951)

iii

proposal for studying the phenomena under more ideal conditions in a novel laboratory facility.

PREVIOUS INVESTIGATIONS AND AVAILABLE TEST FACILITIES

The most successful tool for producing strong shockwaves, with well-known conditions immediately behind the shock front, is the shocktube. It has therefore been used quite extensively to study ionization and electronic excitation phenomena, particularly in monatomic gases.

All the early investigations showed that spectral lines of impurities appeared before any of the lines of the test gas became discernible in the spectrograms. This indicated that the process of adjustment to the high temperature equilibrium involved in the first step only the molecules of the impurities which have the lower excitation levels. The presence of excited states of the impurities and their electrons will influence the subsequent adjustment of the test gas. The electrons will speed up the adjustment because they are very efficient in accomplishing transitions. Transfer of excitation from the impurity molecules to the molecules of the test gas which may occur would also lead to an accelerated adjustment.

Using spectroscopically pure gases and flushing the shocktube repeatedly prior to the test reduces the content of impurities to a level sufficiently low to escape detection under the condition of very short observation time. However, even in this case the impurity originated electrons and excited states could still be sufficient in numbers to trigger and hasten the adjustment process of the test gas. An investigation of the collisional processes leading to ionization and electronic excitation in a shocktube must therefore be viewed with caution.

Wind tunnels are well-established facilities for the study of flow phenomena under stationary conditions. The production of high stagnation temperature flows has, however, not yet been too successful, if requirements for the absence of impurities are stringent. Since all such tunnels use electric arc heating to achieve the required high energy levels, electrodeintroduced impurities are of major concern. Neglecting for the moment the electrode-introduced impurities and those originally in the test gas, other impurities which may be called inherent may still be present in the arc-heated test gas. They may be produced within the originally pure test gases by the process employed to achieve the needed stagnation enthalpy and then remain in the test gas, because the expansion in the nozzle is too fast for adjustment. Others may be formed during the

expansion process. The kinds of inherent impurities which will be present depend on the test gas or gas mixture being used. In the case of air these inherent impurities may be the nitrous oxide, metastable electronic states and other excited states of long relaxation times.

It can be expected that the different kinds of impurities will, to a varying degree, have an effect on the adjustment processes here under consideration.

With regard to the proposed studies, the shocktube must be regarded unsuitable because a definite evidence of the absence of impurities can most likely not be secured in the very short testing time typical for these facilities. Wind tunnels, on the other hand, could provide very long testing times to study even very faintly luminous flows.

If it would be possible to eliminate the impurities from the flow, then an arc-heated wind tunnel would be preferable for the proposed studies.

NEW APPROACH

Monatomic substances which are gases at normal pressure and temperature, namely, the noble gases, do not meet the requirements of a test gas as set forth in the previous section. The most serious restriction is their fairly high ionization potentials. In addition, they exhibit metastable states. The vapors of the alkali metals Na, K and Cs appear to be a better choice, as will be evident from their characteristic properties (fig. 1).

The alkali metal vapors have the lowest ionization potential of all "gases." Impurities, if present in easily controllable amounts do not effect the onset of ionization.* The spectra of the alkali elements are relatively simple and exhibit the resonance lines in the visible region. The alkali atoms have no metastable states. It can therefore be expected that the expansion from reservoir condition to a supersonic flow leads to a completely relaxed monatomic gas, because the de-excitation from the electronic and ionization levels does not require collisions but can proceed mainly through radiative recombination for which the mean life time is in the order of 10^{-8} seconds.**

* In a closed test facility impurities can be completely eliminated by utilizing the capability of the alkali metals to act as getters.

****** Under certain conditions (see ref. (1)) a very small percentage of molecules may be present in the expanded gas.

Another advantage of utilizing alkali metal vapors becomes apparent with respect to the theoretical determination of the collision cross sections. With only one electron outside of closed shells the solution to the various wave functions representing the ground state, the excited states as well as the ion become more amenable for treatment. Knowing the wave functions the transition probabilities between the various electronic states can be evaluated. Finally, the various collisional cross sections could then be determined.

If the cross sections had been theoretically calculated as indicated above, the adjustment process of equilibrium ionization and electronic excitation could be determined and could be expressed in experimentally observable quantities. Unfortunately, this calculation is not yet available and will not be available in the near future because of the large effort involved in the computations. Therefore, theoretical efforts which should be done to supplement the experimental investigations should concentrate first on the calculations of those cross sections which the experiments show to be the most important or the most interesting ones. A comparison of the calculated and observed collisional cross sections will be indicative of the degree of confidence one can have in the approximation used to evaluate the associated wave functions.

PROPOSED TEST FACILITY

As implied in the previous discussions, an alkali metal vapor test facility would essentially be an arc-heated wind tunnel in which the flow conditions necessary for the proposed studies can be produced. It will, however, distinguish itself from the high-enthalpy arc-heated air wind tunnel because of certain properties of its working fluid. Of particular interest is that the working fluid is an electrical conductor in the solid and liquid state, a nonconductor in the gaseous, nonionized state, and a conductor again in the gaseous, ionized state.

This brings about several advantages for the alkali metal vapor arc tunnel which relate to its design and operation. The working fluid, in its liquid state, can be used as electrodes. Evaporation from the electrodes can supply the system with the working fluid, thereby eliminating the impurity problem.

The alkali metal vapor tunnel can, in principle, be designed similar to an air arc-heated tunnel. The arc discharge would take place between two suitably shaped pools of liquid alkali

metal. The arc-heated vapor would enter a settling chamber from which it would expand through a nozzle into a test chamber. The arc would be started in an argon atmosphere which would be gradually removed as the vapor pressure of the alkali metal increases. The vapor pressure in the reservoir reaches its maximum when it equals the saturation vapor pressure at the temperature of the reservoir chamber. The reservoir pressure is thus restricted to a level for which the reservoir temperature is low enough to prevent reactions between the chamber material and the particular alkali metal in use. The stagnation temperature is also restricted because of the conduction and radiation losses in the settling chamber and because of the mixing of the heated gas with cooler vapors.

In the following, suggestions are made for arrangements which are less restrictive with respect to the temperature and pressure. To obtain higher stagnation temperatures, the temperature of the arc column should be increased. This can only be done by constricting the arc column (ref. (2)). To take full advantage of the temperature increase, the constricting opening should also be utilized as the orifice of a supersonic jet or the throat of a supersonic nozzle.

An electrode arrangement as shown in figure 2 for the case of a jet is suggested. An alkali metal pool in the reservoir chamber (A) is used as the cathode. A cover plate (B) with an orifice in its center which is electrically insulated (C) from the container (A) holding the pool completes the reservoir chamber. To avoid attachment of the arc to the metallic cover plate, its thickness must be restricted. The condition is that the change in the potential in the arc column over the thickness of the constricting plate must be smaller than the cathode and anode potential drop taken together.

Above the orifice a doughnut-shaped anode (D), which is cooled internally, is placed as shown in figure 2. The attachment of the arc to this electrode will be diffused over at least the inside of the electrode due to the low pressure in the test section needed for the proposed investigation. The heat load will therefore be uniformly distributed and sufficiently low to prevent, by internal cooling, melting of the electrode material.

A very effective cooling is needed at the orifice where temperatures and densities are higher. But even with the most effective design of internal cooling, melting of the metal wall limits the degree of constriction and thus the temperature of the constricted portion of the arc channel.

To circumvent this limitation, a water pipe has been utilized (ref. (2)) where the extreme heat-transfer rates are taken up by evaporation cooling. The water pipe is formed by centrifugal forces in an arrangement as shown in figure 3. The water enters a pillbox-shaped container tangentially and leaves at openings in the center of the cover plates (E) with greatly increased rotational speeds. In spite of high rates of evaporation, a uniform cross section constriction of the arc discharge is maintained. Maecker (ref. (3)) was very successful in using the device and was able to produce temperatures of 50,000°K.

It is suggested here to utilize the device in the design of an alkali metal vapor arc tunnel. The water which, of course, could not be used would be replaced by the liquid alkali metal. In doing so, there seems to be no apparent reason why a liquid metal should not perform satisfactorily even though the liquid metal would not wet the material of which the device is made, as water does.

The device could serve as an orifice or as an electrode. As an orifice the same restriction on the length for nonattachment of the arc applies, as previously mentioned, since the liquid forming the pipe is electrically conducting.

As an electrode, however, one should use a long sectriction with the arc attached in the center portion where the outward velocity remains small. This portion will reach higher temperatures than the end portions and thus surface temperatures can be produced where electron emission takes place. The arc should remain attached to the center region because in the outward regions evaporation will occur without leading to ionization and the discharge channel should become insulated from the liquid metal pipe. The liquid pipe electrode should be used as the cathode.

There will be interactions between hydrodynamic and electromagnetic forces. The resulting effects are difficult to estimate since the electric current flows radially in the liquid metal and axially in the plasma. Some experimental investigations will indicate the restrictions imposed due to the magnetohydrodynamic forces.

An advantage of the proposed electrode is that it acts as a reservoir system. Higher pressures can be produced in it than in a reservoir chamber with its restricted temperature range.

The anode can be a doughnut-shaped electrode (D), as has previously been described (fig. 4 and 2). Two jets are ejected

from the liquid pipe electrode when it is in operation. Of particular interest is the jet emerging in the direction opposite to the anode. This jet will be of lower enthalpy since it is not subjected to the heating from the arc discharge, but its expansion is not obstructed by the presence of an electrode.

The development of a suitable electrode system will probably require many trials before a successful arrangement may be achieved. In view of the difficulties encountered in handling of and experimenting with alkali metals, it may be advisable to substitute, wherever possible, mercury for the alkali metals in the development of a suitable electrode system.

MEASUREMENTS

It is proposed that initially all investigations of the onset of electronic excitation and ionization and the approach to thermal equilibrium will be made behind stationary shockwaves on wedges. Almost all data on the temperature, pressure, density, composition, and flow velocity of the test gas will be obtained by means of optical techniques. Since well-known techniques will be utilized and no new measuring techniques are proposed, the techniques to be used will not be described. It may, however, be said that in non-equilibrium region information on the adjustment process can only be obtained by evaluating the shape and absolute intensity of individual spectral lines. A spectrograph of highest resolving power, such as a Fabry-Perot interferometer, is thus essential.

FUTURE PLANS

The alkali metal vapor arc tunnel has been proposed for the study of the basic phenomena taking place in the transition of a low temperature gas into one of high temperature where ionization and electronic excitation are present. The advantages of utilizing the alkali metals are, of course, not restricted to the investigation suggested in this proposal but apply equally well to basic studies of hypervelocity flow phenomena; in particular, boundary layers, ion propulsion systems, and magnetohydrodynamic problems.



FIG. I 8

•



FIG. 2

NOLTR 63-33





FIG. 3



NOLTR 63-33

•

FIG. 4

-

Distribution

Chief, Bureau of Naval Weapons Department of the Navy Washington 25, D. C. Attn: RMMO Attn: RMGA Attn: RRMA	1 1 1
Director, Special Projects Department of the Navy Washington 25, D. C. Attn: SP-20 Attn: SP-27 Attn: SP-272	4 2 1
Office of Naval Research Washington 25, D. C. Attn: Technical Library	1
Commanding Officer Office of Naval Research Branch Office, Box 39, Navy 100 Fleet Post Office, New York, N. Y.	5
Director, DTMB Aerodynamics Laboratory Washington 7, D. C. Attn: Library	1
Naval Weapons Laboratory Dahlgren, Va. Attn: Library	1
Commander U. S. Naval Ordnance Test Station China Lake, Calif. Attn: Technical Library	1
Director Naval Research Laboratory Washington 25, D. C. Attn: Technical Library	2
Director of Intelligence Headquarters, USAF Washington 25, D. C. Attn: AFOIN-3B	1

1

Commander Wright Air Development Div. Wright-Patterson Air Force Base, Ohio Attn: WCOSI-3 Attn: WCLSW-5 Attn: WCRRD	1 1 3
Commander, AFBMD Air Res. & Develop. Command I, O. Box 262 Inglewood, Calif. Attn: WDTLAR Attn: WDTVR	1 2
Chief, DASA The Pentagon Washington, D. C. Attn: Document Library	1
Commanding General Arnold Engineering Development Center Tullahoma, Tenn. Attn: Technical Library Attn: AEKS	1 5
Commanding Officer, DOFL Washington 25, D. C. Attn: Library Rm. 211, Bldg. 92	1
NASA George C. Marshall Space Flight Center Huntsville, Alabama Attn: Technical Library	2
Office, Chief of Ordnance Department of the Army Washington 25, D. C. Attn: ORDTU	1
APL/JHU 8621 Georgia Ave. Silver Spring, Md. Attn: Tech. Reports Group Attn: Librarian	2

Copies

٤.,

	Copies
AVCO Manufacturing Corp. Research & Advanced Development Div. 201 Lowell Street Wilmington, Mass.	
Attn: Technical Library	1
AVCO Manufacturing corp. Everett, Mass. Attn: Dr. Kantrowitz	1
General Electric Co. Space Vehicle & Missiles Dept. 21 South 12th St. Philadelphia, Penn.	0
General Electric, Research Lab.	2
Philadelphia, Penn. Attn: Technical Aircraft	1
National Aeronautics and Space Admin. 1520 H Street, N. W. Washington, D. C.	5
NASA High Speed Flight Station Edwards Field, Calif.	
Attn: Technical Library	1
Aerospace Corporation El Segundo, Calif. Attn: Technical Library	l
NASA Langley Research Center Langley Field, Va. Attn: Librarian	2
NASA Ames Research Center Moffett Field, Calif. Attn: Librarian	2

3

NASA Lewis Research Center 21000 Brookpark Rd. Cleveland, Ohio Attn: Chief, Propulsion Aerodynamics Div. 1 Attn: Mr. George Mandel, Chief, Library 2 Office of the Assistant Secretary of Defense (R&D) Room 3E1041, The Pentagon Washington 25, D. C. Attn: Library (Technical) 1 Research and Development Board Room 3D1041, The Pentagon Washington 25, D. C. Attn: Library 2 ASTIA Arlington Hall Station Arlington 12, Va. 10 Attn: TIPDR Commander, NMC Point Mugu, Calif. Attn: Technical Library 1 Commanding General Aberdeen Proving Ground, Md. Attn: Technical Info. Br. 1 Attn: Ballistics Research Laboratories 1 Lockheed Aircraft Corp. Missiles and Space Div. P. 0. Box 504 Sunnyvale, Calif. Attn: Technical Library 1 Lockheed Aircraft Corp. Research Lab. Palo Alto, California Attn: Technical Library 1 Oak Ridge National Laboratory P. 0. Box E Oak Ridge, Tenn. Attn: Technical Library 1

Copies

.

	Copies
Atomic Energy Commission Engineering Development Branch Division of Reactor Development Headquarters, US AEC Washington 25, D. C. Attn: Technical Library	1
University of California Lawrence Radiation Laboratory P. O. Box 808 Livermore, Calif. Attn: Technical Library	1
Polytechnic Institute of Brooklyn 527 Atlantic Avenue Freeport, N. Y. Attn: Dr. Paul A. Libby	1
General Applied Sciences Laboratories, Inc. Merrick and Stewart Avenues East Meadow, New York Attn: Technical Library	1
Jet Propulsion Laboratory 4800 Oak Grove Drive Pasadena 3, California Attn: I. R. Kowlan, Chief, Reports Group	2
Los Alamos Scientific Laboratory P. O. Box 1663 Los Alamos, New Mexico Attn: Technical Library	1
Institute for Defense Analyses Advanced Research Projects Agency Washington 25, D. C. Attn: Mr. W. G. May General Sciences Branch	1
Kaman Aircraft Corporation Nuclear Division Colorado Springs, Colorado Attn: Technical Library	1
U. S. Atomic Energy Commission P. O. Box 62 Oak Ridge, Tennessee Attn: TRI:NLP:ATD:10-7	1

٠

	Copies
Sandia Corporation Livermore Laboratory P. O. Box 969 Livermore, Calif.	1
United Aircraft Corporation Research Laboratories East Hartford 8, Conn. Attn: Technical Library	1
Sandia Corporation Sandia Base Albuquerque, N. Mexico Attn: Technical Library	1
Defense Metals Information Center Battelle Memorial Institute 505 King Avenue Columbus 1, Ohio	1
Commanding General Army Rocket and Guided Missile Agency Redstone Arsenal, Alabama Attn: Technical Library	1
Boeing Airplane Company Seattle, Washington Attn: Technical Library	2
National Bureau of Standards Washington 25, D. C. Attn: Technical Library	2
Cornell Aeronautical Laboratory 4455 Genesee Street Buffalo, N. Y. Attn: Technical Library	1
Defense Systems Division General Motors Corp. Santa Barbara, Calif. Attn: Technical Library	1

6

•

.

.

.

•.

	University of Maryland	
	College Park, Maryland	
	Attn: Dr. Thomas Wilkerson	1
	Attn: Physics Department	- 2
	Attn: Institute for Fluid Dynamics	2
	Loyola University of the South	
	New Orleans, Louisiana	
	Attn: Physics Department	1
,	Tulane University	
	New Orleans, Louisiana	
	Attn: Physics Department	1
	Attn: Mechanical Engineering Dept.	ī
	Louisiana State University	
	New Orleans, Louisiana	
	Attn: Physics Department	1

			118	BLIOGRAPHIC	INFORMATION			
	DESCRI	PTORS		CODES			DESCRIPTORS	CODES
SOURCE	NOL technical re	port		NOLTR	SECURITY CLASSIF	ICATION	Unclassified - 21	n¢21
REPORT NUMBER	63-33			630/33	CIRCULATION LIMI	TATION		
REPORT DATE	5 May 1963			¢563	CIRCULATION LIMI	TATION		
					BIBLIOGRAPHIC (SUPPL., VOL., ET			
			SL	IBJECT ANALY	YSIS OF REPORT			
	DESCRIPTORS	CODES		DESCRIPTORS		CODES	DESCRIPTORS	CODES
Electroni	υ	ELEC	Arc-heate	đ		ARCE		
Excitatio	ų	EXCI	Test faci	lities		TESF		
Ionizatio	u	IONI	Shock tub	65		SHTU		
Shockwave	Ø	SHWV	Wind tunne	els		NIM		
Shock		SHOC	Wind tunne	els (desi	ign)	DUN TW		
Proposal		PRSL	Hypervelo	ci ty		НҮРИ		
Study		STUY	Hypersonic	U		НҮРК		
Collision	L.	COLS	Measuremen	nt		MEAU		
Processes		METD	Plans			PLAG		
Gases		GASE						
Alkali met	tal	ALKI						
Vapor		VAPO						

.

٠

PRMC-NOL-3878/28 (5-42)

CATALOGING INFORMATION FOR LIBRARY USE

.

:	Testing faoilities - Maval Ordmanoe Maval Ordmanoe Isbook tubes, Hypersonic Vapors, Alkali metal Gass - Shock waves Title Shock waves Fiss Froject Project	Testing faoilities - Naval Naval Ordaanoe Crabersonic Vapors Hypersonic Vapors Vapors Alkali metal Gases - Sheck waves Title Finite Froject Froject
	Maral Ordnance Laboratory, White Oak, Md. (NOL teohnical report 63-33) A PROPOSAL FOR THE STOUN OF COLLESTONAL PRO- CESSES LEADING TO ELECTRONIC EXCITATION AND CONTLATION BEHIND SECCRAVES, by Ernst H. UNILLAR. 5 May 1963. 11p. 111us. (Ballis- tics research report 93). NOL task FR-64. Winkler. 5 May 1963. 11p. UNCLASSIFIED III is proposed to utilize alkali metal va- pors to study the fundamental collisional pro- cesses leading to ionization and electronio excitation in gases behind strong shockwaves. The advantages which result from the substitu- tion of alkali metal value arc-boated test facility is described.	Mayal Ordnance Laboratory, White Oak, Md. Nucl teobnical report 63-33 A PROPOSAL FOR THE STUDY OF COLLISIONAL PRO- CESSES LEADING TO ELECTRONIC EXCITATION AND HONEZETON BEHIND SECKWAVES, by Ernst H. Winkler. 5 May 1963. 11p. 411us. (Ballis- tics research report 93). NUL task FR-64. It is proposed to utilize alkali metal va- pors to study the fundamental collisional pro- cesses leading to ionization and electronic excitation in fases behind strong shockwaves. The advantages which result from the substitu- tion of alkali metal vapors for ordinary gase are presented and a suitable arc-heated test facility is described.
	Testing recilities - recilities - Naval Ordnanco Uaboratory Shook tubes, Hypersonic Hypersonic Alkali metal Gases - Shock waves Title Froject V. Project	Testing faoilities - faoilities - Naval Ordmanoe Nypersonic Tabortory Nypersonic Vaporto Alkali metal Gases - Sbock waves Title I. ginkler Froject V. Project
· · · ·	Naval Ordnance Laboratory, White Oak, Md. (NOL technical report 63-33) A PROPOSAL FOR THE STUDY OF COLLISIONAL PRO- CASSES LEADING TO ELECTRONIC EXCITATION AND TONIZATION REHIND SHOCKWAYES, by Ernst H. TONIZATION REHIND SHOCKWAYES, by Ernst H. TONIZATION AND TONIZATION AND SHOCKWAYES, by Ernst H. 100 research report 93). NOL task FR-64. 101 research report 93). NOL task FR-64. 102 research report 93). NOL task FR-64. 103 research report 93). NOL task FR-64. 104 as a proposed to utilize alkali metal va- port to study the fundamental collisional pro- dentia for initation and electronico excitation in fases behind strong shockwaves. The advantages which result from the substitu- tion of alkali metal vapors for ordinary fases I are presented and a suitable arc-beated test facility is described.	Mayal Ordnance Laboratory, White Oak, Md. (NoL technical report 63-33) (NoL technical report 63-33) CASAS READING TO ELECTRONT OF COLLISIONAL PRO- CASASS LEADING TO RECORMAYES, by Ernat PRO- IONIZATION BELIND SFICKWAYES, by Ernat R. Minler. 5 May 1963. 11p. 111us. (Ballis- 2 Winkler. 5 May 1963. 11p. 111us. (Ballis- tics research report 93). NOL task FR-04. It is proposed to utilize alkali metal wa- pore to study the fundamental collisional pro- cesses leading to ionization and electronic cesses leading to ionization and electronic tion of alkali metal wapors for ordinary fases rion for ity is desoribed.

.

•