

UNCLASSIFIED

AD . 4 2 3 9 6 3

DEFENSE DOCUMENTATION CENTER

FOR

SCIENTIFIC AND TECHNICAL INFORMATION

CAMERON STATION, ALEXANDRIA, VIRGINIA




UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

Report No. RF-TR-63-23

COPY **19**



THE EFFECTS OF BASE BLEED AND SUSTAINER ROCKET
NOZZLE DIAMETER AND LOCATION ON THE BASE DRAG
OF A BODY OF REVOLUTION WITH CONCENTRIC BOOST
AND SUSTAINER ROCKET NOZZLES

15 July 1963



U S ARMY MISSILE COMMAND
REDSTONE ARSENAL, ALABAMA

Handwritten or stamped text, possibly a date or reference number, including "1963" and "19".

DDC Availability Notice

**Qualified requesters may obtain copies of this report from the
Defense Documentation Center for Scientific and Technical Information,
Cameron Station, Alexandria, Virginia, 22314.**

Destruction Notice

Destroy; do not return.

15 July 1963

Report No. RF-TR-63-23

THE EFFECTS OF BASE BLEED AND SUSTAINER ROCKET
NOZZLE DIAMETER AND LOCATION ON THE BASE DRAG
OF A BODY OF REVOLUTION WITH CONCENTRIC BOOST
AND SUSTAINER ROCKET NOZZLES

By

Charles E. Brazzel

AMC Management Structure Code No. 5210, 11, 148

Aerodynamics Branch
Advanced Systems Laboratory
Future Missile Systems Division
Directorate of Research and Development
U.S. Army Missile Command
Redstone Arsenal, Alabama

ABSTRACT

A concentric arrangement of boost and sustainer rocket nozzles has been investigated to determine the effects of base bleed and the effects of sustainer nozzle diameter and relative longitudinal position on the base drag of the body during sustainer operation. The results of the investigation indicate that the jet-on base drag of a body can be significantly reduced by the use of base bleed and nozzle arrangement, and that the jet-on base drag is a function of the jet thrust.

The data presented are based on the results of tests in the Aberdeen Ballistic Research Laboratories 13 by 15 inch supersonic wind tunnel at Mach numbers of 2.0 and 2.5. The model tested had sustainer nozzle-to-base diameter ratios of 0.10, 0.20, and 0.30, and boost nozzle-to-base diameter ratio of 0.80. The sustainer nozzle was tested at longitudinal positions between 0.60 calibers aft to 0.98 calibers forward of the base.

TABLE OF CONTENTS

	Page
I. INTRODUCTION	1
II. APPARATUS AND PROCEDURE	1
III. RESULTS	
A. Effect of Diameter Ratio and Mach Number	3
B. Effect of Base Bleed	4
C. Effect of Longitudinal Position	4
IV. CONCLUSIONS	5

LIST OF ILLUSTRATIONS

Figure		Page
1	Model Details	7
2	Effects of Sustainer Nozzle Position on Base Drag	10
3	Effects of Sustainer Nozzle Position on Base Drag	12
4	Effects of Sustainer Nozzle Position on Base Drag	14
5	Effects of Base Bleed on Base Drag at $M = 2.5$	16
6	Effects of Mach Number and Sustainer Nozzle Diameter Ratio on Base Pressure Ratio	20
7	Effects of Mach Number and Sustainer Nozzle Diameter Ratio on Base Pressure Ratio	21
8	Effects of Mach Number on Base Pressure Ratio	22
9	Effects of Bleed on Base Pressure Distribution	23
10	Variation in Bleed Mass Flow Ratio with Sustainer Jet Chamber Pressure	24
11	Increase in Base Pressure Ratio Due to Base Bleed	25
12	Increase in Base Pressure Ratio Due to Aft Nozzle Position	26
13	Incremental Change in Base Pressure Ratio Due to Sustainer Nozzle Position	27
14	Effect of Sustainer Nozzle Diameter Ratio on Local Pressure Distribution	28

LIST OF SYMBOLS

C_{DB}	Base drag coefficient based on integration of pressure distributions over the total base area excluding the sustainer nozzle exit area and referenced to the total base area
C_T	Thrust coefficient = Thrust/ q_{∞} x Reference Area
d_n	Sustainer nozzle exit diameter
D_B	Body base diameter
M	Mach number
\dot{m}_b	Bleed mass flow
\dot{m}_j	Sustainer nozzle mass flow
\dot{m}_{∞}	Body stream-tube mass flow
p	Local static pressure
p_b	Average base pressure, integrated over total base area excluding sustainer nozzle exit area
p_c	Sustainer nozzle chamber pressure
p_j	Sustainer nozzle exit static pressure
p_{∞}	Free-stream static pressure
q_{∞}	Free-stream dynamic pressure
V	Velocity
X	Distance from base of model
X_n	Distance from base of model to base of sustainer nozzle (Forward is positive.)

I. INTRODUCTION

Several potential applications exist in land combat and air defense weapons systems for boost-sustain propulsion. One of the advantages for this type of propulsion lies in the increase in missile performance arising from energy management considerations. As a part of the overall problem, it is necessary to investigate techniques for minimizing missile base drag. Current methods allow prediction and optimization of body forebody and friction drag with a reasonable degree of accuracy; however, methods are not available for reliably predicting the base drag of a body with an operating jet. The jet-on base drag of a body can be as high as 50 percent of the total drag; therefore techniques for predicting the jet-on base drag are needed for proper design and evaluation of the aerodynamic-propulsion configuration of missiles during sustainer operation.

This report presents the results of the second phase of a study on base drag reduction conducted as a part of SR Project, Base Drag Reduction, Code 5210.11.148. A body with concentric boost and sustainer rocket nozzles has been studied to determine the effects of base bleed, and the effects of sustainer nozzle diameter and position on the body base drag. The results of the first phase of the study have been presented in Reference 1.

The data presented in this report are based on the results of wind tunnel tests at Mach numbers 2.0 and 2.5. Parameters varied during the tests were Mach number, base bleed, nozzle diameter, nozzle position, and sustainer nozzle chamber pressure. The boost nozzle was inactive and the sustainer jet was simulated with air. The configuration tested was a body of revolution with an ogive nose and a cylindrical afterbody.

II. APPARATUS AND PROCEDURE

The test was conducted in Tunnel No. 1 of the Ballistic Research Laboratories, Aberdeen Proving Grounds, Maryland. That facility is a continuous flow, supersonic wind tunnel capable of operating at Mach numbers from 1.2 to 5.0, and has a test section 13 inches wide by 15 inches high.

The model tested was a body of revolution with a 4-caliber, tangent ogive nose, and a 2-caliber cylindrical afterbody. It was mounted from the tunnel ceiling at 0° angle of attack by a rigid strut containing the instrumentation and air supply lines. A sustainer rocket nozzle, concentric to a boost rocket nozzle, could be tested at any of ten longitudinal

positions between -.60 and +.98 calibers from the base of the body. The sustainer nozzles had exit diameters of 0.10, 0.20, and 0.30 calibers and were designed for an exit Mach number of 2.7 ($p_j/p_c = 0.0427$). The sustainer jet was simulated with dry air, and the boost nozzle was inactive. During the bleed runs, air was bled from the sustainer chamber to the boost nozzle chamber through orifices in the sustainer nozzle chamber wall. The amount of bleed air was varied by varying the size and number of bleed orifices. Figure 1 presents sketches of the model installation and geometry.

The base of the model was instrumented with pressure orifices along the body just forward of the base, on the base annulus, and along the interior of the boost nozzle as shown in Figure 1. Pressures at the orifices were measured with pressure transducers. Sustainer air supply pressure (p_c) was measured at an orifice in the settling chamber upstream of the nozzle throat.

During each run the sustainer supply pressure was varied while holding constant the test section Mach number, test section static pressure, sustainer nozzle position, and ratio of bleed to sustainer jet mass flow. Data recorded were test section stagnation pressure and temperature, sustainer air supply pressure, model orifice pressures, and transducer reference pressure. Accuracies of the data obtained are the following:

Mach number	± .002
Local model pressures	± .0125 psi
Sustainer supply pressure	
0 - 15 psi range	± .030 psi
0 - 100 psi range	± .200 psi
0 - 320 psi range	± .600 psi

The model local pressures were reduced to pressure coefficient and pressure ratio form, and the base drag coefficients were computed by integrating the base pressure distributions where:

$$C_{DB} = \frac{1}{S_B} \sum a_i C_{pi}$$

and S_B = Total base area

a_i = Incremental area

C_{pi} = Local pressure coefficient

A more detailed discussion of the test apparatus and test procedure as well as the basic data from the test is presented in Reference 2.

III. RESULTS

The wind tunnel test results from Reference 2 have been analyzed to determine the effects of the various test parameters on base drag. The analysis is limited to values of sustainer chamber pressures sufficient to completely fill the sustainer nozzle. Although the test configuration has an inactive boost rocket nozzle concentric to an active sustainer rocket nozzle, or in effect an open base, the data are comparable to data for closed base configurations except for conditions where the sustainer jet impinged on the boost nozzle wall. Subsequent references to the nozzle and jet will refer to the sustainer nozzle and jet.

Figures 2 through 5 present the basic test results and show the effects of sustainer nozzle diameter and position and the effects of base bleed on base drag as a function of jet chamber to free-stream static pressure ratio. These data exhibit a characteristic variation of base drag with jet pressure ratio which is discussed in detail and related to base wake flow in Reference 3.

A. Effect of Diameter Ratio and Mach Number

Analysis of the data for the configuration with the nozzle at the model base ($X_n/D_B = 0.0$) shows a dependence of base pressure on thrust level and jet momentum ratio which are related. Figure 6 presents base pressure ratio as a function of thrust coefficient and Figure 7 presents base pressure ratio as a function of jet momentum ratio for nozzle diameter ratios of 0.10, 0.20, and 0.30 at Mach numbers of 2.0 and 2.5. These data indicate that base pressure ratio is independent of nozzle diameter, jet pressure ratio, and free-stream conditions except for their relative inputs to the thrust coefficient or momentum ratio. Reference 1 presents data from the first series of tests of the model at Mach numbers of 2.0, 2.5, 3.0, and 3.5 for a nozzle diameter ratio of 0.24. Due to instrumentation difficulties, the accuracy of the data from Reference 1 does not approach the accuracy of the present data; however, the data are useful to indicate trends and are presented in Figure 8 as a function of thrust coefficient to illustrate the independence of jet-on base pressure on free-stream Mach number except for its input to thrust coefficient. The relationship between jet-on base pressure and thrust coefficient and momentum ratio correlates well with experimental data from sources for bodies with supersonic jets.

B. Effect of Base Bleed

Air was bled into the boost nozzle combustion chamber through orifices in the sustainer nozzle combustion chamber wall. In most cases, the bleed mass flow was sufficient to choke the boost nozzle throat. Figure 9 presents boost nozzle pressure distributions for various bleed ratios with the 0.20 diameter ratio sustainer nozzle. These data illustrate that the boost nozzle was choked for all bleed ratios except the .015 with the 0.20 diameter ratio nozzle, and provide data for convenient determination of the actual ratio of bleed mass flow to sustainer mass flow for conditions where the boost nozzle was choked. Figure 10 presents calculated values of bleed mass flow ratios based on the pressure distributions of Figure 9. For values of bleed mass flow not sufficient to choke the boost nozzle throat, nominal values are given based on orifice area ratios.

Bleeding gases into the base area increases the base pressure as a function of the bleed mass. The incremental increase in base pressure ratio due to base bleed is presented in Figure 11 as a function of the ratio of bleed mass flow to body stream-tube mass flow. The apparent Mach number effect can be removed by dividing the mass flow ratio by the free-stream velocity. Since the bleed velocity is believed to be constant, the dependence of the effect of base bleed on base pressure ratio on bleed momentum ratio is indicated. The bleed velocity at the base could not be determined from the available data, therefore the bleed momentum ratio could not be calculated. However, since the base pressure ratio without base bleed is a function of jet momentum ratio, it is not illogical to believe that the effects of base bleed are also a function of bleed momentum ratio. The boost nozzle produces some thrust due to bleed, however the effects on base pressure are far greater than the effects of bleed thrust alone.

C. Effect of Longitudinal Position

Extension of the sustainer nozzle aft of the base of the body induces an incremental increase in base pressure which varies almost linearly with nozzle position but which does not vary with nozzle diameter of jet pressure ratio. An effect of free-stream Mach number is also indicated; however, sufficient data are not available to determine the Mach number effects. Figure 12 presents the incremental increase in base pressure ratio as a function of aft nozzle position. It is anticipated that the base pressure would continue to increase with aft nozzle position until the sustainer nozzle approached the position of the jet-off trailing shock ($X_n/D_B \approx -1.20$). Since the aft nozzle positions induce an increase in base pressure which is independent of nozzle diameter

and jet pressure ratio, the base pressure cannot be correlated on a momentum ratio or a thrust coefficient basis.

Movement of the sustainer nozzle forward into the base cavity induces a corresponding decrease in base pressure until a position is reached where the sustainer jet impinges on the boost nozzle. With jet impingement, the static pressure on the boost nozzle aft of impingement is increased due to a pressure rise across an oblique shock produced by impingement. Further movement of the sustainer into the base cavity increases the area of the boost nozzle affected and also increases the angle of impingement which in turn causes an increase in pressure rise across the oblique shock. Therefore movement of the sustainer nozzle forward after the jet has impinged causes an increase in base pressure. This effect is discussed in more detail in Reference 1. It is interesting to note that after the jet has impinged on the boost nozzle base pressure again becomes a function of momentum ratio and thrust coefficient.

Figure 13 illustrates the incremental change in base pressure ratio with nozzle position for the $0.20 d_n/D_B$ nozzle at $M = 2.5$ for several jet pressure ratios.

Reference 1 illustrated that, for a given nozzle position, the point of jet impingement was independent of jet pressure ratio and external conditions. Figure 14 also illustrates that the point of jet impingement is independent of nozzle diameter.

IV. CONCLUSIONS


The following conclusions can be made, based on analysis of the test data:

1. The base pressure ratio, for bodies with jets coplaner to the base, can be expressed as a function of either jet momentum ratio or thrust coefficient and is independent of nozzle diameter, jet pressure ratio, and free-stream conditions except for their respective inputs to the momentum ratio and thrust coefficient.
2. The increase in base pressure due to gases bled into the base area can be expressed as a function of the bleed mass momentum ratio and is independent of bleed area or free-stream conditions except for their respective inputs to the momentum ratio.
3. Extending the nozzle aft of the body base causes an increase in base pressure which is a function of the amount of extension and free-stream Mach number but is independent of nozzle diameter and jet pressure ratio.

4. Moving the nozzle forward into the body can increase the base pressure due to impingement of the jet on the body internal surfaces. The amount is a function of jet conditions and geometry but is independent of environmental conditions.


It is recommended that future phases of the base drag reduction study be conducted to determine the effects on jet-on base drag of the following:

1. Effects of base bleed over wide Mach number range.
2. Effects of aft nozzle extensions over wide Mach number range and for further aft extensions.
3. Effects of jet Mach number and expansion angle.
4. Effects of jet temperature and physical composition.
5. Effects of afterbody geometry.
6. Potential heating problems associated with flow impingement on the boost nozzle.




a. Model Installation

Figure 1. Model Details



b. Boost Nozzle Geometry


Figure 1. Continued




d_n/D_B	d_n	A	B	C	D	R
0.10	0.250	0.27	0.140	0.163	0.623	0.070
0.20	0.500	0.52	0.280	0.327	0.623	0.140
0.30	0.750	0.79	0.420	0.490	0.623	0.210

c. Sustainer Nozzle Geometry

Figure 1. Concluded




a. Aft Nozzle Positions
 Figure 2. Effects of Sustainer Nozzle Position on Base Drag. $d_n/D_B = 0.10$; $M = 2.5$




b. Forward Nozzle Positions

Figure 2. Continued




a. Aft Nozzle Positions

Figure 3. Effects of Sustainer Nozzle Position on Base Drag. $d_n/DB = 0.20$; $M = 2.5$




b. Forward Nozzle Positions

Figure 3. Continued




a. Aft Nozzle Positions
 Figure 4. Effects of Sustainer Nozzle Position on Base Drag. $d_n/D_B = 0.30$; $M = 2.5$




b. Forward Nozzle Positions

Figure 4. Continued




a. $d_n/D_B = 0.10$; $X_n/D_B = 0.0$

Figure 5. Effects of Base Bleed on Base Drag at $M = 2.5$




b. $d_n/D_B = 0.20$; $X_n/D_B = 0.0$

Figure 5. Continued




c. $d_N/D_B = 0.20$; $X_N/D_B = -0.40$

Figure 5. Continued



d. $d_N/D_B = 0.30$; $X_N/D_B = 0.00$

Figure 5. Continued



$X_n/D_B = 0.0$

Figure 6. Effects of Mach Number and Sustainer Nozzle Diameter Ratio on Base Pressure Ratio.





Figure 7. Effects of Mach Number and Sustainer Nozzle Diameter Ratio on Base Pressure Ratio.



$$x_n/D_B = 0.0; \quad d_n/D_B = 0.24$$

Figure 8. Effects of Mach Number on Base Pressure Ratio





Figure 9. Effects of Bleed on Base Pressure Distribution.
 $M = 2.5$; $d_n/D_B = .20$; $X_n/D_B = 0.00$




Figure 10. Variation in Bleed Mass Flow Ratio
 With Sustainer Jet Chamber Pressure
 $M = 2.5$; $d_n/D_B = .20$; $X_n/D_B = 0.00$




Figure 11. Increase in Base Pressure Ratio Due to Base Bleed.




Figure 12. Increase in Base Pressure Ratio Due To Aft Nozzle Position.




Figure 13. Incremental Change in Base Pressure Ratio Due to Sustainer Nozzle Position
 $M = 2.5$; $d_n/D_B = 0.20$




Figure 14. Effect of Sustainer Nozzle Diameter Ratio on Local Pressure Distribution.
 $X_n/D_B = .8245$; $M = 2.5$


REFERENCES


1. Brazzel, Charles E., "The Effects on Base Drag of Relative Longitudinal Arrangement of Concentric Boost and Sustainer Nozzles", AMICOM Report No. RF-TR-63-19, April 1963.
2. Blackwell, Kenneth L., "Some Effects of Nozzle Diameter and Position on Base Drag for Two Concentric Nozzles at Supersonic Mach Numbers", AMICOM Report No. RE-TM-63-25, 17 June 1963.
3. Reid, J., and Hastings, R. C., "The Effect of a Central Jet on the Base Pressure of a Cylindrical Afterbody in a Supersonic Stream", RAE Report No. AERO 2621, December 1959.

15 July 1963

Report No. RF-TR-63-23

APPROVED


JAMES H. HENDERSON
Chief, Analysis Section


RAYMOND A. DEEP
Chief, Aerodynamics Branch


WILLIAM C. MCCORKLE, JR.
Director, Adv Sys Lab, FMSD

DISTRIBUTION

U. S. Army Missile Command Distribution List A for Technical Reports (11 March 1963)	1-103	Applied Physics Laboratory The Johns Hopkins University Attn: Mr. G. L. Seelstad 8621 Georgia Avenue Silver Spring, Maryland	140
Director of Defense Research and Engineering (OSD) Attn: Tech Library Room 3C128 The Pentagon Washington 25, D. C.	104	Autonetics, A Division of North American Aviation, Inc. 9150 E. Imperial Highway Downey, California	141
Commanding General U. S. Army Materiel Command Attn: AMCRD-RS-PE-Bal Res & Devel Directorate Washington 25, D. C.	105	AVCO Manufacturing Corp. Advance Devel Div Res Lab 2385 Revere Beach Parkway Everett 49, Mass.	142
Commanding General Picatinny Arsenal Attn: ORDBB-VC 3, Mr. A. A. Loeb Dover, New Jersey	106	Armour Research Foundation Illinois Institute of Technology Center Chicago, Illinois	143
Commanding Officer Frankford Arsenal Attn: 0270 - Library Philadelphia 37, Pennsylvania	107	Aerojet-General Corp Attn: Tech Info Office Sacramento Plants (Liquid & Solid Rocket Motors) P. O. Box 1947 Sacramento, California	144
Commanding Officer Ballistic Research Labs Attn: AMXBR-E Aberdeen, Maryland	108, 109	American Bosch Arm Corp. Attn: Tech Library Roosevelt Field Garden City, New York	145
Chief, Bureau of Naval Weapons Attn: DIS-33 Department of the Navy Washington 25, D. C.	110-112	Bell Aircraft Corp. P. O. Box 1 Attn: Librarian Buffalo 5, New York	146
Naval Supersonic Laboratory Massachusetts Institute of Technology Attn: Mr. Frank Durgin 560 Memorial Drive Cambridge 39, Mass.	113	Bell Telephone Labs, Inc. Attn: Director of Military Systems Development Whippany, New Jersey	147
Chief of Naval Material Attn: Code M422 Department of the Navy Washington 25, D. C.	114	Bendix Corporation Attn: Reports Library Research Labs Division P. O. Box 5115 Detroit 35, Michigan	148
AFSWC (SWK, SWUND) Kirtland Air Force Base New Mexico	115	Boeing Company Attn: Library Unit Chief P. O. Box 3707 Seattle 24, Washington	149, 150
Commanding Officer and Director Attn: Aerodynamics Lab David W. Taylor Model Basin Washington 7, D. C.	116	Bendix Mishawaka Division Attn: Tech Librarian Bendix Corporation 400 South Beiger Street Mishawaka, Indiana	151
Director, National Aeronautics and Space Administration Attn: Technical Library Ames Research Center Moffett Field, California	117-121	Batelle Memorial Institute 505 King Avenue Columbus 1, Ohio	152
Director, National Aeronautics and Space Administration Attn: Technical Library Langley Research Center Langley Field, Virginia	122-126	Bendix Corporation Bendix Systems Division Ann Arbor, Michigan	153
Director, National Aeronautics and Space Administration Attn: Technical Library Lewis Research Center Cleveland, Ohio	127-131	Beech Aircraft Corporation Wichita 1, Kansas	154
Director, National Aeronautics and Space Administration Attn: W. Dahm E. Linsley J. Sims Marshall Space Flight Center Redstone Arsenal, Alabama	132-136	CONVAIR, A Division of General Dynamics Corp. P. O. Box 1950 San Diego 12, California	155
Director, National Bureau of Standards Attn: G. B. Schubauer 232 Dynamometer Bldg. Washington 25, D. C.	137	Cornell Aeronautical Lab, Inc. Attn: Librarian Buffalo, New York	156
U. S. Atomic Energy Commission Tech Info Service Extension P. O. Box 62 Oak Ridge, Tennessee	138	CONVAIR, A Division of General Dynamics Corp. Attn: Engineering Librarian Fort Worth 1, Texas	157
National Science Foundation Attn: Dr. R. Seeger Washington 25, D. C.	139	Chance Vought Aircraft, Inc. P. O. Box 5807 Dallas, Texas	158, 159
		CONVAIR, A Division of General Dynamics Corp. Attn: Division Library Pomona, California	160
		Chrysler Corporation Attn: Tech Library Missile Operations P. O. Box 2628 Detroit 31, Michigan	161

DISTRIBUTION - Continued

<p>Convair-Astronautics, Division of General Dynamics Corp. Attn: Chief Librarian San Diego 12, California</p>	162	<p>The Martin Company Attn: Research Library Denver Division P.O. Box 179 Denver 1, Colorado</p>	181
<p>Douglas Aircraft Company Attn: Chief Engineer, Miss & Space Systems 3000 Ocean Park Blvd Santa Monica, California</p>	163	<p>The Mitre Corp. 244 Wood Street Lixington 73, Mass.</p>	182
<p>Douglas Aircraft Company Attn: R. L. Coleman, Aero Sec. 1820 Statesville Ave. Charlotte, N.C.</p>	164	<p>Marquardt Aircraft Co. 16555 Saticoy Street P.O. Box 2013 South Annex Van Nuys, California</p>	183
<p>Documentation Inc. Man-Machine Info Center 2521 Connecticut Ave., N.W. Washington 8, D.C.</p>	165	<p>Northrop Corporation Attn: Tech Information Norair Division 1001 East Broadway Hawthorne, California</p>	184
<p>Electronics Defense Lab Sylvania Electric Products, Inc. P.O. Box 205 Mountain View, California</p>	166	<p>North American Aviation, Inc. Attn: Msl Devel Div. 12214 Lakewood Blvd. Downey, California</p>	185
<p>Fairchild Engine and Airplane Corp. Fairchild Astronics Division Wyandanch, Long Island New York</p>	167	<p>Nortronics, A Division of Northrop Aircraft, Inc. Attn: Tech Info Center 222 North Prairie Ave. Hawthorne, California</p>	186
<p>Fairchild Stratos Corp. Aircraft-Missiles Division Attn: Sarah M. Thomas Library Hagerstown, Maryland</p>	168	<p>Raytheon Company Missiles Systems Division Bristol, Tennessee</p>	187
<p>Goodyear Aircraft Corp. Akron 15, Ohio</p>	169	<p>Reeves Instrument Corp. Ease Gate Blvd. Garden City, Long Island, New York</p>	188
<p>General Electric Company Aircraft Products Dept Lakeside Avenue Burlington, Vermont</p>	170	<p>Raytheon Company Attn: Librarian Missile Systems Division Bedford, Massachusetts</p>	189
<p>Grumman Aircraft Engineering Corp. Attn: Director, Engineering Library, Plant 5 Bethpage, Long Island, New York</p>	171	<p>Republic Aviation Corp. Attn: Manager, Contracts and Liaison Guided Missiles Division Mineola, Long Island, New York</p>	190
<p>General Electric Company Attn: Tech Info Svcs Tech Military Planning Operation Box 535 Santa Barbara, California</p>	172	<p>Radio Corp. of America Msl & Surface Radar Dept. Moorestown, New Jersey</p>	191
<p>General Electric Company Msl & Ord Systems Dept. 3198 Chestnut Street Philadelphia, Pennsylvania</p>	173	<p>Raytheon Company Attn: Librarian Andover Plant Haverhill Street Andover, Massachusetts</p>	192
<p>General Electric Company FPD Tech Info Center Mail Stop F-22 Cincinnati 15, Ohio</p>	174	<p>Radioplane, A Division of Northrop Corp. P.O. Box 511 Van Nuys, California</p>	193
<p>Hughes Aircraft Company Attn: Documents Group Tech Library Florence Ave. at Teale St. Culver City, California</p>	175	<p>Ryan Aeronautical Company Attn: Chief Librarian Lindbergh Field San Diego 12, California</p>	194
<p>Institute for Defense Analyses Res & Eng Support Division 1825 Connecticut Ave., N.W. Washington, D.C.</p>	176	<p>Republic Aviation Corp. Military Contract Dept. Farmingdale, Long Island, New York</p>	195
<p>Lockheed Aircraft Corp. Attn: Tech Info Center Msls 1 Space Division P.O. Box 504 Sunnydale, California</p>	177	<p>Sylvania Electric Products, Inc. Waltham Laboratory Library Attn: Librarian 100 First Avenue Waltham 54, Massachusetts</p>	196
<p>Librascope, Inc. 808 Western Avenue Glendale 1, California</p>	178	<p>Sperry Utah Engineering Laboratory 322 North 21st Street, West Salt Lake City 16, Utah</p>	197
<p>McDonnell Aircraft Corp. P.O. Box 516 St. Louis 3, Missouri</p>	179	<p>System Development Corp. Attn: Librarian 2500 Colorado Avenue Santa Monica, California</p>	198
<p>The Martin Company Attn: Librarian Orlando Division Orlando, Florida</p>	180		

DISTRIBUTION - Continued

Sanders Associates, Inc. Document Library 95 Canal Street Nashua, New Hampshire	199	University of Illinois Attn: Prof. C.H. Fletcher Dept. of Aeronautical Eng. Attn: Dr. H.H. Korst Eng. Experimental Station Urbana, Illinois	221, 222
TEMCO Aircraft Corp. Attn: Engineering Library P.O. Box 6191 Dallas, Texas	200	American Institute of Aeronautics & Astronautics Attn: Library 2 East 64th Street New York 21, New York	223
United Aircraft Corp. Missile and Space Division 400 Main Street East Hartford 8, Conn.	201	The Johns Hopkins University Attn: Dr. L. Kosvaszmay Prof. F.H. Caluser, Jr. Dept. of Aeronautical Eng. Attn: Dr. S. Corrain Dept. of Mechanical Eng. Baltimore 17, Maryland	224-226
United Aircraft Corp. Research Department East Hartford 8, Conn.	202	Kansas State University Attn: Prof. W. Tripp Dept. of Mechanical Eng. Manhattan, Kansas	227
Vitro Laboratories Div of Vitro Corp. of America Attn: Librarian 14000 Georgia Avenue Silver Springs, Maryland	203	Lehigh University Attn: Dr. R. Emrich Physics Dept. Bethlehem, Pennsylvania	228
Wright Aeronautical Division Attn: Sales Dept (Fovt.) Curtiss-Wright Corporation Wood Ridge, New Jersey	204	University of Maryland Attn: Director, Institute of Fluid Dynamics & Applied Mathematics Attn: S.F. Shen, Dept. of Aeronautical Eng. College Park, Maryland	229, 230
Brown University Attn: Dr. R. Probstain, Graduate Div. of Applied Mathematics Attn: Prof. William Prager, Chairman, Physical Sciences Council Providence 12, Rhode Island	205, 206	University of Michigan Institute of Science & Technology Attn: Tech Documents Service Ann Arbor, Michigan	231
Catholic University of America Attn: Prof. K.F. Herzfeld Prof. M. Munk Department of Physics Washington 17, D.C.	207	Massachusetts Institute of Technology Attn: Prof. J.R. Markham Dept. of Aeronautical Eng. Cambridge 39, Mass.	232
Auburn University Attn: Dept. of Aerospace Eng. Auburn, Alabama	208	University of Michigan Attn: Dr. Arnold Kuethe Dept. of Aeronautical Eng. East Engineering Bldg. Ann Arbor, Michigan	233
University of Alabama Attn: Dept of Aerospace Eng University, Alabama	209	University of Minnesota Attn: Dept. of Aeronautical Eng. Dept. of Mechanical Eng., Div. of Thermodynamics Minneapolis 14, Minn.	234, 235
Case Institute of Technology Attn: Dr. G. Kuerni Cleveland, Ohio	210	Midwest Research Institute Attn: M. Goland, Director for Engineering Sciences 4049 Pennsylvania Kansas City 11, Missouri	236
California Institute of Technology Guggenheim Aeronautical Lab Attn: Prof. H.W. Leipman Pasadena 4, California	211	New York University Attn: Dr. R.W. Courant, Institute of Mathematics & Mechanics Attn: Dr. J.F. Ludloff, Dept. of Aeronautics 45 Fourth Street New York 53, N.Y.	237, 238
University of California at Berkeley Attn: Prof. S.A. Schaaf Berkeley, California	212	North Carolina State College Attn: Prof. R.M. Pinkerton Dept. of Engineering Raleigh, North Carolina	239
University of California at Los Angeles Attn: Dr. L.M. Boelter Dept. of Engineering Los Angeles 24, California	213	Ohio State University Attn: Prof. G.L. von Eschen Aeronautical Engr. Dept. Columbus, Ohio	240
University of Southern California Engineering Center Los Angeles 7, California	214	Pennsylvania State College Attn: Prof. M. Lessen Dept. of Aeronautical Engr. State College, Pennsylvania	241
University of Chicago Attn: Librarian Labs for Applied Sciences Museum of Science & Industry Chicago 37, Illinois	215	Polytechnic Institute of Brooklyn Attn: Dr. A. Ferri Aerodynamic Laboratory 527 Atlantic Avenue Freeport, New York	242
Cornell University Attn: Dr. W.R. Sears Graduate School of Aeronautical Engineering Ithaca, New York	216, 217		
Harvard University Attn: Prof. H.W. Emmons Dr. A. Bryson Prof. G.E. Carrier Dept. of Applied Physics & Engineering Science Cambridge 38, Massachusetts	218-220		

DISTRIBUTION - Concluded

<p>Princeton University Attn: Prof. S. Bogdonoff Prof. W. Hayes Forrestal Research Center Princeton, New Jersey</p>	<p>243, 244</p>	<p>Commanding General U. S. Army Materiel Command Attn: AMCRD-BE, Mr. Stetson Attn: AMCRD-BE-MI, Mr. Michaels Research & Development Directorate Washington 25, D. C.</p>	<p>263 264</p>
<p>Purdue University Lafayette, Indiana</p>	<p>245</p>	<p>AMSMI-R, Mr. McDaniel -RE, Mr. Hussey -RFS, Record Copies -RFSK, Mr. Deep -RFSK, Mr. Henderson -RFSK, Mr. Brazzel -RFSK, Mr. Johnson -RFSK, Mr. Street -RFSK, Mr. Greene -RFSK, Mr. Becht -RFSK, File Copy -RBL -RG -RK -RE -RFE, Mr. Garner -RT -RH -RL -RR -RS -RAP</p>	<p>265 266 267-269 270 271 272-292 293 294 295 296 297 298-302 303 304 305 306 307 308 309 310 311 312</p>
<p>Princeton University Forrestal Research Center Library Project SQUID Princeton, New Jersey</p>	<p>246</p>		
<p>The Rice Institute Attn: Prof. A. J. Chapman Dept. of Mechanical Eng. Houston, Texas</p>	<p>247</p>		
<p>Rensselaer Polytechnic Institute Attn: Dr. R. P. Harrington Aeronautics Department Troy, New York</p>	<p>248</p>		
<p>Rutgers University Attn: Prof. R. H. Page Dept. of Mechanical Engr. New Brunswick, N. J.</p>	<p>249</p>		
<p>Stanford Research Institute Attn: Acquisitions Documents Center Menlo Park, California</p>	<p>250</p>		
<p>University of Virginia Ordnance Research Laboratory P. O. Box 3366 University Station Charlottesville, Virginia</p>	<p>251</p>		
<p>University of Texas Defense Research Laboratory Attn: Mr. J. B. Oliphint P. O. Box 8029 University Station Austin 12, Texas</p>	<p>252, 253</p>		
<p>University of Washington Attn: Prof. R. E. Street Department of Aeronautical Engr. Attn: Prof. M. E. Childs Dept. of Mechanical Engr. Seattle 5, Washington</p>	<p>254, 255</p>		
<p>Prof. J. W. Beams University of Virginia Department of Physics Charlottesville, Virginia</p>	<p>256</p>		
<p>Dr. E. R. Benton University of Manchester, England</p>	<p>257</p>		
<p>Dr. R. Bolz Case Institute of Technology Cleveland, Ohio</p>	<p>258</p>		
<p>Mr. Gerald Hieser Systems Engineering Dept. General Electric Company 21 South 12th Street Room 514 Philadelphia, Pennsylvania</p>	<p>259</p>		
<p>Prof. J. O. Hirschfelder University of Wisconsin Department of Chemistry Madison, Wisconsin</p>	<p>260</p>		
<p>Prof. C. B. Millikan Director, Guggenheim Aeronautical Laboratory California Institute of Technology Pasadena 4, California</p>	<p>261</p>		
<p>Dr. Henry F. Hruby Dept. of Mechanical Engineering Tulane University New Orleans 18, La.</p>	<p>262</p>		