

UNCLASSIFIED

AD NUMBER
AD463360
NEW LIMITATION CHANGE
TO Approved for public release, distribution unlimited
FROM Distribution authorized to U.S. Gov't. agencies and their contractors; Administrative/Operational Use; 31 MAR 1965. Other requests shall be referred to U.S. Naval Ordnance Lab., White Oak, MD.
AUTHORITY
USNOL ltr, 12 Dec 1972

THIS PAGE IS UNCLASSIFIED

UNCLASSIFIED

AD 4 6 3 3 6 0

DEFENSE DOCUMENTATION CENTER

FOR

SCIENTIFIC AND TECHNICAL INFORMATION

CAMERON STATION ALEXANDRIA, VIRGINIA



UNCLASSIFIED

DISCLAIMER NOTICE

**THIS DOCUMENT IS BEST QUALITY
PRACTICABLE. THE COPY FURNISHED
TO DTIC CONTAINED A SIGNIFICANT
NUMBER OF PAGES WHICH DO NOT
REPRODUCE LEGIBLY.**

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

NOLTR 65-1

CATALOGED BY: DDC
AS AD 7
463360

INITIATION OF EXPLOSIVES BY
EXPLODING WIRES

463360

NOL

31 MARCH 1965

UNITED STATES NAVAL ORDNANCE LABORATORY, WHITE OAK, MARYLAND

NOLTR 65-1

DDC
RECEIVED
MAY 27 1965
DDC-IRA E

NOTICE

Requests for additional copies by Agencies of the Department of Defense, their contractors, and other Government agencies should be directed to:

**Defense Documentation Center (DDC)
Cameron Station
Alexandria, Virginia**

Department of Defense contractors who have established DDC services or have their 'need-to-know' certified by the cognizant military agency of their project or contract should also request copies from DDC.

All other persons and organizations should apply to:

**U.S. Department of Commerce
Clearinghouse for Federal Scientific and Technical Information
Sills Building
5285 Port Royal Road
Springfield, Virginia 22151**

INITIATION OF EXPLOSIVES BY EXPLODING WIRES

VI. Further Effects of Wire Material on the Initiation
of PETN by Exploding Wires

By

Howard S. Leopold

ABSTRACT: Silver, copper, and iron wires were investigated as possible bridgewire materials. The wires were exploded by a 1-microfarad capacitor charged to 2,000 Volts. Wire materials that give high peak powers are favorable for effecting detonation. Low boiling point, low heat of vaporization metals such as silver and copper permit greater energy transfer to an explosive than high boiling point, high heat of vaporization metals such as iron

PUBLISHED JUNE 1965

EXPLOSION DYNAMICS DIVISION
EXPLOSIONS RESEARCH DEPARTMENT
U. S. NAVAL ORDNANCE LABORATORY
WHITE OAK, MARYLAND

NOLTR 65-1

31 March 1965

INITIATION OF EXPLOSIVES BY EXPLODING WIRES
VI. FURTHER EFFECTS OF WIRE MATERIAL ON THE INITIATION OF PETN
BY EXPLODING WIRES

This report is Part VI of an investigation concerning the initiation of explosives by exploding wires. The work was performed under Task RUME-4E000/212-1/F008-08-11 PA 019, Analysis of Explosive Initiation.

The results should be of interest to personnel engaged in initiation research and design of exploding bridgewire ordnance systems.

The identification of commercial materials implies no criticism or endorsement of these products by the Naval Ordnance Laboratory.

R. E. ODENING
Captain, USN
Commander


C. J. ARONSON
By direction

CONTENTS

	Page
INTRODUCTION	1
ELECTRICAL CIRCUITRY	1
TEST PROCEDURE	2
EXPERIMENTAL RESULTS	2
DISCUSSION	3
CONCLUSIONS	6
REFERENCES	7

ILLUSTRATIONS

Figure	Title	Page
1	Test Circuit.	11
2	Current Waveforms for Various Lengths of 2-mil Diameter Silver Wire.	12
3	Current Waveforms for Various Lengths of 2-mil Diameter Copper Wire.	13
4	Current Waveforms for Various Lengths of 2-mil Diameter Iron Wire.	14
5	Voltage across Various Length Silver Wires .	15
6	Voltage across Various Length Copper Wires .	16
7	Voltage across Various Length Iron Wires . .	17
8	Resistance as a Function of Time for Various Lengths of 2-mil Silver Wire.	18
9	Resistance as a Function of Time for Various Lengths of 2-mil Copper Wire.	19
10	Resistance as a Function of Time for Various Lengths of 2-mil Iron Wire.	20
11	Power Input vs. Time for Various Lengths of 2-mil Silver Wire.	21
12	Power Input vs. Time for Various Lengths of 2-mil Copper Wire.	22
13	Power Input vs. Time for Various Lengths of 2-mil Iron Wire.	23
14	Energy Deposition vs. Time for Various Length Silver Wires.	24
15	Energy Deposition vs. Time for Various Length Copper Wires.	25

ILLUSTRATIONS (Cont'd)

Figure		Page
16	Energy Deposition vs. Time for Various Length Iron Wires	26
17	Composite Traces for a 2-mil Diameter, 0.050- inch Length Silver Wire in Explosive Test Fixture	27
18	Composite Traces for 2-mil Diameter, 0.050-inch Length Iron Wire in Explosive Test Fixture . . .	28

TABLES

Table		Page
1	Effect of Bridgewire Length (Silver, 2-mil Diameter) on Detonation of PETN at Various Loading Densities	8
2	Effect of Bridgewire Length (Copper, 2-mil Diameter) on Detonation of PETN at Various Loading Densities	9
3	Effect of Bridgewire Length (Iron, 2-mil Diameter) on Detonation of PETN at Various Loading Densities	10

INTRODUCTION

1. This report is the sixth in a series describing experimental results obtained from an investigation of exploding bridgewires. A previous investigation, reference 1*, had indicated that the detonation of high explosives could be effected more readily by those wire materials capable of absorbing energy from the power supply at a high rate and which were brought to the vapor state by the least quantities of energy. Aluminum and gold (Class I materials with low boiling point and low heat of vaporization), reference 2, were found able to effect detonation in PETN under more difficult conditions than platinum and tungsten (Class II materials with high boiling point and high heat of vaporization).

2. The present investigation was concerned with verifying the extrapolations made from the study of the previous materials i.e., aluminum, gold, platinum, and tungsten. Various lengths of silver, copper, and iron wire were evaluated for their ability to effect detonation in PETN and compared with each other. On the basis of extrapolations made from the first four materials tested, silver (Class I) would be expected to be the best of the three materials, followed respectively by copper (Class I) and iron (Class II). Very low melting point metals were not considered for possible use in electroexplosive devices because of their unfavorable mechanical properties.

ELECTRICAL CIRCUITRY

3. A typical exploding bridgewire circuit for ordnance purposes uses a 1-microfarad capacitor charged to 2,000 volts. The actual test circuit used for this investigation is shown in Figure 1. The transmission line was kept as short as possible consistent with the necessity for testing in an explosive firing chamber. The parameters for the test circuit were:

$C = 0.97$ microfarad

$L = 0.58$ microhenry

$R = 0.35$ ohm

$V_0 = 2,000$ volts

* Reference and other reports in this series are listed on page 7.

TEST PROCEDURE

4. Various lengths of silver, copper, and iron bridgewires were compared for their ability to effect detonation in PETN. The test fixture and experimental methods described in reference 3 were used for observing the growth of explosion. The ability of the wire to effect detonation was gradually decreased by increasing the density of the PETN in contact with the wire. This method was used to determine the most advantageous wire material and its optimum length. Current and voltage waveforms, and the derived resistance, power, and energy values were examined to help interpret the experimental results.

EXPERIMENTAL RESULTS

5. A test series was run with each bridgewire material. A 2-mil diameter wire was used for each material and the wire lengths ranged from 0.0125 to 0.100 inch. An examination of tables 1, 2, and 3 shows that silver and copper bridgewires are almost equally effective in detonating PETN, with iron bridgewires a poor third. Various electrical and physical attributes of the three bridgewire materials were then examined.

6. Examination of the current waveforms shown in figures 2, 3, and 4 shows that the different materials explode on different portions of the current pulse. (To aid in this one visualizes the current burst to the wire as a portion of the sine wave current which would be obtained if the wire were replaced by an electrical short.) Silver wires burst approximately two thirds up the leading edge of the current pulse. Copper wires burst somewhat nearer to the current pulse peak exhibiting less of a resurgence than the silver wires. The various iron wires gave a wide current burst dispersion which seems to be typical of Class II materials. The optimum length of iron wire for effecting detonation explodes approximately half way up the leading edge of the current pulse. The current drop at burst is slower for iron than for the Class I materials.

7. Examination of the voltage waveforms in figures 5, 6, and 7 shows higher voltage peaks for the Class I materials than for iron. For all three materials, the 0.100-inch length gave the highest peak voltage. In general, the peak voltage spikes of the Class I materials tend to be of higher value and shorter duration than those of the Class II materials. Iron showed the

vaporization plateau characteristic of Class II materials and gave the lowest peak voltages of the seven materials evaluated to date.

8. Examination of the resistance curves in figures 8 and 9 for silver and copper shows a smooth rapid rise for both metals to the peak resistance value. Copper exhibited irregular resistance fluctuations just after the peak resistance, whereas the other six elements evaluated tended to give smooth resistance drops in this region. Copper had the lowest peak resistance of the seven elements evaluated. Iron, in figure 10, shows the definite resistance plateau typical of Class II materials before the peak resistance occurs.

9. Comparison of figure 11, 12, and 13 shows that the delivery of power was higher for the Class I materials, silver and copper. The highest peak power was observed with 0.100-inch long copper wire. The wire length which gave the highest power for each of the three materials was longer than the optimum length for effecting detonation. Iron had the lowest power rate of the seven materials evaluated.

10. All three materials show a small energy deposition during the first 0.3 microsecond. See figure 14, 15, and 16. The energy deposition remained low for the first 0.6 microsecond for the high conductivity metals, silver and copper. Silver and copper give a sigmoidal type of energy-time curve similar to the other metals previously tested. Iron shows a different energy-time relation than the other metals, with the rate of energy deposition tending to be more constant than sigmoidal.

DISCUSSION

11. Previous testing with aluminum, gold, platinum, and tungsten wires had indicated that the more efficient wire materials for effecting detonation have lower energy requirements for vaporization and high rates of energy deposition in the fixed firing circuit.¹ The results with silver, copper, and iron wires were found to conform closely to the results of these previous tests. All the Class I materials tested (aluminum, gold, silver, and copper) were found to be better for effecting detonation than any of the Class II materials (platinum, tungsten, iron). Trouton's rule that the heat of vaporization in calories is approximately equal to 21 times the temperature of vaporization (boiling point) indicates that no crossover should be expected between the two classifications.

12. The electrical characteristics help explain the superiority of the Class I materials in effecting detonation. The series RLC circuit used for exploding the wires has for its differential equation

$$L \frac{di}{dt} + Ri + \frac{q}{c} = 0 \quad (1)$$

where L = inductance, i = current, R = resistance, q = charge, c = capacitance, and t = time. It was previously shown³ that the initial rate of rise of current is governed by

$$\frac{di}{dt} = \frac{V_0}{L} \quad t \rightarrow 0 \quad (2)$$

where V_0 is the initial voltage. As long as the Ri term in (1) remains negligible during the initial current rise, the current rise will be mainly governed by (2) since $q = cV_0$. Class I materials such as silver, have an initial small resistance value which remains low until a rapid resistance rise occurs at burst. Figure 17 shows the composite traces for the 0.050-inch length silver wire. The resistance trace shows roughly a ten fold increase from the original value of 0.022 ohm during the first 0.6 microsecond. This permits the current rise to be governed mainly by equation (2) for a relatively long period of time. Class II materials such as iron tend to have higher initial resistances and initially absorb energy at a faster rate. Figure 18 shows the composite traces for the 0.050-inch length iron wire. The resistance trace in figure 18 shows a fast rise until vaporization occurs, at which time the resistance tends to remain constant at 1.05 ohms. At approximately the time the vaporization plateau commences, one observes an inflection in the current; further lowering the rate of rise. This inflection is thought to show the increasing influence of the Ri term. It can be seen that Class I materials tend to permit a higher current density, enhancing the pinch effect. Peak power occurs at a time when the current is decreasing and the resistance is rapidly rising. The higher current levels in the Class I materials help to give higher peak power (i^2R) since the current effect is squared.

13. Class II materials, show a greater resistance effect with increased length because their resistivity is higher. There is a much greater dispersion of the current value at burst over the experimental length range for the Class II than for the Class I materials. Compare figure 2, 3, and 4. Information on the resistance of the lower melting elements in the liquid phase is readily available.⁴ Such information is fairly sparse for the higher melting metallic elements because of experimental difficulties. In general, resistivity increases

more slowly with temperature in metals in the liquid than in the solid state.⁵ The resistance of iron, platinum, and tungsten appears to be almost independent of temperature in the liquid state, indicating much smaller temperature coefficients of resistivity than those of the Class I materials. The marked increase in electrical resistivity at the time of burst has been explained by a vaporization wave proceeding inward from the wire surface, reducing the conducting cross section of the wire.⁶ The wave velocity depends not only on the specific energy, but also on the heat of vaporization.

14. If the wire materials evaluated are listed according to increasing energy required for complete vaporization, the following order is obtained:

Ag<Al<Au<Cu<Fe<Pt<W

The first four metals belong to Class I; the last three metals belong to Class II. If heat of vaporization of the wire material was the predominant property in regard to effecting detonation in PETN, silver should be the best material with the others following in the order shown. However, actual tests reveal the ordering to be as follows for effecting detonation with the optimum length for each material:

Au>Ag*, Cu>Al>Pt>W>Fe

showing other factors are involved in determining the optimum material. The ordering in each classification for the wire lengths of interest appears to be influenced strongly by the peak power. Gold, which exhibits the highest peak power over the lengths of interest in Class I, tends to be the best material for effecting detonation except in the very short lengths (<0.025-inch) where the peak power drops below those of some of the other materials. Aluminum has the lowest peak powers in Class I over the 0.025 to 0.100-inch length range. For the wire materials at their optimum length, the ordering corresponds closely to the order of decrease in peak power. However, the correlation between peak power and the ability to detonate does not exist in general. For example, the peak power for silver and copper is higher at lengths of 0.075 inch and 0.100 inch than it is at 0.050 inch, the optimum length. In the length range from 0.025 to 0.100 inch for the Class II materials, the peak powers for platinum are higher than those of tungsten which in turn are higher than those of iron. Iron, which requires the least energy for vaporization, is the poorest of the three Class II materials for effecting detonation. This shows that for the given conditions, peak power may be relatively more important than the heat of vaporization.

* Silver and copper were about equal in their ability to initiate PETN.

15. Gold exhibits the highest peak power since in addition to having a high current density at burst, gold also has the highest dwell resistance of the seven materials. Platinum has a lower current density at burst, but a relatively high dwell resistance making it one of the better Class II materials. Iron with both a lower current density and a lower dwell resistance had the lowest peak power and was the poorest for effecting detonation of PETN. It appears as though the inherent resistivity and character of the resistivity changes of the wire material are relatively more important than the energy required for vaporization.

16. A low energy requirement for vaporization appears to be a helpful adjunct to the higher peak powers typical of Class I materials. A comparison of the total energy supplied up to shortly after burst to comparative lengths of the different wire materials of both classes shows only minor variations between the metals. Energy in excess of that required for vaporization can be expected to further heat the plasma and/or vapor and also strengthen the shock and kinetic energy transfer to the explosive.

17. The necessity for initiating a critical volume of explosive is again indicated by these experiments. Tungsten wires in the liquid state before burst would be expected to have a greater temperature differential between the wire and the explosive in contact with the wire than would gold wires. Temperature differentials, however, at this time appear to be of no importance because of the limited amount of explosive in contact with the intact wire. Indications are that the wire length of the higher resistivity materials (Class II) should be shortened to reduce the resistance and permit a higher current density, thus giving a higher peak power per unit length. However, the necessity for initiating a critical volume of explosive appears to nullify any further gains by this means once a certain minimum length is reached. The experimental results do show that the optimum lengths of Class II metals for effecting detonation are shorter than those of Class I metals.

CONCLUSIONS

1. Silver and Copper (Class I) are better than iron (Class II) for effecting detonation in PETN.

2. Class I materials (compared to Class II materials) permit a higher current density before burst, allowing a greater rate of energy deposition. This coupled with the lower energy requirement for complete vaporization should allow greater energy transfer to the surrounding explosive.

3. Peak power was found to correlate closely with the ability to detonate PETN when the wire materials were at their optimum length, although this correlation is shown not to be a general one.

REFERENCES

1. Leopold, H., "Initiation of Explosives by Exploding Wires V Effect of Wire Material on the Initiation of PETN by Exploding Wires" NOLTR 64-146
2. Webb, F. H. Jr., Hilton H. H., Levine, P. H., Tollestrup, A. V. "The Electrical and Optical Properties of Rapidly Exploded Wires" Vol II, W. G. Chace and M. K. Moore (eds.), Plenum Press, New York, 1962, p. 37
3. Leopold, H. "Initiation of Explosives by Exploding Wires I Effect of Circuit Inductance on the Initiation of PETN by Exploding Wires" NOLTR 63-159
4. Lyon, R. N. (ed) Liquid - Metals Handbook, U. S. Government Printing Office, Washington, D. C. June 1952
5. Cusock, N. E. "The Electronic Properties of Liquid Metals" in Reports on Progress in Physics Vol. XXVI Published by the Institute of Physics and the Physical Society, London 1963
6. Bennett, F. D., Kohl, G. D., Wedemeyer, E. H. "Resistance Changes Caused by Vaporization Waves in Exploding Wires" BRL Report No. 1241, 1964

OTHER REPORTS IN THIS SERIES

1. Reference 3 above
2. II Effect of Circuit Resistance on the Initiation of PETN by Exploding Wires, NOLTR 63-244
3. III Effect of Wire Diameter on the Initiation of PETN by Exploding Wires, NOLTR 64-2
4. IV Effect of Wire Length on the Initiation of PETN by Exploding Wires, NOLTR 64-61
5. Reference 1 above

TABLE 1 Effect of Bridgewire Length (Silver, 2-mil Diameter)
on Detonation of PETN at Various Loading Densities

Bridgewire Length (inch)	Density of PETN (g/cm ³)					
	1.15		1.2		1.225	
	D	L	D	L	D	L
0.025	2	0	0	2		
0.050	2	0	2	0	0	2
0.075	2	0	1 ^a	1	0	2
0.100	2	0	0	2		

a Unsymmetrical growth to detonation

D = Detonation

L = Low order

TABLE 2 Effect of Bridgewire Length (Copper, 2-mil Diameter) on
Detonation of PETN at Various Loading Densities

Bridgewire Length (inch)	Density of PETN (g/cm ³)							
	1.1		1.15		1.2		1.225	
	D	L	D	L	D	L	D	L
0.025	2	0	2	0	0	2		
0.050	2	0	2	0	2	0	0	2
0.075	2	0	2	0	1 ^a	1	0	2
0.100	2	0	2	0	0	2		

a Unsymmetrical growth to detonation

D = Detonation

L = Low order

TABLE 3 Effect of Bridgewire Length (Iron, 2-mil Diameter) on
Detonation of PETN at Various Loading Densities

Bridgewire Length (inch)	Density of PETN (g/cm ³)					
	1.0		1.1		1.125	
	D	L	D	L	D	L
0.0125	2	0	0	2		
0.025	2	0	1	1	0	2
0.050	2	0	1	1	0	2
0.075	2	0	0	2		
0.100	1	1	0	2		

D = Detonation

L = Low order




FIG. 1 TEST CIRCUIT




FIG. 2 CURRENT WAVEFORMS FOR VARIOUS LENGTHS OF 2-MIL DIAMETER SILVER WIRE




FIG. 3 CURRENT WAVEFORMS FOR VARIOUS LENGTHS OF 2-MIL DIAMETER COPPER WIRE




FIG. 4 CURRENT WAVEFORMS FOR VARIOUS LENGTHS OF 2-MIL DIAMETER IRON WIRE




FIG. 5 VOLTAGE ACROSS VARIOUS LENGTH SILVER WIRES




FIG. 6 VOLTAGE ACROSS VARIOUS LENGTH COPPER WIRES




FIG. 7 VOLTAGE ACROSS VARIOUS LENGTH IRON WIRES




FIG. 8 RESISTANCE AS A FUNCTION OF TIME FOR VARIOUS LENGTHS OF 2-MIL SILVER WIRE




FIG. 9 RESISTANCE AS A FUNCTION OF TIME FOR VARIOUS LENGTHS OF 2-MIL COPPER WIRE




FIG. 10 RESISTANCE AS A FUNCTION OF TIME FOR VARIOUS LENGTHS OF 2-MIL IRON WIRE




FIG. II POWER INPUT VS. TIME FOR VARIOUS LENGTHS OF 2-MIL DIAMETER SILVER WIRE




FIG. 12 POWER INPUT VS. TIME FOR VARIOUS LENGTHS OF 2-MIL DIAMETER COPPER WIRE




FIG. 13 POWER INPUT VS. TIME FOR VARIOUS LENGTHS OF 2-MIL DIAMETER IRON WIRE




FIG. 14 ENERGY DEPOSITION VS. TIME FOR VARIOUS LENGTH SILVER WIRES




FIG. 15 ENERGY DEPOSITION VS. TIME FOR VARIOUS LENGTH COPPER WIRES




FIG. 16 ENERGY DEPOSITION VS. TIME FOR VARIOUS LENGTH IRON WIRES




FIG. 17 COMPOSITE TRACES FOR A 2-MIL DIAMETER, 0.050-INCH LENGTH SILVER WIRE IN EXPLOSIVE TEST FIXTURE




FIG. 18 COMPOSITE TRACES FOR A 2-MIL DIAMETER, 0.050-INCH LENGTH IRON WIRE IN EXPLOSIVE TEST FIXTURE

DISTRIBUTION

Copies

Chief, Bureau of Naval Weapons
 Department of the Navy
 Washington, D. C. 20360
 DLI-3
 RRKE-5
 RUME-11
 RUME-42
 RMMO-5
 RREN-32

2
 1
 1
 1
 1
 1

Director, Special Projects Office
 Department of the Navy
 Washington, D. C. 20360
 SP-20
 SP-273

1
 1

Superintendent
 Naval Post Graduate School
 Monterey, California 93940

1

Office of Naval Research
 Department of the Navy
 Washington, D. C. 20360

1

Commander
 U. S. Naval Ordnance Test Station
 China Lake, California 93557
 Code 556
 Technical Library

1
 2

Director
 Naval Research Laboratory
 Washington, D. C. 20390
 Tech. Info. Section

2

Commander
 U. S. Naval Weapons Laboratory
 Dahlgren, Virginia 22448
 Tech. Library
 Weapons Lab.
 Terminal Ballistics Lab.
 Code WHR

2
 1
 1
 1

Underwater Explosions Research Division
 David Taylor Model Basin
 Portsmouth, Virginia 23709

1

Commanding Officer U. S. Naval Weapons Station Yorktown, Virginia 23491 R&D Division	2
Commanding Officer U. S. Naval Ordnance Laboratory Corona, California 91720 Library Division	2
Commanding Officer U. S. Naval Propellant Plant Indian Head, Maryland 20640 Library Division	1
Commanding Officer U. S. Naval Explosive Ordnance Disposal Facility Indian Head, Maryland 20640 Library Division	2
Commanding Officer Naval Ordnance Plant Guy Paine Road Macon, Georgia 31201	1
Commanding Officer Naval Ammunition Depot Crane, Indiana QEL	1
Commanding Officer U. S. Naval Ammunition Depot Navy Number Six Six (66) c/o Fleet Post Office San Francisco, California 96612 QEL	1
Commanding Officer U. S. Naval Weapons Station Concord, California 94520 QEL	1
Commanding Officer U. S. Naval Underwater Ordnance Station Newport, Rhode Island 02844	1
Commanding Officer U. S. Naval Weapons Evaluation Facility Kirtland Air Force Base Albuquerque, New Mexico 87117	1

Copies

Army Material Command Department of the Army Washington, D. C. 20315 R&D Division	1
Commander Army Rocket & Guided Missile Agency Redstone Arsenal Huntsville, Alabama 35809 ORDXR-RH	1
Commanding Officer U. S. Army Missile Command Redstone Arsenal, Alabama 35809 R. Betts	1
Commanding Officer Picatinny Arsenal Dover, New Jersey 07801	
SMUPA-G	1
SMUPA-V	1
SMUPA-DD	1
SMUPA-DR	1
SMUPA-DR4	1
SMUPA-DW	1
SMUPA-VC	1
SMUPA-VE	1
SMUPA-VL	1
SMUPA-TX	1
SMUPA-TW	1
Commanding Officer Harry Diamond Laboratories Connecticut Ave & Van Ness St., N.W. Washington, D. C. 20438 Ord. Dev. Lab. M. Lipnick, Code 005	1 1
Commanding Officer U. S. Army Research Office Box CM, Duke Station Durham, North Carolina 27706	1
Atomic Energy Commission Washington 25, D. C. DMA	1
Dr. A. H. Keil, Director David Taylor Model Basin Washington, D. C. 20007	1

Copies

Director, U. S. Bureau of Mines
 Division of Explosive Technology
 4800 Forbes Avenue
 Pittsburgh, Pennsylvania 15213
 Dr. R. W. Van Dolah

1

Defense Documentation Center
 Cameron Station
 Alexandria, Virginia 22314
 TIPCR

20

Office of Technical Services
 Department of Commerce
 Washington, D. C. 20250

100

NASA
 Goddard Space Flight Centre
 Greenbelt, Maryland 20771

1

NASA
 Marshall Spacecraft Center
 P. O. Box 1537
 Houston, Texas 77001
 Library
 M. Falbo
 W. H. Simmons

2

1

1

Lawrence Radiation Laboratory
 University of California
 P. O. Box 808
 Livermore, California 94551
 Tech. Info. Div.
 Dr. M. Wilkins
 Dr. J. Kury

1

1

1

Director
 Los Alamos Scientific Laboratory
 P. O. Box 1663
 Los Alamos, New Mexico 87544
 Library
 GMX-7

1

1

Sandia Corporation
 P. O. Box 969
 Livermore, California

1

Sandia Corporation
 P. O. Box 5400
 Albuquerque, New Mexico 87115

1

Copies

The Franklin Institute 20th & Benjamin Franklin Parkway Philadelphia, Pennsylvania 19103 Gunther Cohn	1
Aerojet-General Corporation 11711 Woodruff Avenue Downey, California 90241 Dr. H. J. Fisher, Mgr. Ord. Res. Div.	1
Allegany Ballistics Lab. Cumberland, Maryland 21501	1
Flare-Northern Division Atlantic Research Corp. 19701 West Goodvale Road Saugus, California	1
Atlas Chemical Industries, Inc. P. O. Box 271 Tamaqua, Pennsylvania 18252	1
Flare-Northern Division Atlantic Research Corp. P. O. Box 175 West Hanover, Massachusetts 02380 J. A. Smith, Sec. Off.	1
Bermite Powder Co. 22116 W. Soledad Canyon Road Saugus, California 91350 L. LoFiego	1 1
Hercules Powder Co., Inc. Port Ewen, New York 12466 C. Wood G. Scherer	1 1
The Martin Company 815 Elwell Street Orlando, Florida 32800 M. Hedges	1
Thiokol Chemical Corporation Redstone Arsenal Huntsville, Alabama 35809	1
Stanford Research Institute Poulter Laboratories Menlo Park, California 94025	1

	Copies
Thickol Chemical Corp. Bristol Division P. O. Box 27 Bristol, Pennsylvania	1
McCormick-Selph Associates Hollister, California	1
Link Ordnance Division General Precision Co. Sunnyvale, California Attn: Mr. T. Parker	1 1
Lockheed Aircraft Corp. P. O. Box 504 Sunnyvale, California	1
Beckman & Whitley Research & Development Div. 993 San Carlos Avenue San Carlos, California	1
General Laboratory Associates 17 E. Railroad Street Norwich, New York	1
R. H. Stresau Laboratory Star Route Spooner, Wisconsin 54081	1
Special Devices, Inc. 16830 W. Placerita Canyon Road Newhall, California	1
Hi-Shear Corp. 2600 W. 247th Street Torrance, California 90509	1
Unidynamics P. O. Box 2990 Phoenix, Arizona	1
Atlas Chemical Industries, Inc. Valley Forge Industrial Park Valley Forge, Pennsylvania 19481	1
McDonnell Aircraft Corp. P. O. Box 516 St. Louis, Missouri 63166 V. Drexelius B. Kirk	1 1

UNCLASSIFIED

Security Classification

DOCUMENT CONTROL DATA - R&D		
<i>(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)</i>		
1. ORIGINATING ACTIVITY (Corporate author) NOL, White Oak, Maryland		2a. REPORT SECURITY CLASSIFICATION UNCLASSIFIED
		2b. GROUP
3. REPORT TITLE INITIATION OF EXPLOSIVES BY EXPLODING WIRES, VI. FURTHER EFFECTS OF WIRE MATERIAL ON THE INITIATION OF PETN BY EXPLODING WIRES		
4. DESCRIPTIVE NOTES (Type of report and inclusive dates)		
5. AUTHOR(S) (Last name, first name, initial) Leopold, Howard S.		
6. REPORT DATE	7a. TOTAL NO. OF PAGES 28	7b. NO. OF REFS 6
8a. CONTRACT OR GRANT NO. RUMB-4E000/212-1/F008-08-11		8a. ORIGINATOR'S REPORT NUMBER(S) NOLTR 65-1
a. PROJECT NO. PA-019		8b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)
c.		
d.		
10. AVAILABILITY/LIMITATION NOTICES Released to DDC without restriction		
11. SUPPLEMENTARY NOTES		12. SPONSORING MILITARY ACTIVITY BuWeps
13. ABSTRACT Silver, copper, and iron wires were investigated as possible bridgewire materials. The wires were exploded by a 1-microfarad capacitor charged to 2,000 volts. Peak power input to the bridge-wire is relatively more important than the energy required for vaporization. Low boiling point, low heat of vaporization metals such as silver and copper permit greater energy transfer to an explosive than high boiling point, high heat of vaporization metals such as iron. (U)		

DD FORM 1473
1 JAN 64

UNCLASSIFIED

Security Classification

UNCLASSIFIED

Security Classification

14 KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
Explosives - Initiation Exploding Wire PETN Silver Copper Iron						

INSTRUCTIONS

1. **ORIGINATING ACTIVITY:** Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (corporate author) issuing the report.

2a. **REPORT SECURITY CLASSIFICATION:** Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. **GROUP:** Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. **REPORT TITLE:** Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. **DESCRIPTIVE NOTES:** If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. **AUTHOR(S):** Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. **REPORT DATE:** Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.

7a. **TOTAL NUMBER OF PAGES:** The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. **NUMBER OF REFERENCES:** Enter the total number of references cited in the report.

8a. **CONTRACT OR GRANT NUMBER:** If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. **PROJECT NUMBER:** Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. **ORIGINATOR'S REPORT NUMBER(S):** Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. **OTHER REPORT NUMBER(S):** If the report has been assigned any other report numbers (either by the originator or by the sponsor), also enter this number(s).

10. **AVAILABILITY/LIMITATION NOTICES:** Enter any limitations on further dissemination of the report, other than those

imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. **SUPPLEMENTARY NOTES:** Use for additional explanatory notes.

12. **SPONSORING MILITARY ACTIVITY:** Enter the name of the departmental project office or laboratory sponsoring (paying for) the research and development. Include address.

13. **ABSTRACT:** Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. **KEY WORDS:** Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, roles, and weights is optional.

UNCLASSIFIED

Security Classification