

UNCLASSIFIED

AD NUMBER

AD463362

LIMITATION CHANGES

TO:

Approved for public release; distribution is unlimited.

FROM:

Distribution authorized to U.S. Gov't. agencies and their contractors; Specific Authority; MAY 1965. Other requests shall be referred to Air Force Flight Dynamics Laboratory, RTD, Air Force Systems Command, Wright-Patterson AFB, OH 45433.

AUTHORITY

AFFDL ltr, 20 Dec 1974

THIS PAGE IS UNCLASSIFIED

AEDC-TR-65-105

ARCHIVE COPY  
DO NOT LOAN

ay1



**AERODYNAMIC CHARACTERISTICS OF  
BALLUTES AND HEMISFLO PARACHUTES AT  
MACH NUMBERS OF 2.5, 2.6, AND 2.9**

**Lawrence L. Galigher**

**ARO, Inc.**

This document has been approved for public release  
its distribution is unlimited. *Per TABS 74-26  
Dtd 20 Dec 1974*

**May 1965**

PROPERTY OF U. S. AIR FORCE  
AEDC LIBRARY  
AF 40(600)1000

**PROPULSION WIND TUNNEL FACILITY  
ARNOLD ENGINEERING DEVELOPMENT CENTER  
AIR FORCE SYSTEMS COMMAND  
ARNOLD AIR FORCE STATION, TENNESSEE**

AEDC TECHNICAL LIBRARY



EE90 TE000 0220 5

# NOTICES

When U. S. Government drawings specifications, or other data are used for any purpose other than a definitely related Government procurement operation, the Government thereby incurs no responsibility nor any obligation whatsoever, and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise, or in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Qualified users may obtain copies of this report from the Defense Documentation Center.

References to named commercial products in this report are not to be considered in any sense as an endorsement of the product by the United States Air Force or the Government.

Defense Documentation Center release to the Clearinghouse for Federal Scientific and Technical Information (CFSTI) and foreign announcement and distribution of this report are not authorized. The distribution of this report is limited because it contains technology identifiable with items excluded from export by the Department of State.

THIS DOCUMENT IS UNCLASSIFIED  
DATE 10/20/2000 BY 60322 UCBAW/STP  
FOR public release  
REF ID: A674-26  
D+8 20 Dec 1974

AERODYNAMIC CHARACTERISTICS OF  
BALLUTES AND HEMISFLO PARACHUTES AT  
MACH NUMBERS OF 2.5, 2.6, AND 2.9

Lawrence L. Galigher  
ARO, Inc.

This document is approved for public release  
its distribution is unlimited. *Rec TAB 74-26  
7078 20 Dec, 1974*

## FOREWORD

The work reported herein was done at the request of and for the Air Force Flight Dynamics Laboratory (AFFDL), Research and Technology Division (RTD), Air Force Systems Command (AFSC), under Program Element 62405364/6065.

The results of the test were obtained by ARO, Inc. (a subsidiary of Sverdrup and Parcel, Inc.), contract operator of the Arnold Engineering Development Center (AEDC), AFSC, Arnold Air Force Station, Tennessee, under Contract AF40(600)-1000. The test was conducted from April 2 to 6, 1965 under ARO Project No. PS0552, and the report was submitted by the author on May 6, 1965.

This technical report has been reviewed and is approved.

Francis M. Williams  
Major, USAF  
AF Representative, PWT  
DCS/Test

Jean A. Jack  
Colonel, USAF  
DCS/Test

**ABSTRACT**

A test was conducted in the 16-ft supersonic tunnel to obtain drag, inflation, and stability characteristics of a metal ballute, a cloth ballute, and three hemisflo parachutes (5-, 10-, and 15-percent porosity). The cloth and metal ballutes were investigated at Mach numbers of 2.5 and 2.9, respectively, at a dynamic pressure of 120 psfa. The hemisflo parachutes were investigated at a Mach number of 2.6 at a dynamic pressure of 120 psfa. The drag coefficient of the hemisflo parachutes decreased as canopy porosity increased. There was no discernible effect of canopy porosity on stability of the parachutes.

## CONTENTS

	<u>Page</u>
ABSTRACT. . . . .	iii
NOMENCLATURE. . . . .	vi
I. INTRODUCTION . . . . .	1
II. APPARATUS	
2.1 Test Facility. . . . .	1
2.2 Test Article . . . . .	1
2.3 Instrumentation. . . . .	2
III. PROCEDURE. . . . .	3
IV. RESULTS AND DISCUSSION	
4.1 Deployment Loads . . . . .	4
4.2 Steady-State Loads . . . . .	4
4.3 Inflation and Stability Characteristics. . . . .	4
V. CONCLUDING REMARKS . . . . .	5

## ILLUSTRATIONS

Figure

1. Model Centerbody Dimensions . . . . .	7
2. Location of Model in Test Section	
a. Parachute . . . . .	8
b. Ballute . . . . .	9
3. Installation of Model Centerbody in Test Section . . .	10
4. Three-Quarter Rear View of Model Centerbody . . .	11
5. Ballute Details	
a. Metal Ballute . . . . .	12
b. Cloth Ballute . . . . .	13
6. Cloth Ballute. . . . .	14
7. Parachute Details . . . . .	15
8. Hemisflo Parachute. . . . .	16
9. Decelerator Deployment Characteristics	
a. Metal Ballute . . . . .	17
b. Cloth Ballute . . . . .	17
c. Parachute of 15-percent Porosity . . . . .	18
d. Parachute of 10-percent Porosity . . . . .	18
e. Parachute of 5-percent Porosity . . . . .	18

<u>Figure</u>		<u>Page</u>
10.	Variation of Drag Coefficient with Canopy Geometric Porosity, $M_\infty = 2.6$ , $x/d = 1.93$ . . . . .	19

**TABLE**

I.	Summary of Test Conditions and Results . . . . .	20
----	--	----

**NOMENCLATURE**

$C_{D_0}$	Decelerator drag coefficient, $\frac{F_D}{q_\infty S_0}$
d	Base diameter of strut-mounted centerbody, 1.467 ft
$F_D$	Decelerator drag force, lb
$M_\infty$	Free-stream Mach number
$q_\infty$	Free-stream dynamic pressure, psfa
$S_0$	Decelerator drag-producing area a. Cloth ballute, 28.2753 ft <sup>2</sup> b. Hemisflo parachute, 28.2753 ft <sup>2</sup>
x	Distance aft of centerbody base plane to confluence point of decelerator a. Cloth ballute, 8.15 ft b. Hemisflo parachute, 2.83 ft



## SECTION I INTRODUCTION

A test was conducted in the Propulsion Wind Tunnel, Supersonic (16S) to determine the steady-state drag, inflation, and stability characteristics of two types of aerodynamic decelerators in supersonic flow. The decelerators investigated during this test were conical ballutes and hemisflo parachutes. A cloth ballute and a metal ballute were tested at nominal Mach numbers of 2.5 and 2.9, respectively, at a nominal free-stream dynamic pressure of 120 psfa. Three hemisflo parachute configurations were tested at a nominal Mach number and free-stream dynamic pressure of 2.6 and 120 psfa, respectively.

## SECTION II APPARATUS

### 2.1 TEST FACILITY

Tunnel 16S is a closed-circuit, continuous flow wind tunnel currently capable of operating at Mach numbers from 1.65 to 3.20. The tunnel is capable of operating over a stagnation pressure range from 100 to approximately 1600 psfa. The test section stagnation temperature can be controlled through the range of 100 to 650°F. The wind tunnel specific humidity is controlled by removing tunnel air and supplying make-up air from an atmospheric dryer. A complete description of the facility and its operating characteristics are contained in the Test Facilities Handbook.<sup>1</sup>

### 2.2 TEST ARTICLE

#### 2.2.1 Model Centerbody and Deployment System

The decelerators tested during this investigation were deployed from a strut-mounted centerbody. Dimensions of the centerbody are presented in Fig. 1, and the location of the centerbody in the wind tunnel is shown in Fig. 2. The wind tunnel installation of the centerbody is shown in Fig. 3.

---

<sup>1</sup>Test Facilities Handbook, (5th Edition). "Propulsion Wind Tunnel Facility, Vol. 3." Arnold Engineering Development Center, July 1963.

The ballutes were packed in the aft end of the centerbody and deployed with a drogue parachute. The hemisflo parachutes were packed in the aft end of the centerbody on a spring-loaded plate and were held against the plate by retaining straps. The retaining straps were released by a squib-fired release pin mechanism. A three-quarter rear view of a hemisflo parachute packed in the aft end of the centerbody is shown in Fig. 4. The ballute riser line was affixed to the centerbody by a cable with a load cell in series; the parachute riser line was similarly affixed to the centerbody, but a swivel was used to prevent twisting of the parachute suspension lines. A shear pin, designed to protect the load cell, was used to connect the riser line to the cable.

### 2.2.2 Decelerators

The 6-ft-diam cloth ballute and the 5-ft-diam metal ballute were constructed of nylon and woven stainless steel, respectively. Both ballutes were 80-deg conical ballutes with four side-ram-air inlets. The cloth ballute had a 10-percent burble fence. No burble fence was incorporated on the metal ballute. The dimensions of the ballutes are shown in Fig. 5, and a photograph of the cloth ballute is shown as Fig. 6.

The hemisflo parachute canopies had a roof and skirt constructed of 0.75-in. -wide nylon ribbons and 16-in. -wide solid nylon mesh, respectively. The riser lines and suspension lines were also of nylon construction. The hemisflo parachute configurations are identified by nominal diameter and canopy geometric porosity. Nominal diameter is defined as the diameter of a circle having the same total area as the total area of the drag-producing surface, which includes all openings in the drag-producing surface such as slots and vents. Geometric porosity is defined as the ratio of the open area of a drag-producing surface to the total canopy drag-producing surface area. The parachutes had a nominal diameter of 6 ft and a suspension line length (skirt to confluence point) of 12 ft. The riser line length was 2.83 ft. The hemisflo parachutes had geometric porosities of 5, 10, and 15 percent. Details of the parachutes are shown in Fig. 7, and a photograph of one of the hemisflo parachutes is shown as Fig. 8.

## 2.3 INSTRUMENTATION

Double element load cells of 10,000- and 5,000-lb capacity were used to measure the drag load of the ballutes and hemisflo parachutes, respectively. A direct writing oscillograph was used to monitor the decelerator drag load during testing. Five movie cameras and two television cameras, installed in the test section walls, were used to document and monitor these tests.

### SECTION III PROCEDURE

A decelerator was packed in the aft end of the strut-mounted centerbody before initiation of wind tunnel test operations. Once test conditions were established, the decelerator was ejected from the centerbody into the airstream. Motion pictures and dynamic drag data were obtained during and after each deployment. Upon completion of the decelerator deployment sequence, a steady-state drag load was calculated by averaging the analog output signal from the strain-gage load cell over a 1-sec interval.

The cloth ballute and the metal ballute were deployed at nominal Mach numbers of 2.5 and 2.9, respectively, at a free-stream dynamic pressure of 120 psfa. The three hemisflo parachutes were deployed at a nominal Mach number of 2.6 at a free-stream dynamic pressure of 120 psfa. The centerbody was maintained at zero angle of attack and yaw for the entire test. A complete summary of the test conditions is presented in Table I.

The accuracy of the drag load obtained from the 5,000- and 10,000-lb capacity load cells was determined to be  $F_D = \pm 9$  lb for the range of drag loads measured during these tests.

### SECTION IV RESULTS AND DISCUSSION

A limited amount of steady-state drag data was obtained during this test because of failure of the decelerators during or shortly after inflation. The failure of the metal ballute was caused by a malfunction of one of the four side-air inlets during the ballute inflation process. The sudden change in tunnel flow blockage created by the fully inflated cloth ballute caused a "tunnel flow breakdown" and subsequently, loss of the ballute. The cloth ballute was fully inflated for approximately 1 sec before tunnel flow breakdown. The three hemisflo parachute failures were caused by separation of several suspension lines from the confluence point approximately 12 sec after inflation. The parachutes inflated fully, and steady-state data were obtained before failure of the suspension lines. A complete summary of the test results is given in Table I.

#### 4.1 DEPLOYMENT LOADS

Deployment of trailing aerodynamic decelerators generally creates two forces known as "snatch force" and "opening shock force." For wind tunnel testing of decelerators, the snatch force is defined as that force imposed on the centerbody by the deceleration of the mass of the decelerator from its velocity at line extension to zero velocity relative to the centerbody. The snatch force is followed closely by the opening shock force, which is defined as that force imposed on the centerbody by the sudden inflation of the decelerator at full line extension.

The snatch force and the opening shock force were found to vary considerably during each parachute deployment since they are a function of the parachute packing procedure. The snatch and opening shock forces for the parachutes varied between 1250 and 3500 lb, and 815 and 2560 lb, respectively. The snatch force for the cloth and metal ballutes was 1375 and 875 lb, respectively. The ballutes did not exhibit an opening shock force because a finite amount of time is required for the ballute inflation process. The deployment-time histories of the decelerators are shown in Fig. 9 for each of the deployments.

#### 4.2 STEADY-STATE LOADS

As shown in Fig. 10, the drag coefficient of the hemisflo parachutes decreases with increasing canopy geometric porosity. Decreasing the porosity from 15 to 5 percent increases the drag coefficient approximately 27 percent.

The drag coefficient of the cloth ballute was 0.626 at  $M_{\infty} = 2.5$ . No steady-state drag data were obtained for the metal ballute since it failed during the inflation process.

#### 4.3 INFLATION AND STABILITY CHARACTERISTICS

Photographic coverage obtained by movie cameras permitted the determination of decelerator inflation and stability characteristics. Analysis of the motion pictures indicates that the cloth ballute attained full inflation approximately 1.5 sec after initiation of deployment and that the fully inflated ballute exhibited no oscillation in a plane perpendicular to the riser line axis.

The hemisflo parachutes attained full canopy inflation during each deployment and exhibited approximately  $\pm 2.5$  ft of oscillation in a plane



that is perpendicular to the riser line axis and parallel to the canopy vent cap. There was no discernible effect of canopy geometric porosity on the severity of the oscillation.

#### SECTION V CONCLUDING REMARKS

Tests were conducted to obtain drag, inflation, and stability characteristics of a nylon ballute, a woven stainless steel ballute, and three hemisflo parachutes having geometric porosities of 5, 10, and 15 percent. The cloth ballute, metal ballute, and hemisflo parachutes were investigated at Mach numbers of 2.5, 2.9, and 2.6, respectively, at a dynamic pressure of 120 psfa.

Failure of the metal ballute during the inflation process prevented the acquisition of any usable data. A limited amount of data was obtained for the cloth ballute and hemisflo parachutes before their subsequent failure shortly after inflation.


The cloth ballute inflated fully and exhibited very good stability. The three hemisflo parachutes inflated fully but exhibited poor stability. Analysis of the motion pictures indicates that the effect of canopy porosity on parachute stability was not discernible. The drag coefficient of the hemisflo parachutes decreases as canopy geometric porosity increases.



SECTION A-A


ALL DIMENSIONS IN INCHES

Fig. 1 Model Centerbody Dimensions



a. Parachute

Fig. 2 Location of Model in Test Section



b. Ballute  
 Fig. 2 Concluded






Fig. 3 Installation of Model Centerbody in Test Section






Fig. 4 Three-Quarter Rear View of Model Centerbody



a. Metal Ballute  
Fig. 5 Ballute Details



b. Cloth Ballute  
 Fig. 5 Concluded





Fig. 6 Cloth Ballute



HEMISFLO RIBBON  
 RIBBON WIDTH, 0.75 INCH  
 20 GORES  
 72 IN. NOMINAL DIAMETER  
 SUSPENSION LINE LENGTH,  $\lambda = 144$  IN.

NOTE: CROSSHATCHING REPRESENTS CLOSED SPACING

NOTE: ALL DIMENSIONS IN INCHES




Fig. 7 Parachute Details






Fig. 8 Hemisflo Parachute




a. Metal Ballute




b. Cloth Ballute

Fig. 9 Decelerator Deployment Characteristics






c. Parachute of 15-percent Porosity



d. Parachute of 10-percent Porosity



e. Parachute of 5-percent Porosity

Fig. 9 Concluded




Fig. 10 Variation of Drag Coefficient with Canopy Geometric Porosity,  
 $M_\infty = 2.6$ ,  $x/d = 1.93$

**TABLE I**  
**SUMMARY OF TEST CONDITIONS AND RESULTS**

Configuration	$M_\infty$	$q_\infty$ , psfa	Decelerator Diameter, ft		Canopy Geometric Porosity, percent	$C_{D_0}$	Remarks
			Maximum	Nominal			
Metal ballute	2.900	119.9	5		—	—	Failure of ballute during inflation process
Cloth ballute	2.500	120.0	6		—	0.626	Tunnel flow breakdown approximately 1 sec after full inflation of ballute
Hemisflo	2.596	120.2		6	15	0.313	Separation of several suspension lines from confluence point approximately 12 sec after canopy inflation.
Hemisflo	2.596	120.4		6	10	0.331	Separation of several suspension lines from confluence point approximately 12 sec after canopy inflation
Hemisflo	2.599	120.0		6	5	0.397	Separation of several suspension lines from confluence point approximately 10 sec after canopy inflation

## DOCUMENT CONTROL DATA - R&amp;D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1 ORIGINATING ACTIVITY (Corporate author) Arnold Engineering Development Center, ARO, Inc., Operating Contractor, Arnold Air Force Station, Tennessee		2a REPORT SECURITY CLASSIFICATION UNCLASSIFIED	
		2b GROUP N/A	
3. REPORT TITLE AERODYNAMIC CHARACTERISTICS OF BALLUTES AND HEMISFLO PARACHUTES AT MACH NUMBERS OF 2.5, 2.6, AND 2.9			
4. DESCRIPTIVE NOTES (Type of report and inclusive dates) N/A			
5. AUTHOR(S) (Last name, first name, initial) Galigher, Lawrence L., ARO, Inc.			
6. REPORT DATE May 1965		7a. TOTAL NO. OF PAGES 26	7b. NO. OF REFS None
8a. CONTRACT OR GRANT NO. AF 40(600)-1000		9a. ORIGINATOR'S REPORT NUMBER(S) AEDC-TR-65-105	
b. PROJECT NO. 6065		9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report) N/A	
c. Program Element 62405364			
10. AVAILABILITY/LIMITATION NOTICES Qualified requesters may obtain copies of this report from DDC. DDC release to CFSTI and foreign announcement and distribution of this report are not authorized.			
11. SUPPLEMENTARY NOTES N/A		12. SPONSORING MILITARY ACTIVITY Air Force Flight Dynamics Laboratory, RTD, Air Force Systems Command, Wright-Patterson AF Base, Ohio	
13 ABSTRACT  A test was conducted in the 16-ft supersonic tunnel to obtain drag, inflation, and stability characteristics of a metal ballute, a cloth ballute, and three hemisflo parachutes (5-, 10-, and 15-percent porosity). The cloth and metal ballutes were investigated at Mach numbers of 2.5 and 2.9, respectively, at a dynamic pressure of 120 psfa. The hemisflo parachutes were investigated at a Mach number of 2.6 at a dynamic pressure of 120 psfa. The drag coefficient of the hemisflo parachutes decreased as canopy porosity increased. There was no discernible effect of canopy porosity on stability of the parachutes.			

this document has been approved for public release  
its distribution is unlimited  
OK TAB 77-26  
248 20 Dec, 1974

14. KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
parachutes						
ballutes						
hemisflos						
aerodynamic characteristics						
supersonic flow						
porosity effects						
stability						

**INSTRUCTIONS**

1. **ORIGINATING ACTIVITY:** Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (*corporate author*) issuing the report.

2a. **REPORT SECURITY CLASSIFICATION:** Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. **GROUP:** Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. **REPORT TITLE:** Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. **DESCRIPTIVE NOTES:** If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. **AUTHOR(S):** Enter the name(s) of author(s) as shown on or in the report. Enter: last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. **REPORT DATE:** Enter the date of the report as day, month, year; or month, year. If more than one date appears on the report, use date of publication.

7a. **TOTAL NUMBER OF PAGES:** The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. **NUMBER OF REFERENCES:** Enter the total number of references cited in the report.

8a. **CONTRACT OR GRANT NUMBER:** If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. **PROJECT NUMBER:** Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. **ORIGINATOR'S REPORT NUMBER(S):** Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. **OTHER REPORT NUMBER(S):** If the report has been assigned any other report numbers (*either by the originator or by the sponsor*), also enter this number(s).

10. **AVAILABILITY/LIMITATION NOTICES:** Enter any limitations on further dissemination of the report, other than those

imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through \_\_\_\_\_."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through \_\_\_\_\_."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through \_\_\_\_\_."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. **SUPPLEMENTARY NOTES:** Use for additional explanatory notes.

12. **SPONSORING MILITARY ACTIVITY:** Enter the name of the departmental project office or laboratory sponsoring (*paying for*) the research and development. Include address.

13. **ABSTRACT:** Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. **KEY WORDS:** Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.