# unclassified AD 463919

## **DEFENSE DOCUMENTATION CENTER**

FOR

### SCIENTIFIC AND TECHNICAL INFORMATION

CAMERON STATION ALEXANDRIA. VIRGINIA



UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.



#### ABSTRACT

The excitation function for the  $Al^{27}(n,\alpha)$  cross section was measured from 12.8 to 14.3 Mev. The energy resolution of the data is better than 80 kev, and the statistical errors are less than 1 percent. The data show a peak at 13.55 Mev in the cross section with a width of about 300 kev and an amplitude of about 4 percent of the average cross section in this region.

#### SUMMARY

#### The Problem

Recent developments in nuclear theory suggest that neutron reaction cross sections in the several Mev range may contain a previously unobserved fine structure-fluctuation with widths of the order of 100 kev. Almost all of the available experimental data are too coarse to resolve such structure. To search for such structure, a high-resolution, high-precision measurement of the  $A1^{27}(n,\alpha)$  cross section vs. neutron energy was performed over an energy range of 12.8 to 14.3 Mev.

#### The Findings

A peak in the  $Al^{27}(n,\alpha)$  cross section was found at 13.55 Mev. The width of the peak is about 300 kev and the height of the peak is about 4 percent of the average cross section in this region. The fluctuation is probably one of two effects predicted in recent theory. Further experiments, which should better define the origin of the fluctuations, are planned.

#### INTRODUCTION

Until recently, it had been assumed that nuclear cross sections would not exhibit structure over small energy intervals for energies high enough so that the average widths of the compound nucleus levels greatly exceeded their spacing. However, recent theoretical developments indicate that certain types of cross sections may exhibit structure in this energy region.<sup>1-6</sup> Experiments have verified such structure.<sup>7-10</sup> Because of these developments we decided to re-examine the  $A1^{27}(n,\alpha)$  cross section in the 14 Mev region. Previous studies of this cross section and its gross behavior with energy. Neither the errors, energy spacings, nor energy resolutions of the measurements were small enough to establish structure. The data of Gabbard and Kern<sup>11</sup>, however, suggest a peak in the  $A1^{27}(n,\alpha)$  excitation function at about 13.5 Mev. We chose to study this particular cross section partly because of this indication. Also, the decay characteristics of the reaction product, Na<sup>24</sup>, make it easy to study the cross section by the activation technique. The 13 to 14 Mev energy region was chosen because good energy resolution can be obtained there, and again because of the suggested peak at 13.5 Mev in the data of Gabbard and Kern.

Our data show that a peak does occur in the excitation function. In the next section we describe the experiment and results, and in the last section we discuss some possible interpretations of the results.

#### EXPERIMENTAL PROCEDURE AND RESULTS

Neutrons in the 13 to 14 Mev range were produced by the  $T(d,n)He^4$  reaction. Deuterons with a 1.630 Mev energy were produced with a Van de Graaff accelerator. The deuteron energy was controlled

by bending the deuterons 90 degrees in a magnetic field. The magnet was calibrated using the thresholds of the Li7(p,n) and the T(p,n)reactions. The magnetic field strength was measured using a Halleffect detector. A feedback system on the output slits of the magnet stabilized the Van de Graaff voltage.

The deuterons bombarded a titanium tritide target  $2 \text{ mg/cm}^2$  thick. In part of the experiment the target was perpendicular to the beam, and the rest of the time it was slanted 45 degrees with respect to the beam. In the first geometry, the target thickness to the deuterons is 260 kev, and in the other geometry it is 370 kev. Hence, the energy spread of the interacting deuterons is + 130 or 190 kev.

In each exposure 24 samples were exposed at different angles with respect to the deuteron beam, corresponding to different neutron energies. Each sample is an aluminum cylinder 0.64 cm in diameter and 2.54 cm long. They were placed on the sample holder with their axes perpendicular to the direction of the deuteron beam. The sample holder consisted of a flat surface 6 inches long which was positioned with an error of less than 1 mm with respect to the sample holder. The average distance of the samples from the target was about 25 cm. The deuteron beam itself was focused to form a line on the target parallel to the axes of the samples. The length of the line formed by the beam was 2.5 cm. and its width was less than 0.3 cm.

The samples were irradiated for several hours, and were then counted with a gamma-ray counter to determine the relative amount of Na<sup>24</sup> in each sample. The gamma counting was done with a 7.6 cm high, 7.6 cm diameter NaI(Tl) crystal which has in it a 2.5 cm diameter, 2.5 cm deep well. Each sample was placed in the well and counted for either 20 or 30 minutes. Counting all the samples took about 12 hours, or less than one half life. The NaI(Tl) crystal output was recorded with a 100-channel analyzer, and only pulses corresponding to gamma rays from 1 to 3 Mev were used in the analysis of the data. For each sample about 10,000 counts were recorded, with a background of 1,110 counts per 30 minutes. The spectrometer system was checked for drift before and after each sample run. The drift correction was always less than 0.1 percent.

The gamma counts were corrected for the inverse square distance from the tritium target, sample weight, decay of  $Na^{2l_4}$ , and the variation of the T(d,n) cross section with angle. The data of Bame and Perry<sup>16</sup> were used for this last correction. These corrected counts give the relative cross section as a function of neutron energy. Five exposures were made. The first two exposures had low neutron yields, and the statistical counting errors were several percent. These data were not used since 1 percent statistics were obtained on the last three exposures. Of the three exposures used, two were made under "identical" conditions, to improve the statistics and check the reproducibility. The data agreed within the statistical accuracy, and are shown as the open circles in Fig. 1. In the last exposure, as many as possible of the experimental conditions were changed to check against possible sources of error. A different target and target assembly were used, and the target angle was changed from perpendicular to 45 degrees with respect to the beam. The position and orientation of the sample holder with respect to the target also were changed. These data are shown as the solid circles in Fig. 1.

The error bars in Fig. 1 represent only the statistical error. Other sources of error are all estimated to be well under 1 percent. The errors due to sample positioning and uncertainty in beam position. should be less than 0.2 percent. In particular, a consistent beam positioning error, which would enter into the inverse square correction, would tend to reduce the peak at 13.5 Mev instead of producing an artificial peak. Positioning errors would also produce an uncertainty in angle which could shift the entire energy scale by 20 kev. However, the relative energies of the points would not change more than a few kev. Errors in the deuteron energy would expand or contract the energy scale by 10 to 20 kev at the extremities, with much less effect on the interior of the curve. In any case, the shape of the curve would be virtually unchanged.

The width of the energy resolution curve is determined by the angle subtended by the sample at the target (and vice versa) and the deuterium energy loss in the target. The energy control of the machine is such that variations in the energy of the incident beam itself are negligible. The standard deviation of the neutron energy distribution for the point at 12.816 Mev is 29 kev; for the point at 13.509 Mev it is 25 kev, and for the point at 14.282 Mev it is 41 kev. The energy resolutions for the other points vary smoothly between these extremes. Note that the energy spread (two standard deviations) is somewhat larger than the spacing between the points, but much smaller than the width of the peak at 13.5 Mev.



Fig. 1 Relative excitation function for the  $Al^{27}(n,\alpha)$  cross section. Note the suppressed zeros on both scales. The open circles and solid circles represent data taken under different experimental conditions. The energy spread for each point is roughly equal to the spacing between open (or closed) points. The error bars represent only the standard deviation due to counting statistics. However, other errors are estimated to be small compared to the statistical error. The uncertainty in the energy scale is of the order of 20 keV, but the uncertainty in the relative energies of the different points is much smaller. The scatter of the points in the 13.1 MeV region is probably experimental error.

#### DISCUSSION

The data establish the existence of a bump in the excitation function at 13.5 Mev, with a width of about 300 kev and an amplitude of about 4 percent of the average cross section.

For energies as high as those used here (compound nucleus excitation energies from 19.5 to 22.0 Mev) the widths of the compound nucleus levels should be much larger than the average level spacing. In other words, we are in the "continuum" region. It is not immediately apparent, therefore, why a peak like that observed should occur.

Two mechanisms for producing structure in nuclear excitation functions have been proposed recently. One theory, proposed by Ericson and others,  $1^{-3}$  suggests that interference between overlapping compound nuclear levels will produce fluctuations with spacings of the order of the widths of the compound nuclear levels. This theory appears to be consistent with a great deal of reaction data for high compound nucleus excitations. However, the fluctuations should be highly damped for a cross section integrated over angle and summed over many residual levels, and it is an open question whether even a 4 percent fluctuation is reasonable for the total  $(n,\alpha)$  cross section. A quantitative prediction based on the Ericson theory requires a knowledge of the  $\alpha$ -particle transmission coefficients and spins for all the significant levels of the residual Na<sup>24</sup> nucleus; such an evaluation is not feasible at present because of lack of data on the spins.

An alternative mechanism for producing structure is suggested by Block, Feshbach, Kerman, Rodberg, Young, and others.<sup>4-6</sup> In this mechanism, resonances are caused by the incident nucleon raising one or a few nucleons to excited states. The theory has not been developed to the point where quantitative predictions can be made for our reaction.

Fortunately there exists a clear test between the two mechanisms. For the first mechanism, there should be no correlation between the fluctuations in different cross sections for decay of the same compound nucleus. Hence the observed peak would not be expected in the  $Al^{27}$  total cross section of the  $Al^{27}(n,p)$  cross section, for example. In the second mechanism, on the other hand, the peak should appear to some extent in all the  $Al^{27}(n,x)$  cross sections, since the mechanism is associated with the formation of the compound nucleus. It is planned to look for this structure in one or more  $Al^{27}(n,x)$  cross sections.

5

#### REFERENCES

1. T. Ericson, Annals of Physics (N.Y.), 23, 390 (1963); Physics Letters 4, 258 (1963); Phys. Rev. Letters 5, 430 (1960). D. M. Brink and R. O. Stephen, Physics Letters 5, 77 (1963). 2. C. E. Porter, Revs. of Mod. Physics, 36, 1094 (1946). 3. B. Block and H. Feshbach, Annals of Physics (N.Y.) 23, 47 (1963). 4. A. K. Kerman, L. S. Rodberg, and J. E. Young, Phys. Rev. Letters 5. 11, 422, (1963). A. Lande and B. Block, Phys. Rev. Letters 12, 334 (1964). 6. 7. U. Facchini, E. Saetta Menichella, and G. Tonolini, Physics Letters 1, 209 (1962). 8. L. Colli, U. Facchini, I. Iori, C. M. Marcazzan, M. Milazzo, and F. Tollini, Physics Letters <u>1</u>, 120 (1962); L. Colli, I. Iori, M. G. Marcazzam, and M. Milazzo, Physics Letters 2, 12 (1962). M. L. Halbert, F. E. Durham, C. M. Moak, and A. Zucker, 9. Nuclear Physics 47, 353 (1963). 10. G. M. Temmer, Phys. Rev. Letters 12, 330 (1964). 11. F. Gabbard and B. D. Kern, Phys. Rev. 128, 1276 (1962). 12. J. P. Butler and D. C. Santry, Can. J. Physics 41, 372 (1963). 13. G. S. Mani, Nuclear Physics 19, 535 (1960). 14. B. P. Bayhurst and R. J. Prestwood, Journ. Inorg. and Nuclear Chem., 23, 173 (1961). 15. M. Borman, J. Phys. Radium, 22, 602 (1961). 16. S. J. Bame and J. E. Perry, Phys. Rev. 107, 1616 (1957).

Physics and Shielding

#### INITIAL DISTRIBUTION

#### Copies

#### NAVY

- 1 Chief, Bureau of Ships (Codes 320-364A)
- 2 Chief, Bureau of Ships (Code 210L)
- 1 Chief, Bureau of Ships (Code 364C)
- 1 Chief of Naval Operations (Op-07T)
- 1 Director, Naval Applied Science Laboratory (Code 962)
- 3 Director, Naval Research Laboratory
- 1 CO, Naval Civil Engineering Laboratory
- 1 OiC, Naval School Civil Engineers Corps Officers
- 3 CO, Office of Naval Research, FPO, New York
- 1 Supt., Naval Postgraduate School, Monterey

#### ARMY

- 1 Chief of Research and Development (Atomic Office)
- 2 Commander, Nuclear Defense Laboratory (Library, Donnert)
- 1 CO, Army Electronic Research and Development Laboratory
- 2 CG, Ballistic Research Laboratory (Allen, Ethridge)
- 4 Office of Civil Defense (Buchanan, FitzSimmons, Stangler, Greene)

#### AIR FORCE

- 1 Chief, Systems Engineering Group (SEPIR)
- 1 Director, USAF Project RAND
- 1 Director, Air University Library, Maxwell AFB
- 1 Commander, Air Force Cambridge Research Laboratories (CRT)

#### OTHER DOD ACTIVITIES

- 3 Director, Defense Atomic Support Agency (Library, Daniel)
- 1 Commander, FC/DASA, Sandia Base (FCTG5, Library)
- 20 Defense Documentation Center

#### AEC ACTIVITIES AND OTHERS

4 Argonne National Laboratory (Library, Grotenhuis) 3 Atomic Energy Commission, Washington 1 Atomic Energy of Canada, Limited 1 Atomics International (Ashley) 2 Battelle Memorial Institute 4 Brookhaven National Laboratory 2 Los Alamos Scientific Laboratory (Library) Hq., National Aeronautical Space Administration (Reetz) 1 NASA, Lewis Research Center 1 National Academy of Sciences (Park) 1 National Bureau of Standards (Library, Eisenhauer, Berger) 3 New York University (Kalos) 1 Oak Ridge National Laboratory (Auxier, Zobel, Clifford, Blizard, Penny) 5 2 Radiation Research Associates (Wells, Schaeffer) Sandia Corporation, Albuquerque 1 Sandia Corporation, Livermore 1 Technical Operations, Incorporated (Clarke, Tiller) 2 University of Illinois (Chilton) 1 2 University of California Lawrence Radiation Lab., Livermore 2 University of California Lawrence Radiation Lab., Berkeley United Nuclear Corporation (Mittelman) 1 15 Division of Technical Extension, Oak Ridge

USNRDL

30 Technical Information Division

DISTRIBUTION DATE: 11 June 1965

Security Classification					
DOCUMENT C	ONTROL DATA -	PLD			
(Security classification of title, body of abstract and inde	xing annotation must b	e entered when	the overall report is classified)		
1. ORIGINATIN G ACTIVITY (Corporate author)		2a. REPO	24. REPORT SECURITY CLASSIFICATIO		
U. S. Naval Radiological Defense Labor	ratory	Ţ	UNCLASSIFIED		
San Francisco, California 94135		25. GROU	None		
3. REPORT TITLE	·····	······	<u></u>		
A DESCRIPTIVE NOTES (Type of many and instants date)	DSS SECTION				
S. AUTHOR(S) (Liter name, mer name, ininel)					
Ferguson, James M.					
6. REPORT DATE	74. TOTAL NO. OF	F PAGES	76. NO. OF REFS		
11 June 1965	. 12		T0		
Sa. CONTRACT OR GRANT NO.	S. ORIGINATORS	SA. ORIGINATOR'S REPORT NUMBER(S)			
b. PROJECT NO. Subproject SR Oll Ol Ol Task 0401	USNR	usnrdl-tr-846			
<b>c.</b>	<b>9</b> b. OTHER REPORT NO(5) (Any other numbers that may be assign this report)				
d					
11. SUPPLEMENTARY NOTES	12. SPONSORING MILITARY ACTIVITY Bureau of Ships, Department of the Navy				
	Washington, D. C. 20360				
<ul> <li>13. ABSTRACT The excitation function for the A</li> <li>12.8 to 14.3 Mev. The energy resoluti</li> <li>the statistical errors are less than 1</li> <li>Mev in the cross section with a width</li> <li>4 per cent of the average cross section</li> </ul>	$L^{27}(n,\alpha)$ cross on of the data per cent. The of about 300 here in this regime	s section a is bette ne data sh kev and an ion.	was measured from er than 80 kev, and now a peak at 13.55 n amplitude of about		

I

#### LINCLASSIE: LD

#### Security Classification

14. KEY WORDS	LINK A		LINK B		LINK C		
		WT	ROLE	W۳	ROLE	WT	
Neutrons Cross-sections Aluminum Nuclear reactions						7	
INSTRUCTIONS							

INSTRUCTION

1. ORIGINATING ACTIVITY: Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (corporate author) issuing the report.

2a. REPORT SECURITY CLASSIFICATION: Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. GROUP: Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. REPORT TITLE: Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. DESCRIPTIVE NOTES: If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. AUTHOR(S): Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. REPORT DATE: Enter the date of the report as day, month, year; or month, year. If more than one date appears on the report, use date of publication.

7a. TOTAL NUMBER OF PAGES: The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. NUMBER OF REFERENCES: Enter the total number of references cited in the report.

8a. CONTRACT OR GRANT NUMBER: If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. PROJECT NUMBER: Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9s. ORIGINATOR'S REPORT NUMBER(S): Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. OTHER REPORT NUMBER(S): If the report has been assigned any other report numbers (either by the originator or by the sponsor), also enter this number(s).

10. AVAILABILITY/LIMITATION NOTICES: Enter any limitations on further dissemination of the report, other than those

DD JAN & 1473 (BACK)

imposed by security classification, using standard statements such as:

- "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC, Other qualified DDC users shall request through
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through

."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. SUPPLEMENTARY NOTES: Use for additional explanatory notes.

12. SPONSORING MILITARY ACTIVITY: Enter the name of the departmental project office or laboratory sponsoring (paying for) the research and development. Include address.

13. ABSTRACT: Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. KEY WORDS: Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rales, and weights is optional.