

UNCLASSIFIED

AD NUMBER

AD489200

LIMITATION CHANGES

TO:

Approved for public release; distribution is unlimited.

FROM:


Distribution authorized to U.S. Gov't. agencies and their contractors;  
Administrative/Operational Use; SEP 1966. Other requests shall be referred to Arnold Engineering Development Center, Arnold AFB, TN.

AUTHORITY

AEDC ltr 23 Jan 1975

THIS PAGE IS UNCLASSIFIED

Cy 2



# **AEROTHERMODYNAMIC CHARACTERISTICS OF THE FULL-SCALE SNAP-27 VEHICLE AT SUPERSONIC AND HYPERSONIC MACH NUMBERS**

**J. B. Carman, Jr.**

**ARO, Inc.**

**September 1966**

This document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of AEC, Sandia Base, Albuquerque, N. M.

**VON KÁRMÁN GAS DYNAMICS FACILITY  
ARNOLD ENGINEERING DEVELOPMENT CENTER  
AIR FORCE SYSTEMS COMMAND  
ARNOLD AIR FORCE STATION, TENNESSEE**

# ***NOTICES***

When U. S. Government drawings, specifications, or other data are used for any purpose other than a definitely related Government procurement operation, the Government thereby incurs no responsibility nor any obligation whatsoever, and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise, or in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Qualified users may obtain copies of this report from the Defense Documentation Center.

References to named commercial products in this report are not to be considered in any sense as an endorsement of the product by the United States Air Force or the Government.

AEROTHERMODYNAMIC CHARACTERISTICS  
OF THE FULL-SCALE SNAP-27 VEHICLE AT  
SUPERSONIC AND HYPERSONIC MACH NUMBERS

J. B. Carman, Jr.  
ARO, Inc.

This document is subject to special export controls  
and each transmittal to foreign governments or foreign  
nationals may be made only with prior approval of  
AEC, Sandia Base, Albuquerque, N. M.

## FOREWORD

The work reported herein was done at the request of the Atomic Energy Commission (AEC) for the General Electric Company (GE) under AEC SNAP-27 Program, AEC Activity No 04.30-01-41 3.

The results of the tests presented were obtained by ARO, Inc (a subsidiary of Sverdrup & Parcel and Associates, Inc.), contract operator of Arnold Engineering Development Center (AEDC), Air Force Systems Command (AFSC), Arnold Air Force Station, Tennessee, under Contract AF40(600)-1200. The test was conducted from April 11 to June 11, 1966, under ARO Project No. VT1674, and the manuscript was submitted for publication on August 3, 1966.

This technical report has been reviewed and is approved.

Donald E. Beitsch  
Major, USAF  
AF Representative, VKF  
Directorate of Test

Leonard T. Glaser  
Colonel, USAF  
Director of Test

**ABSTRACT**

Heat-transfer, pressure, and static force tests were conducted at Mach 4 through 10 to obtain performance and design data on the SNAP-27 fuel cell. The tests were conducted using a full-scale model at free-stream unit Reynolds numbers between  $0.6 \times 10^6$  and  $5.0 \times 10^6$  per foot at angles of attack from -90 to 235 deg. Based upon early test results, the basic configuration was modified, successfully making the vehicle statically stable only at zero angle of attack at Mach 8. This was the only Mach number at which the modified configurations were tested.

## CONTENTS

	<u>Page</u>
ABSTRACT . . . . .	iii
NOMENCLATURE . . . . .	vi
I. INTRODUCTION . . . . .	1
II. APPARATUS	
2.1 Models . . . . .	1
2.2 Wind Tunnels . . . . .	1
2.3 Instrumentation . . . . .	2
III. PROCEDURE	
3.1 Test Conditions . . . . .	3
3.2 Data Reduction . . . . .	3
IV. RESULTS AND DISCUSSION . . . . .	3

## ILLUSTRATIONS

Figure

1. Model Photograph . . . . .	7
2. Model Details	
a. Basic Configuration . . . . .	8
b. Modified Nose Configurations. . . . .	9
c. Modified Flare Configurations . . . . .	10
3. Model Instrumentation	
a. Pressure Model . . . . .	11
b. Heat-Transfer Model . . . . .	12
4. Typical Schlieren Photographs, $M_\infty = 8$ , $Re_\infty = 3.4 \times 10^6$ per foot, Basic Configuration . . . . .	13
5. Mach 10 Stability Characteristics . . . . .	15
6. Stability Characteristics of Several Modified Configurations . . . . .	16
7. Variation of Stability Characteristics with Mach Number, Basic Configuration . . . . .	17
8. Mach 4 Flow Field Instability, Basic Configuration . . . . .	18
9. Typical Mach 8 Pressure and Heat-Transfer Distributions, $Re_\infty = 3.4 \times 10^6$ per foot, Windward Ray, Basic Configuration. . . . .	19

## TABLE

	<u>Page</u>
I. Test Summary . . . . .	20

## NOMENCLATURE

$\delta$	Model skin thickness, ft
$C_{A_T}$	Total axial-force coefficient, axial force/ $q_\infty S$
$C_m$	Pitching-moment coefficient, pitching moment/ $q_\infty S D$
$C_N$	Normal-force coefficient, normal force/ $q_\infty S$
$c$	Specific heat of model material, Btu/lb-°R
$c_p$	Specific heat of air at constant pressure, Btu/lb-°R
$D$	Reference length, model cylinder diameter, 4.00 in.
$H$	Enthalpy, Btu/lb
$M$	Mach number
$p$	Pressure, psia
$q$	Dynamic pressure, psia
$\dot{q}$	Local heat-transfer rate, Btu/ft <sup>2</sup> -sec
$Re$	Unit Reynolds number, per foot
$S$	Reference area, model cylinder area, 12.56 in. <sup>2</sup>
$s$	Distance along model circumference from nose, in.
$St$	Stanton number
$T$	Temperature, °R
$t$	Time, sec
$u$	Velocity, ft/sec
$w$	Model skin density, lb/ft <sup>3</sup>
$\alpha$	Angle of attack, deg
$\rho$	Density, lb/ft <sup>3</sup>
$\phi$	Roll angle, deg
$\varepsilon$	



**SUBSCRIPTS**

A	Model nose conditions at $\alpha = 0$
o	Tunnel stagnation conditions
w	Model wall conditions
$\infty$	Free-stream conditions

## SECTION I INTRODUCTION

The SNAP-27 nuclear fuel cask, as the power generator for the Lunar Excursion Module, is to be landed on the moon where it must operate for one year in its lunar environment. In case of a mission abort resulting in an earth orbit, the SNAP-27 fuel cell must have the capability to re-enter the earth atmosphere intact to avoid radioactive contamination of the atmosphere. The objective of these tests was to provide experimental data to support the aerodynamic and thermodynamic design of the SNAP-27 configuration.

Force, pressure, and heat-transfer tests of a full-scale model of the SNAP-27 vehicle were conducted in the 40-in. supersonic tunnel (Gas Dynamic Wind Tunnel, Supersonic (A)) and the 50-in. hypersonic tunnels (Gas Dynamic Wind Tunnels, Hypersonic (B) and (C)) of the von Kármán Gas Dynamics Facility (VKF). Data were obtained at Mach numbers 4, 5, 6, 8, and 10 at Reynolds numbers between  $0.6 \times 10^6$  and  $5.0 \times 10^6$  per foot. Angle of attack varied from -90 to 235 deg.

## SECTION II APPARATUS

### 2.1 MODELS

Model photographs, details, and instrumentation are shown in Figs. 1, 2, and 3, respectively. The force and pressure models were machined from stainless steel, but the heat-transfer model was fabricated using a thin electroformed nickel shell. All models were furnished by the General Electric Company. For configuration clarity, various noses are defined by the letter N, bases by the letter B, and flaps by the letter F.

### 2.2 WIND TUNNELS

Tunnel A is a continuous, closed-circuit, variable density wind tunnel with an automatically driven flexible-plate nozzle and a 40- by 40-in. test section. The tunnel operates at Mach numbers from 1.5 to 6 at maximum stagnation temperatures up to 300°F ( $M_\infty = 6$ ). Minimum operating pressures are about one-tenth of the maximum at each Mach number.

Tunnels B and C are continuous, closed-circuit, variable density wind tunnels with axisymmetric contoured nozzles and 50-in. -diam test sections. Tunnel B operates at a nominal Mach number of 6 or 8 at stagnation pressures from 20 to 280 and from 50 to 900 psia, respectively, at stagnation temperatures up to 1350°R. Tunnel C operates at a nominal Mach number of 10 at stagnation conditions from 200 to 2000 psia at 1900°R. The model may be injected into the tunnels for a test run and then retracted for model cooling or model changes without interrupting the tunnel flow. A description of the tunnels may be found in the Test Facilities Handbook. \*

### 2.3 INSTRUMENTATION

Model forces and moments were measured with a six-component, moment-type, strain-gage balance supplied and calibrated by VKF. Before testing, combined balance static loadings were applied, simulating the model loading range anticipated during the test. The uncertainties listed below correspond to the differences between the applied loads and the values calculated by the final data reduction balance equations.

<u>Balance Component</u>	<u>Design Load</u>	<u>Maximum Static Loads</u>	<u>Uncertainties</u>
Normal force, lb	700	450	±1.5 lb
Pitching moment, in. -lb	3645	1730	±10 in. -lb
Axial force, lb	150	450	±1.0 lb

Pressures were measured using the standard pressure systems of Tunnels A and B. The Tunnel A system utilizes 15-psid transducers, referenced to a near vacuum, calibrated for ranges of 15, 5, and 1 psia. The precision of the system is estimated to have been within 0.2 percent of full scale of the range being used. Model pressures in Tunnel B were measured with 15-psid transducers, referenced to a near vacuum. From repeat calibrations, the estimated measurement precision was ±0.003 psia or ±0.5 percent, whichever was greater.

The heat-transfer model surface temperature was measured with thermocouples welded to the model inner surface. Thermocouple

---

\*<sup>6th</sup> Test Facilities Handbook (5th Edition). "von Kármán Gas Dynamics Facility, Vol. 4." Arnold Engineering Development Center, July 1963.  
Nov 1966.

outputs were recorded on magnetic tape, at a rate of 20 times per second, from the start of the injection cycle until about 3 sec after the model reached the tunnel centerline. From calibrations of typical thermocouple wires and a knowledge of the system sensitivity and noise level, the precision of the VKF temperature recording system is estimated to have been  $\pm 0.2^\circ\text{R}/\text{sec}$  or  $\pm 2$  percent, whichever was greater.

Model flow field schlieren photographs were obtained for the tests at Mach 6, 8, and 10. Figure 4 shows typical photographs at Mach 8.

### SECTION III PROCEDURE

#### 3.1 TEST CONDITIONS

A summary of the configurations tested is given in Table I. The nominal tunnel conditions at which the tests were conducted are given below.

$M_\infty$	$P_O$ , psia	$T_O$ , $^\circ\text{R}$	$Re_\infty/\text{ft} \times 10^{-6}$
4	11 to 50	555	1.02 to 4.36
5	15 to 110	580 to 620	0.76 to 4.96
6	40 to 180	696 to 752	1.06 to 3.00
8	190 to 800	1240 to 1335	1.85 to 3.42
10	400 to 1400	1730 to 1875	0.58 to 1.70

#### 3.2 DATA REDUCTION

Values of aerodynamic heating rate were calculated using temperature-time data in the relation

$$\dot{q} = wbc \frac{dT_w}{dt}$$

which neglects conduction and radiation losses. Stanton numbers were computed from the relation

$$St = \dot{q} / [\rho_\infty u_\infty (H_o - H_w)]$$

### SECTION IV RESULTS AND DISCUSSION

The Mach 10 longitudinal stability characteristics of two full-scale SNAP-27 configurations are presented in Fig. 5. As may be seen, no

Reynolds number effect was apparent on the basic configuration ( $N_1B_1$ ). Also, the magnitudes of the normal-force, pitching-moment, and total axial-force coefficients for configuration  $N_1B_2$  were slightly greater over the angle-of-attack range because of the larger flare. For both configurations, the peak in axial force near  $\alpha = 147$  deg resulted when the bow wave from the vehicle base intersected the rear face of the nose. Although normal force was not affected, pitching moment was significantly increased, creating a stable trim point near  $\alpha = 158$  deg. Both configurations were also stable at  $\alpha = 0$  and  $180$  deg.

As the vehicle must re-enter the atmosphere with the nose heat shield windward to remain intact, elimination of the trim points at large angles was necessary. Figure 6 shows the stability characteristics of several modified vehicles at Mach 8, the only Mach number at which these modifications were investigated. The  $N_1B_1$  data from Fig. 5, used as a reference, show that the combination Mach number-Reynolds number change did not significantly alter the stability characteristics of the basic configuration. The addition of a 3-in. -long flap to the base of the model ( $N_1B_1F_2$ ) eliminated the stable condition at  $\alpha = 180$  deg, but only reduced the other trim angle from  $\alpha = 158$  deg to near  $\alpha = 147$  deg. However, by then modifying the nose ( $N_2B_1F_2$ ), all the large-angle stability conditions were eliminated. Extending the flap length to 5 in. ( $N_1B_1F_3$ ) accomplished the same result. A modification of the vehicle base proved undesirable, even using the most effective nose and base flap ( $N_2B_3F_3$ ). Stability characteristics near  $\alpha = 0$  deg were not significantly altered by the vehicle modifications because all modified surfaces were located in regions of separated flow at low angles of attack.

Variation of stability characteristics with Mach number is shown in Fig. 7. As expected, normal-force, pitching-moment, and total axial-force coefficients decreased in magnitude with increasing Mach number. The appearance of the apparently double-valued pitching-moment and total axial-force coefficient data at Mach 4 is explained in Fig. 8.

At Mach 4, an intermittent flow occurred in the vehicle flow field between angles of attack of  $-3$  and  $3$  deg. Flow behind the large blunted nose was at times partly attached, then fully separated as illustrated by the pressure distributions of Fig. 8. The flow variation affected pitching moment and axial force on the vehicle as might be expected. Fully separated flow reduced the magnitude of the axial force and pitching moment compared to the partly attached flow. However, for both flow conditions, the vehicle was statically stable at  $\alpha = 0$  deg. Intermittent

flow conditions were also observed at Mach 5 and 6, but no evidence of this variation was observed at the higher Mach numbers (8 and 10) apparently because the flow was more capable of expanding into the cavity behind the blunt nose.

Typical pressure and heat-transfer distributions are presented in Fig. 9. In general, the peaks in both distributions were caused by shock wave interaction as seen in the schlieren photographs of Fig. 4.





Fig. 1 Model Photograph







All Dimensions in Inches

a. Basic Configuration

Fig. 2 Model Details




N<sub>2</sub>N<sub>3</sub>N<sub>4</sub>N<sub>5</sub>



All Dimensions in Inches

b. Modified Nose Configurations


Fig. 2 Continued




Top View  
B<sub>1</sub> with Flaps




B<sub>2</sub>




All Dimensions  
in Inches




Top View  
B<sub>3</sub> with Flaps



c. Modified Flare Configurations  
Fig. 2 Concluded




All Dimensions  
in Inches




a. Pressure Model

Fig. 3 Model Instrumentation




All Dimensions  
in Inches




b. Heat-Transfer Model

Fig. 3 Concluded




$\alpha = 0$  deg




$\alpha = 30$  deg

Fig. 4 Typical Schlieren Photographs,  $M_\infty = 8$ ,  $Re_\infty = 3.4 \times 10^6$  per foot, Basic Configuration



$\alpha = 55 \text{ deg}$



$\alpha = 90 \text{ deg}$

Fig. 4 Concluded




Fig. 5 Mach 10 Stability Characteristics




Fig. 6 Stability Characteristics of Several Modified Configurations






Fig. 7 Variation of Stability Characteristics with Mach Number, Basic Configuration




Fig. 8 Mach 4 Flow Field Instability, Basic Configuration




Fig. 9 Typical Mach 8 Pressure and Heat-Transfer Distributions,  $Re_\infty = 3.4 \times 10^6$  per foot, Windward Ray, Basic Configuration

**TABLE I**  
**TEST SUMMARY**

$M_\infty$	$Re_\infty/\text{ft} \times 10^6$	Configuration	$\phi$ , deg	$\alpha$ , deg	Data Type	
4.02	4.31, 2.72	$N_1B_1$	0	-4.5 to 14.5	Static Stability	
4.01	1.85	↓	↓	↓		
3.98	1.02					
5.06	4.96, 2.75					
5.04	1.83					
5.03	0.76					
5.92	3.00					
5.90	1.90					
8.01	3.31					
↓	↓	$N_1B_1$	↓	-8 to 16		
		$N_1B_1F_3$		↓		
		$N_2B_1F_3$				
		$N_2B_3F_3$				
		$N_1B_1, N_1B_3$		124 to 152		
		$N_2B_1, N_3B_1$		↓		
		$N_4B_1$				
		$N_1B_3F_3$		124 to 180		
		$N_2B_3F_3$		124 to 235		
		$N_1B_1F_2$		124 to 180		
↓	↓	$N_1B_1F_3$	↓	and 194 to 220	Pressure	
		$N_2B_1F_1$		↓		
		$N_2B_1F_2$				
		$N_1B_1F_3$				
		$N_2B_1F_2$		155 to 180		
		$N_2B_1F_2$		↓		
		$N_2B_3F_3$				
		$N_1B_1, N_1B_2$		0 to 180		
		0	↓			
						$N_1B_1$
↓	↓	↓	↓	0 to 55 and 155 to 180	Heat Transfer	
				-4.5 to 14.5		
				↓		
				0 to 14.5		
				-4.5 to 14.5		
				↓		
				0 to 100		
				-90 to 90		
4.02	4.36	↓	↓	↓		
4.01	1.85					
5.07	4.90					
5.86	1.06					
5.91	1.91					
8.01	3.42					
7.98	2.15					
7.92	0.96					
8.01	3.42					
7.97	1.86					
7.92	1.01					

UNCLASSIFIED

Security Classification

## DOCUMENT CONTROL DATA - R&amp;D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1 ORIGINATING ACTIVITY (Corporate author) Arnold Engineering Development Center ARO, Inc., Operating Contractor Arnold Air Force Station, Tennessee		2a REPORT SECURITY CLASSIFICATION UNCLASSIFIED
		2b GROUP N/A
3 REPORT TITLE AEROTHERMODYNAMIC CHARACTERISTICS OF THE FULL-SCALE SNAP-27 VEHICLE AT SUPERSONIC AND HYPERSONIC MACH NUMBERS		
4 DESCRIPTIVE NOTES (Type of report and inclusive dates) N/A		
5 AUTHOR(S) (Last name, first name, initial) Carman, J. B., Jr., ARO, Inc.		
6 REPORT DATE September 1966	7a TOTAL NO. OF PAGES 27	7b NO. OF REFS 1
8a CONTRACT OR GRANT NO. AF 40(600)-1200 b AEC Activity No. 04.30-01-41.3 c d	9a ORIGINATOR'S REPORT NUMBER(S) AEDC-TR-66-167 9b OTHER REPORT NO(S) (Any other numbers that may be assigned this report) N/A	
10 AVAILABILITY/LIMITATION NOTICES Qualified users may obtain copies of this report from DDC. Release to foreign nationals or foreign governments must have prior approval of AEC, Sandia Base.		
11 SUPPLEMENTARY NOTES N/A	12 SPONSORING MILITARY ACTIVITY Atomic Energy Commission Sandia Base, Albuquerque, N.M.	
13 ABSTRACT Heat-transfer, pressure, and static force tests were conducted at Mach 4 through 10 to obtain performance and design data on the SNAP-27 fuel cell. The tests were conducted using a full-scale model at free-stream unit Reynolds numbers between $0.6 \times 10^6$ and $5.0 \times 10^6$ per foot at angles of attack from -90 to 235 deg. Based upon early test results, the basic configuration was modified, successfully making the vehicle statically stable only at zero angle of attack at Mach 8. This was the only Mach number at which the modified configurations were tested.		

14 KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
lunar excursion module SNAP-27 nuclear power generation aerothermodynamic characteristics supersonic flow hypersonic flow force tests pressure tests heat-transfer tests						

## INSTRUCTIONS

1. **ORIGINATING ACTIVITY:** Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (*corporate author*) issuing the report.

2a. **REPORT SECURITY CLASSIFICATION:** Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. **GROUP:** Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. **REPORT TITLE:** Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. **DESCRIPTIVE NOTES:** If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. **AUTHOR(S):** Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. **REPORT DATE:** Enter the date of the report as day, month, year; or month, year. If more than one date appears on the report, use date of publication.

7a. **TOTAL NUMBER OF PAGES:** The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. **NUMBER OF REFERENCES:** Enter the total number of references cited in the report.

8a. **CONTRACT OR GRANT NUMBER:** If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. **PROJECT NUMBER:** Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. **ORIGINATOR'S REPORT NUMBER(S):** Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. **OTHER REPORT NUMBER(S):** If the report has been assigned any other report numbers (*either by the originator or by the sponsor*), also enter this number(s).

10. **AVAILABILITY/LIMITATION NOTICES:** Enter any limitations on further dissemination of the report, other than those

imposed by security classification, using **standard statements** such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through \_\_\_\_\_."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through \_\_\_\_\_."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through \_\_\_\_\_."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. **SUPPLEMENTARY NOTES:** Use for additional explanatory notes.

12. **SPONSORING MILITARY ACTIVITY:** Enter the name of the departmental project office or laboratory sponsoring (*paying for*) the research and development. Include address.

13. **ABSTRACT:** Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. **KEY WORDS:** Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical content. The assignment of links, rules, and weights is optional.