UNCLASSIFIED

AD NUMBER

AD489564

LIMITATION CHANGES

TO:

Approved for public release; distribution is unlimited.

FROM:

Distribution authorized to U.S. Gov't. agencies and their contractors; Administrative/Operational Use; SEP 1966. Other requests shall be referred to Air Force Weapons

AUTHORITY

AFWL ltr 1 Jun 1972

Lab., Kirtland AFB, NM.

THIS PAGE IS UNCLASSIFIED

489564

. 8

150

AFWL-TR-66-62

AFWL-TR 66-62

EFFECTS OF GAMMAS AND NEUTRONS ON LEAD SELENIDE DETECTORS

Peter A. Borgo, 1Lt, USAF

TECHNICAL REPORT NO. AFWL-TR-66-62 September 1966

AIR FORCE WEAPONS LABORATORY Research and Technology Division Air Force Systems Command Kirtland Air Force Base New Mexico

Research and Technology Division AIR FORCE WEAPONS LABORATORY Air Force Systems Command Kirtland Air Force Base New Mexico

When U. S. Government drawings, specifications, or other data are used for any purpose other than a definitely related Government procurement operation, the Government thereby incurs no responsibility nor any obligation whatsoever, and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise, as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

This report is made available for study with the understanding that proprietary interests in and relating thereto will not be impaired. In case of apparent conflict or any other questions between the Government's rights and those of others, notify the Judge Advocate, Air Force Systems Command. Andrews Air Force Base, Washington, D. C. 20331.

This document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of AFWL (WLDE), Kirtland AFB, N.M. 87117. Distribution of this document is limited because of the technology discussed.

6

EFFECTS OF GAMMAS AND NEUTRONS ON LEAD SELENIDE DETECTORS

Peter A. Borgo, 1Lt, USAF

TECHNICAL REPORT NO. AFWL-TR-66-62

This document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of AFWL (WLDE), Kirtland AFB, N.M. Distribution of this document is limited because of the technology discussed.

FOREWORD

This research was performed under Program Element 6.24.05.06.4, Project 5791, Task 579122. Inclusive dates of research were February 1966 to May 1966. The report was submitted 17 July 1966 by the AFWL Project Officer, Lt Peter A. Borgo (WLDE).

This report has been reviewed and is approved.

Peter A. Borgo

PETER A. BORGO 1Lt USAF Project Officer

PARLEY D. CRONQU

Major, USAF Chief, Electronics Branch

arby. Jr. noe C.L GEORGE C. DARBY,

Colonel, USAF Chief, Development Division

ABSTRACT

Objectives of this program were to determine the effect of neutrons from a near nuclear burst on infrared systems. A cooled lead selenide detector $(-80^{\circ}C)$ was radiated, using the fast burst reactor at White Sands Missile Range to provide a neutron flux of approximately 10^{13} neutrons/cm². A series of six bursts was conducted over a 2-day period. Results show a large output from the detector at burst time. The recovery time from this pulse is on the order of from 3 to 5 milliseconds. This is approximately 100 times the burst pulse width. There is some indication that a period of approximately 100-150 milliseconds is required before postburst operation of the detector is exactly equivalent to the preburst operation. Recalibration of the detector after the burst series indicated a very small loss in sensitivity. In general, the postburst noise and resistance figures were slightly higher than the preburst values.

This page intentionally left blank.

iv

*

CONTENTS

Section		Page
I	INTRODUCTION	1
II	TEST PROCEDURES	2
	Nuclear Effects Laboratory Facility	2
	Instrumented Van System	3
	Detector Configuration	3
	Recording Instruments	5
III	TEST RESULTS AND ANALYSIS	6
IV	CONCLUSIONS	13
	DISTRIBUTION	14

v

STORE THE ADDRESS OF THE OWNER.

ILLUSTRATIONS

35

Ŷ

Figure		Page
1	Comparison of Fission Spectra	4
2	Burst 1, Operation Number 951	7
3	Burst 2, Operation Number 946	7
4	Burst 3, Operation Number 947	8
5	Burst 4, Operation Number 948	8
6	Burst 5, Operation Number 949	9
7	Burst 6, Aperation Number 950	9
8	Characteristics of Test Bursts	10
9	Pre- and Post-Burst Detector Calibration	11

TABLES

I	Calculated Performance Characteristics of the WSMR TBR (Pulse Mode)	3
TI	Pre- and Post-Burst Detector Characteristics	12

1

1

SECTION I

INTRODUCTION

Interest has been generated in determining the effect neutrons from a near nuclear burst would have on infrared detection systems. The program described in this paper is a result of this interest.

The Fast Burst Reactor (FBR) at White Sands Missile Range was used to provide a neutron flux that simulated a near nuclear burst situation. A van parked outside of the reactor cell was used as an instrumentation laboratory to record the test data.

General operation characteristics of the FBR along with the van data gathering procedures are presented in the following sections. A compilation and discussion of results is also presented.

SECTION 11

TEST PROCEDURES

1. Nuclear Effects Laboratory Facility

The Nuclear Effects Laboratory (NEL) is located in south central New Mexico about 3 miles southeast of the central facilities of the White Sands Missile Range. NEL is a unit within the Electro-Mechanical Laboratories of the White Sands Army Missile Test and Evaluation Directorate*.

The NEL consists of two sections. One section is a laboratory building housing a gamma LINAC, a Pulsed Neutron Generator, and various supporting activities such as a health physics department, radioactive storage areas, etc. The other section is the Fast Burst Reactor Facility.

The FBR is housed in a 38-foot deep pit. The reactor is raised into a 50foot square concrete chamber for firing.

Any experiments to be radiated are placed in this chamber at various distances from the reactor core. Provisions are made for cabling through conduits to allow self-contained instrumentation vans to be used for data acquisition from a parking area outside of the cell.

The FBR is an unreflected and unmoderated critical assembly that consists of a right circular cylinder and four controlling components fabricated from Jranium Molybdenum alloy (U-10 w/o Mo Fuel).

The alloying of uranium with molybdenum improves the dimensional stability by retaining a crystalline structure (gamma phase) of greater stability and strength. The FBR is capable of producing both high yield, short duration neutron pulses and steady state operations up to 10 kilowatts of power. The pulse mode was used throughout this program. Burst performance characteristics are presented in table I.

Nuclear Effects Laboratory Technical Report on Radiation Facilities (dated December 1963) prepared by William M. Cole.

Table I

CALCULATED PERFORMANCE CHARACTERISTICS OF THE WSMR	FBR (PULSE MODE)
Burst Yield, fissions	2×10^{17}
Integrated neutron flux, 1 inch from > reactor surface (neutrons/cm ²)	2×10^{14}
Peak instantaneous gamma ray dose (rads/sec)	3×10^8
Burst half-width (µsec)	50
Average Temperature rise (°C)	250-350

The FBR provides an excellent source of neutrons and gamma radiation for the simulation of nuclear weapon environments. Figure 1 is a comparison of the watt's fission spectrum, fission weapon spectrum, and the FBR spectrum. The ratio of neutron dose to gamma dose is approximately 10 to 1.

2. Instrumented Van System

a. Detector Configuration

The detector was mounted in a small glass dewar. A Copper-Constant m thermocouple was also installed in the dewar to monitor detector cooling. This entire unit was housed in an aluminum box with a small hole for the detector to "look" out of. A 6-volt incandescent light was mounted to the box directly in front of the small hole. The light was pulsed on and off before, during, and after each burst. Provisions were made to record the thermocouple and detector outputs and the light pulse. The detector used in this program was lead selenide cooled by liquid Freon 13 to approximately -80°C. The detector was biased with 26.5 vdc through a 1 megohm load. The detector resistance varied from 350 kilohms at ambient temperature to approximately 5 meghoms when cooled. The measured noise voltage and D* before the test series, were 50 µvolts rms and 4.5 × 10^9 cm cps^{1/2} watt⁻¹ at -80°C, 780 cps respectively.





10%

a. Recording Instruments

A dual recording system was used to ensure data recovery in case of a partial malfunction. An Ampex AR200 magnetic tape recorder was used as the primary system with a Honeywell 1508 visicorder as backup. The tape recorder was run in an FM record mode at 7.5 ips. A 2,500 cps bandwidth is obtained. The visicorder was run at 20 ips and used fluid damped galvanometers having a 5,000 cps response. The detector output was measured on a VTVM before and after each burst, as was the thermocouple output.

Data outputs for all the bursts were monitored through 250 feet of RG58 coaxial cable from the reactor cell.

SECTION III

TEST RESULTS AND ANALYSIS

The results of the burst series have been reproduced from the magnetic tape data and are presented in figures 2 through 7. In each case, the time of burst is indicated by the large peak in detector output. The smaller periodic peaks are due to the flashing light used as a standard source in all bursts.

The recovery time of the detector from the initial pulse is evident along with the longer recovery time to normal output operation. In all cases, the pulse recovery time was on the order of 100 times the FBR pulse width. Approximately 100-150 milliseconds was required for the detector to resume normal amplitude outputs.

Figure 8 shows the gamma dose and neutron flux received for each of the six bursts. On two of the bursts (operation number 948 and 951) a measure of gamma dose was not obtained.

Figure 9 is a composite plot showing detector calibration before and after the test series. The closeness of the two curves indicates that the detector experienced very little permanent damage if any.

Table 2 is a listing of pertinent detector characteristics before and after the burst series.

e

S.



Figure 2. Burst 1, Operation Number 951.



Figure 3. Burst 2, Operation Number 946.







Figure 5. Burst 4, Operation Number 948.

新作。 马克·西勒 境



Figure 6. Burst 5, Operation Number 949.



Figure 7. Burst 6, Operation Number 950.

9

a Burn Station

Figure 8. Characteristics of Test Bursts.

€∦.

10



Figure 9. Pre- and Post-Burst Detector Calibration.

AFWL-TR-66-62

8

Table II

PRE- AND POST-BURST DETECTOR CHARACTERISTICS

Parameter		Before Burst Series	After Burst Series			
Warm	Resistance	350K ohms	400K ohms			
Co1d	Resistance	5 Meg ohms	9 Meg ohms			
Warm	Noise	50 µvolts	80 µvolts			

NOTE: Parameters were measured with a one-megohm load and +30 volts DC detector bias.

ż

SECTION IV

CONCLUSIONS

The results of this test series indicate that a lead selenide detector exhibits a high degree of radiation hardness. The rapid recovery from the simulated nuclear burst is encouraging. Even more so is the apparent small degree of permanent damage as a result of a test series that totals a substantial integrated neutron flux. The small difference in the detector calibration curves could be due to experimental variations.

The largest effect of the radiation exposure appears to be in changes of detector resistance and an increase in detector noise. This would result in effectively making the detector less sensitive to small signals.

DISTRIBUTION

No. cys	
	MAJOR AIR COMMANDS
	ADC, Ent AFB, Colo 80912
1	(ADLPW)
1	(ADOOP)
1	AUL, Maxwell AFB, Ala 30112
	AFSC ORGANIZATIONS
1	FID (TDBTL), Wright-Patterson AFB, Ohio 45433
1	AF Ms1 Dev Cen (RRRT), Holloman AFB, NM 88330
1	APGC (PGBPS-12), Eglin AFB, Fla 32542
1	RADC (EMLAL-1), Griffiss AFB, NY 13442
	KIRTLAND AFB ORGANIZATIONS
1	AFSWC (SWEH), Kirtland AFB, NM 87117
1	ADC (ADSWO), Special Weapons Office, Kirtland AFB, NM 87117
1	TAC Liaison Office (TACLO-S), AFSWC, Kirtland AFB, NM 87117
	AFWL, Kirtland AFB, NM 87117
10	(WLIL)
5	(WLDE)
	OTHER AIR FORCE AGENCIES
1	AFCRL, L.G. Hanscom Fld, Bedford, Mass 01731
	ARMY ACTIVITIES
1	Director, US Army Engineer Research and Development Laboratories, ATTN: STINFO Branch, Ft Belvoir, Va 20260
	NAVY ACTIVITIES
1	Commander, Naval Ordnance Laboratory, ATTN: Dr. Rudlin, White Oak Silver Spring, Md 20910
J.	Commander, Naval Ordnance Laboratory, Corona, Calif 91720
1	Commanding Officer, NWEF (Code 404), Kirtland AFB, NM 87117
	OTHER DOD ACTIVITIES
20	DDC (TIAAS), Cameron Station, Alexandria, Va 22314

¢,

Q

DISTRIBUTION (cont'd)

No. cys

OTHER

- 1 Massachusetts Institute of Technology, Lincoln Laboratory (Document Library), P.O. Box 73, Lexington, Mass 02173
- 1 Official Record Copy (WLDE/Lt Borgo)

\$

This page intentionally left blank.

Ð

DOCUM	ENT CONTROL DAT	. P&D			
(Security classification of title, body of abstract	and indexing annotation mu	et be entered what	the overall report is classified)		
1. ORIGINATING ACTIVITY (Corporate author)		24. REP	24. REPORT SECURITY CLASSIFICATION		
Air Force Weapons Laboratory ((WLDE)	Unc	Unclassified		
Kirtland Air Force Base, New Mexico 87117		2 b GRO	90		
REPORT TITLE	· · ·				
EFFECTS OF GAMMAS AND NEUTRONS	S ON LEAD SELENII	DE DETECTOR	5		
- DESCRIPTIVE NOTES (Type of report and inclusive	dates)				
February 1966 to May 1966					
3. AUTHOR(S) (Lest name, first name, initial)					
Borgo, Peter A., 1Lt, USAF					
REPORT DATE	78 TOTAL NO	OF PAGES	75. NO. OF REFS		
September 1966		2			
A. CONTRACT OR GRANT NO.	94. ORIGINAT	OR'S REPORT NU	MBER(S)		
· · · ·	4				
5. PROJECT NO. 5/91	AFWL-1	R-66-62			
• Task No. 579124	S. OTHER R	PORT NO(S) (A	y other numbers that may be essioned		
	this report)				
d					
10. AVAILABILITY/LIMITATION NOTICES This	document is sub	ject to sp	ecial export controls		
and each transmittal to foreign	governments or i	oreign nat	ionals may be made only		
with prior approval of AFWL (WLD)E), Kirtland AFE	, N.M. 871	17. Distribution of		
this document is limited because	of the technold	gy discuss	ed.		
1. SUPPI SMENTARY NOTES	12. SPONSORI	G MILITARY AC			
11. SUPPLEMENTARY NOTES	12 SPONSORIA	IG MILITARY AC	FIVITY		
11. SUPPLEMENTARY NOTES	12 SPONSORIN AFWL (V Kirtlar	IG MILITARY AC TLDE) Md AFB, N.M			
11. SUPPLEMENTARY NOTES	12 SPONSORIA AFWL (V Kirtlar	IG MILITARY AC ILDE) Id AFB, N.M	· · · · · · · · · · · · · · · · · · ·		
11. SUPPLEMENTARY NOTES	12 SPONSORN AFWL (V Kirtlar	IG MILITARY AC ILDE) Id AFB, N.M	FIVITY		
11. SUPPLEMENTARY NOTES	12 SPONSORIN AFWL (V Kirtlar	IG MILITARY AC ILDE) Id AFB, N.M	FIVITY		
Objectives of this program were	to determine the	AG MILITARY AC ALDE) ad AFB, N.M e effect of	neutrons from a near		
 SUPPLEMENTARY NOTES ABSTRACT Objectives of this program were nuclear burst on infrared system 	to determine the	d AFB, N.M e effect of selenide	neutrons from a near detector (-80°C) was		
 SUPPLEMENTARY NOTES ABSTRACT Objectives of this program were nuclear burst on infrared system radiated, using the fast burst r 	to determine the seactor at White	e effect of Sands Miss	neutrons from a near detector (-80°C) was ile Range to provide		
 SUPPLEMENTARY NOTES ABSTRACT Objectives of this program were nuclear burst on infrared system radiated, using the fast burst r a neutron flux of approximately 	to determine the s. A cooled lea reactor at White 10 ¹³ neutrons/cn	e effect of d selenide Sands Miss	neutrons from a near detector (-80°C) was the Range to provide es of six bursts was from the detector at		
 SUPPLEMENTARY NOTES ABSTRACT Objectives of this program were nuclear burst on infrared system radiated, using the fast burst r a neutron flux of approximately conducted over a 2-day period. 	to determine the s. A cooled leave reactor at White 10 ¹³ neutrons/cm Results show a l	e effect of d selenide Sands Miss ² . A serie arge outpu	neutrons from a near detector (-80°C) was ile Range to provide es of six bursts was t from the detector at		
 SUPPLEMENTARY NOTES ABSTRACT Objectives of this program were nuclear burst on infrared system radiated, using the fast burst r a neutron flux of approximately conducted over a 2-day period. burst time. The recovery time f 	to determine the s. A cooled lease ceactor at White 10 ¹³ neutrons/cm Results show a light from this pulse d	e effect of d AFB, N.M e effect of d selenide Sands Miss ² . A serio arge output s on the other	neutrons from a near detector (-80°C) was the Range to provide es of six bursts was t from the detector at rder of from 3 to 5 the width. There is		
 SUPPLEMENTARY NOTES ABSTRACT Objectives of this program were nuclear burst on infrared system radiated, using the fast burst r a neutron flux of approximately conducted over a 2-day period. burst time. The recovery time f milliseconds. This is approxima 	to determine the s. A cooled leave reactor at White 10 ¹³ neutrons/cm Results show a light to this pulse in the pulse in the pulse in	e effect of d AFB, N.M e effect of d selenide Sands Miss ² . A serio arge output s on the or the burst pr	neutrons from a near detector (-80°C) was ile Range to provide es of six bursts was t from the detector at rder of from 3 to 5 alse width. There is iseconds is required		
 SUPPLEMENTARY NOTES ABSTRACT Objectives of this program were nuclear burst on infrared system radiated, using the fast burst r a neutron flux of approximately conducted over a 2-day period. burst time. The recovery time f milliseconds. This is approxima some indication that aperiod of before perturb operation of the 	to determine the s. A cooled lease reactor at White 10 ¹³ neutrons/cm Results show a light from this pulse d tely 100 times to approximately 100	e effect of d AFB, N.M e effect of d selenide Sands Miss ² . A serio arge output s on the or the burst po 0-150 mill	neutrons from a near detector (-80°C) was ile Range to provide es of six bursts was t from the detector at rder of from 3 to 5 ilse width. There is iseconds is required valent to the preburst		
1. SUPPLEMENTARY NOTES 3. ABSTRACT Objectives of this program were nuclear burst on infrared system radiated, using the fast burst r a neutron flux of approximately conducted over a 2-day period. burst time. The recovery time f milliseconds. This is approxima some indication that aperiod of before postburst operation of the	to determine the AFWL (W Kirtlar to determine the s. A cooled leas reactor at White 10 ¹³ neutrons/cm Results show a l from this pulse d itely 100 times t approximately 10 te detector is ex-	e effect of d AFB, N.M e effect of d selenide Sands Miss ² . A serio arge output s on the or the burst pro- 150 mill actly equint	neutrons from a near detector (-80°C) was ile Range to provide es of six bursts was t from the detector at rder of from 3 to 5 alse width. There is iseconds is required valent to the preburst peries indicated a		
1. SUPPLEMENTARY NOTES 3. ABSTRACT Objectives of this program were nuclear burst on infrared system radiated, using the fast burst r a neutron flux of approximately conducted over a 2-day period. burst time. The recovery time f milliseconds. This is approxima some indication that aperiod of before postburst operation of the operation. Recalibration of the very small loss in vensitivity.	to determine the AFWL (W Kirtlar to determine the s. A cooled les eactor at White 10 ¹³ neutrons/cm Results show a l from this pulse d tely 100 times t approximately 10 te detector is ex- e detector after In general, the	e effect of d AFB, N.M e effect of d selenide Sands Miss ² . A serio arge output s on the or he burst p 0-150 mill actly equiv the burst	neutrons from a near detector (-80°C) was ile Range to provide es of six bursts was t from the detector at rder of from 3 to 5 alse width. There is lseconds is required valent to the preburst series indicated a noise and resistance		
 SUPPLEMENTARY NOTES ABSTRACT Objectives of this program were nuclear burst on infrared system radiated, using the fast burst r a neutron flux of approximately conducted over a 2-day period. burst time. The recovery time f milliseconds. This is approxima some indication that aperiod of before postburst operation of th operation. Recalibration of the very small loss in sensitivity. figures were slightly higher tha 	to determine the AFWL (W Kirtlar to determine the s. A cooled leas reactor at White 10 ¹³ neutrons/cm Results show a l from this pulse d tely 100 times t approximately 10 te detector is ex detector after In general, the	e effect of d AFB, N.M e effect of d selenide Sands Miss ² . A serio arge output s on the or he burst pu- 10-150 mill: actly equip the burst postburst alues.	neutrons from a near detector (-80°C) was ile Range to provide es of six bursts was t from the detector at rder of from 3 to 5 alse width. There is iseconds is required valent to the preburst series indicated a noise and resistance		
1. SUPPLEMENTARY NOTES 3. ABSTRACT Objectives of this program were nuclear burst on infrared system radiated, using the fast burst r a neutron flux of approximately conducted over a 2-day period. burst time. The recovery time f milliseconds. This is approxima some indication that aperiod of before postburst operation of the operation. Recalibration of the very small loss in sensitivity. figures were slightly higher tha	to determine the AFWL (W Kirtlar to determine the s. A cooled leas reactor at White 10 ¹³ neutrons/cm Results show a l from this pulse is the ly 100 times to approximately 10 the detector is ex- tendetector after In general, the in the preburst w	e effect of ad AFB, N.M e effect of ad selenide Sands Miss ² . A serie arge output son the or he burst pr 0-150 mill actly equiv the burst postburst alues.	neutrons from a near detector (-80°C) was ile Range to provide es of six bursts was t from the detector at rder of from 3 to 5 ilse width. There is iseconds is required valent to the preburst series indicated a noise and resistance		
1. SUPPLEMENTARY NOTES 3. ABSTRACT Objectives of this program were nuclear burst on infrared system radiated, using the fast burst r a neutron flux of approximately conducted over a 2-day period. burst time. The recovery time f milliseconds. This is approxima some indication that aperiod of before postburst operation of the operation. Recalibration of the very small loss in sensitivity. figures were slightly higher tha	to determine the AFWL (W Kirtlar to determine the s. A cooled les eactor at White 10 ¹³ neutrons/cm Results show a l from this pulse d tely 100 times t approximately 10 te detector is ex e detector after In general, the in the preburst w	e effect of d AFB, N.M e effect of d selenide Sands Miss ² . A serio arge output s on the or he burst pu- 0-150 mill actly equiv the burst postburst alues.	neutrons from a near detector (-80°C) was ile Range to provide es of six bursts was t from the detector at rder of from 3 to 5 alse width. There is iseconds is required valent to the preburst series indicated a noise and resistance		
1. SUPPLEMENTARY NOTES 1. ABSTRACT Objectives of this program were nuclear burst on infrared system radiated, using the fast burst r a neutron flux of approximately conducted over a 2-day period. burst time. The recovery time f milliseconds. This is approxima some indication that aperiod of before postburst operation of the operation. Recalibration of the very small loss in sensitivity. figures were slightly higher tha	to determine the AFWL (W Kirtlar to determine the s. A cooled leas reactor at White 10 ¹³ neutrons/cm Results show a l from this pulse d tely 100 times t approximately 10 te detector is ex detector after In general, the in the preburst v	e effect of d AFB, N.M e effect of d selenide Sands Miss ² . A serio arge output s on the or he burst pu- 10-150 mill actly equiv the burst postburst alues.	neutrons from a near detector (-80°C) was ile Range to provide es of six bursts was t from the detector at rder of from 3 to 5 alse width. There is iseconds is required valent to the preburst series indicated a noise and resistance		
1. SUPPLEMENTARY NOTES 3. ABSTRACT Objectives of this program were nuclear burst on infrared system radiated, using the fast burst r a neutron flux of approximately conducted over a 2-day period. burst time. The recovery time f milliseconds. This is approxima some indication that aperiod of before postburst operation of the operation. Recalibration of the very small loss in sensitivity. figures were slightly higher tha	to determine the AFWL (W Kirtlar to determine the s. A cooled leas reactor at White 10 ¹³ neutrons/cm Results show a l from this pulse is tely 100 times to approximately 10 te detector is ex- e detector after In general, the in the preburst w	e effect of ad AFB, N.M e effect of ad selenide Sands Miss ² . A serie arge output s on the of the burst p 0-150 mill actly equiv the burst alues.	neutrons from a near detector (-80°C) was ile Range to provide es of six bursts was t from the detector at rder of from 3 to 5 ilse width. There is lseconds is required valent to the preburst series indicated a noise and resistance		
1. SUPPLEMENTARY NOTES 3. ABSTRACT Objectives of this program were nuclear burst on infrared system radiated, using the fast burst r a neutron flux of approximately conducted over a 2-day period. burst time. The recovery time f milliseconds. This is approxima some indication that aperiod of before postburst operation of the very small loss in sensitivity. figures were slightly higher tha	12. SPONSORIN AFWL (W Kirtlar to determine the seactor at White 10 ¹³ neutrons/cm Results show a l trom this pulse d tely 100 times t approximately 10 te detector is ex e detector after In general, the in the preburst w	e effect of ad AFB, N.M e effect of ad selenide Sands Miss ² . A serio arge output s on the or he burst pro- 0-150 mill actly equiv- the burst postburst alues.	neutrons from a near detector (-80°C) was the Range to provide es of six bursts was t from the detector at rder of from 3 to 5 alse width. There is detected a series indicated a noise and resistance		
Objectives of this program were nuclear burst on infrared system radiated, using the fast burst r a neutron flux of approximately conducted over a 2-day period. burst time. The recovery time f milliseconds. This is approxima some indication that aperiod of before postburst operation of th operation. Recalibration of the very small loss in sensitivity. figures were slightly higher tha	to determine the AFWL (W Kirtlar to determine the s. A cooled leas reactor at White 10 ¹³ neutrons/cm Results show a l from this pulse d tely 100 times t approximately 10 te detector is ex e detector after In general, the in the preburst v	e effect of d AFB, N.M e effect of d selenide Sands Miss ² . A serio arge output s on the or he burst pr 0-150 mill actly equiv the burst postburst alues.	neutrons from a near detector (-80°C) was ile Range to provide es of six bursts was t from the detector at rder of from 3 to 5 alse width. There is iseconds is required valent to the preburst series indicated a noise and resistance		
D) SUPPLEMENTARY NOTES D) ABSTRACT Objectives of this program were nuclear burst on infrared system radiated, using the fast burst r a neutron flux of approximately conducted over a 2-day period. burst time. The recovery time f milliseconds. This is approxima some indication that aperiod of before postburst operation of the operation. Recalibration of the very small loss in sensitivity. figures were slightly higher tha	to determine the AFWL (W Kirtlar to determine the s. A cooled les reactor at White 10 ¹³ neutrons/cm Results show a l from this pulse i tely 100 times t approximately 10 te detector is ex detector after In general, the in the preburst w	effect of d AFB, N.M effect of d selenide Sands Miss ² . A serie arge output s on the or he burst pr 0-150 mill actly equiv the burst alues.	neutrons from a near detector (-80°C) was ile Range to provide es of six bursts was t from the detector at rder of from 3 to 5 ilse width. There is iseconds is required valent to the preburst series indicated a noise and resistance		
D) SUPPLEMENTARY NOTES Objectives of this program were nuclear burst on infrared system radiated, using the fast burst r a neutron flux of approximately conducted over a 2-day period. burst time. The recovery time f milliseconds. This is approxima some indication that aperiod of before postburst operation of the operation. Recalibration of the very small loss in sensitivity. figures were slightly higher tha	12 SPONSORIN AFWL (W Kirtlar to determine the seactor at white 10 ¹³ neutrons/cm Results show a l trom this pulse d tely 100 times t approximately 10 te detector is ex e detector after In general, the in the preburst w	e effect of ad AFB, N.M e effect of ad selenide Sands Miss ² . A serio arge output s on the or the burst pro- 150 mill actly equivate postburst alues.	neutrons from a near detector (-80°C) was the Range to provide es of six bursts was t from the detector at rder of from 3 to 5 alse width. There is desconds is required valent to the preburst series indicated a noise and resistance		

DD 15484 14/3

The second s

ł

Ļ

Unclassified Security Classification

		-		_	_			
4. KEY WORDS		LIN	KA				KC	
Infrared detectors Radiation hardening (gammas, neutrons) Lead Selenide detectors								
						-		
INS 1. ORIGINATING ACTIVITY: Enter the name and address of the contractor, subcontractor, grantee, Department of De- fense activity or other organization (corporate author) issuin the report.	FRUCTIONS imposed t such as: (1) '	Qualified	ciassific requester DC.''	cation, u rs may of	sing stand	dard state les of this	ments s	
 REPORT SECURITY CLASSIFICATION: Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking in to be in accordance with appropriate security regulations. GROUP: Automatic downgrading is specified in DoD D: "ective 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optiona markings have been used for Group 3 and Group 4 as authorized. REPORT TITLE: Enter the complete report title in all 	 (?) "Foreign announcement and dissemination of this report by DDC is not authorized." (3) "U. 3. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through (4) "U. 5. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through 							
capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classifica- ler, show title classification in all capitals in parenthesis immediately following the title. A. DESCRIPTIVE NOTES: If appropriate, enter the type of	(5)	'All distri	oution of sers sha	this repo 11 reques	rt is cont t through	rolied. Q	'' ual- .''	
report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered. 5. AUTHOR(S): Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. (f militery, show rank and branch of service. The name of	If the Services, cate this 11, SUP5 tory notes	report has Departmen fact and en LEMENT	been fur t of Com tor the p ARY NOT	nished to merce, fo rice, if k 'ES: Use	the Offic r sale to nown for addition	tional exp	hnicul 2, indi- 1ana-	
he principal author is an absolute minimum requirement. i. REPORT DATE: Enter the date of the report as day, nonth, year; or month, year. If more than one date appears in the report, use date of publication. A. TOTAL NUMBER OF PAGES: The total page count bould follow more procedures i.e. enter the	12. SPON the depart ing for) the 13. ABST summary of it may also	VSORING A mental pro- ie research RACT: E of the docu o appear e	ILLITARY ject office and deve nter an a ment indi laewhere	ACTIV te or labo slopment. batract g icalive of in the bo	TY: Ent pratory ap Include iving a ba the repo ody of the	er the nur onworing (address, rief and fa rt, even the technica	ne of (pay- ictual hough 1 re-	
number of pages containing information. 'b. NUMBER OF REFERENCES: Enter the total number of eferences cited in the report. b. CONTRACT OR GRANT NUMBER: If eppropriate, enter	port. If ac be attached It is i be unclass an indicat	id. highly des lified. Ea ion of the	rable that ch paragr military a	equired, t the abs sph of th scurity of	tract of c abstract lassifica	lausified t shall en tion of th	report id with e in-	
ne applicable number of the contract of grant under which he report was written. a, ac, a ad. PROJECT NUMBER: Enter the appropriate ulitary department identification, such as project number, ubproject number, system numbers, task number, etc. a. ORIGINATOR'S REPORT NUMBER(S): Enter the offi- ial report number by which the document will be identified ad controlled by the originating activity. This number must 9 unique to this report.	There ever, the s 14. KEY or short ph indox entri selected s filers, such project cos	WORDS: B WORDS: B Transs that les for cat o that no s as equipt de name, a	graph, fo tation on length is characte aloging th security c nent mode sographic	the leng from 150 are tech rize a re he report. lassifica of design c location	th of the to 225 w port and i Key wo tion is m ation, transition,	abstract. ords. neaningful may be us rds must 1 quired. I de name, used as 1	How- terms od as be denti- milita key	

APEC (KAPE NM)

10. AVAILABILITY/LIMITATION NOTICES: Enter any limitations on further dissemination of the report, other than those

÷

Unclassified Security Classification 10

64

Q