

UNCLASSIFIED

AD NUMBER

AD489777

LIMITATION CHANGES

TO:

Approved for public release; distribution is unlimited.

FROM:

Distribution authorized to U.S. Gov't. agencies and their contractors;
Administrative/Operational Use; OCT 1966. Other requests shall be referred to Arnold Engineering Development Center, Arnold AFB, TN.

AUTHORITY

AEDC ltr 25 May 1977

THIS PAGE IS UNCLASSIFIED

C. 2
OCT 20 1966
JUN 25 1968
SEP 19 1968



**PERFORMANCE OF THE AEROJET-GENERAL CORPORATION
ALCOR 1B SOLID-PROPELLANT ROCKET MOTOR
UNDER THE COMBINED EFFECTS
OF ROTATIONAL SPIN AND SIMULATED ALTITUDE**

**L. R. Bahor
ARO, Inc.**

October 1966

This document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of BSD.

*This document is for release
per TAB 77-19
9/16/97*

**ROCKET TEST FACILITY
ARNOLD ENGINEERING DEVELOPMENT CENTER
AIR FORCE SYSTEMS COMMAND
ARNOLD AIR FORCE STATION, TENNESSEE**

NOTICES

When U. S. Government drawings specifications, or other data are used for any purpose other than a definitely related Government procurement operation, the Government thereby incurs no responsibility nor any obligation whatsoever, and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise, or in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Qualified users may obtain copies of this report from the Defense Documentation Center.

References to named commercial products in this report are not to be considered in any sense as an endorsement of the product by the United States Air Force or the Government.

PERFORMANCE OF THE AEROJET-GENERAL CORPORATION
ALCOR 1B SOLID-PROPELLANT ROCKET MOTOR
UNDER THE COMBINED EFFECTS
OF ROTATIONAL SPIN AND SIMULATED ALTITUDE

L. R. Bahor
ARO, Inc.

This document is subject to special export controls
and each transmittal to foreign governments or foreign
nationals may be made only with prior approval of
BSD.

FOREWORD

The test program reported herein was conducted at the request of the Ballistic Systems Division (BSD) (BSRPT), Air Force Systems Command (AFSC), for the Aerojet-General Corporation under Program Element 64406124, System 627A.

The results of the tests were obtained by ARO, Inc. (a subsidiary of Sverdrup & Parcel and Associates, Inc.), contract operator of the Arnold Engineering Development Center (AEDC), AFSC, Arnold Air Force Station, Tennessee, under Contract AF40(600)-1200. The test was conducted in Propulsion Engine Test Cell (T-3) of the Rocket Test Facility (RTF) on July 20, 1966, under ARO Project No. RC0638, and the manuscript was submitted for publication on September 1, 1966.

This technical report has been reviewed and is approved.

John W. Hitchcock
Major, USAF
AF Representative, RTF
Directorate of Test

Leonard T. Glaser
Colonel, USAF
Director of Test

ABSTRACT

One Aerojet-General Corporation, Alcor 1B, solid-propellant rocket motor was successfully tested at an average simulated altitude of 100,000 ft while spinning about its axial centerline at an average spin rate of 304.3 rpm. The objective of this test was to evaluate the ballistic performance, tailoff characteristics, and structural integrity of the flightweight motor assembly under the combined effects of rotational spin and near-vacuum environment. The vacuum total impulse was 256,616 lbf-sec; the vacuum specific impulse, based on the vacuum total impulse and pre- and post-fire weight difference, was 279.12 lbf-sec/lbm. The total burn time, defined as the time interval from the application of voltage to the igniter to the time when the chamber pressure-to-cell pressure ratio is 1.3, was 35.30 sec.

CONTENTS

	<u>Page</u>
ABSTRACT.	iii
NOMENCLATURE.	vi
I. INTRODUCTION	1
II. APPARATUS	1
III. PROCEDURE	4
IV. RESULTS AND DISCUSSION	5
V. SUMMARY OF RESULTS	7
REFERENCES	10

ILLUSTRATIONS

Figure

1. Aerojet-General Corporation Alcor 1B Solid-Propellant Rocket Motor	
a. Schematic	11
b. Pre-Fire Photograph	12
2. Igniter Assembly	
a. Schematic	13
b. Photograph	14
3. Installation of the Alcor 1B Rocket Motor in the T-3 Test Cell	
a. Schematic	15
b. Photograph	16
4. Schematic of Thermocouple Locations	17
5. Analog Trace of Ignition Event.	18
6. Variation of Thrust, Chamber Pressure, and Cell Pressure during Firing.	19
7. Low Range Chamber Pressure from Diffuser Breakdown to Chamber Pressure Equal to 12 psia	20
8. Low Range Chamber Pressure from 12 psia to Chamber Pressure-to-Cell Pressure Ratio Equal to 1.3	21
9. Definition of Vacuum Total and Critical Impulse	22
10. Detail of Products of Combustion Deposited on the Nozzle Exit.	23

<u>Figure</u>	<u>Page</u>
11. Temperature History for Alcor 1B Rocket Motor	
a. Forward and Aft Dome Temperatures.	24
b. Temperature on the Cylindrical Portion of the Chamber.	25

TABLES

I. Instrumentation.	27
II. Summary of Motor Performance	28
III. Summary of Motor Physical Dimensions	29

NOMENCLATURE

A_{ex}	Nozzle exit area
A_{th}	Nozzle throat area
c_f	Vacuum thrust coefficient
F	Measured axial thrust
F_{vac}	Vacuum corrected axial thrust
$I_{vac_{action}}$	Vacuum corrected impulse based on action time
$I_{vac_{critical}}$	Vacuum corrected impulse based on critical time
$I_{vac_{total}}$	Vacuum corrected impulse based on total time
P_{cell}	Measured cell pressure
P_{ch}	Measured chamber pressure
t_a	Time from 100-psia chamber pressure at ignition to 100-psia chamber pressure at tailoff
t_{bd}	Time of nozzle flow breakdown
t_c	Time from t_0 to 30-psia chamber pressure at tailoff
t_d	Time from t_0 to 100-psia chamber pressure at ignition
t_0	Time of application of voltage to the igniter
t_t	Time from first indication of thrust or chamber pressure until curve decays to zero

SECTION I INTRODUCTION

The four-stage, partially guided, Athena booster is a solid-propellant re-entry test vehicle used to place a payload at a designated point in space and at certain specified conditions so that useful re-entry experiments may be performed.

The vehicle consists of first- and second-stage boosters and a re-entry package consisting of the third and fourth stages and the payload. The third and fourth stages of the vehicle are used to drive a 50-lbm payload back into the atmosphere at a speed of about 22,000 ft/sec. Staging is controlled by a time sequence based on the predicted performance of each motor, whereas the trajectory and impact point are dependent on in-flight ballistic performance (Ref. 1).

The data from the most recent static test firing of the Alcor 1B motor indicated an abnormally long tailoff. Consequently, a test program was conducted to document the tailoff characteristics and ballistic performance of the Aerojet Alcor 1B when fired under the combined effects of simulated altitude and 300-rpm rotational spin.

One Aerojet Alcor 1B, solid-propellant rocket motor was fired at an average simulated altitude of 100,000 ft while rotating about its axial centerline at approximately 300 rpm. Ignition and tailoff characteristics are discussed along with motor ballistic performance.

SECTION II APPARATUS

2.1 TEST ARTICLE

The Aerojet Alcor 1B, solid-propellant rocket motor (Fig. 1) has a titanium alloy case (proof-pressure-from 645 to 650 psi) with a nominal outside diameter of 20.52 in. and a length of 55.16 in. The overall length of the motor with the 16.3:1 area ratio nozzle installed is 76.10 in. The motor case is insulated throughout with 0.075-in.-thick Elastomer Gen-Gard V-44 and V-45 rubber.

The Aerojet Alcor 1B (Fig. 1a) is loaded with 913.7 lb_m of Aerojet ANB-3066 Type III Polybutadiene propellant. The propellant is cast in a modified 6-point-star configuration with the star points every 60 deg.

The loaded motor weighs approximately 1000 lb_m. Nominal motor performance is: thrust, 10,000 lbf; chamber pressure, 528 psia; and action time, 25.6 sec.

The 16.3:1 area ratio contoured nozzle has a nominal exit half-angle of 14 deg. The glass roving, epoxy-impregnated nozzle exit cone is attached to the motor case by means of a 4130 steel adapter flange. The nozzle is insulated internally with silica phenolic tape. The ATJ graphite throat insert has an area of 13.39 in.².

Ignition was accomplished by an igniter (Fig. 2), which contains a main charge of Alclo pellets weighing nominally 120 gm. The igniter incorporates four Bermite 400735 squibs in two parallel sets. Each set contains two squibs in parallel. The squibs are used to ignite an initiator charge of boron and potassium nitrate (BPN) powder. The igniter charge is contained in a honeycomb-like tube overwrapped with polyester tape. The total igniter weight, including charges, is 1.9 lb_m. The igniter contained ports to house chamber pressure transducers.

Since the nozzle did not contain a closure, motor chamber pressure was equal to cell pressure at ignition.

2.2 INSTALLATION

The motor was installed in Propulsion Engine Test Cell (T-3) (Ref. 2) in a spin fixture assembly mounted on a thrust cradle, which was supported from the cradle support stand by three vertical and two horizontal double-flexure columns (Fig. 3). The spin fixture assembly consisted of a 10-hp squirrel-cage-type drive motor, a forward thrust bearing assembly, a drive shaft and thrust pylon, and an aft bearing assembly. Electrical leads to and from the igniter, pressure transducers, and thermocouples on the rotating motor were provided through a 52-channel slip-ring assembly mounted on the drive shaft. Axial thrust was transmitted through the drive shaft-thrust bearing assembly to two double-bridge load cells mounted just forward of the thrust bearing.

Pre-ignition pressure altitude conditions were maintained in the test cell by a steam ejector operating in series with the RTF exhaust compressors. During the motor firing, the motor exhaust gases were used as the driving gas for the 47.25-in. -diam, ejector-diffuser system to maintain test cell pressure at an acceptable level.

2.3 INSTRUMENTATION

Instrumentation was provided to measure axial thrust, test cell pressure, motor chamber pressure, motor case and grain temperatures, and motor rotational speed. Table I presents instrument ranges, recording methods, and system accuracies for all measured parameters.

The axial thrust measuring system consisted of two double-bridge, strain-gage-type load cells mounted in the axial double-flexure column forward of the thrust bearing on the rocket motor centerline. Unbonded strain-gage-type transducers (0- to 1-psia) were used to measure test cell pressure. Bonded strain-gage-type transducers in ranges from 0 to 15, 0 to 30, and 0 to 750 psia were used to measure motor chamber pressure. Iron-Constantan (IC) thermocouples were bonded to the motor case (Fig. 4) to measure outer surface temperatures during and after motor burn time. In addition, thermocouples were taped to the propellant grain to measure pre-fire grain temperature.

Rotational speed of the motor and spin rig assembly was determined from the output of a magnetic pickup.

The output signal of each measuring device was recorded on independent instrumentation channels. Ballistic data were obtained from four axial thrust channels, two high range (0- to 750-psia) and two low range (0- to 30- and 0- to 15-psia) motor chamber pressure channels, and three test cell pressure channels. These data were recorded as follows: Each instrument output signal was indicated in totalized digital form on a visual readout of a millivolt-to-frequency converter. A magnetic tape system, recording in frequency form, stored the signal from the converter for reduction at a later time by an electronic digital computer.

The output signal from the magnetic rotational speed pickup was recorded and displayed on visual indicators in the following manner: A frequency-to-analog converter was triggered by the pulse output from the magnetic pickup and in turn supplied a square wave of constant amplitude to the electronic counter, magnetic tape, and oscillograph recorders. The scan sequence of the electronic counter was adjusted so that it displayed directly the motor spin rate in revolutions per minute.

The millivolt outputs of the thermocouples were recorded on magnetic tape from a multi-input, high speed, analog-to-digital converter at a scan rate for each thermocouple of 6.66 times/sec. A photographically recording, galvanometer-type oscillograph provided an independent backup of all operating instrumentation channels.

Selected channels of thrust, pressures, and temperatures were recorded on null-balance, potentiometer-type strip charts for analysis immediately after the motor firing. Visual observation of the firing was provided by a closed-circuit television monitor. High speed, motion-picture cameras provided a permanent visual record of the firing.

2.4 CALIBRATION

The thrust calibrator weights, thrust load cells, and pressure transducers were laboratory-calibrated prior to usage in this test. After installation of the measuring devices in the test cell, all systems were calibrated at sea-level ambient conditions and again at pressure altitude conditions after the 300-rpm rotative speed was attained.

The pressure systems were calibrated by an electrical, four-step calibration, using resistances in the transducer circuits to simulate selected pressure levels. The axial thrust instrumentation systems were calibrated by applying to the thrust cradle known forces which were produced by the deadweights acting through a bell crank. The calibrator is hydraulically actuated and remotely operated from the control room.

After the motor firing, with the motor spinning at simulated altitude, the systems were re-calibrated to determine if any shift had occurred.

SECTION III PROCEDURE

The Aerojet General Corporation, Alcor 1B (S/N STV097), solid-propellant rocket motor arrived at AEDC on July 1, 1966. The motor was visually inspected for possible shipping damage and radiographically inspected for grain cracks, voids, or separation and found to meet criteria provided by the manufacturer. During storage in an area temperature conditioned at $80 \pm 5^\circ\text{F}$, the motor was checked to ensure correct fit of mating hardware, the electrical resistance of the igniter was measured, the nozzle throat and exit diameters were obtained, thermocouples were bonded to the grain and motor case, and the entire motor assembly was weighed. Before installation in the test cell, the motor was temperature-conditioned at $80 \pm 5^\circ\text{F}$ for a minimum of 48 hr.

After installation of the motor in the test cell, the cell temperature conditioning system was adjusted to maintain the cell temperature at

80 ± 2°F, instrumentation connections were made, and a continuity check of all electrical systems was performed. The motor was spun at sea-level conditions at 300 rpm to ensure proper balance of the spin rig assembly. Pre-fire, sea-level calibrations were completed, the test cell pressure was reduced to the desired simulated altitude condition, and altitude calibrations were accomplished. Spinning of the unit was then started, and after spinning had stabilized at 300 rpm, a complete set of altitude calibrations was taken. The final operation prior to firing was adjustment of the circuit resistance and voltage to provide the desired current to the igniter squibs. The entire instrumentation measuring-recording complex was activated, and the motor was fired while spinning (under power) at 300 rpm. After motor burnout, the 300-rpm spin rate was maintained until post-fire altitude calibrations were accomplished. The unit was then decelerated slowly until rotation had stopped, and an additional set of calibrations was taken. The test cell pressure was returned to ambient conditions, and the motor was inspected, photographed, and removed to the storage area. Post-fire inspections consisted of measuring the nozzle, weighing the motor, and photographically recording the post-fire condition of the motor.

SECTION IV RESULTS AND DISCUSSION

One Aerojet Alcor 1B solid-propellant rocket motor was fired at an average simulated altitude of 100,000 ft while spinning at 300 rpm. Ignition and tailoff characteristics, altitude ballistic performance, structural integrity, and motor temperatures are discussed.

The ballistic performance data obtained are summarized in Table II, and the summary of motor physical dimensions is presented in Table III. When more than one instrumentation channel was used to obtain values of a single parameter, the average of these values was used to calculate the data presented.

The ballistic performance data are presented and evaluated on the basis of parameters defined in Ref. 3. The parameters are defined as follows:

1. Ignition delay time (t_d) is defined as the time from application of voltage to the igniter to the time the chamber pressure increases to 100 psia.
2. Action time (t_a) is defined as the time interval between the 100-psia points on the rising and decaying portions of the chamber pressure-time curve.

3. Critical time (t_c) is the time interval between application of voltage to the igniter and the time when the chamber pressure decays to 30 psia during tailoff.
4. Total time (t_t) is the time from the first indication of thrust or chamber pressure until the curve decays to zero. *
5. Maximum thrust ($F_{\max_{\text{vac}}}$) is the highest thrust developed by the motor during firing.
6. Maximum pressure (P_{\max}) is the highest chamber pressure developed by the motor during firing.
7. Vacuum critical impulse ($I_{\text{vac}_{\text{critical}}}$) is the area under the thrust time curve for the duration of critical time (t_c).

Tabulated below are the acceptable performance limits stated in Ref. 3:

<u>Parameter</u>	<u>Value at 80°F</u>	<u>Tolerance</u>
Vacuum Critical Impulse ($I_{\text{vac}_{\text{critical}}}$), lbf-sec	256,500	±2670
Maximum Thrust ($F_{\max_{\text{vac}}}$), lbf	13,075	±915
Maximum Pressure (P_{\max}), psia	640	---
Action Time (t_a), sec	25.46	±1.86
Critical Time (t_c), sec	26.44	±2.00
Total Time (t_t), sec	28.38	±3.92
Maximum Ignition Delay Time (t_d), sec	0.100	---

4.1 IGNITION AND TAILOFF CHARACTERISTICS

The motor was ignited at a pressure altitude of 106,000 ft. The average simulated altitude during the motor action time was 100,000 ft. An analog

*Because nozzle flow becomes unchoked when the ratio of chamber pressure-to-cell pressure decreases to about 1.3, data beyond this point are not representative of vacuum performance of the motor. For this report, total time (t_t) is defined as the time from the first indication of chamber pressure until the ratio of chamber pressure-to-cell pressure decreases to 1.3.

trace of thrust and chamber pressure characteristics during motor ignition is presented in Fig. 5. The ignition delay time was 0.035 sec, this is 0.065 sec less than the maximum allowable.

Figure 6 presents variation of measured thrust, chamber pressure, and cell pressure during the firing. Tailoff characteristics are presented in detail in Figs. 7 and 8. Figure 7 presents the tailoff data starting with the increase in cell pressure, indicating that the rocket motor exhaust plume has become unattached from the diffuser duct, and ending at the point when motor chamber pressure decreases to approximately 12 psia. Figure 8 presents the tailoff data starting with a chamber pressure of approximately 12 psia and continuing until the ratio of chamber pressure-to-cell pressure decreases to 1.3 (point at which exhaust flow in the throat becomes subsonic).

Abnormally high cell pressure was experienced during the time interval from the rocket exhaust plume becoming unattached to the diffuser and the re-establishment of the steam ejector's plume. Post-fire inspection of the test cell and water jacket on the diffuser showed that the diffuser water jacket had failed during the firing. Thrust data fluctuations during tailoff (Fig. 6) indicate that the density of the exhaust gases re-entering the test chamber suddenly increased, indicating that water and/or steam was introduced into the system from the diffuser water jacket. Water and steam in combination with the exhaust gases increased the cell pressure to a maximum value of 1.8 psia.

The low range chamber pressure data (Figs. 7 and 8) do not contain inflection points. It is, therefore, concluded that chamber pressure was unaffected by the cell pressure (nozzle remained choked) during the period of high test cell pressure.

The values of the following parameters defined in the previous section were determined to be:

<u>Parameter</u>	<u>Motor S/N STV 097</u>	<u>Performance Limits</u>
Action Time (t_a), sec	25.627	23.60 to 27.32 (Specified)
Critical Time (t_c), sec	26.692	24.44 to 28.44 (Specified)
Total Time (t_t), sec	35.30	24.46 to 32.30 (Predicted)

Action and critical times were within the specifications, whereas total time was 3 sec longer than the predicted limits.

4.2 BALLISTIC PERFORMANCE

The variations of thrust, chamber pressure, and test cell pressure with time during the motor firing are shown in Fig. 6.

Since the exhaust nozzle does not operate fully expanded at the low chamber pressure encountered during tailoff, the measured thrust data cannot be corrected to vacuum conditions by adding the product of cell pressure integral and nozzle exit area. Therefore, total, critical, and action times were segmented, and the method used to determine vacuum impulse is illustrated in Fig. 9. The exhaust nozzle flow breakdown was considered to have occurred simultaneously with the exhaust diffuser flow breakdown (as indicated by a rapid increase in cell pressure). The flow at the nozzle throat was considered sonic until the ratio of chamber pressure-to-cell pressure had decreased to a value of 1.3.

The vacuum total and critical impulse and the specified limits are tabulated below:

<u>Parameter</u>	<u>Motor S/N STV 097</u>	<u>Specified Performance Limits</u>
Vacuum Critical Impulse, lbf-sec	255,696	253,830 to 259,170
Vacuum Total Impulse, lbf-sec	256,616	---
Vacuum Action Impulse, lbf-sec	254,366	---

The specified performance limits apply only to vacuum critical impulse; however, the vacuum total and action impulse also fall within the specified limit.

The vacuum total specific impulse based on pre- and post-fire motor weight (expended mass including the combustion products deposited in the nozzle exit) was 279.12 lbf-sec/lb_m. The vacuum critical impulse based on expended mass was 278.12 lbf-sec/lb_m. The average vacuum thrust coefficient based on critical time was 1.733.

4.3 STRUCTURAL INTEGRITY AND TEMPERATURE DATA

Motion-picture films of the firing and the post-fire condition of the motor indicate that an unusually large amount of combustion products was deposited on the interior of the nozzle cone near the area of the exit (Fig. 10). Centrifugal forces acting on the deposited molten products of combustion caused the material to flow from the nozzle exit in a direction radial to the axis of rotation. Post-fire inspection of the motor revealed that the nozzle throat area had increased 7.588 percent (Table III) during

motor operation. The nozzle exit area decreased 0.73 percent during motor operation. The structural integrity of the motor case, nozzle, and igniter assemblies appeared to be satisfactory.

Figure 11 presents temperature-time histories from thermocouples located on the motor case. A maximum temperature of 357°F was recorded on the forward dome of the motor chamber at thermocouple position 7 (Figs. 4 and 11a) at approximately 108 sec after ignition. The maximum temperature of 444°F occurred in the cylindrical portion of the motor case at position 5 (Figs. 4 and 11b) at 156 sec after motor ignition.


SECTION V SUMMARY OF RESULTS

The results of testing an Aerojet-General Corporation, Alcor 1B, solid-propellant rocket motor at an average simulated altitude of 100,000 ft, while spinning about the axial centerline at an average rotational speed of 304.3 rpm, are summarized as follows:

1. Satisfactory motor ignition was obtained at a pressure altitude of 106,000 ft. The ignition delay time, defined as the time interval from application of voltage to the igniter to the time the chamber pressure reached 100 psia, was 0.035 sec. The maximum specified ignition delay time is 0.100 sec.
2. The vacuum total impulse was 256,616 lbf-sec. Vacuum critical impulse was 255,696 lbf-sec. Specified limit of vacuum critical impulse is $256,500 \pm 2670$ lbf-sec. The vacuum specific impulse, based on the vacuum total impulse and the pre- and post-fire weight difference, was 279.12 lbf-sec/lb_m.
3. The total time, defined as the time interval from the application of voltage to the igniter to the time that the chamber-to-cell pressure ratio equals 1.3, was 35.30 sec. The specified limit of total time is 28.38 ± 3.925 sec. The critical time, defined as the time interval from application of voltage to the igniter to the time that chamber pressure decreases to 30 psia at tailoff, was 26.692 sec. The specified limit of critical time is 26.44 ± 2.00 sec.


REFERENCES

1. Friedman, Robert F. and Reed, Jack. "Athena - - A Unique Re-Entry Test Vehicle." AIAA Paper No. 64-275 - Paper presented at the First AIAA Annual Meeting, Washington, D. C. , June 29 to July 2, 1964.
2. Test Facilities Handbook (5th Edition). "Rocket Test Facility, Vol. 2." Arnold Engineering Development Center, July 1963.
3. "Model Specification Rocket Motor, Solid-Propellant Alcor 1B." Contract AF 04(694)-846, BSD Specification CP-23-65-1, March 16, 1966.




a. Schematic


Fig. 1 Aerojet-General Corporation Alcor 1B Solid-Propellant Rocket Motor




b. Pre-Fire Photograph
Fig. 1 Concluded



a. Schematic
 Fig. 2 Igniter Assembly




b. Photograph
Fig. 2 Concluded




a. Schematic

Fig. 3 Installation of the Alcor 1B Rocket Motor in the T-3 Test Cell



b. Photograph
Fig. 3 Concluded



No.	Function and Location
T1	TCA 60 deg - 2.8
T2	TCA 60 deg - 5.0
T3	TCA 60 deg - 6.8
T4	TCC 60 deg - 4.4
T5	TCC 60 deg - 8.7
T6	TCF 60 deg - 10.5
T7	TCF 60 deg - 5.9
T8	TCF 60 deg - 1.9
T9	TCA 180 deg - 6.8
T10	TCC 180 deg - 4.4
T11	TCC 180 deg - 8.7
T12	TCF 180 deg - 10.5

Fig. 4 Schematic of Thermocouple Locations




Fig. 5 Analog Trace of Ignition Event




Fig. 6 Variation of Thrust, Chamber Pressure, and Cell Pressure during Firing




Fig. 7 Low Range Chamber Pressure from Diffuser Breakdown to Chamber Pressure Equal to 12 psia





Fig. 8 Low Range Chamber Pressure from 12 psia to Chamber Pressure-to-Cell Pressure Ratio Equal to 1.3



$$I_{vac_total} = \int_{t_0}^{t_{bd}} F dt + A_{ex(avg)} \int_{t_0}^{t_{bd}} P_{cell} dt + c_f A_{th(post)} \int_{t_{bd}}^{t_t} P_{ch} dt$$

$$I_{vac_critical} = \int_{t_0}^{t_{bd}} F dt + A_{ex(avg)} \int_{t_0}^{t_{bd}} P_{cell} dt + c_f A_{th(post)} \int_{t_{bd}}^{t_c} P_{ch} dt$$

$$I_{vac_action} = \int_{t_a}^{t_{bd}} F dt + A_{ex(avg)} \int_{t_a}^{t_{bd}} P_{cell} dt + c_f A_{th(post)} \int_{t_{bd}}^{t_a} P_{ch} dt$$

where: $c_f = \frac{F_{measured} + P_{cell} \cdot A_{ex(post)}}{P_{ch} \cdot A_{th(post)}}$ established from data during the time interval from 22.45 to 23.45 sec after ignition

Fig. 9 Definition of Vacuum Total and Critical Impulse







Fig. 10 Detail of Products of Combustion Deposited on the Nozzle Exit



a. Forward and Aft Dome Temperatures

Fig. 11 Temperature History for Alcor 1B Rocket Motor



b. Temperature on the Cylindrical Portion of the Chamber

Fig. 11 Concluded

**TABLE I
INSTRUMENTATION**

Parameter	Estimated System Accuracy (2σ)		Measuring Device	Range of Measuring Device	Recording Device	Method of System Calibration
	Steady-State Operating Level	Integral, percent				
Axial Force, lb_f	± 0.32 percent	---	Bonded Strain-Gage-Type Load Cells (2 Used)	0 to 13,200 lb_f	Millivolt-to-Frequency or Digital Converter onto Magnetic Tape	Deadweight
Total Impulse, lb_f -sec	---	± 0.32				
Motor Chamber Pressure, psia	± 0.46 percent	---	Bonded Strain-Gage-Type Transducers (2 Used)	0 to 650 psia		Electrical
Chamber Pressure Integral, psia-sec	---	± 0.44				
Low Range Chamber Pressure, psia	± 1 percent	---		0 to 30 psia		
Low Range Pressure, psia	12 percent	---		0 to 15 psia		
Test Cell Pressure, psia	± 1.86 percent	---	Unbonded Strain-Gage-Type Transducers (2 Used)	0 to 1 psia		
Test Cell Pressure Integral, psia-sec	---	± 1.86				
Time Interval, msec	± 5 msec	---	Synchronous Timing Line Generator	---	Photographically Recording Galvanometer-Type Oscillograph	Compare with 60 cps
Temperature, $^{\circ}F$	$\pm 5^{\circ}F$	---	Chromel [®] -Alumel [®] Iron-Constantan Thermocouples	0 to 600 $^{\circ}F$	Digital Millivoltmeter onto Magnetic Tape	Known Millivolt Source and NBS Temperature Tables
Weight, lb_m	± 0.031 lb_m	---	Beam Balance Scales	0 to 3000 lb_m	Visual Readout	Periodic Deadweight Calibration

TABLE II
SUMMARY OF MOTOR PERFORMANCE

Test Number	RC0638-01
Test Date	7/20/66
Motor Serial Number	STV097
Simulated Altitude at Ignition, ft	106,000
Average Simulated Altitude (Based on Action Time), ft	100,000
Average Spin Rate during Firing, rpm	304.3
Ignition Delay Time (t_d), sec	0.035
Action Time (t_a), sec	25.627
Critical Time (t_c), sec	26.692
Total Burn Time (t_t), sec	35.30
Maximum Thrust (vac), lbf	12,963
Maximum Chamber Pressure, psia	520.11
Measured Impulse (from Ignition until Diffuser Breakdown), lbf-sec	
Average of Four Channels of Data	248,814
Maximum Deviation from Average, percent	+0.006
Chamber Pressure Integral (from Ignition until Diffuser Breakdown), psia-sec	
Average of Two Channels of Data	10,401.4
Maximum Deviation from Average, percent	+0.052
Cell Pressure Integral (from Ignition until Diffuser Breakdown), psia-sec	
Average of Four Channels	3.47010
Maximum Deviation from Average, percent	-1.20
Vacuum Impulse (Based on Time Interval from Ignition until Diffuser Breakdown), lbf-sec	249,592
Vacuum Thrust Coefficient (c_f) (Based on 1-sec Data 22.45 to 23.45 sec after Ignition and Post-Fire Throat Area)	1.738
Chamber Pressure Integral (from Diffuser Breakdown until Chamber Pressure-to-Cell Pressure Ratio Equals 1.3), psia-sec	280.26
Chamber Pressure Integral (from Diffuser Breakdown until Chamber Pressure Equals 30 psia), psia-sec	243.60
Chamber Pressure Integral (from Diffuser Breakdown until Chamber Pressure Equals 100 psia), psia-sec	190.5
Vacuum Total Impulse (Based on t_t), lbf-sec*	256,616
Vacuum Critical Impulse (Based on t_c), lbf-sec*	255,696
Vacuum Action Impulse (Based on t_a), lbf-sec*	254,366
Vacuum Specific Impulse (Based on Vacuum Total Impulse and Consumed Weight), lbf-sec/lb _m	279.12
Average Vacuum Thrust Coefficient, c_f , (Based on Total Burn Time (t_t) and Average Pre- and Post-Fire Throat Area)	1.727

*Vacuum total, critical, and action impulse defined in Fig. 9

TABLE III
SUMMARY OF MOTOR PHYSICAL DIMENSIONS

Test Number	RC0638-01
Test Date	7/20/66
Motor Serial Number	STV097
Pre-Fire Motor Assembly Weight (Includes Igniter), lb _m	1005.226
Post-Fire Assembly Weight (Includes Igniter), lb _m	85.856
Expended Mass (Includes Igniter Propellant) (AEDC), lb _m	919.370
Manufacturer's Stated Propellant Weight (W _p) (Includes Igniter Propellant), lb _m	913.7
Nozzle Throat Area, in. ²	
Pre-Fire	13.403
Post-Fire	14.420
Percent Change from Pre-Fire Measurement	+7.588
Average	13.9115
Nozzle Exit Area*, in. ²	
Pre-Fire	218.568
Post-Fire	216.968
Percent Change from Pre-Fire Measurement	-0.73
Average	217.768
Nozzle Area Ratio, A/A*	
Pre-Fire	16.31
Post-Fire	15.05
Average	15.654

*Exhaust products removed before measurements

DOCUMENT CONTROL DATA - R&D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1 ORIGINATING ACTIVITY (Corporate author) Arnold Engineering Development Center ARO, Inc., Operating Contractor, Arnold Air Force Station, Tennessee		2a REPORT SECURITY CLASSIFICATION UNCLASSIFIED	
		2b GROUP N/A	
3 REPORT TITLE PERFORMANCE OF THE AEROJET-GENERAL CORPORATION ALCOR 1B SOLID- PROPELLANT ROCKET MOTOR UNDER THE COMBINED EFFECTS OF ROTATIONAL SPIN AND SIMULATED ALTITUDE			
4 DESCRIPTIVE NOTES (Type of report and inclusive dates) N/A			
5 AUTHOR(S) (Last name, first name, initial) Bahor, L. R., ARO, Inc.			
6 REPORT DATE October 1966		7a TOTAL NO OF PAGES 35	7b NO OF REFS 3
8a CONTRACT OR GRANT NO AF40(600)-1200 b System 627A c Program Element 64406124 d		9a ORIGINATOR'S REPORT NUMBER(S) AEDC-TR-66-186	
		9b OTHER REPORT NO(S) (Any other numbers that may be assigned this report) N/A	
10 AVAILABILITY/LIMITATION NOTICES Qualified users may obtain copies of this report from DDC, and release to foreign governments or foreign nationals must have prior approval of BSD.			
11 SUPPLEMENTARY NOTES N/A		12 SPONSORING MILITARY ACTIVITY Ballistic Systems Division (BSD) Air Force Systems Command (AFSC) Norton Air Force Base, California	
13 ABSTRACT One Aerojet-General Corporation, Alcor 1B, solid-propellant rocket motor was successfully tested at an average simulated altitude of 100,000 ft while spinning about its axial centerline at an average spin rate of 304.3 rpm. The objective of this test was to evaluate the ballistic performance, tailoff characteristics, and structural integrity of the flightweight motor assembly under the combined effects of rotational spin and near-vacuum environment. The vacuum total impulse was 256,616 lbf-sec; the vacuum specific impulse, based on the vacuum total impulse and pre- and post-fire weight difference, was 279.12 lbf-sec/lb _m . The total burn time, defined as the time interval from the application of voltage to the igniter to the time when the chamber pressure-to-cell pressure ratio is 1.3, was 35.30 sec.			

14

KEY WORDS

solid propellants
 performance
 rocket motor
 spin
 altitude simulation
 structural integrity
 pressure

LINK A		LINK B		LINK C	
ROLE	WT	ROLE	WT	ROLE	WT

INSTRUCTIONS

1. **ORIGINATING ACTIVITY:** Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (*corporate author*) issuing the report.
- 2a. **REPORT SECURITY CLASSIFICATION:** Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.
- 2b. **GROUP:** Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.
3. **REPORT TITLE:** Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.
4. **DESCRIPTIVE NOTES:** If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.
5. **AUTHOR(S):** Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.
6. **REPORT DATE:** Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.
- 7a. **TOTAL NUMBER OF PAGES:** The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.
- 7b. **NUMBER OF REFERENCES:** Enter the total number of references cited in the report.
- 8a. **CONTRACT OR GRANT NUMBER:** If appropriate, enter the applicable number of the contract or grant under which the report was written.
- 8b, 8c, & 8d. **PROJECT NUMBER:** Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.
- 9a. **ORIGINATOR'S REPORT NUMBER(S):** Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.
- 9b. **OTHER REPORT NUMBER(S):** If the report has been assigned any other report numbers (*either by the originator or by the sponsor*), also enter this number(s).
10. **AVAILABILITY/LIMITATION NOTICES:** Enter any limitations on further dissemination of the report, other than those

imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. **SUPPLEMENTARY NOTES:** Use for additional explanatory notes.
12. **SPONSORING MILITARY ACTIVITY:** Enter the name of the departmental project office or laboratory sponsoring (*paying for*) the research and development. Include address.
13. **ABSTRACT:** Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U)

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. **KEY WORDS:** Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.