

UNCLASSIFIED

AD NUMBER

AD491854

CLASSIFICATION CHANGES

TO: UNCLASSIFIED

FROM: RESTRICTED

LIMITATION CHANGES

TO:  
Approved for public release; distribution is unlimited.

FROM:  
Distribution authorized to DoD only;  
Administrative/Operational Use; 04 JUL 1942.  
Other requests shall be referred to Ballistic  
Research Laboratories, Aberdeen Proving Ground,  
MD. Pre-dates formal DoD distribution  
statements. Treat as DoD only.

AUTHORITY

E.O. 10501 dtd 5 Nov 1953 BRL ltr dtd 22 Apr  
1981

THIS PAGE IS UNCLASSIFIED

**UNCLASSIFIED**

**AD**

**491854**

**DEFENSE DOCUMENTATION CENTER**

**FOR**

**SCIENTIFIC AND TECHNICAL INFORMATION**

**CAMERON STATION, ALEXANDRIA, VIRGINIA**



**UNCLASSIFIED**

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

491854

**BRL**

*Handwritten initials*

REPORT NO. 287  
JULY 1942

**491854**

THE RELATION BETWEEN THE SKIN FRICTION DRAG AND  
THE SPIN REDUCING TORQUE

A. C. Charters  
R. H. Kent

**BALLISTIC RESEARCH LABORATORIES**

**ABERDEEN PROVING GROUND, MARYLAND**

(11) 4 Jul 42,  
(12) 6p.

(6) THE RELATION BETWEEN THE SKIN FRICTION DRAG AND THE SPIN  
REDUCING TORQUE,

(10) A. C. Charters and T. H. Kent.

(14) BRL-287

On certain simplifying assumptions, a relation between the skin friction drag and the spin reducing torque or axial couple is deduced. On the basis of measured values of the axial couple coefficient the skin friction drag coefficient is deduced and compared with the measured total drag.  $\rightarrow$  a method is derived for utilizing

It occurred to one of us\* that  $\rightarrow$  the measured values of the axial couple coefficient should afford a method  $\rightarrow$  to estimate, ~~of estimating~~ the skin friction drag coefficient. The purpose of this report is to derive a method of making this estimate.

Consider a shell of caliber,  $d$ , moving nose on into the air with a velocity,  $v$ , and a velocity of rotation,  $\omega$ . We make the assumption that the skin friction drag on an element  $dS$  of the surface of the shell is

$$\rho f(z) u^2 dS$$

\* A. C. Charters.

in magnitude, where  $u$  is the velocity of the element with respect to the atmosphere,  $\rho$  is the density of the undisturbed air and  $f(z)$  is a function of  $z$ , the distance of the element from the base of the shell. The direction of the skin friction drag on the element  $dS$  is taken to be opposite to the direction of motion of the element  $dS$ .

If the radius of the shell at the section on which  $dS$  lies is  $r$ , the relative velocity  $u$  is evidently the vector sum of  $v$  and  $r\omega$  or

$$\sqrt{v^2 + r^2 \omega^2} = u.$$

The component of this force parallel to the axis of the shell is obviously

$$\rho \frac{v}{u} f(z) u^2 dS = \rho f(z) u v dS$$

and the total skin friction drag on these assumptions is

$$\int \rho f(z) uv dS = \rho \bar{u} v \int f(z) dS \quad (1)$$

if  $\bar{u}$  is an appropriate average value of  $u$ .

The tangential component of the skin friction force is evidently

$$\rho \frac{r\omega}{u} f(z) u^2 dS = \rho f(z) r \omega u dS.$$

The torque produced by this force acting on the element  $dS$  is

$$\rho f(z) r^2 \omega u dS$$

and the total torque is

$$\int \rho f(z) r^2 \omega u dS = \rho \omega \bar{u}' \int f(z) r^2 dS \quad (2)$$

if  $\bar{u}'$  is another appropriate average value of  $u$ .

It is apparent that to evaluate (1) one needs to know the value of  $\int f(z) dS$ .

If  $\bar{r}^2$  represents a certain average value of  $r^2$  and the torque is known,  $\int f(z) dS$  is determined by the relation.

$$\int f(z) dS = \frac{(\text{torque})}{r^2 \rho \omega \bar{u}'}$$

and the skin friction drag is given by

$$\rho \bar{u} v \int f(z) dS = \frac{v(\text{torque})\bar{u}}{r^2 \omega \bar{u}'} \quad (3)$$

We accordingly take the case of a cylindrical shell, like a proof slug, and neglect the skin friction drag on the nose and the base. Under these conditions

$$\bar{u} = \bar{u}' = \sqrt{v^2 + \frac{d^2 \omega^2}{4}},$$

$\bar{r} = d/2$ , and the skin friction drag is

$$\frac{4 v (\text{torque})}{d^2 \omega} \quad (4)$$

According to Ballistic Research Laboratory Report No. 154, the torque designated by  $M_s$  has been represented by

$$M_s = C_A \rho d^4 \omega v, \quad (5)$$

where  $C_A$  is the axial couple coefficient. Practical units are used as follows:

Quantity	Units
$M_s$	lb ft <sup>2</sup> /sec <sup>2</sup>
$\rho$	ratio of air density to normal
$d$	in
$\omega$	rad/sec
$v$	ft/sec

If self-consistent units are used we have

$$M_s = K_A \rho d^4 \omega v, \quad (6)$$

where  $K_A$  the axial couple coefficient is dimensionless. It may be shown that

$$K_A = \frac{12^4}{.0751} C_A = 2.76 \times 10^5 C_A.$$

From (4) and (6)

$$D_F = \frac{4v \rho d^4 \omega v K_A}{d^2 \omega} = 4K_A \rho d^2 v^2 \quad (7)$$

where  $D_F$  is the skin friction drag. If the skin friction drag coefficient is designated by  $K_{DF}$  so that

$$D_F = K_{DF} \rho d^2 v^2,$$

then from (7)

$$K_{DF} \rho d^2 v^2 = 4K_A \rho d^2 v^2 \quad \text{or,} \quad K_{DF} = 4K_A.$$

According to Captain Sterne's analysis of Dr. Van Allen's results the value of  $C_A$  for the 3" shell M42 is  $2.12 \times 10^{-8}$  from which the value of  $K_A$  is found to be  $5.85 \times 10^{-3}$ . The corresponding value of  $K_{DF}$  is therefore  $4 \times 5.85 \times 10^{-3} = .0234$ .\*

The drag coefficient of this shell is approximately .153 at a velocity of 2000 ft/sec. Hence the ratio of the skin friction drag to the total drag is, on these assumptions

$$\frac{.0234}{.153} = .153.$$

If the skin friction drag is evaluated by (3) instead of (4), in other words, if  $r^2$  is substituted for  $d^2/L$ , we have

$$K_{DF} = \frac{d^2 \bar{u}}{r^2 \bar{u}'} K_A,$$

and the ratio  $\frac{K_{DF}}{K_D}$  may be larger than the value given, .153.

\* The customary aerodynamic expression for the skin friction drag is:

$$D_F = C_{DF} \rho S v^2$$

where  $S$  is the surface of the projectile. For the 3" shell M42, the calculated  $S$  is  $103.5 \text{ in}^2$ , and  $S/d^2$  is 11.50. Hence,

$$C_{DF} = .00203, \quad K_A = .000,500 S/d^2.$$

If  $S'$  represents the surface of the projectile, exclusive of the base,  $S'$  is  $96.5 \text{ in}^2$  and  $S'/d^2$  is 10.72 for the 3" shell M42. Then,

$$C'_{DF} = .00218, \quad K_A = .000,545 S'/d^2.$$



von Kármán<sup>1</sup> and Moore give 11% as an estimated value of this ratio.

It follows from the argument of page 2 equation (2) that in place of (5) the axial couple could be expressed more accurately in the form

$$M_s = K_A \rho d^4 \omega \bar{u}'$$

and for the cylindrical shell this would become

$$M_s = K_A \rho d^4 \omega \sqrt{v^2 + d^2 \omega^2 / 4}^*.$$

*A. C. Charters*

A. C. Charters

*R. H. Kent*

R. H. Kent

<sup>1</sup> von Kármán and Moore, Trans. A.S.M.E., June 1932.

\* This form was proposed independently by J. A. Van Allen in a letter dated June 25th, received while this report was being written.

~~RESTRICTED~~

ATI-40334

TITLE: Relation between the Skin Friction Drag and the Spin Reducing Torque

AUTHOR(S): Kent, R.H.; Charters, A.C.

ORIGINATING AGENCY: Aberdeen Proving Ground, Ballistic Research Lab., Md.

PUBLISHED BY: (Same)

U

REVISION  
(None)

ORIG. AGENCY NO.  
R-287

PUBLISHING AGENCY NO.  
(Same)

DATE	DOC. CLASS.	COUNTRY	LANGUAGE	PAGES	ILLUSTRATIONS
July '42	<del>SECRET</del>	U.S.	Eng.	5	(None)

ABSTRACT:

EO 10501 dd 5 NCV 1953

A method is derived for making an estimate of the skin friction drag coefficient for projectiles. On certain simplifying assumptions, a relation between the skin friction drag and the spin reducing torque or axial couple is deduced. On the basis of measured values of the axial couple coefficient the skin friction drag coefficient is deduced and compared with the measured total drag.

DISTRIBUTION: Copies of this report obtainable from Air Documents Division; Attn: MCIDXD

DIVISION: Ordnance and Armament (22)  
SECTION: Ballistics (12)  
ATI SHEET NO.: R-22-12-34

22-46  
46

SUBJECT HEADINGS: Projectiles,- Drag (75415.8); Skin friction - Theory (86798.5)

Air Documents Division, Intelligence Department  
Air Materiel Command

AIR TECHNICAL INDEX

Wright-Patterson Air Force Base  
Dayton, Ohio