

UNCLASSIFIED

AD NUMBER

AD501931

CLASSIFICATION CHANGES

TO: unclassified

FROM: confidential

LIMITATION CHANGES

TO:  
Approved for public release, distribution unlimited

FROM:  
Distribution authorized to U.S. Gov't. agencies and their contractors; Administrative/Operational Use; MAY 1969. Other requests shall be referred to Commanding Officer, Army Edgewood Arsenal, Attn: SMUEA-TSTI-T, Edgewood, MD 21010.

AUTHORITY

EA D/A ltr 20 mar 1978; ECBC D/A ltr 26 July 2011

THIS PAGE IS UNCLASSIFIED

UNCLASSIFIED

AD 501931

DEFENSE DOCUMENTATION CENTER

FOR

SCIENTIFIC AND TECHNICAL INFORMATION

CAMERON STATION ALEXANDRIA, VIRGINIA

CLASSIFICATION CHANGED  
TO: UNCLASSIFIED  
FROM: CONFIDENTIAL  
AUTHORITY:

*EX. D/H 1000, 21 MAR 71*

BEST AVAILABLE COPY

UNCLASSIFIED

# **SECURITY**

---

# **MARKING**

**The classified or limited status of this report applies to each page, unless otherwise marked.**

**Separate page printouts MUST be marked accordingly.**

---

THIS DOCUMENT CONTAINS INFORMATION AFFECTING THE NATIONAL DEFENSE OF THE UNITED STATES WITHIN THE MEANING OF THE ESPIONAGE LAWS, TITLE 18, U.S.C., SECTIONS 793 AND 794. THE TRANSMISSION OR THE REVELATION OF ITS CONTENTS IN ANY MANNER TO AN UNAUTHORIZED PERSON IS PROHIBITED BY LAW.

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U.S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

~~CANCELLED~~ UNCLASSIFIED  
~~CONFIDENTIAL~~

AD 501931

EATM-134-2  
\*AD 501931 001\*



EDGEWOOD ARSENAL  
TECHNICAL MEMORANDUM

EATM 134-2


VISCOSITY OF VX IN THE TEMPERATURE RANGE  
-4° TO -40°F (U)

by

Donald Fielder  
E-4 Robert E. Beck

May 1969

This document contains information which is classified "Confidential" under Executive Order 12958, Section 1.5, and is exempt from automatic downgrading and declassification under E.O. 12958, Section 1.4. It is controlled under the provisions of the Arms Control and Disarmament Act, Public Law 90-367, and the Arms Control and Disarmament Act, Public Law 90-367, and the Arms Control and Disarmament Act, Public Law 90-367.



UNCLASSIFIED

DECLASSIFIED BY: [Signature]  
DATE: [Signature]

DEPARTMENT OF THE ARMY  
EDGEWOOD ARSENAL  
Research Laboratories  
Chemical Research Laboratory  
Edgewood Arsenal, Maryland 21010

GROUP 3

Downgraded and/or declassified at 2-year intervals  
or automatically declassified

~~CONFIDENTIAL~~

UNCLASSIFIED

TECHNICAL LIBRARY  
AD 501931

Edgewood Arsenal, MD 21010

501931

AD 501931

CONFIDENTIAL

AD

EDGEWOOD ARSENAL  
TECHNICAL MEMORANDUM

EATM 134-2

VISCOSITY OF VX IN THE TEMPERATURE RANGE  
-4° TO -40°F (U)

by

Donald Fielder  
E-4 Robert E. Beck

May 1969

This publication contains information affecting the National Defense of the United States within the meaning of the Espionage Laws, Title 18, U.S.C., Sections 793 and 794. The transmission or the revelation of its contents in any manner to an unauthorized person is prohibited by law.



DEPARTMENT OF THE ARMY  
EDGEWOOD ARSENAL  
Research Laboratories  
Chemical Research Laboratory  
Edgewood Arsenal, Maryland 21010

GROUP 3

Downgraded at 12 year intervals;  
not automatically declassified

This document contains information affecting the National Defense of the United States within the meaning of the Espionage Laws, Title 18, U. S. C., Section 793 and 794. Its transmission or the revelation of its contents in any manner to an unauthorized person is prohibited by law.

UNCLASSIFIED  
JUL 5 1989

CONFIDENTIAL

### Distribution Statement

In addition to security requirements which must be met, this document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of the Commanding Officer, Edgewood Arsenal, ATTN: TSTI-T, Edgewood Arsenal, Maryland 21010.

### Disclaimer

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

### Disposition

When this report is no longer needed, Department of the Army organizations will destroy it as prescribed by AR 380-5. Navy and Air Force elements will destroy it in accordance with applicable directions. Department of Defense contractors will destroy the report as prescribed by paragraph 19 of the Industrial Security Manual for Safeguarding Classified Information. All other recipients will return the report to Commanding Officer, Edgewood Arsenal, ATTN: SMJEA-AGA, Edgewood Arsenal, Maryland 21010.

**CONFIDENTIAL**

EDGEWOOD ARSENAL TECHNICAL MEMORANDUM

EATM 134-2

VISCOSITY OF VX IN THE TEMPERATURE RANGE  $-4^{\circ}$  TO  $-40^{\circ}$  F (U)

by

Donald Fielder  
E-4 Robert E. Beck

Physical Chemistry Department  
Chemical Research Laboratory

May 1969

This publication contains information affecting the National Defense of the United States within the meaning of the Espionage Laws, Title 18, U. S. C., Sections 793 and 794. The transmission of the revelation of its contents in any manner to an unauthorized person is prohibited by law.

In addition to security requirements which must be met, this document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of the Commanding Officer, Edgewood Arsenal, ATTN: SMJEA-TSTI-T, Edgewood Arsenal, Maryland 21010.

Task (1B522301A060-07-01)  
1B562602A060-07-01

DEPARTMENT OF THE ARMY  
EDGEWOOD ARSENAL  
Research Laboratories  
Chemical Research Laboratory  
Edgewood Arsenal, Maryland 21010

DOWNGRADED AT 12 YEAR  
INTERVALS; NOT AUTOMATICALLY  
DECLASSIFIED. DOD DIR 5200.10

**CONFIDENTIAL**

**UNCLASSIFIED**

(U)

FOREWORD

The work described in this report was conducted under Task 1B522301A060-07-01, G and V agents (U). This work was started and completed in April 1968. The experimental data are contained in notebook no. 7701.

Reproduction of this document in whole or in part is prohibited except with permission of the Commanding Officer, Edgewood Arsenal, ATTN: SMUEA-RCRP(2), Edgewood Arsenal, Maryland 21010; however, DDC is authorized to reproduce this document for United States Government purposes.

Acknowledgment

The authors wish to acknowledge the technical assistance of the personnel of the Analytical Chemistry Department in performing the analyses.

**CONFIDENTIAL**

**UNCLASSIFIED**



# CONFIDENTIAL

(c)

## DIGEST

The purpose of this investigation was to determine the viscosity of VX at subambient temperatures. This was accomplished by using Cannon viscometers in a low temperature bath. The viscosity of VX at  $-4^{\circ}$ ,  $-22^{\circ}$ , and  $-40^{\circ}$  F was 182.4, 630.7 and 3,261.5 centistokes, respectively. The viscosity of VX which contained 2.5 wt % N,N'- diisopropyl carbodiimide (ICDI) was 203.9, 722.2 and 3,773.6 centistokes at  $-4^{\circ}$ ,  $-22^{\circ}$  and  $-40^{\circ}$  F, respectively.

CONFIDENTIAL

UNCLASSIFIED

(U)

CONTENTS

	<u>Page</u>
I. INTRODUCTION .....	7
II. EXPERIMENTATION .....	7
A. Materials .....	7
B. Methods .....	7
III. RESULTS .....	8
IV. DISCUSSION .....	8
V. CONCLUSION .....	11
DISTRIBUTION LIST .....	13
DD FORM 1473 (DOCUMENT CONTROL DATA - R&D).....	25

UNCLASSIFIED

# CONFIDENTIAL

(C) VISCOSITY OF VX IN THE TEMPERATURE RANGE  $-4^{\circ}$  TO  $-40^{\circ}$ F (U)

## I. (U) INTRODUCTION

(U) The design, and ultimately, the successful testing of a dissemination system for a liquid agent requires a knowledge of the temperature-viscosity relationship of the agent. The Air Force, in their development of a dissemination system for VX, requested information on the viscosity of VX at  $-40^{\circ}$ F. A search of the literature revealed that the only published viscosity data<sup>1</sup> were for temperatures  $77^{\circ}$ F and above. However, some unpublished data had been obtained at Edgewood Arsenal in 1957 which indicated that the viscosity of VX at  $32.90^{\circ}$ F was 35.4 centistokes and 25,590 centistokes at  $-57.46^{\circ}$ F.

(U) This investigation was undertaken to determine the viscosity of VX at  $-4^{\circ}$ ,  $-22^{\circ}$ , and  $-40^{\circ}$ F.

## II. (C) EXPERIMENTATION

### A. Materials

(C) Two samples of VX used in this study had purities of 93.5 and 88.6 wt %. The latter contained 2.5 wt % N,N'-diisopropyl carbodiimide (ICDI).

### B. (U) Methods

(U) The viscosities of the VX samples were determined by using calibrated Cannon viscometers which had been cleaned and dried for 24 hours under vacuum at  $230^{\circ}$ F. The viscometers were loaded with the proper quantity of VX under a nitrogen atmosphere in a dry box and capped with drying tubes containing a desiccant. They were transferred to a Rosemount Engineering\* Temperature Calibration Bath (stabilized to  $\pm 0.02^{\circ}$ F) using ethylene glycol-water as the bath fluid. The bath was constructed of a stainless steel Dewar which prevented direct observation of the flow of the samples through the viscometers. Observation of the menisci flowing past the reference points on the viscometers was accomplished by using a rigid fiber optic rod which was 1 foot long,  $\frac{1}{4}$  inch in diameter and bent to an angle of  $80^{\circ}$ . Illumination of the reference points on the viscometers was achieved by employing a cladded Lucite light rod equipped with a high intensity light source.

<sup>1</sup> Coulter, P. B., Callahan, J. J., Link, R. S. Physical Constants of 13 V-Agents, CWLR 2346, Dec 1959. (The report is classified Secret).

\* The use of a company name indicates a source of material and is not to be construed as an endorsement of the product.

CONFIDENTIAL

## UNCLASSIFIED

(U) The temperature of the bath was monitored with a Hewlett-Packard Quartz thermometer which had a resolution capability of 0.00018°F. The flow time was measured with a mechanical stopwatch.

### III. (U) RESULTS

(U) The experimental data for the viscosity of the two VX samples are listed in the following table:

<u>Sample</u>	<u>VISCOSITY OF VX (U)</u>	
	<u>Temperature</u>	<u>Viscosity</u> <sup>(1)</sup>
	°F $\pm$ 0.02°	centistokes
VX	-4.00	182.4 $\pm$ 0.6
	-22.00	630.7 $\pm$ 1.5
	-40.00	3,261.5 $\pm$ 2.4
VX W/ICDI	-4.00	203.9 $\pm$ 1.0
	-22.00	722.2 $\pm$ 1.3
	-40.00	3,773.6 $\pm$ 1.9

(1) Standard deviation of 4 determinations

### IV. (U) DISCUSSION

(U) The data in the above table, along with the two previously unreported viscosity values at 32.90°F and -57.46°F were plotted on American Society for Testing and Material (ASTM) Standard Viscosity-Temperature Chart (see Chart). These data show good agreement although they are for three different samples of VX.

(U) The viscosity values obtained in this investigation were reproducible to better than  $\pm$  0.5% over the temperature range studied.

UNCLASSIFIED

## CONFIDENTIAL

### V. (C) CONCLUSION


(U) a. The viscosity of VX obtained in this investigation at  $-4.00^{\circ}$ ,  $-22.00^{\circ}$ , and  $-40.00^{\circ}$  F agrees very well with previously unpublished VX viscosity values obtained at  $32.9^{\circ}$  and  $-57.46^{\circ}$  F in 1957, when plotted on ASTM Viscosity Temperature chart paper.

(U) b. The viscosity of VX was determined to be 182.4 centistokes at  $-4.00^{\circ}$  F, 630.7 centistokes at  $-22.00^{\circ}$  F, and 3,261.5 centistokes at  $-40.00^{\circ}$  F.

(C) c. The viscosity of VX containing 2.5 wt % ICDI was determined to be 203.9 centistokes at  $-4.00^{\circ}$  F, 722.2 centistokes at  $-22.00^{\circ}$  F, and 3,773.6 centistokes at  $-40.00^{\circ}$  F.

CONFIDENTIAL

UNCLASSIFIED



UNCLASSIFIED

UNCLASSIFIED

Security Classification

DOCUMENT CONTROL DATA - R & D		
<i>(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)</i>		
1. ORIGINATING ACTIVITY (Corporate author) CO, Edgewood Arsenal ATTN: SMJEA-RCRP(2) Edgewood Arsenal, Maryland 21010		2a. REPORT SECURITY CLASSIFICATION <b>CONFIDENTIAL</b>
		2b. GROUP 3
3. REPORT TITLE  Viscosity of VX in the Temperature Range $-4^{\circ}$ to $-40^{\circ}$ F (U)		
4. DESCRIPTIVE NOTES (Type of report and inclusive dates) The work was started and completed in April 1968.		
5. AUTHOR(S) (First name, middle initial, last name) Donald Fielder, E-4 Robert E. Beck		
6. REPORT DATE May 1969	7a. TOTAL NO. OF PAGES 25	7b. NO. OF REFS 1
8a. CONTRACT OR GRANT NO.	9a. ORIGINATOR'S REPORT NUMBER(S)  EATM 134-2	
b. PROJECT NO: 1B562602A060-07-01 (1B522301A060-07-01)	9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report) NA	
c.		
d.		
10. DISTRIBUTION STATEMENT In addition to security requirements which must be met, this document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of the Commanding Officer, Edgewood Arsenal, ATTN: TSTI-T, Edgewood Arsenal, Maryland 21010.		
11. SUPPLEMENTARY NOTES NA	12. SPONSORING MILITARY ACTIVITY NA	
13. ABSTRACT (U) The viscosity of two VX samples, one of which contained N,N'-diisopropyl carbodiimide, were determined in the temperature range from $-4^{\circ}$ to $-40.0^{\circ}$ F using Cannon viscometers in a temperature calibration bath.		
14 (U) KEYWORDS  Viscosity Centistokes Cannon viscometers VX Temperature calibration bath Fiber optic rod Cladded light rod Subambient temperatures		

DD FORM 1473

NOV 68

REPLACES DD FORM 1473, 1 JAN 64, WHICH IS OBSOLETE FOR ARMY USE.

UNCLASSIFIED

Security Classification

**CONFIDENTIAL**



DEPARTMENT OF THE ARMY  
US ARMY RESEARCH, DEVELOPMENT AND ENGINEERING COMMAND  
EDGEWOOD CHEMICAL BIOLOGICAL CENTER  
5183 BLACKHAWK ROAD  
ABERDEEN PROVING GROUND, MD 21010-5424

RDCB-DPC-RS

MEMORANDUM FOR Defense Technical Information Center (DTIC), 8725 John J. Kingman Road, Fort Belvoir, VA 22060-6218.

SUBJECT: Change in Limitation (Public Release of Information)

1. The purpose of this memorandum is to recommend the Release of Information to the General Public regarding Edgewood Arsenal Technical Memorandum (EATM 134-2), Viscosity of VX in the Temperature Range -4 degrees - -40 degrees F, dated May 1969; and Edgewood Arsenal Technical Report (EC-TR-76058), The Vapor Pressure of Chemical Agents GD, VX, EA 2223, EA 3547, EA 3580, EA 5365 and EA 5593, dated August 1976. The first memorandum was Confidential and was previously downgraded to Unclassified on 20 Mar 1978. The DTIC Number is AD-501931. The second report is Unclassified and the DTIC Number is ADB-013164.
2. This document has been reviewed by Subject Matter Experts from the Edgewood Chemical Biological Center (ECBC) on Aberdeen Proving Ground, Maryland and deemed releasable to the General Public. Request that this document be properly identified and appropriately marked.
3. As the Security Manager for the documents in question, I concur with the recommendations made by the ECBC Review Team.
4. Point of contact for this action is the Information Security Officer, Ronald Stafford at 410-436-6810 or the undersigned at 410-436-7232.

Encl

*June K. Sellers*  
JUNE K. SELLERS  
ECBC Security and Surety Manager