٢

DO NOT PHOTOGRAPH THIS PAGE

DEVELOPMENT OF A SABOTING TECHNIQUE FOR LIGHT GAS HYPERVELOCITY PROJECTORS

COPY 2	0F3_	
HARD COPY	\$.	
MICROFICHE	<b>\$</b> .	



San Ramon (near San Francisco) California 837–7201 AD605 836

#### DEVELOPMENT OF A SABOTING TECHNIQUE

FOR



U. S. Noval Research Laboratory Washington, D.C.

MB-R-63/14

February 1963

Sponsored by Advanced Research Projects Agency Ballistic Missile Defense Systems Branch ARPA Order No. 70

Reproduction of this report in whole or in part is permitted for any purpose of the United States Government. This research was supported by the Advanced Research Projects Agency, Ballistic Missile Defense Systems Branch, and was monitored by the U.S. Naval Research Laboratory under J Contract No. Nonr 2618(00)(X).

MB ASSOCIATES San Ramon (near San Francisco) Califernia 837–7201

## TABLE OF CONTENTS

		Poge
	SUMMARY	ī
1	INTRODUCTION	1
11	DESIGN	3
	A Requirements B Engineering Calculations C Mechanical Design	3 3 7
Ш	EXPERIMENTS	15
	A. Experimental Facilities B. Experimental Results	15 19
IV	CONCLUSIONS	24
v	RECOMMENDATIONS	25

## LIST OF FIGURES

Figure la	Copper Propellant Cup	10
Figure 1b	Aluminum Propellant Cup	10
Figure 2a	Mark V Sabot	11
Figure 2b	Mark VI Sobot	11
Figure 2c	Mark VI Mod 1 Sabot	11
Figure 2a	Vertical Initiator Placement	13
Figure 3b	Horizontal-Longitudinal Initiator Placoment	13
Figure 4	Diagram of Powder Gun Range	16
Figure 5	Block Diggreen of Instrumentation System	17
Figure 6	Flash x-ray of Shot 5.2-8 Separation	21
Figure 7	Photographs of Mark VI Mod 1 Sabot	21

)

#### SUMMARY

A sabot, utilizing internal gas expansion to separate its halves, was developed for use in the launching of hypervalocity projectiles. Most sabots are designed so that aerodynamic forces will strip the parts away from the projectile. Here, separation was achieved by burning a propellant inside the sabot while it traveled down the gun barrel. Upon launch, the high pressure gases imparted lateral valocity to the halves by expension work.

It was desired to achieve separation velocities of  $1.5 \times 10^4$  cm/sec. At this velocity each half of the sabot would be displaced 10 cm from the trajectory at 6 meters from launch when fired at a velocity of 29,500 feet per second. A total of 33 experimental firings were carried out from CAL .60 powder and light gas guns. Both aluminum and fiberglas sabots were used. The lighter fiberglas sobot gave the desired separation velocity when fired at 8570 feet/second from the powder gun. Howe ver, it fractured when fired from the light gas gun. The aluminum sabot gave a lateral velocity of  $0.8 \times 10^4$  cm/sec when fired at 14,000 feet/second from the light gas gun. The lower than predicted separation velocities may be a result of the assumptions used in the calculations. However, the velocities achieved are adequate for present light gas gun work.

Two major problems were high projectile dispersion and sebot mass. In most of the light gas gun firings the projectile missed the target. This was thought to be caused by the sabot geometry. Lower sabot masses are required to permit higher velocity firings. Improvements in materials and design should solve both the mass and dispersion problems.

#### I. INTRODUCTION

A current problem in hypervelocity projection is the technique of saboting the projectile. Sabots are necessary for achieving high velocity and for the acceleration of projectile shapes which are not suited to forming a gas seal within the launch tube. Once the acceleration is complete and the sabct and projectile assembly leaves the launch tube of the hypervelocity projector, the sabot must be separated from the projectile so that It will not interfere with in-flight and terminal ballistics measurements. The most widely used method of sabot separation at the present time is the application of the acrodynamic forces encountered in high velocity (even in the evacuated ranges). Thus the sabots are usually split into two or more pieces which have an undurcut angled surface at the forward end. The air implinging upon the surface creates a lateral force component as well as a longitudinal one, and the sabot sections are pulled away from the projectile.

Under some circumstances, aerodynamic forces cannot be used to achieve subot separation. For example, if the sabot must be made of a dense material, it may not move away from the projectile fast enough, particularly at very high valocities to prevent it from striking the target along with the projectile. This interfares with terminal ballistics data. Other situations would be where the sabot and projectile and design does not permit the use of aerodynamic separating surfaces.

The objective of this program is to develop a sabot which has an active rather than a passive means of separation. The method uses a propellant, such as gunpowder, which is burned in a cavity within the sabot while the sabot is in the launch tube of the hypervelocity projector. When the sabot leaves the launch tube, so that it is no longer restrained, the high pressure generated in the cavity will perform PdV work on the two sabot halves, causing them to fly apart. The propellant is ignited by a setback initiator at the instant the gun is fired. By adjusting the type and quantity of the propellant and the volume of the cavity, the total burning time can be controlled; thus, knowing the time the sabot will spend in the launch tube of any given gun, the propellant burn characteristics can be adjusted to match so that the maximum pressure is developed in the tavity (at the instant of complete propellant consumption) close to the time that the sabot leaves the launch tube.

The following criteria were established for this project:

 The sabot is to be of aluminum, and will fit a caliber .60 launch tube. It will weigh 6 grams or less, exclusive of the projectile. Materials other than aluminum may be investigated if they have potentially the same strength characteristics, but a lower density, so that the total mass may be reduced.

- 2. Each half of the mabot must be separated by 10 cm from the trajectory at 6 meters from a gun launch tube when fired at a velocity of 9 kilometers per second, and a range pressure of 1 mm Hg. The required velocity of separation of each sabot half is therefore 1.5 x 10<sup>4</sup> cm/sec.
- 3. The projectile is to be a 3/8" diameter steel sphere weighing 3.5 grams.
- 4. Testing during the development of the sabot will be done with a high velocity powder gun. Final tests will be done in a light gas gun.

#### II. DESIGN

#### A. REQUIREMENTS

The required kinetic energy of separation can be calculated simply from mechanics. Thus, for a separation velocity of  $1.5 \times 10^4$  cm/sec and a maximum mass of 6 grams, the maximum energy required is

$$KE = \frac{mv^2}{2} = 67.5 \text{ joules}$$

For velocity ranges of interest, the acceleration time of most light gas guns is between 400 and 800 microseconds. Ideally, the propellant would be completely consumed close to the time the sabot emerges from the gun muzzle. This burning time requirement restricts the propellant to rifle and pistol powders.

Calculations were done for the following powders:

Bullseye
 Unique
 No. 2400
 Hivel No. 2
 Herco

All calculations assumed that 10 percent of the energy content of the powder would be converted to kinetic energy of the sabot halves. When computing the cavity volume for each powder, 10 percent was added for the initiator.

#### B. ENGINEERING CALCULATIONS

1. Calculation of PdV Work, Pressure, and Volume Change

The following procedure was used to compute the PdV work, pressure, and volume change requirements for the powders listed in Section A. (See Appendix A for detailed sample calculation.)

- a. Using heat of explosion and 10 percent conversion efficiency, calculate mass of powder.
- b. From bulk density and result of step a, calculate the volume the powder will occupy. Add 10 percent for initiator. This is propellant cavity volume.
- c. Assuming the perfect gas law,  $p = \frac{nRT}{V}$ , calculate the pressure

developed in the propellant cavity at complete consumption of the powder.

Assuming a reversible adiabatic expansion and a perfect gas, one may derive the following equation from thermodynamic relations:

$$W = \frac{\partial nRT}{\partial -1} \left[ \left( \frac{P_2}{P_1} \right)^{\frac{\partial -1}{\partial T}} - 1 \right]$$
(1)

where

W	3	required	kinetic ene	rgy of sabo	ot halves

- $\mathcal{T} = \mathbf{ratio} \text{ of specific heats}$
- n = moles of powder
- R = gas constant
- T = adiabatic, isochoric gas temperature
- P1 = initial cavity pressure (maximum developed)
- P2 = cavity pressure after performance of the required PdV work
- d. Using given characteristics and results of steps a-c. calculate P<sub>2</sub> from Equation (1),

For a reversible adiabatic expansion, the following equation holds:

$$\frac{P_2}{P_1} = \left(\frac{V_1}{V_2}\right)^{2}$$
(2)

where

r1 -	#	initial cavity pressure
P2	<b>1</b> 2	final cavity pressure
$\overline{v_1}$	×	initial cavity volume
V5	36	final cavity volume

- $\mathcal{T}$  = ratio of specific heats
- e. Using the values determined above for P<sub>1</sub>, P<sub>2</sub>, V<sub>1</sub>, and calculate V<sub>2</sub> from Equation (2). The values of V<sub>1</sub> and V<sub>2</sub> determined from this calculation procedure are input data for the mechanical design of the sabot propellant cavity.

The values of  $\triangle P(P_2 - P_3)$  and  $\triangle V(V_2 - V_3)$  found from the above procedure were compared with those obtained directly from Newton's Second Law of mechanics, viz:  $F = \frac{d}{dt}$  mv.

The results thus obtained were found to be a reasonable check of the values calculated from thermodynamics.

2. Calculation of Powder Burn Time

Since the weights of powder, required cavity volumes, and  $\Delta V$  for the five powders previously listed, were reasonable, the next step was to calculate the burning times. Using data supplied by the monufacturer, and calculated from the procedure described in Section 1, the burning times for these powders were computed as follows:

- a. Using granulation data, calculate the volume of one grain.
- b. Using the density and desired weight of powder, calculate the number of grains.
- c. Using moles per grain data from manufacturer and result of step 6, calculate the total number of moles of gas produced by burning the powder.

Noting that the length of a grain is reduced by burning, along with the radius, it is possible to express the volume of a grain as a function of the radius. This equation is

$$V = \Pi r^{2}(2r-K) = 2\Pi r^{3} - K\Pi r^{2}$$

where

V	=	volume of powder per grain
r	=	radius of the grain
2r -k	=	length of grain $(k = constant depending on amin dimensional)$
		on grain giniensions)

Now the number of moles of gas which can be produced, N', is

$$N' = m \rho V n^*$$

where

m	×	moles of gas per grain of powder
م	×	density of powder
n <sup>#</sup>	=	number of grains

And the number of moles of gas present in the cavity at any given grain radius is

$$N(r) = N - N^{r}$$

where

$$N(r) = N - m \rho n^{*} (2\pi r^{3} - K\pi r^{2})$$
(3)

Since the pressure in the cavity is  $P = \frac{RT}{V_1}$  N, it can be

expressed as a function of radius thusly,

$$P = \frac{RT}{V_1} N(r)$$
(4)

The burning rate of a powder grain is a function of the pressure

$$R = cP^{n} = \frac{dr}{dt}$$
(5)

Combining Equations (3), (4), and (5), we have

$$\frac{dr}{dt} = c \left\{ \frac{RT}{V_1} \left[ N - m\rho n^* (2\pi r^3 - \kappa \pi r^2) \right] \right\}^{\prime \prime}$$
(6)

whose reciprocal is

$$\frac{dt}{dr} = \frac{1}{c} \left\{ \frac{RT}{V_1} \left[ N - m\rho n^* (2\pi r^3 - \kappa \pi r^2) \right] \right\}^{-n}$$
(7)

- d. Using Equation (7), calculate  $\frac{dt}{dr}$  for various values of r and plot  $\frac{dt}{dr}$  vs. r.
- e. Graphically integrate the curve obtained in step a. This value is the burning found to be in the range of interest.

The burning times of the five powders were calculated in this manner and found to be in the range of interest.

#### 3. Results of Calculations

Results of the calculations are presented in Table 1. From this table it can be seen that propellants (1), (2), and (5) are suitable for use in light gas guns. Propellant (4) has a burning time suitable for the standard caliber 0.60 powder gun used for some of the experiments.

#### C. MECHANICAL DESIGN

#### 1. Propellant Cavity and Cup

The accomplishment of PdV work which imparts kinetic energy to the sabot halves requires a discrete change of volume of the propellant cavity. Since each half of the sabot carries half of the propellant cavity, provision must be made for sealing in the high pressure gas to permit an adiabatic expansion as the sabot halves start to separate. If the propellant cavity is a cylinder this can be accomplished by simply placing a thin wall sleeve within the cavity. Thus the sabot halves slide along this sleeve for some small distance which allows

	<u> </u>	SULTS OF CALC	<b>ULATIONS</b>		
	(1)	(2)	(£)	(4)	(2)
Powder	Bullseye	Unique	2400	Hivel \$2	Herco
Mass	124 mg	124 mg	150 mg	146 mg	152 mg
Cavity Volume (V1)	0.245 cm <sup>3</sup>	0,210 cm <sup>3</sup>	0,192 cm <sup>3</sup>	0, 169 cm <sup>3</sup>	0,284 cm <sup>3</sup>
Pressure (P <sub>1</sub> )	88 × 10 <sup>3</sup> psi	99 x 10 <sup>3 psi</sup>	12 <b>4</b> × 10 <sup>3</sup> psi	136 × 10 <sup>3</sup> pai	86 × 10 <sup>3</sup> psi
△ V (V2 - V1)	0.118 cm <sup>3</sup>	0.105 cm <sup>3</sup>	0,080 cm <sup>3</sup>	0.074 cm <sup>3</sup>	0.114 cm <sup>3</sup>
Burn Time	554 Ju sec	403 y sec	1096 Ju s	1200 y s	664 Ju s

TABLE I

л •

i4 ⊀≁

8

8

.

the proper volume expansion. There is a limit, of course, to the amount of travel that can be allowed, that is, the required PdV work would have to be completed when the sabot halves were some small distance apart. This separation distance was selected to be 0.1 inch.

Simply using a sleeve is not enough, however. It is quite likely that after separation the sleeve would remain behind the projectile and strike the target. Thus it is desirable to force the sleeve to separate with one of the sabot halves. This is easily accomplished by merely closing one end so that it takes the form of a cup. The gas pressure works against the closed end, transmitting the separating force through it to the sabot half so that the cup must go with that half.

The two different types of propellant cups used are shown in Figure 1. In Figure 1a is the propellant cup used with Hivel No. 2 powder. The cavity in which this cup was used had a volume of 0.169 cubic cuntimeters. These cups were fabricated from copper. The canical bottom is simply the angle of the end of a drill bit so that it fits properly in a drilled cavity. The cups were fabricated by punch and die. Figure 1b shows the cup used with 0.22 cm<sup>3</sup> and 0.25 cm<sup>3</sup> cavities. These cups were machined from 2024-T4 aluminum to reduce weight. The wall thickness however was made greater than that of the copper cup. This was necessary because the copper cup had a tendency to rupture under the high pressures developed in the cavities.

#### 2. Sabot Design

The schot configurations used were extensions of previous work. The three different types, all fabricated from 2024-T4 aluminum, are shown in cross section Figure 2. Figure 2a shows the Mark V sabot. This sabot was used only with the copper cup which is shown in Figure 1a. The conical tail is to prevent formation of a shock wave within the sabot to result from sudden application of the high pressure gas of the light gas gun. Figure 2b shows the Mark VI sabot. In order to reduce the weight of the sabot, metal was removed from the rear so that it was humispherical instead of conical. It too used the copper cup of Figure 1a. Figure 2c shows the Mark VI Mod 1 sabot. This sabot was designed for the aluminum cup of Figure 3E and was used with the shorter burning time powders which require the larger cavity.



.

Figure 1(a) Copper Propellant Cup



Figure 1(b) Aluminum Propeilant Cup



Figure 2(a) Mark V Sabot

T







Figure 2 (c) Mark VI Mod 1 Sabot

One of the problems of designing sabots of this type is to keep the weight to a minimum. The presence of the cavity not only increases the required length of the sabot but also impairs its structural strength. The Mark VI Mod 1 sabot was designed to be made of aluminum. Its mass of approximately 9.85 grams was the minimum that could be obtained with any degree of structural integrity. In an attempt to reduce the mass by using a lower density material, an extensive search was made for plastics which might be strong enough to withstand the acceleration forces. Only one was salected for testing. This material was GB28E dielectroc fiberglass-epoxy laminate. The total mass of sabots made from this material was about 8 grams.

The projectile used in all of the sabots was a 3/8 inch diameter chrome alloy steel sphere weighing 3,52 grams. The mass of the sphere is included in the total masses given for the sabots. Also included in this total mass is the propellant and initiator.

#### 3. Initiator

The initiator compound used to ignite the propellant was lead styphnate. This was packed into a thin walled glass tube which was placed in the propellant cavity. The tube was made by drawing down standard glass tubing to a small diameter. After resolidification of the glass, several initiator tubes could be cut from the drawn section.

Two kinds of tube placement were used. These are shown in Figure 3. During the first part of the experimentation, the tubes were placed as shown in Figure 3a, verticially in the rear of the cavity. In the remaining shots the tubes were placed as shown in Figure 3b, horizontally and longitudinally in the cavity, with one end of the glass tube against the front of the cavity. This latter arrangement was found to offer greater reliability.

The operation of the initiator is as follows. When the gun is fired the sudden acceleration causes the tube to crush under its own weight. The glass splinters are forced into the lead styphnate. The resulting friction detonates the styphnate which creates a very hot flash that ignites the propellant.



Figure 3(b) Horizontal-Longitudinal Initiator Placement

ः

This initiator works cuite volt of the other theory reliable. To improve reliability, theory mound glass was mixed with lead styphiate before packing into the tube. About one part glass was used with three parts of lead styphiate. These initiators proved to be entirely satisfactory. As an additional precaution, however, zirconium ead peroxide powder was mixed in with the propellant grains. This compound is much more flame sensitive than the propellant and puts cut a horter flame sensitive than the propellant and puts cut a horter flame sensitive than the propellant and puts cut a horter flame sensitive than the propellant and puts cut a horter flame sensitive than the propellant and puts cut a horter flame sensitive that the propellant and puts cut a horter flame sensitive that the propellant and puts cut a horter flame sensitive that the propellant and puts cut a horter flame sensitive that the propellant and puts cut a horter flame sensitive that the propellant and puts cut a horter flame sensitive that the propellant and puts cut a horter flame sensitive that the propellant and puts cut a horter flame sensitive that the propellant and puts cut a horter flame sensitive that the propellant and puts cut a horter flame sensitive the propellant and puts cut a horter flame sensitive flame sensitive and proved styphing of a sensitive that the propellant flame of icud styphing of a sensitive were used in each initiator and about 50 milligrams of zirconium lead peroxide ZrPbO2 were used

Best Available Copy

#### III. EXPERIMENTS

Two types of experiments were conducted on this program and a total of 33 shots were fired. The development work was done with a caliber .60 powder gun range at velocities up to 8000 feet/second. This encompassed the first 27 shots. Final testing was done in the light gas gun range at the U.S. Naval Research Laboratory at velocities up to 14,000 feet/second.

#### A. EXPERIMENTAL FACILITIES

#### 1. Powder Gun Range

A diagram of the powder gun range used is shown in Figure 4. Two smooth bore caliber .60 powder guns served as the high velocity projectors. One gun had a five foot long launch tube and was used for achieving maximum muzzle velocity. The other gun had a 2.5 foot long launch tube and was used for simulating the time-in-launch-tube of light gas guns so that the shorter burning time propellants could be tested

The sabots were launched into a 12 foot long, 19 inch diameter vacuum chamber in which the separation took place. Inside the chamber were steel baffles spaced 16 inches apart down the full length. The projectile and sabots passed through 4 inch diameter holes in the center of the baffles. At the end of the tank was a 1/8 inch thick necprene diaphragm 5 inches in diameter. After sabot separation and trapping by the baffles, the projectile passed through the rupture diaphragm into a sand chamber which was cutside the tank. The gun was electrically fired by a 50 volt pulse from an electronic timing generator. This timing generator was also used for operation of the instrumentation. Overall control of the system was accomplished with a remotely operated sequence timer.

#### Instrumentation

Two types of diagnostics were used. The sabot and projectile velocity was measured by time of flight down the length of the range, and flash x-ray was used to investigate sabot separation. In addition the baffle assembly inside the tank was designed to be removed. Sabot separation velocity could therefore be measured from the locations of penetration of the baffles. A block diagram of the instrumentation system appears in Figure 5.



)

1

Hgure 4. Diagram of Powder Gun Range



,

Triggering of the flash x-ray and the first time of flight pulse was received from a switch at the end of the launch tube. Both make contact and break contact types were used which were actuated by the sabots. This switching proved to be the most troublesome part of the system. The percentage of reliability of proper functioning was much less greater than the desired.

The flash x-ray was a 1 channel, 105 kilovolt system with a 30 nancsecond pulse width. It was triggered by a time delay generator which was started by the switch at the end of the launch tube. The flash x-ray proved to be extremely valuable and much information was obtained. Failure of the triggering switch to function properly did prevent the acquisition of some data, although it was usually still possible to measure the sabot separation velocity from the baffle penetration.

The second time-of-flight signal was received from foil screens placed between the end of the vacuum chamber and the sand chamber which caught the projectiles. The sweep of an oscilloscope was storted at the same time the firing signal was sent to the gun. The two pulses, one from the launch tube and the other from the time of flight screens, were then displayed on the oscilloscope sweep.

#### 2. Light Gas Gun Facility

The last 6 experiments were conducted in a caliber .60 light gas gun at the U. S. Naval Research Laboratory, Washington, D. C. This gas gun uses a 40 millimeter pump tube and fires into an evacuated range approximately 35 feet in length. This vacuum range has thick sized baffles spaced down its entire length. Holes in the beffles are from 2 - 3 inches in diameter.

The instrumentation on these shots consisted of two high speed framing cameras. One of these was stationed at the target end of the range and was used to measure the velocity. The other was at the gun end of the range and was used to investigate sabot separation. Velocity measurements were made relicibly, however, much difficulty was experienced with the sabot separation camera. This camera was stationed about 40 inches from the end of the launch tube. The gas stream from the launch tube was still dense enough at this position to obscure the projectile and sabot halves from view. The desired range pressure was 1 millimeter of mercury. However, shots at 50 and 100 millimeters of mercury were tried in an attempt to slow down the gas stream. There was no improvement in this problem; however, some information was gathered from this camera station.

#### **B. EXPERIMENTAL RESULTS**

Table 11 is a summary of the experimental result. This table presents a cross section of the types of experiments that were done. The separation velocities achieved were not quite as high as desired, but are entirely adequate for most applications. For example: if the sabot can withstand the high "g" forces, a separation velocity of  $1.0 \times 10^4$  cm/sec would give a total distance between sabot halves of about one foot at the end of a 35 foot range, for a projectile velocity of 25,000 feet/second. Figure 6 is the flash x-ray photograph showing second of experiment 5.2-8. Figure 7 is a photograph of the sabot.

In general, it was found that if complete consumption of the cavity propellant (calculated burn time) occurred within 10) microseconds before sabot exit from the launch tube, the sabot separation velocity was not significantly impaired. If the time difference was 200 - 300 microseconds, the reduction in separation velocity was serious. This indicates that cavity pressure was last due to cooling of the gas, or possibly leckage. Leakage seems unlikely because of the sulf-sealing effect of the gas pressure acting on the walls of the propellant cup. The aluminum propellant cups were found to be better than the coppel cups. The copper had a tendency to rupture from the cavity pressure as the sabot halves separated,

The flash x-ray photographs showed that the sabots opened from the recr. This is probably due to the center of pressure being aft of the center of gravity of each sabot half. This may have induced some of the fracturing of the copper cups. It also could cause a lower separation velocity because of drag on the cup. The fiberglass sabots worked well in the powder gun. The one which was tried in the light gas gun broke up in the launch tube.

Of the six light gas gun shots, a separation velocity measurement was obtained on only one. This was  $0.8 \times 10^4$  cm/sec. This was due to the difficulty with the instrumentation, as previously stated. Since the real test is not so much the separation velocity as it is just whether or not the sabot material strikes the target, steel and aluminum targets were used

TABLE II

SUMMARY OF EXPERIMENTAL RESULTS

<mark>Separation Vel</mark> ocity 1.1 x 10 <sup>4</sup> cm/sec	1.5 x 10 <sup>4</sup> cm/soc	1.0 × 10 <sup>4</sup> cm/sec	0,9 × 10 <sup>4</sup> cm/sec	0.8 × 10 <sup>4</sup> cm/suc
Time in aunch Tube 1, 155 y sec	ا <sub>د</sub> ا55 ب هود	657 µ soc	675 y sec	620 Ju sec
Velocity L 7,800 fps	8.570 fps	6, 830 fps	6,670 fps	14,000 fps
Yacuum 0,8 mm	0.6 mm	0.9 mm	0.8 mm	50 mm
Powder Hivel #2	Hivel <sup>4</sup> 2	Rullseye	Unique	Bullseye
Sabot Material Aluminum	Fiberglass	Aluminum	Aluminum	Aluminum
Shot No. 5.2-8	5.2-11	5.2-21	5.2-27	5.2-30

All sabots Mark VI Model 1. All projectiles 3/8" diameter chrome alloy steel sphere.

.

20



,

.

Figure 6. Flash X-Ray of Shot 5.2-8 Separation



Figure 7. Photograph of Mark VI Mod. 1 Sabot

and examined after every shot. The first light gas gun shot fired was a dummy sabot, i.e., inert material was in the cup in place of the propellant. The intent of this was to look for breakup of the sabot in the launch tube. The sabot did not break up; the projectile struck the target, and a very few pieces of the sabot did also. On all of the other shots, however, the projectiles failed to hit the target. Some sabot material did strike the targets on most of these shots, however, Since the sabots apparently were not breaking up in the launch tube, and since separation was being achieved, it appears that some force was causing the projectilesabot assembly to be knocked off trajectory. This appears to be substantiated by the fact that in several shots a part of the sabot struck the target but no projectile hit was observed. Thus if the whole assembly were canted out of line and separation was achieved, this result would be expected. The failure of the projectiles to hit the target in this shot could be attributed to one or more of three causes:

- Balloting in the launch tube. This is quite likely, since the L/D of the sabot (contact surface) is less than 1. L/D of 2 is usually considered best.
- 2 Gas blast. The sabots begin to open immediately after leaving the launch tube. Since this opening is asymmetrical, the inside surfaces of the sabot halves are at different angles relative to the trajectory; thus a net lateral force could be applied by the gas stream emerging from the bore immediately behind the sabot. The force of the stream is an order of magnitude greater than from the powder gun.
- 3 Sabet-half dragging on projectile. Part way through the experimentation it was noticed that the projectiles in some of the remaining sabots had a tendency to stick in one half. This could cause the sphere to be pulled off trajectory as the sabot opened. Correction of this tendency to stick did not produce a larget impact, however. It should be noted that the light ges yen range is guite long, with numerous baffles inside. Some of these baffles have holes only two inches in diameter, thus a small perturbation can prevent a hit.

Complete data on all the experiments conducted is given in Table III.

22

Best Available Copy

# A

	Sebet Type	Totel Weight	Initiator Tube	Initiator Material	Powder
5.2-1	Mk V	11,02 gm	None	Pb styph.	Hivel
2	Mk V	11,02 gm	Vertical	••	••
3	Mk ∨	11 <b>.00 g</b> m	н	11	0
4	Mk VI Mod 1	9,95 gm		16	11
5	Mk VI Mod 1	9,95 gm		••	
6	M' VI Mod 1	9,95 gr	••	11	**
7	Mk VI Mod 1	9,95 gm	••	11	*1
8	Mk VI Mod 1	9,85 gm	89	81	1.
9	Mk VI Mod 1	9.85 gm	80	83	
10	Mk VI Mod 1	9,85 gm	None	None	None
11	Mk VI Mod 1 fiberglo	as 8.09 gm	Vertical	Pb styph.	Hivel N
12	Mk VI Mod 1 fibergia	ns 8,09 gm	٧J		11
13	Mk VI fiberglass	8.09 gm	11		
14	Mk VI	10.22 gm	Horizontal	11	
1\$	Mk VI	10.1 gm	11	Pb styph./	11
16	Mk ∨I	10,16 gm	••	crushed glass "	
17	Mk VI Mad 1	10.09 gm	11	Styph. glass	"
18	Mk∨l Mod 1 fibergla	s 8,14 gm	**	ZrPbO2	
19	Mk VI Mod I fibergia	as 8,10 gm	"		••
20	Mk VI Mod 1 fibergla	s 8,12 gm	61	<b>6</b> 9	Builseye
21	Mk VI Mod 1	8,12 gm	H	**	34
22	Mik ∨I Mod 1	ዮ, 78 gm	н	"	••
23	Mik VI Mod 1	9,74 gm	н	••	Herco
24	Mik VI Mod 1	9,80 gm	14	n	Unique

# TABLE III

# EXPERIMENTAL RESULTS

Hivel No.2       152 mg       1200 μ s       1300 μ s       6° U0 fps       0.8 mm       -         "       "       1285 μ s       7000 fps       0.8 mm       0.9 x 10 <sup>4</sup> cm/sec         "       "       1270 μ s       7060 fps       0.4 mm       -         "       "       1300 μ s       6900 fps       0.8 mm       0.77 x 10 <sup>4</sup> cm/sec         "       "       1300 μ s       6900 fps       0.8 mm       0.77 x 10 <sup>4</sup> cm/sec         "       "       1300 μ s       6900 fps       0.8 mm       0.77 x 10 <sup>4</sup> cm/sec         "       "       1300 μ s       6700 fps       0.15 mm       0.74 x 10 <sup>4</sup> cm/sec         "       "       1300 μ s       6700 fps       0.8 mm       1.1 x 10 <sup>4</sup> cm/sec         "       "       1300 μ s       7500 fps       0.8 mm       1.1 x 10 <sup>4</sup> cm/sec         "       "       1200 μ s       7500 fps       0.8 mm       1.5 x 10 <sup>4</sup> cm/sec         "       "       1200 μ s       7600 fps       0.9 mm       nil         Hivel No.2       152 mg       1200 μ s       1150 μ s       7800 fps       0.6 mm       1.5 x 10 <sup>4</sup> cm/sec         "       "       -       -       0.9 mm       -	
<ul> <li>1285 μ s</li> <li>1285 μ s</li> <li>1270 μ s</li> <li>1270 μ s</li> <li>1270 μ s</li> <li>1270 μ s</li> <li>1300 μ s</li> <li>6900 fps</li> <li>0.4 mm</li> <li>1300 μ s</li> <li>6900 fps</li> <li>0.8 mm</li> <li>0.77 x 10<sup>4</sup> cm/sec</li> <li>1300 μ s</li> <li>6500 fps</li> <li>0.2 mm</li> <li>1300 μ s</li> <li>6500 fps</li> <li>0.2 mm</li> <li>1300 μ s</li> <li>6500 fps</li> <li>0.15 mm</li> <li>0.74 x 10<sup>4</sup> cm/sec</li> <li>1300 μ s</li> <li>6700 fps</li> <li>0.15 mm</li> <li>0.74 x 10<sup>4</sup> cm/sec</li> <li>1300 μ s</li> <li>6700 fps</li> <li>0.8 mm</li> <li>1.1 x 10<sup>4</sup> cm/sec</li> <li>1150 μ s</li> <li>7500 fps</li> <li>0.8 mm</li> <li>1.1 x 10<sup>4</sup> cm/sec</li> <li>1180 μ s</li> <li>7600 fps</li> <li>0.9 mm</li> <li>1.5 x 10<sup>4</sup> cm/sec</li> <li>1180 μ s</li> <li>7600 fps</li> <li>0.6 mm</li> <li>1.5 x 10<sup>4</sup> cm/sec</li> <li>1160 μ s</li> <li>7750 fps</li> <li>0.9 mm</li> <li>0.52 x 10<sup>4</sup> cm/sec</li> <li>1160 μ s</li> <li>7750 fps</li> <li>0.9 mm</li> <li>0.52 x 10<sup>4</sup> cm/sec</li> <li>1160 μ s</li> <li>7750 fps</li> <li>0.9 mm</li> <li>0.26 x 10<sup>4</sup> cm/sec</li> <li>1160 μ s</li> <li>7750 fps</li> <li>0.9 mm</li> <li>0.26 x 10<sup>4</sup> cm/sec</li> </ul>	
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	
""""""""""""""""""""""""""""""""""""	
$\frac{1}{100 \ \mu s} = \frac{1}{100 \$	
""""       1340 μs       6700 fps       0.15 mm       0.74 x 10 <sup>4</sup> cm/sec         """"       1300 μs       6930 fps       0.7 mm       _         """"       1300 μs       6930 fps       0.7 mm       _         """"       1150 μs       7800 fps       0.8 mm       1.1 x 10 <sup>4</sup> cm/sec         """"       1200 μs       7500 fps       0.8 mm       0.9 x 10 <sup>4</sup> cm/sec         None       -       -       1180 μs       7600 fps       0.9 mm       nil         Hivel No.2       152 mg       1200 μs       1150 μs       7800 fps       0.6 mm       1.5 x 10 <sup>4</sup> cm/sec         """"       -       -       0.9 mm       nil         Hivel No.2       152 mg       1200 μs       1150 μs       7800 fps       0.6 mm       1.5 x 10 <sup>4</sup> cm/sec         """"       -       -       0.9 mm       -       -       -       0.9 mm       -         """       ""       -       -       0.9 mm       -       -       -         """       ""       -       -       0.9 mm       -       -       -       -       -       -       -       -       -       -       -       -       -       -	
"       1300 μ s       6930 fps       0.7 mm       -         "       "       1150 μ s       7800 fps       0.8 mm       1.1 x 10 <sup>4</sup> cm/sec         "       "       1200 μ s       7500 fps       0.8 mm       0.9 x 10 <sup>4</sup> cm/sec         None       -       -       1180 μ s       7600 fps       0.9 mm       nil         Hivel No.2       152 mg       1200 μ s       1150 μ s       7800 fps       0.6 mm       1.5 x 10 <sup>4</sup> cm/sec         "       "       -       -       0.9 mm       nil         Hivel No.2       152 mg       1200 μ s       1150 μ s       7800 fps       0.6 mm       1.5 x 10 <sup>4</sup> cm/sec         "       "       -       -       0.9 mm       -       -         "       "       -       -       0.9 mm       -         "       "       1160 μ s       7750 fps       0.9 mm       0.26 x 10 <sup>4</sup> cm/sec         "       "       1160 μ s       7650 fps       0.7 mm <td></td>	
"       1150 μs       7800 fps       0.8 mm       1.1 x 10 <sup>4</sup> cm/sec         "       "       1200 μs       7500 fps       0.8 mm       0.9 x 10 <sup>4</sup> cm/sec         None       -       -       1180 μs       7600 fps       0.9 mm       nil         Hivel No.2       152 mg       1200 μs       1150 μs       7800 fps       0.6 mm       1.5 x 10 <sup>4</sup> cm/sec         "       "       -       -       0.9 mm       nil         Hivel No.2       152 mg       1200 μs       1150 μs       7800 fps       0.6 mm       1.5 x 10 <sup>4</sup> cm/sec         "       "       -       -       0.9 mm       -       -       0.9 mm       -         "       "       -       -       0.9 mm       -       -       -       0.9 mm       -         "       "       -       -       0.9 mm       -	
"       1200 $\mu$ s       7500 fps       9.8 mm       0.9 x 10 <sup>4</sup> cm/sec         None       -       -       1180 $\mu$ s       7600 fps       0.9 mm       nil         Hivel No.2       152 mg       1200 $\mu$ s       1150 $\mu$ s       7800 fps       0.6 mm       1.5 x 10 <sup>4</sup> cm/sec         "       "       -       -       0.9 mm       -       -         "       "       -       -       0.9 mm       -         "       "       1160 $\mu$ s       7750 fps       0.9 mm       0.52 x 10 <sup>4</sup> cm/sec         "       "       1160 $\mu$ s       7750 fps       0.9 mm       0.26 x 10 <sup>4</sup> cm/sec         "       "       1180 $\mu$ s       7605 fps       0.7 mm       0.62 x 10 <sup>4</sup> cm/sec	
None       -       -       1180 μ s       7600 fps       0.9 mm       nil         Hivel No.2       152 mg       1200 μ s       1150 μ s       7800 fps       0.6 mm       1.5 x 10 <sup>4</sup> cm/sec         "       "       -       -       0.9 mm       -         "       "       1160 μ s       7750 fps       0.9 mm       0.52 x 10 <sup>4</sup> cm/sec         "       "       1160 μ s       7750 fps       0.9 mm       0.26 x 10 <sup>4</sup> cm/sec         "       "       1160 μ s       7750 fps       0.7 mm       0.62 x 10 <sup>4</sup> cm/sec	
Hivel No.2       152 mg       1200 μ s       1150 μ s       7800 fps       0.6 mm       1.5 x 10 <sup>4</sup> cm/sec         "       "       -       -       0.9 mm       -         "       "       1160 μ s       7750 fps       0.9 mm       0.52 x 10 <sup>4</sup> cm/sec         "       "       1160 μ s       7750 fps       0.9 mm       0.26 x 10 <sup>4</sup> cm/sec         "       "       1180 μ s       7650 fps       0.7 mm       0.62 x 10 <sup>4</sup> cm/sec	
$\frac{1}{100 \mu s} = - 0.9 \mu m = - 0.52 \times 10^4 cm/sec$	
""""""""""""""""""""""""""""""""""""	, ,
" $1160 \mu s 7750 \text{ fps} 0.9 \text{ mm} 0.52 \times 10^4 \text{ cm/sec}$ $1160 \mu s 7750 \text{ fps} 0.9 \text{ mm} 0.26 \times 10^4 \text{ cm/sec}$ $1180 \mu s 7650 \text{ fps} 0.7 \text{ mm} 0.62 \times 10^4 \text{ cm/sec}$	N
" $1160 \mu s 7750 \text{ fps} 0.9 \text{ mm} 0.26 \times 10^4 \text{ cm/sec}$ " $1180 \mu s 7650 \text{ fps} 0.7 \text{ mm} 0.62 \times 10^4 \text{ cm/sec}$ " $1180 \mu s 7650 \text{ fps} 0.7 \text{ mm} 0.62 \times 10^4 \text{ cm/sec}$	· ·
" " $1180 \mu s$ 7650 fps 0.7 mm 0.62 x 10 <sup>4</sup> cm/sec	, v
H H H SALE	, ,
" 1160 $\mu$ s 7750 fps 0.7 mm 0.04 x 10 <sup>4</sup> cm/sec	т V
$1 Half = 1120 \mu s 8000 fps 0.5 mm 1 l x 104 cm/rec$	v
	T (
Bullseye 124 mg 554 μ s 580 μ s 7740 fps 0.8 mm	N
и и «б55 м в 6850 fps 0.9 mm 1.0104 (	N
" " 675 µs 6670 for 0.7 mm 1.0 x 10° cm/sec	Ŷe
Herco 150 mg 654 µs 510 µs 6670 for 0.7 0.07 mm	Ye
Unique 124 mg 403 µs 67	N

# TABLE III

# EXPERIMENTAL RESULTS

		iator Material	Powder Type	Powder Weight	Powder Burn Time	Time in Lounch Tube	Velocity	١
locity	Baffle	b styph.	Hivel No.2	152 mg	ء بر 1200	<b>ء بر 1300</b>	6900 fps	-
	No	69	<b>0</b> 1	84		<b>ا بر 1285</b>	7000 fps	
n/sec	Yes		10	11		ا بر 1 <b>27</b> 0	7060 fps	
	No	81	•	11	<b>4</b> 4	1300 м в	6900 fps	
m/sec	Yes	11	11	47		1380 μ κ	6500 for	Č
	No	81	11	0		1340	6700 fm	, ,
m/sec	Yes	**	44	aı	n	1300	6930 fee	
	No	44	<b>B</b> I	*	u	1150	7900 6	0
/sec	Yes	**	<b>17</b>			1200		U
Isec	_	3 <b>00</b>	Nena			1200 μ s	/500 fps	Q
	_			-	-	<b>ء</b> بر 1180	7600 fps	0
	No	styph.	Hivel No.2	152 mg	1200 JA S	<b>ا بر</b> 1150	7800 fps	0
/sec	Yes	••	11	*	4 11 1	-	-	0,
	No			H ···		-	-	0.
	No	**	н	"	0	a بر 1160	7750 fps	0.
/sec	Yes	styph./	đi	11	**	1160 д в	7750 fps	0.
/sec	Yes	H H	"	11	u	ه بر 1180	7650 fps	0.
/sec	Yes	ph. glass	84	4	• • •	ء بر 1160	7750 fps	0.
/sec	Yes		38	4.	**	1120	8000 (	•.
sec	Yes		41	"	9 89	-	ooo ips	0.
	No	11	Bullseye	124 ma	554	500	-	0.
	Nia	8 <b>9</b>	14			380 μ 1	7740 fps	0.8
	140	*1				<sup>655</sup> µ s	6350 fps	0.9
Sec	Yes		€€ .	\$ <b>5</b>	€€	s 11 675	6670 fps	0.7
lec	Yes	м	Herco	1 <b>5</b> 0 mg	664 ji s	s بر 675	6670 fps	0.7
sec	No	it	Unique	124 mg	403 Ju s	<del>5</del> 75 μ s	6670 fps	0.8

# B

Vacuum	Separation Velocity	Baffle Impact	Sabot in Target	Remarks
0.8 mm	-	No	Yes	Initiator powder sprinkled in propellant.
0.8 mm	0.9 × 10 <sup>4</sup> cm/sec	Yes	Little	
0.4 mm	-	No	Yes	
0.8 mm	0.77 x 10 <sup>4</sup> cm/sec	Yes	No	X-ray shows sabot opening from the rear
0.2 mm	-	No	Yes	ar 3 from launch tube.
0,15 mm	$0.74 \times 10^4$ cm/sec	Yes	Very little	
0.7 mm	-	No	Yes	
0,8 mm	1.1 x 10 <sup>4</sup> cm/sec	Yes	No	
0, <b>8 mm</b>	0.9 x 10 <sup>4</sup> cm/sec	-	Very little	
0 <b>.</b> 9 mm	nil	No	Yes	Test for aerodynamic separation. X-ray
0,6 mm	$1.5 \times 10^4$ cm/sec	Yes	Very little	snows succe opening from from.
0.9 mm	-	No	No	
0,9 mm	-	No	Yes	
0.9 mm	0.52 x 10 <sup>4</sup> cm/sec	Yes	Very little	X-ray shows cup ruptured.
).9 mm	0.26 x 10 <sup>4</sup> cm/sec	Yes	No	X-ray shows cup intact but free of sabot.
).7 mm	0.62 × 10 <sup>4</sup> cm/sec	Yes	Some	X-ray shows cup ruptured.
),7 mm	0.04 x 10 <sup>4</sup> cm/sec	Yes	1 Half	
).5 mm	1.1 x 10 <sup>4</sup> cm/sec	Yei	Very little	
•.9 mm	-	No	No	
.8 mm	-	No	Very little	
.9 mm	$1.0 \times 10^4$ cm/sec	Yei	No	
.7 mm	$1.0 \times 10^4$ cm/sec	Yes	No	
,7 mm	0.07 x 10 <sup>4</sup> cm/sec	No	Yes	Front opening (aerodynamic) Powder failed to insite
, 8 mm	nil	No	Yes	iomder idned id ignine.

	11	Mk VI Mod 1 fiberglass	8.09 gm	Vertical	Pb styph.	
	12	Mk VI Mod 1 fiberglass	8.09 gm	"	11	
	13	Mk VI fibergias	8.09 gm	0	"	
	14	Mk ∨I	10.22 gm	Horizontal		
	15	Mk VI	10,1 gm	11	Pb styph./	
	16	Mk VI	10,16 gm	••	crushed glass	
	17	Mk VI Mad 3	10.09 gm	11	Styph. glass	
	18	Mk VI Mod 1 fiberglass	8,14 gm	••	221002	
	19	Mk VI Mod I fiberglass	8,10 gm	"		
	20	Mk VI Mad 1 fiberglass	8.12 gm	**	**	
	21	Mk VI Mod 1	8,12 gm	"	"	
	22	Mk VI Mod 1	9,78 gm	•1		
	23	Mik VI Mod 1	9 <b>,74 g</b> m	**	51	
	24	Mk VI Mod 1	9 <b>,8</b> 0 gm	e#	IA .	
	25	Mk VI Mod 1	9,58 gm	••		
	26	Mk VI Mad 1	9,83 gm		"	
	27	Mk VI Mad 1	9,87 gm	**	17	
	28	Mk VI Mod 1	10.1 gm	None	None	
f	29	Mk VI Mod 1	9.91 gm	86	11	
5	30	Mk VI Mod 1	10.0 gm	**	84	
	31	Mk VI Mad 1	9 <b>,</b> 94 gm		"	
	32	Mk VI Mad 1 fiberglass	7.97 gm	88		
I	33	Mk VI Mod 1	9,95 gm	10	n	

l

E

ł

ι

٢

8

C

------

	Hivel No.2	152 mg	s بر 1200 s	<b>ء</b> ببر 1150	7800 Fps	0,6 mm	1.5 x 10 <sup>4</sup> cm/se
	11	t.	11	-	-	0.9 mm	-
	U	u	D	-	-	0,9 mm	-
	11	31	11	<b>ء</b> بر ۱۱۶۵	7750 fps	0.9 mm	$0.52 \times 10^4$ cm/s
	11	1.	0	s بر 1160	7750 fps	0 <b>.</b> 9 mm	$0.26 \times 10^4$ cm/s
	D	11	11	<b>ء بر</b> 1180	7650 fp:	0.7 mm	$0.62 \times 10^4$ cm/se
<b>5</b> 5	н	*1	11	s بر 1160	7750 fp <b>s</b>	0 <b>.</b> 7 mm	$0.04 \times 10^4$ cm/se
	"	11		1120 H S	8000 fps	0.5 mm	1 Half 1.1 x 10 <sup>4</sup> cm/sec
	"	**	41	-	-	0 <b>.</b> 9 mm	-
	Bullsøy e	124 mg	s بر 554 s	s بر 580	7740 fps	0 <b>.</b> 8 mm	-
	11	¥1	н	s بر 655	6850 fps	0.9 mm	$1.0 \times 10^4$ cm/sec
	u .	**		s بر 675	6670 fps	0.7 mm	$1.0 \times 10^4$ cm/sec
	Herco	150 mg	664 µ s	s بر 675 s	6670 fps	0.7 mm	0.07 x 10 <sup>4</sup> cm/se
	Unique	124 mg	403 µ s	s بر 575	6670 fps	0.8 mm	nit
	Bullseye	124 mg	s بر 554 s	750 µ s	6000 fps	0 <b>.</b> 8 mm	0.9 x 10 <sup>4</sup> cm/sec
	Herco	130 mg	s بر 664 s	s بر 675 s	6670 fps	0 <b>.</b> 9 mm	nil
	Unique	124 mg	s بر 403	s بر 675	6670 fps	0,8 mm	0.9 x 10 <sup>4</sup> cm/sec
	None	-	-	s بر910	13156 fps	1.0 mm	Yes
	Bullseye	124 mg	s بىر 554 s	s بر 850	14133 fps	50 <b>.</b> 0 mm	Yes
	"	11	н	<b>6</b> 20 مر s	14000 fps	50.0 mm	0.8 × 10 <sup>4</sup> cm/sec
	0	11	11	680 µ s	14000 fps	50.0 mm	Yes
	11	0	11	s بر 1000	12037 fps	100.0 mm	-
	11	"	11	**	-	1.0 mm	Yes

10 <sup>4</sup> cm/ <b>sec</b>	Yes	Pb styph.	Hivel No.2	152 mg	s بر 1200	<b>ء بر</b> 1150	280
	No		u.	11	44	-	
	No	11	11	0	ti.	-	-
x 10 <sup>4</sup> cm/sec	Yes		u .	li.	н	<b>ء بر 116</b> 0	775
x 10 <sup>4</sup> cm/sec	Yes	Pb styph./ crushed glass	n	11	11	1160 у в	775
x 10 <sup>4</sup> cm/sec	Yes		11	11	11	<b>ء بر</b> 1180	765
x 10 <sup>4</sup> cm/sec	Yes	Styph, glass ZrPbO2	"	"	11	<b>ء بر</b> 1160	775
10 <sup>4</sup> cm/sec	Yes	¥8	**	11	ti.	<b>1</b> 120 بر 1	800
	No	**	88	4	81	-	-
	No	"	Bullseye	124 mg	s بر 554 s	s بر 580	77 <b>4</b>
10 <sup>4</sup> cm/sec	Yes	14	H	"	n	655 μ s	685
10 <sup>4</sup> cm/sec	Yes	11	H .	11	16	575 µ s	667
(10 <sup>4</sup> cm/sec	No	H	Herco	150 mg	664 µ s	s بر 675 s	667
1	No	88	Unique	124 mg	403 <sub>н s</sub>	s بر 575	667(
10 <sup>4</sup> cm/sec	Yes	57	Bullseye	124 mg	554 jų s	750 µ s	600
1	No		Herco	130 mg	s بر 664 s	675 µ s	667(
10 <sup>4</sup> cm/sec	Yes	"	Unique	124 mg	s بر 403 s	ء بر 675	6670
52		None	None	-	-	s بر 910	13156
25		"	Bullseye	124 mg	s بنر 554	<b>ء بر 850</b>	14133
10 <sup>4</sup> cm/sec	-	•	**		11	s بر 620	14000
25	-	n	*1	11	u -	680 µ s	14000
	-	11	**	tr.	"	, s بر 1000	12037
25	-	11	**	"	11	-	-

7600 fp <b>s</b>	0, 9 mm	nit	No	Yes	Test for derodynamic separation, 2000 shows salid opening from trout
7800 fp <b>s</b>	0,6 mm	1.5 x 10 <sup>4</sup> cm/sec	Yes	Verv little	
-	0.9 mm	-	Nło	No	
-	0.9 mm	-	No	Yes	
7750 fps	0 <b>.</b> 9 mm	0.52 x 10 <sup>4</sup> cm/sec	Yes	Very little	X-ray shows cup ruptured.
7750 fp <b>s</b>	0.9 mm	0.26 x 10 <sup>4</sup> cm/sec	Yes	No	X-ray shows cup intact but free of sa
7650 fp <b>s</b>	0.7 mm	0.62 x 10 <sup>4</sup> cm/sec	Yes	Some	X-ray shows cup ruptured.
7750 fps	0.7 mm	0,04 x 10 <sup>4</sup> cm/sec	Yes	1 Half	
8000 fps	0.5 mm	$1.1 \times 10^4$ cm/sec	Yes	Very little	
-	0 <b>.9</b> mm	-	No	No	
7740 fps	0.8 mm	-	No	Very little	
6850 fps	0.9 mm	1.0 x 10 <sup>4</sup> cm/sec	Yes	No	
6670 fps	0.7 mm	1.0 x 10 <sup>4</sup> cm/sec	Yes	No	
6670 fps	0.7 mm	0.07 x 10 <sup>4</sup> cm/sec	No	Yes	Front opening (a <b>ero</b> dyn <b>ami</b> c) Powder failed to ignite
6670 fps	0.8 mm	nit	No	Yes	rowder aneu to ignite.
6000 fp <b>s</b>	0.8 mm	0.9 x 10 <sup>4</sup> cm/sec	Yes	Very little	
6670 fps	0 <b>. 9 mm</b>	nil	No	Yes	Front opening (aerodynamic) Powder failed to ignite
6670 fp <b>s</b>	0.8 mm	0.9 x 10 <sup>4</sup> cm/sec	Yes	No	Towder Tarred To Tgimte.
13156 fps	1.0 mm	Ýes	*	ìíes	Sabot break-up test. No break-up.
14133 fps	50 <b>.</b> 0 mm	Yes	-	1 Half	Projectile missed target.
4000 fps	50.0 mm	0.8 x 10 <sup>4</sup> cm/sec	~	Very little	01 IX
4000 fps	50.0 mm	Yes	-	1 Half	1 12
2037 fp <b>s</b>	100.0 mm	-	-	Very little	е т.
-	1.0 mm	Yes	-	011	41 U

. . . . . . . . . .

D

#### **IV** CONCLUSIONS

It can be seen from the experimental results that for velocities up to 14,000 fps this scheme of active sabot separation works. Although the separation velocity of the sabot halves was not as high as predicted by the calculations, it is nevertheless quite satisfactory for most applications.

It is difficult to assess the exact reasons for the separation velocity being less than calculated; however, the following factors may be involved:

- 1. The calculation assumed a reversible adiabatic expansion which this process is not. The error due to this is not expected to be greater than ten percent, however.
- 2. The assumed efficiency of energy conversion was ten per cent. This is believed to be a reasonable value, but a lower efficiency would have caused the slower velocity.
- The burning time calculations are certainly not exact. A significant difference in the burning time and the time in launch tube would result in a lower velocity than calculated.

Additional experimental work would be required to determine which one of the above is causing the lower separation velocity. In all probability, it is some combination of the three. This is somewhat academic, however, since adequate separation performance was achieved.

24

#### V, RECOMMENDATIONS

Two problems remain which need additional attention. The first is the elimination of the effect which causes the projectiles to miss the targets in light gas gun ranges; the second is overall sabot weight reduction so that higher velocities may be achieved.

The two most likely effects which are causing the projectiles to miss the target are (1) sabot balloting in the launch tube, and (2) unsymmetrical opening of the sabot from the rear. The present L/D of the sabot is about 0.55. The L/D should be about 1.5 and preferably 2.0. With the present overall length of the sabot, on L/D of 1.5 could be achieved. This would require one of two things, either not turning a taper and a dame on the ends of the sabot so that the sabot becomes a cylinder, or the fitting of a hollow sleeve about the sabot which would extend the contact surface length without adding metal to the main sabot bady. The first of these solutions has the drawback of adding a lot of weight. It would be however, a much more rigid structures. The addition of a hollow sleeve, as in the sabot to engage the sleeve and the sleeve itself would have to be fairly thin. There is some question whether this latter assembly would withstand the acceleration forces in the gun. Both should be tried, however.

The correction of the unsymmetrical opening of the sabot from the rear should not be a severe problem. The sabot tends to open from the rear now because the center of pressure from the cavity is aft of the center of gravity in the sabot halves. An attempt was made during this program to move the center of gravity aft by removing metal from the front taper of the sabot. This was unsuccessful, however.

The use of a davity which is contaured more to the exterior shape of the sabot would probably correct this. Such a davity could be any shape. These sabots would have to be made by dasting. The use of dasting would provide a possible solution to the problem of unsymmetrical opening, also. The unsymmetrical opening is new daused by the propellant cup going with one half of the sabot. Thus one half has a higher mass than the other. The use of casting would eliminate the need for a propellant cup. Interlocking ridges could be cast on each side of the sabot so that the gas seal is carried integrally with euch half. It could be designed so that each half had the same amount of metal in the seal and thus the same mass. A contoured davity would also permit a shorter sabot, reducing the overall mass Significant mass reduction can only be accomplished by the use of lower density materials. At the moment this appears to be a severe problem. Many metallic and nonmetallic materials have been tried in various laboratories with no results so far. One possible solution however lies in the use of combinations of materials in a single sabot. For example, if it were desired to accelerate a high density projectile, the main body of the sobot cauld be made of a tough low density plastic material, such as Lexan, with a steel insert for carrying the projectile. The insert would be designed to distribute the force over a much larger area of the sabot than if the plastic were carrying the projectile directly. A program utilizing both design analysis and experimentation would be required to develop a configuration which would give the desired results.

#### APPENDIX A

#### SAMPLE CALCULATION FOR BULLSEYE PISTOL POWDER

Bullsaye pistol powder has the following characteristics:

Solid density -  $\mathcal{P} = 1.6 \text{ gm/cm}^3$ 

Bulk density - 0.56 gm/cm<sup>3</sup>

Ratio of specific heats -  $\mathcal{T} = 1.21$ 

Moles of gas generated = m = 0,036 gm moles gm (powder)

Gas temperature (adiabatic, isocharic) -  $T = 4000^{\circ}$  K

Heat of explosion - 1306 <u>cal</u> gm

Granulation - 9.65 x  $10^{-2}$  cm diameter x 8.38 x  $10^{-3}$  cm long

Burn rate equation factors - n = 1.006c = 6.22 x 10<sup>-4</sup>

- La Calculation of PdV Work, Pressure, and Volume Change
  - a. Mass of Powder Required

 $M = 10 \times 67.5$  joules x  $\frac{cal}{4.18}$  ioules x  $\frac{gram}{1300} = 124$  milligrams

b Volume Required

$$V = 124 \times 10^{-3} \text{ grcm} \frac{\text{cm}^3}{0.56 \text{ grcm}} = 0.222 \text{ cm}^3 = 13.58 \times 10^{-3} \text{ in}^3$$

add 10% for initiation

Cavity volume:  $V_1 = 1.1 \times 0.222 \text{ cm}^3 = 0.245 \text{ cm}^3 = 14.88 \times 10^{-3} \text{ in}^3$ 

# c. Cavity Pressure

Neglect contribution from initiator. Assume perfect gas law.

$$P_{1} = \frac{nRT}{V} = \frac{124 \times 10^{-3} \text{ gm}}{2.45 \times 10^{-1} \text{ cm}^{3}} \times \frac{0.036 \text{ gm-moles}}{\text{gm}} \times \frac{8.2057 \times 10^{-2} \text{ liter atm}}{\text{gm-mole}} \times \frac{4000^{\circ} \text{ K} \times 10^{-3} \text{ cm}^{3}}{10^{\circ} \text{ cm}^{3}}$$

$$P_1 = 5990 \text{ atmospheres} = 88 \times 10^3 \text{ psi}$$

d. Prossure Change

1

Assume reversible adiabatic expansion. Assume perfect gas

$$W = -\frac{\mathcal{F} nRT}{\mathcal{F}^{-1}} \left[ \left( \frac{P_2}{P_1} \right) \frac{\mathcal{F}^{-1}}{\mathcal{F}} - 1 \right]$$

$$\delta7.5 \text{ joules} = -\frac{(1.21)(124 \times 10^{-3} \text{gm})(0.036 \text{ gm-moles})(8.31 \text{ joules})(4000^{\circ} \text{K})}{(1.21-1)} \left[ \frac{P_2}{\text{gm}} \right]^{1.21-1}_{1.21}_{-1} \\ -\left(\frac{P_2}{88 \times 10^3}\right)^{0.1736}_{-1.21}_{-1} + 1 = 0.0789$$

$$\frac{P_2}{88 \times 10^3} = (0.9211)^{\frac{1}{0.1736}} = 0.622$$

$$P_2 = 54.75 \times 10^3 \text{ psi}$$

$$\Delta P = P_1 - P_2 = 33.25 \times 10^3 \text{ psi}$$

# e, Volume Change

For reversible adiabatic expansion

$$\frac{P_2}{P_1} = \left(\frac{V_1}{V_2}\right)^{7}$$

$$\frac{54.75 \times 10^{5}}{88 \times 10^{2}} = \left(\frac{0.245}{V_2}\right)^{1.21}$$

$$\frac{0.245}{V_2} = (0.622)^{\frac{1}{1.21}} = 0.6753$$

$$V_2 = 0.363 \text{ cm}^3 = 22.2 \times 10^{-3} \text{ in}^3$$

$$\Delta V = V_2 - V_1 = 0.113 \text{ cm}^3 = 7.3 \times 10^{-3} \text{ in}^3$$

- 2. Calculation of Powder Burn Time
  - a. Grain Volume

$$V' = \frac{\pi D^2 \mathcal{L}}{4} = \frac{\Pi (9.65 \times 10^{-2})^2 (8.38 \times 10^{-3})}{4} = 6.13 \times 10^{-5} \text{ cm}^3$$

b. Number of Grains

$$n^{\circ} = 124 \times 10^{-3} \text{ gram} \times \frac{\text{cm}^3}{\sqrt{6} \text{ gram}} \times \frac{\text{grain}}{6.13 \times 10^{-3} \text{ cm}^3} = 1268$$

c. Total Moles of Gas Produced  

$$N = mM = 3.6 \times 10^{-2} \qquad \frac{m \cdot moles}{gm} \times 0.124 \text{ gm} = 4.46 \times 10^{-3} \text{ gm-moles}$$

# d. Calculate Burning Rate Vs. Grain Radius

Use reciprocal of burning rate equation

$$\frac{dt}{dr} = \frac{1}{C} \left\{ \frac{RT}{V_1} \left[ N - m \rho n^* (2\pi r^3 - k\pi r^2) \right] \right\}^{-n}$$

where  $k = 2r - \mathcal{L} = 9.65 \times 10^{-2} - 0.838 \times 10^{-2}$ 

 $= 3.812 \times 10^{-2}$  cm

$$R = 1.205 \times 10^3 \frac{\text{cm}^3 - \text{psi}}{\text{gm mole }^9 \text{ K}}$$

$$\frac{dt}{dr} = \frac{1}{6.22 \times 10^{-2}} \left\{ \frac{1.205 \times 10^3 \times 4 \times 10^3}{2.45 \times 10^{-1}} \right\}^{-1.006}$$

$$\left[ 4.46 \times 10^{-3} - 3.6 \times 10^{-2} \times 1.6 \times 1.268 \times 10^3 (211r^3 - 8.812 \times 10^{-2} rr^2) \right]^{-1.006}$$

$$\frac{dt}{dr} = 1.61 \times 10^{3} \left\{ 1.97 \times 10^{7} \left[ 4.46 \times 10^{-3} - 2.29 \times 10^{2} r^{2} (2r - 8.812 \times 10^{-2}) \right] \right\}^{-1.006}$$

r (cm)	dt sec dr cm	dr cm dt sec
0,04825		0
0.04824	0.798	1.252
0.04820	0.529	1.890
0,04800	0.224	4.460
0.04783	0.1128	8,87
0.04741	0.0830	12.05
0.04699	0.0560	17.85
0.04657	0.0415	24.10
0,04615	0.0326	30.70
0.04573	0.0275	36.39
0,04531	0.0233	42.95
0.04489	0.0211	47.40
0 01447	0.01905	52.50
0.04406	0.01778	56.30

From this equation, the following table lists  $\frac{dt}{dr}$  and  $\frac{dr}{dt}$  for various values of r.

Note that at r = 0.04406, the grain is completely consumed. This is because the length is much less than the diameter. Figure A is a plot of dt vs r.  $\frac{1}{dr}$ 

e. Graphically integrating under the curve in Figure A, the burning time is found to be  $5.54 \times 10^{-4}$  seconds.

31

