ESD TDR 64-74 ESTI FILE COPY

ESD-TDR-64-74

TM-3865

ELECTRONIC TRACKING ERRORS VERSUS PLASMA EFFECTS

TECHNICAL DOCUMENTARY REPORT NO. ESD-TDR-64-74

ESD RECORD COPY

AUGUST 1964

J. Hoffman

RETURN TO SCIENTIFIC & TECHNICAL INFORMATION DIVISION (ESTI), BUILDING 1211

COPY NR. OF COPIES

Prepared for

ESTI	PROCESSED
TAB	PROJ OFFICER

ACCESSION MASTER FILE

CY NR OF

ESTI CONTROL NR AL 42177

CYS

DIRECTORATE OF AEROSPACE INSTRUMENTATION

ELECTRONIC SYSTEMS DIVISION

AIR FORCE SYSTEMS COMMAND

UNITED STATES AIR FORCE

L.G. Hanscom Field, Bedford, Massachusetts



Prepared by

THE MITRE CORPORATION Bedford, Massachusetts Contract AF19(628)-2390 Copies available at Office of Technical Services, Department of Commerce.

Qualified requesters may obtain copies from DDC. Orders will be expedited if placed through the librarian or other person designated to request documents from DDC.

When US Government drawings, specifications, or other data are used for any purpose other than a definitely related government procurement operation, the government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise, as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Do not return this copy. Retain or destroy.

TM-3865

ELECTRONIC TRACKING ERRORS VERSUS PLASMA EFFECTS

TECHNICAL DOCUMENTARY REPORT NO. ESD-TDR-64-74

AUGUST 1964

J. Hoffman

Prepared for

DIRECTORATE OF AEROSPACE INSTRUMENTATION ELECTRONIC SYSTEMS DIVISION AIR FORCE SYSTEMS COMMAND UNITED STATES AIR FORCE

L.G. Hanscom Field, Bedford, Massachusetts



Project 705.1

Prepared by

THE MITRE CORPORATION Bedford, Massachusetts Contract AF19(628)-2390

FOREWORD

The author would like to express his thanks to Dr. Harry Schecter for reviewing the manuscript.

ELECTRONIC TRACKING ERRORS VERSUS PLASMA EFFECTS

ABSTRACT

Simple models are utilized to calculate the order of magnitude of errors generated by reentry and flame plasma effects in typical tracking systems.

REVIEW AND APPROVAL

Publication of this technical documentary report does not constitute Air Force approval of its findings or conclusions. It is published only for the exchange and stimulation of ideas.

CONTENTS

	Page
SECTION 1 - INTRODUCTION	1
GENERAL	1
OBJECTIVES AND SCOPE	1
SECTION II - PLASMA-INDUCED ERRORS	3
GENERAL	3
CW RANGE MEASUREMENTS	3
DOPPLER RANGE-RATE MEASUREMENTS	4
CW ANGLE MEASUREMENTS	6
PULSE MEASUREMENTS	7
SECTION III - APPLICATIONS	11
GENERAL	11
REENTRY PLASMA	13
CW Range Measurements	14
Doppler Range - Rate Measurements	14
CW Angle Measurements	16
Pulse Measurements	18
FLAME PLASMA	18
CW Range Measurements	19
Doppler Range-Rate Measurements	19
CW Angle Measurements	23
Pulse Measurements	24
SECTION IV - SUMMARY AND CONCLUSIONS	25
REFERENCES	27

v

ELECTRONIC TRACKING ERRORS VERSUS PLASMA EFFECTS

SECTION I

INTRODUCTION

GENERAL

Plasma is generated during important portions of a missile trajectory, namely boost and reentry. The two primary types of plasma generated are flame plasma and reentry plasma. Either type interferes with the electromagnetic linkage of the vehicle with the ground stations. The interference is frequently severe enough to completely break this linkage, causing "blackout." Considerable effort has been, and is continuing to be, focused upon attempts to overcome this blackout.

During a substantial portion of the trajectory, the electromagnetic linkage is maintained, even in the presence of plasma. This is because the plasma properties change throughout the trajectory and, hence, the level of interference also changes. Also, the electromagnetic path length through the plasma changes throughout the trajectory, resulting in variations in the degree of interference.

In this report, we shall be concerned with those portions of the trajectory where the degree of interference is less than blackout. More specifically, we shall investigate the interference in electronic tracking which results in tracking errors.

OBJECTIVES AND SCOPE

During those portions of the trajectory where tracking is successful, the presence of plasma results in numerous tracking errors. We shall investigate those errors which are related to phase and transit time variations produced when the tracking signal traverses the plasma before reaching the vehicle and before returning to the ground station.

Since the main purpose of this document is to point out the existence of plasma-induced tracking errors and to estimate their magnitudes, extremely simple models will be used. To make a more precise error calculation would require further refinement of the plasma models and also would require consideration of specific vehicles and trajectories; these are outside the scope of this report.

The phase and transit time plasma variations produce errors in:

- (a) Continuous wave (CW) range measurements,
- (b) Doppler range-rate measurements,
- (c) CW angle measurements, and
- (d) Pulse measurements.

This report is limited to these types of plasma-generated electronic tracking errors.

SECTION II

PLASMA-INDUCED ERRORS

GENERAL

The basic assumptions and equations describing the plasma-electromagnetic interaction are contained in Reference 1. We shall draw heavily from the results contained in this Reference. Only significant extensions of these results and the derivation of new relationships will be contained in this report.

The presence of a plasma between the vehicle and the tracking station may generate a multitude of different types of errors. We shall concern ourselves with time and phase variations produced by traversing the plasma. These produce errors in the electronic tracking parameters: range, range-rate and angle.

We shall first determine the functional dependence of these errors upon the plasma characteristics, and then apply the results to reentry and flame plasma.

CW RANGE MEASUREMENTS

Let us consider the range error produced when the tracking signal traverses the plasma, reaches the vehicle, is retransmitted, and traverses the plasma again before reaching the ground station. CW measurements of range (GLOTRAC, MISTRAM, etc.,) are based on the fact that the wave experiences a phase shift proportional to the distance travelled. The plasma-induced phase shift differs from the free space phase shift and produces a range error, ΔR .

The phase φ of the wave received by the ground station is

$$\varphi = \omega \left[t - \frac{2}{c} (R + SP) \right], \qquad (1a)$$

where

ω = tracking signal angular free	quency,	
---	---------	--

- t = time,
- R = range,
- c = velocity of light in free space,
- S = plasma distance traversed, and
- P = plasma phase shift factor. (The factor of 2 is due to the round trip.)

The total phase shift $\Delta \varphi$ experienced by the wave is

$$\Delta \varphi = 2 \frac{\omega}{c} (R + SP) . \tag{1b}$$

The range is, therefore, given by

$$\mathbf{R} = \frac{1}{2} \frac{\mathbf{c}}{\omega} \Delta \varphi - \mathbf{SP} . \tag{2}$$

Since the range is, in practice, obtained from Eq. (2) with P = 0, the range error is

$$\Delta R = -SP. \qquad (3)$$

The phase shift factor P is, in general, a function of signal frequency and plasma characteristics.

DOPPLER RANGE-RATE MEASUREMENTS

Doppler systems transform received frequency shifts into range-rate data. From Reference 2, the first-order round-trip Doppler equation is

$$\omega_{\mathbf{R}} \approx \omega_{\mathbf{T}} \left(1 - 2 \frac{\dot{\mathbf{R}}}{c} \right) , \qquad (4a)$$

where

 ω_{R} = received angular frequency, ω_{T} = transmitted angular frequency, and \dot{R} = range-rate,

and where the receiver and transmitter are collocated.

To include the plasma medium, Eq. (4a) is modified to be

$$\omega_{\mathbf{R}} \approx \omega_{\mathbf{T}} \left[1 - \frac{2}{c} \frac{\mathrm{d}}{\mathrm{dt}} \int_{0}^{\mathbf{R}} \mathrm{n} \mathrm{dr} \right],$$
 (4b)

where

n = index of rafraction.

For the range of integration 0 to (R - S), n = 1 (neglecting atmospheric refraction). For the range of integration (R - S) to R, n = (1 + P). If P is assumed constant with respect to space,

$$\omega_{\rm R} \approx \omega_{\rm T} \left[1 - \frac{2}{c} \frac{d}{dt} ({\rm R + SP}) \right],$$
 (4c)

and

$$\omega_{\rm R} \approx \omega_{\rm T} \left[1 - \frac{2}{c} \left(\dot{\rm R} + \dot{\rm SP} + \dot{\rm SP} \right) \right]$$
 (5)

Since, in practice, the range-rate is obtained from Eq. (5) with P, S = 0, then the range-rate error is

$$\Delta \mathbf{R} = -(\mathbf{SP} + \mathbf{SP}) \quad . \tag{6}$$

Differentiation of Eq. (3) with respect to time also yields Eq. (6).

Thus, we see that the plasma contributes to the range-rate error in two ways; by changing plasma characteristics (P), and by changing plasma thickness (S).

CW ANGLE MEASUREMENTS

CW angle measurement systems utilize an interferometer to obtain phase difference measurements, which are then transformed into angle measurements. Two antennas, located at the ends of a baseline of known length D, each receive the same tracking signal but with a difference in phase. The path length from the vehicle to one antenna differs from the path length from the vehicle to the other antenna by a path length difference L. The phase difference $\Delta \varphi$ is proportional to L. The direction cosine, $\cos \theta$, is approximately equal to L/D. If the paths to the two antennas both traverse the same plasma then there is no angle error, since both signals have the same plasma-induced phase shift and this is cancelled by the interferometer. However, if the paths do not traverse the same plasma, there is an angle error.

The phase at antenna (1) is

$$\varphi_{1} = \omega \left[t - \frac{2}{c} \left(\mathbf{R}_{1} + \mathbf{S}_{1} \mathbf{P}_{1} \right) \right], \qquad (7a)$$

and, at antenna (2),

$$\varphi_2 = \omega \left[\mathbf{t} - \frac{2}{\mathbf{c}} \left(\mathbf{R}_2 + \mathbf{S}_2 \mathbf{P}_2 \right) \right]. \tag{7b}$$

The phase difference at the two antennas results in a path length difference

$$\mathbf{L} = \mathbf{R}_{2} - \mathbf{R}_{1} = \frac{1}{2} \frac{\mathbf{c}}{\omega} \left(\varphi_{1} - \varphi_{2} \right) + \left(\mathbf{S}_{1} \mathbf{P}_{1} - \mathbf{S}_{2} \mathbf{P}_{2} \right)$$
(7c)

The direction cosine is

$$\cos \theta \approx \frac{L}{D}$$
 (7d)

and

$$\cos \theta \approx \frac{1}{2} \frac{c}{\omega} \left(\frac{\varphi_1 - \varphi_2}{D} \right) + \left(\frac{S_1 P_1 - S_2 P_2}{D} \right)$$
(7e)

As discussed previously, if the plasma traversed is the same for the two antennas, then the last term in Eq. (7e) is zero. However, if the plasma traversed is different, then the error $\Delta \cos \theta$ in the direction cosine is

$$\Delta \cos \theta \approx \frac{S_1 P_1 - S_2 P_2}{D} . \tag{8}$$

PULSE MEASUREMENTS

In pulse radar range measurements, the fundamental measurement is that of transit time. An identified pulse of radio energy travels from the radar to the vehicle, and is reflected or retransmitted to the ground station. The round-trip transit time is then transformed into range measurement. The R is related to the round-trip transit time t as

$$\mathbf{R} = \frac{\mathbf{V}\mathbf{t}}{2} \quad , \tag{9a}$$

where

V = velocity of the radar pulse.

There are three distinct types of velocities associated with an electromagnetic wave. These are phase, group, and signal velocities. In free space, all three velocities are identical and equal to the velocity of light c. Of course, the signal velocity is always less than or equal to c. For the plasma cases which we shall consider, the group and signal velocities are equivalent, and it is this velocity that must be used in Eq. (9a).

The group velocity V_{g} is defined as

$$V_{g} = \frac{d\omega}{d\beta} , \qquad (9b)$$

where

$$\beta = \frac{\omega}{c} (1 + P) = \frac{\omega}{c} n .$$
(9c)

efore,

$$V_{g} = \frac{c}{n + \omega \, dn/d\omega} \quad . \tag{9d}$$

Since the round-trip transit time is given by

$$t = 2 \left[\frac{R - S}{c} + \frac{S}{V_g} \right], \qquad (9e)$$

then the range is

$$R = \frac{ct}{2} - S\left(n-1 + \omega \frac{dn}{d\omega}\right) .$$
 (9f)

Since n = (1 + P),

$$R = \frac{ct}{2} - S\left(P + \omega \frac{dP}{d\omega}\right).$$
 (9g)

In practice, Eq. (9g) is used to obtain the range with S = 0. Therefore, the range error is

$$\Delta \mathbf{R} = -\mathbf{S}\left(\mathbf{P} + \omega \frac{\mathrm{dP}}{\mathrm{d}\omega}\right). \tag{10}$$

The error in the transit-time measurement of range differs from that of the CW measurement by the dispersive characteristics of the plasma, the ω dP/d ω term. Compare Eqs. (10) and (3).



SECTION III

APPLICATIONS

GENERAL

The two major sources of plasma-induced electronic tracking errors which we shall consider are reentry plasma and flame plasma. For the purpose of a first-order investigation of error effects, reentry and flame plasma are considered to differ only in the thickness of the plasma and in the time dependency of the plasma properties. The difference is, of course, much more complex. However, the approach used is sufficient to illustrate the first-order magnitude of errors which are possible.

During certain portions of the trajectory, blackout will occur and tracking will be lost. No signal is received, and, therefore, no errors are produced. Since we are concerned with the errors in tracking, a substantial signal must be received. Therefore, we will focus our attention on those portions of the trajectory which allow a successful tracking operation. Since we are concerned with present tracking accuracies, we will not consider techniques for reducing detrimental plasma effects (see Reference 1). For a successful tracking operation, the "Permissible Condition" must hold. From Reference 1, the Permissible Condition is

$$\omega_{\rm p}^2 \ \omega_{\rm c} \le \omega \ \left(\omega^2 + \omega_{\rm c}^2\right), \tag{11}$$
$$\omega_{\rm p}^2 \le \omega^2 + \omega_{\rm c}^2 ,$$

where

 ω_{p} = angular plasma frequency, ω_{c} = collision frequency, and ω = angular signal frequency.

In Section II, the error equations were derived. The errors were found to be functions of signal frequency ω , baseline length D, plasma thickness S, phase shift factor P, and appropriate derivatives of these parameters. The signal frequency and baseline length are fixed by the tracking system. The phase shift factor, from Reference 1, is

$$P \approx \frac{1}{2} A^2 - A\left(\frac{\omega}{\omega_c}\right) < 1$$
, (12)

where

$$A \approx \frac{1}{2} \left(\frac{\omega_p^2}{\omega^2 + \omega_c^2} \right) \left(\frac{\omega_c}{\omega} \right) < 1 \quad .$$
 (13a)

The dispersion term is

$$\omega \frac{\mathrm{dP}}{\mathrm{d\omega}} \approx \omega \frac{\mathrm{dA}}{\mathrm{d\omega}} \left[\mathbf{A} - \left(\frac{\omega}{\omega_{\mathrm{c}}}\right) \right] - \mathbf{A} \left(\frac{\omega}{\omega_{\mathrm{c}}}\right) , \qquad (13b)$$

where

$$\omega \frac{dA}{d\omega} \approx -A \left[1 + \frac{2\omega^2}{\omega^2 + \omega_c^2} \right] , \qquad (13c)$$

and, therefore,

$$\omega \frac{\mathrm{dP}}{\mathrm{d}\omega} \approx 2A \left(\frac{\omega}{\omega_{\mathrm{c}}}\right) \left(\frac{\omega}{\omega^{2} + \omega_{\mathrm{c}}^{2}}\right) - A^{2} \left(1 + \frac{2\omega^{2}}{\omega^{2} + \omega_{\mathrm{c}}^{2}}\right). \quad (14)$$

If an electronic tracking system operates successfully in spite of the presence of plasma, Eqs. (12) and (14) are the phase and dispersion contributions to the first-order errors generated.

We may now proceed to the determination of the possible first-order error magnitudes produced by the presence of reentry and flame plasma.

REENTRY PLASMA

We shall first investigate the plasma-generated electronic tracking errors during reentry. Those portions of the trajectory which are blacked out usually have plasma characteristics such that |P, A| > 1 (see Reference 1). Successful tracking usually implies |P, A| < 1. Therefore, we will approach the accuracy analysis from the viewpoint that successful tracking and the production of errors start at |P, A| < 1, with maximum errors occurring at $|P, A \approx 1$. Using $|P, A| \leq 1$ frees us, in general, from the necessity of considering the plasma properties as a function of the trajectory. Thus, the error magnitudes obtained will not be related to any specific trajectory point. Rather, these errors are indicative of those that may occur before and after the blackout period as well as during other trajectory portions where plasma exists and tracking is successful.

For successful tracking, we usually have $\omega > \omega_p$, ω_c (see Reference 1). A typical value for the plasma thickness is $S_0 \approx 1.0$ feet.

We may now proceed with the determination of the errors.

CW Range Measurements

The plasma distance S traversed by the signal is generally greater than the plasma thickness S_0 . For the geometry illustrated in Fig. 1,

$$S = \frac{S_0}{\cos \theta} . \tag{15a}$$

Substitution of Eq. (15a) into (3) yields the range error

$$\Delta R = -\frac{S_0}{\cos \theta} P . \qquad (15b)$$

For S_0 \approx 1.0 feet and θ = 60 degrees, the range error is

$$\Delta \mathbf{R} \approx -2 \mathbf{P} \lessapprox | 2 \mathrm{ft} |$$
 (15c)

Doppler Range - Rate Measurements

The plasma thickness will change as the plasma builds up around the vehicle. However, as viewed by the ground station, it will also change as the aspect angle changes. We shall investigate this latter change, which is depicted in Fig. 1.

From Fig. 1 we have

$$R \sin \theta = h, \qquad (16a)$$

$$S \cos \theta = S_0$$
. (16b)

For the vehicle descending straight down,

$$R = h \sin \theta \tag{16c}$$

and

$$\frac{S}{S} = \frac{R}{R} \quad . \tag{16d}$$

Combining (16c) and (16d), we have



$$S = \frac{S}{R} + \sin \theta$$
 (16e)



$$\dot{P} = \frac{dP}{dh} \dot{h} . \qquad (17a)$$

From Eq. (12), with $\omega > \omega_p, \omega_c$, we find that

$$\dot{P} \approx 2 \frac{P}{\omega_p} \frac{d\omega_p}{dh} \dot{h}$$
 (17b)

Substitution of Eqs. (17b), (16e), and (16a) into Eq. (6) yields

$$\Delta \dot{\mathbf{R}} \approx -\frac{\mathbf{S}_{0}}{\mathbf{h}\cos\theta} \dot{\mathbf{P}} \dot{\mathbf{h}} \left[\sin^{2}\theta + 2\frac{\mathbf{h}}{\omega} \frac{d\omega}{\mathbf{p}} \right] . \tag{18a}$$

From Reference (3), Figure 18, for

 $\dot{h} = 1.5 \times 10^4 \text{ ft./sec.},$ $h = 2.5 \times 10^5 \text{ ft.},$

we find that

$$rac{\mathrm{h}}{\omega_{\mathrm{p}}} \; rac{\mathrm{d}\omega}{\mathrm{d}\mathrm{h}} \; pprox \; -4.5 \; .$$

For S $_0 \approx 1.0$ feet and $\theta \approx 60$ degrees, the range-rate error is

$$\Delta R \approx 1.0 P \lessapprox | 1 \text{ ft./sec.} |$$
 (18b)

CW Angle Measurements

Since we are concerned with a homogeneous plasma, the path length plasma variation which we will consider is as shown in Fig. 2. From the figure

$$\frac{S_2}{S_1} = \frac{R_2}{R_1} ,$$
 (19a)

and

$$S_1 - S_2 = S_1 \left(\frac{R_1 - R_2}{R_1} \right) = -S_1 \frac{L}{R_1}$$
 (19b)



Fig. 2. Reentry Geometry for CW Angle

Substitution of Eqs. (19b) and (7d) into Eq. (8) yields

$$\frac{\Delta \cos \theta}{\cos \theta} \approx - P \frac{S_1}{R_1} , \qquad (20a)$$

where

$$P_1 = P_2 = P.$$

Equation (20a) is the fractional error in the direction cosine.

For $R_1 \approx 10^6$ feet and $S_1 \approx 2$ feet,

$$\frac{\Delta \cos \theta}{\cos \theta} \approx -P \ 2 \ x \ 10^{-6} \quad \lesssim \quad | \ 2 \ x \ 10^{-6} \quad ft \quad | \ . \tag{20b}$$

Pulse Measurements

For $\omega > \omega_{\rm p}$, $\omega_{\rm c}$, Eqs. (12) and (14), respectively, become

$$P \approx -A\left(\frac{\omega}{\omega_c}\right),$$

 $\omega \frac{dP}{d\omega} \approx 2A\left(\frac{\omega}{\omega_c}\right) \approx -2P$. (21b)

Substitution of Eqs. (21a) and (21b) into (10) yields

$$\Delta R \approx SP.$$
 (22)

The pulse and CW range errors differ in sign and are approximately of equal magnitude. Compare Eqs. (22) and (3).

For the geometry depicted in Fig. 1, we again have

$$\Delta \mathbf{R} \approx \frac{\mathbf{S}_0}{\cos \theta} = \mathbf{P}$$
 (23a)

For S $_0 \approx 1.0$ feet and $\theta = 60$ degrees, the range error is

$$\Delta \mathbf{R} \approx 2 \mathbf{P} \lessapprox 2 \mathbf{ft}.$$
 (23b)

FLAME PLASMA

The ionization in the exhaust consists of thermal ionization, chemiionization, impact ionization, etc. Because of the multitude of ionization mechanisms, there is considerable difficulty in determining the plasma plume properties as a function of trajectory. At present most of the available information is concerned with thermal ionization, which is a principal contributor to the total ionization. We shall, therefore, limit our investigation to thermal ionization. The errors obtained will, therefore, be on the low side, since the other ionization mechanisms will also contribute to the tracking error.

In addition, as in the reentry plasma section, we shall be concerned with successful tracking. Therefore, the third paragraph on Page 13 applies here also, and reference should be made to it.

A characteristic plasma radial thickness is $S_0 \approx 25$ feet.

We now proceed with the error determination.

CW Range Measurements

The path length thickness through the plume is assumed, for simplicity, as depicted in Fig. 3. From Fig. 3 we have

$$S = \frac{S_0}{\cos \theta} \quad . \tag{24a}$$

Substitution of Eq. (24a) into (3) yields the range error

$$\Delta R = -\frac{S_0}{\cos \theta} P . \qquad (24b)$$

For S $_{0}$ \approx 25 feet and θ = 60 degrees, the range error is

$$\Delta R \approx -S_0 P \stackrel{<}{\approx} | 50 \text{ ft.} | . \qquad (24c)$$

Doppler Range-Rate Measurements

The path length through the plume will change as the aspect angle (S_{θ}) changes and as the plume volume (S_h) changes with altitude due to decreasing ambient pressure. The S term, therefore, is

$$\dot{S} = \dot{S}_{\theta} + \dot{S}_{h}$$
 (25a)





For the simple geometry depicted above, Eq. (16e) applies, and we have

$$\dot{S}_{\theta} = \frac{S}{R} h \sin \theta$$
 (25b)

To obtain \dot{S}_{h} , we let the plume volume F be any volume, such that

$$F = a S_0^m , \qquad (25c)$$

where a and m are constants. The time derivative is

$$\dot{\mathbf{F}} = \mathbf{m} \frac{\mathbf{F}}{\mathbf{S}_0} \dot{\mathbf{S}}_0 . \tag{25d}$$

For thermal ionization, the total electron content of the plume remains approximately constant as the plume expands. The electron density, of course, changes as the plume expands. Since the electron density is proportional to ω_p^2 (see Reference 1), we have

$$\omega_{\rm p}^2$$
 F = constant. (25e)

Use of the time derivatives yields

$$2 \omega_{\rm p} F = -\omega_{\rm p} F . \qquad (25f)$$

The combination of Eq. (25f) with (25d) yields

$$\dot{S}_0 = -2 \frac{S_0}{m} \frac{\omega_p}{\omega_p} . \qquad (25g)$$

From Eq. (12), with $\omega > \omega_{\rm p}$, $\omega_{\rm c}$, we find that

$$\dot{P} \approx 2P \frac{\dot{\omega}_p}{\omega_p}$$
 (25h)

Substitution of Eq. (25h) into (25g) yields

$$\dot{S}_{0} = -\frac{\dot{S}_{0}}{m} \frac{\dot{P}}{P}$$
 (25i)

From Fig. 3, we have

$$S \cos \theta = S_0$$
, (25j)

and, holding θ = constant,

$$\dot{S}_{h} \cos \theta = \dot{S}_{0}$$
, (25k)

and, from Eq. (25i),

$$\dot{S}_{h} \cos \theta = -\frac{S_{0}}{m} \frac{\dot{P}}{P} . \qquad (251)$$

Finally, we substitute Eqs. (251) and (25b) into (25a) to obtain

$$\dot{S} \approx \frac{S}{R} \dot{h} \sin \theta - \frac{S_0}{m \cos \theta} \frac{\dot{P}}{P}$$
 (26)

The time derivative of the path length through the plume consists of the aspect angle change (the h portion) and the plasma expansion change (the P portion).

The next step is to determine P. Since, from Eqs. (25h) and (25f),

$$P \approx -P \frac{F}{F}$$
, (27a)

we may write

$$\dot{P} \approx -P \frac{1}{F} \frac{dF}{dp} \frac{dp}{dh} \dot{h},$$
 (27b)

where p = ambient pressure.

Utilizing the well-known relationship

$$\frac{\mathrm{d}p}{\mathrm{d}h} = -\mathrm{g}\rho \quad , \tag{27c}$$

where

g = gravity acceleration, and ρ = ambient density,

we have

$$\dot{P} \approx P \frac{1}{F} \frac{dF}{dp} g \rho \dot{h}$$
 (28)

Substitution of Eqs. (28) and (26) into Eq. (6) yields the range-rate error (using R sin θ = h, S cos θ = S₀) :

$$\Delta \dot{\mathbf{R}} \approx -\frac{\mathbf{S}_{0} \mathbf{P} \dot{\mathbf{h}}}{\cos \theta} \begin{cases} \sin^{2} \theta & +\left(\frac{\mathbf{m}-1}{\mathbf{m}}\right) \frac{1}{\mathbf{F}} \frac{d\mathbf{F}}{d\mathbf{p}} \mathbf{g} \rho \end{cases} .$$
(29a)

Let us consider volumes for which m = 3. For θ = 60 degrees and S₀ \approx 25 feet, Eq. (29a) becomes

$$\Delta \dot{R} \approx -50 P\dot{h} \left\{ \frac{3}{4h} + \frac{2}{3} \frac{1}{F} \frac{dF}{dp} g\rho \right\}.$$
(29b)

From Reference (4), Fig. 6, for h \approx 10⁵ feet,

$$\frac{1}{\mathrm{F}} \quad \frac{\mathrm{d}\mathrm{F}}{\mathrm{d}\mathrm{p}} \ \approx \ - \ 0.7 \ \mathrm{x} \ 10^{-2} \ \mathrm{per} \ \mathrm{lb.} \, / \mathrm{ft.}^2 \ ,$$

and since

g
$$\approx$$
 32 ft./sec.², and
 $\rho \approx$ 3.3 x 10⁻⁵ slugs/ft.³,

the range-rate error for h $\,\approx\,1.\,5\,$ x 10 4 ft./sec. is

$$\Delta R \approx -1.9 P \approx |1.9 \text{ ft./sec.}|. \qquad (29c)$$

CW Angle Measurements

Since we are concerned with a homogeneous plasma, the plume path length variation which we will consider is depicted in Fig. 4. To a first approximation, Eq. (20a) applies:

$$\frac{\Delta \cos \theta}{\cos \theta} \approx - P \frac{S_1}{R_1} . \tag{30a}$$

Equation (30a) is the fractional error in the direction cosine.

The assumption that $\rm S^{}_{1}~\approx~50$ feet yields, for $\rm R^{}_{1}~\approx~10^{6}$ feet,

$$\frac{\Delta \cos \theta}{\cos \theta} \approx - P \times 5 \times 10^{-5} \leq |5 \times 10^{-5}|.$$
(30b)



Fig. 4. Flame Geometry for CW Angle

Pulse Measurements

Equations (21) and (22) and the discussion on Page 13 apply directly. From Eq. (22) we have

$$\Delta R \approx SP$$
. (31a)

From Fig. 3 we again have

$$\Delta \mathbf{R} \approx \frac{\mathbf{S}_0}{\cos \theta} \quad \mathbf{P} \quad .$$
 (31b)

For S $_0 \approx 25$ feet and $\theta = 60$ degrees, the range error is

$$\Delta R \approx 50 P \lessapprox | 50 \text{ ft.} |$$
 (31c)

SECTION IV

SUMMARY AND CONCLUSIONS

We have investigated plasma-generated electronic tracking errors for both reentry and flame plasma. Simple models have been utilized to obtain order-of-magnitude errors for a number of measurement techniques. Table 1 lists the measurement systems, techniques employed, and parameters measured.

Table 1

System	Technique	Parameter		
CW range	Round-trip phase dis- placement	Range		
Doppler	Frequency shift	Range-rate		
CW angle	Path length baseline phase comparison	Direction cosine		
Pulse	Round-trip transit time	Range		

Measurement Systems Investigated

The CW range error results from the plasma-induced phase shift. The Doppler range-rate error results from the time rate of change of the plasma properties and the time rate of change of the aspect angle. The CW angle error results from the different plasma path lengths to the ends of the baseline. The pulse range error results from the increased transit time produced by the presence of the plasma.

Table 2 summarizes the possible error magnitudes for the simple models investigated.

Table 2	Ta	ble	e 1	2
---------	----	-----	-----	---

System	Reentry	Flame
CW range	2.0 ft	50 ft.
Doppler	1.0 ft./sec.	1.9 ft./sec.
CW angle	$2 \times 10^{-4}\%$	$5 \times 10^{-3}\%$
Pulse	2.0 ft.	50 ft.

Plasma Electronic Tracking Errors

The CW angle error is the percentage error in the direction cosine.

For the simple model considered, the errors for flame plasma are greater than for reentry plasma; basically, for the reason that the plume is considerably larger than the plasma sheath.

With the present emphasis upon greater electronic tracking accuracies, it would appear that consideration should be given to plasma-generated errors.

Jhome Hoffman

REFERENCES

- 1. Hoffman, J. Detrimental Plasma Effects vs. Techniques for Alleviation, Bedford, Massachusetts: The MITRE Corporation, W-6053, 1 May 1963.
- Hoffman, J. <u>Relativistic and Classical Doppler Electronic Tracking</u> <u>Accuracies</u>, Bedford, Massachusetts: The MITRE Corporation, W-5785, 17 December 1962; see also, ESD-TDR-63-178.
- 3. Sisco, W. B. and Fiskin, J. M. "Basic Hypersonic Plasma Data of Equilibrium Air for Electromagnetic and Other Requirements," Planetary and Space Science, Vol. 6, 1961.
- 4. Balwanz, W. W. and Weston J. P. "The Prediction of Rocket Exhaust Interference with Radio Signals," <u>Ions in Flame and Rocket Exhausts</u> <u>Conference</u>, American Rocket Society, Palm Springs, California, October 1962.

POL	CUMENT CONTROL DATA - R&D			
(Security classification of title, body of abst	tract and indexing annotation must be entered when the overall report is classified)			
ORIGINATING ACTIVITY (Corporate author)	28. REPORT SECURITY CLASSIFICATION			
MITRE Corporation, Bedford, 1	UNCLASSIFIED			
	2b GROUP			
	N/A			
REFORTITILE				
Electronic Tracking Errors V	Versus Plasma Effects			
DESCRIPTIVE NOTES (Type of report and inclu	sive dates)			
None				
AUTHOR(S) (Last name, first name, initial)				
Haffran ?				
Horrman, J.				
DEPO DT DA TE				
REFORT DATE	78. TOTAL NO. OF PAGES 70. NO. CF REFS			
Aug 64				
F10/600 10000	St. ON GIVE FOR S REPORT NOMBER(O)			
- 19 (028)2390 6. PROJECT NO.				
705 1	96. OTHER REPORT NO(S) (Any other numbers that may be assigned			
C.				
	50. OTHER REPORT NO(5) (Any other numbers that may be assigned			
	this report)			
d.	ESD-TDR-64-74			
d. D. AVAILABILITY/LIMITATION NOTICES	ESD-TDR-64-74			
d. 0. AVAILABILITY/LIMITATION NOTICES	ESD-TDR-64-74			
d. D. AVAILABILITY/LIMITATION NOTICES Qualified Requesters May Obta	ESD-TDR-64-74			
d. O. AVAILABILITY/LIMITATION NOTICES Qualified Requesters May Obta 1. SUPPLEMENTARY NOTES	ESD-TDR-64-74 12. SPONSORING MILITARY ACTIVITY			
d. Qualified Requesters May Obta 1. SUPPLEMENTARY NOTES	ESD-TDR-64-74 in Copies From DDC. 12. SPONSORING MILITARY ACTIVITY Directorate of Aerospace Instrumentation			
d. D. AVAILABILITY/LIMITATION NOTICES Qualified Requesters May Obta	ESD-TDR-64-74 in Copies From DDC. 12. SPONSORING MILITARY ACTIVITY Directorate of Aerospace Instrumentation ESD. L.G. Hanscom Field, Bedford, Masso			
d. D. AVAILABILITY/LIMITATION NOTICES Qualified Requesters May Obta 1. SUPPLEMENTARY NOTES	ESD-TDR-64-74 12. SPONSORING MILITARY ACTIVITY Directorate of Aerospace Instrumentation ESD, L.G. Hanscom Field, Bedford, Massa			
d. Qualified Requesters May Obta USUPPLEMENTARY NOTES ABSTRACT	ESD-TDR-64-74 in Copies From DDC. 12. SPONSORING MILITARY ACTIVITY Directorate of Aerospace Instrumentation ESD, L.G. Hanscom Field, Bedford, Massa			
d. D. AVAILABILITY/LIMITATION NOTICES Qualified Requesters May Obta I. SUPPLEMENTARY NOTES D. ABSTRACT	ESD-TDR-64-74 in Copies From DDC. 12. SPONSORING MILITARY ACTIVITY Directorate of Aerospace Instrumentation ESD, L.G. Hanscom Field, Bedford, Masso			
d. A VAILABILITY/LIMITATION NOTICES Qualified Requesters May Obta Supplementary notes ABSTRACT Simple models are ut	illized to calculate the order of magnitude of			
d. Qualified Requesters May Obta Supplementary notes Abstract Simple models are ut rors generated by reentry and	in Copies From DDC. 12 SPONSORING MILITARY ACTIVITY Directorate of Aerospace Instrumentation ESD, L.G. Hanscom Field, Bedford, Massa ilized to calculate the order of magnitude of flame plasma effects in typical tracking systems.			
d. A VAILABILITY/LIMITATION NOTICES Qualified Requesters May Obta SUPPLEMENTARY NOTES ABSTRACT Simple models are ut rors generated by reentry and	ESD-TDR-64-74 in Copies From DDC. 12 SPONSORING MILITARY ACTIVITY Directorate of Aerospace Instrumentation ESD, L.G. Hanscom Field, Bedford, Massa ilized to calculate the order of magnitude of flame plasma effects in typical tracking systems.			
d. A VAILABILITY/LIMITATION NOTICES Qualified Requesters May Obta I. SUPPLEMENTARY NOTES ABSTRACT Simple models are ut rors generated by reentry and	ESD-TDR-64-74 in Copies From DDC. 12 SPONSORING MILITARY ACTIVITY Directorate of Aerospace Instrumentation ESD, L.G. Hanscom Field, Bedford, Massa ilized to calculate the order of magnitude of flame plasma effects in typical tracking systems.			
d. A VAILABILITY/LIMITATION NOTICES Qualified Requesters May Obta Supplementary notes ABSTRACT Simple models are ut rors generated by reentry and	ESD-TDR-64-74 in Copies From DDC. 12 SPONSORING MILITARY ACTIVITY Directorate of Aerospace Instrumentation ESD, L.G. Hanscom Field, Bedford, Massa ilized to calculate the order of magnitude of flame plasma effects in typical tracking systems.			
d. A VAILABILITY/LIMITATION NOTICES Qualified Requesters May Obta SUPPLEMENTARY NOTES ABSTRACT Simple models are ut rors generated by reentry and	ESD-TDR-64-74 in Copies From DDC. 12 SPONSORING MILITARY ACTIVITY Directorate of Aerospace Instrumentation ESD, L.G. Hanscom Field, Bedford, Massa ilized to calculate the order of magnitude of flame plasma effects in typical tracking systems.			
d. O. AVAILABILITY/LIMITATION NOTICES Qualified Requesters May Obta 1. SUPPLEMENTARY NOTES 3. ABSTRACT Simple models are ut rors generated by reentry and	ESD-TDR-64-74 in Copies From DDC. 12. SPONSORING MILITARY ACTIVITY Directorate of Aerospace Instrumentation ESD, L.G. Hanscom Field, Bedford, Massa ilized to calculate the order of magnitude of flame plasma effects in typical tracking systems.			

٦

UNCLASSIFIED

Security Classification

14.	KEY WORDS		LINKA		LINKB		LINKC	
			ΨT	ROLE	WΤ	ROLE	WT	
Mie Tra	sile acking							
pla Bla	ackouts		-					
						-		
	INCODUCAT	0.10		**************************************				

INSTRUCTIONS

1. ORIGINATING ACTIVITY: Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (corporate author) issuing the report.

2a. REPORT SECURITY CLASSIFICATION: Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. GROUP: Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. REPORT TITLE: Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. DESCRIPTIVE NOTES: If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. AUTHOR(S): Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. REPORT DATE: Enter the date of the report as day, month, year; or month, year. If more than one date appears on the report, use date of publication.

7a. TOTAL NUMBER OF PAGES: The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. NUMBER OF REFERENCES: Enter the total number of references cited in the report.

8a. CONTRACT OR GRANT NUMBER: If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. PROJECT NUMBER: Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. ORIGINATOR'S REPORT NUMBER(S): Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. OTHER REPORT NUMBER(S): If the report has been assigned any other report numbers (either by the originator or by the sponsor), also enter this number(s).

10. AVAILABILITY/LIMITATION NOTICES: Enter any limitations on further dissemination of the report, other than those imposed by security classification, using standard statements such as:

- "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. SUPPLEMENTARY NOTES: Use for additional explanatory notes.

12. SPONSORING MILITARY ACTIVITY: Enter the name of the departmental project office or laboratory sponsoring (paying for) the research and development. Include address.

13. ABSTRACT: Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. KEY WORDS: Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.