USATRECOM TECHNICAL REPORT 65-12

A DEVICE FOR THE DIRECT MEASUREMENT OF UNSTEADY AIR FLOWS AND SOME CHARACTERISTICS **OF BOUNDARY LAYER TRANSITION**

By

Joseph J. Cornish III

March 1965 MICROFICHE

COPY

L OF HARD COPY S. 2. 0 \$.0.52

AD

U. S. ARMY TRÄNSPORTATION RESEARCH COMMAND FORT EUSTIS, VIRGINIA

CONTRACT DA 44-177-AMC-892(T) MISSISSIPPI STATE UNIVERSITY



DISCLAIMER NOTICE



THIS DOCUMENT IS BEST QUALITY AVAILABLE. THE COPY FURNISHED TO DTIC CONTAINED A SIGNIFICANT NUMBER OF PAGES WHICH DO NOT REPRODUCE LEGIBLY.

DDC Availability Notice

Qualified requesters may obtain copies of this report from DDC.

This report has been furnished to the Department of Commerce for sale to the public.

Disclaimer

The findings in this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission, to manufacture, use or sell any patented invention that may in any way be related thereto.

Disposition Instructions

Destroy this report when it is no longer needed. Do not return it to the originator.

HEADQUARTERS U S ARMY TRANSPORTATION RESEARCH COMMAND FORT EUSTIS VIRGINIA 29604

٤.

A Construction of the second se

The work presented in this report was performed by the Azrophysics Department of Mississippi State University and is published for the dissemination of information and stimulation of ideas.

Task 1D121401A14203 Contract DA 44-177-AMC-892(T) USATRECOM Technical Report 65-12

March 1965

A DEVICE FOR THE DIRECT MEASUREMENT OF UNSTEADY AIR FLOWS AND SOME CHARACTERISTICS OF BOUNDARY LAYER TRANSITION

Child and a stranged the S

4.2 2

Aerophysics Research Note No. 24

Prepared by The Aerophysics Department Mississippi State University State College, Mississippi

for U. S. ARMY TRANSPORTATION RESEARCH COMMAND FORT EUSTIS, VIRGINIA

ABSTRACT

A device for use in obtaining instantaneous velocity profiles of unsteady air flows is described. The techniques for its use are illustrated by two typical examples in laminar and turbulent boundary layers.().

.

.

÷

÷

CONTENTS

	rage
ABSTRACT	iii
LIST OF ILLUSTRATIONS	vi
INTRODUCTION	1
DESCRIPTION OF APPARATUS	3
DISCUSSION	5
CONCLUDING REMARKS	8
BIBLIOGRAPHY	9
FIGURES	10
DISTRIBUTION	18

v

ILLUSTRATIONS

*

A.F. A.M.

Figure		Page
1	Apparatus for Visualizing and Photographing Boundary Layer Profiles	10
2	Circuit for Producing a Line of Smoke from an Oil- Coated Resistance Wire	11
3	Typical Laminar Boundary Layer Profile Measurements .	12
4	Some Examples of Instantaneous Measurements of the Turbulent Boundary Layer on a Flat Plate	13
5	Comparison of Experimental and Theoretical Turbulent Mean Velocity Profiles after Natural Transition	14
6	Streamwise Velocity Fluctuations in Turbulent Boundary Layer after Natural Transition	15
7	Comparison of Experimental and Theoretical Turbulent Mean Velocity Profiles with Artificially Stimulated Transition	16
8	Streamwise Velocity Fluctuations in Turbulent Boundary Layer with Artificially Stimulated Transition	17

vi

INTRODUCTION

The instrumentation used in the study of fluid flows generally measures the time-average, or mean, velocity of the flows involved. For flows which are time-dependent, these techniques are very satisfactory, and such instrumentation has also been used with remarkable success in flows which do vary with time. The turbulent boundary layer, for example, has been examined for years by the use of boundary layer rakes, or probes, which consist, for the most, of simple Pitot-static tubes. The hot-wire anemometer, of course, has been extensively used to measure the fluctuating quantities in the turbulent boundary layer. Besides its rather formidable complexity, the hot-wire anemometer has a further disadvantage in that flow properties can be measured at only one point, or, at best, a few points, in the flow simultaneously.

The use of dyes or stains to visualize the characteristics of a flowing liquid has long been practiced. Probably the earliest experiment of significance is that of Reynolds, who used a thin filament of dye to picture the transition from laminar to turbulent flow. More recently, researchers have ejected colored dye from orifices in the surfaces of bodies submerged in water to delineate the flow patterns around these bodies.

These methods have been extended to use in wind tunnels or smoke tunnels by many researchers. Notably, Brown (Reference 1) has been very successful in picturing flows by means of smoke filaments. In general, however, these techniques are intended to make visible the stream lines of the flow rather than to measure velocities. Head (Reference 3) has also ejected smoke into the turbulent boundary layer of various models in order to study the intermittence of turbulence.

One successful technique for measuring velocity profiles in flowing liquids was developed by Wortman (Reference 5), who discharged an electrical current through tellurium wires and photographically recorded the resulting streaks which were formed in the fluid. Later, Geller (Reference 2) developed a similar technique, in which velocity profiles were visualized by oxygen bubbles shed from a wire through the electrolysis of the water caused by the passage of a rather high current through the wire.

In the early 1950's, Dr. August Raspet and Mr. Thomas S. Moore of the Aerophysics Department of Mississippi State University extended this technique to use in air. A thin wire, coated with oil and suddenly heated by the passage of a large electrical current discharged from a condenser, was used to measure, by means of the resulting oil smoke, the velocity profiles within a channel.

ł

The present report describes subsequent refinements and modifications to this technique.

DESCRIPTION OF APPARATUS

The equipment used in this method consists of three main components: a thin wire with its supports, which is mounted in the air flow; an electrical condenser with its controls and power source to provide the properly regulated current to the wire; and a camera with electronic flash attachment to record the velocity profiles depicted by the smoke generated by the wire. (Figure 1)

The present experiments made use of a nichrome wire 0.0015 inch in diameter and approximately 2.0 inches long. A support of berylium copper strips, approximately 0.025 inch thick and 0.20 inch wide, maintained a slight tension in the wire. The supports at each end of the wire, which were given a streamline cross section in the flow direction to minimize disturbances, also served to conduct the electrical current to the wire. Electrical leads connected to the supports were attached to the control box and power source.

The electrical charge to be used was stored in a condenser, which could be discharged through the wire by means of a manual switch. The passage of the resulting rather high current heated the wire very rapidly and caused the oil with which the wire had been coated to vaporize. This oil smoke was then carried downstream at the local velocity of the flow as it passed across the wire. A short time later, approximately several milliseconds, the resulting smoke was brightly illuminated by an electronic flash and was simultaneously photographed. The photograph obtained in this manner thus recorded the velocity profiles of the flow across the wire. The circuit diagram of this equipment is shown in Figure 2.

The circuit shown was designed to produce a thin line of smoke and, after a short delay, to fire a strobeflash to supply the light needed to take a picture of this smoke.

The key, S_1 , referred to in the circuit diagram, is normally open, and it is closed to cause the cycle to begin. With the key open, relay K_1 is inactive; this allows capacitor C_1 to charge to a voltage of 180 volts. When the key is closed, relay K_1 is activated, and C_1 discharges through the resistance wire and causes smoke to be produced. The time constant of this loop is approximately 100 microseconds. Another pair of contacts of the relay K_1 triggers the delay circuit. The amount of delay is determined by the time constant $(R_3 + R_4)(C_2)$. The delay is adjustable from 4 milliseconds to 12 milliseconds with the components used. Time measurements for calibration of the delay circuit were made on an oscilloscope. The voltage pulse of the resistance wire was used to trigger the sweep circuit of the oscilloscope, and a photo-electric cell was used to indicate when the strobeflash fired.

and the second

Statistical Statistics of the

DISCUSSION

In order to determine the applicability and accuracy of this method of flow visualization, the probe was used to measure a laminar boundary layer profile on a flat plate with zero pressure gradient. A photograph of the resulting profile is shown in Figure 3. By projecting and enlarging the negative of this picture in a microfilm viewer, the velocities indicated were measured at various heights, and the velocity profile was determined. The velocities measured in this manner are shown in nondimensional form in comparison to the classical Blasius laminar boundary theory.

Two observers independently measured the example profile shown, and it can be seen that good agreement with theory was obtained in both cases. The actual values of velocities were deduced from a knowledge of the height of the wire and the time delay between the generation of the smoke and the taking of the picture. Several photographs taken at the same position and under the same conditions also showed good repeatability of the process.

With this good agreement found in the steady-state laminar flow condition, the apparatus was next mounted in the turbulent boundary layer of a plate in a zero pressure gradient. The wire was located approximately 6.0 feet downstream of the leading edge of the plate, and the free-stream velocity was maintained at approximately 8.0 feet per second. Under these conditions the boundary layer had only just completed transition to turbulent flow. Slightly upstream of this position, evidence of the Tollmien-Schlichting waves during transition could be seen in smoke filaments allowed to flow parallel to the plate.

Observations of smoke profiles made at the 6.0-foot position indicated strong velocity fluctuations in the boundary layer, and no two profiles observed had the same, or even similar, shapes. Therefore, a number photographs, 21 in all, were made consecutively under identical conditions. Typical examples of this series are shown in Figure 4. The velocities at various heights were measured from each of these photographs, and, with the use of all of the photographs the average velocity at each height was computed. The resulting average, or mean, velocity profile is shown in Figure 5 in comparison with a theoretical flat-plate profile wherein the skin-friction coefficient, C_F , is equal to 0.00405. The deviations between the theoretical profile and the experimental data are thought to result from the fact that fully developed turbulent flow has not yet been realized in the boundary layer.

In order to determine the magnitude of the local values of the streamwise velocity fluctuations, u', the experimentally determined average velocity at various heights in the boundary layer was subtracted from each of the 21 individual profiles, and the deviations from the mean were recorded. The average value of the streamwise fluctuations, u', at any height in the boundary layer should be zero if sufficient samples are measured. In the present case, the average value of the u' fluctuations at any height was never greater than 1 percent of the freestream velocity, which indicates that a sufficient number of profiles, 21, had been measured to obtain a valid statistical average. With this assurance, the root-mean-square values of the fluctuations at any height were calculated and are shown in Figure 6. Examination of this figure shows an apparent anomaly at the height $\frac{1}{8} = 0.65$, where the value of the nondimensionalized streamwise fluctuations, "/u, is much greater than might be expected. Further reference to the photographs of Figure 4 reveals that it is at this height that the predominant perturbations occur in the profiles. It can also be seen from the smoke filaments shown in these photographs, particularly photograph 4(a), that a nearly periodic oscillation exists at approximately the same height. It is felt, therefore, that the unusually high level of turbulence at this height results from the early transition to turbulent flow of disturbances to the mean velocity caused by the Tollmien-Schlichting waves. This premise is further substantiated by the experimental results of Schubauer and Skramstad, who have shown that a 180-degree phase shift in direction of the streamwise fluctuations occurs at a height $\frac{y}{s} = 0.65$. **Presumably**, when the turbulence generated in this region is dissipated, and since it is no longer generated when fully developed turbulence is established, the high level at this height vanishes as the flow moves well downstream from the transition region.

In order to test this proposition that turbulence may be simultaneously generated at the wall and also at some height in the boundary layer as a result of amplified Tollmien-Schlichting waves, the plate was roughened by glueing a 6.0-inch strip of No. 180 sandpaper across the plate about 1 foot downstream of the leading edge. It was thought that this disturbance would cause the turbulence generated at the wall to spread more rapidly throughout the boundary layer and thereby preclude the transition caused by the amplification of the Tollmien-Schlichting waves.

With the roughness in place and with all other conditions the same, 36 smoke profiles were recorded at the measuring position. The data from these photographs were reduced in the manner previously described, and the results are shown in Figures 7 and 8. Here, a much closer agreement between the theory and the experimentally determined mean velocities can be seen. Furthermore, the high turbulence level at $\frac{4}{8}$ = 0.65 no longer appears. It may be concluded, therefore, that the

profile should have a shape more closely corresponding to that of fully developed turbulent flow. This conclusion is substantiated by the good agreement of Figure 7.

and the second of the

Aritetureli, Men. X. M.

the the conductor

CONCLUDING REMARKS

v 15.

Handards a

ar 197 - 198

The usefulness of the present technique of tlow visualization as a means for the quantitative measurement of fluctuating or timedependent flows has been demonstrated by the previous examples. By consecutive measurements at the same position, time-average, or mean, velocities can be measured and, from these, the instantaneous fluctuating velocities can be computed.

The device described is simple to construct and to operate, and no extensive maintenance is required. Furthermore, wide variations of application are possible by different orientations of the wire and by multiple flash photography.

REPERENCES

2

- Brown, R. N. M., "The Visible Wind", <u>Proceedings of the Second</u> <u>Midwestern Conference on Fluid Mechanics</u>, 1952.
- Geller, Edward W., "An Electro-Chemical Method of Visualizing the Laminar Boundary Lyaer in Water", presented to Southeastern Student Branch, Institute of Aeronautical Sciences, Atlanta, Georgia, April 15-17, 1954.
- 3. Head, M. R., "Personal Communication", At Cambridge University, England, 1963.
- 4. Schubauer, G. B., and Skramstad, H. K., <u>Laminar Boundary Layer</u> Oscillations and Transition on a Flat Plate, NACA Report No. 909, Langley Station, Hampton, Virginia, 1948.
- Wortmann, F. X., "Eine Hethode zur Beobachtung und Messung von Wasserstromungen mit Tellur", <u>Zeilschrift fur angew andte Physik</u>, Vol. 5, Book 1, Springer-Verlag, Berlin, Germany, 9 January 1953, p. 201.



うちんえる かんのうないのです

Figure 1. Apparatus for Visualizing and Photographing Boundary Layer Profiles.



Circuit for Producing a Line of Smoke from an Oil-Coated Resistance Wire. Figure 2.

128.18

第二年編5日 またもく

Paral lar

56.00







Figure 4. Some Examples of Instantaneous Measurements of the Turbulent Boundary Layer on a Flat Plate.





.

14

· · · · manificerely · · ·

gr





15

and a char

. . 44

ы^ў



meters - make in which



16

-





17

~*

DISTRIBUTION

US Army Materiel Command	3
US Army Mobility Command	2
US Army Aviation Materiel Command	5
Chief of R&D, DA	2
US Army Transportation Research Command	19
USATRECOM Liaison Officer, US Army R&D Group	
(Europe)	3
US Army Engineer R&D Laboratories	2
Army Rescarch Office-Durham	3
US Army Engineer Waterways Experiment Station	3
US Army Combat Developments Command Aviation	
Agency	3
US Army War College	1
US Army Command and General Staff College	1
US Army Transportation School	1
US Army Aviation School	1
US Army Aviation Test Board	1
US Army General Equipment Test Activity	1
David Taylor Model Basin	3
Marine Corps Liaison Officer, US Army Transportation	
School	1
Ames Research Center, NASA	3
NASA-LRC, Langley Station	3
Lewis Research Center, NASA	3
NASA Representative, Scientific and Technical	
Information Facility	2
National Aviation Facilities Experimental Center	3
US Army Standardization Group, Canada	3
Canadian Liaison Officer, US Army Transportation	
School	1
British Army Staff, British Embassy, Washington	3
US Army Standardization Group, U.K.	3
Defense Documentation Center	20
US Patent Office	1
US Government Priniting Office	1

.

*

۰.

UNCLASSIFIED

Security Classification	
DOCUMENT CO	NTROL DATA - RAD
(Security close incation of bile body of abovect and index	ing annotation much be entered when the avatall report is closelied)
Mississioni State University	THEY ACCTUTY
Astophysics Department	
Staro College Miggingioni	20 SROUP
State Correge, Alssissippi	
A Device for the Direct Measurement	of Unstrady Air Play and Some ("heresteriaria
of Boundary Layer Transition	of onsteady MIL Flow and Some Gharacteristics
of boundary bayer framsteron	
4 DESCRIPTIVE NOTES (Type of report and inclusive dates)	
Interi- Report	
S AUTHOR(S) (Last name, Bret name, initial)	
Cornish, Joseph J. III	
S REPORT DATE	74 TOTAL NO OF PAGES TO NO OF REPS
March 1965	18 5
SA CONTRACT OR GRANT NO	Se ORIGHATOR'S REPORT HUMBER(5)
LAR 44-1//-APL-092(1)	Persenth Note No. 2/
A PROJECT NO	Readerin Note No. 24
¢	So GTHER REPORT HO(S) (Any other numbers that may be escipted this report)
	USATERCON Technical Report 65-12
10 AVAILABILITY/LIMITATION NOTICES	
Qualified requesters may obtain coni	es of this menout from DDC
This weport has been furnished to the	a Department of Compares for sale to the
mulic	te bepartment of commerce for sale to the
11 SUPPLEMENTARY NOTES	12 SPONSORING MILITARY ACTIVITY
	U.S. Army Transportation Research Command
	Fort Eustis, Virginia 23604
13 ABSTRACT	
A device for use in obtaining in	nstantaneous velocity profiles of unsteady
air flows is described. The technique	ies for its use are illustrated by two
typical examples in laminar and turbu	ilent boundary layers.
DD 1080 1473	
UU (JAN 14/3	UNCLASSIFIED
	Frankley Classification

UNCLASSIFIED Security Classification

うち ちょうかい ちょういん ちょうちょう ちょうちょう

14 KEV mons	LINK A		LINK B		LINK C	
		W T	HOLE	ŵ T	ROLE	**
					T	
					1	
			,			
	1					
			1			
		1				
INSTRUCTIONS	L	L	J			
1 OPICINATING ACTIVITY: From the sure and the	, 					

1. ORIGINATING ACTIVITY: Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (corporate author) issuing the report.

2a. REPORT SECURITY CLASSIFICATION: Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

25. GROUP: Automatic downgrsding is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as suthorized.

3. REPORT TITLE: Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediataly following the title.

4. DESCRIPTIVE NOTES: If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. AUTHOR(S): Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. REPORT DATE: Enter the date of the report ss day, month, year; or month, year. If more than one date appears on the report, use date of publication.

7a. TOTAL NUMBER OF PAGES: The total psge count should follow normal pagination procedures, i.e., enter the number of pages containing information.

75. NUMBER OF REFERENCES: Enter the total number of references cited in the report.

8a. CONTRACT OR GRANT NUMBER: If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, 8 8d. PROJECT NUMBER: Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. ORIGINATOR'S REPORT NUMBER(S): Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. OTHER REPORT NUMBER(S): If the report has been assigned any other report numbers (either by the originator or by the sponsor), also enter this number(s).

10. AVAILABILITY/LIMITATION NOTICES: Enter any limitations on further dissemination of the report, other than those imposed by security classification, using standard statements such as:

- (I) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign snnouncement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through

If the report has been furnished to the Office of Technical Servicas, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known-

11. SUPPLEMENTARY NOTES: Use for sdditional explanatory notes.

12. SPONSORING MILITARY ACTIVITY: Enter the name of the departments1 project office or lab ratory sponsoring (paying for) the research and development. Include address.

13 ABSTRACT Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as $(TS)_{-}(S)_{-}(C)$, or $(U)_{-}$

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14 KEY WORDS. Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Idenfuers, such as equipment model designation, trade name military project code name geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links rules and weights is optional.

UNCLASSIFIED

Security Classification

t 47 4=6 5