AD

# **USATRECOM TECHNICAL REPORT 65-2**

DEVELOPMENT OF A CRASHWORTHY, ARMORED, UNIVERSAL CREW SEAT FOR U.S. ARMY AIRCRAFT

> BY GEORGE I. HACKENBERGER WALLACE O. MATTENSON

> > FEBRUARY 1965

U. S. ARMY TRANSPORTATION RESEARCH COMMAND FORT EUSTIS, VIRGINIA

CONTRACT DA 44-177-AMC-93(T)

KAMAN AIRCRAFT CORPORATION



61423

AD

£ .

(-





## DDC Availability Notice

Qualified requesters may obtain copies of this report from DDC.

This report has been furnished to the Department of Commerce for sale to the public.

## Disclaimer

The findings in this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission, to manufacture, use, or sell any patented invention that may in any way be related thereto.

## Disposition Instructions

Destroy this report when it is no longer needed. Do not return it to the originator.

HEALCH LARTERS USARMY TRAUSPORTATION RESEARCH COMMAND FORT EUSTIE, VIRGINIA 23604

おいたのではないです。

Investigation of Liroraft accidents and results of dynamic crash tests of representative types of Army zircraft have pointed up the design strength inadequacy of crew seats manufactured in accordance with existing military specifications. Also, experience has proved the need for personnel armor protective systems for aircraft crews operating in combat areas. To determine the feasibility of integrating armor protection into the basic design of a crew seat fabricated to meet specific crashworthiness criteria, the U. S. Army Transportation Research Command negotiated contracts with four different airframe manufacturers.

This report, prepared by Kaman Aircraft Corporation under the terms of Contract DA 44-177-AMC-93(T), represents the approach of one manufacturer toward a solution to the problem. In addition to crashworthiness oriteria and armor protection, the work under this contract included investigation of the possibility of designing a crew seat having universal application to many types and models of Army aircraft. This Command reserves comment on the appropriateness of the Contractor's conclusions and recommendations, pending the results of programmed flight, ballistic, and dynamic crash tests of the seats reported on herein. Task 1D121401A1500301 Contract DA 44-177-AMC-93(T) USATRECOM Technical Report 65-2

February 1965

DEVELOPMENT OF A CRASHWORTHY, ARMORED, UNIVERSAL CREW SEAT FOR U. S. ARMY AIRCRAFT

> Prepared by Kaman Aircraft Corporation Bloomfield, Connecticut

> > for

U. S. ARMY TRANSPORTATION RESEARCH COMMAND Fort Eustis, Virginia

#### SUMMARY

This program developed five experimental armored crashworthy crew seats for application in Army aircraft.

Study and analysis indicated that a universal crew seat or family of seats may be adapted for usage in existing Army aircraft. Structural reinforcement would be required to withstand the higher seat loads and compromises would be necessary to clear equipment and to adapt to varying structural configuration.

Problems of optimum restraint, crash load attenuation, armor selection, armor coverage, mechanical system and structural system are discussed.

To achieve the safety objectives of the seat system, improvements to the standard restraint harness have been recommended.

Installation of the armor introduces clearance problems especially with aft control stick travel. Resolution of this problem may require aircraft variations.

Supply and maintenance of future aircraft would be enhanced by the application of an armored crashworthy crew seat. Specifications, which control the seat installation and the area around the seat, are necessary to achieve universality in these aircraft.

# CONTENTS

							Page
SUMMARY	• •	•	•	•	•	•	111
LIST OF ILLUSTRATIO	. en	•	•	•	•	•	vii
INTRODUCTION .	• •	•	•	•	•	٠	3
RECOMMENDATIONS.	• •	•	•	•	•	•	4
DISCUSSION	• •	•	•	•	•	•	5
ENERGY ABSORPTION	• •	•	•	•	•	•	12
SEAT TRAVEL .	• •	•	•	•	•	•	15
ARMOR CONSIDERATION	S.	•	•	•	•	•	16
RESTRAINT SYSTEM	• •	•	•	•	•	٠	22
MECHANICAL CONSIDER.	ATIONS	•	•	•	•	٠	24
STRESS ANALYSIS	• •	•	٠	•	•	•	26
BIBLIOGRAPHY	• •	•	•	•	•	•	27
DISTRIBUTION	• •	•	•	•	•		29
APPENDIX I, LOAD AN	ALYSIS	•	•	•	٠	•	31
APPENDIX II, STRESS	ANALYSIS	•	•	•	•	•	53

V

# ILLUSTRATIONS

Figure		Page
1	Seat Assembly	2
2	Energy Absorber	13
3	Armor Coverage	17
4	Seat with Occupant Demonstrating Torso	
	Shield Travel	18
5	Seat Loads and Directions	35
6	Seat Geometry and C.G. Data	39
7	Reference Axes for Load Analysis	41
8	Geometry of Seat Bucket Loads	41
9	Geometry of Seat Support Loads	45
10	Upper Torso Restraint Loads from Chest	
	Strap and Shoulder Harness	50
11	Upper Torso Restrant Loads from Shoulder	
	Harness Only	51
12	Lower Torso Restraint Loads	52
13	Lap Belt Attachment Details	54
14	Lap Belt Attachment Plate	56
15	Chest Belt Loading	57
1 <b>6</b>	Seat Upper Cross Beam Loading	58
17	Attachment of Seat Upper Beam to Seat Side	60
18	Seat Bottom Loading	62
19	Seat Bottom Load Distribution	63
20	Seat Bottom Connecting Angle	64
21	Track Flange Loading	68
22	Seat Upper Roller Bracket Loading	69
23	Seat Back Loading due to Energy Absorber	
	Loads	71
24	Loading of Seat Back at Upper Rollers .	72
25	Bending of Seat Back and Reinforcing Rib .	73
26	Upper Roller Fitting	75
27	Upper Roller Fitting Loading	78
28	Seat Side Frame Loading at Upper Roller .	76
29	Upper Roller Fitting Lug Loading	79
30	Seut Side Frame Loading	83
31	Seat Support Side Beam Loading	86
32	Side Beam Torque Box	88

## INTRODUCTION

Recent operations in Asia have proven the need for aircrew protection from small arms fire. Also, in recent years it has been realized that aircrew seats crashworthiness criteria were inadequate. Research in crash safety has repeatedly shown that survivable crash loads were much more severe than seat design criteria.

Achievement of acceptable armor protection confronts the designer with severe problems of comfort, cockpit space limitations, and weight. Crashworthiness involves both the latter two problems and the additional problems of energy absorption to limit the acceleration levels experienced by the seat occupant. All of these problems are aggravated in smaller classes of aircraft.

This program contemplates the creation of a basic seat design, incorporating both armor protection and crashworthiness, capable of installation in all size classes of Army aircraft. Contract objectives included a definition of this basic seat and a study of the degree of compromise required to adapt the seat to the various aircraft classes. A major objective of the overall program (including the test phases not performed by the contractor) is felt to be a determination of seat weight and space requirements which would be of use in formulating design specifications for future Army aircraft.

The following aircraft were studied for application of a common seat or family of seats:

1.	0-1B	3.	<b>U-1A</b>	5.	CH-47	7. (	<b>刑-1B</b>
2.	U-6A	4.	CV-2A	6.	CH-34		

As will be shown, a seat design was evolved, which, with appropriate support modifications, could be installed in these aircraft. In all cases, some degree of compromise would be involved in the installation.





2

----

## CONCLUSIONS

- 1. A crashworthy armored seat essentially fulfilling the objectives of the Work Statement is practical and could be accommodated (dimensionally) by all size classes of Army aircraft. Compromises which allow for variations in space and structural provisions are necessary to permit installation of the seat in existing aircraft.
- 2. Because the supporting structure is not designed to the strength requirements of the seat, the seat would probably not develop its full crashworthy potential in existing aircraft without extensive structural modifications to the aircraft. This would probably be particularly true of the smaller existing aircraft.
- 3. Such a seat could realize its crashworthy potential more fully and efficiently in a new aircraft, in which original design specifications could provide for the seat by specifying:
  - (a) Adequate strength in seat backup structure, and
  - (b) Adequate clear space under the seat for energy absorbing stroke.
- 4. Allowing 20 pounds for the mean weight of currently used crew seats, the weight penalty (in the seat itself) should not exceed:
  - 40 pounds for crashworthy features
  - 150 pounds for crashworthy features and armor

The weight penalty in the airframe resulting from 3 (a) and (b), above, would be in addition.

- 5. Compromises in control clearance would be involved in all existing aircraft studied if armor protection for the torso in the forward sector is required.
- 6. Compromises in energy absorption stroke would be involved in all existing aircraft studied, if the crashworthiness feature is required.
- 7. Present shoulder harness geometry is inadequate for the protection of crewmen at the deceleration levels contemplated by the Work Statement.

## RECOMMENDATIONS

1. For any Army aircraft:

「「「「「「「「「「「「「」」」」」」

τ

Š.

- (a) Consider testing crashworthy-design seats under conditions wherein vertical accelerations are combined with simultaneous fore and aft accelerations to determine the effects on energy-absorbing devices.
- (b) Consider testing to determine the effects in inducing spinal compression, of forward loads on shoulder harness geometry.
- (c) Consider the development of an integrated restraint system, including adequate pelvic support and possible head restraint.
- 2. For existing Army aircraft:

If the crashworthiness feature is required, consider the seat and its backup structure as a single system and determine the strength and deceleration characteristics of this system in the presence of combined vertical and forward loadings.

- 3. For future Army aircraft:
  - (a) Consider modification to MS 33575 cockpit dimensions to resolve interferences between the control throw and the chest armor.
  - (b) Consider specifications for seat backup structure strength requirements and seat space requirements to assure that the aircraft is compatible with the crashworthy armored seat.

#### DISCUSSION

#### GENERAL

The seats were designed with the following objectives, which are the specifics of the Work Statement:

- 1. Provide fore and aft and up and down adjustment of the seat.
- 2. Provide protection against 7.62 mm AP projectiles fired at a range of 100 yards and striking at 15 degree obliquity.
- 3. Protect the trunk-torso body area of the air crewmen, when seated in the normal manner, against fire delivered from positions below an imaginary horizontal plane . passing across the shoulders of the pilot/copilot, while the aircraft is in level flight attitude.
- 4. Provide protection against multiple hits striking more than 6 inches apart.
- 5. Protective equipment will not restrict or interfere with the movements of the crew required in normal operation of the aircraft.
- 6. Protective equipment will not interfere with the normal operation of the aircraft.
- 7. Protective equipment will not unduly restrict the external field of vision of the crew, nor impair depth or color perception nor degrade visual acuity.
- 8. Protection equipment will include quick release or disconnect features, as necessary, to permit rapid egress from the aircraft in emergency situations.
- 9. Protective materials will be fire retardant.
- 10. The seat, its support system (exclusive of airframe structure, and the occupant restraint system, individually and in combination, shall have sufficient strength to withstand the reaction from longitudinal

decelerations of 25g for 0.20 second and 45g for 0.10 second combined with lateral decelerations of 10.5g in the pelvic region of a suitable anthropomorphic dummy having a weight and mass distribution of that of the 95th percentile man. Progressive plastic deformation of the seat is permissible provided complete failure and subsequent injurious situations do not occur.

11. The seat, its support system (exclusive of airframe structure), and the occupant restraint system in combination, during high vertical impact conditions, shall be capable of continuously maintaining 20g +3g, in the pelvic region of the dummy described above, while deforming through 12 inches of vertical travel with respect to the airframe and, where possible, up to 15 inches or more of vertical travel. あるの時間にしょう

Ð

- 12. The seat system must restrain the occupant, during or after impact, in such a manner as to maintain alignment of the occupant's torso in a normal sitting position.
- 13. The system will present no projections or cutting edges in the event of failure due to loads in excess of the design values.
- 14. The restraint system will include a lap belt, shoulder harness, and crotch or thigh strap(s).

First studies of seat installations in the subject aircraft showed that a completely interchangeable seat installation could not be simply achieved in the existing aircraft due to the diversity of structural attaching points.

For example the following is a tabulation of the width between seat attaching points for the aircraft:

Aircraft	Width Between Structural Attachments
0-1 <b>E</b>	14.50
СН-47	20.14
B-34	18.00 (Bulkhead Mounted)
<b>U-6</b>	12.00
CV-2A	20.30
UH-1	16.00

In addition to the width differences noted above there is the same diversity in fore and aft location of frames and attaching points in relation to the seat position for each aircraft.

A reasible approach to the universal seat is to design a seat which, with minor structural variations, can be installed on the floor of aircraft like the CH-47 and CV-2A. Such a seat could be adapted to the narrower support spacing of the remaining aircraft through the use of a structural box. This adapter box, in effect, would create a false floor for mounting of the standardized seat. This elevated false floor would reduce the load-limiting stroke during crash, but, with proper design, buckling of the adapter box would contribute to the required energy absorption.

「「「「「「「」」」」」

This approach, however, assumed structural strength in the existing airframe backup structure adequate to carry, without substantial deflection, enough load to operate the energy absorber. If the aircraft structure is appreciably weaker than the seat, deformation of the structure can allow the seat to pull loose, cock, or otherwise assume a random attitude prior to structural "bottoming out", in which case proper operation of the energy absorption means cannot be assured.

Since the Work Statement excludes consideration of the aircraft structure, it cannot be stated that seats furnished would be permitted to devolop the full measure of crashworthiness designed into them. As a consequence, and as a result of discussions with USATENCON representatives, the experimental seats are designed to be floor-mounted and to have an energy absorption stroke which travels the seat to the floor.

The contractor has furnished, at USATRECOM's request, simple plate adapters connecting the seat mounting points to the existing structural hard points of the test aircraft, to permit installation without modification of the aircraft. These adapters are considered test hardware and are designed to carry maneuvering loads only. Sufficient margin is provided to carry moderate crash loads. The weight of these adapters should be excluded from any consideration of seat weight. In addition to structural variations, there is the problem of space requirements. All of the subject aircraft have intrusions into the area that would be occupied by the seat system. General de la

1

5

1

1.1

A general problem is that of clearance with the pilot's controls. In all the subject aircraft, normal stick or wheel aft travel touches or barely misses the pilot's torso. Interposing an armored protective torso shield results in control interference except in the most aft seat positions. This interference negates the fore and aft seat adjustment function and emphasizes the problem of accommoditing the shorter pilot. This problem has not been solved because the large pilot with parachute harness and restraint system requires that the torso shield be well forward, while control travel requires that it be well aft.

These opposing requirements cannot be satisfied by seat design alone because the short pilot, who needs the forward seat position, does not necessarily have a small chest. (See page 86 in Reference 18.) The noted table shows that chest depth and stature are widely variable and that the 65-inch stature may have the same 10-inch chest depth as the 74-inch stature. Because of the diverse requirements, control interference with the torso shield cannot be eliminated for all seat positions. For the experimental seat flight testing, the seats must be positioned to clear the controls when the torso shield is in use.

In future aircraft which may require pilot torso protection, allowance should be made to permit torso shield installation without interfering with operation of the pilot's controls.

A special requirement for the helicopter seat is space allowance for operating the collective stick. Full travel of the stick sweeps the left arm through a large area on the left side of the seat.

Clearance for the pilot's hand on the collective stick is a factor which limits allowable seat width. Arm clearance is a factor in determining shoulder armor location and seat support configuration.

Because of the noted variations in the seat installation requirements for the subject aircraft, universality can be achieved only in the seat bucket. Each support must be adapted and fitted to the individual aircraft.

The seat bucket of the experimental seats conforms generally to MIL-5-5622 and with an average of the seats in the existing aircraft. A 3-inch thick foam seat cushion is provided. While it is recognized that optimum crashworthiness is attained by seating the pilot directly on seat structure eliminating any soft elastic element in the system, it was felt that this would result in a seat which would be impractical because it would be excessively unconfortable to pilots. It is true that space can be developed, in a crash, between the pilot and his restraining harness as a result of cushion deflection. This is also true of a rigid/crushable type of seat pad. However, considering initial deflection of the cushion when the pilot seats himself, and "solid heighth" of a fully compressed foam pad, this space will be much less than the full 3-inch thickness of the uncompressed cushion. Potentially injurious rebound energy stored in the compressed airframe structure will be limited to 25g headward by the seat's energy absorber, which operates in both directions. The degree to which potentially injurious re-bound energy might be stored in the sprung mass of the seat bucket itself, and, therefore, the significance of elastic cushion from a crashworthiness standpoint, should be readily determinable from dynamic test results.

The parachute thickness allowance is 4 inches.

The back of the seat is made of three flat panels which conform approximately to the parachute pack shape.

The seat support of the experimental seats is configured for minimum protrusion into the area occupied by the crewmen. The concave shape (see Figure 1) of the support clears the pilot's arms during the energy absorption stroke in a crash, and makes for easier postcrash egress. This design approach results in a somewhat heavier support structure; however, the added safety and ease of operation are considered a reasonable trade-off for the estimated 5 pounds per seat weight increment.

#### INSTALLATION CONSIDERATIONS IN ARMY AIRCRAFT

Seat installations in the subject aircraft will have a variety of problems which must be net with compromises to allow seat installation. For example: 1. In the O-1E aircraft, the aft rudder pedals extend into the area under the forward seat. Serious design variations and compromises would be necessary to make the rudder pedal installation compatible with the seat space requirements. The shoulder shields of the experimental seats interfere with free access to the window and door handles, and it is probable that an optimum installation would integrate the shoulder protection into the aircraft structure instead of the seat.

のののないので、「「「「「」」」」」

An adapter is required to fit the standardized seat to the O-IE aircraft structure. This adapter would have the special problem of clearing the control system torque tube which is above the aircraft floor. Energyabsorption stroke would be shortened by the height of the adapter assembly.

- 2. In the UH-1B, the adapter to fit the seat to the structure would have special problems of clearance with the collective stick installation, access to floor openings for maintenance, and clearance for the heater outlets. The shoulder protector again impedes access to the door handle, and supporting this armor from the structure may be necessary for optimum design. A special factor in the UH-1B is the low position of the collective stick, which requires that the pilot lower his left shoulder to get full down collective. Space allowed to permit this motion reduces the armor coverage in the left underarm area.
- 3. In the CH-47, aft and upward travel of the seat is limited by the canted bulkhead behind the pilot. This clearance requirement results in reduced energy-absorber travel because the seat must be aft to clear the control stick and must be in a low position to clear the canted bulkhead. The seat installation in the CH-47 is enhanced by the special collective stick, which occupies minimum space above the floor, and by the existing backup beams, which are spaced wide enough to nearly coincide with the requirements of the seat support.
- 4. The CV-2A seems best suited for installation of the crashworthy armored seat. The structural backup for the existing seat is spaced to be suitable for the seat support. Space is adequate for seat installation. Allowances must be made for the trim control installation and for adjacent equipment and controls, but these problems appear to be minor and routine.

5. The H-34 has the unique requirement for bulkhead mounting, and the existing seats have the capability of hinging to permit access to the cockpit from below. This seat installation will be considerably different from the floor-mounted seat, but many components such as armor panels, energy absorber, and some structural members may be common parts.

n general methods and a second and the second

- 5. The seat installation in the U-1A is difficult because of interferences with trim controls, flap hydraulic pump and system, and other equipment under or adjacent to the meat. The armored seat bucket itself may be installed with minimum changes, but the energy-absorbing system would require significate reduction in stroke or complete deletion unless significant airframe changes were contemplated. The most desirable trade-off of seat/airframe compromise involves considerations of military requirements and economics beyond the scope of this contract.
- 7. The U-6A seat installation has close side and aft clearance requirements. Heater system components and an emergency hydraulic system under the pilot's seat protrude into the seat area. As in the U-1A, installation of the armored seat bucket on a support which meets the space requirements will result in reduced energyabsorption capability.

, a.

#### ENERGY ABSORPTION

To prevent spinal injury, compression loads on the spine must be limited to those generated by 25g vertical loads. Since the anticipated crash loads are much in excess of this safe limit, it is necessary to provide load-limiting energy absorbers which isolate the seat from the critical vertical loads. To be effective, the energy-absorbing stroke must be as long as practical.

Various mechanical energy absorbers were considered. These include:

- 1. Crushable materials such as aluminum honeycomb, other aluminum foil shapes, balsa, and plastic foam.
- 2. Metal deforming devices such as metal drawing or extruding, metal bending.

でもうというというないのない

日朝の間である。それも行

- 3. Frangible tubular strut shattering as it is compressed onto a die which flares the tube end beyond its elastic limit. See Reference 6.
- 4. Friction slides which depend upon holding effect of a sliding brake.
- 5. Hydraulic struts which maintain load by metering or hydraulic fluid through an orifice.

The following factors are considered essential in the selection of the energy absorber:

- 1. The device must be bidirectional. Load reversals can and do occur during crashes (as shown on page 36 of Reference 17), and unidirectional energy absorbers (such as crushable material beneath a seat only) will not idequately protect the occupant. If a unidirectional device is employed, it requires at least an antirebound device. as shown in Reference 15.
- 2. The energy absorber must fit into a small volume in order to achieve minimum size for the seat support which is vital for universal application.

3. The energy absorber must be simple and predictable for reliable operation. In the vast majority of cases it will never be called upon to act. In the rare case where a crash does occur, the device must operate reliably after perhaps years with no attention. This requires simplicity and complete freedom from required adjustments.

The metal-bending type of energy absorber was selected for use in this program. The unit absorbs energy by bending and rebending four metal straps around a set of pins. (See Figure 2.)



Figure 2. Energy Absorber

This unit was selected for the following reasons:

- 1. It is an operationally proven device.
- 2. It is bidirectional. Antirebound mechanism is inherent.
- 3. It is a small package  $(1.56 \times 1.25 \times 16.75 \text{ inches})$ which may be compactly incorporated into the seat assembly.
- 4. Stroke is limited only by the length of the strap.
- 5. This type of energy absorber is suited for bulkheadmounted seats as well as floor-mounted seats.

6. Energy absorption capability may be readily varied by change in strap width. If a criterion-type change should be made after a production quantity of seats is in the field, retrofit of new straps would be simple and inexpensive.

in white the second

To conserve space and to simplify the mounting of the seat bucket, the load limiter was installed in a position parallel to the seat back. Hence, load limiting travel is parallel to the seat back. It was considered that this travel would provide maximum alleviation of load on the occupant's spine and would be most suitable for a universal seat.

簀

The state of the state of

L

## SEAT TRAVEL

The Work Statement objective of 12 to 15 inches of vertical travel for energy absorption requires that this much space be available beneath the seat in its lowest adjustment. Existing aircraft do not approach this desirable objective. Since the seats for installation in existing aircraft must place the pilot in the same position with respect to controls and instruments as the aircraft's normal seat, the stroke available to the energy absorber is necessarily limited to less than the desirable 12 to 15 inches.

Obviously space for increased stroke could become a specification requirement of new aircraft. The design presented herein is limited in stroke only by the space limitations of the aircraft in which it is installed. Changes in seat support height and energy-absorber length will permit the longer recommended energy-absorber stroke.

The adjustable height of the seat reference point above the heel rest line is 10.0( to 14.50 inches. Energy-absorption travel is the seat height less 5 inches. That is, the seat will travel 9.5 inches from its high position and 5 inches from its low position to bottom out on the seat track and seat support structure.

The seat height agrees with the UH-1B and 0-1E. The top height is approximately 1.5 inches lower than that of the CH-47, but interference with the aircraft bulkhead behind the pilot precludes this high position.

To meet the stroke requirement of the energy-absorption system, the seat and bucket must travel until the system nearly reaches the cockpit floor. Any obstruction which shortens this travel will reduce the effectiveness and safety of the energy-absorbing system.

The 0-1E, U-6A, and U-1A aircraft all have equipment, controls, structure, or plumbing which interferes with travel of the seat bucket to the floor during the energy-absorption stroke. For future aircraft, the requirements of the crashworthy seat should govern in this area.

#### ARMOR CONSIDERATIONS

## MATERIAL

あるためにないというないであると

Contraction of the second second

Second Second

· · · · ·

j.

ί

÷

A hard-faced composite, made from ceramic tile with laminated backing, was selected as the armor material. The contractor was guided in this choice largely by Reference 10. Independent consultation with competent suppliers of both armor materials and armament reinforced this decision. No alternate materials or types of construction were found which could compete with the chosen material on a weight basis.

In order to achieve minimum weight and minimum envelope for the seats, a design approach was taken which used the armor panels as structural elements of the seat. The back and seat armor panels are essential parts of the seat bucket structure. A part of the weight maved by permitting the armor backing material also to carry structural loads is reinvested in additional armor coverage and in features (discussed elsewhere in this report) to increase the crashworthiness of the seat.

The side armor panel, the shoulder panel, and the torso shield are easily removed for replacement. Bacause the seat and back argor panels are integrated into the seat structure, some weight sacrifice was made to provide for ease of seat bucket replacement to minimize down time due to armor damage. Individual bucket panels would also be interchangeable, on a production quantity of seats made from hard tooling.

#### ARMOR COVERAGE

The ideal situation (from guniire protection) of having the seat occupant completely enveloped in armor wust be compromised in favor of:

- 1. Weight
- 2. Adequate clearance for pilot's vision
- 3.
- Adequate clearance for pilot's operation of controls Adequate clearance for ingress and egress from air-4. craft.

The armor configuration which was developed to protect the occupant and to permit normal and emergency operation is shown in Figures 3 and 4.



Figure 3. Armor Coverage



The armor coverage provided by the seat is apparent from Figures 3 and 4. The back, bottom, and sides of the seat bucket are protected, except for narrow strips at the edges. These areas could readily be included in the protected areas on a production quantity of seats sufficient to justify the accessary tooling. In addition, a hinged shoulder shield is provided to protect the upper arm and upper torso from fire from the side. Hinging is necessary for ingress and egress. In aircraft with side-by-side pilots, one such hinged shoulder shield is used on the outboard side of each seat, the assumption being made that the inboard sides are protected by the opposite seat. In tandem aircraft, two shoulder shields may be used, one on each side.

Protection from fire from the forward sector is provided by a detachable torso shield, which protects the upper torso and groin, as shown in Figure 4.

This coverage was worked out empirically, in concert with the contractor's Flight Test Staff, with the aid of mockups.

#### TORSO SHIZLD

This portion of the armor represented the greatest design problem and is felt worthy of separate discussion. Despite the difficulties which are apparent with a torse shield (such as aft control throw interference and restriction of pilot's motion), it was felt to be the only feasible method of providing significant forward protection integrated with a seat.

The following features of the torso shield were considered to be design requirements:

- 1. Depth to clear 95th percentile pilot's chest.
- 2. Underarm height nonrestrictive to 25th percentile pilot.
- 3. Easily detachable for ingress and egress.
- 4. Fully supported from seat.
- 5. Connected to seat until released. Crash loads cannot be permitted to dislodge torso shield and make a missile of it.
- 6. Single point of release.

7. Provision for pilot to reach instrument panel or overhead panel (lean forward) without disconnecting the structural support.

の大学の日本

÷

ţ

Ą

ŭ

8. Protection of pilot by upper front portion without interference, and yet without guillotining the pilot or crushing his face if forward crash loads snap head forward upon shield.

The torso shield provided meets these requirements. Its barrel shape is formed from multiple connected flat panels for the experimental seats; for a production quantity justifying the tooling, the shield could be furnished in onepiece construction with no fasteners except in the upper front. The latter is connected with breakaway shear pins for the reasons stated in feature 8 above.

The torso shield is strapped to a four-bar linkage train which supports the shield and allows it to travel in front of the pilot (see Figure 4). The travel permits the pilot to lean forward and reach switches or controls on the instrument panel or the forward overhead panels.

The four-bar linkage is used to support the torso shield for the following reasons:

- 1. Protrusion into pilot's operating area is minimized.
- 2. Direct structural connection to seat structure is achieved.
- 3. Necessary freedom of motion is provided.
- 4. Restraint system is not compromised by requirements of torso shield support.
- 5. Weight of torso shield is supported at all times by the linkage.
- 6. Single point of release is provided.
- 7. Torso shield does not add to crash loads applied to seat occupant.

Latches are provided to connect the shield to the seat structure. The latched condition is the normal mode for almost all flight situations. Release of the latch is effected by raising the shield approximately 1/2 inch and leaning forward to separate the latch and allow motion. Re-latching of the shield is accomplished by pushing the shield back to the seat. Slight upward pressure is necessary to reach the position where both latches will drop into the retaining hooks of the seat structure.

The torso shield is attached to the support linkage by a nylon strap which encircles the shield and bolts to the linkage. The strap has a buckle for adjustment, positive tensioning and quick release. Installation of the torso shield consists of placing the shield into the guide channels of the support linkage and buckling the strap. Removal of the shield is accomplished by operating the buckle of the retaining strap and moving the shield forward out of the guide channels.

#### RESTRAINT SYSTEM

「おおいた」「おき」の事

7

- #•

The high load capability of the seat system demands that the restraint system be of optimum configuration. An optimum restraint system should support and safely restrain the crewman during crash, allow freedom to operate the aircraft, be simple to operate, and be universally suited for all sizes of crewmen.

To be safe, the restraint harness should not induce critical loads into the crewman's body or allow the body to be loaded in a manner which may cause injury.

The standard shoulder harness is less than optimum because forward loads induce compression loads in the crewman's spine.

When forward and downward loads are considered as acting simultaneously, the spineward compression induced by the standard shoulder harness is additive to the aircraft downward load. If a combined loading of 45g forward and 20g downward (aircraft load factors) is assumed, the resulting loads developed in the crewman are critically high. The analysis upon which this is based is given in Appendix I.

While the analysis is uncertain because of belt friction factors, body dynamics and internal load distribution, the magnitude of the calculated induced load (28g) is too high to be disregarded. A load only one-third as high when added to the direct spinal compression due to vertical loads will be critical. Any load increment added to spinal compression tends to negate the function of the load relief system. For this reason upper torso support, which acts directly to restrain without inducing spinal loads, is necessary for a safe restraint system.

From page 13 in Reference 2, about 70 percent of injuries which were attributed to pure decelerative forces involved the spinal column. In rotary-wing aircraft, most of these spinal injuries (70 percent) occurred in accidents with high vertical forces. In fixed-wing, less than half (45 percent) the spinal injuries occurred in accidents with high vertical forces.

Incidence of spinal injury without causative high vertical forces seems to support the position that the restraint harness may be inducing critical loads into the survivor. Pelvic support is another critical factor in the restraint system.

During crash, high inertia forces of the leg act to pull the pelvis into a tilted position ("submarining").

Any tilting of the pelvis causes eccentric loading and bending of the lower spine and vertebrae; failure may result. Such an injury may result in fatal damage of the spinal cord or incapacitation, which may cause the survivor to succumb to postcrash factors, such as fire.

One experimental seat includes an inverted vee strap for pelvic support and a chest safety belt for upper torso support.

1

It was considered beyond the scope of this program to carry out the necessary development, testing, and evaluation which would be required to develop the optimum restraint system. The experimental restraint system is a first step toward a suitable restraint harness.

A program which examines all factors and establishes, by test and subjective evaluation, the detail requirements of the system is necessary for achieving the optimum restraint system.

#### MECHANICAL CONSIDERATIONS

The designer is tempted to save weight by providing for vertical energy-absorption travel (and adjustment travel) via slides. However, systems which may operate admirably on slides during a test in which only vertical accelerations are applied could very easily malfunction (with disastrous consequences to the seat occupant) during an actual crash, in which the vertical acceleration is accompanied by simultaneous forward and/or lateral accelerations. Since the seats will be flown, as well as tested, the contractor has elected to make a further weight sacrifice to assure that vertical load limiting is not unduly influenced by fore and aft or side loads.

From page 44 of Appendix I, seat bucket guide loadings were derived. The maximum combined seat guide loading occurs in the condition Px + Py + Pz:

Fx Fx GHx Hy	8191 12869 6620 940 5027 3265	Note:	"J" is not a seat guide load.
			· · · ·

Total = 36912 pounds

For energy-absorption travel, the minimum combined seat guide loading occurs during the condition Pz = 6000 pounds:

E <sub>x</sub>	<b>7</b>	2650	Note:	Ouit Fy and Hy
P <sub>x</sub>		5300		because they result
G	-	2650		from a nonsymmetrical
H <sub>x</sub>	•	5300		loading which may not
				decur.

Total = 15900 pounds

A rolling guide system and a sliding guide system were investigated. The slide system which had the advantages of simplicity and low cost was checked first. Because of the high variable loads on the guides, it was imperative that the coefficient of friction be small and predictable. The coefficient of sliding griction is sensitive to contamination, humidity, surface finish, velocity of sliding, and bearing pressure. Since all of these factors would be impossible to control, it was concluded that only a low friction roller system would allow the load limiter to operate within the 15g-25g specified limits. The effects of guide roller friction are discussed in detail on page 33 of Appendix I.

The seat bucket adjusts vertically on tracks of the seat support, and the support adjusts fore and aft on floor tracks. "Vertical" adjustment is actually parallel to the seat back in order to conserve cockpit space. The seat is spring balanced by four 35-pound extension springs which maintain an upward force on the seat bucket when the seat is being adjusted.

The vertical adjustment is held by shear lugs on the bucket which latch into a notched guide on the seat support. This notched guide is linked to the seat support by the load limiter so that the seat may travel its energy-absorbing stroke from any adjustment position. The fore and aft position is held by shear pins which protrude from the support assembly into the forward track.

The vertical adjustment lever is inside the seat bucket on the right side. The handle protrudes forward of the seat in position for easy operation. Upward motion of the handle retracts the shear lugs which hold the seat in position. The fore and aft adjustment lever is at the left side of the seat support, and upward rotation of the lever retracts the shear pins and allows fore and aft seat motion.

The inertia reel is attached to the upper back of the seat. The reel lock is under the left side of the seat bucket within easy reach of the pilot but concealed so that it does not interfere with the energy-absorbing stroke.

#### STRESS ANALYSIS

In the structural analysis of the seat design, it is considered that the area of prime importance is the translation of the specified load factors into loads and the distribution of these loads upon the several components of the seat. This, therefore, is treated in considerable detail in Appendix I.

The detailed sizing of individual seat components, number and size of bolts, etc., is considered routine engineering, and is not repeated herein in detail; several typical examples are shown (in Appendix II) of the detailed stress analysis of critical areas of the seat. Methods are typical of standard aircraft stress analysis procedures which have been applied throughout.

As previously stated, the armor panels are integral structural elements of the seat. Applied loads to be carried by the armor were determined by the contractor, as shown in Appendix I. The detailed stress analysis of the armor panels was conducted by the supplier of the armor. Typical examples of this analysis are included in Appendix II.

## BIBLIOGRAPHY

- 1. Anorymous, Strength of Metal Aircraft Elements, MIL-HEBK-5, Armed Forces Supply Support Center, Washington, D.C., March 1959.
- 2. Be. 20%, A. A., "Helicopter Versus Fixed Wing Crash Injuries", Journal of Aerospace Medicine, Volume 34, Pages 11-14, January 1963.
- 3. Dempster, W. T., <u>Space Requirements of the Seated</u> <u>Operator</u>, WADC Technical Report 55-159, Wright Air Development Center, Wright Patterson Air Force Base, Ohio, July 1955.
- 4. Eibard, A. M., <u>Accelerations and Passenger Harness</u> Loads Measured in Full Scale Light Airplane Crashes. NASA Technical Note 2991, National Advisory Committee for Aeronautics, Washington, D. C., August 1951.
- 5. Eiband, A. M., <u>Human Tolerance to Rapidly Applied</u> <u>Accelerations, a Summary of the Literature</u>, NASA <u>Memorandum 5-19-59E</u>, June 1959.
- 6. Esgar, J. B., <u>Survey of Energy Absorption Devices for</u> <u>Soft Landing of Space Vehicles</u>. NASA TN S1309, National Aeronautics and Space Administration, Washington, D.C., June 1962.
- Flight Safety Foundation, United States Army Aviation Crash Injury Research, TREC Technical Report 62-13, U.S. Army Transportation Research Command, Fort Eustis, Virginia, September 1961.
- 8. Goldman, D. E., and Von Gierke, H. J., <u>The Effects of</u> <u>Shock and Vibration on Man</u>, Lecture and Review Series No. 60-3, Naval Medical Research Institute, January 1960.
- 9. Haley, J. L., Jr., <u>Personnel Restraint Systems Study</u>, TCREC Technical Report 62-94, U.S. Army Transportation Research Command, Fort Eustis, Virginia, December 1962.

- 10. Hegge, E. N. and Medeiros, M. F., Current Technology of Light Weight Armor Materials for United States Army Aircraft, USAMRA Monograph Series 63-03, United States Army Material Research Agency, Watertown, Massachusetts, May 1963.
- Marks, L. S., Mechanical Engineers Handbook, Fifth Edition, McGraw Hill Book Company, Inc., New York, N.Y., 1951.

記録を見ていたというというというです。

v≠121、3、31863-16

小いた

÷

ŝ

小学

大学をあるいという

- 12. Pearson, R. G., PhD et al, Mechanisms of Injury in Modern Lightplane Crashes: A Statistical Summary of Causative Factors, TCREC Technical Report 62-93, U. S. Army Transportation Research Command, Fort Eustis, Virginia, November 1962.
- 13. Peery, D. J., Aircraft Structures, First Edition, McGraw Hill Book Company, Inc., New York, N.Y., 1950.
- 14. Roark, R. J., Formulas for Stress and Strain, Third Edition, McGraw Hill Book Company, Inc., New York, N.Y., 1954.
- 15. Robertson, S. H., Dynamic Test of an Experimental Troop Seat, TCREC Technical Report 62-18, U. S. Army Transportation Research Command, Fort Eustis, Virginia, June 1962.
- 16. Roegner, H. F., et al, U. S. Army HU-1A Bell Iroquois Helicopter Accident Fort Bragg, North Carolina, TREC Technical Report 60-71, U. S. Army Transportation Research Command, Fort Eustis, Virginia, August 1960.
- 17. Turnbow, J. W., PhD, et al, Crew Seat Design Criteria for Army Aircraft, TREC Technical Report 63-4, U. S. Army Transportation Research Command, Fort Eustis, Virginia, February 1963.
- 18. White, R. M., <u>Anthropometry of Army Aviators</u>, Technical Report EP 150, U. S. Army Quartermaster Research and Engineering Command, Natick, Massachusetts, June 1961.
- 19. Anonymous, Structures Manual, North American Aviation Inc., Los Angeles, California, 1951.

### APPENDIX I

## LOAD ANALYSIS

The seat assembly consists of two major components. They are the seat bucket and the support structure. The seat bucket is suspended within the support assembly.

The occupant loads the seat by direct contact and by the restraint harness. The seat loads the support by roller and track systems for longitudinal and lateral loads. Vertical loads are carried from the seat back panel to the vertical adjustment mechanism which is suspended on the load limiter strap. This load limiter is bolted to the center of the aft web of the support assembly.

The support assembly is tied to the floor at its four corners. The aft fittings carry vertical and side loads. The forward fittings carry vertical and longitudinal loads.

This section deals with distribution of loads at the major points of transfer; namely, the harness attachment points, the seat support rollers, the load limiter, and the floor attachment fittings.

## SEAT LOADS

The seat ultimate loads are as follows:

- Longitudinal 45g for duration of .10 second, 25g for duration of .2 second.
- 2. Lateral 10.5g.
- Vertical 45g for duration of .10 second limited by the energy-absorber system to 25g + 5g at the pelvic region of a 95 percentile dummy.

Because of the relatively long duration of the high loads, the seats and support structure are designed to support statically the 45g longitudinal load combined with 10.5g lateral and 25g vertical loads.

The design objective was a ductile structure with strength sufficient for the above loads.

Preceding Page Blank
### LOAD DIRECTION

1

Load directions are in agreement with the recommendations of Reference 9. Longitudinal loads are assumed to be perpendicular to the spine and vertical loads are assumed to be parallel to the spine. This conservative application of loads provides for maximum protection of the seat occupant.

1

1

### TABLE 1

### WEIGHT AND LOAD DATA

	Weight (1b.)	Load Due to 10.5g (1b.)	Load Due to 45g (1b.)	Load Due to 25g (1b.)
Man + Sest Bucket	318.8	3350	14,360	
Man + Seat Bucket + Support	360.8	3800	16,250	
Man (80% Effective)* + Seat Bucket + Support	320.8	. <b></b>		8030

\* For vertical loads, it is estimated that half of the occupant's leg weight is supported by the floor structure. Since the occupant's legs comprise approximately 40% of his total weight, 80% of his total weight is applied for vertical loads.

### FRICTIONAL LOADS

The loads at the seat bucket guide rollers will develop frictional forces which tend to resist vertical travel of the seat. The maximum load at the seat guide rollers is 36,912 pounds and the minimum load at the seat guide rollers is 15,900 pounds (reference Page 24). The rolling friction of the roller system under load was computed as follows:

Rolling Friction =  $\frac{K}{2}$  L

(Page 223, Reference 11)

k - Rolling friction coefficient

- k = .002 for steel on steel
- k = .02 for hardwood on hardwood
- k = .01 estimated for steel on aluminum alloy

日本の言い

r - Roller radius

- r = .50 inch average
- L Roller loading

Maximum roller friction  $= \frac{.01(36,912)}{5}$ 

- 738 pounds

Minimum roller friction =  $\frac{.01(15,900)}{.5}$ 

= 318 pounds

For the analysis of the operation load limiter, the above friction loads were used. For the analysis of the seat structure, a conservative 1,000 pound frictic% load was added to the supporting force of the load limiter.

### LOAD LIMITER

The load limiter for this seat is rated at 4,750 pounds minimum and 5,250 pounds maximum. This rating applies throughout the stroke of the limiter.

The weight of the moving load, which is supported by the load limiter, is 278.8 pounds. This includes 118.8 pounds for the seat bucket and 160 pounds for the occupant. The 160 pound weight represents 80% of the weight of the occupant (reference Page 32).

The supporting force of the load limiter combined with roller friction will have the following limits:

Maximum supporting force = 5250 + 738

- 5988 pounds

Minimum supporting force = 4750 + 318

= 5068 pounds

Based on the above seat supporting forces, the load limiting system will operate at the following load factors.

Load factor - Force Weight

Load	factor	(maximum)	-	<u>5,988</u> 278.8
			-	<u>21 .4</u>
Load	factor	(minimum)	-	<u>5,068</u> 278.8
			-	18.2g

- Law, other of anti-

72.2

s'

CALL OF A LEASE

5 (5) (5) (5)

!

1.1.1.1.1

The above load factors represent the load limiter operational limits for a 200-pound occupant. Based on the above calculations, the load limiter system will maintain the safe 25g load factor when the moving load is at least 240 pounds. Thus the seat is fulfilling its safety requirement when 121.2 pounds of the occupant's weight is acting to force the seat down.



Figure 5. Seat Loads and Directions.

### RESTRAINT HARNESS LOADS

「古地におき」に

おいたので

Values for the restraint harness loads were calculated (reference Pages 50, 51, and 52). These values were compared with similar values derived in another investigation. (See Reference 9.) The comparison showed reasonably close agreement of load values. The slightly higher more conservative values derived (see Reference 9) were used for this analysis. These loads are listed below.

### TABLE 2

RESTRAINT HARNESS LOADS

# Harness ComponentLoad<br/>(1b.)Shoulder Harness \*4000Lap Belt6000Inverted Vee Strap3000Belt Tie-Down Strap2500

\* Use of chest belt for direct restraint will greatly reduce the shoulder harness loads.

# TABLE 3

	%	Weight Pounds
Whole arm and hand	5.65 x 2ea.	22.6
Whole leg and foot	19.55 x 2ea.	78.2
Head & Neck	7.9	15.8
Trunk	41.7	83.4
Total		200.0

# WEIGHT DISTRIBUTION-200-LB. MAN

NOTE: See Reference 3, pages 186 and 211

TABLE	4
-------	---

We are the event of variable part of a dimension with the

CENTER	0 <b>F</b>	GRAVI	[TY	OF	SEAT	BUCKET
(1)	NCLI	JDING	TO	RSO	SHIE	(D)

32 .5.7	3.80 -6.10	0	10.80	121.5	0	346
.5.7	-6.10	0				
			-4.70	-95.7	0	-73.7
7	-1.40	0	6.60	-37.8	0	178
.0.65	-2.80	13.9	17.10	-29,8	148.3	182
8.45	-2.20	9.3	2.20	-18.5	78.6	18.5
15	-8.08	0	8.50	-202	0	212
8.8				-262.3	226.9	862.8
<b>x</b> - 1	E.W	-2.2	2			
ÿ =	C <u>WY</u>	1.9	2			
<u>z</u> - <sup>1</sup>	L WE	7.2	5			
	0.65 8.45 5.8.8 $\overline{x} = \frac{1}{2}$ $\overline{y} = \frac{1}{2}$	$ \begin{array}{cccccccccccccccccccccccccccccccccccc$	$\begin{array}{rrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrr$	$ \begin{array}{r} 0.65 & -2.80 & 13.9 & 17.10 \\ 8.45 & -2.20 & 9.3 & 2.20 \\ 5 & -8.08 & 0 & 8.50 \\ 8.8 \\ \hline \overline{x} & -\frac{x}{x}}{\overline{x}} & -2.22 \\ \hline \overline{y} & -\frac{x}{x}}{\overline{y}} & -2.22 \\ \hline \overline{y} & -\frac{x}{x}}{\overline{y}} & -1.92 \\ \hline \overline{z} & -\frac{x}{x}}{\overline{y}} & -7.26 \\ \end{array} $	$x = \frac{x \cdot y x}{x \cdot y} = \frac{x \cdot y \cdot y}{x \cdot y} = \frac{x \cdot y}{x \cdot y} = x $	$x = \frac{x}{x} = $



39

۲.

\*

	CENTER OF	GRAVITY OF	SEAT ANI	OCCUPANT	
	Weight	x	Z	WX	WZ
Seat	118.8	-2.22	7.26	-264	862
Man	200	-9.00	7.8	-1800	1560
Totals	318.8			-2064	2422
	<u>المرتبطة التي محمد المرتبط الم</u>	$\bar{x} = -6.4$	18		
		ž = 7.6	50		
		<b>y</b> - 3.0	) ( <b>Ma</b> tima	ated)	
*Reference	ce Figure 6				

TABLE 5\*

THE REPORT OF A DESCRIPTION OF A DESCRIP

TABLE 6+

CENTER OF GRAVITY OF COMPLETE SEAT AND OCCUPANT

	Weight	x	2	WX	WZ
Bucket & Occupant	318.8	-6.48	7.60	-2064	2422
Support	42	0	-3.50	0	-147
Totals	360.8			-2064	2275
		$\vec{x} = -5.$	73		
		ž - 6.	3		
		<b>y</b> - 3.	20 (Esti	mated)	
* <b>Edferen</b> ce	Figure 6				

51

-2.5 Berlin

# UNIT SOLUTIONS



Figure 7. Reference Axes for Load Analysis.



 $P_x = -1000$  Pounds in X Direction



Figure 8. Geometry of Seat Bucket Loads

 $\sum M_{GH} = 0;$   $E_X + F_X = \frac{9000}{10} = 900$  Pounds  $\mathbf{E}_{\mathbf{X}} = \frac{6}{18} \times 900 = 300 \text{ Pounds}$ Assume  $F_{x} = 900 - 300 - 600$  Pounds  $\Sigma F_{X} = 0;$   $G_{X} + H_{X} = 100$  Pounds  $G_{\rm X} = \frac{6}{18} \times 100 = 33.3$  Pounds  $H_x = 66.7$  Pounds  $P_v = 1000$  Pounds in Y Direction  $\sum M_{\rm FH} = 0;$   $E_{\rm X} + G_{\rm X} = \frac{1000 \times 13.25}{18} = 736$  Pounds Assume 50% of  $M_{\rm FH}$  is reacted by  $E_{\rm X}$  and  $F_{\rm X}$ Then  $E_{X} = G_{X} = .5 \times 736 = 368$  Pounds  $\Sigma F_{\rm X} = 0;$   $F_{\rm X} = H_{\rm X} = -368$  Pounds  $\sum M_{x \in H} = 0; \quad x_{y} + F_{y} = -1000 \times \frac{9}{10} = -900 \text{ Pounds}$  $G_y + H_y = -100$  Pounds

P<sub>z</sub> = 1000 Pounds in 2 Direction

 $XM_{GH} = 0; \quad E_{X} + F_{X} = \frac{100 \times 13.25}{10} = 1325 \text{ Pounds}$ Assume  $E_{X} = \frac{6}{18} \times 1325 = 442 \text{ Pounds}$   $F_{X} = 883 \text{ Pounds}$   $F_{X} = 0; \quad G_{X} = -442 \text{ Pounds}$   $H_{X} = -883 \text{ Pounds}$  J = 1000 Pounds T = 1000 Pounds

**X** \*

 $1000(9) - 1000(12) + (G_y + H_y)(10) = 0$  $G_y + H_y = 300$  Pounds

 $\mathbf{x}\mathbf{F}_{y} = 0;$   $\mathbf{E}_{y} + \mathbf{F}_{y} = -300$  Pounds

1,00048

1

Crege Cre in

TABLE 7

					SEAT B	UCKET LO	ADS				1
Locet	ton (			P		F					5
Loadi	a.		×	Ъ. I	×	, ,	×	¥	Ħ	y**	N
	1000	-	300	0	600	0	33.3	0	66.7	0	0
1 4 2	1000		368	0	-368	006-	368	0	-368	-100	0
	1000		42	0	883	-600	-442	0	-883	600	1000
- - -	-143	60	4310	0	8620	0	479	0	958	0	0
	3350	1	1231	ð	-1231	-3020	1231	0	-1231	-335	0
	009	0	2650	0	5300	-3600	-2650	0	-5300	3600	6000
+ 1 A	¢,		5541	0	7399	-3020	1710	0	273	-335	0
+ * 1 •			6960	0	13920	-3600	-2171	¢	-1342	3600	0
+ 4	N 8		3881	0	4069	-6620	-1419	0	-6531	3265	6000
+ 5 X 6	ч ч +	D N	8191	0	12689	-6620	- 940	0	-5027	3265	6000
Maxin			13920	*	13920	0	1710	¥ ¥	1710	3600	6000
Minim			-1231	¥	-1231	-6620*	-6531	*	-6531	-335	0
4	Side	loads	Fv are	e shared	by <b>B</b> <sub>v</sub>						
**	Side	loads	Hy ar	e shared	by Gy						

1.11.1.1

. . . .

# Support Structure Unit Solution

(With Seat in Uppermost Position)













### UNIT SOLUTION

 $P_x = 1000$  Pounds in X Direction  $C_{x}' = \frac{8.2}{20.8}(974.4)$  $\Sigma M_{z}$ '  $\Theta$  D - 0 ;  $C_x' = 385$  Pounds  $D_{x}' = \frac{12.6}{20.8}(974.4)$ **Σμ<sub>z</sub>' α** c = 0 ;  $D_x' = 590$  Pounds  $\Sigma M_{CD} = 0$ ;  $A_{z}' + B_{z}' = \frac{-(10.64x222+21.22x974.4)}{18}$  $A_{g}' + B_{g}' = -1270$  Pounds  $A_{z}' = \frac{7.9}{20.2} \times -1270$ Skry  $A_{z}' = -497$  Pounds  $B_z' = -774$  Pounds  $\Sigma H_{x}' \in D = 0$ ; -497(20.5) + (774)(.3) + 222(8.2) + 20.8  $C_{z}' = 0$ C<sub>z</sub>' - 414 Pounds  $\Sigma M_{\mathbf{x}}' \bullet \mathbf{C} = \mathbf{0};$ -(497)(.3) - (-774)(20.5) - 222(12.6) - $20.8 D_{2}' = 0$  $D_{x}' = 626$  Pounds

# UNIT SOLUTION

 $P_y = 1000$  Pounds in Y Direction

$$\mathbb{E}M_{Z}' \in D$$
;  $C_{X}' = \frac{7.36 \times 1000}{30.5} = 354$  Pounds

 $D_{x}' = -354$  Pounds

$$\mathbf{z}\mathbf{F_y}' = 0$$
;  $\mathbf{A_y} = \mathbf{B_y} = 500$  Pounds

 $\Sigma M_{X}' = B = 0; A_{X}' = \frac{-31.32 \times 1000}{20.3} = -1050$  Pounde

47

).

 $P_{z}$  = 1000 Pounds in Z Direction  $C_{x}' = \frac{222x8.2}{20.8}$ **₹ M<sub>2</sub>' @ D - 0;**  $C_x' = 87.5$  Pounds  $D_x' = 222 - 87.5$ £7.' = 0;  $D_{x}' = 134.5$  Pounds  $= N_{CD} = 0; A_{z}' + B_{z}' = \frac{974.4 \times 10.64 - 222 \times 21.22}{100}$ 18  $A_{z}' + B_{z}' = 313$  Pounds  $A_{z}' = \frac{(7.9)(313)}{20.2}$ Say Az' = 122 Pounds B. ' = 191 Pounds 122(20.5)+191(.3)+(-974.4)(8.2)+ $20.8 C_{z}' = 0$  $C_{\pi}' = 26!$  Pounds - 0; -(122)(.3)-191(20,5)-(-074.4)(12.6)-20.8 D<sub>z</sub>' = 0 D<sub>z</sub>" = 398 Pounds

TABLE 8

FLOOR ATTACHMENT LOADS

and the second second

• •

	"Londing	<b>h</b>	N 1			×	N	×	N
H	P <sub>2</sub> = - 1000	•	- 497		+174 -	385	414	590	626
<b>FI</b>	Py = 1000	- 500	- 1060	- 500	- 1050	354	0	- 354	0
63	Pg = - 1000	0	123	•	191	87.5	261	134.5	398
	P <sub>x</sub> = -16250	0	- 8060	0	-12560	6260	6730	<b>96</b> 00	10180
iÔ	P <sub>w</sub> = 3800	-1900	- 3000	-1909	+ 3990	1345	¢	-1345	0
10	Pg = - 8030	•		0	1532	704	2005	1080	3200
•	<b>P</b> <sub>x</sub> +P <sub>y</sub> (4+5)	0062-	-13060	-1900	- 8570	7605	6730	82155	03101
	Px+Px (4+6)		1000		-11036	6964	8825	10680	13380
•	Py+Ps (5+8)	-1900	- 3010	-1900	+ 5532	2019	2095	- 265	3200
0	P_X+P_y+P_E (4+5+6)	-1900	-11070	-1900	- 7056		6625	9335	13380
11	Harian.	0			5622	<b>8</b> 30 <b>8</b>		10680	13380
8	<b>State</b>		09061					-1345	0
	Matin Per P.					10690	13380	10630	1338
					-19660	-1345		-1345	•

ية: ولو

The second s

•

...

...........

,

### UPPER TORSO RESTRAINT; 45G LOAD IN X-DIRECTION

### Chest Strap Plus Shoulder Harness

Sa.y



Figure 10. Upper Torso Restraint Londs from Chest Strap and Shoulder Harness.

0 A<sub>T</sub> 1017 + 712 + 2820 - 8 - C = 0Z P<sub>x</sub> 0; . C + 8 = 4549A\_ - .88 0; ٤7, **≈**M<sub>A</sub> = 0;  $16.5 \times 712 = 11,750$  $12.6 \times 1017 = 12,800$  $7,1 \times 2820 = 20,000$ 44,550 + 6(.88) - 17.508 - 9C = 0C + 1.418 - 4960Combining:

### Shoulder Harness Only



Û

### Figure 11. Upper Torso Mestraint Loads from Shoulder Marness Only.

۳. MA	0;	44,550 +	6(.85)	-	17.508	- 0	
	.,	1	1.4		12.708	- 44,550 Pe	made
			· · ·		1 - E - E -	- 3590 Pc	winds
٤1 <u>,</u>	0;						n an trainn an trainn Trainn an trainn Trainn an trainn
					A_	- 3830 Pc	mada

### Upper Torso Weight = 101 Pounds Spinal Compression = 2820 Pounds

Load is induced by 45g forward load. Equivalent vertical acceleration is:

 $a' = \frac{P}{W}$   $a' = \frac{2820}{101}$  a' = 26g

Applied vertical loads and induced spinal leads must be superimposed: With an estimated 20g vertical load (safe load per Reference 5), and a 28g induced load, then the effective total spinal load is 48g. A load of this magnitude is not tolerable per Reference 5.

# LOWER TORSO RESTRAINT; 45G LOAD IN X-DIRECTION

.



Figure 12. Lower Torso Restraint Loads.

٤¥ <sub>B</sub>	-	0;	-5 V + 4455 (1.5) + 890 (6)	-	0
			5 V	-	11,000
			v	-	2200
ΣF <sub>x</sub>	-	0;	86 L - V + .15 P + 4455		0
			86 L + .15 P		2255
٤ı,	-	0;	50 L + .99 P	-	0
			50 L + .09 P	-	-1310
			Combining: .90 P	-	1310
			P	-	1455
			L	-	2880

### APPENDIX II

### STRESS ANALYSIS

The loads derived in Appendix I were applied to the detail components, and stresses were determined. Typical examples of the procedures used are included in this section.

The objective of this seat design was a ductile structure which would sustain the applied loads. These loads are the design ultimate loads developed in Appendix I with no superimposed safety factor.

Stress levels are intentionally high to minimize weight. This approach is justified because higher than normal ultimate stresses are predicted with the dynamic load application and because many of the critical components are relieved as the seat travels through its energy-absorption stroke.

Routine procedures were used and simplifying assumptions a used in redundant situations are noted in the text.

DETAIL STRESS ANALYSIS

### Lap Belt

Although lap belt calculated loads are relatively low (reference Page 52), conservative loads will be applied.



Figure 13. Lap Belt Attachment Details.

1

### Belt Attaching Bolt

2000 pounds per lug

Bolt shear allowable = 3680 pounds (Reference 1) Margin of Safety (N.S.) = .84

Bearing in Lug:

N.S.		.255	(Reference	1)
F <sub>bru</sub>	-	251,000	p.s.i.	
f <sub>br</sub>	9	200,000	<b>p.s.i.</b>	
<sup>f</sup> br	-	<u>2000</u> .25 x .0	4	

.....

Shear of Lug:

f <sub>S</sub>	-	2000		
		2 x .37 x .04		
f <sub>s</sub>	-	67,500 p.s.i.		
F <sub>su</sub>	-	82,000 p.s.i.	(Reference	1)
M.S.	-	.213		

Lap Belt Tie

.



Figure 14. Lap Belt Attachment Plate.

Seat Lug Bolt Shear Load = 3000 pounds Ps all = 3680 pounds (keference 1) N.S. = .225

Bearing in Seat Lug

$$f_{br} = \frac{3000}{.25 \times .08}$$
  

$$f_{br} = 150,000 \text{ p.s.i.}$$
  

$$F_{bru} = 251,000 \text{ p.s.i.} (Reference 1)$$
  

$$M.S. = .67$$



Figure 15. Chest Belt Loading.

Conservatively, the side load is assumed to be 80% of upper body (head, neck, arms, upper torso) side load.

> Upper body weight = 101 pounds Side load = 101 x 10.5g

Belt side load = 850 pounds



Belt end load = 1960 pounds

This belt is fabricated to details of Specification MIL-B-6703 and has a breaking strength of 4500 pounds loop load.

Belt M.S. = 
$$\frac{4500 \text{ x}}{1960} - 1 = .15$$

Bending in Seat Upper Cross Beam

4.



Figure 16. Seat Upper Cross Beam Loading.

ł

	M	-	2000(7)
	M	-	14,000 inch pounds
	fc	-	<u>14,000(.88</u> ) .40
	fc	-	30,800 p.s.i.
F <sub>cr</sub> based on	b/t	-	8
	Fcr	18	55,000 p.s.i.
	R <sub>c</sub>		.58
	ft	-	$\frac{14,000(1.52)}{.40}$
	ft	-	53,200 p.s.i.
	Ftu	-	77,000 p.s.i.
	Rt	-	.69

# Shear in Seat Upper Cross Beam

$$V = 2000 \text{ pounds}$$
Area = .063 x 1.75  
Area = .110  
f<sub>s</sub> = 18,200 p.s.i.  
F<sub>s</sub> = 30,000 p.s.i. (Reference 13  
Page 410)  
R<sub>s</sub> =  $\frac{18,200}{30,000}$ 

I

1

M.S. - 
$$\frac{1}{\sqrt{.603^2 + .69^2}}$$
 -1

M.S. - 
$$\frac{1}{\sqrt{.363 + .476}}$$
 -1

M.S. - .092

Attachment of Upper Beam to Seat Side



Figure 17. Attachment of Seat Upper Beam to Seat Side.

Assume Shear = 2666 pounds (2/3 shoulder harness capacity)

Assume 1000 pound/fastener shear load

Moment in joint:

M = .5(2666) = 1333 in. lb.

Couple to React Moment:

$$C = \frac{M}{1.7} = \frac{1333 \text{ in. lb.}}{1.7 \text{ in.}}$$

C = 785 pounds

Load on forward fastener:



Resultant shear = 1270 pounds

Shear Allowable = 2000 pounds (Reference 1) Bearing Allowable

$$F_{bru} = 14,500 \text{ p.s.i.} (\text{Reference 1})$$

$$P_{br} = 14,500(.19)(.063)$$

$$P_{br} = 1735 \text{ pounds}$$

$$M.S. = \frac{1735}{1270} -1$$

$$M.S. = .365$$

2

ł.

山田市 子 あつたる

### Seat Bottom Bending Strength

キューアアノテアンション

and a substantial state of

7

The material is composite armor. The backing material is .44 inch thick.

The properties of this backing material, supplied by the manufacturer, are as follows:

Bending Modulus	25,000 p.s.i.
Modulus of Elasticity in Bending	1,700,000 p.s.i.
Compressive Strength (Edgewise)	12,600 р.в.і.
Tensile Strength	33,000 p.s.i.

These values are in general agreement with low strength fiberglass-epoxy laminates of MIL-HDBK-17.

Primary loading is the normal load from the occupant whose weight is 80 percent effective for vertical accelerations.

P = .8 x 200 x 25g

P = 4000 pounds

Add load induced by lateral load = 1455 pounds (Reference Page 52)

5455 pounds



Figure 18. Seat Bottom Loading.



Figure 19. Seat Bottom Load Distribution.

Deflection under Load and Bending Stress: (From reference 14, Page 206)

$$Y_{max} = .140 - \frac{Wb^4}{Et^3}$$

$$Y_{max} = \frac{.140 \times 5455 \ (16)^2}{1,700,000 \ (.44)^3}$$

$$Y_{max} = 1.39$$
 inches  
Max S =  $\frac{.67 \text{ Wb}^2}{.67 \text{ Wb}^2}$ 

t = .44 (backing only)

$$Max S = \frac{.67 \times 5455}{.44^2}$$

Max S = 18,900 p.s.i.

$$F_b = 25,000$$
  
M.S. =  $\frac{25,000}{18,900} - 1 = .32$ 

Seat Bottom Connections

Screws:

Say that the position of the man applies one-half of the 5455-pound load to a 9-inch width of edge connection.

Unit load along edge =  $\frac{.5 \times 5455}{.9}$  = 330 pounds per inch

At 1.5-inch spacing,

Load per screw = 500 pounds

**Connecting Angles:** 



Bearing on Sheet:

$$f_{\rm br} = \frac{P}{A}$$

$$f_{\rm br} = \frac{500}{.156(.190)}$$

$$f_{\rm br} = 16,500 \, {\rm p.s.i.}$$

# N.S. is ample.

Seat to Angle Fasteners:

AN 525-10 screws Load = 500 pounds (tension)  $P_t = 2210$  pounds (Reference 1) M.S. =  $\frac{2210}{500} - 1$ M.S. = 3.42 1.11.11.11

1. Succession

Seat Bucket Upper Rollers

efe.

1

The critical load in X direction is 13,920 pounds (reference Table 7).

Two rollers are used at each roller bracket. The bracket is designed with a single staching bolt which allows bracket rotation to equalize the roller loads.

Roller load =  $\frac{13,920}{2}$ Roller load = 6960 pounds Use McGill Camrol CFH-1 $\frac{1}{8}$ S Aircraft Static Capacity = 9180 pounds (reference McGill catalog) N.S. =  $\frac{9180}{6960}$  -1 N.S. = .315 Although loading is extreme, rolling capability for three

Although loading is extreme, rolling capability for three revolutions (total travel under load) is predicted.

Track Contact Stress:

Steel Roller 7075-T652 Track Roller Load = 6960 pounds Roller Width = .62 Unit Roller Load p =  $\frac{6960}{.62}$ p = 11,210 pounds per inch

From reference 14, Page 288, stress due to pressure between elastic bodies, Case 4 cylinder on flat plate:

Max S<sub>c</sub> = .798 
$$\sqrt{\frac{p}{D \frac{1-\gamma^2}{E_1} + \frac{1-\gamma^2}{E_2}}}$$

$$S_{c} = .798 \sqrt{\frac{11,210}{1.125 \frac{1-(.26)^{2}}{29 \times 10^{6}} + \frac{1-(.36)^{2}}{10 \times 10^{6}}}$$

$$S_{c} = .798 \times \frac{10^{4}}{3.452} \sqrt{\frac{11,210}{1.125}}$$

$$s_c = 231,000 \text{ p.s.i.}$$

This is high for material with  $F_{\rm bru}$  equaling 131,000 p.s.i., but some yielding will enlarge the bearing contact area, reduce the contact stress and permit survival.
Track Flange Bending

For each upper roller, P = 6960 pounds (reference Page 66)



7075 T652 Aluminum Alloy

Figure 21. Track Flange Loading.

Say b effective = 1.25 inches M = .44(6960) = 3060 inch pounds  $f_b = \frac{6M}{bt^2}$   $f_b = \frac{6(3060)}{1.25(.50)^2}$   $f_b = 59,000 \text{ p.s.i.}$   $F_{tu} = 70,000 \text{ p.s.i.}$  (Reference 1)  $F_b = 1.25 (70,000)$   $F_b = 87,500 \text{ p.s.i.}$  $R_b = .675$  ł

Upper Roller Bracket Loading

From Table 7, the loads in the area of the upper roller brackets are shown below:

Total side load = 6620 pounds

Apply 60 percent of side load to critical side.



Figure 22. Seat Upper Roller Bracket Loading.

Calculate P and  $P_x$  and  $P_y$ : Say AC is free body, Z XA 0 8191(.7) - 2650 5.8 + 5.06P 0 5.06 P 9960 1908 Tension P .432 P P., 823 pounds .904 P 1720 pounds

Calculate Q and  $Q_{x}$  and  $Q_{y}$ .

ţ.

Say BD is free body;  $\Sigma M_B = 0$ -12,869(.7) - 3970(5.8) + 5.06Q = 0 5.06Q = +32,010 Q = 6340 pounds compression  $Q_x = .432 Q$   $Q_x = 2735 pounds$   $Q_y = .904 Q$  $Q_y = 5720 pounds$ 

Calculate A<sub>y</sub>:

(AC is free body)  $\Sigma M_{C} = 0$ -2650 x .2 + 8191(.7) - 5.6 A<sub>y</sub> = 0 5.6 A<sub>y</sub> = 5190 A<sub>y</sub> = 926 pounds

Calculate By:

(BD is free body)  $\Sigma M_D = 0$ -12,869(.7) -3970(.2) + 5.6 B<sub>y</sub> = 0 5.6 B<sub>y</sub> = 9804 B<sub>y</sub> = 1752 pounds



Seat Back Loads due to Energy Absorber Loads

сâ,

Loads on Back at Level of Upper Rollers





$$\Sigma F_{y} = 0$$

$$-926 - 1720 - 5720 + 1752 + S = 0$$

$$S = 6614 \text{ pounds}$$

$$\Sigma M_{A} = 0$$

$$-1720(3.35) - 823(4.7) + 1320(817) + 2735(12.7)$$

$$-5720(3.35) - 1740R_{B} + 6614(4.00) = 0$$

$$17.4 R_{B} = 43,850$$

$$R_{B} = 2520 \text{ pounds}$$
Bending at C;
$$M = 1752(3.35) + 2520(4.70)$$

$$M = 17,710 \text{ inch-pounds}$$



Check Back Punel and Rib for Bending

Figure 25. Bending of Seat Back and Reinforcing Rib.

1

Assume rib and back bend independently with load sharing in proportion to relative stiffness:

E fiberglass = 1,700,000

**E** aluminum - 10,500,000

Say I of both fiberglass and 2024 reinforcing rib are equal for bending about Z axis:

Fiberglass carries 13.9% of load.

Aluminum alloy rib carries 86.1% of load bending stresses in rib:

M = 17,710 inch-pounds.861 M = 15,250 inch-pounds  $f_{b} = \frac{6(15,330)}{4.50(.5)^{2}}$ 

 $f_{b} = 81,400 \text{ p.e.i.}$   $F_{b} = 1.25 F_{tu}$  $F_{b} = 81,300 \text{ p.s.i.}$ 

Slight negative margin is compensated by beneficial effect of composite beam action which was conservatively neglected.

Bending stress in fiberglass lawinate:

.139 M = 2470 inch-pounds effective width = 5.2 inches  $f_b = \frac{6(2470)}{5.2(.44)^2}$  $f_b = 14,800 \text{ p.s.i.}$ 

## Upper Roller Fitting

Conservatively, say socket action of roller shaft reacts overhang moment.



Figure 26. Upper Roller Fitting.

Overhang moment:

**M = .35 (6960)** 

M = 2440 inch-pounds

By the use of Reference 19, the socket stresses may be solved as follows:

- M = 2440 inch-pounds
   S = 6960 pounds
   L = .50 inch
- $t_1 = .44$  inch

$$t_2 = .58$$
  
 $\frac{M}{SL} = \frac{2440}{6960(.5)}$   
 $\frac{M}{SL} = .70$ 

Maximum unit loads:

K<sub>1</sub> = 8.20 (Reference 19)

$$W_1 = \frac{K_1 S}{L}$$
  
 $W_1 = \frac{8.20 \times 6960}{.50}$   
 $W_1 = 114,000$  pounds per inch

Bearing in socket:

$$f_{br} = \frac{W}{D}$$

$$f_{br} = \frac{114,000}{.625}$$

$$f_{br} = 182,500 \text{ p.s.i.}$$

$$F_{bru} = 219,000 \text{ p.s.i.}$$

$$M.S. = .20$$

Tension in fitting due to socket load:

$$f_{t} = \frac{W}{2t_{1}}$$

$$f_{t} = \frac{114,000}{.88}$$

$$f_{t} = 129,300 \text{ p.s.l.}$$

$$F_{tu} = 150,000 \text{ p.s.l.}$$

$$W.S. = .16$$

Shear in fitting due to socket load:

$$f_{s} = \frac{W}{2t_{2}}$$

$$f_{s} = \frac{114,000}{2(.58)}$$

$$f_{s} = 98,500 \text{ p.s.1.}$$

$$F_{su} = 95,000 \text{ p.s.1.}$$

$$M.S. = -.035$$

Clamp-up of the roller stud will relieve the conservative socket load, and fitting is expected to sustain the applied loads.



P = 15,604

Figure 27. Upper Roller Fitting Loading.

The moment at the main bolt due to the offset roller load is transferred by bearing of the bolt in the seat side, clamp-up of the main bolt, and by secondary bending of the fitting lugs.

Say that the moment transferred in the joint is 2000 inchpounds. Balance the seat side frame:



$$M_{P_2} = 1752(3.70) - 1.50 P_1 - 2000$$
  
 $P_1 = 3000 \text{ pounds}$ 

ster attende i alla sulla in

・ふから



Figure 29. Upper Roller Fitting Lug Loading.

Say that 3000-pound shear is divided between lugs by stiffness ratio

at C t = .200  

$$t^3$$
 = .008  
at D t = .125  
 $t^3$  = .00195  
Shear at C =  $\frac{.008}{.006 + .00195}$  (3000)  
Shear at C = .2420

Neglecting fixity; Moment

r and rotation of reality

ŝ

ļ

Moment at C = 1.75(2420)

- M = 4230 inch-pounds
- $f_{b} = \frac{6 (4230)}{3.3(.20)^2}$
- $f_{b} = 192,000 \text{ p.s.i.}$
- F<sub>tu</sub> 150,000 p.s.i. (Reference 1)
- F<sub>b</sub> = 1.25(150,000) (Reference 1)
- $F_{\rm b} = 187,500 \text{ p.s.i.}$

I

 $R_{b} = 1.023$ 

Load in inboard lug due to primary bending and direct tension:

	P =	$\frac{15,604}{2}$ - 3700
	· P =	7802 - 3700
	P =	4102 pounds tension
Tension stress in lug:	f <sub>t</sub> -	<u>4102</u> ,66
	f <sub>t</sub> -	6240 p.s.i.
	R <sub>t</sub> -	<u>6240</u> 150,000
	R <sub>t</sub> -	.0415
	$R_b + R_t =$	1.064

Beam shear in lug:

$$f_{g} = \frac{2420}{3.3(.20)}$$

$$f_{g} = 3660 \text{ p.s.i.}$$

$$F_{gu} = 95,000 \text{ p.s.i.} (\text{Reference 1})$$

$$R_{g} = .0385$$

$$M.S. = \frac{1}{\sqrt{1.064^{2} + .039^{2}}} - 1$$

. 2

M.S. = -.06

This margin is considered adequate because the major load (bending) is based on conservative moment distribution.

Using the same methods as above, the margin of safety at point D was calculated to be a noncritical +0.50.

## Seat Side Frame

1

÷

4

This frame was checked for the load condition  $P_x : P_z$  (reference Table 6). Loading was established by the following factors:

1. Weights are taken from Table 3, Page 37.

2. Load factors, which agree with the applied loads of Table 6, are 45g in x direction and 21.5g in z direction.

3. The lateral position of the center of gravity of the seat, with occupant, was conservatively assumed to be 3 inches from the centerline of the seat. To match this assumption, 70 percent of the occupant's loads were applied to the critical frame.

4. Loads in the x direction due to the occupant were proportioned in general agreement with the chest belt and shoulder harness loads (reference Page 50) and with seat belt and inverted wee belt loads (reference Page 52). Small arbitrary adjustments were made to distribute the loads in accordance with the estimated center of gravity of the occupant.

5. The load in the z direction due to the occupant was applied as a concentrated load.

6. The shoulder shield loads and the torso shield loads were applied by transferring the loads to support points on the frame.

7. The loads in x direction due to the seat components and seat back were considered to be uniformly distributed along the height of the seat.

8. The vertical load on the convex back panel of the seat causes a moment about the y axis. This moment is transferred to the seat frame by the frame-to-back connecting angles. For simplicity, this moment is shown as a couple with concentrated loads.



Figure 30. Seat Side Frame Loading.

## Side Frame Bending at A-A



Axial Load at A-A:

Axial load =  $+4000 - 298 - 269 - 634(\frac{15.5}{29})$ 

Axial load = 3089 pounds (Tension)  $\hat{r}_t = \frac{p}{A}$   $\hat{r}_t = \frac{3089}{1.17}$  $\hat{r}_t = 2730 \text{ p.s.i.}$ 

Combining Bending and Axial Stresses:

$$f_{c} = 32,000 - 2730$$

$$f_{c} = 29,270 \text{ p.e.i.}$$

$$f_{t} = 36,400 + 2730$$

$$f_{t} = 39,130 \text{ p.e.i.}$$

$$F_{tu} = 64,000 \text{ p.e.i.} \text{ (Reference 1)}$$

$$R_{t} = .612$$

· · \*\* \*\*\*\*\*\*\*\*\*\*\*\*\*

Shear at A-A:

$$V = 740 + 1200 + 621 + 1976 + 493$$

$$V = 5030 \text{ pounds}$$

$$f_{g} = \frac{5030}{6(.075)}$$

$$f_{g} = 12,900 \text{ p.s.i.}$$

$$F_{gu} = 27,000 \text{ p.s.i.} \text{ (Reference 13, Page 410)}$$

$$R_{g} = .478$$

$$W.S. = \frac{1}{\sqrt{.612^{2} + .478^{2}}} -1$$

$$W.S. = .28$$



ų.

÷ Ŷ.

Roller Loads (Reference Table 7.)

Floor Loads (Reference Table 8.)



I = 7.17 inches<sup>4</sup>

Neutral Axis

Material: 7075-T6 Bar and 7075-T6 Alclad Webs

**...** 



The critical section for bending and shear is Section A-A where the track web has been out back and the beam depth is still relatively short.

Two conditions are checked: One with the seat in the uppermost position and the second with the seat 2.5 inches below the uppermost position. The first condition results in maximum moment and reduced shear on the critical section. The second condition applies maximum shear and reduced bending moment to the critical section:

For Uppermost Position:

M = -12.5(13,920) + 2.5(4342) M = 174,200 + 10,820 M = -163,380  $f_{b} = \frac{Mc}{I}$   $f_{b} = \frac{163,390(2.67)}{7.17}$   $f_{b} = 62,600 \text{ p.s.i.}$   $F_{tu} = 77,000 \text{ p.s.i.}$   $R_{b} = .814$ 

Shear and Torsion:

Conservatively neglecting shear reduction due to beam cap taper:

(Reference 1)

V - 13920 - 4342

V = 9578 pounds

For shear and torsion, the side frame section is idealized as a constant section box.



¢,

- 24

Figure 32. Side Bean Torque Box.

Area of box:

÷

とき、 書からの見かる ないたいいの見

A = 2.40(.84) + 2.50(1.01)

A = 4.55 square inches

Average wall thicknoss:



$$\overline{t}$$
 = .127  
A = 1.48 square inches

Direct Shear:

$$f_s = \frac{9578}{1.48}$$
  
 $f_s = 6460 \text{ p.s.i}$ 

forsion:

$$f_{s} = \frac{T}{2At}$$

$$f_{s} = \frac{9578(1.00)}{2(4.55).127}$$

The critical web is inboard and the shear stresses combine:

$$f_s = 6460 + 8290$$
  
 $f_s = 14,750$  p.s.i.  
 $F_s = 33,000$  p.s.i. (Reference 13, Page 410)  
 $R_s = .447$ 

Combining Stress Ratios:

.

M.S. = 
$$\frac{1}{\sqrt{.814^2 + .447^2}}$$
 -1  
M.S. ~ .075

With the seat 2.5 inches below the uppermost position: Bending Stress:

ĩ

ł.

٩,

Ë

(Reference 1)

$$M = 13,920(10)$$

$$M = 13,920 \text{ inch-pounds}$$

$$f_{b} = \frac{Mc}{I}$$

$$f_{b} = \frac{13,920(2.67)}{7.17}$$

$$f_{b} = 51,900 \text{ p.s.i.}$$

$$R_{b} = \frac{51,900}{77,000}$$

$$R_{b} = .675$$

Shear Stress (direct):

V = 13,920 pounds  $f_{s} = \frac{13,920}{1.48}$  $f_{s} = 9420$  p.s.1.

Shear Stress (torsion):

$$f_{B} = \frac{T}{2At}$$

$$f_{B} = \frac{13,920(1.0)}{2(4.55)(.127)}$$

$$f_{B} = 12,060 \text{ p.s.i.}$$

F<sub>s</sub> = 33,000 p.s.i.

(Reference 13, Page 410)

ł

- $R_{\oplus} = \frac{21,480}{33,000}$
- $R_{\pm} = .652$
- M.S. =  $\frac{1}{\sqrt{.675^2 + .652^2}}$  -1

M.S. = .065