

U. S. ARMY

Technical Memorandum 9-65

TARGET DETECTION USING BLACK-AND-WHITE TELEVISION STUDY I: THE EFFECTS OF RESOLUTION DEGRADATION ON TARGET DETECTION

Lynn C. Oatman

July 1965

AMCMS Code 5011.11.841

HUMAN ENGINEERING LABORATORIES



ABERDEEN PROVING GROUND,
MARYLAND

CLEARANCE			
FOR			
CLASSIFICATION			
1.00	0.50	22	AS

Code 1

Distribution of this document is unlimited.

**BLANK PAGES
IN THIS
DOCUMENT
WERE NOT
FILMED**

TARGET DETECTION USING BLACK-AND-WHITE TELEVISION
STUDY I: THE EFFECTS OF RESOLUTION DEGRADATION
ON TARGET DETECTION


Lynn C. Oatman

Technical Assistance

William T. Nemeth
Raymond F. Blackmer

July 1965

APPROVED


JOHN D. WEISZ

Technical Director
Human Engineering Laboratories

U. S. ARMY HUMAN ENGINEERING LABORATORIES
Aberdeen Proving Ground, Maryland

ABSTRACT

The probability of detecting an M-48 tank at four different levels of television (TV) resolution (800, 600, 400, and 300 lines) was investigated on a black-and-white closed-circuit TV system.

The four levels of TV resolution were presented to 16 subjects, who were asked to indicate in which one of nine areas the tank appeared on the TV screen.

The data indicated that subjects performed about equally well at the 800, 600, and 400 levels of resolution; however, their performance was significantly poorer at the 300 level of resolution. The tank's location on the TV screen was an important factor in the probability of target detection, but was confounded with other variables.

CONTENTS

ABSTRACT	iii
INTRODUCTION	1
METHOD	3
Subjects	3
Apparatus	3
Procedure	4
RESULTS	5
DISCUSSION	7
SUMMARY	8
REFERENCES	13
APPENDIX	15
FIGURES	
1. Arrangement of Experimental Test and Control Rooms	2
2. Percent Correct Detections as a Function of Resolution and Subjects	9
3. Mean Response Time as a Function of Resolution and Subjects	10
4. Mean Response Time as a Function of Resolution and Locations	11
5. Percent Correct Detections as a Function of Locations	12

TABLES

1. Means and Standard Deviations of Correct Detection Scores as a Function of Resolution	5
2. Means and Standard Deviations of Response Times as a Function of Resolution	6
3. Summary of Analysis of Variance of Correct Detection Scores	6
4. Summary of Analysis of Variance of Response Times	7

TARGET DETECTION USING BLACK-AND-WHITE TELEVISION STUDY I: THE EFFECTS OF RESOLUTION DEGRADATION ON TARGET DETECTION


INTRODUCTION

Television (TV) is becoming an important means of presenting visual information to man in a variety of military applications. Television is currently being used for many different military purposes. For example, TV has been used to present visual information to operators of remote-control combat vehicles (5). In another study (6), men have driven tanks using a TV display as the sole source of visual information. Television has also been used in lunar and planetary explorations and in satellites that provide televised reconnaissance information. In military control centers (2), TV displays are used for more effective weapon system deployment and damage assessment. The increasing use of TV in modern weapon and surveillance systems makes more stringent demands on the operators' ability to accurately interpret TV displays.

In some military applications of TV, the operator's task would be to detect and identify targets on the TV display. In a recent article, Gordon (4) has pointed out that target detection and target identification are two important aspects of the combat situation. Target detection ordinarily refers to an observer's ability to determine whether a man-made object is present or absent in a place where such objects are not usually seen. Target identification, on the other hand, refers to the observer's ability to characterize or specify the object he has detected.

Little attention has been given to the extent to which TV resolution affects the probability of target detection. In a preliminary study, Oatman (7) compared target-location scores from a projected-slide display and a TV display. Performance was superior with the slide display, which was interpreted as due to better resolution. Freeberg (3) found that reducing information on a video screen increased form thresholds significantly. In a more recent study, Shanahan (8) found that reducing the bandwidth of a closed-circuit TV system likewise reduced the subjects' ability to identify targets.

The present study attempted to measure the effects of resolution on the probability of detecting targets on a black-and-white closed-circuit TV system.



- 1. TV Camera
- 2. Foto-Video F-101A TV Light Box
- 3. Hunter Interval Timer
- 4. Standard Timer
- 5. Intercom
- 6. Response Panel
- 7. 14-inch TV Monitor

Fig. 1. ARRANGEMENT OF EXPERIMENTAL TEST AND CONTROL ROOMS

METHOD

Subjects

Sixteen male enlisted men from the U. S. Army served as subjects (Ss). The Ss' ages ranged from 18 to 26. The Ss' vision (corrected or uncorrected) ranged from 20/20 to 20/13 as measured by Ortho-Rater tests.

Apparatus

Television

The equipment for the TV presentation was a General Precision Laboratories P.D.-601 closed-circuit high-resolution TV system. The TV camera in a control room fed radio-frequency (RF) signals to a 14-inch TV monitor in an adjacent test room. A Foto-Video F-101A light box, holding one 8" by 10" positive-transparency photograph, was placed in front of the TV camera.

The TV monitor in the test room was divided into nine equal areas by black thread. The Ss had a response panel with nine buttons, which was similarly divided into nine areas by thin strips of masking tape. Each button on the response panel represented one of the areas on the TV monitor. The control room contained a similar panel to display the Ss' responses.

The amount of time that a picture remained on the TV monitor was controlled by a Hunter interval timer, model 100-C, series D. A Standard electric timer recorded the Ss' response times. There was an intercom to provide communication between the test and control rooms. Figure 1 shows the experimental arrangements.

Picture Degradation

Freeberg (3) pointed out that bandwidth can be linearly related to the number of scan lines per frame. However, in this experiment, the number of scan lines per frame in the actual displayed TV picture remained at 875 lines. The picture was degraded by an appropriate reduction in bandwidth which, in turn, reduced the information in a horizontal scan line. Thus the amount of information within a scan line was decreased, but there was reduction only in the horizontal dimension. To obtain four levels of picture degradation (800, 600, 400, and 300, as measured with a standard RETMA TV test pattern), four different values of capacitance to ground were inserted into the coaxial cable between TV camera and monitor. The capacitance to ground, in conjunction with other elements

in the TV circuit, acted as a low-pass filter. The bandwidth was reduced to 20.0, 6.0, 1.7, and 1 megacycles, which correspond to the 800, 600, 400, and 300 levels of resolution respectively. The amount of picture degradation (800, 600, 400, and 300) was measured with a standard RETMA TV test pattern, and these levels refer to resolution in the center of the TV screen.

Procedure

After S was checked for visual acuity, he was seated approximately 72 inches from the TV screen, instructed, and given the response panel. Each S saw ten 8" x 10" photographs, nine showing an M-48 tank (one in each area) against a homogeneous background, and one showing only the background. The tank was 3/8" long and 3/16" wide, subtending a visual angle of 18 minutes.

Every S saw the ten photographs four times, at each of the four levels of picture degradation. The photographs were shown in a random order, identical for all Ss.

To offset practice effects, the four levels of resolution were presented in the same order (800, 600, 400, and 300) to all Ss, but each S began with the level following the one at which the preceding S began. For example, the first S observed the photographs at the 800, 600, 400, and 300 levels of resolution; the next S observed them at the 600, 400, 300, and 800 levels; the third began with the 400 level; and so on, until all Ss had observed the photographs at all levels. Since the Ss were initially selected at random, assigning them to groups by this procedure gave random groups.

The TV monitor was always illuminated. When the experimenter started the interval timer, the picture was transmitted from the control room to the Ss' monitor in the test room for a 0.5-second exposure.

If the S saw no target on the screen (and there was none when the blank slide was presented), he pushed any two buttons.

RESULTS

Two aspects of the S_s ' performance were measured: response times and detections. Response time was defined as the time between the target's appearance on the TV screen and the S 's response. A detection error occurred when S could not locate the target on the TV screen. In scoring, one point was allowed for each correct detection.

A constant value of one was added to all treatment-by-subject cells in order to avoid blank cells in the analysis. This procedure raised the means by one but did not affect the variance.

Tables 1 and 2 present the means and standard deviations for the correct detection scores and response times, as a function of picture degradation. These means were analyzed with Duncan's (1) multiple-range test for correlated means. Detection scores on the 300-level-resolution TV display differed significantly ($p < .01$) from those on the 400-, 600-, and 800-level-resolution TV displays. However, the 400-, 600-, and 800-level-resolution TV displays did not differ significantly on detection scores. With response time, none of the resolutions differed significantly from the others.

TABLE 1

Means and Standard Deviations of Correct Detection Scores
as a Function of Resolution
(N = 144/cell)

	Resolution			
	800	600	400	300
Mean	3.41	3.25	3.23	2.78
Standard Deviation	0.83	0.96	1.02	1.14

TABLE 2

Means and Standard Deviations of Response Times
as a Function of Resolution
(N = 144/cell)

	Resolution			
	800	600	400	300
Mean	1.55	1.55	1.53	1.83
Standard Deviation	0.51	0.76	0.47	0.78

Tables 3 and 4 give summaries of the analyses of variance of detection scores and response times. With correct detection scores, the main variables of resolution and locations were significant ($p < .01$). However, the locations variable was the only significant main effect ($p < .01$) for response times. All of the interactions were significant ($p < .01$) for the response times; but only two interactions, resolution by subjects and locations by subjects, were significant ($p < .01$) for the detection scores.

TABLE 3

Summary of Analysis of Variance of Correct Detection Scores

Source	df	Sum of Squares	Mean Square	F
Resolutions (A)	3	31.07	10.36	6.11**
Locations (B)	8	63.36	7.92	11.98**
Subjects (C)	15	194.69	12.98	--
A x B	24	13.04	0.54	1.23
A x C	45	76.23	1.69	3.84**
B x C	120	79.36	0.66	1.50**
A x B x C	360	158.91	0.44	--
Total	575	616.66		

** $p < .01$

TABLE 4

Summary of Analysis of Variance of Response Times

Source	df	Sum of Squares	Mean Square	F
Resolutions (A)	3	10.31	3.43	2.43
Locations (B)	8	7.12	0.89	6.04**
Subjects (C)	15	49.59	3.30	--
A x B	24	6.47	0.26	5.67**
A x C	45	63.55	1.41	29.73**
B x C	120	17.66	0.14	3.09**
A x B x C	360	17.10	0.04	--
Total	575	171.80		

** $p < .01$

DISCUSSION

The results show that reducing the bandwidth reduces target-detection probability significantly. Although it was expected that reductions in bandwidth and/or resolution would affect the probability of target detection, it is interesting that the relationship between resolution and target detection probability is nonlinear. The data indicate a significant difference between 300 and 400; however, there were no significant differences between the 400, 600, and 800 levels of resolution. One factor which may influence the obtained relationship is the fact that the resolution was reduced only in the horizontal plane. It seems likely that the \bar{S}_s ' equivalent performance on the 400, 600, and 800 levels of resolution may be attributed to the unchanged vertical resolution (650). However, the \bar{S}_s ' performance decreased at the lowest horizontal resolution level (300).

The interaction of resolution by subjects was significant for both detection scores and response times. These interactions are plotted in Figures 2 and 3, both of which show only two levels (800 and 300) of resolution. The figures show that \bar{S}_s perform quite differently at different levels of resolution.

With response time, there was a significant interaction between resolution and location. The plot of this interaction, in Figure 4, indicates that mean response time differs as a function of resolution and location; however, for the most part, mean response time is faster with higher levels of resolution.

The analysis of variance indicated that the target location on the TV screen significantly affected the number of correct detections. The percentage of correct detections for each of the nine areas on the TV screen is plotted in Figure 5. The highest percentages of correct detections were in the upper middle, middle, and lower middle areas of the TV screen. Percentage of correct detections was lowest in the corners of the TV screen. However, the effects of the target's location on the TV screen are confounded by several other factors. First, Ss use different techniques to scan visual displays, so the obtained location effects could occur if the middle areas of the TV screen are scanned more frequently than other areas. However, this scanning effect is confounded with a second factor: resolution. With a bandwidth of 20 megacycles, resolution is not uniform across the surface of the TV monitor. When the center of the screen has 800-line resolution, the level in the corner areas may be as low as 500. Conceivably, this accentuated degradation in the TV display's corners could account for low target-detection probabilities in the corners. A third factor which is confounded with the location effect is the luminance of the TV screen. The TV screen's luminance, as measured with a Pritchard photometer (model 1970-PR), is not uniform. When the center area of the screen measures 7.6 foot-Lamberts, the corner areas may be as low as 6.2 foot-Lamberts. It is possible, therefore, that these differing luminance values may also contribute to low target-detection probabilities in the corner areas.

SUMMARY

This experiment investigated how TV resolution affects target-detection probability. Sixteen Ss viewed an M-48 tank on a closed-circuit black-and-white TV system under four levels of resolution (800, 600, 400, and 300). The Ss' task was indicating in which one of nine areas the tank appeared.

The data indicate that Ss' target-detection probability decreases significantly between the 300 and 400 levels of resolution; however, there were no significant differences among the 400, 600, and 800 levels of resolution. In addition, the target's location on the TV screen affected the target-detection probability significantly; however, this effect was confounded with resolution, luminance, and Ss' search techniques.




FIG. 2. PERCENT CORRECT DETECTIONS AS A FUNCTION OF RESOLUTION AND SUBJECTS




Fig. 3. MEAN RESPONSE TIME AS A FUNCTION OF RESOLUTION AND SUBJECTS




Fig. 4. MEAN RESPONSE TIME AS A FUNCTION OF RESOLUTION AND LOCATIONS




Fig. 5. PERCENT CORRECT DETECTIONS AS A FUNCTION OF LOCATIONS

REFERENCES

1. Duncan, D. B. Multiple range tests for correlated and heteroscedastic means. Biometrics, 1957, 13, 164-176.
2. Electronic Proving Ground. Feasibility test of high-resolution closed-circuit television system. AD 259-864, U. S. Army, Fort Huachuca, Ariz., March 1961.
3. Freeberg, N. E. Form perception in video viewing: Effects of resolution degradation and stereo on form thresholds. Technical Documentary Report ESD-TDR-63-136, Operational Applications Laboratory, Bedford, Mass., December 1962.
4. Gordon, D. A. Visual detection and identification: Military applications. Memorandum 2144-397-R, Project Michigan, University of Michigan, April 1959.
5. Martindale, R. L. & Lowe, W. F. Use of television for remote control: A preliminary study. J. appl. Psychol., 1959, 43, 122-124.
6. Moler, C. G. & Brown, G. L. Closed-circuit television vehicle driving: I. A preliminary investigation. Technical Memorandum 10-60, U. S. Army Human Engineering Laboratories, Aberdeen Proving Ground, Md., August 1960.
7. Oatman, L. C. Target detection as a function of exposure time and display mode. Technical Note 8-63, U. S. Army Human Engineering Laboratories, Aberdeen Proving Ground, Md., October 1963.
8. Shanahan, D. Effects of television bandwidth on target identification. Technical Memorandum NCM-TM-64-2, U. S. Naval Missile Center, Point Mugu, Calif., April 1964.

APPENDIX

INSTRUCTIONS TO SUBJECTS

We are going to present a series of pictures on the screen. Each one will be a photograph in which there may be a military target (tank), or the screen may be blank. Here is an example (SLIDE ONE). Can you spot the target? As you see, it is in the _____ grid on the screen. This panel is also marked into nine areas. As soon as you spot the target, press the button that corresponds with the area on the screen where you see the target. Press the button as soon as possible after you spot the target. If the screen does not have a target, push two different buttons (any two). I will say "Ready" before I flash each slide. If the TV fails at any time, notify me through the intercom. Do you have any questions?

DOCUMENT CONTROL DATA - R&D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1 ORIGINATING ACTIVITY (Corporate author) U. S. Army Human Engineering Laboratories Aberdeen Proving Ground, Md.		2a REPORT SECURITY CLASSIFICATION Unclassified	
		2b GROUP	
3 REPORT TITLE TARGET DETECTION USING BLACK-AND-WHITE TELEVISION STUDY I: THE EFFECTS OF RESOLUTION DEGRADATION ON TARGET DETECTION			
4 DESCRIPTIVE NOTES (Type of report and inclusive dates)			
5 AUTHOR(S) (Last name, first name, initial) Oatman, Lynn C.			
6 REPORT DATE July 1965		7a TOTAL NO OF PAGES 20	7b NO OF REFS 8
8a CONTRACT OR GRANT NO.		9a ORIGINATOR'S REPORT NUMBER(S) Technical Memorandum 9-65	
b. PROJECT NO.		9b OTHER REPORT NO(S) (Any other numbers that may be assigned this report)	
c.			
d.			
10 AVAILABILITY/LIMITATION NOTICES Distribution of this document is unlimited. Released to Dept. of Commerce for sale to public.			
11 SUPPLEMENTARY NOTES		12 SPONSORING MILITARY ACTIVITY	
13 ABSTRACT <p>The probability of detecting an M-48 tank at four different levels of television (TV) resolution (800, 600, 400, and 300 lines) was investigated on a black-and-white closed-circuit TV system.</p> <p>The four levels of TV resolution were presented to 16 subjects, who were asked to indicate in which one of nine areas the tank appeared on the TV screen.</p> <p>The data indicated that subjects performed about equally well at the 800, 600, and 400 levels of resolution; however, their performance was significantly poorer at the 300 level of resolution. The tank's location on the TV screen was an important factor in the probability of target detection, but was confounded with other variables.</p>			

14 KEY WORDS Target Detection Television Displays Human Engineering	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT

INSTRUCTIONS

1. ORIGINATING ACTIVITY: Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (*corporate author*) issuing the report.

2a. REPORT SECURITY CLASSIFICATION: Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. GROUP: Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. REPORT TITLE: Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. DESCRIPTIVE NOTES: If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. AUTHOR(S): Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. REPORT DATE: Enter the date of the report as day, month, year; or month, year. If more than one date appears on the report, use date of publication.

7a. TOTAL NUMBER OF PAGES: The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. NUMBER OF REFERENCES: Enter the total number of references cited in the report.

8a. CONTRACT OR GRANT NUMBER: If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. PROJECT NUMBER: Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. ORIGINATOR'S REPORT NUMBER(S): Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. OTHER REPORT NUMBER(S): If the report has been assigned any other report numbers (*either by the originator or by the sponsor*), also enter this number(s).

10. AVAILABILITY/LIMITATION NOTICES: Enter any limitations on further dissemination of the report, other than those imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. SUPPLEMENTARY NOTES: Use for additional explanatory notes.

12. SPONSORING MILITARY ACTIVITY: Enter the name of the departmental project office or laboratory sponsoring (*paying for*) the research and development. Include address.

13. ABSTRACT: Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. KEY WORDS: Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.