

AD 628161 Report 2127



DEPARTMENT OF THE NAVY

1.60 C-50 16 a

HYDROMECHANICS

THE FORCE AND MOMENT ON A SLENDER BODY OF  
REVOLUTION MOVING NEAR A WALL *C-50 16 a*

○

AERODYNAMICS

by

○

J. Nicholas Newman

REC-111  
FEB 4 1966  
DDC-IRA B

STRUCTURAL  
MECHANICS

○

Distribution of this document is unlimited

APPLIED  
MATHEMATICS

○


HYDROMECHANICS LABORATORY  
RESEARCH AND DEVELOPMENT REPORT

ACOUSTICS AND  
VIBRATION

December 1965

Report 2127

# DISCLAIMER NOTICE



THIS DOCUMENT IS BEST  
QUALITY AVAILABLE. THE COPY  
FURNISHED TO DTIC CONTAINED  
A SIGNIFICANT NUMBER OF  
PAGES WHICH DO NOT  
REPRODUCE LEGIBLY.

THIS DOCUMENT CONTAINED  
BLANK PAGES THAT HAVE  
BEEN DELETED

REPRODUCED FROM  
BEST AVAILABLE COPY

This Document Contains  
Missing Page/s That Are  
Unavailable In The  
Original Document

THE FORCE AND MOMENT ON A SLENDER BODY OF  
REVOLUTION MOVING NEAR A WALL

by

J. Nicholas Newman

Distribution of this document is unlimited

December 1965

Report 2127

TABLE OF CONTENTS

	Page
ABSTRACT .....	1
INTRODUCTION .....	1
THE VELOCITY POTENTIAL .....	3
THE VERTICAL FORCE AND PITCH MOMENT .....	6
THE VERTICAL FORCE ON A SPHEROID .....	8
ACKNOWLEDGMENT .....	10
REFERENCES .....	10

LIST OF FIGURES

	Page
Figure 1 - The Coordinate System and Flow Geometry .....	3
Figure 2 - Ratio of the Vertical Force to Its Limiting Maximum Value for a Slender Spheroid .....	9

## NOTATION

$a$	$a = [z_0^2 - r_0^2(x)]^{1/2}$
$F_z$	Vertical force acting on body
$f(x)$	Arbitrary function
$i$	Unit vector in x-direction
$L$	Body length
$M_y$	Pitch moment acting on body
$n$	Unit normal vector, positive into the fluid
$r$	Polar radius coordinate
$r_0(x)$	Body radius as function of $x$
$r_{om}$	Maximum body radius
$S(x)$	Sectional area, $S(x) = \pi[r_0(x)]^2$
$U$	Forward velocity of the body
$V$	Velocity vector of the fluid
$(x, y, z)$	Cartesian coordinates (cf. fig. 1)
$z_0$	Height of body axis above the wall
$\zeta$	$\zeta = z_0/r_{om}$
$\xi$	Dummy variable corresponding to the coordinate $x$
$\theta$	Polar angular coordinate
$\rho$	Fluid density
$\phi$	Velocity potential
$\phi_{2D}$	Two-dimensional velocity potential

## ABSTRACT

Analytical results are derived for the vertical force and pitch moment acting on a body of revolution which is moving with constant forward velocity parallel to an infinite horizontal wall. It is assumed that the fluid is ideal and incompressible and that the body is slender and situated close to the wall. The force and moment are given in terms of simple integrals involving the body shape and separation distance from the wall. Calculations are made for a spheroid, and it is shown that the vertical force rises rapidly as the body is brought progressively closer to the wall.

## INTRODUCTION

It is well known in naval architecture that when a body moves through a fluid parallel to a wall, an interaction force and moment will act on the body because of the presence of the wall. Normally the force will be positive in the direction toward the wall, due to the venturi effect of the accelerated flow between the body and the wall, and this force will become more pronounced as the body is moved closer to the wall. The moment will generally increase also, under these circumstances, but its sign is not definite and will depend on the detailed shape of the body; for a body with fore-and-aft symmetry the moment will vanish, under the assumptions of ideal flow, because of the corresponding symmetry of the resulting flow.

There are several instances in which this problem may be of practical interest, particularly for a ship moving in restricted water near a bank or wall of a canal (and where at low speeds the effects of the free surface are not important). Recent interest in oceanographic submarines has posed a similar problem for a vehicle moving in close proximity to the bottom.

To obtain a complete analytical prediction for the force and moment acting on a body near a wall, it is necessary to idealize the problem. With this goal in mind we shall assume not only that the fluid is ideal, incompressible, and unbounded except by the wall and the body, but also that the body is axisymmetric, slender, and in close proximity to the wall. The

last assumptions permit us to use the slender-body approach of aerodynamics<sup>1</sup> to obtain an explicit solution of the boundary-value problem for the velocity field, in terms of a source distribution inside the body plus a corresponding image source system below the wall. The strength of this source distribution is unchanged by the presence of the wall, but the effect of the wall is not only to introduce the image system, but also to require that the original source distribution be offset from the body axis toward the wall; this can be inferred from the corresponding two-dimensional problem in bipolar coordinates. If the body were not axisymmetric, a more complicated singularity distribution would be required, and this could only be obtained from a numerical scheme. Nevertheless, it is felt that the present results should be valid for bodies which do not depart too much from axial symmetry, as in the case of a submarine.

Having found the velocity potential, in terms of a three-dimensional source distribution within the body and its image, we can easily find the force and moment acting on the body by the use of Lagally's theorem,<sup>2</sup> and the final results take the form of integrals over the body length involving the cross-sectional area of the body and its first derivative, and the distance of the body from the wall. These results are illustrated for a slender spheroid.

Several years ago Eisenberg<sup>3</sup> considered the same problem for a spheroid, and although his results were limited to finding the pressure distribution on the body, the force and moment could be found therefrom by integration. However, there is a significantly different assumption in Eisenberg's analysis, from those made here, in that the flow is approximated by that due to a single spheroid in an infinite fluid plus the corresponding disturbance due to an image spheroid, without regard for the fact that there will be an induced velocity on each spheroid due to its image which must be accounted for. In fact Eisenberg's approximation will be valid provided the two spheroids are far apart, whereas ours, based upon the

---

<sup>1</sup>References are listed on page 10.

lender-body theory, is valid provided the two bodies are close together. It is felt that the latter is more appropriate in the present context, since the force and moment under consideration increase rapidly as the body is brought closer to the wall and are comparatively negligible if the body axis is greater than one or two diameters from the wall.

### THE VELOCITY POTENTIAL

We shall employ Cartesian coordinates  $(x,y,z)$ , with  $z = 0$  the plane of the wall and with the body axis on the line  $y = 0, z = z_0$ . Thus the body axis is parallel to the  $x$ -axis and is a distance  $z_0$  from the wall (Figure 1). The body is assumed to be defined by a smooth continuous radius function  $r_0(x)$ , according to the equation

$$r_0(x) = [y^2 + (z - z_0)^2]^{1/2}, \text{ for } -\frac{L}{2} < x < \frac{L}{2}, \quad [1]$$




Figure 1 - The Coordinate System and Flow Geometry

where  $L$  is the body length and by assumption  $r_0(\pm \frac{L}{2}) = 0$ . Because of the slender body assumption and because the wall is in the near field,  $L \ll 1$  and  $z_0/L \ll 1$ .

The body is considered to be fixed in space, with a free stream of velocity  $U$  flowing past it in the  $-x$  direction. The velocity field is defined by the vector

$$\mathbf{V} = \nabla \phi(x, y, z) - U\mathbf{i} \quad [2]$$

where  $\phi$  is the velocity potential of the perturbation flow. This potential must satisfy Laplace's equation, the boundary condition

$$\frac{\partial \phi}{\partial z} = 0 \quad \text{on the wall } z = 0,$$

and the boundary condition

$$\frac{\partial \phi}{\partial \mathbf{n}} = U \cos(\mathbf{n}, \mathbf{x}) = -U r_0'(x)$$

on the body. Here  $\mathbf{n}$  is the unit normal vector out of the body and  $r_0'(x) \equiv dr_0/dx$ . In addition,  $\nabla \phi$  must vanish at infinity. In the near field, close to the body, it follows from slender body theory<sup>1</sup> that

$$\phi(x, y, z) \approx \phi_{2D}(y, z; x) + f(x), \quad [3]$$

where  $\phi_{2D}$  is the potential of a two-dimensional flow in the "cross-flow" plane. The function  $f(x)$  can be found, but since it depends only on  $x$  it does not contribute to the vertical force or to the pitch moment.

The potential  $\phi_{2D}$  must satisfy the body boundary condition

$$\frac{\partial \phi_{2D}}{\partial \mathbf{n}} = -U r_0'(x). \quad [4]$$

Physically this is the velocity potential for the flow of fluid out (or in) through the periphery of the circle  $y^2 + (z - z_0)^2 = r_0^2$ , in the presence of a wall at  $z = 0$ . By reflection this is equivalent to the flow out of (or in through) two circles with centers at  $z = \pm z_0$ . To solve this two-dimensional problem, we look for a solution of the form\*

---

\* Some motivation for attempting to find a solution of this form can be found from the properties of bipolar coordinate systems.

$$\phi_{2D}(y, z; x) = C \log \left\{ [y^2 + (z-a)^2] [y^2 + (z+a)^2] \right\}, \quad [5]$$

where  $C$  and  $a$  are constants (which may depend on  $x$ ). Physically this potential represents the flow due to a source at  $y = 0, z = a$ , plus an image source at  $y = 0, z = -a$ . Changing to polar coordinates  $(r, \theta)$ , with the origin at the center of the original circle, gives

$$y = r \sin \theta$$

$$z = z_0 + r \cos \theta,$$

It follows that

$$\phi_{2D}(r, \theta; x) = C \log \left\{ (r^2 + 2 z_0 r \cos \theta + z_0^2 + a^2)^2 - 4 a^2 (z_0 + r \cos \theta)^2 \right\}.$$

It can be easily verified that, on the circle  $r = r_0(x)$ ,

$$\frac{\partial}{\partial r} \phi_{2D} = 2 C / r_0, \quad [6]$$

provided the parameter  $a$  is chosen to satisfy the relation

$$a^2 = z_0^2 - r_0^2.$$

From the boundary condition [4] it follows that

$$C = -\frac{1}{2} U r_0(x) r_0'(x) = -\frac{1}{4\pi} U S'(x),$$

where  $S(x) = \pi r_0^2(x)$  is the cross-sectional area and  $S'(x) = dS(x)/dx$ . Thus the desired two-dimensional potential is

$$\phi_{2D}(y, z; x) = -\frac{1}{4\pi} U S'(x) \log \left\{ [y^2 + (z-a)^2] [y^2 + (z+a)^2] \right\} \quad [7]$$

with

$$a(x) = \left\{ z_0^2 - [r_0(x)]^2 \right\}^{1/2}$$

The three-dimensional source distribution which is associated with  $\phi_{2D}$  is

$$\phi(x,y,z) = \frac{1}{4\pi} U \int_{-\frac{L}{2}}^{\frac{L}{2}} S'(\xi) \left\{ [(x-\xi)^2 + y^2 + (z-a)^2]^{-1/2} + [(x-\xi)^2 + y^2 + (z+a)^2]^{-1/2} \right\} d\xi, \quad [8]$$

where in the integral the parameter  $a$  is a function of  $\xi$ . It can be shown<sup>1</sup> that this three-dimensional potential reduces to  $\phi_{2D}$ , as given by Equation [7], plus a function only of  $x$ , for points on or near the body surface.

#### THE VERTICAL FORCE AND PITCH MOMENT

It is now a straightforward matter to find the vertical force  $F_z$  and pitch moment  $M_y$  from Lagally's theorem.<sup>2</sup> For this purpose we note from [8] that the body is generated by a distribution of three-dimensional sources, of strength

$$\frac{1}{4\pi} U S'(x),$$

in the presence of an "external flow" due to the free stream of velocity  $-U_i$ , where  $i$  is a unit vector in the  $x$ -direction, and an additional external flow due to the image potential

$$\frac{1}{4\pi} U \int_{-\frac{L}{2}}^{\frac{L}{2}} S'(\xi) [(x-\xi)^2 + y^2 + (z+a)^2]^{-1/2} d\xi.$$

From Lagally's theorem the vertical force acting upon the body is the integral of the differential force on each source element, which in turn is equal to  $4\pi\sigma$  times the product of the source strength and the vertical component of the external flow. Thus

$$F_z = \frac{1}{4\pi} \rho U^2 \int_{-\frac{L}{2}}^{\frac{L}{2}} S'(x) \left\{ \int_{z=a(x)}^{\frac{3}{2}} \int_{-\frac{L}{2}}^{\frac{L}{2}} S'(\xi) [(x-\xi)^2 + (z+a)^2]^{-1/2} d\xi \right\} dx. \quad [9]$$

The quantity in brackets can be evaluated for a slender body since it is a vertical dipole distribution:

$$\begin{aligned}
 & \left\{ \frac{\partial}{\partial z} \int_{-\frac{L}{2}}^{\frac{L}{2}} S'(\xi) [(x-\xi)^2 + (z + (a(\xi))^2)^{-1/2}] d\xi \right\}_{z=a(x)} \\
 &= - \int_{-\frac{L}{2}}^{\frac{L}{2}} S'(\xi) [a(\xi) + a(x)] [(x-\xi)^2 + (a(\xi) + a(x))^2]^{-3/2} d\xi \\
 &\approx - 2 a(x) S'(x) \int_{-\infty}^{\infty} [(x-\xi)^2 + 4 (a(x))^2]^{-3/2} d\xi \\
 &= - S'(x) / a(x).
 \end{aligned}$$

Thus, from [9], the vertical force is given by the integral

$$F_z = - \frac{1}{4\pi} \rho U^2 \int_{-\frac{L}{2}}^{\frac{L}{2}} [S'(x)]^2 \left\{ z_o^2 - [r_o(x)]^2 \right\}^{-1/2} dx,$$

or

$$F_z = - \pi \rho U^2 \int_{-\frac{L}{2}}^{\frac{L}{2}} [r_o(x) r_o'(x)]^2 \left\{ z_o^2 - [r_o(x)]^2 \right\}^{-1/2} dx. \quad [10]$$

Similarly, for the moment,

$$M_y = \pi \rho U^2 \int_{-\frac{L}{2}}^{\frac{L}{2}} [r_o(x) r_o'(x)]^2 \left\{ z_o^2 - [r_o(x)]^2 \right\}^{-1/2} x dx. \quad [11]$$

These two integrals are the principal results of the analysis. We note that for a body with longitudinal (fore-and-aft) symmetry the integral for the pitch moment  $M_y$  vanishes, as a consequence of the symmetrical flow which will then occur. Moreover, the vertical force  $F_z$  is always less than zero, in keeping with the fact that the flow velocity will be higher

between the wall and the body, as compared with the corresponding value on the "outside" portion of the body. Thus there will always be a suction force tending to attract the body toward the wall and this force will increase monotonically to a finite limit as  $z_0 \rightarrow r_0$ , or the body is brought in to the wall. We can conclude from the above integrals that for geometrically affine bodies, having the same cross-sectional distributions but different lengths, the force will be inversely proportional to the length whereas the moment will be independent of the length. Finally, we note that for bodies with flat ends, such as a right circular cylinder, the above integrals are divergent as a consequence of the "end effect" error in the slender-body theory.

The pitch moment is more difficult to discuss qualitatively since the integrand of [11] is not positive-definite, and the sign of the integral will depend critically on the distribution of the sectional area  $S(x)$ , and possibly also on the separation distance  $z_0$ . However, it seems likely that for bodies with full or blunt ends this integral will be dominated by the large values of  $S'(x)$  at the two ends, and thus that the pitch moment will be positive (bow down) if the bow is blunt compared to the stern, and vice versa. (An analogous argument is common in naval architecture to explain the tendency of ships with full sterns to tend to head away from a bank when moving in restricted waters.)

#### THE VERTICAL FORCE ON A SPHEROID

As an illustration we shall consider the body to be a slender spheroid, of maximum radius  $r_{om}$ , so that

$$r_0(x) = r_{om} (1 - 4x^2/L^2)^{1/2}$$

For convenience we introduce the nondimensional parameter

$$\zeta = z_0/r_{om},$$

representing the nondimensionalized vertical height of the body axis above the bottom. Substituting in [10], we obtain the integral

$$\begin{aligned}
F_z &= - 16 \pi \rho U^2 r_{om}^3 L^{-4} \int_{-\frac{L}{2}}^{\frac{L}{2}} (\zeta^2 - 1 + 4x^2/L^2)^{-1/2} x^2 dx \\
&= - 2 \pi \rho U^2 r_{om}^3 L^{-1} \left\{ \zeta - \frac{1}{2} (\zeta^2 - 1) \log \left( \frac{\zeta + 1}{\zeta - 1} \right) \right\} \quad [12] \\
&= - \frac{4}{3} \pi \rho U^2 r_{om}^3 L^{-1} \left[ Q_0(\zeta) - Q_2(\zeta) \right]
\end{aligned}$$

where  $Q_n$  is the Legendre function of the second kind. For  $\zeta \rightarrow 1$  the force tends to a limiting value of

$$F_{zmax} = - 2\pi\rho U^2 r_{om}^3 L^{-1}. \quad [13]$$

In Figure 2 we show the ratio  $F_z/F_{zmax}$ , as a function of the height parameter  $\zeta = z_o/r_{om}$ .




Figure 2 - Ratio of the Vertical Force to Its Limiting Maximum Value for a Slender Spheroid

#### ACKNOWLEDGMENT

The author is grateful to Dr. T. F. Oglivie for several valuable suggestions pertaining to this project.

#### REFERENCES

1. "Linearized Theory of Steady High-Speed Flow," by G. V. Ward, Cambridge University Press, 1955, Chapter 9.
2. "The Force and Moment on a Body in a Time-Varying Potential Flow,:" by W. E. Cummins, Journal of Ship Research, Volume 1, No. 1, pp. 7-18, April 1957.
3. "An Approximate Solution for Incompressible Flow About an Ellipsoid Near a Plane Wall," by Philip Eisenberg, Journal of Applied Mechanics, Volume 17, pp. 154-158, 1950.

UNCLASSIFIED

Security Classification

DOCUMENT CONTROL DATA - R&D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1 ORIGINATING ACTIVITY (Corporate author) David Taylor Model Basin Washington, D.C. 20007	2a REPORT SECURITY CLASSIFICATION Unclassified
	2b GROUP

3 REPORT TITLE  
THE FORCE AND MOMENT ON A SLENDER BODY OF REVOLUTION MOVING NEAR A WALL

4 DESCRIPTIVE NOTES (Type of report and inclusive dates)

5 AUTHOR(S) (Last name, first name, initial)  
Newman, J. Nicholas

6 REPORT DATE December 1965	7a. TOTAL NO OF PAGES 12	7b. NO OF REFS 3
--------------------------------	-----------------------------	---------------------

8a. CONTRACT OR GRANT NO.	9a. ORIGINATOR'S REPORT NUMBER(S) 2127
b PROJECT NO. S-R011 01 01, Task 0401	9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)
c	
d	

10 AVAILABILITY/LIMITATION NOTICES  
Distribution of this document is unlimited

11 SUPPLEMENTARY NOTES	12. SPONSORING MILITARY ACTIVITY Bureau of Ships Washington, D.C.
------------------------	---

13 ABSTRACT

Analytical results are derived for the vertical force and pitch moment acting on a body of revolution which is moving with constant forward velocity parallel to an infinite horizontal wall. It is assumed that the fluid is ideal and incompressible and that the body is slender and situated close to the wall. The force and moment are given in terms of simple integrals involving the body shape and separation distance from the wall. Calculations are made for a spheroid, and it is shown that the vertical force rises rapidly as the body is brought progressively closer to the wall.

UNCLASSIFIED

Security Classification

14 KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
Slender Bodies						
Wall Effects						
Bodies of Revolution						
Force and Moment						
Spheroid						

INSTRUCTIONS

1. ORIGINATING ACTIVITY: Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (corporate author) issuing the report.

2a. REPORT SECURITY CLASSIFICATION: Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. GROUP: Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. REPORT TITLE: Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. DESCRIPTIVE NOTES: If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. AUTHOR(S): Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. REPORT DATE: Enter the date of the report as day, month, year; or month, year. If more than one date appears on the report, use date of publication.

7a. TOTAL NUMBER OF PAGES: The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. NUMBER OF REFERENCES: Enter the total number of references cited in the report.

8a. CONTRACT OR GRANT NUMBER: If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. PROJECT NUMBER: Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. ORIGINATOR'S REPORT NUMBER(S): Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. OTHER REPORT NUMBER(S): If the report has been assigned any other report numbers (either by the originator or by the sponsor), also enter this number(s).

10. AVAILABILITY/LIMITATION NOTICES: Enter any limitations on further dissemination of the report, other than those

imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through \_\_\_\_\_."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through \_\_\_\_\_."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through \_\_\_\_\_."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. SUPPLEMENTARY NOTES: Use for additional explanatory notes.

12. SPONSORING MILITARY ACTIVITY: Enter the name of the departmental project office or laboratory sponsoring (paying for) the research and development. Include address.

13. ABSTRACT: Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. KEY WORDS: Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, roles, and weights is optional.

UNCLASSIFIED

Security Classification