

ANTENNA IMPEDANCE IN THE IONOSPHERE

by

Alvin M. Despain

~

Upper Air Research Laboratory University of Utah Salt Lake City, Utah

Scientific Report No. 3

Contract No. AF 19(628)-4995 Project No. 7663 Task No. 766303

Contract Monitor: James C. Ulwick

13 May 1966

This research is sponsored, in part, by the Defense Atomic Support Agency, Washington, D.C. under Web No. 07.007, Project 5710

Prepared for

Air Force Cambridge Research Laboratories Office of Aerospace Research United States Air Force Bedford, Massachusetts

Distribution of this document is unlimited

ب يە يىرە خىمى

an Maria and and and analysis of the

Submitted by Obed C. Haycock, Director

به جهد العبيد بر الع

and the second second

LIST OF CONTRIBUTORS

Obed C. Haycock, Director Kay D. Baker, Assistant Director

RELATED CONTRACTS

AF 19(628)-447

AF 19(628)-229

RELATED PUBLICATIONS

- "A Plasma Resonance and Electron Temperature Experiment," Scientific Report No. 3, Contract No. AF 19(628) 447, AFCRL No. 64-809, August 1964.
- "The Theory of Cylindrical Antenna Impedance as a Function of Plasma Frequency and Temperature," Scientific Report No. 1, Contract No. AF 19 (628)-4995, March 1965.
- "Direct In Situ Measurements of Auroral Parameters," Scientific Report No. 4, Contract No. AF 19(628)-4995, May 1966.
- "RF Probe Techniques," Final Report, Contract No. AF 19(628)-447, 1965.
- "Measurement of Missile Trail Ionization by the Drop-Out Probe Technique," Final Report under Contract No. AF 19(628)-229, 21 June 1965.
- "Experiences with Antenna Impedance Measurements in the Ionosphere," pap'r presented at the 1965 Fall URSI Meeting, Dartmouth College, Hanover, New Hampshire, 5 October 1965.
- "Ionospheric Electron Temperatures from Antenna Impedance Measurements," paper presented at the 1966 Spring URSI Meeting, National Academy of Sciences, Washington D.C., 19 April 1966.
- "Experimental and Theoretical Studies of Antenna Impedance in the D and E Regions," paper presented at the Second Conference on Direct Aeronomic Measurements in the Lower Ionosphere, University of Illinois, Urbana, Illinois, September 28, 1965.
- "Simultaneous Comparison of RF Frobe Techniques for Determination of Ionospheric Electron Density," J. Geophys. Res., 71, 935-949, February 1966.

ACKNOWLEDGEMENT

Sincere appreciation is expressed to the many individuals who have been of assistance in the pursuit of the research reported here and in the preparation of this paper.

The author is deeply indepted to all the staff of the Upper Air kesearch Laboratories, especially to Professor Obed C. Haycock and Mr. Kay D. Baker for guidance and support. Mr. Grant Duffin, Mr. Kent Olsen, Mr. Michael Taylor and Mr. Wayne Wride have all provided valuable aid in data reduction while Mr. Glenn Allred, Mrs. Lonnie Dalrymple, Mr. Robert Fowler, Mrs. Diane Hansen, Mrs. Susan Lambert and Mr. Andre Schwager have materially assisted in the preparation of this report.

Gratitude is also due to Mr. James C. Ulwick and Dr. Wolfgang Pfister of the Air Force Cambridge Research Laboratories for providing scientific consultation and support.

The University of Utah Computer Center gave valuable assistance in preparation and execution of several computer studies.

ABSTRACT

The impedance of an antenna probe surrounded by ionospheric plasma is examined. A review of several physical plasma parameters, research techniques, some past experimental results, and various theories is presented. A need is shown for further theoretical sophistication. The theory develops the impedance of an electrically short, cylindrical antenna probe immersed in a warm, lossy, compressible, magneto-ionic, electron fluid. The results are examined and compared to previous work and are applied to several ionospheric experiments. Experimental results as interpreted by the theory are examined and the usefulness of the theory is thus demonstrated. In particular, the theory is shown to be of value in determining electron density, temperature, and collision frequency from RF probe measurements.

TABLE OF CONTENTS

Pa	<u>ge</u>
Acknowledgement	11
Abstract	iv
Table of Contents	v
List of Figures	11
List of Symbols and Useful Relations	11
INTRODUCTION	1
The Plasma State	1
The Ionosphere	6
Ionospheric Measurement Techniques.	10
Standing Wave Impedance Probe (SWIP)	12
Plasma Frequency Probe (PFP).	13
Resonance Rectification Probe	16
Preliminary Conclusions	16
PROBE THEORIES	17
	- /
DERIVATION OF ANTENNA IMPEDANCE.	22
Introduction	22
Fundamental Equations	23
Solution of Swstem Equations	22
	22
	34
	31
Sheath Effects	39
COMPARISON OF RESULTS	42
Introduction	42
Cold Plasma Comparison	44
Balmain Finite Temperature Theory	44
Whale Theory.	45
Comparison of Theories	45
Transfert Tralications of the Theory	51
Important Implications of the Ineory.	21
Further Examination of the Theory	51
Comparison of the Theory to Experimental Results	53
DETERMINATION OF PLASMA PARAMETERS	58
Introduction	58
Plasma Parameters from the Standing Wave Impedance Probe.	59
Disara Deventors from the Disara Frequency Drobo	62
riasma ratameters from the riasma riequency riobe • • • • • • •	00
Calculation of Series Resonance Frequency	03
Electron Temperature from Resonance Frequencies	67
Example of Electron Temperatures from Measured Antenna	
Characteristics	67

TABLE OF CONTENTS (Cont.)

.

Finance .

1

T

Page

SUMMARY	AND) CC	NCLU	ISI	ONS	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	73
REFERENC	CES.	•	••	•	••	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	77
APPENDIX	K A	ANI	ENNA	I	MPE	DAI	NCE	F	RO	M	IC	NI	C	TH	EC	RY	•	•	•	•	•	•	•	•	•	A-1
APPENDI	K B	CON	PUTE	R	PRO	GR/	AMS	•	•	•	•	•	•	•	•	•	•	•	٠	•	•	•	•	•	•	B-1

vi

-

The set of the second date deside at the second life

LIST OF FIGURES

figure

A REAL PROPERTY OF A REAL PROPER

1.	Normal Electron Distribution of the Ionosphere • • • • • • • 8
2.	Normal Electron Temperature in the Ionosphere
3.	Normal Debye Length in the Ionosphere • • • • • • • • • • • • • • • • • •
4.	Normal Electron Collision Frequency in the Ionosphere 10
5.	Basic Concept of RF Probe Systems
6.	Standing Wave Impedance Probe
7.	Plasma Frequency and Resonance Rectification Probe • • • • • 15
8.	Coordinate System
9.	Balmain Theory Antenna Impedance
10.	Despain Theory Antenna Impedance
11.	Comparison of Despain, Balmain, and Whale Theories • • • • • • • 49
12.	Antenna Impedance in the Presence of a Longitudinal Magnetic Field • • • • • • • • • • • • • • • • • • •
13.	Antenna Impedance With Longitudinal Magnetic Field and Electron Collisions
14.	Experimental Series and Parallei Resonance Frequencies • • • • 56
15.	Antenna Resistance Versus Reactance • • • • • • • • • • • • 60
16.	Antenna Resistance Versus Reactance Including Electron Collisions
17.	Antenna Resistance Versus Reactance for 75 km
18.	Series Versus Parallel Resonance Frequencies • • • • • • • • • 65
19.	Antenna Radius Versus Series Resonance Frequency • • • • • • • 66
20.	Antenna and Vehicle Potential
21.	Collapsed Sheath Electron Temperatures
22.	Averaged Electron Temperatures

· •

and the second second

LIST OF SYMBOLS AND USEFUL RELATIONS

[A]	-	a tensor operator	V	-	a differential space operator
a ²	-	K'/K _o	2	-	a partial differential
a ²	18	$(\psi^2 - 1)\omega_N^2/\mu^2$	0	-	operator
a'2	=	$-\alpha^2$	Ē	=	electric field vector
в В	=	magnetic field vector ω/c	e	=	electronic charge (1.60206 x 10 ⁻¹⁹ cou-
β(x)	-	a special function	ε	=	dielectric permittivity
β _n	=	$\mu^2/UN\omega$	[ɛ]	=	dielectric permitivity tensor
۴ _p	=	e/Umw	ε		permittivity of free,
β _r	×	a special operator	0		space $(8.85434 \times 10^{-12} \text{ farads/m})$
β _θ	-	a special operator	F	=	$\sin^2 \alpha + a^2 \cos^2 \alpha$
С	=	capacitance	F	-	effective force due to
C'	-	a general purpose constant	C		collisions
с _N	-	model atmosphere constant	F _L	=	Lorentz Force
C _s		sheath capacitance	^F р	=	force due to pressure
с _о	-	free space capacitance	f	=	operating, exciting or applied frequency
c ₁	-	arbitrary constant	f'	-	a given frequency
с ₂	-	$-\mathrm{en}_2/\varepsilon_0 \alpha^2$	fu	=	gyrofrequency (aprox.
с	-	velocity of light	11		1.4 MHz in ionosphere)
→		(2.99/930 x 10° m/sec)	f _N	2	plasma frequer.cy
Ď	-	electric flux vector	fp	=	parallel resonance
d	=	differential operator	•		frequency
₫Ŝ	=	a differential surface element vector	fs	=	series resonance frequency
dV	=	a differential volume element	Y	3	angle between antenna & earth's magnetic field
[Δ]	=	a tensor operator	γ'	-	ratio of specific heats

viii

LIST OF SYMBOLS AND USEFUL LELATIONS (Cont)

Ĩ	=	magnetic field strength vector	ν	=	electron collision frequency
H(x)=	Hankel function of the first kind	ω		radian operating, excit-
н ⁽²⁾)	Hankel function of the second kind			ing or applied frequency
[I]	=	unit tensor	ωн	-	radian gyrofrequency
I	=	current at antenna terminals	ωN	=	radian plasma frequency
a T	=	displacement current depaits	P		polarization vector
D			Pr	1 12	radiated power
J	-	v-1	Р	=	pressure
K	7	Boltzmann's constant (1.38044 x 10 ⁻²³ Joules/°K)	π		3.14159265
К	=	$1 - XU/(U^2 - Y^2)$	Φ	=	electric potential
K(x)=	modified Bessel function of second kind	ø(x)=	$H_o(x)/xH_1(x)$
v	-		Q	=	total electric charge
°o L	=	antenna length	9 ₁	-	radiated power per unit length
λ		wavelength	R	=	antenna radius
λo	=	Debye length	Ra	e.	antenna resistance
М	-	molecular mass	R _L	=	$2\pi\epsilon_{o}LR_{s}\sqrt{1-x}/x\beta^{2}\mu C_{o}^{2}$
m	-	electronic mass (9.1083 x 10 ⁻³¹ kg)	Rr	=	radiation resistance
11		velocity associated with	R _s	Ξ	sheath radius
μ	_	longitudinal waves	r	=	radius coordinate of
μ ²		γ'KT/m			cylindrical coordinate system
μ _o		permeability of free space $(4\pi \times 10^{-7} \text{ Hepry/m})$	Ģ	2	mass density
			S	=	sheath scaling constant
IN	=	electron density	S(x	:)=	a differential operator
Nt	=	total particle density	[σ]	=	a tensor variable
n		variation in electron density	т	-	electron temperature
n	=	initial electron density variation	•	2	erceron competature

ix

and and the second s Second second

LIST OF SYMBOLS AND USEFUL RELATIONS(Cont.)

T

È

1 - Sec

ſ

5

]

. . .

-

t	=	time	Y _z	=	Ϋ́ζz
٤ _{ij}	-	cross components	Z	-	ν/ω
0	-	angle coordinate of cylindrical coordinate system	z _a	-	antenna impedance
U	•	1 - <u>j</u> Z	Z _{ar}	=	antenna impedance due to radiation resistance
[T]		a tensor variable	Z _{at}	=	total antenna impedance
V	-	μ^2/ω_N^2	z	=	height coordinate of
v _a	-	antenna voltage			system
v	-	velocity	ζ	*	unit vector in direction of magnetic field
→ V	=	velocity vector	~		
ī	-	mean electron velocity	٢	-	direction
v m	=	mean molecular velocity	ζ _θ	=	component of ζ in θ direction
ν _θ		component of \vec{v} in θ direction	7	_	
vr	z	component of \vec{v} in r direction	۲, x	=	direction
v _z	=	component of \vec{v} in z direction	ζy	=	component of ζ in y direction
W	-	Y/U			^ ^ ·
W ₀	=	wς _θ	ζz	*	component of ζ in z direction
Wr	*	₩¢ _r			
Wz	=	Ψζz			
x	-	$\omega_{\rm N}^2/\omega^2$			
x	-	a general variable			
ψ ²	=	$(u^2 - y^2)/ux$			
Y	-	ω _H /ω			
Y x	-	۲۶ _x			
Y.	8	۲ζ			

х

and the spranched and includes the state of the

Chapter I

INTRODUCTION

It is the purpose of this report to examine the interaction between an antenna probe and the ionospheric plasma surrounding it. This introductory chapter discusses plasma and ionospheric parameters and several research techniques. Chapter II considers past theoretical work that relates antenna probe impedance to the plasma parameters. The need for further effort is then demonstrated. A theory that relates the impedance of an electrically short, cylindrical, antenna probe to the magnetic field and plasma parameters of a warm, lossy, compressible electron fluid is developed in Chapter III. The theory is explored as a function of its parameters and is compared to other accepted results in Chapter IV. Chapter V describes the application of the work to various experiments. In particular, the theory is useful in interpreting measurements of electron density, electron temperature, and electron collision frequency. The results of the analysis then demonstrate the usefulness of the theory and its broad application in ionospheric research.

It should be noted that rationalized MKS units are used throughout.

The Plasma State

С

A gaseous plasma is an electrically neutral system of particles containing primarily free electrons and positive ions, but sometimes negative ions and neutral molecules as well. It has been estimated that perhaps more than 99.9 percent of the universe exists in such an ionized form [*Bachynski*, 1961]. While approximately 10^{-2} electron volts of energy per particle are required to change from the solid to liquid or from the liquid to gaseous state, one to ten electron volts of energy per particle are required to obtain the plasma state. Coulomb forces are dominant in plasmas as they are much more effective than gravitational or short-range nuclear effects. Thus, the ionized particles are endowed with considerable energy and exhibit strong electrical interactions that determine the primary character of the plasma.

A system of ionized particles is considered to be a plasma only if collective effects dominate any single particle effects. Therefore, the dimensions of a plasma must be at least as large as the range of interaction of single particles. This range is called the Debye length $\lambda_{\rm D}$ [Brown et al., 1963] and can be expressed by the equation

$$\lambda_{\rm D} = \left[\frac{\varepsilon_{\rm o \ KT}}{{\rm Ne}^2}\right]^{1/2} \tag{1}$$

Where

K = Boltmann's Constant
 T = kinetic temperature (electrons)
 N = ionization density (electrons)
 e = electronic charge
 ε = permittivity of free space

The Debye length is a very useful parameter and is often used as a length scaling constant in normalized equations. The Debye length can also be thought of as the maximum distance over which some charge separation can occur. If any macroscopic region (large dimensions compared to $\lambda_{\rm D}$), free of external influence, should have a net charge, then the charge would

create an electric field. This field would then cause the free ionized particles to redistribute into a minimum energy condition of zero field and thus zero net charge density would again result. It is not surprising then to find that the characteristic shielding distance $h_{\rm D}$ is directly dependent upon the energy of the electrons (electron temperature) and is inversely related to the average number of electrons that shield any discontinuities.

From the above discussion, it is apparent that disturbed plasma tends to return to equilibrium. Because the particles also have mass, the system exhibits properties characteristic of second order systems, including a natural resonant frequency, known as the plasma frequency, f_N . This quantity, the frequency of the "quivers" of the "plasma jelly," can be directly related to the electron density N and the physical constants electronic charge e, electronic mass m, and permittivity of free space ε_0 by the equation

$$\omega_{\rm N} = 2 \pi f_{\rm N} = \left[\frac{{\rm Ne}^2}{{\rm m}\epsilon_{\rm o}}\right]^{1/2}$$
(2)

[Brown et al , 1963]. The only variable in this equation is N, the electron density. Since the feature that distinguishes a plasma from other types of matter is its ionization, it is natural to expect that the electron density is the major parameter that describes the behavior of a plasma.

At this point, perhaps it is only natural to ask, "Why are the variables, electron density and temperature, the only ones specified in ^{n}D and ω_{N} ? Shouldn't the positive ion density and temperature also be included?" Of course in the strict sense, the answer is that ^{n}D and $^{\omega_{N}}$

are defined in this manner, but it is true that shielding and natural oscillation in plasmas are indeed affected by other types of particles. However, the electrons are much less massive than the other particles (by about four orders of magnitude) and since they have the same charge, they respond to electric and magnetic fields to a much larger degree. Then too, approximate thermal equilibrium usually exists in a plasma; therefore, electrons have the same energy per particle as the other heavier particles. Thus the average electron velocity is at least two orders of magnitude larger than the ion velocity. This is easily seen by equating the mean kinetic energies as follows

$$1/2 m \bar{v}^2 = 1/2 M \bar{v}_m^2$$
 (3)

$$\overline{\mathbf{v}} = \sqrt{\frac{M}{m}} \overline{\mathbf{v}}_{\mathbf{m}} \tag{4}$$

$$\overline{\mathbf{v}} = 10^2 \, \overline{\mathbf{v}}_{\mathrm{m}}$$
 (5)

where

1.

 \bar{v} = mean electron velocity \bar{v}_{m} = mean molecular velocity M = molecular mass

m = electronic mass

Thus the electrons can be visualized as mobile, rapidly moving particles among relatively fixed positive ions and neutral molecules. For most of our work, it will be possible to consider a plasma as compressible electron gas, diffused among fixed ions and molecules whose only effect is to maintain average charge neutrality and to possibly thermalize the rapidly moving electrons through collisions. This will require that any exciting

frequency ω be at least as large as $10^{-1} \omega_N$ to $10^{-2} \omega_N$. Otherwise ion and molecular motions must also be considered.

A useful measure of the collisions of electrons with other paricles is the effective electron collision frequency v. It is defined as the average number of times a second that an electron suffers a collision that effectively changes its direction of motion [Cambel, 1963]. Pfister (1965) considers several definitions of electron collision trequency and relates these to the mean collision frequency as derived from the average electron velocity.

If the exciting frequency ω is considerably larger than ω , then essentially no collisions occur during one cycle of excitation. Thus only one degree of freedom is possible for the electrons, that is, the direction of the original excitation. Thus, the ratio of specific heats for our compressible electron gas must be taken as 3 [Spitzer, 1962].

It was shown earlier that steady state charge separation does not generally exist in a plasma However, one important exception occurs at any sharp boundary where the ionization density changes markedly over a few Debye lengths. At such a surface, in the absence of electromagnetic fields, the electron flux impinging upon the boundary will greatly exceed the positive ion flux because of the much larger average electron velocity. Thus in the steady stare, electric fields are set up by the accumulation of electrons on the surface, such that the ion and electron currents are equal. There results, therefore, a depletion of electrons near the boundary and a sheath (free of electrons) is said to exist between the surface and the plasma. The thickness of this sheath is on the order of a Debye length and can be modified, even dispelled, by the external application of electric potentials to the surface.

This generally draws current from the plasma and thus upsets, to some degree, the natural plasma conditions. Nevertheless, it will sometimes be assumed that sheaths around antenna probes can be collapsed so that sheath effects can be ignored.

An external magnetic field greatly modifies the behavior of a plasma. The general effect is to "stiffen" the plasma in directions normal to the direction of the field. Magnetic fields are thus responsible for the anisotropic character of such plasmas. It is possible to consider the field as a parameter of the medium, however, a related quantity, the gyrofrequency $f_{\rm H}$, will often be more useful. The relation is

$$\omega_{\rm H} = 2\pi f_{\rm H} = \frac{eB}{m} \tag{6}$$

where

B = magnetic flux density.

In summary, our physical model of the plasma state may be visualized as a warm, compressible gas of electrons, diffused among fixed ions and molecules so that macroscopic charge neutrality is maintained. The properties of the medium can be expressed by specifying the plasma parameters, that is, by stating plasma frequency f_N , gyrofrequency f_H , electron collisional frequency \lor , electron temperature T and the ratio of specific heats of the electron gas.

The Ionosphere

The ionosphere is a particularly significant system which is composed of dilute, weakly ionized plasma in the earth's magnetic field. It is produced above the earth, primarily by the ionizing radiation from the sun incident upon the earth's upper atmosphere. The structure of the ionosphere is thus strongly dependent upon the local sun angle and the level of solar activity [*Johnson*, 1961]. It is customary to identify several distinctive levels of ionization as the D, E and F layers as shown in Figure 1.

The parameters of the ionospheric plasma are illustrated in Figures 1, 2, 3 and 4. Figure 1 shows electron density and plasma frequency as a function of altitude. Figure 2 is a similar plot of electron temperature, while the expected range of Debye length is shown in Figure 3. The expected electron collision frequency is given in Figure 4. The gyrofrequency in the ionosphere is completely determined by the strength of the earth's magnetic field. This does not change radically as a function of height in this region, and the value 1.4 MHz is a representative value.

Since the time (1902) Heavyside and Kennelly [Mitra, 1952, p. 177] first postulated the ionosphere to explain transatlantic radio communication, measurements of the properties of the ionosphere have been of great interest. Not only are the ionospheric parameters of interest for communication studies, but they are also important to studies of other geophysical phenomena such as aurora, airglow, radio noise, magnetic field fluctuations and weather. More recently, perturbation of the ionosphere by space vehicles and atomic weapons tests have emphasized the need for studies of localized regions of the ionosphere. Thus it can be seen that a knowledge of the properties of the ionosphere is very important for many activities.



Fig. 1. Normal electron distribution of the ionosphere.

and the set of the set of the set of the set of the set

مر ورا

1.

....



412.146 1.1

10.0

-

-

س بار لم

14

1772

١

. .

i





Fig. 4. Normal electron collision frequency in the ionosphere.

Ionospheric Measurement Techniques

Ionospheric parameters have been traditionally measured from the earth's surface by several techniques, notably by ionospheric sounders [Mitra, 1952, p. 219]. However, fine structure of localized regions and disturbed areas of the ionosphere can only be examined by direct, in situ measurements. Sounding rockets are often the most useful for examining these localized or disturbed regions. Satellite vehicles are, on the other hand, especially useful in obtaining worldwide coverage, otten over an extended period of time.

Three general plasma measurement techniques have been extensively exploited for rocket and satellite application. The first technique was developed from the concepts of the ground-based ionospheric sounder. That is, the electromagnetic propagation characteristics of the ionospheric plasma are measured by transmitting probing signals between the carrier vehicle and the ground. Many variations of this basic technique have been utilized even though extensive instrumentation and complex analyses are required.

The second technique is the application of the Langmuir Probe [Langmuir, 1923] to ionospheric measurements. One or more electrodes are extended from the vehicle into the ionospheric plasma and excited by various potentials. The resulting dc currents carry the measurement information. Related devices such as ion traps and resonance probes have also been developed. These all use dc potentials to collect and examine the ionized plasma particles by measuring dc currents from the collector electrodes. These techniques have nearly dominated the measurements of electron and ion temperatures and ion densities. These methods often suffer from disturbing vehicle potential perturbations; nevertheless, they have provided the only direct measurements of electron temperature.

The third method is the measurement of the plasma perturbated, RF probe impedance. Although previously well known in the laboratory, ionosphere measurements using this technique seem to have started when apparent antenna impedance changes were noted in a dipole being used in a rocket propagation experiment. This effect was then used to estimate the local electron density. Since that time, many variations of the basic technique have been used. The interaction of an antenna with the ionospheric plasma is the prime concern here, thus we will examine some of thes difference type experiments in details. Later, flight data from some of these experiments will be analyzed by applying the theory developed herein.

Three RF probes will be considered. Each technique utilizes a pair of 2.5 to 3-meter probes, sometimes referred to as a dipole antenna, mounted normal to the longitudinal vehicle axis and extended into the iono-

And a support of the support of the

£



Fig. 5. Basic concept of RF probe systems.

spheric plasma (see Figure >). In each case, the antenna is excited with a low-level RF signal (approximately 0.5 volt rms) in the 0.5 to 15-MHz range; in addition, a slowly varying bias voltage from 0 to +5 volts is placed on the antennas with respect to the vehicle skin. The bias modifies the sheath and allows the effect of the sheath to be determined. An analysis of the effects of the plasma on the antenna RF impedance or on the dc current variations as a function of frequency provides a measure of the plasma parameters.

Standing Wave Impedance Probe (SWIP)

Perhaps one of the most successful impedance probes is the Standing Wave Impedance Probe [*Ulwick et al.*, 1964]. This system measures the RF impedance of a dipole antenna which is being driven by one or two timemultiplexed RF frequencies (see Figure 6). The impedance probe frequencies are set so that one or the other is near the local plasma frequency throughout the experiment. The RF fields from the antenna excite motion in the plasma electrons which, in turn, modify the antenna impedance. This change of impedance is indicated by a change in the standing wave pattern of the voltage along an artificial transmission line connecting the driving RF oscillator and the antenna. The voltage standing wave pattern is sampled, detected and telemetered to a ground station where it is recorded for further analysis. This experiment can provide reliable impedance measurements at one or two fixed exciting frequencies.

A very simple analysis is usually employed [Ulwick et al., 1964], and this generally produces good results [Baker, et al., 1966]. Occasionally, electron temperature and other effects become important, thus pointing out the need for further theoretical development [Baker et al., 1965, and Whale, 1962].

Plasma Frequency Probe (PFP)

The Plasma Frequency Probe [Haycock and Paker, 1962] excites the antenna with a variable frequency that sweeps from about .1 to 10 MHz (see Figure 7). The resonance frequencies of the antenna impedance are sensed by determining the frequency where the phase angle between the RF antenna current and voltage is zero. A parallel resonance condition (high impedance) is expected to occur near the natural frequency of the plasma, that is, the plasma frequency. Experimentally, it has been found that a series resonance condition (low impedance) also occurs [Baker et al., 1966]. It will be shown later that this series resonance is related to the electron temperature of the plasma.



. . .

Fig. 6. Standing Wave Impedance Probe.

1000

alines of a



 Fig. 7. Plasma Frequency and Resonance Rectification Probe.

Resonance Rectification Probe (RRP)

The Resonance Rectification Probe [Takayama, Ikegami and Miyazaki, 1960; Despain, 1964] is a combination of a Langmuir Probe and an RF sweep oscillator similar to that used in the Plasma Frequency Probe (see Figure 7). A dc bias (0 to +5 volts), stepped with successive RF oscillator sweeps, is applied to the antenna. The resulting dc current is monitored. Because the RF antenna impedance changes with frequency and the dc characteristics of the antenna probe exhibit nonlinearities, the dc current is a function of the RF frequency. It had been contended that the frequency where the dc current reaches a maximum is the local electron plasma frequency [Takayama, 1960; Miyazaki et al., 1960; Ichikawa and Ikegami, 1962; Hirao and Muraoka, 1964]; however, Baker, Despain and Ulwick [1966] have shown experimentally that this conclusion is not true; in fact, the maximum is more closely associated with the series resonance frequency. Thus additional theoretical work on antenna impedance is also needed to aid in the interpretation of this experiment.

Preliminary Conclusion

The ionosphere is of general interest and exhibits interesting and complex behavior. A knowledge of the ionospheric parameters, especially in localized regions, is prerequisite to an understanding of this behavior. Some of the probe techniques for ionospheric parameter measurement require an analysis of the interaction of an RF-driven probe with the surrounding ionospheric plasma. The theories of such interactions will now be discussed in Chapter II.

Chapter II

PROBE THEORIES

The problem of interaction of a small RF excited probe with a plasma has been studied for at least sixty years [*Wilson and Gold*, 1906]. Most investigators have assumed that the impedance change is due solely to a change in the effective complex permittivity ε of a locally homogeneous ionized gas as expressed in the Appleton-Hartree Theory [*Ratciiffe*, 1962]; that is, the electrons are considered as mobile charges, free to move under the influence of electromagnetic fields. The electric current that results from such movement is accounted for by a change in the permittivity of the medium. If thermal motions and magnetic fields are ignored, the result of such a calculation is shown in Appendix A to produce the following expression for the total antenna impedance Z_{at} .

$$Z_{at} = \frac{1}{j\omega C_{o}} \left[1 - \frac{X}{1 - jZ} \right]^{-1} + R_{r} \left[1 - \frac{X}{1 - jZ} \right]^{-1/2}$$
(7)

where

°	*	free space capacitance of the probe
ω	2	radian operating frequency
ω _N	=	radian plasma frequency
ν	8	electron collision frequency
^R r	-	free space radiation resistance
X	=	$\omega_{\rm N}^2/\omega$
Z	=	v/w

For R_r and v equal to zero, a particularly simple interpretation results in the probe being considered as a capacitor C of value

1

$$C = C_{o} \left[1 - X \right] = C_{o} \left[1 - \frac{\omega_{N}^{2}}{\omega} \right]$$
(8)

This simple, idealized model has been extensively applied to interpret impedance probe results [Ulwick et al., 1964; Jackson and Pickar, 1957; Whale 1963].

A more righrous approach by King and Harrison [1960] results in some highly involved expressions; while an expression developed by DeChamps [1961] is somewhat simpler. However, neither of these works consider magnetic field or electron temperature effects and hence add little to the general formulation that we seek here. If magnetic field effects are to be considered, then the dielectric constant becomes a tensor [Rateliffe, 1962] and the geometry of the probe must be considered. The prime interest of this paper is cylindrical geometry; therefore, only solutions for this case are considered.

Perhaps the most obvious approach for a tensor dielectric constant is to apply the tensor [ε] as given by the usual Appleton-Hartree formulation [*Ratcliffe*, 1962] or the formulation of *Sen* and *Wyler* [1960]. The Sen-Wyler approach allows for collisional frequency variations with electron energy but is otherwise identical to the Appleton-Hartree tensor. *Shkarofksy* [1961] has generalized the Appleton-Hartree equations even further by considering the degree of plasma ionization as well.

The question of how a given $[\varepsilon]$ should be applied to determine antenna impedance has been considered by several workers. Herman [1963] and Crouse [1964] investigated conical geometries, while Kaiser [1962] considered biconical antennas. These workers all assumed a simple capacitor model. In Appendix A, the impedance of a cylindrical monopole,

and the set of the set

using the capacitor model and the Appleton-Hartree formulation for $[\epsilon]$ is also developed. The result is

$$Z_{a} = \frac{1}{j\omega C_{o}} \left[1 + \chi \frac{1 - 1/2 (Y/U)^{2} \sin^{2} \gamma}{U((Y/U)^{2} - 1)} \right]^{-1}$$
(9)

where

U = 1 - jZ $Y = \omega_{\rm H}/\omega$ $\gamma = Angle between antenna axis and the magnetic field$

The capacitor models discussed above ignore source current distributions and, in fact, all magnetic fields except the steady field as it appears in [ϵ]. The classical approach to antenna theory, on the other hand, generally assumes a source current distribution and all the parameters are then determined from this specification. *Bramley* [1962] used this approach to first obtain results in an isotropic region similar to those of *King*, *Harrison and Denton* [1961]. Then he extended the results to the magneto-ionic case by deriving an approximation valid for weak magnetic fields or small electron densities. *Ament et al.* [1964] considered the general case and produced an expression for impedance that requires extensive numerical in' gration and, in general, seems to be very difficult to apply. *Balmain* [1964], however, has developed some very useful impedance relations. His results appear to be the most physically satisfying of all the work mentioned above and yet are quite tractable in terms of computation. His expression is

$$Z_{a} = \frac{a}{j\omega^{2}\pi\varepsilon_{0}LK'\sqrt{F}} \left[\ln \frac{L}{R} - i - \ln \frac{a+\sqrt{F}}{2F} \right]$$
(10)

where

14 M

$$F = Sin^{2} + a^{2}Cos^{2}\gamma$$

$$a^{2} = K'/K_{o}$$

$$K' = 1 - \frac{XU}{U^{2} - \gamma^{2}}$$

$$K_{o} = 1 - \frac{X}{U}$$

None of the above derivations includes the explicit effects of finite electron temperature. That is, a cold, yet lossy medium is always assumed. However, electron temperature can appreciably perturbate the impedance of an antenna probe in a plasma, other than its effect on collisional frequency. *Whale* [1963] observed such effects in an impedance probe experiment, primarily as an energy loss mechanism. It will also be shown later that the experimentally determined antenna series resonance frequencies of *Baker*, *Despain and Ulwick* [1966] are indeed related to the electron temperature as they suspected. Thus electron temperature must be considered in a derivation of antenna impedance.

Several workers have attempted to include electron temperature as a parameter. Cohen [1961] presented a thorough theoretical discussion of sources in isotropic warm plasmas. Whale [1963] developed some theory to explain his experimental results mentioned above. Balmain [1964] applied Cohen's equations to his problem for the case of no magnetic field and derived an approximate impedance relation. In a similar manner, Fejer [1964] theoretically investigated spherical geometry without magnetic field and predicted a series resonance below the plasma frequency directly dependent upon the electron temperature. Despain [1965], in preliminary work to this report, investigated cylindrical geometry with similar results. The work of Wait [1964] should also be mentioned as it concerns slot antennas in warm plasmas. An attempt to develop a permittivity tensor [ϵ]

and the second second

valid for finite electron temperature and to apply this $[\varepsilon]$ to the capacitor model of the antenna met with failure (see last section of Appendix A). The impedance expression that resulted did not agree even approximately with the other theoretical work nor did it exhibit behavior know, experimentally to be characteristic of such systems. Further discussion is included in Appendix A.

In reviewing the work mentioned above, it is apparent that further theoretical work is needed on the electron temperature effects on cylindrical antennas, especially in the presence of magnetic fields and electron collisions. Therefore, the present investigation was initiated in order to relate electron density, temperature and collisional frequency to antenna impedance.

Chapter III

DERIVATION OF ANTENNA IMPEDANCE

Introduction

The basic assumption of this derivation is that the electrons behave as a continuous fluid and the effect of all electron interactions may be represented by various forces on the electron fluid. This view of a plasma is similar to that of *Spitzer* [1962], *Cohen* [1961] and *Fejer* [1964]. This approach allows the electron temperature effects to be taken into account as a property of the electron fluid. Besides the effect of electron density and temperature, the effects of an external constant magnetic field and electron collisions are also included. It is further assumed that the undisturbed plasma is neutral and homogeneous. Later some restricted space variations of the plasma parameters are allowed near the antenna probe surface by using a simple sheath model.

The antenna probe is taken to be an isolated, electrically short cylinder, whose length to radius ratio is large enough so that end effects can be ignored. Because of the long wavelength of the excitation, electromagnetic effects are assumed to be small in comparison to the plasma effects, and thus the antenna impedance may be calculated from the effective quasi-static electric fields of the antenna. It is further assumed that the excitation level is very low so that linearized equations can be used and only first order effects considered. Exp (jwt) time dependence and MKS units are assumed throughout.

The strategy of the derivation is to first develop a force equation that relates all the forces on an element of the electron fluid. From this equation, the velocity of the electron fluid is found. The velocity expression is

and the second second second second second

العبر ال

حائدين والمريد هويدنها

then substituted into the continuity equation and a second order partial differential equation is derived in terms of the scalar parameters n (electron density variation) and ϕ (electric potential). Poisson's equation, also a second order partial differential equation in ϕ and n, is used to simplify the first equation. A solution of this equation for n leads directly to a solution of Poisson's equation. Boundary conditions can be applied to determine a solution for the potential ϕ . Once ϕ is known, the fields surrounding the antenna can be easily determined, and the antenna impedance can be found as the complex ratio of antenna potential to antenna current. Sheath effects are then added as an additional effect.

Fundamental Equations

Consider the forces that are exerted on a volume element dV of the electron fluid. The force F_p due to the variations of the pressure p is

$$\vec{dF_p} = -(\nabla p) dV \tag{11}$$

The Lorentz force F_{L} on the element is

$$d\vec{F}_{I} = -Ne[\vec{E} + \vec{v} \times \vec{B}] dV$$
(12)

where

- N = average electron density (constant)
- e = electronic charge
- \vec{v} = average velocity of the electrons in the element
- \vec{B} = external constant magnetic field
- \vec{E} = electric field
- p = pressure variation from its mean value

and the force due to electron collisions is giver in terms of the effective electron collision frequency v as follows

$$d\vec{F}_{c} = -vNm \vec{v} dV$$
(13)

where m is the electronic mass.

Applying Newton's Law, we equate these forces to the mass of the element times its acceleration to produce the force equation

$$\operatorname{Nm} \frac{d\vec{v}}{dt} dV = -(\nabla p) dV - \operatorname{Ne}[\vec{E} + \vec{v} \times \vec{B}] dV - v \operatorname{Nm} \vec{v} dV \qquad (14)$$

or

$$\mathbf{j}\omega\mathbf{N}\mathbf{m}\mathbf{v} = -\nabla \mathbf{p} - \mathbf{N}\mathbf{e} \left[\vec{\mathbf{E}} + \vec{\mathbf{v}} \times \vec{\mathbf{B}}\right] - \mathbf{v}\mathbf{N}\mathbf{m}\mathbf{v}$$
(15)

Now ∇p may be written according to the chain rule of differentiation as

$$\nabla \mathbf{p} = \frac{\partial \mathbf{p}}{\partial \rho} \nabla \mathbf{p} \tag{16}$$

where ρ is the mass density. The adiabatic law relates p and ρ

A TARE LART & AND TREE TREE

$$\mathbf{p} = \mathbf{C}^{*} \boldsymbol{\rho}^{\boldsymbol{\gamma}^{*}}$$
(17)

where $\gamma' = ratio$ of specific heats. As discussed in Chapter I, γ' has the value of 3.0 for an electron gas provided $\omega >> v$:

Now

$$\frac{\partial \mathbf{p}}{\partial \rho} = 3C'_{\rho}^{2} \tag{18}$$

$$= 3p/\rho \tag{19}$$

but from the equation of state

 $\mathbf{p} = \mathbf{K} \mathbf{T} \mathbf{n} \tag{20}$

and the second second

where

K = Boltzmann's constant
T = electron temperature
n = variation of electron density from its mean value,

and by definition

$$\rho = mn \tag{21}$$

thus

$$\frac{\partial \mathbf{p}}{\partial \rho} = 3KT/m \tag{22}$$

At this point, it is interesting to note that $\frac{\partial p}{\partial \rho}$ is just the square f the propagation velocity μ that describes the velocity of longitudinal (sound) waves in compressible fluids. Thus

$$\mathbf{p} = \mu^2 \nabla(\mathbf{mn}) \tag{23}$$

where

$$\mu^2 = 3KT/m$$

Thus (15) is, in linearized parameters

$$j\omega Nm\vec{v} = -\mu^2 \nabla(mn) - Ne \left[\vec{E} + \vec{v} \times \vec{B}\right] - \nu Nm\vec{v}$$
(24)

or

$$N[j_{\omega}\vec{v} + \omega_{H}\vec{v} \times \hat{\zeta} + \nu\vec{v}] = -\mu^{2}\nabla n + (Ne/m) \nabla \Phi$$
(25)

· 78 · 14

where

$$\omega_{\rm H}$$
 = eB/m, electron gyrofrequency
- ζ = direction of magnetic field (unit vector)
- \$ = scalar potential

Up to this point, the force equation is valid in any system of coordinates. A further attack on the problem will now require that the cylindrical coordinates \hat{r} , $\hat{\theta}$ and \hat{z} be applied. The axis of the antenna probe has been chosen to coincide with the \hat{z} axis (see Figure 8).





The next step is to determine the velocity v in terms of n and Φ . Because v is entangled in a curl operation, this is not a straight forward process. We begin by solving for the velocity components separately. In the r direction,

$$j\omega N \left[Uv_{r} - jY(v_{\theta}\zeta_{z} - v_{z}\zeta_{\theta}) \right] = -\mu^{2} \frac{\partial n}{\partial r} + \frac{Ne}{m} \frac{\partial \Phi}{\partial r}$$
(26)

In the θ direction

$$j\omega N \left[Uv_{\theta} - jY(v_{z}\zeta_{r} - v_{r}\zeta_{z}) \right] = -\mu^{2} \frac{1}{r} \frac{\partial n}{\partial \theta} + \frac{Ne}{m} \frac{1}{r} \frac{\partial \Phi}{\partial \theta}$$
(27)

In the z direction

$$j\omega N \left[Uv_{z} - jY(v_{r}\zeta_{\theta} - v_{\theta}\zeta_{r})\right] = -\mu^{2} \frac{\partial n}{\partial z} + \frac{Ne}{m} \frac{\partial \Phi}{\partial z}$$
(28)

where

However because of symmetry

and many a

Contraction of the

WEL

a more than a second

$$\frac{\partial \mathbf{n}}{\partial z} = 0$$
 and $\frac{\partial \Phi}{\partial z} = 0$

and thus from (28)

$$\mathbf{v}_{\mathbf{z}} = \mathbf{j} W(\mathbf{v}_{\mathbf{r}} \boldsymbol{\zeta}_{\theta} - \mathbf{v}_{\theta} \boldsymbol{\zeta}_{\mathbf{r}})$$
(29)

or

$$\mathbf{v}_{\mathbf{z}} = \mathbf{j}\mathbf{v}_{\mathbf{r}}^{W}_{\theta} - \mathbf{j}\mathbf{v}_{\theta}^{W}_{\mathbf{r}}$$
(30)

-

$$j\omega UN \left[v_{r} - jW_{z}v_{\theta} + jW_{\theta} (jv_{r}W_{\theta} - jv_{\theta}W_{r}) \right] = -\mu^{2} \frac{\partial n}{\partial r} + \frac{Ne}{m} \frac{\partial \Phi}{\partial r}$$
(31)

$$j\omega UN \left[v_{\theta} + jW_{z}v_{r} + jW_{r}(jv_{r}W_{\theta} - jv_{\theta}W_{r})\right] = -\mu^{2} \frac{1}{r} \frac{\partial n}{\partial \theta} + \frac{Ne}{m} \frac{1}{r} \frac{\partial \Phi}{\partial \theta} \quad (32)$$

where

3

$$W = Y/U$$
$$W_r = W\zeta_r$$
$$W_{\theta} = W\zeta_{\theta}$$
$$W_z = W\zeta_z$$

or

$$\mathbf{v}_{\mathbf{r}}(1-\mathbf{W}_{\theta}^{2}) \equiv \mathbf{j}\boldsymbol{\beta}_{\mathbf{r}} - \mathbf{v}_{\theta}(\mathbf{W}_{\mathbf{r}}\mathbf{W}_{\theta} - \mathbf{j}\mathbf{W}_{z})$$
(33)

$$\mathbf{v}_{\theta}(1 - W_{\mathbf{r}}^2) = \mathbf{j}\beta_{\theta} - \mathbf{v}_{\mathbf{r}}(W_{\mathbf{r}}W_{\theta} + \mathbf{j}W_{\mathbf{z}})$$
(34)

where

$$\beta_{\mathbf{r}} = \beta_{\mathbf{n}} \frac{\partial \mathbf{n}}{\partial \mathbf{r}} - \beta_{\mathbf{p}} \frac{\partial \Phi}{\partial \mathbf{r}}$$

$$\beta_{\theta} = \beta_{\mathbf{n}} \frac{1}{\mathbf{r}} \frac{\partial \mathbf{n}}{\partial \theta} - \beta_{\mathbf{p}} \frac{1}{\mathbf{r}} \frac{\partial \Phi}{\partial \theta}$$

$$\beta_{\mathbf{n}} = \frac{\mu^{2}}{UN\omega}$$

$$\beta_{\mathbf{p}} = \frac{\mathbf{e}}{Um\omega}$$

now with the aid of the relation

$$W_{r}^{2} + W_{\theta}^{2} + W_{z}^{2} = W^{2}$$
 (35)

explicit values of v_r and v_θ can be obtained. By solving the equations simultaneously, we find that

$$v_{r} = j \frac{\beta_{r} (1 - w_{r}^{2}) - \beta_{\theta} (w_{r} w_{\theta} - j w_{z})}{1 - w^{2}}$$
 (36)

and

$$\mathbf{v}_{0} = -\mathbf{j} \frac{\beta_{\mathbf{r}} (\mathbf{W}_{\mathbf{r}} \mathbf{W}_{\theta} + \mathbf{j} \mathbf{W}_{z}) - \beta_{\theta} [1 - \mathbf{W}_{\theta}^{2}]}{1 - \mathbf{W}^{2}}$$
(37)

Now

$$\nabla \cdot \vec{v} = \frac{v}{r} + \frac{\partial v}{\partial r} + \frac{1}{r} \frac{\partial v}{\partial \theta} + \frac{\partial v}{\partial z}$$
(38)

Hence $\frac{\partial \mathbf{v}_{\mathbf{r}}}{\partial \mathbf{r}}$, $\frac{\partial \mathbf{v}_{\theta}}{\partial \theta}$ and $\frac{\partial \mathbf{v}_{z}}{\partial z}$ must be calculated.

$$\frac{\partial \mathbf{v}_{\mathbf{r}}}{\partial \mathbf{r}} = \left[\frac{1}{1+W^{2}}\right] \left[\frac{\partial \beta_{\mathbf{r}}}{\partial \mathbf{r}} \left(1 - W_{\mathbf{r}}^{2}\right) - \frac{\partial \beta_{\theta}}{\partial \mathbf{r}} \left(W_{\mathbf{r}}W_{\theta} - \mathbf{j}W_{\mathbf{z}}\right)\right]$$
(39)
$$\frac{\partial \mathbf{v}_{\theta}}{\partial \theta} = \left[\frac{-1}{1+W^{2}}\right] \left[\frac{\partial \beta_{\mathbf{r}}}{\partial \theta} \left(W_{\mathbf{r}}W_{\theta} + \mathbf{j}W_{\mathbf{z}}\right) + \beta_{\mathbf{r}} \left(\frac{\partial W_{\mathbf{r}}}{\partial \theta} W_{\theta} + W_{\mathbf{r}} - \frac{\partial W_{\theta}}{\partial \theta} + \mathbf{j} - \frac{\partial W_{\mathbf{z}}}{\partial \theta}\right) - \frac{\partial \beta_{\theta}}{\partial \theta} \left(1 - W_{\theta}^{2}\right) - 2\beta_{\theta} \left(W_{\theta} - \frac{\partial W_{\theta}}{\partial \theta}\right)\right]$$
(40)

$$\frac{\partial \mathbf{v}}{\partial z} = 0 \tag{41}$$

But

$$\frac{\partial W_{\mathbf{r}}}{\partial \theta} = +W_{\theta}$$
(42)

$$\frac{\partial W_{\theta}}{\partial \theta} = -W_{r}$$
(43)

and the second second

a monotone as another

$$\frac{\partial W}{\partial \theta} = 0 \tag{44}$$

Thus

¥

$$\frac{\partial \beta_{\mathbf{r}}}{\partial \mathbf{r}} = \beta_{\mathbf{n}} \frac{\partial^2 \mathbf{n}}{\partial \mathbf{r}^2} - \beta_{\mathbf{p}} \frac{\partial^2 \Phi}{\partial \mathbf{r}^2}$$
(45)

$$\frac{\partial \beta_{\mathbf{r}}}{\partial \theta} = \beta_{\mathbf{n}} \frac{\partial^2 \mathbf{n}}{\partial \mathbf{r} \partial \theta} - \beta_{\mathbf{p}} \frac{\partial^2 \phi}{\partial \mathbf{r} \partial \theta}$$
(46)

$$\frac{\partial \beta_{\theta}}{\partial r} = \beta_{n} \frac{1}{r} \frac{\partial^{2} n}{\partial r \partial \theta} - \beta_{p} \frac{1}{r} \frac{\partial^{2} \phi}{\partial r \partial \theta} - \beta_{n} \frac{1}{r^{2}} \frac{\partial n}{\partial \theta} + \beta_{p} \frac{1}{r^{2}} \frac{\partial \phi}{\partial \theta}$$
(47)

$$\frac{\partial \beta_{\theta}}{\partial \theta} = \beta_{n} \frac{1}{r} \frac{\partial^{2} n}{\partial \theta^{2}} - \beta_{p} \frac{1}{r} \frac{\partial^{2} \phi}{\partial \theta^{2}}$$
(48)

and thus

$$\nabla \cdot \vec{v} = \left[\frac{1}{1-W^2}\right] \left[\left(\frac{1}{r}\beta_n\frac{\partial n}{\partial r} - \frac{1}{r}\beta_p\frac{\partial \phi}{\partial r}\right) (1-W_r^2) - \left(\frac{1}{r^2}\beta_n\frac{\partial n}{\partial \theta} - \frac{1}{r^2}\beta_p\frac{\partial \phi}{\partial \theta}\right) (W_rW_\theta - jW_z) + \left(\beta_n\frac{\partial^2 n}{\partial r^2} - \beta_p\frac{\partial^2 \phi}{\partial r^2}\right) (1-W_r^2) - \left(\beta_n\frac{1}{r}\frac{\partial^2 n}{\partial r\partial \theta} - \beta_p\frac{1}{r}\frac{\partial^2 \phi}{\partial r\partial \theta}\right) (W_rW_\theta - jW_z) - \left(\beta_n\frac{1}{r}\frac{\partial^2 n}{\partial r\partial \theta} - \beta_p\frac{1}{r}\frac{\partial^2 \phi}{\partial r\partial \theta}\right) (W_rW_\theta + jW_z) + \left(\beta_n\frac{1}{r^2}\frac{\partial n}{\partial \theta} - \beta_p\frac{1}{r^2}\frac{\partial \phi}{\partial \theta}\right) (W_rW_\theta - jW_z) + \left(\beta_n\frac{1}{r^2}\frac{\partial n}{\partial \theta} - \beta_p\frac{1}{r^2}\frac{\partial \phi}{\partial \theta}\right) (W_rW_\theta - jW_z)$$

<u>.</u>

and a section of the section of the

-

$$+ \left(\beta_{n} \frac{1}{r^{2}} \frac{\partial^{2} n}{\partial \theta^{2}} - \beta_{p} \frac{1}{r^{2}} \frac{\partial^{2} \phi}{\partial \theta^{2}}\right) (1 - W_{\theta}^{2})$$

$$- \left(\beta_{n} \frac{1}{r} \frac{\partial n}{\partial r} - \beta_{p} \frac{1}{r} \frac{\partial \phi}{\partial r}\right) (W_{\theta}^{2} - W_{r}^{2})$$

$$- 2\left(\beta_{n} \frac{1}{r^{2}} \frac{\partial n}{\partial \theta} - \beta_{p} \frac{1}{r^{2}} \frac{\partial \phi}{\partial \theta}\right) (W_{\theta} W_{r})]$$

$$(49)$$

This can be reduced to

$$\nabla \cdot \vec{v} = \left[\frac{1}{1-W^2}\right] \left[(\beta_n \nabla^2 n - \beta_p \nabla^2 \phi) - W^2 \sin^2 \gamma (\beta_n S(n) - \beta_p S(\phi)) \right]$$
(50)

where

-

$$S(\mathbf{x}) = \cos^{2}\theta \frac{\partial^{2}\mathbf{x}}{\partial r^{2}} - 2 \sin\theta \cos\theta \frac{1}{r} \frac{\partial^{2}\mathbf{x}}{\partial r^{\partial \theta}} + \sin^{2}\theta \frac{1}{r^{2}} \frac{\partial^{2}\mathbf{x}}{\partial \theta^{2}} + \sin^{2}\theta \frac{1}{r^{2}} \frac{\partial^{2}\mathbf{x}}{\partial \theta^{2}} + \sin^{2}\theta \frac{1}{r} \frac{\partial \mathbf{x}}{\partial r} + 2 \sin\theta \cos\theta \frac{1}{r^{2}} \frac{\partial \mathbf{x}}{\partial \theta}$$
(51)

This result can now be substituted into the continuity equation

$$N(\nabla \cdot \vec{v}) + j\omega n = 0 \tag{52}$$

and Poisson's equation

$$\nabla^2 \phi = ne/\varepsilon_0$$
 (53)

can also be applied to yield the result

$$N\left[\frac{j}{1-W^{2}}\right]\left[\frac{\mu^{2}}{UN\omega}\nabla^{2}n - \frac{e}{Um\omega}\left(ne/\varepsilon_{0}\right) - W^{2}Sin^{2}\gamma(\beta_{n}S(n) - \beta_{p}S(\Phi))\right] + j\omega n = 0$$
(54)

and the second second

Simplifying

$$\nabla^2 \mathbf{n} = -\alpha^2 \mathbf{n} + W^2 \operatorname{Sin}^2 \gamma [S(\mathbf{n}) - U(\omega_N^2 / \mu^2)(\varepsilon_0 / \mathbf{e}) S(\Phi)]$$
(55)

where

$$\alpha^{2} = (\psi^{2} - 1) \omega_{N}^{2} / \mu^{2}$$
(56)

$$\psi^2 = (U^2 - Y^2)/UX$$
 (57)

$$\omega_{\rm N}^2 = {\rm Ne}^2/{\rm m}\varepsilon_{\rm o}$$
(58)

$$x = \omega_N^2 / \omega^2$$
 (59)

$$W = Y/U \tag{60}$$

For either $\gamma << 1$ or W<<1, this equation can be solved directly. However, the general case requires the solution for a pair of coupled, second order partial differential equations whose parameters are functions of the space coordinates. Clearly a straight forward analytic solution seems to be out of the realm of possibility, and it appears that an approximation technique will be required in order to solve the generalized system equations. In any case, the solution for $\gamma = 0$ is still of the highest interest since this only mildly restricts the applicability of the theory. If the restriction $\gamma = 0$ had been applied from the beginning, the derivation would have been a little less complicated; however by developing (55), we now have an equation that can possibly be solved at a later time to provide an estimate of antenna impedance for $\gamma \neq 0$. Thus for the purposes of this report, it will be sufficient to limit the solution and only solve the restricted equation (61).

$$\nabla^2 \mathbf{n} = -\alpha^2 \mathbf{n} \tag{61}$$

Thus the plasma may be described by the system equations (53) and (61). For $\gamma = 0$ however, symmetry exists in the θ direction so that only the r coordinate need be considered. Thus it is sufficient to solve the set of equations

$$\nabla_{\mathbf{r}}^{2} \phi = \mathbf{n} \mathbf{e} / \varepsilon_{0}$$
 (62)

$$\nabla_r^2 n = -\alpha^2 n \tag{63}$$

where the r subscript indicates that only the r component is under consideration.

Solution of System Equations

Equation (63) may be expanded and transformed by performing the indicated operations and allowing $x = \alpha r$.

$$\frac{d^2 n}{dx^2} + \frac{1}{x} \frac{dn}{dx} + n = 0$$
(64)

This is the familiar Bessel's equation of zero order. Hence, it has, as solutions, all of the various Bessel functions of order zero. Since x is in general a complex variable, it is convenient to use a linear combination of the Hankel functions $H_0(x)$ and $H_0^{(2)}(x)$ [sometimes $H_0(x)$ is written as $H_0^{(1)}(x)$]. In general, there are two values of x to be considered, $x = -\sqrt{\alpha^2} r$ and $x = +\sqrt{\alpha^2} r$. However, it is a property of the Hankel functions [Jahnke and Emde, 1945] that $H_0^{(2)}(-x) = H_0(x)$ and that $H_0(-x) = H_0^{(2)}(x)$. Thus we need to consider only the one solution of x which lies in the first two quadrants of the complex plane. Then for large values of x, that is, at distances far removed from the antenna, we require that the solution for n, the density variations, become small. Thus since $H_0^{(2)}(x)$ approaches infinity as x approaches zero, only H(x) can be an acceptable solution.

ار در بار بار بار بار میکند. در این از میکند میکند در میکند در میکند میکند. از میکند بار از میکند میکند. میکند. میکند بار بار بار میکند میکند در میکند میکند در میکند میکند میکند میکند میکند. Therefore,

$$n = n H_0(\alpha r)$$
(65)

where

- n_{o} = arbitrary constant to be determined by boundary conditions
- α = the square root of α^2 that lies in the top half of the complex plane.

The solution to the homogeneous part of the system equation (62) may be written as

$$\Phi = C_1 \ln(r/L) \tag{66}$$

where C_1 is an arbitrary constant yet to be determined and L is the length of the antenna. This form of solution was chosen to produce the correct form of potential near the surface of a long, thin, charged rod in free space. Since (62) is very similar to (63), a solution of the form

$$\Phi = C_2 H_0(\alpha r) \tag{67}$$

would also be expected to satisfy (62). Such is indeed the case and the total solution may be written as

$$\Phi = C_1 \ln(r/L) - (e_0 / \varepsilon_0 \alpha^2) H_0(\alpha r)$$
(68)

and the second second

الإلىيانة ورابور الحمر الداسيس منيس

where $C_2 = -n_0 e/\epsilon_0 \alpha^2$ has been chosen so as to satisfy (62).

Boundary Conditions

General solutions for n and Φ now exist; however, the arbitrary constants C_1 and n have not yet been determined. These constants can be obtained by a consideration of boundary conditions near the antenna surface. Our original pair of second order differential equations require the specification of four independent boundary conditions to determine n and ϕ . Two of these conditions were fixed in the derivation above when both n and ϕ were required to approach zero as the distance from the antenna increased indefinitely. Only one of the other two conditions need be specified if only the antenna impedance is desired. This is true since we desire not a knowledge of ϕ or n but only a knowledge of the ratio of antenna voltage to current. Ultimately, one of the arbitrary constants n_o or C₁ must cancel out of the impedance expression. Thus if a boundary condition at the antenna surface can be specified such that C₁ is determined, it will be possible to later cancel out n_o and completely determine the antenna impedance.

It has previously been assumed that the plasma surrounding the antenna is homogeneous; that is, that no sheath exists. Immediately inside the antenna-plasma boundary, the electrons are no longer in a free, gaseous state and are thus essentially restrained from any movement. Hence, it is assumed that the velocity v is zero at the antenna surface.

This is the same boundary condition used by *Fejer* [1964] in a similar problem. As he points out, it does not correspond exactly to the physical situation, but only approximates it. More exact boundary conditions can become very difficult, but they can also lead to a more general solution. *Balmain* [1965], for example, has considered the complex boundary conditions that actually exist at a probe-plasma boundary, and it is possible that his technique could be applied in this case. However, it is not necessary to include all of these complex conditions if only high frequency, small amplitude effects are of interest as is the case in this derivation.

For v = 0 at the antenna surface (r = R), equation (25) becomes at the surface

$$[\mu^2 \nabla_r \mathbf{n}]_{r=R} = [(Ne/m) \nabla_r \phi]_{r=R}$$
(69)

$$\frac{\mu^2 \mathbf{e}}{\epsilon_0} \left[\frac{\partial \mathbf{n}}{\partial \mathbf{r}} \right]_{\mathbf{r}=\mathbf{R}} = \omega_{\mathrm{N}}^2 \left[\frac{\partial \Phi}{\partial \mathbf{r}} \right]_{\mathbf{r}=\mathbf{R}}$$
(70)

but from (68) and the fact that $\frac{d}{dx} [H_o(x)] = -H_1(x)$

$$\frac{\partial \Phi}{\partial r} = C_1/r + (e_0/\epsilon_0 \alpha) H_1(\alpha r)$$
(71)

and similarly

$$\frac{\partial n}{\partial r} = -n_0 \alpha H_1(\alpha r)$$
(72)

Thus

Ĩ

ſ

-

Bannany-

S

ŧ

$$-\mu^{2}(e/\varepsilon_{o})(n_{o}\alpha H_{1}(\alpha P)) = \omega_{N}^{2}(C_{1}/R + (en_{o}/\varepsilon_{o}\alpha)H_{1}(\alpha R))$$
(73)

or

$$C_{1} = -(e_{0}R/\epsilon_{0}\alpha)H_{1}(\alpha R) \psi^{2}$$
(74)

since

en servit,

$$\psi^{2} = 1 + \mu^{2} \alpha^{2} / \omega_{N}^{2}$$
(75)

Thus the expression for the potential, (68), becomes

and the second second

$$\Phi = -(n_o e/\epsilon_o \alpha^2) H_o (\alpha r) + \alpha R \psi^2 H_1 (\alpha R) \ln (r/L)$$
(76)

Antenna Impedance

Impedance is defined as the complex ratio of voltage to current. In the case of the antenna under consideration here, the voltage is just the potential at the surface of the antenna and the current is just the displacement current summed over the antenna surface. Thus

'0)

59)

$$Z_{a} = \frac{\Phi(R)}{\int_{D} dS}$$
(77)

or since

1)

$$\vec{J}_{D} = \frac{\partial \vec{D}}{\partial t} = j\omega \vec{D}$$
(78)

$$Z_{a} = \frac{\Phi(R)}{2\pi RLj \omega \epsilon_{o} E_{r}(R)}$$
(79)

2)

but

3)

$$E_{\mathbf{r}}(\mathbf{R}) = -\left[\frac{\partial \Phi}{\partial \mathbf{r}}\right]_{\mathbf{r}=\mathbf{R}}$$
(80)

and

$$\frac{\partial \Phi}{\partial \mathbf{r}} = (\mathbf{n_0} \mathbf{e}/\varepsilon_0 \alpha^2) (\alpha H_1(\alpha \mathbf{r}) - \alpha R \psi^2 H_1(\alpha R)/\mathbf{r})$$

Thus (81) becomes

)

$$Z_{a} = \frac{1}{j\omega^{2}\pi RL\varepsilon_{o}} - \frac{H_{o}(\alpha R) - \alpha R\psi^{2}H_{1}(\alpha R)\ln(L/R)}{\alpha H_{1}(\alpha R) - \alpha R\psi^{2}H_{1}(\alpha R)/R}$$
(82)

or

$$Z_{a} = \frac{\ln(L/R)}{j\omega 2\pi\varepsilon_{o}L} \frac{H_{o}(\alpha R)/\alpha RH_{1}(\alpha R) \ln(L/R) - \psi^{2}}{1 - \psi^{2}}$$
(83)

(81)

Now the free space capacitance of a long thin rod is easily shown to be

$$C_{o} = 2\pi\varepsilon_{o}L/\ln(L/R)$$
(84)

Thus

$$Z_{a} = \frac{-i}{\omega C_{o}} \left[\frac{\phi(\alpha R) / \ln(L/R) - \psi^{2}}{1 - \psi^{2}} \right]$$
(85)

where

$$\phi(\alpha R) = H_{o}(\alpha R) / \alpha R H_{1}(\alpha R)$$
(86)

This is the impedance of a monopole antenna in a magneto-ionic plasma with the antenna axis aligned with the magnetic field.

The expression includes electron collision effects as a parameter in α . If $\nu = 0$ and $X \ge 1$, then α becomes entirely imaginary and ϕ can be expressed in terms of the real modified Bessel functions of the second kind $K_0(x)$ and $K_1(x)$

Thus

$$\phi(ijx) = \frac{H_{o}(ijx)}{ijxH_{1}(ijx)} = \frac{K_{o}(x)}{xK_{1}(x)}$$
(87)

We will find this result useful in some cases where v = 0.

If
$$\omega_{\rm H} = 0$$
, then ψ^2 becomes
 $\psi^2 = U/X$ (88)

while if v = 0 as well, then a particularly simple expression results

$$\psi = \omega/\omega_{\rm N} \tag{89}$$

A.

39

and

$$\alpha^{2} = (\omega^{2} - \omega_{N}^{2})/\mu^{2}$$
(90)

or

$$\alpha' = \left[\left(\omega_{\rm N}^2 - \omega^2 \right) / \mu^2 \right]^{1/2} \tag{91}$$

where

$$\alpha'^2 = -\alpha^2 \tag{92}$$

This expression is useful when (87) is used to determine ϕ as

$$\phi(\alpha^{*}R) = \frac{K_{0}(\alpha^{*}R)}{\alpha^{*}RK_{1}(\alpha^{*}R)}$$
(93)

Sheath Effects

The first order effects of the plasma sheath on the antenna impedance can be taken into account by use of a very simple physical model. As long as the dc potential of the antenna is below the plasma potential (this is usually the case), a region of electron depletion will surround the antenna. The mechanism of this sheath formation is discussed in Chapter I. The model assumes that no electrons exist within a region of S Debye lengths of the antenna. Generally S will vary from 0 when the antenna is at the plasma potential, through about 4 when no net dc current is allowed to flow to the antenna, and up to about 10 if large negative potentials are applied to the probe. Thus the effective radius R_S of the sheath is

$$R_{S} = R_{A} + S\lambda_{D}$$
(94)

The capacitance between the antenna and the surface of the plasma is then the capacitance of two concentric cylinders of radii R_A and R_S .

$$C_{\rm S} = 2\pi\epsilon_{\rm o} L/\ln(R_{\rm S}/R_{\rm A})$$
(95)

The effective antenna impedance is then the impedance of this capacitor in series with the impedance of an antenna of radius R_S since the plasma begins at a radius of R_S . The general impedance relation is then

$$Z_{a} = \frac{1}{j\omega C_{S}} + \frac{1}{j\omega C_{O}} - \frac{\phi(\alpha R_{S})/\ln(L/R_{S}) - \psi^{2}}{1 - \psi^{2}}$$
(96)

where

$$C_{o} = 2\pi\varepsilon_{o} L/\ln(L/R_{S})$$
(97)

The derivation of the antenna impedance is now complete. It can be seen that the major goals have been met; that is the effects of a hot, lossy, magneto-ionic plasma on antenna impedance have been calculated. It should be noted that this expression is valid when the axis of the antenna is parallel to the magnetic field. A summary of the final expression and related parameters is tabulated in Table 1.

Antenna Impedance		$z_{a} = \frac{1}{j_{u}C_{S}} + \frac{1}{j_{w}C_{o}} \left[\frac{\phi(\alpha R_{S})/\ln(L/R_{S}) - \psi^{2}}{1 - \psi^{2}} \right]$
Sheath Capacitance		C _S = 2πε _o L/ln(R _S /R _A)
Antenna System Capacitance		$C_{o} = 2\pi\varepsilon_{o}L/\ln(L/R_{S})$
Sheath Radius		$R_{S} = R_{A} + S_{A}_{D}$
Debye Length		$\lambda_{\rm D} = ({\rm K}/4\pi^2{\rm m})^{1/2} ({\rm T}^{1/2}/f_{\rm N})$
Antenna Length	L	φ(αR) = H _o (αR)/αRH ₁ (αR)
Antenna Radius	RA	$\psi^2 = (u^2 - \gamma^2)/ux$
Exciting Frequency (radian)	З	$\alpha^2 = (\psi^2 - 1) \omega_N^2 / \mu^2$
Plasma Frequency (radian)	N 3	μ ² = 3KT/m
Collision. Frequency	2	U = 1-j2
Gyrofrequency (radian)	н _э	$x = \frac{2}{N}/\omega^2$
Electron Temperature	[-1	m/Hm ■ X
Electronic Mass	ŭ	2 = v/w
Boltzmann's Constant	K	
Sheath Scaling Constant	'n	

** -

- 13

....

Summary of Antenna Impedance Theory

TABLE I

41

Þ

Chapter IV

COMPARISON OF RESULTS

Introduction

It is desirable to empirically examine the impedance expression developed in Chapter III in order to compare it to both experimental data and other theories. Generally, other theoretical expressions are of completely different form and often either gross approximations or empirical methods must be applied before a favorable comparison can be discerned. Thus, the theoretical expression developed here and the other theoretical results of Chapter II have been programmed for digital computer analysis so that empircal comparisons can be carried out.

If the conventional free space expression for antenna impedance of a short dipole is examined [Balmain, 1964, p. 56], it is found that the impedance in the low frequency limit is just the impedance of the free space capacitance given by

$$C_{\rm c} = 2\pi\epsilon_{\rm c} L/(\ln(L/R) - 1)$$
(98)

This expression is the same as the C_0 derived in Chapter III except for the -1 term. This term represents the end effects that were ignored in the formulation of Chapter III. The above expression could be used to define C_0 , but it is even more preferable to use an experimentally measured value of free space capacitance so that all perturbating influences can be taken into account (rocket body, etc.). Thus the actual mean antenna radius will be used in the impedance expressions, but the length of the antenna in the calculations will be changed from its true value to a value that will produce the correct value of C_0 as determined by measurements.

It could be argued that end effects could modify more than just the free space capacitance. These effects should be small, however, since the plasma medium tends to shield the antenna from any external disturbing influences at distances greater than a few Debye lengths (see Chapter I). This is especially true at frequencies below the plasma frequency and at frequencies above the plasma frequency, the end effects are not especially critical.

The empirical comparison of impedance theories can be approached from many directions. However, it is desirable to examine theoretical results so that they can easily be compared to experimental measurements as well. Thus the chosen antenna dimensions are typical of experimental antennas. In analogy with the Plasma Frequency Probe, the plasma parameters can all be held constant while the exciting frequency is swept through a wide range of values (.1 to 10 MHz) and the impedance determined. The theory can also be explored by fixing the exciting frequency and determining the antenna impedance as a function of the dominant plasma variable, plasma frequency with electron temperature as a parameter. This situation will then correspond to the Standing Wave Impedance Probe. It is also possible to plot antenna resistance versus antenna reactance with both plasma frequency and temperature as parameters. Perhaps only the dominate characteristics of the impedance are desired, such as the series and parallel resonance frequencies of the antenna. This situation actually more closely approximates the plasma frequency probe which determines only the frequencies of zero phase or resonance. Thus, these four methods will all be used to illustrate antenna impedance throughout the remainder of this paper.

A computer program, (SWP4MD) was written to plot the antenna impedance as a function of either plasma frequency or exciting frequency. Various subroutines were written to calculate the antenna impedance according to the

different theories of interest. Thus, empirical impedance plots of any of these theories could be obtained by use of the proper subroutine in the main computer program. Fortran listings of these programs are included in Appendix B for reference.

Cold Plasma Comparison

It was mentioned earlier that most of the proposed theories of antenna impedance are for the cold plasma case. Thus the first test is to compare the derived impedance relations with other theories for zero electron temperature. For zero temperature, however, the theory of Chapter III reverts to the cold plasma magneto-ionic theory of Appendix A. This theory agrees very well with other results and is discussed and empirically compared to Balmain's Theory in Appendix A.

For non-zero electron temperature, the author is only aware of two other theories for cylindrical antenna impedance; that of *Balmain* [1964] and that of *Whale* [1965]. Both considered the case of finite electron temperature, but only for no magnetic field.

Balmain Finite Temperature Theory

Balmain's theoretical result contained several difficult transendental functions, and he found it expedient to assume that the parameter α 'R (see below) is large compared to one. This approximation greatly simplified his more exact result. The resulting expression is

$$Z_{a} = \frac{\ln(L/R) - 1 + (K - 1)/2\alpha' R}{j\omega 2\pi \epsilon_{0} K_{0} L}$$
(99)

where

$$K_{o} = 1 - X/U$$

 $\alpha' = (X-1)^{1/2} \omega/\mu$

Whale Theory

Whale [1963], considered antenna power losses due to electroacoustic waves. Therefore, his results apply to an antenna in a warm plasma. His expression can be used to estimate antenna impedance if simple ionic theory is assumed for the antenna reactance while the power loss is interpreted as the result of antenna resistance. Whale's power loss equation is

$$Q_{1} = \frac{X \square \beta^{2} V^{2} (C_{0}/L)}{4 \pi c_{0} R_{s}^{2} (1-X)}$$
(100)

where

 Q_1 = Radiated power per unit length β = A special function calculated by Whale and presented in the form of a graph V_a = Antenna voltage R_s = $R_a + 4A_D$

If this expression is used to estimate antenna resistance and magnetoionic theory is used to find the antenna reactance, the result is

$$Z_{a} = R_{L}^{2} - X_{a}^{2} - \frac{1}{\omega C_{0}^{2} - X_{a}^{2}} - \frac{1}{\omega C_{0}^{2} - 1}$$
(101)

where

$$R_{L} = 2\pi\varepsilon_{o}LR_{s}\sqrt{1-X} / X\beta^{2}\mu C_{o}^{2}$$
(102)

Comparison of Theories

Both of the above expressions, as well as the expressions for antenna impedance from the Despain and magneto-ionic theories were programmed as computer subroutines with the name ANTZ. Thus all the theories could be simulated and later compared by using the desired subroutine in the main computer program.

and the second s

Balmain's expression is plotted as a function of exciting frequency in Figure 9. Figure 10 is a similar plot of the Despain theory with the same parameters. For T = 0, the results from each theory are identical. However, as the temperature is increased, some discrepancies appear. These are especially evident in the antenna resistance when the exciting frequency is above the plasma frequency. Near T = 1000 °K, there is reasonably good agreement, but as the temperature is increased further, it can be seen that the shapes of corresponding curves begin to show radical differences. This is very evident just below the plasma frequency. This discrepancy should not be unexpected since for high temperatures and for exciting frequencies near the plasma frequency, $\alpha' \aleph$ becomes small and the large $\alpha' \aleph$ approximation made by Balmain is not valid. Balmain's complete, though very difficult expression, must be used if his theory is to apply under these conditions.

It should be noted that in Balmain's theory (in contrast to the Despain theory) no appreciable reactance variation occurs as a function of temperature for exciting frequencies above the plasma frequency. This lack of variation is viewed with suspicion since even in regions where $\alpha'R$ is large, it seems only reasonable that antenna reactance is always changed to some degree by a change in electron temperature and antenna resistance. Appendix A also includes a discussion of a problem that occurs in Balmain's theory under certain special conditions.

It can thus be seen that the general characteristics of the two theories agree in this particular example for temperatures below 1000°K.

Figure 11 contains a comparison of the Balmain and Despain theories for fixed exciting frequency with plasma frequency as a variable. Again, good agreement is noted for low temperatures and for operating frequencies well separated from the plasma frequency. Again, some disagreement is evident wherever α 'R becomes small. In fact, in the Balmain theory, the resistance



1.4





-

- 5 M. 19-50

語い

ſ

F

ſ

I

R

I

I

I

100

X





-



is negative for high electron temperatures in certain regions. This is clearly an impossible result for the physical system; and as discussed above, comparisons in these regions are not possible. Again, it appears that the Despain and Balmain theories generally agree over those regions where valid comparisons can be made.

Although only a few sets of parameters have been examined here, more extensive comparisons of the two theories have been made for several other sets of parameters typical of ionospheric experiments. In each case, the conclusions are identical to those discussed above.

In addition to the results from the theories of Balmain and Despain, the impedance expression as derived from Whale's theory is also presented in Figure 11. It can be noted that all the theories predict finite antenna resistance for finite electron temperature over at least part of the frequency range. Also the resistance increases with increasing plasma frequency in each case. The similarity ends at this point, however, since the Whale theory resistance curve is clearly in variance with both the Balmain and Despain theory. It is felt that because both the Despain and Balmain theories were more rigorously derived than Whale's work, that they are the more accurate formulations of antenna impedance. Therefore, Whale's work will not be considered further.

The Despain theory has been compared to other theoretical results. It was found to agree with Balmain's work where comparisons were possible. It did not agree with the Whale theory. Thus the Despain theory seems to be at least as good theoretically as the Balmain theory and yet it was derived from a somewhat different viewpoint and is somewhat more general in its formulation.

Important Implications of the Theory

There are several very important implications that can be noted in the examples of the Despain theory given in Figures 10 and 11. First, for no electron collisions and zero electron temperature, no antenna resistance appears. However, if finite electron temperatures exist, then antenna resistance appears for exciting frequencies above the plasma frequency. Thus one effect of electron temperature is to add a loss mechanism not considered in the usual cold plasma formulations. Second, it can be observed that for exciting frequencies below the plasma frequency, a series (low impedance) resonance exists, whose frequency is a sensitive function of the electron temperature. Above the plasma frequency, the electron temperature has a much smaller effect on the antenna impedance. Third, the electron density (plasma frequency), temperature, and collision frequency all greatly affect antenna impedance. Hence, it should be possible to directly determine those parameters from antenna impedance measurements. This problem is the subject of the next chapter.

Further Examination of the Theory

The effect of magnetic field has not yet been investigated. Therefore, in Figure 12, the gyrofrequency has been taken as 1.4 MHz. By comparing Figures 10 and 12, it can be seen that the primary effect of the magnetic field is to transform the frequency scale so that the zero reactance point of the zero temperature curve is transformed up to the gyrofrequency and the parallel resonance (high impedance) point is shifted from the plasma frequency to the upper hybrid frequency given by

$$f_{\rm P}^2 = f_{\rm N}^2 + f_{\rm H}^2$$
 (103)



•

r



1

and the second second

If a close examination is made, it is found that the impedance at f with no magnetic field is about the same at f' with longitudinal magnetic field where

$$f' = \sqrt{f^2 + f_H^2}$$

The additional effect of collisions is shown in Figure 13. It can be noted that the resonances are not changed in frequency although some change is evident in the shape of the reactance curves. Furthermore, large values of resistance are evident throughout the complete frequency range.. Thus the primary result of electron collisions is an increase in antenna resistance.

Comparison of the Theory to Experimental Results

There are two basic methods for comparing the theory to experimental results. One method is to use the theory to simulate antenna impedance from the best independent estimate of the experimental plasma parameters and to then compare these results with the experimental antenna impedance values. The other method is to use the theory to determine the plasma parameters from the experimentally determined antenna impedance values. The resulting plasma parameters are then compared to the independent estimate of the actual plasma parameters. The first technique will be employed in this section while the second will be used in the next chapter.

There are three crucial impedance characteristics predicted by the theory. The first is a parallel resonance condition for an exciting frequency near the upper hybrid frequency described by

$$f_{\rm P}^2 = f_{\rm N}^2 + f_{\rm H}^2$$
(105)





I

1

(and

-

1

2 81.5

The second is the existance of an electron temperature controlled series resonance condition for an exciting frequency between the gyrofrequency and the upper hybrid frequency. The third is the appearance of appreciable antenna losses for exciting frequencies above the upper hybrid frequency even when the electron collision losses are neglegible. Thus each of these characteristics should be observed in experimental results whenever the proper conditions are met.

Experimentally, series and parallel resonances have been observed many times in results from the Plasma Frequency Probe. In fact, whenever it could be established that according to the theory, that these resonances should occur, they were indeed observed. In most cases, independent measurements of plasma frequency were also made so that the parallel resonance condition could be checked. It was indeed at the predicted hybrid frequency in every case. Several such comparisons are discussed in a paper by Baker, Despain and Ulwick [1966] Independent measurements of electron temperature were not made in most cases. Thus even though the series resonances were consistently observed in all cases, it is not possible to determine at exactly what frequency they should have occurred. A typical example from one of these experiments is shown in Figure 14. Each experimental measurement is shown as a dot. A curve has been drawn through the mean of these points as a representation of the parallel frequency. There was evidence for this flight, that vehicle potential was rapidly changing over a several volt range. Thus it has not been possible to completely determine the antenna potential except to note that it varied repeatedly from about zero down to about minus five volts during a period of about 1.6 seconds. Sheath effects that correspond to a value of S from about zero to four must therefore be effective here. This accounts for some of the spread in the series resonance data. So that this data could be compared to theory, a pair of curves were





drawn near the series resonance points. These curves represent the predictions of the theory using the parallel resonance curve and the indicated sheath and electron temperature parameters. These parameters are respectively, the highest and lowest limits that can be reasonably estimated for this flight for the sheath variable S and electron temperature T. It can be seen that in this particular case, and within the experimental uncertainties, there is good agreement between theory and experiment. This same conclusion was reached after an examination of the other flights where good measurements were obtained.

The observation of high antenna losses in regions of low electron collision frequency have been observed by Whale[1964] as mentioned earlier. A recent experiment using the Standing Wave Impedance Probe also exhibited a similar phenomena [Baker et al., 1965]. Since impedance measurements of electron temperature are not available, it is again impossible to predict exactly what losses should have been observed.

It is possible to assert that at least these experiments demonstrate results consistent with the theory and no contradictions are yet evident Such is not the case for the various other theories discussed earlier. The cold plasma theories and Whale's results do not predict a series resonance, and Balmain's warm plasma theory ignores magnetic fields that are always present in the ionosphere. Thus Balmain's theory does not predict correct values of series resonance or antenna losses. It is not possible to assert that the Despain theory is absolutely correct, but it has been proved that it is more accurate for the range of parameters of interest here than have any of the other theories of which the author is aware.

Chapter V

DETERMINATION OF PLASMA PARAMETERS

Introduction

Historically, RF antenna measurements have been used to determine electron density (plasma frequency) and electron collision frequency, using one of the magneto-ionic theories in the interpretation of the data. From the theory developed in this paper, it can be seen that electron temperature must also be considered; indeed, it is possible to determine electron temperature from the antenna impedance measurements using this theory. The purpose of this chapter is, therefore, to demonstrate how electron density, temperature and collision frequency can all be determined by use of this theory.

Antenna impedance is described by two parameters; resistance and reactance. It is desired, however, to determine three parameters; that is, electron density, temperature and collision frequency. Thus either impedance measurements must be made at (a) more than one exciting frequency or (b) simultaneously on at least two antennas of significantly different configuration or (c) there must be some known relation between at least two of the plasma parameters.

Over the usual range of natural ionosphere conditions, there is a simple relationship between electron collision frequency, electron temperature and total particle density [*Pfister*, 1965]. The relation is

$$v = C_N T N_t$$
(106)

where

- N_{f} = Total particle density (particles/meter³)
 - $C_N = A$ constant derived from any desired model atmosphere, taken to be 2.6 x 10^{-17} in this paper.

The total density can be found from a model atmosphere once the desired altitude is specified. The altitude, in turn, is known from the rocket trajectory. Thus the parameters altitude and antenna impedance can specify electron density, temperature, and collision frequency.

Plasma Parameters from the Standing Wave Impedance Probe

The Standing Wave Impedance Probe determines antenna impedance at a single frequency and at a given time. Thus for a given altitude, a plot of antenna impedance as a function of plasma frequency and electron temperature can be used to determine these parameters. Such a plot is generated by a computer program known as IMPPLT in conjunction with the subroutine ANTZ. These programs are listed in Appendix B for reference.

A plot of antenna resistance versus reactance is shown in Figure 15 for v = 0, and for no magnetic field. It describes a typical antenna used in ionospheric experiments of 3 meter length, 1/2 cm radius and driven at The impedance values shown are the differential impedance changes 3 MHz. from the free space conditions. Curves are shown for various constant electron temperatures and also for various constant plasma frequencies. Figure 16 is a similar plot for v = 1 MHz in which the effect of electron collisions can be discerned. The primary effect of the collisions is to increase the antenna resistance. In Figure 17, the collisions are assumed to follow the relation given in equation (106) at 75 km. In addition, magnetic field effects have also been taken into account by assuming a gyrofrequency of 1.4 MHz. It is evident that given antenna impedance and altitude, the plasma frequency and electron temperature can be determined directly, and that equation (106) can specify electron collision frequency. Thus these parameters can all be determined from the results of the Standing Wave Impedance Probe.



See Bear

THE CONTRACTOR

AC 1





and the providence




Fig. 17. Antenna Resistance versus reactance for 75 km.

 $x_{-\frac{1}{2}} = x_{-\frac{1}{2}} = x_{-\frac{1}{2}}$

Plasma Parameters from the Plasma Frequency Probe

The Plasma Frequency Probe, as explained in Chapter I, directly determines the series and parallel resonance frequencies of an antenna that occur in the range of .1 MHz to 10 MHz. It was shown in the last chapter that the resonance frequencies are not modified by modest electron collision frequencies so that v is assumed to be zero in the work that follows. The parallel frequency is not a function of electron temperature, and hence it defines the plasma frequency. The relationship for longitudinal magnetic field is

$$f_{\rm N}^2 = f_{\rm P}^2 - f_{\rm H}^2$$
(107)

For other magnetic aspect angles, it can be easily shown from magnetoionic theory (Appendix A) that this equation produces at most an error of about 10% in plasma frequency. For $f_N^{>>}f_H^{-}$, the error is very small. The series frequency, on the other hand, is a function of plasma frequency, gyrofrequency and electron temperature. Thus it is desirable to calculate the series resonance frequency as a function of the antenna and plasma parameters so that this relationship can be examined.

Calculation of Series Resonance Frequency

The condition for series resonance is that the imaginary part of the antenna impedance be equal to zero. Thus from Table I

$$Imag\left[\frac{1}{j\omega C_{s}} + \frac{1}{j\omega C_{o}} \left(\frac{\phi(\alpha R_{s})/\ln(L/R_{s}) - \psi^{2}}{1 - \psi^{2}}\right)\right] = 0$$
(108)

or

$$C_{o}/C_{s} + Real\left[\frac{\phi(\alpha R_{s})/\ln(L/R_{s})-\psi^{2}}{1-\psi^{2}}\right] = 0$$
(109)

If ψ^2 is found, the series frequency will be defined. Thus since v = 0, ϕ and ψ are both real for

$$\mathbf{f}_{\mathbf{H}} < \mathbf{f} < \mathbf{f}_{\mathbf{P}}$$
(110)

then

$$\psi^{2} = [\ln(R_{s}/R_{A}) + \phi(\alpha R_{s})]/\ln(L/R_{A})$$
(111)

where

1

$$C_{o}/C_{s} = \ln(R_{s}/R_{A})/\ln(L/R_{s})$$
 (112)

Equation (111) is the series respnance condition. It is a transcendental equation and is therefore not subject to analytical solution. It can be solved by a numerical technique such as Newton's iterative procedure. Subroutine SICALC of Appendix B solves the equation for ψ by Newton's method. The series frequency f is then given by the definition of ψ as

$$f_{s} = \left[\psi^{2} f_{\bar{N}}^{2} - f_{H}^{2}\right]^{1/2}$$
(113)

A computer program named TMPC1 (see Appendix B) calculates and plots this series frequency by calling SICALC and several other routines. The result is a plot of series versus parallel frequency with electron temperature as a parameter for a given set of plasma and antenna parameters. Figure 18 is an illustration of such a graph for a typical antenna. It can be seen from the figure that given the series and parallel resonance frequencies, the electron temperature can be determined.

The parameters of antenna radius, magnetic field and sheath radius all have some influence on the series resonance frequency. To illustrate the effect of these parameters, the curves of Figure 19 were developed. Note the decrease of series frequency as the antenna radius is increased



-





Fig. 19. Antenny ratios ersus serve disonatte traquency

when they get means the

and the increase in series frequency as magnetic field and sheath width are increased. Thus a knowledge of the sheath and magnetic field are required in addition to the antenna parameters and resonance frequencies in order to define electron temperature.

Electron Temperature from Resonance Frequencies

Electron temperature can be found from diagrams similar to Figure 19, or they can also be calculated directly. It electron temperature is desired, the resonance condition (109) is used to define ϕ as follows

$$\phi(\alpha R_{s}) = \left[\psi^{2} + (1 - \psi^{2})C_{o}/C_{s}\right] \ln(L/R_{s})$$
(114)

where all the parameters on the right hand side are known. Now ϕ is a transcendental function of αR_s and while αR_s cannot be expressed analytically, it can be found numerically from the value of ϕ . Subroutine ETAA determines αR_s from the value of ϕ by a series of simple iterations. The parameter ϕ is a function of the electron temperature T and thus

$$T = (4\pi^2 R_s^2 m/3K) (f_s^2 - f_H^2) (1 - \psi^2) / (\alpha R_s)^2$$
(115)

This temperature is calculated by a subroutine named IEMPSP. The routines ETAA and TEMPSP are used in the main line program TEP601 to find electron temperature from the series and parallel resonance trequencies. Again the programs are listed in Appendix B.

Example of Electron Temperatures from Measured Antenna Characteristics

To illustrate the measurement of electron temperature, the results from a Plasma Frequency Probe flown on an Aerobee rocket AC 3.603 were analyzed. This tooket was tired into an active aurora; and hence, some large variations of the plasma parameters occurred, including high electron temperatures. The complete experiment has been described in detail elsewhere (*Ulwick*, *et al.*, 1965) and an extensive analysis of the RF probe experiments aboard has also been reported (*Baker et al.*, 1965). The important feature of this particular flight was the independent measurement of electron temperature by two other instruments: a planer retarding potential analyzer and an RF electron temperature probe (RF perturbated Langmuir probe, part of the Resonance Rectification Probe).

Sheath variations occurred with this experiment. However, the vehicle and antenna potential could be defined, and it was found that the antenna potential was zero at certain times during the flight [Richards, 1965]. The experimentally determined potentials are shown in Figure 20 as a function of the voltage step applied between the vehicle and the antenna. It can be seen that at step 5, the antenna potential is near zero and that the sheath must be collapsed for this condition. Thus the theory for no sheath can be applied at this time to determine electron temperature.

Program TEP601 was used to calculate electron temperature for the step 5 case over a limited region of the flight where good results were obtained. The results are shown in Figure 21, along with measurements from the other two instruments. There is considerable scatter in the measurement of the resonance frequencies due to telemetry noise and other experimental limitations. Hence the temperature values show large variations from what must be the true values. In addition, the true temperature values must also vary greatly as well, since the antenna is in an active auroral region characterized by disturbed temperature and density variations. Since each independent instrument measures at an independent time, some differences between instruments is expected due solely to the variations in the ionospheri, medium The general agreement between all the measurements is seen to be quite good when the above arguments are kept in mind.

In an attempt to further observe the correlation between the various







No.

A well

T

I

Fig. 21 Collapsed sheath electron temperatures.

techniques, the data under all sheath conditions was analyzed with the collapsed sheath theory and the results were averaged. This average curve is compared to the other measurements in Figure 22. Again reasonable correlations were obtained. It should be noted that the experiment was not designed to determine electron temperature and that further experimental refinements with this goal in mind would greatly improve the quality of the data. In general, it is felt that the measurements of electron temperatures by the resonance frequencies could be a very accurate technique, especially for experimental designs optimized for accurate determination of the resonance frequencies.





Chapter VI

SUMMARY AND CONCLUSIONS

This paper first discussed the plasma state and the important parameters needed to specify the character of a plasma. Then the range of parameters encountered in the ionospheric plasma was examined. Various RF probe techniques were presented and a need was shown for a theory to describe the plasma - antenna interaction so that measurements from these probes could be interpreted correctly.

Various theories have been previously presented but while some of these were suitable for a restricted range of plasma parameters, none of these theories could account for all the experimental results as observed in data from the probe experiments. Thus clearly further theoretical work was required.

In the theoretical work, the antenna was assumed to be cylindrical, electrically short, yet with sufficient length as compared to the radius so that end effects could be ignored. The surrounding plasma was characterized as a homogeneous, compressible electron fluid surrounding relatively fixed positive ions so that macro charge neutrality is maintained. The plasma properties are described by the plasma frequency, gyrofrequency and the electron temperature and collision frequency.

The theoretical approach considered the forces on an element of the electron fluid. In addition to the usual acceleration term, there were forces due to electric and magnetic fields, electron collisions and gradients of pressure in the electron fluid. The pressure gradients were related to density gradients and electron temperature through the ideal gas law and equation of state. The velocity of the electron fluid was found from this force equation. This expression was then combined with the continuity and Poisson's equation to produce a second order partial differential equation in terms of the electron density variations. Solutions to this equation were found to be expressible as the well known Hankel functions. Boundary conditions then determined a unique solution. From a knowledge of the charge density, Poisson's equation was solved and the potential in the region was then defined. The fields were then easily determined and antenna impedance was found as the ratio of antenna potential to antenna current as derived from the field quantities. The usual discontinuous sheath model was employed to account for sheath effects. The result was an impedance expression that included all the important plasma parameters discussed earlier, especially electron temperature.

The results of the theoretical calcuation were numerically simulated with a computer, and the emperical results were compared to several other theories. The theory exhibited good agreement with magneto-ionic theories and also with Balmain's work for a range of parameters in which it was valid to make comparisons. In addition, a comparison was made to experimental results. The agreement was good, at least to within the limits of the accuracy of the experimental parameters. In contrast to all the other theories, n: contradictions were noted between the theory and experimental results. Thus the theory appears, at least, to be the best available for interpretation of ionospheric RF probe experiments.

The problem of determining plasma parameters from impedance measurements was considered next. First it was demonstrated that plasma frequency, electron temperature, and collision frequency could be obtained from the altitude and a single frequency impedance measurement. Next it was shown how plasma frequency and electron temprature are defined by the series and parallel resonances of the antenna. Finally an example of determining electron

temperature from experimental Plasma Frequency Probe results was considered. The electron temperatures determined with the aid of the theory were compared to two other independent measurements and good correlations were obtained.

It is believed that the experimental electron temperatures derived by use of the theory are the first reported, direct electron temperature measurements of the ionosphere that do not use some variation of the Langmuir Probe Technique (see Chapter I). The theory therefore makes possible a valuable new method of measuring electron temperature.

It should be noted that the theory was developed to interpret RF probe results. Hence, the antennas were always very short compared to the RF servelengths; and therefore, the electromagnetic effects were dominated by the plasma effects. In addition, the free space impedance of the antenna systems could be experimentally determined; and thus, the theory was only required to account for changes in the impedance due to the plasma.

In conclusion, it can be noted that the theory successfully accounts for all the experimental phenomena observed. It agrees well with other theories where comparisons are valid. Finally, its use makes possible, for the first time, the determination of electron temperature by an RF impedance probe technique.

REFERENCES

- Ament, W.S., J.C. Katzin, M. Katzin, and B.Y.-C. Koo, Impedance of a cylindrical dipole having a sinusoidal current distribution in a homogeneous anisotropic ionosphere, *Radio Sci.*, J. Res., 68D, 379-405, 1964.
- Bachynski, M.P., Plasma physics an elementary review, Proc. IRE, 49, 1751-1766, 1961.
- Baker, K.D., A.M. Despain, J.C. Ulwick, and W. Pfister, Experiences with antenna impedance measurements in the ionosphere, URSI 1965 Fall Meeting, Dartmouth College, (to be published in Radio Science), 1965.
- Baker, K.D., A.M. Despain, and J.C. Ulwick, Simultaneous comparison of RF probe techniques for determination of ionospheric electron density, J. Geophys. Res., ⁷¹, 935-944, 1966.
- Balmain, K.G., The impedance of a short dipole antenna in a magnetoplasma, Aeronomy Report No. 2, University of Illinois, Urbana, 1964.
- Balmain, K.G., Impedance of a radio frequency plasma probe with an absorptive surface, in Second Conference on Direct Aeronomic Measurements in the Lower Ionosphere, Conference Digest-Program, 92-104, University of Illinois, Urbana, 1965.
- Bramley, E N., The impedance of a short cylindrical dipole in the ionosphere, *Planet Space Sci.*, 9, 445-454, 1962.

Brown, Sanborn C. et al., Outline of a course in plasma physics, Am. J. Phys, 31, 637-691, 1963.

Cambel, Ali Bulent, Plasma Physics and Magnetofluid Mechanics, McGraw-Hill Pub. Co., Inc., New York, 1963.

- Cohen, M.H., Radiation in plasmas, Part I, Phys. Rev., 123, 711-721; Part II, Phys. Rev., 126, 389-397; Part III, Phys. Rev., 126, 398-404, 1961.
- Crouse, P.E., Methods for obtaining electron density profiles from capacitive ionospheric rocket probes, *Ionos. Res. Sci. Report No. 208*, The Pennsylvania State University, University Park, 1964.
- DeChamps, G.A., Impedance of an antenna in a conducting medium, Trans. IRE AP-10, 648-650, 1962.
- Despain, A M., A plasma resonance and electron temperature experiment, Scientific Report No 3, AFCRL 64-809, Contr. No. AF 19(628)-447, University of Utah, Salt Lake City, 1964.
- Despain, A.M., The theory of cylindrical antenna impedance as a function of plasma frequency and temperature, *Scientific Report No. 1*, AFCRL 65-480, Contr. No. AF 19(628)-4995, University of Utah, Salt Lake City, 1965
- Fejer, J A., Interaction of an antenna with a hot plasma and the theory of resonance probes, J. Res. NBS, 68D, 1171-1176, 1964.
- Harrison, C.W., Jr., and D H. Denton Jr., Impedance of a dipole in an ionized medium-II, Sandia Corp. Tech. Memo.No. SCTM 225-59(14, 1959.
- Haycock, O.C., and K.D. Baker, New ionospheric measurement technique: plasma frequency probe, *Electronics*, 35, No. 48, 81-83, 1962.
- Herman, J.R., Theoretical determination of the impedance characteristics of a capacitive ionosphere rocket probe, *Ionos. Res. Sci. Report No. 180*, The Pennsylvania State University, University Park, 1963.
 Hirao, K., and T. Muraoka, Resonance probe, *COSPAR Information Bulletin No. 17*, 83-116, 1964.

- Ichikawa, Y. and H. Ikegami, Theory of resonance probe, Prog. Theor. Phys., 28(2), 315-322, 1962.
- Jackson, J.E., and A.D. Pickar, Performance of a rocket-borne 7.75 Mc transmitting antenna in the ionosphere, Upper Atmosphere Report 28, U.S. Naval Research Laboratory Report 4940, 1957.
- Jahnke, Eugene, and Fritz Emde, Tables of Functions with Formulae and Curves, Dover Publications, New York, 1945.
- Johnson, Francis S. (Editor), Satellite Environment Handbook, Stanford University Press, Stanford, 1961.
- Kaiser, T.R., The admittance of an electric dipole in a magneto-ionic environment, Space Sci., 9, 639-657, 1962.
- King, R., and C.W. Harrison, Half-wave cylindrical antenna in a dissipative medium: current and impedance, J. Res. NBS, 64D, No. 4, 365-380, 1960.
- King, R., C.W. Harrison, and D.H. Denton, The electrically short antenna as a probe for measuring free electron densities and collision frequencies in an ionized region, J. Res. NBS, 65D, No. 4, 371-384, 1961.
- Krauss, John D., Antennas, McGraw-Hill Publishing Co., Inc., New York, 1950.
 Langmuir, Irving, Positive ion currents in the positive column of the mercury arc, Gen. Elect. Rev., 26, No. 11, 731-735, 1923.

Mitra, S.K., The Upper Atmosphere, The Asiatic Society, Calcutta, 1952.

- Miyazaki, S., K. Hirao, Y. Aono, K. Takayama, H. Ikegami, and T. Ichimiya, Resonance probe - a new probe method for electron density and electron temperature in the ionosphere, *Report of Ionos. Space Res. in* Japan, 14(2), 148-159, 1960.
- Pfister, W., Non-deviative absorption, in Handbook of Geophys. and Space Environment, edited by S.L. Valley, pp. 12-15 to 12-28, Air Force Cambridge Research Laboratories, Bedford, 1965.

- Ratcliffe, J.A., The Magneto-Ionic Theory and Its Applications to the Ionosphere, Cambridge University Press, Cambridge, 1962.
- Richards, E.N., Analysis of retarding potential analyzer experiment from rocket flight AC 3.603, Boston College Laboratory Report, Chestnut Hill, 1965.
- Sen, H K., and A.A. Wyller, On the generalization of the Appleton-Hartree magnetoionic formulas, J. Geophys. Res., 65, 3931-3950, 1960.
- Shkarofsky, I.P., Generalized Appleton-Hartree equation for any degree of ionization and application to the ionosphere, *Proc. IRE*, 49, 1857-1871, 1961.
- Spitzer, L. Jr., Physics of Fully Ionized Gases, Interscience Publishers, New York and London, 1962.
- Stone, R.G., R.R. Weber, and J.K. Alexander, Measurement of antenna impedance in the ionosphere 1. Observing frequency below the electron gyrofrequency, Goddard Space Flight Center Report No. X-615-66-44, 1966.
- Takayama, K., Plasma resonance in a radio frequency probe, Phys. Rev. Letters, 5(6), 238-240, 1960.
- Ulwick, J.C., W. Pfister, G.C. Haycock, and K.D. Baker, Description of standing wave impedance probe, in COSPAR Information Bulletin No. 17 117-146, 1964.
- Ulwick, J.C., W. Pfister, O.C. Haycock, and K.D. Baker, Rocket measurements with electron and ion probes in an aurora, *Space Res. V*, edited by King-Hele, Muller, and Righini, 293-311, North Holland Publishing Co., Amsterdam, 1965.

- Wait, J.R., Theory of a slotted-sphere antenna immersed in a compressible
 plasma, Part I, Radio Sci. J. Res. NBS/USNC-URSI 68D, No. 10, 11271136, 1964.
- Whale, H.A., The excitation of electroacoustic waves in the ionosphere, J. Geophys. Res., 68, 415-422, 1963.
- Wilson, M.A., and E. Gold, On the electrical conductivity of flames containing salt vapours for rapidly alternating currents, *Phil. Mag.*, *11*, 484-505, 1906.

APPENDIXES

- -

APPENDIX A

ANTENNA IMPEDANCE FROM IONIC THEORY

Isotropic Media-Capacitor Model

If magnetic fields and thermal motions other than collisions are ignored, then antenna impedance can be simply determined from ionic theory.

The frequencies of interest are in the range .1 to 10 MHz. Thus the shortest wavelength involved is 30 meters. In almost all cases, the antenna probes under consideration will be much shorter than this, typically about 3 meters. Therefore, the antennas are always short compared with the operating wavelengths, and hence may be considered as capacitors whose dielectric reflects the properties of the plasma medium that surrounds the probes. Capacitance of an object is defined as the ratio of the total charge stored on the surface to the electric potential of the object.

$$C = Q/\Phi \tag{A1}$$

In terms of the electric flux parameter \vec{D} , the capacitance is from Gauss's Law

$$c = \frac{j \int_{S} \vec{D} \cdot d\vec{S}}{\Phi}$$
 (A2)

In terms of the free space capacitance C_0 and from the relation valid in free space $\vec{D} = \epsilon_0 \vec{E}$, it is found that

$$\frac{C}{C_{o}} = \frac{\iint_{s} \vec{D} \cdot d\vec{S}}{\varepsilon_{o} \iint_{s} \vec{E} \cdot d\vec{S}}$$
(A3)

For the well behaved geometries encountered in practice (planes, cylinders, etc.), it is permissible to consider both D and E invariant in magnitude and perpendicular with respect to the surface. Thus these quantities can be taken outside the integrals and the following relation results

$$\frac{C}{C_0} = \frac{\varepsilon}{\varepsilon_0}$$
(A4)

where

 $\vec{D} = \epsilon \vec{E}$

The antenna impedance Z_a can now be obtained from

 $Z_a = 1/j\omega C$

Ratcliffe [1962] derives an expression for ε expressed by

$$\varepsilon = \varepsilon_{0} \left[1 - \frac{X}{1 - jZ} \right]$$
(A5)

where

$$X = \omega_N^2 / \omega^2$$

$$Z = \nu / \omega$$

$$\omega_N = \text{radian plasma frequency}$$

$$\omega = \text{radian operating frequency}$$

$$\nu = \text{electron collision frequency}$$

Thus the antenna impedance Z_a is

$$Z_{a} = \frac{1}{j\omega C} = \frac{1}{j\omega C_{o}} \left[1 - \frac{X}{1 - jZ} \right]$$
(A6)

or

$$Z_{a} = \frac{1}{\omega C_{o}} \left[\frac{XZ}{(1-X)^{2} + Z^{2}} - j \frac{(1-X) + Z^{2}}{(1-X)^{2} + Z^{2}} \right]$$
(A7)

In this expression, it is assumed that the antenna probe does not radiate. In actual practice however, even a very electrically short antenna will radiate some energy. This is often described by a radiation resistance R_r

$$R_r = P_r / I_a^2$$
 (A8)

where

Pr = total radiated power
I = antenna current at terminals.

Kraus [1950] in (5-55) gives the following expression for R_r of a short dipole

$$2R_{r} = \sqrt{\frac{\mu}{\epsilon}} \frac{\beta^{2}(2L)}{6\pi}$$
(A9)

or

$$R_{r} = \sqrt{\frac{\beta^{2}L}{\epsilon}} \frac{\beta^{2}L}{6\pi}$$
(A10)

where

 $R_r = resistance of monopole$ L = length of monopole β = ω/c = 2π/λ c = velocity of light λ = wavelength In a plasma medium μ_0 is invariant, but as shown above, ϵ varies according to (A5). Thus, the antenna impedance Z_{ar} arising from the radiation can be determined by substituting (A5) into (A10). (K.D. Baker, private communication, 1964) has examined this problem and has verified that both the real and imaginary parts of the radiation resistance should be included in the total expression for antenna impedance. A similar approach for the more general case of antenna impedance has been developed by Harrison and Denton [1959], where they have let Imag [ϵ] be represented by $-\sigma/\omega$ where σ is the conductivity of the medium.

The antenna resistance is thus

$$Z_{\rm ar} = \frac{\sqrt{\mu_0} \beta^2 L}{6\pi} \left[1 - \frac{X}{1 - jZ} \right]^{-1/2}$$
(A11)

and the total impedance Z_{at} is then

$$Z_{at} = \frac{1}{j\omega C_{o}} \left[1 - \frac{X}{1 - jZ} \right]^{-1} + \frac{\sqrt{\mu_{o}\beta^{2}L}}{6\pi} \left[1 - \frac{X}{1 - jZ} \right]^{-1/2}$$
(A12)

The radiation term should be included whenever the antenna is not extremely short or when very small changes of resistance are of interest.

Magneto-Ignic Cold Plasma

If a steady magnetic field permeates the plasma, the medium is no longer isotropic. Thus while (A3) still applies, the relation between \vec{D} and \vec{E} involves a tensor [ϵ]. Since E is always normal to the antenna surface, (A3) can be expressed as

$$\frac{C}{C_{o}} = \frac{\iint \left[\frac{\vec{D} \cdot \vec{E}}{|E_{s}|} dS\right]}{\epsilon_{o} \iint_{s} |E_{s}| dS}$$
(A13)

where $|E_g| = magnitude$ of E at the antenna surface. But by definition of $[\varepsilon]$

$$\vec{D} \cdot \vec{E} = \sum_{i,j} E_i \varepsilon_{ij} E_j$$
(A14)

or

1

. .

$$\vec{D} \cdot \vec{E} = E_x^2 \epsilon_{11} + E_y^2 \epsilon_{22} + E_z^2 \epsilon_{33} + \sum_{\substack{i,j \\ i\neq j}} t_{ij}$$
(A15)

where t_{ij} = all cross products.

linus (A13) becomes

At the surface of the cylindrical antenna

$$E_{x} = |E_{s}| \cos \theta$$
 (A17)

$$E_{y} = |L_{s}| \sin \epsilon$$
 (A18)

$$E_{z} = 0 \tag{A19}$$

Thus since $E_z = 0$ and the t_{ij} integrals all go to zero as they contain cross terms that integrate to zero, the equation becomes

$$\frac{C}{C_{o}} = \frac{\varepsilon_{11}}{\varepsilon_{o}} \frac{\int_{0}^{L} \int_{0}^{2\pi} |C_{os}^{2}\theta d\theta dr}{\int_{0}^{L} \int_{0}^{2\pi} |E_{s}| d\theta dr} + \frac{\varepsilon_{22}}{\varepsilon_{o}} \frac{\int_{0}^{L} \int_{0}^{2\pi} |E_{s}| G d\theta dr}{\int_{0}^{L} \int_{0}^{2\pi} |E_{s}| d\theta dr}$$
(A20)

It is assumed that E_s is not a function of θ . Thus (A20) becomes

$$\frac{C}{C_{o}} = \frac{\epsilon_{11}}{\epsilon_{o}} \frac{1}{2\pi} \int_{0}^{2\pi} \cos^{2} \theta \, d\theta + \frac{\epsilon_{22}}{\epsilon_{o}} \frac{1}{2\pi} \int_{0}^{2\pi} \sin^{2} \theta \, d\theta \qquad (A21)$$

$$\frac{C}{C_{o}} = \frac{\varepsilon_{11} + \varepsilon_{22}}{2\varepsilon_{o}}$$
(A22)

According to Appleton-Hartree Theory [Ratcliffe, 1962]

$$\epsilon_{11} = \epsilon_{o} \left[1 + \frac{XU^2}{U(Y^2 - U^2)} \right]$$
(A23)

$$\epsilon_{22} = \epsilon_{0} \left[1 + \frac{X(U^{2} - Y^{2}Sin^{2}\gamma)}{U(Y^{2} - U^{2})} \right]$$
 (A24)

Thus

$$\frac{C}{C_{o}} = 1 + 1/2 \left[\frac{XU^{2} + X(U^{2} - Y^{2}Sin^{2}\gamma)}{U(Y^{2} - U^{2})} \right]$$
(A25)

$$\frac{C}{C_{o}} = 1 + X \frac{1 - 1/2 (Y/U)^{2} \sin^{2} \gamma}{U(Y/U)^{2} - 1}$$
(A26)

or antenna impedance is

$$Z_{a} = \frac{1}{j\omega C} = \frac{1}{j\omega C_{o}} \left[1 + X \frac{1 - 1/2 (Y/U)^{2} \sin^{2} Y}{U(Y/U)^{2} - 1} \right]^{-1}$$
(A27)

anne 19 a nase i Barrer Billinger Billinger

This expression is the expression for antenna impedance from the magnetoionic theory of a cold plasma.

The second s

Comparison to Balmain Theory

The antenna impedance of (A27) can be directly compared to the results of Balmain (see Equation 10). As mentioned in the main text of this report, Balmain's work is probably the best published to date on cold plasma antenna impedance. To compare these two theories, they were written up as Fortran subroutines known as ANTZ - BALMAIN and ANTZ-MAGNETO-IONIC THEORY. These routines were successively used in a program called SWP4MD that calculated and plotted the antenna impedance as a function of plasma frequency and for fixed exciting frequency (see Appendix B). The results have shown very good empirical agreement except when the exciting frequency is near the plasma frequency. A typical sample of both theories is shown in Figure A-1 and illustrates the areas of disagreement. Stone, Weber and Alexander [1966] have also noted a theoretical discrepancy between Balmain's theory and the theory of Herman and others when the plasma frequency is in the vicinity of the exciting frequency. In addition, it appears that their experimental evidence confirms that Balmain's results are not valid in this region. Thus it may well be that the magneto-ionic theory presented here is more correct and much easier to derive than the theory of Balmain. It should also be noted here that this derivation is similar in many respects to the derivation of Crouse [1964] made on a rocket nose cone and thus should agree very well with his results if the cone angle is set to zero.

Hot Plasma

The basic assumptions and view of the plasma in this section are identical to those developed in Chapter III. The strategy of deriving the antenna impedance differs in that it is assumed that the plasma can be represented by an effective permittivity tensor [ε]. Thus the same basic

A-7



Fig. A-1. Comparison of Balmain and magneto-ionic antenna theories.

equations are used to find [ε], but instead of developing partial differential equations as in Chapter III, this derivation derives the antenna impedance directly from ε by an integration process similar to that used above for the cold plasma case.

Permittivity $[\varepsilon]$

The starting point in deriving [ϵ] is the force equation (25).

$$\mathbf{j}\omega\mathbb{X} \left[\mathbf{U}\vec{\mathbf{v}}-\mathbf{j}\mathbf{Y}(\vec{\mathbf{v}}\ \mathbf{x}\ \hat{\boldsymbol{\zeta}}\)\right] = -\mu^2 \nabla \mathbf{n} + \frac{\mathbf{N}\mathbf{e}}{\mathbf{m}} \quad \nabla \boldsymbol{\phi}$$
(A23)

Where

Ļ

$$\vec{E} = -\nabla \Phi \tag{A29}$$

$$\nabla^2 \Phi = \frac{ne}{\varepsilon_0}$$
(A30)

the force equation becomes

$$j\omega_{\lambda}^{\lambda} [\vec{v}\vec{v}-jY(\vec{v} \times \vec{\zeta})] = \frac{\mu^{2} \varepsilon_{0}}{e} \nabla(\nabla \cdot E) - \frac{\lambda e}{m} \vec{E}$$
(A31)

Now the usual assumption is made [Rateliffe, 1962, p. 15] that the velocity can be represented by a polarization P as follows

$$\vec{P} = -N\vec{er}$$
(A32)

$$\dot{\vec{P}} = +j\omega\vec{P} = -k\vec{ev}$$
(A33)

Thus

$$\vec{v} = -\frac{j\omega}{Ne}\vec{P}$$
 (A34)

and the force equation becomes

A-10

$$\varepsilon_{0} \mathbf{X} \vec{E} - \frac{\vec{\mu} \varepsilon_{0}}{\omega} \nabla (\nabla \cdot \vec{E}) = - [U\vec{P} - \mathbf{j} \mathbf{Y} \vec{P} \mathbf{x} \hat{\zeta}]$$
(A35)

where

$$X = \omega_N^2 / \omega^2 = Ne^2 / m\epsilon_0 \omega^2$$
 (A36)

Now tensor notation is introduced.

Let

$$[\Delta] = \begin{bmatrix} \frac{\partial^2}{\partial x^2} & \frac{\partial^2}{\partial x \partial y} & \frac{\partial^2}{\partial x \partial z} \\ \frac{\partial^2}{\partial x \partial y} & \frac{\partial^2}{\partial y^2} & \frac{\partial^2}{\partial y \partial z} \\ \frac{\partial^2}{\partial x \partial z} & \frac{\partial^2}{\partial y \partial z} & \frac{\partial^2}{\partial z^2} \end{bmatrix}$$
(A37)

and

$$\begin{bmatrix} \sigma \end{bmatrix}^{-1} = \begin{bmatrix} -U & -jY_z & jY_y \\ jY_z & -U & -jY_x \\ -jY_y & -jY_x & -U \end{bmatrix}$$
(A38)

where

$$\vec{Y} = Y\hat{\zeta} = Y_x\hat{x} + Y_y\hat{y} + Y_z\hat{z}$$
 (A39)

Then the force equation can be written as

$$\begin{bmatrix} \varepsilon_{o} X - \frac{\mu^{2} \varepsilon_{o}}{\omega^{2}} [\Delta] \end{bmatrix} \stackrel{?}{E} = [\sigma] \stackrel{-1}{P}$$
(A40)

However

No. A PARTY OF

** ·**

> 26E

$$\vec{D} = [\varepsilon]\vec{E} = \varepsilon_0\vec{E} + \vec{P}$$
(A41)

A-11

or

$$\vec{P} = [\varepsilon]\vec{E} - \varepsilon_0[I]\vec{E}$$
(A42)

Thus

$$\left[\varepsilon_{0}X - \frac{\mu^{2}\varepsilon_{0}}{\omega^{2}}\left[\Delta\right]\right]\vec{E} = \left[\sigma\right]^{-1}\left[\varepsilon_{1} - \varepsilon_{0}[I]\right]\vec{E}$$
(A43)

$$\varepsilon_{o} X[\sigma] - \frac{\mu^{2} \varepsilon_{o}}{\omega^{2}} [\sigma] [\Delta] = [\varepsilon] - \varepsilon_{o} [I]$$
(A44)

or

$$[\varepsilon] = \varepsilon_{o} \left[X[\sigma] + [I] - \frac{\mu^{2}}{\omega^{2}} [\sigma] [\Delta] \right]$$
(A45)

now

$$X[\sigma] = -\left[\frac{X}{\upsilon(\upsilon^{2}-Y_{x}^{2})}\right] \begin{bmatrix} (\upsilon^{2}-Y_{x}^{2}) & (-j\upsilon Y_{z}-Y_{x}Y_{y}) & (j\upsilon Y_{y}-Y_{x}Y_{z}) \\ (j\upsilon Y_{z}-Y_{y}Y_{x}) & (\upsilon^{2}-Y_{y}^{2}) & (-j\upsilon Y_{x}-Y_{y}Y_{z}) \\ (-j\upsilon Y_{y}-Y_{z}Y_{x}) & (j\upsilon Y_{x}-Y_{z}Y_{y}) & (\upsilon^{2}-Y_{z}^{2}) \end{bmatrix}$$
(A46)

[See Ratcliffe, 1962; p. 182-184]

.....

$$\begin{bmatrix} \mathbf{I} \end{bmatrix} = \begin{bmatrix} \mathbf{1} & 0 & \dot{0} \\ 0 & \mathbf{1} & 0 \\ 0 & 0 & \mathbf{1} \end{bmatrix}$$
(A47)

Let

and the contract

$$-\frac{\mu^{2}}{\omega^{2}} [\sigma] [\Delta] = \frac{VX}{U(U^{2}-Y^{2})} [A]$$
(A48)

at 1 mars man in a substate diverse in the first

-

where

$$v = \mu^2 / \omega_N^2$$

then the elements of [A] are

$$A_{11} = (U^2 - Y_x^2) \frac{\partial^2}{\partial x^2} - (jUY_z - Y_x Y_y) \frac{\partial^2}{\partial x \partial y} + (jUY_y - Y_x Y_z) \frac{\partial^2}{\partial x \partial z}$$
(A49)

$$A_{12} = (U^2 - Y_x^2) \frac{\partial^2}{\partial x \partial y} - (jUY_z - Y_x Y_y) \frac{\partial^2}{\partial y^2} + (jUY_y - Y_x Y_z) \frac{\partial^2}{\partial y \partial z}$$
(A50)

$$A_{13} = (U^2 - Y_x^2) \frac{\partial^2}{\partial z^2} - (jUY_z - Y_x Y_y) \frac{\partial^2}{\partial y \partial z} + (jUY_y - Y_x Y_z) \frac{\partial^2}{\partial z^2}$$
(A51)

$$A_{21} = (jUY_z - Y_x Y_y) \frac{\partial^2}{\partial x^2} + (U^2 - Y_y^2) \frac{\partial^2}{\partial x \partial y} - (jUY_x - Y_y Y_z) \frac{\partial^2}{\partial x \partial z}$$
(A52)

$$A_{22} = (jUY_z - Y_x Y_y) \frac{\partial^2}{\partial x \partial y} + (U^2 - Y_y^2) \frac{\partial^2}{\partial y^2} - (jUY_x - Y_y Y_z) \frac{\partial^2}{\partial y \partial z}$$
(A53)

$$A_{23} = (jUY_z - Y_x Y_y) \frac{\partial^2}{\partial x \partial z} + (U^2 - Y_y^2) \frac{\partial^2}{\partial y \partial z} - (jUY_x - Y_y Y_z) \frac{\partial^2}{\partial z^2}$$
(A54)

$$A_{31} = -(jUY_y - Y_x Y_y) \frac{\partial^2}{\partial x^2} + (jUY_x - Y_y Y_z) \frac{\partial^2}{\partial x \partial y} + (U^2 - Y_z^2) \frac{\partial^2}{\partial x \partial z}$$
(A55)

$$A_{32} = -(jUY_y - Y_x Y_z) \frac{\partial^2}{\partial x \partial y} + (jUY_x - Y_y Y_z) \frac{\partial^2}{\partial y^2} + (U^2 - Y_z^2) \frac{\partial^2}{\partial y \partial z}$$
(A56)

$$A_{33} = -(jUY_y - Y_x Y_z) \frac{\partial^2}{\partial x \partial z} + (jUY_x - Y_y Y_z) \frac{\partial^2}{\partial y \partial z} + (U^2 - Y_z^2) \frac{\partial^2}{\partial z^2}$$
(A57)

Now let
$$[\varepsilon] = \varepsilon_0 \frac{-X}{U(U^2 - Y^2)} [T]$$
 (A58)

Then the elements of [T] are given by

.....

- -

the state of the

104

$$\varepsilon_{ij} = \varepsilon_{o} \left[X\sigma_{ij} + I_{ij} + \frac{VX}{U(U^2 - Y^2)} A_{ij} \right] = \varepsilon_{o} \frac{-X}{U(U^2 - Y^2)} T_{ij}$$
(A59)

١

A-13

$$T_{ij} = -U(U^2 - Y^2)\sigma_{ij} - (U/X) (U^2 - Y^2)I_{ij} - VA_{ij}$$
(A60)

Thus

I

T

Paren o

I

$$T_{11} = (U^2 - Y_x^2) - (U/X)(U^2 - Y^2) - 7A_{11}$$
(A61)

$$\hat{T}_{12} = -(j U Y_z - Y_x Y_y) - V A_{12}$$
 (A62)

$$T_{13} = (JUY_y - Y_x Y_z) - VA_{13}$$
 (A63)

$$T_{21} = (jUY_z - Y_x Y_y) - VA_{21}$$
 (A64)

$$T_{22} = (U^2 - Y_y^2) - (U/X)(U^2 - Y^2) - VA_{22}$$
 (A65)

$$T_{23} = -(jUY_x - Y_y Y_z) - VA_{23}$$
(A66)

$$f_{31} = -(jUY_y - Y_x Y_z) - VA_{31}$$
(A67)

$$T_{32} = (jUY_x - Y_yY_z) - VA_{32}$$
 (A68)

$$T_{33} = (U^2 - Y_z^2) - (U/X)(U^2 - Y^2) - VA_{33}$$
 (A69)

Therefore $[\varepsilon]$ is

$$[\varepsilon] = \varepsilon_0 \frac{-X}{U(U^2 - Y^2)} [T]$$
 (A70)

where the elements of [T] are given above.

The permittivity :ensor represents the hot, magneto-ionic medium. It should be noted that it contains partial derivatives with respect to the coordinates. Thus the spatial form of the \vec{E} field must be specified before [ϵ] is completely defined. This implies that [ϵ] is a function of the coordinates.

Hot Plasma Antenna Impedance

The E field around the cylindrical antenna is given by

$$\vec{E} = E(r)[Cos(6)\hat{x} + Sin(6)\hat{y}]$$
 (A71)

and the magnetic field vector is assumed to lie in the y-z plane, at an angle γ with respect to the z axis (see Figure 8 in the main text).

Thus

$$Y_x = 0, Y_y = Y \sin \gamma, Y_z = Y \cos \gamma$$
 (A72)

$$E_{x} = E_{r} \cos \theta$$
 (A73)

$$E_{y} = E_{r} \sin \theta$$
 (A74)

$$\frac{\partial E}{\partial x} = \frac{\partial E}{\partial r} \frac{dr}{dx} + \frac{\partial E}{\partial \theta} \frac{d\theta}{dx}$$
(A75)

$$\frac{\partial E_{\mathbf{x}}}{\partial \mathbf{x}} = \frac{\partial E_{\mathbf{r}}}{\partial r} + \frac{E_{\mathbf{r}}}{\mathbf{r}} \sin^2 \theta$$
 (A76)

$$\frac{\partial^2 E_x}{\partial x^2} = \frac{2E_o}{r^3} \cos^3 \theta$$
 (A77)

where

$$E_r = \frac{E_o}{r}$$

Similarly

the stand of the second second

and the second se

$$\frac{\partial^2 E_x}{\partial x \partial y} = \frac{2E_0}{r^3} \frac{\cos^2 \theta (1 + \sin^2 \theta)}{\sin \theta}$$
(A78)

arrille Automatic Science da sera a

$$\frac{\partial^2 E_y}{\partial y^2} = \frac{2E_o}{r^3} \sin^3\theta$$
(A79)

$$\frac{\partial^2 E_y}{\partial x \partial y} = \frac{2E_o}{r^3} \frac{\sin^2 \theta (1 + \cos^2 \theta)}{\cos \theta}$$
(A80)

All partial derivatives with respect to z are zero as are all partial derivatives of E_{z} .

Thus

$$\frac{1}{E_{x}}\frac{\partial^{2}E_{x}}{\partial x^{2}} = \frac{\cos^{2}\theta}{r^{2}}$$
(A81)

$$\frac{1}{E_{x}}\frac{\partial^{2}E_{x}}{\partial x \partial y} = \frac{2 \cos \theta (1+\sin^{2} \theta)}{r^{2} \sin \theta}$$
(A82)

$$\frac{1}{E_{y}}\frac{\partial^{2}E_{y}}{\partial x \partial y} = \frac{2 \sin \theta (1 + \cos^{2} \theta)}{r^{2} \cos \theta}$$
(A83)

$$\frac{1}{E_y} \frac{\partial^2 E_y}{\partial y^2} = \frac{2 \sin^2 \theta}{r^2}$$
(A84)

and

$$A_{11} = U^2 \frac{2\cos^2 \theta}{r^2} - (jUYCos\gamma) \frac{2\cos\theta(1+\sin^2 \theta)}{r^2\sin\theta}$$
(A85)

$$A_{12} = U \frac{2 \operatorname{Sin} \theta (1 + \cos^2 \theta)}{r^2 \cos \theta} - (j U Y \cos \gamma) \frac{2 \operatorname{Sin}^2 \theta}{r^2}$$
(A86)

$$A_{21} = jUYCos\gamma \frac{2Cos^2\theta}{r^2} + (U^2 - Y^2Sin^2\gamma) \frac{2Cos\theta(1+Sin^2\theta)}{r^2Sin\theta}$$
(A87)

$$A_{22} = jUYCos\gamma \frac{2Sin\theta (1+Cos^2\theta)}{r^2Cos\theta} + (U^2-Y^2Sin^2\gamma) \frac{2Sin^2\theta}{r^2}$$
(A88)

It follows that

$$T_{11} = U^{2} - (U/X) (U^{2} - Y^{2}) - VU^{2} \frac{2\cos^{2} \theta}{r^{2}} + jVUY \cos \gamma \frac{2\cos \theta (1 + \sin^{2} \theta)}{r^{2} \sin \theta}$$
(A89)

$$T_{12} = -jUYCos\gamma - VU^2 \frac{2Sin\theta(1+Cos^2 \epsilon)}{r^2 Cos \theta} + jVUYCos\gamma \frac{2Sin^2 \epsilon}{r^2}$$
(A90)

$$T_{21} = jUYCos\gamma - V(U^2 - Y^2Sin^2\gamma) \frac{2Cos\theta(1+Sin^2\theta)}{r^2Sin\theta} - jVUYCos\gamma \frac{2Cos^2\theta}{r^2}$$
(A91)

$$T_{22} = U^2 - Y^2 \sin^2 \gamma - (U/X) (U^2 - Y^2) - V(U^2 - Y^2 \sin^2 \gamma) \frac{2 \sin^2 \theta}{r^2}$$

$$-jVUYCos\gamma \frac{2Sin\theta(1+Cos^2\theta)}{r^2Cos\theta}$$
(A92)

Since

$$[\varepsilon] = \frac{-\varepsilon_0 X}{U(U^2 - Y^2)} [T]$$
(A93)

 $[\epsilon]$ is now defined. The antenna capacitance is given by (Al3) and with (Al4) it is possible to write

$$\frac{C}{C_{o}} = \frac{\frac{-\epsilon_{o}X}{U(U^{2}-Y^{2})} \iint_{s} \frac{E_{i}T_{ij}E_{j}}{|E_{s}|} dS}{\epsilon_{o}\iint_{s} |E_{s}| dS}$$
(A94)

now since $E_z = 0$, and $r = R_s$

The statement of the statement of the statement

·

$$\frac{C}{C_{o}} = \frac{-X}{U(U^{2}-Y^{2})} \frac{1}{2\pi} \int_{0}^{2\pi} \frac{E_{x}^{T}11^{E}x}{|E_{s}|^{2}} + \frac{E_{x}^{T}12^{E}y}{|E_{s}|^{2}} + \frac{E_{y}^{T}21^{E}x}{|E_{s}|^{2}} + \frac{E_{y}^{T}22^{E}y}{|E_{s}|^{2}} d\theta \quad (A95)$$

and the second second

by use of the following relations

$$\begin{cases}
\frac{\partial \pi}{\partial t} & \text{Sin}^2 \theta d\theta = \pi \\
0 & \text{(A96)}
\end{cases}$$

$$\int_{0}^{\partial \pi} \cos^{2} \theta d\theta = \pi$$
(A97)

$$\sin^4 \theta d\theta = \frac{3\pi}{4}$$
 (A98)

$$\cos^4 \theta d\theta = \frac{3\pi}{4}$$
 (A99)

$$\partial \pi$$

Sin² $\partial \cos^2 \theta d\theta = \frac{2\pi}{8}$ (A100)

and by noting that all the other trigonometric expression integrate to zero, it is found that

$$\frac{1}{2\pi} \int_{0}^{2\pi} \frac{E_{x}^{T} 11^{E}_{x}}{|E_{s}|^{2}} dS = \frac{1}{2} \left[U^{2} (1 - 3V/2R_{s}^{2}) - (U/X) (U^{2} - Y^{2}) \right]$$
(A101)

$$\frac{1}{2\pi} \int_{0}^{2\pi} \frac{\frac{E_{x}T_{12}E_{y}}{|E_{y}|^{2}} = -\frac{1}{2} [5U^{2}V/2R_{s}^{2}]$$
(A102)

$$\frac{1}{2\pi} \int_{0}^{2\pi} \frac{\frac{E_{y}T_{21}E_{x}}{|E_{s}|^{2}} = -\frac{1}{2} \left[\left(U^{2} - Y^{2}Sin^{4}Y \right) \left(5V/2R_{s}^{2} \right) \right]$$
(A103)

$$\frac{1}{2\pi} \int_{0}^{2\pi} \frac{\frac{E_{y}T_{22}E_{y}}{|E_{s}|^{2}} = \frac{1}{2} \left[U^{2} (1-3V/2R_{s}^{2}) - (U/X) (U^{2}-Y^{2}) \right]$$
(A104)

The capacitance is then

$$\frac{C}{C_{o}} = 1 - (X/U) (1 - (W^{2}/2) \sin^{2} \gamma) (1 - 4V/R_{s}^{2}) / (1 - W^{2})$$
(A105)

This expression is identical to (A26) except for the $4V/R_s^2$ term that represents the effects of electron temperature. Thus (A105) is the antenna impedance from magneto-ionic theory including the effects of electron temperature.

Simulated Results

The above expression (A105) was programmed and the results were plotted. An example is shown in Figure A-2. If it is compared to a similar curve from Despain Theory as developed in the main text, the comparison is very poor. In fact, the results shown are physically so unlike other results that they cannot be accepted even as an approximation. Thus this theoretical technique cannot be used when finite electron temperatures are under consideration.

The exact reason for the discrepancy is unknown to the author; however, it is his opinion that the use of a polarization vector P to represent the hot electrons is in error. This formulation does not allow for electroacoustic (longitudinal) waves to exist in the plasma as does the theory developed in the text. It may well be that for

$$4V/R_{s}^{2} << 1$$

A-18



Fig. A-2. Magneto-ionic finite temperature theory impedance plot

that this formulation would produce correct results. This would be the case for either very high plasma frequencies or low electron temperatures. It is not suitable for the usual range of ionospheric parameters.

1.1.18

APPENDIX B

COMPUTER PROGRAMS

Introduction

All of the following programs were coded in Fortran IV and processed on an IBM 7044 computer at the University of Utah Computer Center. The computer system includes a CalComp digital plotter. Extensive use was made of this device to display simulated and experimental results. There are many programs that are part of the IBM 7044 and CalComp system. These system subroutines will not be included here, but can be obtained from the University of Utah Computer Center. Only the special external routines developed for the work reported in this paper will be given.

There are four mainline programs and a number of subroutines, some of which are used in more than one of the main line programs. Hence if a given routine cannot be found after the main program in which it is called, then it will either be cataloged under one of the other main line programs or is a subroutine included in the 7044/CalComp system. Each subroutine called by a program can also call other subroutines and read input data cards. Thus before an attempt is made to use the programs, all subroutines should be checked for additional call statements. The Fortran IV program listings follow the descriptions of the routines.

Main Program SWP4MD

SWP4MD is the main program for plotting theoretical antenna impedance as a function of frequency. The theory is contained in subroutine ANTZ of which there are four versions:

(a)	Magneto-ionic	theory	(c)	Wha!	le t	heory
-----	---------------	--------	-----	------	------	-------

(b) Balmain theory (d) Despain theory

Any one of these can be used with the main program. The program produces a tabular listing of the frequency, impedance, and plot coordinates with a heading block on each page. It can also write a tape suitable for data storage and external plotting. It produces a CalComp plot of impedance versus frequency. Each plot is 8" x 15", the ordinate ranges from -10^8 to $+10^8$ ohms on a logarithmic scale. The abscissa begins at zero and ends at a specified maximum frequency (MHz). There are many options and input variables. These are explained below.

N MEN

Variable Name	Function
npløts	Number of separate figures.
NRESLV	Number of separate data points per curve (resolution).
NTAPE	Identification of tape drive unit that out- put is written on. If negative or greater than 4, no tape is written.
NSKIP	Number of files skipped before data is written on tape unit NTAPE.
NPRINT	Ratio of total data points plotted and written on the tape to the data points printed on the listing.
NPLT	A branching constant. If set to zero, no plot is produced. If set to 1, a plot is produced including labels. If set equal to 2, the plot figure is labeled, but the curves are not.
MTHY	A branching constant such that if set to 2, the impedance is found as a function of plasma frequency, otherwise impedance as a function of operating frequency is determined
NDØ	Number of curves per figure.
KGRID	A dummy variable. May be set to any value.
FMAX	Maximum desired frequency (MHz) on the ab- scissa of the figure.

B-2

Variable Name

Function

FX The plasma frequency (MHz) is MTHY is 2, otherwise it is the operating frequency (MHz).

FH Electron gyrofrequency (Hz).

FNU Electron collision frequency (Hz).

T Electron temperature (°K).

R Antenna radius (m).

AL Effective antenna length (m).

- ANGLE Angle between the antenna axis and the magnetic field vector (degrees).
- RINIT Resistance to be added to the antenna impedance and its shunt capacitance.
- XINIT Reactance divided by the applied frequency that is to be added to the antenna impedance if MODE is 1. Otherwise, it is the fixed inductance in series with the antenna and its shunt capacitance.
- MØDE A branching constant. If MØDE is set to 1, jXINIT*F and RINIT are added to the antenna impedance. If MØDE and MTHY are set to 2, the difference between free space and actual antenna impedance is produced. If MTHY is not 2 and MØDE is set to 2, the actual antenna impedance is produced. If MØDE is set to 3, first the shunt capacitance and then the series resistance and inductance are added to the antenna impedance. If set to 4, the difference impedance from free impedance is plotted, with first the shunt capacitance and then the series resistance and inductance taken into account.

The following cards are called by the program:

Card No.	Format	Variables
1	7110	NPLØTS, NRESLV, NTAPE, NSKIP, NPRINT, MPLØT, MTHY
2	13A6	Major Title
3	13A6	Minor Title
4	2I10,2F10.3, 3E 12.6,I4	NDØ, KGRID, FMAX, FX, RINIT, XINIT, MODE
5	6E13.6	FH, FNU, T, R, AL, ANGLE

There is one card similar to card 5 for every separate curve (the number of curves is given by NDØ). Thus, if NDØ should equal 3, cards 6 and 7 would be similar to card 5. Each separate figure requires the groups of cards that follow card 1. Thus, if NPLØTS should be 2, all the cards after card 1 would be repeated for the second figure.

The following subroutines are called by SWP4MD:

Subroutine Name	Location	Function
CØNSTS	External	Calculate physical constants
SKPFLS	System	Skip over tape files
ANTZ	External	Calculate antenna impedance
IDPLØT	System	Generate plot identification
PLØT	System	Generate plot pen movements
SYMBL4	System	Generate plot symbols
NUMBER	System	Generate plot numbers
FINI	System	Generate plot ending

Subroutine ANTZ

There are several versions of ANTZ, each of which calculates antenna impedance according to several different theories. The primary variables are transferred through a labeled common statement as follows:

CØMMØN/IMPCØM/Z, F, FP, FNU, FH, ANGLE, T, R, AL

where

Variable	Function
Z	Complex antenna impedance
F	Exciting frequency
FP	Plasma frequency

B-4

Variable	Function
FNU	Electron collision frequency
FH	Electron gyrofrequency
ANGLE	Magnetic aspect angle (degrees)
Т	Electron temperature
R	Antenna radius (m)
AL	Antenna length (m)

Physical constants are transferred through another labeled common statement /C ϕ NSTA/. These constants can be obtained by a CALL C ϕ NSTS statement in the main line program. Further definitions of the constants are included under the description of subroutine C ϕ NSTS.

The Despain theory version of ANTZ also includes an additional labeled common statement /FPHIC/AR, PHI where

Variable	Function
AR	Complex variable αR in the Despain theory
PHI	Complex variable ϕ in the Despain theory

The Despain theory version of ANTZ calls subroutine APHICF that calculates PHI from AR and transfers the variables through the above described common statement. Subroutine APHICF must be included along with the main line and other programs when the Despain theory versions of ANTZ is used.

The Whale theory of ANTZ requires an interpolation subroutine INTERP, and this subroutine must be included when the Whale theory version of ANTZ is used.

And and a mark the second seco

Subroutine APHICF

This subroutine calculates the function PHL, given by

B--5

$$PHI = H_{AR} (AR) / (AR + H_{1} (AR))$$

where

14 Jac +

H = Hankel function of the first kind, zero order

 H_1 = Hankel function of the first kind, first order and PHI and AR are complex variables transferred through a labeled common statement as follows:

CØMMØN/APHIC/AR, PHI

Subroutine INTERP

INTERP is a interpolation subroutine that produces a interpolated value of YØUT for a given XIN from the arrays of data XA and YA where NPTS is the size of the array.

Subroutine CØNSTS

This subroutine calculates several physical constants. These constants arc transferred through a labeled common statement as follows:

CØMMØN/CØNSTA/PI, PI2, EMASS, Q, CK, EO, G, UO, ALPHAK

The constants are as follows:

Constants	Value	
PI	3.14159265	
PIZ	2.0 * PI	
EMASS	9.1083E-31	
AMASS	EMASS*1836.12*26.5	
Q	1.60206E-19	
CK	1.38044E-23	
EO	8.85434E-12	

Constants	Value
G	3.0
UO	PI*4.0E-07
ALPHAK	4.0*PI*PI*EMASS/(G*CK)

Main Program TMPCI

TMPCI is the main program for calculating and plotting the series resonance frequency of an antenna versus the parallel resonance frequency with electron temperature as a parameter. The program calls the following subroutines in the given order:

Subroutine Name	Location	Function
INPUT	External	Read in input data
GRID	External	Generate a plot grid
SICALC	External	Calculate ψ function
CURVEL	External	Plot array of data as a line
ARRØW	System	Generate a plot arrow
pløt	System	Generate plot pen movements
NUMBER	System	Write numbers on the plot
ØUTPUT	External	Generate output listing
FINI	System	End plotting
EXIT	System	End computing

Subroutine INPUT (TMPCI)

2.977.2

INPUT reads in the input data for main program TMPCI. The following cards are called by this routine:

Card No.	Format	Variables
1	215,6E11.5	NT, NFP, R, AL, FPMAX, FPMIN, SHEATH, FH
2	5E16.8	T(1), T(2), T(3), T(4), T(5)
3	5E16.8	T(6), T(7), T(8), T(9), T(10)

36 27

B-7

1

where

Variable Name	Function
NT	Number of curves per figure
NFP	Number of calculated points per curve
R	Antenna radius (m)
AL	Antenna length (m)
FPMAX	Maximum desired value of parallel frequency (MHz)
FPMIN	Minimum desired value of parallel frequency (MHz)
SHEATH	Desired size of sheath in Debye lengths
FH	Value of electron gyrofrequency
Т	Electron temperature

Subroutine SICALC

SICALC computes the ψ function of the Despain antenna impedance theory. It is used in conjunction with main program TMPC1 and the input variables are described under the description of TMPC1. Newton's method is used in an iteration process to find ψ from the imput parameters. The following subroutines are called by SICALC:

Subroutine Name	Location	Function
CØNSTS	External	Calculation of constants
К	External	Calculation of Bessel Function

Subroutine K

Subroutine K is a function subprogram. The call statement is K(N,X). It calculates the modified Bessel function of the second kind, of order N and argument X for N = 0,1. Subroutine I is called by subroutine K. X is a real variable.

Subroutine I

Subroutine I is a function subprogram. The call statement is I(N,X). It calculates the modified Bessel function of the first kind of order N and argument X for N = 0,1. X is a real variable.

Subroutine GRID

Subroutine GRID is a plot routine that draws a system of labeled coordinates 9" high and of variable length. There are four options controlled by TITLE, the first variable in the call list. Option 1 takes all the control constants from the call list. Option 2 reads the control constants from input cards and puts the values in the call list and in the labeled common statement /PLTCMN/. Option 3 reads the constants and puts them only in /PLTCMN/. Option 4 reads no cards but takes the variables from /PLTCMN/. The call list specifies the desired option, and the various possibilities are given below.

<u>Option</u>	Call List
1	(TITLE, SCX, SCY, XXB, XXE, YYB, YYE, NXX, NYY, XX15)
2	(6HVREADR, SCX, SCY, XXB, XXE, YYB, YYE, NXX, NYY, XX15)
3	(6HbREADb)
4	(6HCØMMØN)

The input variables are explained below:

Variable Name	Function
TITLE and HEAD	These are dimentioned arrays of A format data. These data are the labels for the plot coordinates.
SCX and SCALEX	The number of major divisions along the abscissa.
SCY and SCALEY	The number of major divisions along the ordinate.

Variable Name	Function
XXB and XB	The smallest value of the variable to be plotted along the abscissa.
XXE and XE	The largest value of the variable to be plotted along the abscissa.
YYB and YB	The smallest value of the variable to be plotted along the ordinate.
YYE and YE	The largest value of the variable to be plotted along the ordinate.
NXX and NX	The number of significant figures in the abscissa number labels.
NYY and NY	The number of significant figures in the ordinate number labels.
XX15 and X15	The desired length of the abscissa of the graph in inches.

Cards are read where options 2 and 3 are used.

Card No.	Format	<u>Variables</u>
1	13A6	HEAD (Label for abscissa)
2	13A6	HEAD (Label for ordinate)
3	13A6	HEAD (Major title of figure)
4	13A6	HEAD (Minor title of figure)
5	6F10.5,215,F10.5	SCALEX, SCALEY, XB, XE, YB YE, NX, NY, X15

No external subroutines are called. The result is a labeled graph X15" by 9", divided into SCALEX x SCALEX divisions with 10 minor divisions indicated along the edge of the figure.

Subroutine CURVEL

Ι

....

Ī

£.

Curvel is a plot routine used in conjunction with subroutine GRID. Curvel generates a curve of line segments that connect the array of points given by AX, AY, and N. The abscissa values are AX, the ordinate values are AY and N is the number of points or array values. AX and AY may be dimensioned at any desired value in the main program. The remaining arguments in the call list are scaling constants provided by subroutine GRID and have the same meaning as explained above.

Subroutine ØUTPUT (TMPC1)

ØUTPUT prints a listing of the results of subroutine SICALC in a tabular form with a heading block on each page. ØUTPUT is called by TMPTC1. No subroutines are called and no cards are read by ØUTPUT. All data is transferred through the labeled common statement /INPTS/.

Main Program TEP601

TEP601 is the main program for the calculation of electron temperature from the series and parallel resonance frequencies of the antenna impedance. TEP601 reads the input data, calls subroutine TEMPSP, and punches and prints both the input data and calculated temperature. The program variables are:

Vari	able Name	Function
	R	Antenna radius (m)
	AL	Antenna length (m)
	PERCNT	Allowable error in calculation of temperature (10% error would be put in as .10).
	LIMIT	Maximum number of interations allowed in the recursive cal- culation of electron temperature.
	CC	Value of any coupling capacitor (farads). If none exists, CC should equal 1.0.
	S	Sheath width in number of Debye lengths.

Variable Name	Function
TSTART	Iteration starting value of electron temperature (typ- ically 1000.0).
FMT	Format specification for main input data card deck.
F	Series resonance frequency (MHz).
FP	Parallel resonance fre- quency (MHz).
SEC	Time in seconds or any other data identification variable.
ØΤ	An input variable carried over from the input data to the new punched cards and printed listing.

The following cards are called by the program:

I

٢

.

Card No.	Format	Variables
1	3F10.2,15,E15. 7,2F10.2	R, AL, PERCNT, LIMIT, CC, 3, TSTART
2	13A6, A2	FMT
3	FMT	F, FP, SEC, ØT
4	FMT	F, FP, SEC, ØT
	etc.	

The following routines are called:

Subroutine Name	Location	Function
CRUIDS	System	Identify punched cards
TEMPSP	External	Calculate electron temperature
CRDIDF	System	End card punching

and the set of the set

Subroutine TEMPSP

Subroutine TEMPSP calculates the electron temperature from the series and parallel resonance frequencies of an antenna. Sheath effects can be taken into account by specifying the width of the sheath.

The calculation begins by assuming an initial electron temperature. This is provided externally along with the resonance frequencies and antenna parameters. The Debye length is then calculated from these values. The Debye length is then used to find the capacitance between the antenna and the outside edge of the sheath. The value of ϕ in the Despain theory can now be calculated. External subroutine ETTA calculates the argument of ϕ from the value of ϕ . The electron temperature can then be determined from this argument (α 'R in the Despain theory). This value of temperature is compared to the initial value, and if it is within the set error limits, the value of temperature is printed and punched and a new set of data is considered. If the temperatures differ more than the allowed error, the initial test temperature is set equal to the newly calculated temperature, and the calculation is repeated.

The variables for this routine are transferred through the labeled common block /KEN/ and they are defined above in connection with program TEP601.

Subroutine ETAA

ETAA calculates the inverse function η of the ϕ (α 'R) of the Despain theory for real numbers only. Given the value of ϕ , the subroutine determines α 'R by a iteration process. A value of α 'R is assumed. The corresponding value of ϕ is then determined. This value is compared to the original value of ϕ , and according to the difference between the values, the program either returns a value for α 'R or makes a better estimate of α 'R and repeats the process until the difference is less than .00001.

ETAA calls subroutine K(N,X) discussed above in connection with main program TMPTC1.

Main Program IMPPLT

NUMBER OF

IMPPLT is the main program for plotting antenna resistance versus reactance with electron temperature and plasma frequency as parameters. The actual antenna impedance is calculated in subroutine ANTZ. As discussed above, several versions of ANTZ have been developed and any of these can be used in this main program. The program variables are:

Variable Name	Function
NPLØTS	The n umber of separate figures to be produced.
NRESLV	The number of calculated points per curve.
NTAPE, NSKIP	Dummy variables, may be any integer.
NPRINT	The desired ratio of calculated and plotted points to the number of points printed on the tabular listing.
MPLT	The desired ratio of calculated and plotted points to the number of points indicated by a short line segment drawn normal to the curve and through the indicated point.
МТНҮ	A branching constant such that if it is set to 1, the electron collision frequency is specified by the altitude and electron temperature, otherwise collision frequency is taken from the input data.

V	a	r	1	a	b	1	e	N	a	m	e	
		_		_		-			-	_	_	

N DØ, KGRID	Dummy variables, may be any integer.
FMAX	The maximum value of plasma frequency (MHz) to be plotted.
FX	The value of the antenna exciting frequency (Miz).
FI	Electron gyrofrequency (Hz).
FKU	Electron collision frequency (Hz).
R	Antenna radius.
AL	Antenna length.
ANGLE	Magnetic aspect angle (degrees).
FNUCØN	A constant that relates collision frequency to altitude and electron temperature.
DEN	Total particle density of atmosphere at the given altitude.
ALT	Altitude

The following cards are called by the program:

Patration of a second

Card No.	Format	Variables
1	7110	NPLØTS, NRESLV. NTAPE, NSKIP, NPRINT, NPLT, MTHY
2	2110, 2F10.3	DNØ, KGRID, FMAX, FX
3	6E13.6	FH, FNU, T, R, AL, ANGLE
4	2E20.8, F10.3	FNUCØN, DEN, ALT
5,6,7,8,9	are called by subr	outine GRID discussed above.

Cards 2 through 9 are called once for each individual figure. The number of figures is specified by NPLØTS.

an area - area in

The following routines are called by IMPPLT:

Subroutine Name	Location	Function
CØNSTS	External	Calculate physical constants
GRID	External	Generate a plot grid
ANTZ	External	Calculate antenna imped- ance
pløt	System	Generate plot pen move- ments
FINI	System	End plotting

ł

To and the

Prime v

ſ

the second second second second

MAIN PROGRAM FOR PLOTTING ANTENNA IMPEDANCE AS A FUNCTION OF FREQUENCY

```
SIBFTC SWP4MD
C PRUGRAM FOR PLCITING ANTENNA IMPEDANCE
OIMENSION XX(1510), HEAD(50), XYZ(50), XRII5IO)
CUMPLEX 2,2FIRST,2SERIE,ZSHUNT,2PAR,ZINTSH
COMMUN/IMPCOM/2,F,FP,FHU,FH,ANGLE,T,R,AL
        LOGICAL NTFRST , UTAPE , FIRST
UTAPE = .FALSE.
        CALL CONSTS
         READ 1, NPLOTS, NRESLV, NTAPE, NSKIP, NPRINT, MPLT, MTHY
         PRINT 1, NPLOTS, NRESLV, NTAPE, NSKIP, NPRINT, MPLT, MTHY
      1 FORMAT(7110)
        NR1 = NRESLV +1
NRX = 1500/NRESLV
         IF ( (NTAPE.GE. 0). AND. (NTAPE.LE.4) ) UTAPE=.TRUE.
      IF(.NOT.UTAPE) GO TO 6
6 REWIND NTAPE
      7 CALL SKPFLS(NTAPE,NSKIP,0)
8 00 113 JNP =1, NPLOTS
NTFRST = .FALSE.
      READ 9, (HEAD(J),J=1,I3)
READ 9, (HEAD(J),J=14,26)
9 FURMAT(I3A6)
         READ 10, NOO, KGRIO, FMAX, FX, RINIT, XINIT, CSHUNT, MUDE
         PRINT 3,NDO,KGRID,FMAX,FX,RINIT,XINIT,CSHUNT,HODE
    10 FORMAT (2110,2F10.3,3E12.5,14)
3 FORMAT(1H1,2110,2F10.3,3E12.6,14)
        FXM = FMAX+ 1.0E+06
FXX = FX+ 1.0E+06
SCALE = 15.0/FMAX
         SCXCON = .1E+05/SCALE
     11 \text{ FP} = \text{FXX}
    12 F = FXX
     13 DO111 M=1, NOG
         READ 14, FH, FNU, T, R, AL, ANGLE
      PRINT 2, FH, FNU, T, R, AL, ANGLE
2 FORMAT( 1H1, 6E13.6)
     14 FORMAT(6E13.6)
         FHX=FH+1.0E-06
         FNUX=FNU+1.0E-06
         IF (UTAPE) WRITE (NTAPE, 15) F, FP, FXM, FH, FNU
         IF (UTAPE) WRITE (NTAPE, 15) T, R, AL, ANGLE, SCALE
     15 FORMAT(5E16.8)
         KPAGE = 52
         JK = NPRINT
         IF (MTHY.EQ.2) GO TO 26
     16 00 25 K = 1, NR1
AK = (K-1)+(NRX)
         IFPNT = AK/10.0
         F = AK+SCXCON
         ZSHUNT=CMPLX(0.0,(-1.0/CSHUNT+F+P12))
         ZSERIE=CMPLX(RINIT,XINIT+F+P12)
         FPNT = F+.1E-05
         CAEL ANTZ
         GO TO (551,552,553,552),MODE
   551 RAA=REAL(2)+RINIT
```

The second second of the second s

And a second second

The second stranger

```
XAA=AIMAG(2)+XINIT+F
552 GU TO 67
553 ZPAR=Z+ZSHUNT/IZ+ZSHUNT)
     RAA=REAL(ZPAR)+REALIZSERIE)
     XAA=AIMAG(ZPAR)+AIMAGIZSERIE)
554 GO TO 67
67 RA = RAA
XA = XAA
     AM =1.0
     IF(XA.EQ.0.0) XA=1.0E-37
     IF (XA.GE.0.0)GO TO 17
     AM = -1.0
     XA = -XA
 17 XT = ALOGIO(XA)
IF (MODE.EQ.1) GO TO 68
     IF(XT.LT.I-2.0)) XT=0.0
     XX(K)=XT+AM
 GO TU 69
68 IF(XT.LT.O.O)XT =0.0
XX(K) = XT*AM/2.0
69 IX = 1000.0*XX(K)
AR= +1.0
      IF(RA.EQ.0.0)RA=1.0E-37
      IF (RA.GE.0.0)GU TO 18
     AR = -1.0
 RA = -RA

18 RT = ALOGIO(RA)

IF (MODE.EQ.1) GO TO 7J

IF (RT.LT.(-2.0)) RT=0.0

XR(K)=RT=AR
 GO TO 71
70 IF(RT.LT.0.0) RT=0.0
     XR(K) = RT+AR/2.0
 71 IR = 1000.0+XR(K)
IF(UTAPE) WRITE (NTAPE, 5) IFPNT, IR ,IX,RAA,XAA, F
   5 FORMAT (3110,2X,3E16.8)
     JK = JK+1
      JJ = JK/NPRINT
      IFIJJ.LT.I)GU TU 25
     KPAGE = KPAGE + 1
IF(KPAGE.LE.50)GO TO 23
      KPAGE = I
     PRINT 19
  19 FORMAT(1H1)
      PRINT 20
  20 FORMAT(1H ,:32H-----
    2-----
                             1
   PRINT 4, FX, FHX, FNUX, ANGLE, T,R,AL
4 FURMAT( 2X,4H<sup>5</sup>P =,F5.2,14H MHZ , NH =,F4.2, 14H MLZ , NU =,
1F7.4, 17H MHZ , ANGLE =,F5.2, 13H DEG , T =, F7.1, 14H DEG K
2 , R =, F7.5, 11H M , L =, F5.2, 2H M)
PRINT 37,(HEAD(J),J=1,13)
  37 FORMATCIH ,2X,1346,50H -
                                         IMPEDANCE AS A FUNCTION OF DRIVING FREQ
    IUENCY
                         1
```

and the set of the set

3. A.S. A.S.

B-18

```
PRINT 20
     PRINT 20
 PRINT 22
22 FORMAT(110H FREQUENCY (MHZ)
                                                RESISTANCE (OHMS)
PLOTR (INCHES)
                                                                                     REACTANCE
                           PLOTX (INCHES)
    1 (OHMS)
     PRINT 20
 23 PRINT 24, FPNT,RAA,XAA,XR(K),XX(K)
24 FORMAT(IH ,FI0.3,2E25.8,2F20.3)
     JK=0
 25 CONTINUE
 GU TO 36
26 ZSERIE=CMPLX(R(NIT,XIN(T+FXX+P(2)
     ZSHUNT=CMPLX(0.0,1-1.0/(CSHUNT+FXX+P12)))
     DO 35 K = I, NRI
AX = {K-1}+{NRX;
IFPNT = AK/10.0
FP = AK+SCXCCN
FPNT = FP+.1E-05
     CALL ANTZ
     IF(K.EQ.1) ZFIRST=Z-ZSERIE
GO TO (441,442,443,444),MODE
441 RAA=REAL(Z)+RINIT
     XAA=A(MAG(Z)+XINIT+FXX
     GO TO 87
442 RAA=REAL(Z)-REAL(ZF(RST)
     XAA=A(MAG(Z)-AIMAG(ZFIRST)
     GO TO 87
443 ZPAR=Z+ZSHUNT/(Z+ZSHUNT)
RAA =REAL(ZPAR)+REAL(ZSERIE)
XAA=AIMAG(ZPAR)+AIMAG(ZSERIE)
     GU TO 87
444 ZPAR=Z=ZSHUNT/(Z+ZSHUNT)
     IF(K.EQ.1) ZINTSH=ZPAR
     RAA =REAL(ZPAR)-(REAL(ZINTSH)-REAL(ZSER1E))
     XAA+AIMAG(ZPAR)-(AIMAG(ZINTSH)-AIMAG(ZSERIE))
 87 RA = RAA
     XA = XAA
     AM =1.0
     AM = 1.0

IF(XA.EQ.0.0) XA=1.0E-37

IF(XA.GE.0.0)GU TO 27

AM = -1.0

XA = -XA
 27 XT = ALOGIO(XA)
     IF (MODE.EQ.I) GO TO 78
IF (XT.LT.(-2.0)) XT=0.0
     XX(K) = XT + AM
     GU TO 79
 78 IF (XT.LT.0.0) X1 =0.0
 XX(K) = XT+AM/2.0
79 IX = 1000.0+XX(K)
AR= +1.0
      IF (RA. EQ. 0.0) RA=1.0E-37
     IF (RA.GE.0.0)GU TO 28
     AR = -1.0
RA = -RA
```

And a state of the second of the second state of the second state

and States and

and the second secon

16-

B-20

```
28 RT = ALOGIO(RA)
      IF (MODE.EQ.1) GO TO 80
IF (RT.LT.(-2.0)) RT=0.0
      XR{K)=R[=AR
      GO TO 81
 80 IFIRT_LT.0.03 RT=0.0
 XR{K} = &T+AR/2.0
81 IR = 1000.0+XR{K}
      IFIUTAPE) WRITEINTAPE,5) IFPNT, IR, IX, RAA, XAA, FP
      \mathsf{JK} = \mathsf{JK+1}
      JJ = JK/NPRINT
      IF(JJ.LT.1)GO TO 35
KPAGE = KPAGE + 1
      IFIKPAGE .LE.SO) GO TO 33
      KPAGE = 1
PRINT 19
      PRINT 20
      PRINT 21, (HEAD(J), J=1, 13)
 21 FORMAT(1H , 2X, 13A6, 48H - IMPEDANCE AS A FUNCTION OF PLASKA FREQUE
     INCY 1
INCY )

PRINT 666, FX, FHX, FNUX, ANGLE, Y,R,AL

666 FORMAT(2X,4HFO =,F5.2,14H MHZ , WH =,F4.2, 14H MHZ , NU =,

IF7.4, 17H MHZ , ANGLE =,F5.2, 13H DEG , T =, F7.1, 14H DEG K

2 , R =, F7.5, 11H M , L =, F5.2, 2H M)

PRINT 20

PRINT 20

PRINT 20

PRINT 20
      PRINT 22
      PRINT 20
 33 PRINT 24, FPNT, RAA, XAA, XR(K), XX(K)
       JK=0
  35 CONTINUE
 36 IFIUTAPEIEND FILE NTAPE
      IF (MPLT.EQ.0)GO TO 111
IF (NTFRST)GO TO 106
SCFP = SCALE+FX
      W1B=(SCALE+FX-1.5)/2.0
      W1E=W18+1.5
      W2B = (13.5+SCALE+FX)/2.0
W3B = W2B + .05
      A18=W18+1.55
      A2B=W2B+1.6
      YYS = 0.0
YYM = 0.0
      KI = K
      CALL IDPLOT
CALL PLOT (2.0,5.3,-3)
      FPP=FX+SCALE
       L = 150./SCALE
      LL = L/10
      00100J=1.L
      AJ = J
AJ = AJ=SCALE/10.0
      CALL PLOT (AJ,0.0.2)
CALL PLOT (AJ,+0.1,3)
CALL PLOT (AJ,-0.1,2)
```

و و و و و و و و

÷ .

Ē.

-

77

```
100 CALL PLOT (AJ,0.0, 3)
     IF(MPLT.NE.1) GO TO 101

CALL PLOT (FPP,+0.1,3)

CALL PLOT (FPP,-0.1,2)

CALL SYMBL4(FPP-.05,+0.25,0.15,1HF,0.0,1)
     CALL SYMBL4(FPP+.02,+0.2,0.1,1HP,0.0,1)
101 DO 102J =1,LL
AA = Lt+1-J
BJ = AA+SCALE
CALL PLOT(BJ,+.15,3)
CALL PLOT(BJ,-.15,2)
102 CALL NUMBER(BJ-0.17,-0.30,0.15,AA,0.0,1)
     CALL SYMBL4(6.35,-.65,0.2,12HFREQUENCY-MC,0.0,12)
103 CALL PLOT (0.0,-4.0,3)
     IF(MODE .NE.1) GO TO 222
OO 105J =1,17
     JC = J-9
JL = JC
     CY = CJ/2.0
CZ = CJ
     IF(CJ.LT.0.0) CZ = -CJ
CALL PLOT(0.0, CY ,2)
CALL PLOT(+0.1,CY ,2)
     CX = +10.0
      IF(CJ.LT.0.0) GO TO 114
      CALL NUMBER(-0.1,CY-0.1 ,.15,CX ,90.0,0)
104 CALL NUMBER(-.25,CY+0.1,0.1,C2,90.0,0)
105 CALL PLOT (0.0,CY,3)
GO TO 406
222 DO 405 JJJ=1,13
      JC = JJJ = 7
     CJ=JC
     CY=CJ+.66666666
     CZ=CJ
      IF(CJ.LT.0.0) CZ=-CJ
     CZ=CZ-2.0
     CALL PLOT(0.0, CY ,2)
CALL PLOT(+0.1,CY ,2)
CALL PLOT(+0.1,CY ,2)
CX = +10.0
      (F(CJ.LT.0.0) GO +0 114
       CALL NUMBER(-0.1,CY-0.1 .15,CX ,90.0,0)
223 CALL NUMBER(-.25,CY+0.1,0.1,CZ,90.0,0)
405 CALL PLOT (0.0,CY,3)
406 CALL SYMBL4(-.5,-1.8,.2,24HANTENNA IMPEDANCE (OHMS),90.0,24)
     CALL SYMBL4(0.0, -4.5, 0.2, HEAD(1),0.0,78)
CALL SYMBL4(3.35, -4.7, 0.1, HEAD(14),0.0,78)
CALL PLOT(+0.0, -4.0,3)
CALL PLOT(15.0, -4.0,2)
     DO 118 J = 1 , 17
JC = J - 9
CJ = JC
     CY = CJ/2.0
     CALL PLOT(15.0,CY.2)
     CALL PLOT(14.9,CY,2)
```

···· ••*

and the second second

The second states and the

يسرد درار ويتبين ويتعاد وراد بمراه

And a Distance

with the second second

```
118 CALL PLOT(15.0,CY,3)
        CALL PLOT( 0.0,+4.0,2)
106 NTFRST = TRUE.
FIRST = TRUE.
        DO 109 K = 1, NR1
        AK = (K-1) \circ NEX
        AK = AK/100.0
        XY = XX(K)
IF(XY.GT.4.0) XY = 4.0
        IF (XY.LT. (-4.0)) XY = -4.0
IF (FIRST) CALL PLOT(AK,XY,3)
        IF ( FIRST) CALL PLOT(A)
FIRST = .FALSE.
CALL PLOT(AK,XY,2)
IF(MPLT.NE.1) GO TO 109
IF(AK.LT.NIE) GO TO 107
IF(AK.GT.A1B) GO TO 107
         1F(XY.GT.YYS)YYS = XY
1F(XY.LT.YYM)YYN = XY
107 IF (AK.LT.W28) GO TO 108
IF (AK.GT.W38) GO TO 108
         IF (XY.LT.XYS)XYS = XY
IF (XY.GT.XYN)XYM = XY
108 IF(KI.EQ.0) GO TO 109
IF((XY.GE.0.0).AND.(XYY.LE.0.0))GO TO 115
         XYY = XY
109 CONTINUE
        FIRST = .TRUE.
DO 110 K=1,NR1
         AK = (K-1)+NRX
AK = AK/100.0
         RR = XR(K)
        RR = ARIN;

IF(RR.GT.4.0) RR = 4.0

IF(RR.LT.(-4.0)) RR = -4.0

IF(FIRST ) CALL PLOT (AK,RR,3)

FIRST = .FALSE.
         CALL PLOT (AK,RR,2)
         IF (MPLT.NE.1)GO TO 110
         IF(AK.LT.W28) GO TO 110
IF(AK.GT.W38) GO TO 110
         IF (RR.GT.RYS)RYS = RR
         IF(RR.LT.RYM)RYM = RR
110 CONTINUE
111 CONTINUE
         IF (MTHY.NE.1)GO TO 112
IF (MPLT.EQ.0) GO TO 113
IF (MPLT.NE.1)GO TO 112
        IF(MPLT.NE.1)GO TO 112

IF(SCFP.LT.1.0)GO TO 112

IF(YYS.GT.3.0)YSW = YYM - .5

IF(YYS.LE.3.0)YSW = YYM - .5

IF(YYS.LT.0.0)YSW = YYM - .5

IF(YYS.LT.(-3.0))YSW = YYS + .5

CALL SYMBL4(W1B,YSW,0.1,17HANTENNA REACTANCE,0.0,17)

IF((SCFP-15.0).GT.(-1.6)) GO TO 112

IF(XYS.LT.(-3.0))XSW = XYM + .5

IF(XYS.GE.(-3.0))XSW = XYS - .5
```

. .

```
IF(XYS.GE.( 0.0))XSW = XYN + .5
IF(XYS.GE.( 3.C))XSW = XYS - .5
IF(RYS.GT.( 3.0))RSW = RYM - .5
IF(RYS.LE.( 3.0))RSW = RYM - .5
IF(RYS.LE.( 0.0))RSW = RYM - .5
IF(RYS.LE.( 0.0))RSW = RYS + .5
CALL SYNBL4( W28,XSW,0.1,17MAMTENMA REACTANCE,0.0,17)
CALL SYNBL4(W28,RSW,0.1,18HAMTENMA RESISTANCE,0.0,18)
112 CONTINUE
CALL PLOT (18.0,-5.3,-3)
113 CONTINUE
IF(UTAPE)REWINDNTAPE
IF(MPLT.EQ.O) STOP
CALL FINI
STOV
114 CX = -10.0
CALL NUMBER(-0.1,CY-.22,.15,CX,90.0,0)
IF(MODE.NE.1) GO TO 223
GO TO 104
115 CALL SYNBL4(AK-.03,.17,.07, 3HT =,90.0,3)
TT = T
IF(T.EQ.0.0) TT = 1.0E-36
KAT = ALOGIO(TT)
TAK = KAT +7
TX =.17 + TAK*.05636363
CALL SYMBL4(AK-.10,TX-.05,.15,1H.,90.0,1)
CALL SYMBL4(AK-.03,.41,.07,T,90.0,0)
KI = 0
CALL PLOT (AK,XY,3)
GO TO 109
END
```

معمد المعريد والمراجرة محافظته والمعقوم والمعامد والمعرب والمعراقة

and the second s

A an age of the second se

~ 4

SUBROUTINE TO CALCULATE ANTENNA IMPEDANCE ACCORDING TO MAGNETO-IONIC THEORY

END

0 \$IBFTC ANTZ HAGNETO - IONIC THEORY C FUNCTION SUBPROGRAM FOR CALCLATION OF ANTENNA IMPEDANCE SUBROUTINE ANTZ COMPLEX U,U2, YU,O,Z COMMON/CONSTA/PI,PI2,EMASS,AMASS,Q,CK,EO,G,UO,ALPHAK COMMON/INPCOM/Z, F, FP, FNU, FH, ANGLE, T, R, AL CL=ALOG(AL/R) IF(F.LE.0.0) GO TO 1 WF=P120F CO=P120E00AL/CL IF (FP.LE.0.0) GO TO 2 F2=F002 FP2=FP++2 X=FP2/F2 Y=FH/F Z=FNU/WF U=(1.6,0.0)-(0.0,1.0)+Z¥2=¥+¥ U2=U+U YU=Y2/U2 YR=((G+CK+T)/(2.0+EMASS+R+R)+FP2) O=(0.0,1.0)+WF+CO+(U+(YU-1.0)+(1.-VR)+(X-(X+YU+SIN(ANGLE)++2)/2.)) IF(REAL(0).EQ.J.O.ANO.AIMAG(0).EQ.O.O) GO TO 11 Z=U+(YU-1.0)/0 RETURN 1 Z=(0.0,-.1E+37) RETURN 2 Z=- (0.0,1.0)/(WF+CO) RETURN 11 PRINT 12,YU,U,X 12 FORMAT(14H ERROR IN ANTZ , 5E16.8) RETURN

B-24

SUBROUTINE ANTZ ACCORDING TO BALMAIN THEORY

.

```
SEBETC ANTZ
                   LIST
C FUNCTION SUBPROGRAM FOR CALCULATION OF ANIENNA IMPEDANCE
       SUBROUTINE ANTZ
        COMPLEX U, A2, EKO, EKP, AA7, AA, FM, FR , AR, J, TT, CSQRT, CLOG, TNMAG, AA1, Z
        COMMON/CONSTA/PI, PI2, EMASS, AMASS, Q, CK, EO, G, UO, ALPHAK
        COMMON/IMPCOM/2+F+FP+FNU+FH+ANGLE+T+R+AL
       CIMPUTA/MPC
WF = P(2*F
F2 = F*F
F2 = F*F
F2 = F*F
X = FP2/F2
Y = FH/F
7 = FNU/WF
       U = \{1.0, 0.0\} - \{0.0, 1.0\} = Z
       ku = (1.0, C.0) - X/U
fkp = (1.0, G.0)-X+U/(U+U+Y+Y)
AA2 = EKP/EKU
        TT ={0.0,0.0}
        IF(T.LT.1.0)60 TO 2
        A2 = \{F2 + ALPHAK/T\} + (X-U)
AR = R+CSURT(A2)
     RAD = P(+ANGLE/180.
SN2 = SIN( RAD )+2
CN2 = COS( RAD )+2
        FM = CMPLX(SN7+0.0) + AA2+CMPLX(CN2+0.0)
FR =CSURT(FM)
        AA1 = {AA+FR}/((2.0.0.0)+FM)
TNMAG = TT
        IFIIREALIAAL).EQ.U.U.AND. (AIMAGIAAL) .EQ.O.O))GO TO 3
     TNMAG = -CLOG(AA1) +TT

3 Z=AA+((ALOG(AL/R)-1.G)+TNMAG)/(((0.0,1.0)+EKP+FR)+(P12+#F+E0+AL))
        RETURN
        END
```

- -

.

SUBROUTINE ANTZ ACCORDING TO WHALE THEORY

.

FN0

.

SUBROUTINE ANTZ COMPLEX Z, ARC, AZC COMMON/CONSTA/PI, PIZ, EMASS, AMASS, Q, CK, ED, G, HO, ALPHAK COMMON/IMPCUM/ Z.F.FP.FNU.FH.ANGLE.T.K.AL DIMENSION XRO(100), BKHO(100) LUGICAL FIRST REAL LAMD IF(FIRST) GO TU 11 FIRST=.TRUE. DATA 8KR0/.50,.52,.535,.55,.565,.58,.60,.61,.62,.635,.645,.655,.66 15,.67,.675,.685,.695,.70,.705,.710,.715,.72,.725,.728,.73,.73,.73 25,.738,.740,.745,.748,.750,.755,.758,.759,.760,.762,.763,.764,.765 3+.77+.772+.77+.765+.75+.75+.74+.735+.72+.715+.70+.695+.665+.65+.6 43++615++600++580++565++555++545++53++52++51++505++495++485++475++4 565++455++450++440++435++430++42++415++410++405++402++395++390++385 6+- 380+- 375+- 370+- 368+- 365+- 360+- 355+- 350+- 340+- 325+- 315+- 305+- 295+ 7.290, 280, 275, 270, 265/ DATA XRO/.10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 124, 25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35, 36, 37, 38, 39, 40 2, 41, 42, 43, 44, 45, 46, 47, 48, 50, 55, 60, 65, 70, 75, 80, 25, 390, 95, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24 4,2.5,2.6,2.7,2.8,2.9,3.0,3.1,3.2, 3,3.4,3.5,3.6,3.7,3.8,3.9,4.0,4 5.1,4.2,4.3,4.4,4.5,4.6,4.7,4.8,4..,5.0,5.5,6.0,6.5,7.0,7.5,8.0,8.5 6,9.0,9.5,10.0 / 11 CL = ALOG(AL/R) IF(F.LE.0.0) GU TO 1 WE =PI2=F CO = PIZ+EO+AL/CL X0 = -1.0/(#F+C0)IF(FP.LE.0.0) GO TO 2 F2 = F++2 FP2= FP++2 X = FP2/F2IF(X.EQ.1.0) GO TO 1 2x = x0/(1.0 - x)IF(T.LE.O.O) GU TO 3 V = SQRT(G+CK+T/EMASS) LAMD =625.0+SQRT(T)/FP R0 =R + 4.0.0LAMD C2 ={C0/AL}+2 IF(X.GE.1.0) GU TO 3 $A2 = [1 \cdot 0 - X] \cdot FP2 \cdot ALPHAK/T$ $AR = SURT(A2) \cdot RO$ 2:4 =4.0+(ZX++2) CALL INTERP (XRO, BKRO, AR, WHETA, 100) PVI=PI2+E0+R0+SQRT(1.0-X)/(X+V+C2+AL+WBETA++2) PVI2= PVI++2 IF(ZX4.GT.PVI2)GO TO 3 kI= .5*(PVI + SQRT(PVI2-2X4))
R2= .5*(PVI - SQRT(PVI2-2X4)) ZR =R1 IF(RI_GT_R2)ZR=R2 / = CMPLX(ZR,ZX) RETURN 1 Z = CMPLX(0.0, -1E+37)RETURN 2 / = CMPLX(0.0,X0) RETURN 3 Z = CMPLX(0.0+ZX)RETURN

Rendered and a state of the second and the second second second second second second second second second second

1. 16.

SUBROUTINE TO CALCULATE ANTENNA IMPEDANCE ACCORDING TO DESPAIN THEORY

SIGFTC ANTZ DESPAIN THEORY 12/08/65 C Subroutine to calculate antenna impedance according to despain theory Subroutine antz SUBROUTINE ANTZ COMPLEX U,A2,U2,S2,A2U2DW,AR,CSQRT,PHI,Z,XO CONNON/CONSTA/PI,PI2,EMASS,AMASS,Q,CK,EQ,G,UO,ALPHAK COMNON/INFCON/2,F,FP,FNU,FH,ANGLE,T,R,AL COMNON /FPHIC/AR,PHI CL=ALOG(AL/R) IF(F.LE.0.0) GO TO 1 WF=PI2+F COMPD24ED0A4 /C1 CO=P12+EO+AL/CL XQ--(0.0,1.0)/(WF+C0) IF (FP.LE.0.0) GO TO 2 F2=F++2 FP2=FP++2 X=FP2/F2 Y=FWF Z=FNU/WF U=(1.0,0.0)-(0.0,1.0)+Z ¥2=¥•¥ U2=U+U \$2=(U2-Y2)/(U+X) IF(T.LE.0.0) GO TO 3 A2=(\$2-(1.0,0.0))+FP2+ALPHAK/T AR=R+CSQRT(A2) 5 IF(REAL(AR)) 6,7,8 6 IF(AIMAG(AR))11,17,10 7 IF(AIMAG(AR))9,17,10 8 IF(AIMAG(AR))9,9,11 9 AR--AR 17 IF(AINAG(AR).LE.O.O) AR-AR+(0.0,.1E-16) 10 CALL APHICF 2=X0+(PHI/CL-S2)/((1.0,0.0)-S2) RETURN 1 Z=(0.0,-.1E+37) RETURN Z-XO RETURN REIGAN 3 Z=-XD=52/((1.0,0.0)-52) RETURN 11 PRINT 12,AR,FH,FINS,ALP(4AK,T,R 12 FORMAT(14H ERROR IN ANT2 , 7216.8) RETURN

· •

- Interingent and

.

100

B-27

SUBROUTINE FOR CALCULATION OF PHYSICAL CONSTANTS

\$IBFTC CONSTS SUBROUTINE CONSTS COMMON /CONSTA/PI;PI2;EMASS;AMASS;Q;CK.E0,G; U0;ALPMAK PI = 3.14159265 PI2 =2.00PI EMASS = 9.1083E-31 AMASS = EMASS*1836.12*26.5 Q =1.60206E-19 CK = 1.38044E-23 E0 = 8.85434E-12 G = 3.0 U0 = PI *4.0E=07 ALPMAK = 4.00PI*PI*EMASS/(G*CK) RETURN ENO

INTERPOLATION SUBROUTINE

.

1.

· . . .

-

ng si yan

10.00

```
SUBRCUTINE INTERP(XA,YA,XIN,YOUT,NPTS)
DIPENSION XA(100),YA(100)
I=I
I IF(XA(I+I).GE.XIN.AND.XA(I).LT.XIN) G0 TO 2
IF(I.GE.(NPTS-2)) G0 TO 2
2=I+I
GC TO 1
2 YCUT=((XIU-XA(I+I))*(XIN-XA(I+2))*YA(I)/((XA(I)-XA(I+1))*(XA(I)-XA(I))*(XI)-XA(I))*(XI)*XA(I))*(XIN-XA(I+1))*(XA(I)-XA(I))*(XA(I))*(XI)*XA(I))*(XIN-XA(I+1))*(XA(I+2)/((XA(I+2)-XA(I))*(XI)*XA(I))*(XI)*XA(I))*(XI)*XA(I))*(XI)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I)*XA(I
```

SUBROUTINE FOR CALCULATION OF

A CONTRACTOR OF A CONTRACTOR OF A CONTRACTOR OF A CONTRACTOR OF A CONTRACTOR OF A CONTRACTOR OF A CONTRACTOR OF

PHI FUNCTION

A REAL AND ADDRESS

-

44"

```
SIBFTC APHICE DECK
        SUBROUTINE APHICE
        LOGICAL NTFRST, VALL, VAL2, VAL3, VAL4
        DOUBLE PRECISION XR, XI, PHIR, PHII, PI, PII, PIIZ, CPI2R, CPI2I, PI4I, PI3
      14, CP4R, CP4I, CP3R, CP3I, JR, JI, CMULTR, CMULTI, COVDR, DCVDI, AK, AI, SR, BI
      2, YR, YI, Y2R, Y21, BOR, BD1, B1R, B11, BJOR, BJ01, BJ1R, BJ11, BNOR, BND1, BN1R,
      38N11, TJOR, TJOI, TJIR, TJ11, TNOR, TNOI, TNIR, TN11, F, S, BORS, BOIS, BIRS, BI
      4IS, F1, SM, BN1RS, BN1IS, BJ1RS, BJ1IS, BFR, BF1, DLOG, DATAM2, HOR, HOI, HIR, H
511, X8R, X8I, X8GR, X8GI, POR, POI, Q0R, Q0I, P1R, P11, Q1R, Q11, TPOR, TPD1, TQD
      6R, TQDI, TP1R, TP11, TQ1R, TQ11, D, D2, DM2, D4, D4Q, D6, DQ, D2Q, F2, X81R, X8
      711, XBQIR, XBQII, RPO, RQO, RP1, R
BIRS, Q1IS, QDRS1, Q0IS1, Q1RS1, Q1IS1
COMPLEX AR, PH1
                               RP0,RQ0,RP1,RQ1,PORS,POIS,QORS,QOIS,P1R5,P115,Q
        COMMON /FPHIC/AR,PHI
        XR =REALIAR)
        XI=AIMAG(AR)
        VAL1=.FALSE.
        VAL2=.FALSE.
        VAL3=.FALSE.
        VAL4=.FALSE.
        IF (NTFRST) GO TO 1
        NTFRST=.TRUE.
       P1=3.1415926535897932
       PII=1.000/PI
       P112=16.000=P11
       CP128=P112
        CP121=0.000
        P141 =P1/4.000
        P134=P141+3.000
        CP4R=P141
        CP41=0.000
        CP3R=P134
        CP 31=0.000
        JR =0_000
        JI=1.000
        CNUL TR (AK, AI, BR, BI) = IAK+BR-AI+BI)
        CMULTI(AK,AI,BR,BI)=(BR+AI+AK+BI)
        CDVDR (AK,AI,BR,BI)= {AK+BR+AI+BI}/IBR+BR+BI+BII
       CDVD1 (AK,AI,BR,BI)= (AI+BR-AK+BI)/(BR+BR+BI+BI)
YR=CAULTRI.5D0,0.000,XR,XI)
YI=CAULTII.5DD,0.000,XR,XI)
     1
        K=1
        IF((YR.EQ.D.DDD).AND. 191.EQ.0.0)) K=2
       GO TO (3,4),K
YR=.10-17
     4
        Y1=0.0
     3 Y2R=CHULTRIYR, YI ; YR, YI)
        Y2I=CMULTIIYR, YI, YR, YI)
        IF(1XR++2+X1++2).GE.64.DD0) GO TO 13
        BDR=1.000
        801=0.000
        B1R=BOR
        811=80I
        BJOR=BDR
        8.101=801
```

```
BJ1R=BOR
BJ1I=BOI
   BNOR=0.000
BNOI=0.000
   BNIR=BOR
   BNLI=BOI
    TJOR=BOR
    TJ01=801
    TJIR=BOR
    TJ11=801
    TNOR=BNOR
   TNOI=BNOI
TNIR=BOR
    TN11=801
   F=1.000
   S=0.000
   DO 9 K=1+100
BORS=BOR
    801 S=801
   BIRS=BIR
   B115=B11
   F1=F+1.000
B0R=-(B0RS+Y2R-B0IS+Y2I)/(F+F)
B0I=-(B0IS+Y2R+B0RS+Y2I)/(F+F)
B1R=-(B1RS+Y2R-B1IS+Y2I)/(F+F1)
   B11=-(B11S+Y2R+B1RS+Y21)/(F+F1)
    S=S+1.0D0/F
    SM=2.000+5 +1. J00/F1
   BJOR=BJOR+BOR
   BJ0I=BJ0I+B0I
   BJ1R=BJ1R+B1R
   BJ11=BJ11+B11
BNOR=BNOR+BOR+S
    BNOI=BNOI+BOI+S
    BN1R=BN1R+B1R+SM
    BN11=BN11+B11+SM
    IF(BJOR.NE.TJOR.OR.BJOI.NE.TJOI) GG TO B
IF(BJIR.NE.TJIR.OR.BJII.NE.TJII) GO TO 7
   IF (BNOR.NE.TNOR.OR.BNOI.NE.TNOI) GO TO 6
IF (BNIR.NE.TNIR.OR.BNII.NE.TNII) GO TO 5
 GC TO 10
5 TN1R=BN1R
   TN11=8N11
 6 TNOR=BNOR
    TNOI=BNCI
 7 TJ1R=BJ1R
 TJ11=BJ11
B TJOR=BJOR
   TJOI=BJOI
 9 F=F1
10 BNOR=2. ODO+BNOR
   BN01=2.000+BN01
   BNIRS=BNIR
   BN11S=BN11
   BJ1RS=BJ1R
```

· • •

ų

```
BJ115=8J11
   BN1R=CMULTR(BN1RS,BNIIS,YR,YI)+CDYDR( 1.000,0.000,YR,YI)
BN1I=CMULTI(BN1RS,BNIIS,YR,YI)+CDVDI( 1.000,0.000,YR,YI)
   BJIR=CMULTR(BJIRS,BJIIS,YR,YI)
BJII=CMULTI(BJIRS,BJIIS,YR,YI)
    BFR=2.0D0+1.5772156649015328 +.5D0+DL0G(YR+YR+YI+YI))
   8F1=2.0D0+DATAN2(YI, YR)
    BNOR=(CMULTR(BFR,BFI,BJOR,BJOI)-BNOR)+FII
   BNOI=(CMULTI(BFR,8FI,BJOR,8JOI)-8NGI)•PII
BNIR=(CMULTR(BFR,8FI,BJIR,BJII)-8NIR)•PII
BNII=(CMULTI(BFR,8FI,8JIR,8JII)-8NII)•PII
11 HOR=BJOR+CHULTR (JR, JI, BNOR, BNOI)
   HOI=BJOI+CHULTI(JR,JI,BNOR,BNOI)
HIR=BJIR+CHULTR(JR,JI,BNIR,BNII)
HII=BJII+CHULTI(JR,JI,BNIR,BNII)
    PHIR=CDVDR(HQR,HOI,(CHULTR(CHULTR(YR,YI,HIR,HII),CHULTI(YR,YI,HIR,
   1H11),2.000,0.000)), (CHULTI (CHULTR (YR, YI, HIR, H11), CHULTI (YR, YI, H1R,
  2H11),2.0D0,0.0D0)))
   PHIL=COVDI (HOR,HOI, (CMULTR(CMULTR(YR,YI,HIR,HII),CMULTI(YR,YI,HIR,
  1H11),2.0D0,0.000)), (CHULTI (CHULTR (YR, YI, H1R, H11), CHULTI (YR, YI, H1R,
  2H11),2.0D0,0.0D0)))
PH[= CMPLX(PHIR,PH[1)
    RETURN
13 XBR=CMULTR(16.000,0.000,YR,YI)
   X8I=CMULTI(16.0D0,0.0D0,YR,YI)
X8QR=CMULTR(X8R,X8I,X8R,X8I)
X8QI=CMULTI(X8R,X8I,X8R,X8I)
    H=2
    IF((X8QR.EQ.0.0).AND.(X8QI.EQ.0.0))#=1
    GD TD (14,15),H
14 X8QR=.1D-17
    X8QI =0.0D0
15 POR=1.0D0
    P01=0.000
    QOR=POR
    001 = P01
    PIR=POR
    P11=P01
    018 = 3.000
    Q11=0.0D0
    TPOR=POR
    TP01=P01
    TOOR=POR
    TQ01 = P01
    TPIR= POR
    TP11=P01
    TQ1R=Q1R
    TQ11=Q11
    D=1.0D0
    F=1.000
    X8IR=CDVDR(1.0D0,0.0D0,X8R,XBI)
    X8II=CDVDI(1.0D0,0.0D0,X8R,X8I)
X8QIR=CDVDR(1.0D0,0.0D0,X8QR,X8QI)
    X8QII=CDVDI(1.0D0,0.0D0,X8QR,X8QI)
    DD 20 K=1,500
```

The second se

• • •

ومعجمين المراجعين ومادا والمراجع والمتع

And a

A CONTRACTOR OF STREET

----- CS**PNG**----- (

DM2=0-2.000 D2=D+2.000 04=0+4.000 040=04+04 06=0+6.000 DQ=D+D 02Q=02+D2 F1=F+1.000 F2=F+2.000 RP0=-D2Q+DQ/(F+F11 RQ0=-D2Q+04Q/(F1+F21 RP1=-DM2+0+02+D4/(F+F1) RQ1=-0+D2+D4+06/(F1+F21 PORS=([X8QIR+RP0I+TPOR-(X8QII+RP0)+TP0II POIS=((X8QIR+RPO)+TPOI+(X8QII+RPO)+TPOR) QORS=((X8QIR+RQ0I+TQOR-(X8QI1+RQ0I+TQ0II QOIS=((X8QIR+RQ0I+TQ0I+(X8QII+RQ0I+TQ0RI P1R5=((X8QIR+RP1)+TP1R-(X8QI1+RP1)+TP111 P115=((X8Q1R+RP1)+TP11+{X8Q11+RP11+TP1R1 QIRS=((x8QIR+RQI I+TQIR-(x8QII+RQI I+TC11 I Q115=((X8QIR+RQ11+TQ11+(X8Q11+RQ11+TQ1R1 IF(VAL1) GD TO 32 IF((QIRS+QIRS+QIIS).LE.(TQIR+TQIR+TQII+TQII)I GO TO 19 VAL 1=. TRUE. 32 IF(VAL21 GO TO 33 IF((PIRS+PIRS+PIIS+PIIS).LE.(TPIR+TPIR+TPII+TPII)1 GO TO 18 VAL2=. TRUE. 33 1F(VAL3) GD TO 34 IF((QORS+QORS+QOIS+QOISI+LE+(TQOR+TQOR+TQOI+TQOI)) GD TO 17 VAL3=.TRUE. 34 IF (VAL41 G3 T0 35 IF (PORS+POIS+POIS)+LE. (TPOR+TPOI+TPOI+TPOI1) G0 T0 16 VAL4=.TRUE. 35 IF(VAL1.AND.VAL2.ANO.VAL3.ANO.VAL4) GO TO 21 GD TO 693 16 POR=PORS+POR POI=POIS+POI IF(TPOR.EQ.POR.AND.TPOI.EQ.POI) VAL4=.TRUE. TPOR=PORS TPOI=POIS GD TO 35 17 QOR-QORS+QOR Q01=Q01 S+Q01 IF (TQOR. EQ. QOR. AND. TGOI. EQ. QOII VAL3=. TRUE. TOOR=QORS TQ01=Q01 S GO TO 34 18 PIR=PIRS+PIR P11=P11S+P11 IF(TPIR.EQ.PIR.ANO.TPII.EQ.PII) VAL2=.TRUE. TPIR=FIRS TPI1=PIIS GO TD 33 19 QIR=QIRS+QIR Q11=Q11S+Q11

A state of the second se

```
IF(TQ1R.EQ.QIR.AND.TQ11.EQ.Q11) VAL1=.TRUE.
      TOIR=OIRS
      T011=0115
      GO TO 32
693 D=04
 20 F=F2
 21 QORS1=QOR
      Q0151=Q01
      QIRSI=QIR
      Q1151=Q11
    Q1151=Q11

Q0R=-CMULTR(Q0RS1,Q0151,X81R,X811)

Q0I=-CMULTI(Q0RS1,Q0151,X81R,X811)

Q1R=CMULTI(Q1RS1,Q1151,X81R,X811)

Q1I=CMULTI(Q1RS1,Q1151,X81R,X811)

PHIR =CDVDR(CMULTR(JR,JI,(POR+CMULTR(JR,JI,Q0R,Q01)),(POI+CMULTI(J

IR,JI,Q0R,Q01))),(CMULTI(JR,JI,(POR+CMULTR(JR,JI,Q0R,Q01)),(POI+CMULTI(J

2LTI(JR,JI,Q0R,Q01))),CMULTR(2.0D0,0.0D0, CMULTR(YR,YI,(P1R+CMULTR

3(JR,JI,Q1R,Q11)),(P11+CMULTI(JR,JI,Q1R,Q11))),CMULTI(YR,YI,(P1R+CMULTR

3(JR,JI,Q1R,Q11)),(P11+CMULTI(JR,JI,Q1R,Q11))),CMULTI(YR,YI,(P1R+CMULTR)))
     4ULTR(JR, JI, QIR, QII)), (PII+CHULTI(JR, JI, QIR, QII)))), CHULTI(2.000,0
     5.000, CHULTR(YR, YI: (PIR+CHULTR(JR, JI, QIR, Q11)), (P11+CHULTI(JR, JI, Q1
     6R,Q11))),CHULTI(YR,YI,(PIR+CHULTR(JR,JI,QIR,Q11)),(P1I+CHULTI(JR,J
     71,Q1R,Q11)))))
      PHIL =CDVD1(CHULTR, JR, JI, (POR+CHULTR(JR, JI, QOR, QOI)), (POI+CHULTI(J
    71,Q1R,Q11)))))
      PHI= CMPLX(PHIR, PHII)
      RETURN
      END
```

......

ويترجع والمراجع

-#is :

100
MAIN PROGRAM FOR CALCULATING AND PLOTTING SERIES AND PARALLEL RES-ONANCE FREQUENCIES WITH ELECTRON TEMPERATURE AS A PARAMETER.

```
SIBFIC THPICL
        COMMON /INPTS/ T(10),NT,FP(1500),NFP,R,AL,SI(1500),SS(10,1500),
       1 SHEATH, FH, FS(1500)
        DO 6 KKK=1,6
CALL INPUT
        CALL GRID (6HVREADR, SCALEX, SCALEY, XB, XE, YB, YE, NX, NY, X'5)
        PRINT 3, (T(K),K=1,10)
PRINT 4,NT,NFP,NX,NY,(FP(K),K=1,5)
        PRINT 3, SCALEX, SCALEY, XB, XE, YB, YE: X15, R, AL, SHEATH, FH
        00 2 J =1,NT
        CALL SICALC(T(J),R,AL,FP,SI,NFP,SHEATH,FH)
        DO 1 K =1,NFP
FS(K)=SQRT(FH++2+SI(K)++2+(FP(K)++2-FH++2))
      1 SS(J,K) = S((K))
        CALL CURVEL(FP.FS.NFP.X8.XE.Y8.YE.X15)
FFF=(FS(NFP)-Y8) •9.0/(YE-Y8)
         FF=(FP(NFP)-X8)+X15/(XE-X8)
         AJ=J-1
        CALL ARROW (FF, FFF, 0.0 )
        CALL PLOT ((FF+1.0),FFF,2)
CALL PLOT((FF+2.0),AJ,2)
     LALL PLOT((FF+2.0),AJ,2)
CALL PLOT (IFF+3.0),AJ,2)
2 CALL NUMBERI(FF+1.75),AJ,.125,T(J),0.0,0)
3 FORMAT(1H ,11E12.6)
4 FORMAT(1H ,4(10,5E16.8)
CALL OUTPUT
CALL FUNT
        CALL FINI
      6 CONTINUE
        CALL EXIT
         ENO
```

SUBROUTINE FOR READING INPUT DATA FOR MAIN PROGRAM TMPTCI

```
$(8FTC (HPUT

SUBRCUT(NE (NPUT

CCMMCN /INPTS/ T(10), MT, FP(1500), NFP, R, AL, SI(1500), SS(10, 1500),

1 SHEATH, FH, FS(1500)

REAO 1, NT, NFP, R, AL, FPMAX, FPMIN, SHEATH, FH

1 FCRMAT(215, 6E11.5)

REAO 2, (T(J), J =1, 10)

2 FCRMAT( 5E16.8)

AN = NFP -1

DELF =(FPMAX-FPMIN)/AN

OC 3 J = 1, NFP

A J=J-1

3 FP(J)=FPMIN+AJ=0ELF

RETURN

END
```

B-34

· · · · · · · · ·

SUBROUTINE FOR PRINTING DATA OUT OF MAIN PROGRAM TMPTC1

and the second second

```
SLEROUTINE OUTPUT
  CCPPCN /INPTS/ T(I0),NT,FP(I500),NFP,R,AL,SI(1500),SS(10,1500),
1 SHEATH,FH,FS(1500)
   DIPENSION 1(10)
LCGICAL FIRST
   FIRST =.TRUE.
   R = R+1.0E+02
13 KPAGE = 52
CC 3 J = 1,NFP
KPAGE = KPAGE + 1
   IF(KPAGE.GT.50) GO TO 4
 1 PPINT 2 , FP(J),(SS(K,J),K =1,NT)
2 FCRMAT(1H ,FII.3,10F12.3)
   IF(.NOT.FIRST) GO TO 3
   CC 3 K=1,NT
   SS(K, J)=SGRT(FH++2+SS(K, J)++2+(FP(J)++2-FH++2))
 3 CENTINUE
   IF(.NCT.FIRST)RETURN
   FIRST =.FALSE.
GC TO 13
 4 KPAGE=1
   PPINT 5
 5 FERMAT(1H1)
   PRINT 6
 6 FCRMAT(1H ,132H-----
  1------ )
                                                                       --------
   IF(F(RST) PRINT
                         7
 IF(.NOT.FIRST)PRINT12
7 FCRMAT(IH , 90H
1CVLINDRICAL ANTENNA PSI CALCULATIONS
12 FERMATE 1H, 105H
                                                                      CYLINDRICAL AN
  ITENNA CALCULATIONS OF SERIES RESONANCE FREQUENCY
 PRINT 8 ,R, AL,FH
8 FCPMAT(1H ,24X,IOH RADIUS = ,F6.4,17H CM , LENGTH = ,F
128H METERS , GYRO FREQUENCY =,F 5.3 ,11H MEGACYCLES )
                                                             LENGTH = ,F6.4,
   PPINT 6
 PPINT 9
9 FCRPAT( 92H PARALLEL FREQUENCY
1 ELECTRON TEMPERATURE
                                                              )
   CC 1C L=1,10
10 I(L) = T(L)
   PRINT 11,(1(L),L=1,10)
11 FCRMAT(16H (MEGACYCLES) , 16,4H+K , 9(18,4H+K ))
   PRINT 6
   GC TC 1
ENC
```

A CARACTER A REPORT OF THE AT A CARACTER AT

B-35

SUBROUTINE TO CALCULATE SERIES **RESONANCE FREQUENCY**

```
SIBFTC SICALC
         SUBROUTINE SICALC(T,R,AL,FP,SI,NFP,SHEATH,FH )
DIMENSION FP(1500) , SI(1500)
COMMON /CONSTA/ PI,PI2,EMASS,AMASS,O,CK,EO,G,UO,ALPHAK
          REAL K
         CL = ALOG(AL/R)
CALL CONSTS
          UBYCON =SQRT(CK/(4.0+P12+EMASS))+1.0E-06
         S12 =.1
DG 7 J =1+NFP
L = NFP+1-J
          IF(FP(L).LE.FH) GO TO 10
          ALPFT =ALPHAK+(FP(L)++2-FH++2)/T
         DBYLNT = DBYCON*SORT(T)/FP(L)
RS = R + DBYLNT*SHEATH
SHTCON = ALOG(RS/R)
         N = 0
GO TU 3
      1 SI2=AN+.04
2 SI2=.5+SI2
       3 S2 = 1.0 - S12
N = N+1
          AN = N
          IF (N.GT. 100) GO TO 8
          A2 = S2+ALPFT
          IF(A2.LE.1.0E-18) A2 = 1.0E-18
AR = RS+SQRT(A2)
          RKAR = K(0,AR)/K(1,AR)
         KKN = 1.0-RKAR++2

S22 = 2.0+S2

S12P = (S12+RKH+S22+(SHTCON+RKAR/AR))/(RKH+S22+CL)

SLOPE = 1+0 + RKM/(S22+CL)

DEL =(S12P -S12)
          IF(SLOPE)2,2,4
       4 IF(SI2P)2,2,5
5 IF(SI2P-1.0)6,1,1
6 SI2 = SI2P
          IF(ABS(DEL).GT..001)GO TO 3
      7 SI(L) = SQRT(SI2)
RETURN
     B PRINT 9,UEL,SI2,AR,T,FP(J),SLOPE
9 FORMAT(JIH SICALC HAS FAILED TO COVERGE. ,6E16.8)
GU TO 7
10 SI2=0.0
          GU TO 7
```

END

.

SUBFUNCTION PROGRAM FOR CALCULATION OF THE BESSEL FUNCTIONS K, AND K,

5 V.X.V

REAL PUNCTION K(N,X) REAL I K = 0.0 IF(N.LT.O) N -- N IF(N.GE.2) RETURN IF(X.EQ.0.0)60 TO 1 IF(N.EQ.1) 60 TO 3 IF(X.GT.2.0) 60 TO 2 Y = X/2.0Y2 = Y•Y Y4 = Y2•Y2 Y6 = Y4•Y2 Y8 = Y4•Y4 Y10 - Y6+Y4 Y12 - Y6+Y6 K = -ALOC(Y)+I(N,X)-.57721566 +.42278420+Y2 +.23069756+Y4 1+ .03488590+Y6 + .00262698+Y8 +.00010750+Y10 + .30000740+Y12 RETURN 1 K=1.0E+37 RETURN 2 Z = 2.0/X22 = 2•2 23 = 22•2 24 = 23•2 25 = 24+2 26 = 25+2 K = 1.25331414 -.07832358•Z + .02189568•Z2 - .01062446•Z3 1+ .00587872•Z4 -.00251540•Z5 +.00053208•Z6 K = K+EXP(-X)•(X++(-.5)) RETURN 3 [F(X.GT.2.0)GO TO 4 Y = X/2.0 Y = Y/2.0 Y = Y=Y Y = Y2=Y2 Y = Y4=Y2 Y = Y6=Y2 ¥10=¥8•¥2 ¥12=¥10+¥2 K = ALOG(Y) • [(N,X) +(1.0 +.15443144•Y2 -.67278579•Y4-.18156897•Y6 1- .01919402•Y8 - .00110404•Y10 - .0000468•Y12)/X RETURN 4 Z = 2.0/XZ2= Z+Z 23= 22+2 Z4= Z3+Z 25= 24+Z 26= 25+Z $\begin{array}{l} K = 1.25331414 + .23498619 \cdot 2 & - .03655620 \cdot 22 + .01504268 \cdot 23 \\ 1 & - .00780353 \cdot 24 + .00325614 \cdot 25 & - .00066245 \cdot 26 \\ K = K \cdot E \cdot 2P (-X) \cdot (X \cdot \cdot \cdot (-.5)) \end{array}$ RETURN END

. . .

SUBFUNCTION PROGRAM FOR THE CALCULATION OF THE BESSEL FUNCTIONS ${\rm I}_{\rm D}$ AND ${\rm I}_{\rm I}$

Ţ

-

.

```
REAL FUNCTION I(N,X)
   DCUBLE PRECISION Y, FACN, FACH, FJ, SUN, YERN, FK, FKN
   Y=X/2.0
   I =C.O
   IF(N.LT.0) N = -N
   FACN =1.0
FACM =1.0
   IFIN.EQ.0) GD TO 4
DC I J = 1,N
FJ =J
1 FACN = FACN•FJ
SUM ={Y••N}/FACN
SUM = (TWON)/FACN

TERM = SUM

2 DO 3 K = 1 , SGO

FK = K

FKN = K + N

TERM = TERM=Y=Y/(FKN=FK)
   SUM = SUM + TERM
   SS=SUM
   IFII.EQ.SS ) RETURN
3 I = SS
RETURN
4 SUM = 1.0
TERM = 1.0
   GO TO 2
   END
```

SUBROUTINE FOR DRAWING A CURVE FROM AN ARRAY OF DATA

```
$I8FTC CURVEL
SUBROUTINE CURVEL(AX,AY,N,X8,XE,YB,YE,X15)
DIMENSION AX(10),AY(I0)
LOGICAL FIRST
FIRST = .TRUE.
DX = XE-X8
DY *YE-YB
SCX=X15/DX
SCY=9.0/DY
DO 1 J = 1.0
X = (AX(J)- XB)*SCX
Y = (AY(J)- YB)*SCY
IF(X.GT.X15) GO TO 3
IF(Y.GT.9.0) GO TO 3
IF(Y.GT.9.0) GO TO 3
IF(Y.GT.9.0) GO TO 3
IF(FIRST)CALL PLOT(X,Y,3)
CALL PLOT(X,Y,2)
FIRST = .FALSE.
GO TO 1
3 FIRST = .TRUE.
1 CONTINUE
RETURN
END
```

A STATE OF A

SUBROUTINE TO PRODUCE A LABELED GRID FOR PLOTTED DATA

```
SUBROUT (NE GRID(TITLE, SCX, SCY, XXB, XXE, YYB, YYE, NXX, NYY, XX15)
C ALTERNATE ARGUMENTS GRID(6H READ } , GRID(6HVREADR) , GRID(6HCOMMON)
        D(PENSION TITLE(52)
COPMON/PLTCMN/HEAD(65),SCALEX,SCALEY,X8,XE,Y8,YE,NX,NY,X15
         CALL HOL(CHN, 6HCOMMON)
        IF(TITLE(1) .EQ.CMN) GO TO 106
CALL HOL(READIN,6H READ )
         CALL HOL (READER, 6HVREADR)
         IF((TITLE(1).NE.READER).AND.(TITLE(1).NE.READIN)) GO TO 104
         READ 101+(HEAD(J)+J =1+52)
   101 FCRMAT(1346)
  READ 102, SCALEX, SCALEY, X8, XE, Y8, YE, NX, NY, X15
102 FCRMAT( 6F10.5, 215, 1F10.5)
PRINT 1000
 1CCO FCRMAT(1H1)
        PRINT 1C2,SCALEX , SCALEY,XB,XE,YB,YE,NX,NY,X15
PRINT 1C00
         IF(TITLE(1).EQ.READIN) GO TO 103
        SCX = SCALEX
SCY = SCALEY
XXB = XB
XXE = XE
         YY8 = Y8
         YYE = YE
        NXX = NX
        NYY= NY
  XX15 = X15
103 CALL IDPLOT
  GC TO 106
104 CALL IDPLOT
   CC 105 J = 1,52
105 HEAD(J) = TITLE(J)
        SCALEX =SCX
SCALEY =SCY
        XE = XXB
        XE = XXE
        YB = YYB
YE = YYE
NX = NXX
        NY = NYY
        X15= XX15
   106 CENTINUE
        (F(SCALEX.LT.0.0) SCALEX = SCALEX

IF(SCALEX.GT.100.0) RETURN

IF(SCALEY.LT.0.0) SCALEY = -SCALEY

IF(SCALEY.GT.100.0) RETURN
         IF(X15.LT.0.0) X15 = -X15
         IF(X15.G7.100.0) RETURN
        X = 0.0
         ¥ = 0.0
        AN = N
    AN = N
CALL PLDT( 4.0,1.45,-3)
12 CALL PLDT(0.0,9.0, 2)
CALL PLDT(X15,9.0, 2)
CALL PLOT(X15,0.0, 2)
CALL PLOT(0.0, 0.0, 2)
CX=(XE -XB)/SCALEX
```

يستريب المرجبين وبرادان المحموقين والمحموم

NUMBER OF STREET, SALES

	DYAL YE - YEL/SCALEY
	NIT
	AX = AL2/JUALEX
	AX10 = AX/10.0
	AY = 9.0/SCALEY
	AY10 447/10.0
1	V-VAAVLO
	1F(Y.62. 9.0) GO 10 Z
	CALL PLOT(0.0, Y, 2)
	CALL PLOT(0.1.Y.2)
	CALL BLOTIO A.V.3)
	60 TO 1
2	Y = 9.0
	CALL PLOT(0.0.9.0.2)
1	Y - YAAYIO
	1P1X-0E-X12 J 60 10 4
	CALL PLOT(X ,9.0,2)
	CALL PLOT(X .8.9.2)
	CALL PLOT (X . 0.0.3)
	6U 1U 3
- 4	CALL PLOT(X15 ,9.0,2)
5	Y =Y -AY10
-	16(Y.16.0.0) 60 TO A
	CALL PLUIIXIS, THE I
	CALL PLOT(X151.Y.Z)
	CALL PLOT(X15 .Y.3)
	CO TO 5
•	X =X17
	CALL PLOT(X15 ,0.0,2)
7	$\mathbf{X} = \mathbf{X} - \mathbf{A}\mathbf{X}10$
•	TE(Y.15.0.0) CO TO 8
	CALL PLUE (X,U.U,Z)
	CALL PLOT (X,0.1,2)
	CALL PLOT (X.0.0.33
	GO TO 7
•	X = 0.0
	Y = 0.0
	xs = (x15-13.6)/2.0
	CALL PLOT(0.0. 0.0. 2)
	NNY - O
	RRT = U
	IF(XE)200,200,201
199	IF(YE)210,210,211
200	XA = ARS(XR)
	6C 10 199
201	X A=XE
	GO TO 199
210	VA # ARS(VR)
	GC IU ZIZ
211	YA = YE
212	CONTINUE
	IF(XA.1 T. 1000.) NNX
	10/WA 17 1000 1 MMA - MA - 3
	IFITA-LI- LUUU-J NAT = AT - 3
	IF(XA.LT. 100.] NHX = NX - 2
	IF(YA.LT. 100.) NNY = NY - 2
	16(XA.LT. 10.) MNY = NY = 1
	TRIVALT IN LAW _ WY _ 1
	IFITA-LIA LUAJ MAY = AY - 1
	$IF(XA_{\bullet}LT_{\bullet} = 1c) RWX = NX$
	IF(YA.LT. 1.) NWY = NY

the sound it

1

I

N.C.N.

```
IF (NNX.LT.O) NNX = 0
       IF(NNY.LT.O) NNY = 0
      XSN = NX
YSN = NY
       SPACEX = .07+XSN
SPACEY = .07+YSN
       IF(XE.LT.O.G) SPACEX = SPACEX + .07
IF(YE .LT.O.G)SPACEY = SPACEY + .07
       XN = XB
       YN = YB
       CALL NUMBER(X-SPACEX,-.25,.15,XN,0.0,NNX)
CALL NUMBER(-.10,Y-SPACEY,.15,YN,90.0,NNY)
  9 Y = Y +AY
      YN = YN+DY

1F(Y.GT.9.0) GO TO 10

CALL NUMBER(-.10,Y-SPACEY,.15,YN,90.0,NNY)

CALL PLOT(0.0,Y,3)

CALL PLOT(X15,Y,2)
       Y = Y + AY
YN = YN + DY
IF{Y.GT.9.0} GO TO 10
       CALL PLOT(X15,Y,3)
       CALL PLOT (0.0, Y.2)
       CALL MUMBER (-. 10, Y-SPACEY, . 15, YN, 90.0, NNY )
CALL PUNDER(-.10, Y-SPALEY, 15, YN, 90.0, NHY
GC TO 9
10 X = X + AX
XN = XN+DX
1F(X.GT.X15 ) CO TO 11
CALL NUMBER(X-SPACEX,-.25,.15, XN, 0.0, NNX)
CALL PLOT(X, 0.0,3)
CALL PLOT(X, 9.0,2)
       \begin{array}{l} \mathbf{X} = \mathbf{X} + \mathbf{A}\mathbf{X} \\ \mathbf{X}\mathbf{N} = \mathbf{X}\mathbf{N} + \mathbf{D}\mathbf{X} \end{array}
       IF(X.GT.X15 ) GO TO 11
CALL PLGT(X,9.0,3)
       CALL PLOT (X, 0.0,2)
       CALL NUPBER(X-SPACEX,-.25,.15, XN, 0.0, NNX)
       GC TO 10
11 CALL SYMBL4(1.65+XS,-.55,.15,HEAD(1),0.0,78)
CALL SYM5L4(XS, -1.00,.20,HEAD(27),0.0,78)
CALL SYM5L4(1.65+XS,-1.30,.15,HEAD(40),0.0,78)
CALL SYMBL4(-.35,-.55,.15,HEAD(14),90.0,78)
       RETURA
       ENC
```

and the second second

en. 16

1.1000

MAIN PROGRAM FOR CALCULATION OF TEMPERATURE FROM SERIES AND PARALLEL RESONANCE FREQUENCIES

\$IBFTC TEP601

2

.

ر . معر .

.

```
DIMENSION FHT(14)

15 FURMAT(12X,2F8.2,F10.2,2F9.0,10X,I6)

COMMON /KEN/ R, AL, PERCNT, LIMIT, CC, S, TSTART,F,FP,T,KK,N

1 FORMAT (3FI0.2, 15, E15.7, 2F10.2)

READ 1, R,AL,PERCNT,LIMIT,CC,S,TSTART

PRINT1, R,AL,PERCNT,LIMIT,CC,S,TSTART

K=3

READ 2, FMT

PKINT2, FMT

2 FORMAT(13A6, A2)

CALL CRDIDS

PRINT 3

3 FORMAT (1H1, 8X, 4HTIME, 2X, 6MSERIES, 5X, 3HPAR, 5X, 3HSEC, 2X,

1 8HNEW TEMP, 2X, 8HOLD TEMP, 5X, 3HALT)

8 READ FMT, F, FP, SEC, OT

CALL TEMPSP

PH INT 15, F,FP,SEC,T,OT,K

PUNCH 15, F,FP,SEC,T,OT,K

K= K+1

GO TU 8

CALL CRDIDF

CALL EXIT

END
```

SUBROUTINE FOR CALCULATION OF THE ETA FUNCTION

```
SIBFTC ETAA
          SUBROUTINE ETAAL Y , ETA, KL)
          REAL K
          N=0
          AJ =0.0
          AL =0.0
KL= 0
          IF (Y.GT.0.0)GO TO 1
ETA =1.0E+37
          RETURN
       1 X=1.0
          DX = .5
DYH = Y +.00001
DYL = Y -.00001
       2 IF(X.LE.0.0)X =1.0E-37
          KL= KL+1
          IF(X .GT. I.0E+30) GD TO 5
IF (N.GT.500) GD TO 5
PHI = K(0,X)/(X+K(1,X))
          IF(PHI.GE.DYH) GO TO 3
IF(PHI.LE.DYL) GO TO 4
          ETA = X
          RETURN
      3 AL = AL +1.0
AJ = 0.0
DX = DX •AL/2.0
X = X+DX
      GG TO 2
4 AJ = AJ +1.0
AL = 0.0
fX - 7X+AJ/2.0
          \begin{array}{l} X = \lambda - DX \\ GO TO 2 \end{array}
      5 PRINT 6 , X ,Y ,DX ,PHI
6 FORMAT(16H ETA HAS FAILED ,4E20.8)
          ETA = X
          RETURN
          END
```

1

2.4

SUBROUTINE FOR CALCULATING ELECTRON TEMPEATURE FROM SERIES AND PARALLEL RESONANCE FREQUENCIES

1

125

-

SUBROUT INE TEMPSP SUBRUITINE TEMPSP COMMON /KEN/ R. AL, PERCNT, LINIT, CC, S, TSTART, F, FP, T, KK, M DATA PI/3.14159265/, EM/9.1003E-31/, EK/1.30044E-23/, G/3.0/, 1 A/0.0/, FH/1.4/, E00/8.05434E-12/ PI2= PI4PI TCON={EN/(G•EK})•4.0E+12•PI•PI DEYCCN=(EK/(4.0* PI2•EN}) DEYCON = SQRT(DBYCON)•1.0E-06 CKCN= 0.0 IF(CC .GE. 1.0) GO TO 22 CKDN=(2.0=PI+AL/CC)=E00 22 FH2= FH+FH N=0 KK=0 FP2 = FP+FP F2 = F+F FN2= FP2-FH2 FC2 = FP2-F2IF (FN2 .LE. 0.0) GO TO 28 IF(F .LT. FH) GO TO 28 FN= SQRT(FN2) SI2= (F2-FH2)/FN2 S2= 1.0-S12 T= TSTART 32 TEST = T DLENGT= DBYCON+SQRT(T)/FN RS# R+DLENGT+S PHI= SI2+ALOG(AL/RS) - S2+(ALOG(RS/R) + CKON) IF (PHI .LE. 0.0) GO TO 28 CALL ETAA(PHI, ETAS, KL) KK=KK+KL TCON+RS+RS+FC2 /(ETAS+ETAS) T= N=N+1 N=N+1 IF (N .GT. LIMIT) GO TO 36 IF (S .EQ. 0.0) RETURN IF ((ABS(T-TEST)/T) .GT. PERCNT) GO TO 32 28 Y= 0.0 RETURN 36 PRINT 37, F, FP, T, N, KK 37 FCRMAT (1H1, 21HTOO MANY ITERATIONS (, 2F5-2, F10-0, 217, 1H)) RETURN END

and a second sec

. .

MAIN PROGRAM FOR PLOTTING ANTENNA REDISTANCE VERSUS REACTANCE

SIBFIC IMPPLT MAIN PROGRAM FOR PLOTTING ANT Z VS R AND X PROGRAM FOR PLOTTING ANTENNA IMPEDANCE AS A FUNCTION OF R AND X С DINENSION HEAD(50), TEN (11) COMPLEX Z,ZO LOGICAL FIRST COMMON/IMPCDM/Z,F,FP,FNU,FH,ANGLE,T,R,AL COMMON_/COMSTA/PI,PI2,EMASS,AMASS,Q,CK,E0,G, U0,ALPHAK CALL CONSTS ALPH=ALPHAK READ 1 ,NPLOTS, NRESLY, NTAPE, NSKIP, NPRINT, NPLT, NTHY PRINTI ,NPLDTS, NRESLV, NTAPE, NSKIP, NPRINT, MPLT, NTHY 1 FORMAT(7110) DO 32 JNP = 1, NPLOTS READ 10 ,NDO,KGRID,FMAX,FX PRINT 3 ,NDD,KGRID,FMAX,FX 3 FORMAT(1H1,2110,2F10.3) 10 FORNAT(2110,2F10.3) FX=FX+.1E+07 FMAX=FNAX+.1E+07 READ 14,FH;FNU,T;R;AL;ANGLE PRINT 2;FH;FNU,T;R;AL;ANGLE 2 FORMAT(1H1;6E13-6) 14 FORMAT(6E13.6) 20 FDRMAT(2E20.8, F10.3) 21 FORNAT(1H1,2E20.8) READ 20,FNUCON , DEN,ALT PRINT 21 , FNUCON , DEN CALL GRID(GHVREADR,SX,SY,X8,XE,Y8,YE,HX,NY,X13) SCX = X15/(XE-XB) SCY = 9.0/(YE-YB) PLOT FOR 10 C 10 CONSTANT TEMPERATURES С DATA TEM/250., 350., 500., 700., 1000., 1400., 2000., 2800., 4000., 5600. 1 , 4000. F = FX FP = 0.0T = 0.0 CALL ANTZ 20 = Z RES #NRESLY REF =FHAX/RES PRINT 1000 1000 FORMAT(1H1) PRINT70, SCX , SCY :F, FP, T, Z, RES, REF 70 FDRMAT(9E14.6) PRINT 1000 0030JT =1,11 10 TENPERATURE RESIS 89 FURHATI127H T(127H PLOT X PLDT Y DP FREQ PLA FRE ENPERATURE RESISTANCE REACTANCE FUN //19H TEMPERATURE EQUALS,F20.1,8H DEGREES,,12HALT. EQUALS, 3 F10.2, 3H KM///) PRINT 88 88 FORMAT (1H1) PRINT 89.T.ALT IF(NTHY.EQ.1) FNU = FNUCDN+DEN+T IF(FNU.GT.2,+PI+FX) ALPHAK=ALPH+5.0/9.0

.

· .

.

والمتعاد والمتعا فتعاد

. . .

1.

21

The state of the

```
PX0- = 0.0
          PY0 = 0.0
          FIRST =. TRUE.
           JL = 0
         DO 28 JF=1,NRESLV
FJ = JF-1
FP = FJ+REF
          \begin{array}{l} \text{CALL ANTZ} \\ \text{Z} = \text{Z} - \text{ZO} \\ \text{PXO} = \text{PX} \end{array}
           PYO = PY
          PY =(REAL(Z)-YB)+SCY
PX =(A(MAG(Z)-XB)+SCX
           IF(NPRINT.EQ.O.AND.JF/5+5.EQ.JF) PRINT 70,PX,PY,F,FP,T,Z,FNU,REF
          IF(PX.GT.X15) PX = X15
IF(PX.LT.0.0) PX = 0.0
IF(PY.LT.0.0) PY=0.0
IF(P).GT.9.0)PY=9.0
           IF(FIRST)CALL PLOT(PX,PY,3)
           FIRST =.FALSE.
           CALL PLOT(PX, PY,2)
           JL = JL +1
IF(JL.LE. MPLT) GO TO 28

JL = 0

OXX = PX-PX0

OYY = PY-PY0

100 IF(OXX) 103,101,103

101 IF(DYY) 102,28,102

102 OXX = .1E-06

103 S = OYY/OXX

S2 = S*S

OY =.05*SQRT(S2/(S2+1.0))

OX =.05*SQRT(1.0/(S2 +1.0))

IF(S) 104,105,105

104 DX = -DX

105 CALL PLOT(PX-DY,PY+DX,3)

CALL PLOT(PX-DY,PY+DX,2)

CALL PLOT(PX, PY, 3)

28 CONTINUE
           IF(JL.LE. MPLT) GO TO 28
    28 CONTINUE
    29 T =TEM(JT)
IF(ALPHAK .NE.ALPH) ALPHAK=ALPH
   30 CONTINUE
32 CALL PLOT(X15+4.0.-1.45,-3)
CALL FINI
STOP
           END
```

4

100

-

• a = 1

......

DOCUMENT CON	TROL DATA - RAD	the example equation of the state of			
(Security classification of the, body of abarract and indexin ORIGINATING ACTIVITY (Corporate author)	20. REP	DAT SECURITY CLASSIFICATION			
Upper Air Research Laboratory	Unc	lassified			
University of Utah	25 GROI	25 GROUP			
Salt Lake City, Utah					
REPORT TITLE					
Antenna Impedance in the Ionosphere	2				
DESCRIPTIVE NOTES (Type of report and inclusive dates)					
Scientific Report No. 3					
AUTHOR(S) (Lest name, liret name, initial)					
Despain, Alvin M.		•			
REPORT DATE	78. TOTAL NO. OF PAGES	75. NO. OF REFS			
13 May 1966	145 pages	43 references			
AF 19(628)-4995*	Se. ORIGINATOR'S REPORT NU	INDER(3)			
7663 766303	UU 66-7				
⁶²⁴⁰⁵³⁹⁴ , 76008015	S. OTHER REPORT NO(S) (AI	y other number; that may be sealgre			
681000 6892066395	AECDI 66/12				
AVAILABILITY/LIMITATION HOTICES	AFCRE 00-412				
*Sponsored in part, by DASA, Wash. D.C. under Web No. 07.007, Project	Hq. AFCRL, OAR (CRU) United States Air Force				
5710.	L.G. Hanscom Field	l, Bedford, Mass.			
The impedance of an antenna p is examined. A review of several techniques, some past experimental presented. A need is shown for fu The theory develops the impedance antenna probe immersed in a warm,	robe surrounded by id physical plasma parage results, and various rther theoretical so of an electrically so lossy, compressible,	onospheric plasma meters, research s theories is phistication. mort, cylindrical magneto-ionic, to previous work			

DD 1 DAN 04 1473

Unclassified Security Classification The state of the second se

Unclassified Security Classification

14.	. KEY WORDS	LINK A		LINK D		LINK C		
			ROLE	WT	ROLE	WT	ROLE	W T
ł								
	Ionospheric research							
	Antenna impedance probe							
	Ionospheric electron density				, , 		-	
	Ionospheric electron temperature							
	RF probe measurements							
	Parameters of the ionosphere							
INSTRUCTIONS								*
1	. ORIGINATING ACTIVITY: Enter the name and address of the contractor, subcontractor, grantee, Department of De-	imposed by security classification, using standard statements auch as:						
fense the ze	e activity or other organization (corporata author) issuing report.	 "Qualified requesters may cotsin copies of this report from DDC." 						

2a. REPORT SECURITY CLASSIFICATION: Enter the overail security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. GROUP: Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as suthorized.

3. REPORT TITLE: Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. DESCRIPTIVE NOTES: If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. AUTHOR(S): Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. if military, show rank and branch of aervice. The name of the principal author is an absolute minimum requirement.

6. REPORT DATE: Enter the date of the report as day, month, year; or month, year. If more than one date appears on the report, use date of publication.

7a. TOTAL NUMBER OF PAGES: The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. NUMBER OF REFERENCES: Enter the total number of references cited in the report.

8a. CONTRACT OR GRANT NUMBER: If appropriate, enter, the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. PROJECT NUMBER: Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. ORIGINATOR'S REPORT NUMBER(S): Enter the official report number by which the document will be identified and controlied by the originating activity. This number must be unique to this report.

9b. OTHER REPORT NUMBER(S): If the report has been assigned any other report numbers (either by the originator or by the sponsor), also enter this number(a).

10. AVAILABILITY/LIMITATION NOTICES: Enter any limitations on further dissemination of the report, other than those

- -----

GPO 886-551

- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through
- (4) ⁽¹⁾U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. SUPPLEMENTARY NOTES: Use for additional explanatory notes.

12. SPONSORING MILITARY ACTIVITY: Enter the name of the departmental project office or laboratory sponsoring (paying for) the research and development. Include address.

i3. ABSTRACT: Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abatract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. KEY WORDS: Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.

Unclassified

Security Classification

4.3