

AD84137

NOLTR 63-36

DRAG AND STABILITY DATA OBTAINED  
FROM FREE-FLIGHT HYPERSONIC FIRINGS  
OF BOTH SHARP AND BLUNT NOSED  
12-DEGREE 40-MINUTE TOTAL-ANGLE  
CONES AT SEVERAL RANGE PRESSURES

CLEARINGHOUSE FOR FEDERAL SCIENTIFIC AND TECHNICAL INFORMATION			
Hardcopy	Microfiche	22	bl
\$1.00	\$0.50	PP	
ARCHIVE COPY			

11 July 1966

*code 1*

# NOL

UNITED STATES NAVAL ORDNANCE LABORATORY, WHITE OAK, MARYLAND

NOLTR 63-36

DDC

NOV 3 1966

RECEIVED

C

NOLTR 63-36

Ballistics Research Report 94

DRAG AND STABILITY DATA OBTAINED FROM FREE-FLIGHT  
HYPERSONIC FIRINGS OF BOTH SHARP AND BLUNT NOSED 12-DEGREE  
40-MINUTE TOTAL-ANGLE CONES AT SEVERAL RANGE PRESSURES

Prepared by:  
Leonard E. Crogan

ABSTRACT: Drag and stability data obtained from hypersonic firings of both pointed and blunt nosed 12-degree 40-minute total-angle cones at several range pressures are tabulated. The drag coefficient of both cones decreased with an increase in the Reynolds number. No effect of Reynolds number on the center of pressure of either cone configuration was observed.

U. S. NAVAL ORDNANCE LABORATORY  
WHITE OAK, MARYLAND

NOLTR 63-36

11 July 1966

DRAG AND STABILITY DATA OBTAINED FROM FREE-FLIGHT HYPERSONIC  
FIRINGS OF BOTH SHARP AND BLUNT NOSED 12-DEGREE 40-MINUTE  
TOTAL-ANGLE CONES AT SEVERAL RANGE PRESSURES

This report presents the results of firings made with 12-degree 40-minute total-angle cones to determine their free-flight characteristics at hypersonic velocities and at several range pressures. The firings were conducted in the Pressurized Ballistics Range at the Naval Ordnance Laboratory.

J. A. DARE  
Captain, USN  
Commander

*A. E. Seigel*  
A. E. SEIGEL  
By direction

NOLTR 63-36

CONTENTS

	Page
LIST OF SYMBOLS . . . . .	iv
INTRODUCTION . . . . .	1
MODEL DETAILS . . . . .	1
DISCUSSION AND RESULTS . . . . .	4

ILLUSTRATIONS

Figure	Title	
1	Cone Configurations . . . . .	1
2	Printed Cone With its Sabot, both Assembled and Exploded . . . . .	3
3	Zero-Yaw Drag Coefficient as a Function of Reynolds Number . . . . .	6
4	Slope of the Pitching-Moment Coefficient Corrected to Zero Yaw as a Function of Reynolds Number . . . . .	7
5	Slope of the Normal-Force Coefficient Corrected to Zero Yaw as a Function of Reynolds Number . . . . .	8
6	Zero-Yaw Center of Pressure Location as a Function of Reynolds Number . . . . .	8
7(a) - (1)	Shadowgraph Prints of Cones in Flight . . . . .	9

TABLES

Table	Title	
I	Physical Dimensions of Aeronutronics Cones . . . . .	2
II	Drag and Stability Data for 12° 40' Total-Angle Blunt Cones . . . . .	4
III	Drag and Stability Data for 12° 40' Total-Angle Pointed Cones . . . . .	5

REFERENCE

(1) Murphy, C. H., "Data Reduction for the Free-Flight Spark Ranges," BRL Report No. 900 (1954)

NOLTR 63-36

LIST OF SYMBOLS

$C_D = \frac{D_t}{qS}$	total-drag coefficient based on the maximum body cross-sectional area (S) of the model
$C_{M\dot{\alpha}}$	(slope of the pitching moment)/ $qSD$ = slope of the pitching-moment coefficient referred to the CG of the model
$C_{M\dot{q}} + C_{M\dot{\alpha}}$	$\frac{(\text{slope of yaw-damping moment due to } \dot{q})}{\frac{D}{2V} qSD} + \frac{(\text{slope of yaw-damping moment due to } \dot{\alpha})}{\frac{D}{2V} qSD} =$ slope of damping-moment coefficient referred to the CG of the model
$C_{n\dot{\alpha}}$	(slope of normal force)/ $qS$ = slope of normal-force coefficient
Cal.	Caliber = one maximum diameter of model
CG	center of gravity
CP	center of pressure
D	maximum diameter of model
$D_t$	component of the aerodynamic force directed along the trajectory
$I_B$	transverse moment of inertia about CG of model
$k_D, k_M, k_N$	parameters used to correct to zero yaw the drag, pitching-moment, and normal-force coefficients, respectively
l	length of model
M	free-stream Mach number (usually based on midrange value of V)
P	free-stream range pressure
P.E.	probable error based on accuracy of data fitting (P. E.s, swerve equation; P. E. y, yaw equation)

NOLTR 63-36

$q = \frac{\rho V^2}{2}$	dynamic pressure; or $q$ = lateral component of angular velocity of model
$Re_1 = \frac{\rho V_1 l}{\mu}$	Reynolds number based on length of model
$S = \frac{\pi D^2}{4}$	maximum cross-sectional area of model
$V$	velocity (usually a midrange value)
$\alpha$	angle of attack
$\dot{\alpha}$	rate of change of angle of attack with time
$\overline{\delta^2}$	mean-squared yaw
$\mu$	coefficient of viscosity
$\rho$	density of air

Subscripts

$o$	quantity corrected to zero yaw
$B$	quantity measured from base of model; or $B$ designates transverse moment of inertia

**BLANK PAGE**

INTRODUCTION

Cone firings were conducted in the Pressurized Ballistics Range at the Naval Ordnance Laboratory to determine drag and stability characteristics at several Reynolds numbers and at a hypersonic velocity.

MODEL DETAILS

With the exception of one round, the cones were all one size as illustrated in figure 1. This one cone was round number 4339 and was twice the size of the other cones. Drag only was obtained from this round because of the insufficient number of stations for a stability reduction. The drag coefficient agreed favorably with those obtained with the smaller models. The physical dimensions of the cones are listed in Table I.




FIG. 1 CONE CONFIGURATIONS

NOLTR 63-36

TABLE I

PHYSICAL DIMENSIONS OF AERONUTRONICS CONES

Round No.	Base Dia. (in.)	Length (in.)	CGB (in.)	Weight (gms.)	IB (gm.-in. <sup>2</sup> )
Pointed Cones					
4296	.222	.987	.387	1.4375	.068
4299	.223	.996	.390	1.4296	.068
4302	.223	.993	.390	1.4277	.067
4307	.223	.999	.386	1.4074	.067
4309	.222	.994	.395	1.4395	.068
4322	.223	1.004	.394	1.4500	.071
4323	.222	.998	.394	1.4126	.068
4335	.222	.989	.394	1.4422	.069
4336	.223	.994	.393	1.4080	.068
4337	.223	1.000	.395	1.4471	.070
4338	.222	.985	.389	1.4381	.067
4339	.452	2.000	.720	4.9660	1.029
4340	.223	.992	.390	1.4208	.067
4399	.224	.999	.400	1.4025	.070
4400	.223	1.002	.401	1.3626	.070
4401	.223	1.001	.400	1.4086	.071
4402	.224	1.001	.402	1.4040	.072
4404	.223	1.000	.400	1.4255	.073
4732	.221	.973	.406	1.5109	.052
Blunt Cones					
4388	.225	.731	.369	1.3485	.056
4389	.224	.730	.370	1.3512	.056
4390	.224	.730	.370	1.3251	.055
4392	.224	.732	.374	1.3523	.056
4395	.224	.731	.370	1.3373	.055
4396	.225	.731	.370	1.3284	.055
4397	.224	.731	.370	1.3321	.055
4723	.222	.731	.373	1.1854	.050
4727	.222	.731	.370	1.1954	.050
4742	.222	.725	.351	1.4734	.063

Except for the rounds fired at atmospheric conditions, all cones had tungsten alloy noses which were silver soldered to hollow titanium alloy afterbodies. The cones launched at atmospheric conditions were manufactured with pure tungsten noses in order to alleviate the ablation problem which exists at atmospheric conditions and accompanying high Mach numbers. Figure 2 shows the pointed cone with its sabot used to launch it from a 1.25-inch single-stage light-gas gun.




FIG. 2 POINTED CONE WITH ITS SABOT, BOTH ASSEMBLED AND EXPLODED

NOLTR 53-36

DISCUSSION AND RESULTS

The drag and stability coefficients were obtained using standard data reduction techniques as described in reference (1). Table II lists the drag and stability data obtained for the blunt cones, and Table III lists the data obtained for the pointed cones.

TABLE II  
DRAG AND STABILITY DATA FOR 12° 40' TOTAL ANGLE BLUNT CONES

Round No.	4742	4723	4727	4388	4389	4390	4397	4396	4392	4395
$r$ (mm dia)	761.4	760.1	758.2	99.2	91.0	75.5	72.9	47.8	47.5	46.3
$M$	8.244	7.712	7.390	9.308	9.186	9.181	9.428	9.433	9.422	9.642
$R_{e1} \times 10^{-6}$	3.354	3.181	3.013	0.500	0.453	0.374	0.372	0.244	0.242	0.24
$\frac{R_{e1}}{\sigma^2}$ (deg. <sup>2</sup> )	34	40	48	33	25	120	49	38	30	45
$C_D$	0.1479	0.1594	0.1573	0.1661	0.1590	0.2421	0.1573	0.2266	0.1674	0.147
$\pm P. E.$	0.0001	0.0002	0.0002	0.0005	0.0005	0.0004	0.0007	0.0009	0.0006	0.001
$C_{D0}$	0.1246	0.1316	0.1247	0.1407	0.1395	0.1407	0.1448	0.1477	0.1442	0.145
P. E. yaw ( $\pm$ deg.)			2			0.5		0.3	0.2	
P. E. surge ( $\pm$ in.)			0.02			0.01		0.007	0.006	
$C_{M0}$ deg.	-0.0080	-0.0119	-0.0122	-0.0101	-0.008	-0.0135	-0.009	-0.0124	-0.00910	
$\pm P. E.$	0.0004	0.0002	0.0001	0.0002	-	0.0002	-	0.0004	0.0004	
$C_{M0}/deg.$	-0.0065	-0.0101	-0.0100	-0.0086	-0.007	-0.0076	-0.008	-0.00811	-0.00773	
$C_{M0}/deg$			-0.052			-0.036		-0.031	-0.022	
$\pm P. E.$			0.005			0.004		0.001	0.001	
$C_{M00}/deg$			-0.025			-0.019		-0.022	-0.016	
(CP-CG) cal.			0.396			0.377		0.388	0.454	
CG <sub>B</sub> (cal.)			1.667			1.652		1.644	1.670	
CP <sub>B</sub> (cal.)			1.271			1.275		1.246	1.256	
(CP-CG) <sub>0</sub> cal.			0.400			0.400		0.406	0.483	
CP <sub>B0</sub> (cal.)			1.267			1.252		1.238	1.287	
$C_{M0} - C_{M00}$			0					-6		
$\pm P. E.$			2					2		

NOLTR 63-36

TABLE III

DRAG AND STABILITY DATA FOR 12° 40' TOTAL ANGLE POINTED CONES

Round No.	4732	4337	4296	4307	4339	4302	4326	4322	4296	4338
$\bar{r}$ (mm Hg)	755.8	100.2	99.9	98.5	97.8	85.8	82.9	79.7	77.1	76.4
$M$	9.198	9.133	9.001	8.206	9.260	9.037	9.076	9.203	9.167	9.126
$R_{01} \times 10^{-6}$	4.984	0.626	0.667	0.675	1.401	0.579	0.557	0.549	0.527	0.515
$\bar{S}^2$ (deg. <sup>2</sup> )	2.1	3.4	85	17	20	20	55	174	10	59
$C_D$	0.05823	0.061	0.126	0.0910	0.067	0.0950	0.124	0.267	0.096	0.125
$\pm P. E.$	0.00009	0.004	0.001	0.0009	0.003	0.0005	0.008	0.007	0.002	0.001
$C_{D0}$	-	0.079	0.079	0.0815	0.076	0.0817	0.067	-	0.089	0.085
$P. E. \text{ yaw } (\pm \text{ deg.})$	0.3			0.3		0.5				0.4
$P. E. \text{ swerve } (\pm \text{ in.})$	0.02			0.02						0.02
$C_{M1}/\text{deg.}$	-0.0095	-0.010	-0.011	-0.00913		-0.0123	-0.008	-0.011		-0.00965
$\pm P. E.$	0.0001			0.00008		0.0002	0.002			0.00008
$C_{M0}/\text{deg.}$	-0.0095	-0.010	-0.010	-0.00894		-0.0122	-0.007	-0.009		-0.00927
$C_{M0}/\text{deg.}$	-0.02			-0.036						-0.036
$\pm P. E.$	0.01			0.004						0.003
$C_{M00}/\text{deg.}$	-0.03			-0.035						-0.034
(CP-CG) cal.	0.300			0.256						0.272
$CG_B$ (cal.)	1.837			1.731						1.752
$CP_B$ (cal.)	1.537			1.475						1.480
(CP-CG) <sub>0</sub> cal.	0.317			0.256						0.273
$CP_{B0}$ (cal.)	1.520			1.475						1.479
$C_{M1} + C_{M2}$	-3			-16						-13
$\pm P. E.$	3			5						5

Round No.	4399	4323	4309	4401	4400	4335	4402	4404	4340
$\bar{r}$ (mm Hg)	66.0	65.6	63.2	62.4	56.2	50.7	37.7	35.9	32.5
$M$	8.971	8.662	9.336	9.038	9.131	9.135	9.198	9.104	8.968
$R_{01} \times 10^{-6}$	0.437	0.323	0.439	0.413	0.377	0.363	0.255	0.270	0.318
$\bar{S}^2$ (deg. <sup>2</sup> )	156	1366	71	48	115	89	53	114	640
$C_D$	0.2208	1.364	0.15	0.1196	0.201	0.150	0.240	0.183	0.96
$\pm P. E.$	0.0006	0.009	0.01	0.0004	0.001	0.004	0.001	0.004	0.02
$C_{D0}$	-	-	0.10	0.0862	-	0.096	0.103	0.103	-
$P. E. \text{ yaw } (\pm \text{ deg.})$	0.3	1.6		0.2	0.2		0.2		
$P. E. \text{ swerve } (\pm \text{ in.})$	0.01			0.007	0.01		0.008		
$C_{M1}/\text{deg.}$	-0.01156	-0.0134	-0.012	-0.01040	-0.01249	-0.011	-0.0117	-0.011	-0.014
$\pm P. E.$	0.00002	0.0001		0.00003	0.00003		0.0001		
$C_{M0}/\text{deg.}$	-0.01002	-	-0.011	-0.00992	-0.01132	-0.010	-0.0112	-0.010	
$C_{M1}/\text{deg.}$	-0.0369			-0.033	-0.037		-0.032		
$\pm P. E.$	0.0008			0.001	0.001		0.001		
$C_{M00}/\text{deg.}$	-0.0316			-0.031	-0.033		-0.030		
(CP-CG) cal.	0.313			0.316	0.340		0.366		
$CG_B$ (cal.)	1.786			1.794	1.798		1.795		
$CP_B$ (cal.)	1.473			1.478	1.458		1.429		
(CP-CG) <sub>0</sub> cal.	0.317			0.320	0.343		0.373		
$CP_{B0}$ (cal.)	1.469			1.474	1.455		1.422		
$C_{M1} + C_{M2}$	-8			-7	-7				
$\pm P. E.$	1			2	2				

The drag coefficients and the slopes of the pitching-moment and normal-force coefficients were corrected to zero yaw. The equations used are as follows:

$$C_{D0} = C_D - k_D \bar{\delta}^2$$

$$C_{M\alpha 0} = C_{M\alpha} - k_M \bar{\delta}^2, \text{ and}$$

$$C_{N\alpha 0} = C_{N\alpha} - k_N \bar{\delta}^2$$

where the slope  $k_D$  was determined using data from a number of rounds launched at approximately the same conditions, and the slopes  $k_M$  and  $k_N$  were determined using all rounds regardless of pressure. No trend of the slope of the dynamic stability coefficient with mean-squared yaw could be observed, and therefore, this coefficient was not corrected to zero yaw.

Figure 3 is a plot of the zero-yaw drag coefficient as a function of Reynolds number. The plot shows a decrease in




FIG. 3 ZERO YAW DRAG COEFFICIENT AS A FUNCTION OF REYNOLDS NUMBER

the drag coefficient with an increase in Reynolds number for both cones investigated at the Mach numbers at which the program was conducted. Within the probable error of the coefficient, no effect of Reynolds number on the slopes of the pitching-moment and normal-force coefficients was observed. Therefore, no movement of the center of pressure with varying Reynolds number occurred at the conditions investigated. These conditions were for laminar-boundary layer flow only. Figures 4, 5, and 6, respectively, show the slopes of the pitching-moment and normal-force coefficients and center of pressure as a function of Reynolds number.




FIG. 4 SLOPE OF THE PITCHING MOMENT COEFFICIENT CORRECTED TO ZERO YAW AS A FUNCTION OF REYNOLDS NUMBER




FIG. 5 SLOPE OF THE NORMAL FORCE COEFFICIENT CORRECTED TO ZERO YAW AS A FUNCTION OF REYNOLDS NUMBER





FIG. 6 ZERO YAW CENTER OF PRESSURE LOCATION AS A FUNCTION OF REYNOLDS NUMBER

Figures 7(a) through 7(l) include a set of representative shadowgraph prints of both cone configurations at all of the pressures investigated.



(a) SHOT NO. 4732, STATION 9V  
 $R_N \cdot R_B = 0.027, M = 9.260$   
 $P = 1 \text{ ATM}, R_{ef} = 9.193 \times 10^6$   
TUNGSTEN NOSE




(b) SHOT NO. 4732, STATION 27V  
 $R_N \cdot R_B = 0.027, M = 9.080$   
 $P = 1 \text{ ATM}, R_{ef} = 9.196 \times 10^6$   
TUNGSTEN NOSE




(c) SHOT NO. 4727, STATION 9V  
 $R_N \cdot R_B = 0.297, M = 7.586$   
 $P = 1 \text{ ATM}, R_{ef} = 3.013 \times 10^6$   
HEVIMET NOSE  
FIG. 7 CONTINUED


NOLTR 65-36




(d) SHOT NO. 4338 STATION 20  
 $R_N R_p = 0.0027 \text{ M} = 9.120$   
 $P = 76.4 \text{ mm Hg. } \sigma = 0.315 \times 10^6$   
HELMET NOSE



(e) SHOT NO. 440 STATION 20  
 $R_N R_p = 0.027 \text{ M} = 9.104$   
 $P = 66.2 \text{ mm Hg. } \sigma = 0.277 \times 10^6$   
HELMET NOSE




(f) SHOT NO. 444 STATION 20  
 $R_N R_p = 0.227 \text{ M} = 9.104$   
 $P = 46.9 \text{ mm Hg. } \sigma = 0.241 \times 10^6$   
HELMET NOSE  
FIG. CONTINUED



(g) SHOT NO. 4742, STATION 13V  
 $R_N / R_B = 0.297$ ,  $M = 8.244$   
 $P = 1 \text{ ATM}$ ,  $R_{e_l} = 3.354 \times 10^6$   
HEVIMET NOSE




(h) SHOT NO. 4723, STATION 16V  
 $R_N / R_B = 0.297$ ,  $M = 7.639$   
 $P = 1 \text{ ATM}$ ,  $R_{e_l} = 3.181 \times 10^6$   
HEVIMET NOSE



(i) SHOT NO. 4402, STATION 21V  
 $R_N / R_B = 0.027$ ,  $M = 9.198$   
 $P = 37.7 \text{ mm Hg}$ ,  $R_{e_l} = 0.255 \times 10^6$   
HEVIMET NOSE

FIG. 7 CONTINUED

NOLTR 63-36




(j) SHOT NO. 4390, STATION 24V

$R_N / R_B = 0.297$ ,  $M = 9.123$

$P = 75.5 \text{ mm Hg}$ ,  $R_{c1} = 0.372 \times 10^6$

HEVIMET NOSE




(k) SHOT NO. 4397, STATION 7V

0.002" NOSE FLAT DIA.,  $M = 8.226$

$P = 98.5 \text{ mm Hg}$ ,  $R_{c1} = 0.605 \times 10^6$

HEVIMET NOSE



(l) SHOT NO. 4389, STATION 11V

$R_N / R_B = 0.297$ ,  $M = 9.219$

$P = 91.0 \text{ mm Hg}$ ,  $R_{c1} = 0.453 \times 10^6$

HEVIMET NOSE

FIG. 7 CONTINUED

BALLISTICS DEPARTMENT DISTRIBUTION LIST B1

	Copies
Commander, Naval Air Systems Command Department of the Navy Washington, D. C. 20360 Attn: AIR-604	1
AIR-5301	1
AIR-5302	1
AIR-3032B	1
AIR-532	1
Commander, Naval Ordnance Systems Command Department of the Navy Washington, D. C. 20360 Attn: ORD-9132	1
ORD-035	1
ORD-0321	1
Defense Documentation Center Cameron Station Alexandria, Virginia 22314	20
Office of Naval Research Washington, D. C. 20360 Attn: Fluid Dynamics Branch	1
Structural Mechanics Branch, 4214 Main Navy	1
Commanding Officer Office of Naval Research Branch Office, Box 39 Fleet Post Office, New York, New York 09510	5
U. S. Army Ballistics Research Laboratories Aberdeen Proving Ground, Maryland 21005 Attn: Technical Library, Bldg 313	1
E. D. Boyer, Chief, Transonic Range Facility	1
Advanced Research Projects Agency Washington, D. C. 20301 Attn: Mr. Clifford E. McLain, Missile Phenomenology Branch	1
Arnold Engineering Development Center (ARO, Inc.) Arnold Air Force Station, Tennessee 37389 Attn: Library/Documents	2
Mr. J. Lukasiewicz, Chief, VKF	1
Mr. Pat Clemens	1

BALLISTICS DEPARTMENT DISTRIBUTION LIST B1

	Copies
Director Defense Research and Engineering The Pentagon Washington, D. C. 20301 Attn: Library (Technical) 3C-128	1
Los Alamos Scientific Laboratory P. O. Box 1663 Los Alamos, New Mexico 87544 Attn: Report Library	1
National Aeronautics and Space Administration Lewis Research Center 21000 Brookpark Road Cleveland, Ohio 44135 Attn: Mr. George Mandel, Chief, Library	1
National Aeronautics and Space Administration Goddard Space Flight Center Greenbelt, Maryland 20771 Attn: Library	1
Mr. E. F. Sargent, Code 671.2	1
National Aeronautics and Space Administration George C. Marshall Space Flight Center Huntsville, Alabama 35812 Attn: R-P&VE-PT, Mr. H. A. Connell	1
Aero-Astrodynamics Laboratory, Dr. Ernst Geissler	1
National Aeronautics and Space Administration Langley Research Center Langley Station Hampton, Virginia 23365 Attn: Librarian, MS 185	1
Mr. Mitchel H. Bertram, MS 243	1
Mr. Russell Hopko, PARC, MS 213	1
National Aeronautics and Space Administration Ames Research Center Moffett Field, California 94035 Attn: Mr. A. G. Boissevain	1
National Aeronautics and Space Administration Headquarters, MTG 400 Maryland Avenue, S. W. 20546 Washington, D. C. Attn: Dr. W. L. Haberman	1

BALLISTICS DEPARTMENT DISTRIBUTION LIST B1

	(Copies
National Aeronautics and Space Administration 600 Independence Avenue, S. W. Washington, D. C. 20546 Attn: Dr. H. H. Kurzweg, Director of Research	1
National Bureau of Standards Washington, D. C. 20760 Attn: Dr. Galen E. Schubauer	1
Commanding Officer U. S. Naval Air Development Center Johnsville, Pennsylvania 18974 Attn: NADC Library	1
Commander U. S. Naval Missile Center Point Mugu, California 93041 Attn: Technical Library, Code N0322	1
Commander U. S. Naval Ordnance Test Station China Lake, California 93555 Attn: Code 406 Code 50704 Technical Library	1 1 1
Superintendent U. S. Naval Postgraduate School Monterey, California 93940 Attn: Library (Code 0384)	1
Director U. S. Naval Research Laboratory Washington, D. C. 20390 Attn: Code 2027 H. F. Swift, Impact Damage Section	1 1
Commanding Officer U. S. Naval Underwater Ordnance Station Newport, Rhode Island 02844 Attn: Mr. R. J. Grady	1
U. S. Navy Underwater Sound Laboratory Fort Trumbull New London, Connecticut 06320 Attn: Library	1
U. S. Naval Weapons Laboratory Dahlgren, Virginia 22448 Attn: Library Code KE Code TX	1 1 1

BALLISTICS DEPARTMENT DISTRIBUTION LIST E1

	Copies
Scientific and Technical Information Facility P. O. Box 5700 Bethesda, Maryland 20014 Attn: NASA Representative (SAK/DL)	2
Aerospace Corporation P. O. Box 95085 Los Angeles, California 90045 Attn: Dr. J. S. Whittier Mr. J. F. Mullen	1 1
Director Alden Hydraulic Laboratory Worcester Polytechnic Institute Worcester 9, Massachusetts 01609 Attn: Professor L. J. Hooper	1
Allegheny Ballistics Laboratory Hercules Powder Company Cumberland, Maryland 21502 Attn: Captain N. J. Kleiss	1
Applied Physics Laboratory The Johns Hopkins University 8621 Georgia Avenue Silver Spring, Maryland 20910 Attn: Dr. Freeman Hill Dr. L. L. Cronvich Document Librarian Mr. I. B. Weckesser	1 1 4 1
AVCO-Everett Research Laboratory 2385 Revere Beach Parkway Everett, Massachusetts 02149 Attn: Dr. Kantrowitz	1
Battelle Memorial Institute 505 King Avenue Columbus, Ohio 43201 Attn: Remote Area Conflict Information Center Mr. Daniel E. Stohecker	1 1 1
The Boeing Company Aero-Space Division P. O. Box 3707 Seattle, Washington 98124 Attn: Ruth E. Peerenboom, Library Process Supervisor	1

BALLISTICS DEPARTMENT DISTRIBUTION LIST B1

	Copies
California Institute of Technology Pasadena, California 91109 Attn: Professor T. Y. Wu	1
The Catholic University of America Washington, D. C. 20017 Attn: Dr. C. C. Chang, Department of Space Science and Applied Physics	1
Ohio State University Department of Aero & Astronautical Engineering 2036 Neil Avenue Columbus, Ohio 43210 Attn: Professor Ting Yi Li	1
Cornell Aeronautical Laboratory 4455 Genesee Street Buffalo, New York 14225 Attn: Dr. Gordon Hall	1
Department of Mechanical Engineering University of Delaware Newark, Delaware 19711 Attn: Dr. James P. Hartnett	1
General Applied Sciences Laboratories, Inc. Merrick and Stewart Avenues Westbury, New York 11590 Attn: Mr. Robert Byrne	1
General Dynamics/Convair P. O. Box 1950 San Diego, California 92112 Attn: Mr. R. H. Oversmith, Chief, ASW/Marine Sciences 6-107	1
General Electric Company Missile and Space Division P. O. Box 8555 Philadelphia, Pennsylvania 19101 Attn: Mr. Lawrence I. Chasen, Manager/MSD Libraries	2
General Electric Company Re-entry Systems Dept. P. O. Box 8555 Philadelphia, Pa. 19104 Attn: Jerome Persh, Rm. U-7039(VF-STC)	1

BALLISTICS DEPARTMENT DISTRIBUTION LIST B1

	Copies
GM Defense Research Laboratories General Motors Corporation Box T Santa Barbara, California 93102 Attn: Dr. A. C. Charters - #27	1
The Johns Hopkins University Baltimore, Maryland 21218 Attn: Professor F. H. Clauser	1
Jet Propulsion Laboratory 4800 Oak Grove Drive Pasadena, California 91103 Attn: Library, TDS - N. E. Devereux	1
Kaman Aircraft Corporation Nuclear Division Colorado Springs, Colorado 80901 Attn: Dr. A. P. Bridges	1
Lockheed Missiles and Space Company 3251 Hanover Street Palo Alto, California 94304 Attn: Mr. Paul E. Sandorff, 52-20/201/2	1
Lockheed Missiles and Space Company Missile Systems Division P. O. Box 504 Sunnyvale, California 94086 Attn: R. A. Fuhrman, Dept. 81-01, Bldg 181	1
National Engineering Science Company 711 South Fair Oaks Avenue Pasadena, California 91105 Attn: Dr. Gunner Bergman	1
North American Aviation, Inc. Space and Information Systems Division 12214 Lakewood Boulevard Downey, California 90241 Attn: Technical Information Center, D/096-722 (AJ01)	1
Sandia Corporation Albuquerque, New Mexico 87115 Attn: Mr. R. C. Maydew, Aero-Thermodynamics Dept.	1

BALLISTICS DEPARTMENT DISTRIBUTION LIST B1

	Copies
Sandia Corporation Livermore Laboratory P. O. Box 969 Livermore, California 94551 Attn: Technical Library Reference	1
Director Southwest Research Institute Department of Mechanical Sciences San Antonio 6, Texas 78206 Attn: Library	1
Director St. Anthony Falls Hydraulic Laboratory University of Minnesota Minneapolis, Minnesota 55455 Attn: Professor E. Silberman	1
Stanford University Department of Aeronautics and Astronautics Stanford, California 95373 Attn: Dr. Daniel Bershader	1
Therm Advanced Research, Inc. 100 Hudson Circle Ithaca, New York 14851	1
United Aircraft Corporation Research Laboratories East Hartford, Connecticut 06108 Attn: Mr. H. J. Charette Mr. F. S. Owen	1 1
U. S. Army Engineer Research and Development Laboratories Fort Belvoir, Virginia 22060 Attn: Scientific and Technical Information Branch	1
Commanding Officer and Director David Taylor Model Basin Washington, D. C. 20007 Attn: Library, Aerodynamics Laboratory	1

BLANK PAGE

BALLISTICS DEPARTMENT DISTRIBUTION LIST B2

	Copies
Commander, Naval Air Systems Command Department of the Navy Washington, D. C. 20360 Attn: AIR-5203	1
National Aeronautics and Space Administration George C. Marshall Space Flight Center Huntsville, Alabama 35812 Attn: Dr. W. R. Lucas, R-P&VE-M	1
Director U. S. Naval Research Laboratory Washington, D. C. 20390 Attn: Mr. Edward Chapin, Code 6303	1
Commanding Officer U. S. Naval Underwater Ordnance Station Newport, Rhode Island 02844 Attn: Mr. M. T. McGowan	1
Space Systems Division Los Angeles Air Force Station Los Angeles, California 90045 Attn: SSSD	1
University of California Lawrence Radiation Laboratory P. O. Box 808 Livermore, California 94551 Attn: Mr. Carl Cline Mr. W. M. Wells, Propulsion Div., L-301	1 1
California Institute of Technology Pasadena, California 91109 Attn: Professor M. S. Plesset, Div. of Engineering	1
Colorado State University Fort Collins, Colorado 80521 Attn: Civil Engineering Hydraulics Lab.	1

BALLISTICS DEPARTMENT DISTRIBUTION LIST B2

	Copies
General Dynamics/Convair P. O. Box 1950 San Diego, California 92112 Attn: Dr. Blaine R. Parkin, Mail Zone 6-114	1
Hydronautics, Inc. Pindell School Road Howard County Laurel, Maryland 20810 Attn: Mr. P. Eisenberg Mr. M. P. Tulin	1 1
Jet Propulsion Laboratory 4800 Oak Grove Drive Pasadena, California 91103 Attn: Dr. L. Jaffee	1
Lockheed Missiles and Space Company P. O. Box 504 Sunnyvale, California 94086 Attn: Mr. R. W. Kermeen, Dept 51-35, Bldg 153 F/1	1
Sandia Corporation Albuquerque, New Mexico 87115 Attn: W. V. Hereford, Div. 7215	1
Technical Research Group, Inc. Route 110 Melville, New York 11746 Attn: W. Graham	1
Union Carbide Corporation Stellite Division 1020 Park Avenue Kokomo, Indiana 46901 Attn: Mr. W. D. Manly	1
University of Nebraska Lincoln, Nebraska 68508 Attn: Dr. R. C. Nelson, 202J Richards Hall	1

BALLISTICS DEPARTMENT DISTRIBUTION LIST B2

	Copies
Aeronutronics Division of Ford Company Newport Beach, California 92660 Attn: Mr. Walt Davey	5
Commander Air Force Ballistics Missile Division Air Research And Development Command Norton Air Force Base San Bernardino, California 92409	1
Sandia Corporation Livermore Laboratory P. O. Box 969 Livermore, California 94551 Attn: Mr. Stoller, 8149, Analytical Div.	1

BLANK PAGE

UNCLASSIFIED

Security Classification

DOCUMENT CONTROL DATA - R & D

Security classification of title, body of abstract and index annotations is entered when the overall report is classified.

3a ORIGINATING ACTIVITY (Corporate author) U. S. Naval Ordnance Laboratory White Oak, Silver Spring, Maryland		3b REPORT SECURITY CLASSIFICATION Unclassified	
3c REPORT TITLE DRAG AND STABILITY DATA OBTAINED FROM FREE-FLIGHT HYPERSONIC FIRINGS OF BOTH SHARP AND BLUNT NOSED 12-DEGREE 40-MINUTE TOTAL-ANGLE CONES AT SEVERAL RANGE PRESSURES			
4 DESCRIPTIVE NOTES (Type of report and inclusive dates) Ballistics Research Report			
5 AUTHOR(S) (First name, middle initial, last name) Leonard E. Crogan			
6 REPORT DATE 11 July 1966	7a TOTAL NO. OF PAGES 12	7b NO. OF REFS 1	
8a CONTRACT OR GRANT NO.	9a ORIGINATOR'S REPORT NUMBER(S) NOLTR 63-36		
b PROJECT NO.	9b OTHER REPORT NUMBER(S) (Any other numbers that may be assigned this report) Ballistics Research Report 94		
c			
d			
10 DISTRIBUTION STATEMENT Distribution of this document is unlimited.			
11 SUPPLEMENTARY NOTES		12 SPONSORING MILITARY ACTIVITY	
13 ABSTRACT Drag and stability data obtained from hypersonic firings of both pointed and blunt nosed 12-degree 40-minute total-angle cones at several range pressures are tabulated. The drag coefficient of both cones decreased with an increase in the Reynolds number. No effect of Reynolds number on the center of pressure of either cone configuration was observed.			

KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
Drag Stability Hypersonic Aeroballistic Cones Range						