U. S. NAVAL AIR ENGINEERING CENTER

PHILADELPHIA, PENNSYLVANIA

Aerospace Crew Equipment Laboratory Aerospace Crew Equipment Laboratory AN ENVIRONMENTAL WHOLE-BODY PLETHYSMCGRAPH By E. Hendler, Ph.D., D. W. Dery, Ph.D., J. B. Kearney, and S. Greco Foundational Research Project #32 BUMED Work Unit MR005.04-0046 NAEC-ACEL-545 13 JANUARY 1967


11

4ND . NAEC . 5213/8 (REV. 1.43)

DDC AVAILABILITY NOTICE

Distribution of this document is unlimited.





ARCHIVE COPY

FORESSION crsu 000 UNA NHO BUCED HOTF ACA THOM AND WIND ANALLE (1) AYALL CI

日本語のとう あまできる

「たちない」の必要

きょうない 二、「

NOTICE

Reproduction of this document in any form by other than naval activities is not authorized except by special approval of the Secretary of the Navy or the Chief of Naval Operations as appropriate.

The following Espionage notice can be disregarded unless this document is plainly marked CONFIDENTIAL or SECRET.

This document contains information affecting the national defense of the United States within the meaning of the Espionage Laws, Title 18, U.S.C., Sections 793 and 794. The transmission or the revelation of its contents in any manner to an unauthorized person is prohibited by law. An Environmental Whole-Body Plethysmograph

E. HENDLER, D.W. DERY, J.B. KEARNEY and S. GRECO

Aerospace Crew Equipment Laboratory Naval Air Engineering Center Philadelphia, Pennsylvania 19112

Whole body plethysmographs have been used to conveniently measure certain aspects of pulmonary function in man, including thoracic gas volumes and simultaneous airway resistances. These plethysmographs have been constructed for relatively short term occupancy and have been characterized by a gas-tight construction. We have constructed a whole-body plethysmograph which also functions as a controlled environmental chamber, capable of enclosing a subject for indefinitely extended periods. No attempt was made to make our plethysmograph gas-tight; on the contrary, by maintaining communication between the interior of the plethysmograph and the ambient environment, we have eliminated disturbing pressure effects due to changes in temperature and humidity within the enclosure.

Our plethysmograph was constructed of reinforced aluminum sheets (except for a reinforced plexiglas lid), to produce a box having overall dimensions of about 2.5 ft x 2.5 ft x 7 ft, and an internal volume of about 43.1 ft³ (1220 L.). As shown in Fig. 1, the box is supported on a wheeled carriage and can be oriented so that the subject within is either recumbent, seated, or standing. Additional features include: ports on each side with attached sleeves through which the subject can extend his arms, with minimal contamination of the box atmosphere, for such purposes as the withdrawal of blood samples; a mouthpiece-tube-valve arrangement through which expired gases can be collected into a container located outside the box; a pipe with shower heads located within the box for fire-fighting (a rather unlikely event, but nevertheless possible when the box atmosphere contains increased concentrations of oxygen); a respiratory assembly supported by a jointed arm, consisting of a mouthpiece, a solenoid-activated shutter, a Fleisch pneumotachygraph, and a number of access tubes for pressure measurements; a variety of sensors for measuring box temperature, subject temperature, box humidity, gaseous composition and pressure; and a two-way communications system.

Recumbent subjects have been exposed in this plethysmograph for 12 hr periods at sea ievel in eicher air or oxygen, and at altitude (5 psia in a low pressure chamber) in oxygen.* Plethysmographic measurements of thoracic gas (lung) volumes and airways resistance have been carried out by shutting off gas flow into the box, and having the subjects pant through the respiratory assembly. The plethysmograph is calibrated by pumping known gas volumes into and out of the box with a motor-driven syringe. Slowly changing box pressures due to temperature and humidity changes are relieved through an open valve, which exerts no appreciable effect on the rapid pressure changes upon which lung function measures are based. 4




Fig. 1. Environmental Whole-Body Plathysmograph

For comparative purposes, the residual voiumes of three supine subjects were determined using the body plethysmograph just described, and the open-circuit gas dilution technic. In addition, calculated values based upon sitting plethysmographic measures (courtesy of Dr. A. B. DuBois) and upon a formula based on age, sex, weight, and height, are shown in Table 1

TABLE 1

SUPINE RESIDUAL VOLUME (L)

	Measured		Calculated			
<u>Subj</u> ,	Pleth.	Gas <u>Dil.</u>	From <u>Sitting</u>	Formula		
D	1.06	1.12	1.04	1.40		
н	1.98	1.99	2.38	2.20		
R	1.90	1.56	1.45	2.24		

*In connection with studies being conducted under NASA DPR T-41832(G).

This work was supported by funds from the Bureau of Medicine and Surgery and from Foundational Research Projec: #32.

12.1

Plethysmography A.M., Tuesday 15 November

UNCLASSIFIED					
Security Claasification		-			
	CONTROL DATA - RAD				
	exing annotation must be entered when the overall report is classifie	and the second se			
1 ORIGINATING ACTIVITY (Corporate author)	24. REPORT SECURITY CLASSIFICA	TIÔN			
Aerospace Crew Equipment Laboratory		Unclassified			
Naval Air Ergineering Center	25. GROUP	25. GROUP			
Philadelphia, Pa. 19112					
AN ENVERONMENTAL WHOLE-BODY					
AN CHARACTER AC WHOLE BUD'	TELET SHUGKAPH				
4. DESCRIPTIVE NOTES (Typs of report and inclusive dates)					
Interim November 1965 Nov 5 AUTHOR(S) (Last name, Hest name, initial)	vember 1966				
Hendler, Edwin, Dery, Donald W., Kea	rney, John B.; and Greco, Samuel				
S. REPORT DATE	74. TOTAL NO. OF PAGES 75. NO. OF REFS				
13 January 1967	1				
A. CONTRACT OR GRANT NO.	94. ORIGINATOR'S REPORT NUMBER(S)				
b. PROJECT NO. Foundational Research #32	NAEC-ACEL-545				
. BUMED Work Unit MR005.04-0046	\$5. OTHER REPORT NO(5) (Any other numbers that may be assigned the report)				
ď					
0. A VAILABILITY/LIMITATION NOTICES					
1. SUPPLEMENTARY NOTES	12 SPONSORING MILITARY ACTIVITY Naval Arr Systems Command & Bureau of Medicine & Surgery Dept. of the Navy, Wash., D. C.				
3 ABSTRACT					
as an environmental chamber. In which periods This device has been used to	chs both as a whele-body plethysmograph a human subjects can be confined for prolor make pulmonary function measures while or periods to all and 100 per cent oxygen.	nged			

• ~

.

1 .

;

Security Classification

- -

UNCLASSIFIED

Security Classification

14. KEY WORDS	LINK A		Lap e 🕅		LINKC		
KEY WORDS		WT	per spe	³ ку т	ROLE	WT	
Plethysmograph Respiratory function Lung volumes	ROLE			· · · · · · · · · · · · · · · · · · ·			
INSTRUCTIONS							

1. ORIGINATING ACTIVITY: Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (corporate author) issuing the report.

2a. RFPORT SECURITY CLASSIFICATION: Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. GROUP: Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. REPORT TITLE: Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. DESCRIPTIVE NOTES: If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. AUTHOR(S): Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. REPORT DATE: Enter the date of the report as day, month, year; or month, year. If more than one date appears on the report, use date of publication.

7a. TOTAL NUMBER OF PAGES: The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. NUMBER OF REFERENCES. Enter the total number of references cited in the report.

8a. CONTRACT OR GRANT NUMBER: If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, 6s 8d. PROJECT NUMBER: Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. ORIGINATOR'S REPORT NUMBER(S): Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. OTHER REPORT NUMBER(S): If the report has been ssigned any other report numbers (either by the originator or by the sponsor), also enter this number(s).

10. AVAILABILITY/LIMITATION NOTICES: Enter any limitations on further dissemination of the report, other than those

imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through
- (5) "All distribution of this report is controlied. Qualified DDC users shall request through

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known

11. SUPPLEMENTARY NOTES: Use for additional explanatory notes.

12. SPONSORING MILITARY ACTIVITY: Enter the name of the departmental project office or laboratory sponsoring (paying for) the research and development. Include address.

13. ABSTRACT: Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (1S). (S). (C). or (U)

There is no limitation on the length of the abstract. Lowever, the suggested length is from 150 to 225 words.

14. KEY WORDS: Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, reles, and weights is optional.

. 1

UNCLASS FIED