

SECURITY

MARKING

The classified or limited status of this report applies to each page, unless otherwise marked.

Separate page printouts MUST be marked accordingly.

THIS DOCUMENT CONTAINS INFORMATION AFFECTING THE NATIONAL DEFENSE OF THE UNITED STATES WITHIN THE MEANING OF THE ESPIONAGE LAWS, TITLE 18, U.S.C., SECTIONS 793 AND 794. THE TRANSMISSION OR THE REVELATION OF ITS CONTENTS IN ANY MANNER TO AN UNAUTHORIZED PERSON IS PROHIBITED BY LAW.

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

AD 652357

NOLTR 67-32

(Handwritten circle)

MOLLIER DIAGRAM FOR NITROGEN

NOL

14 MARCH 1967

DDC
RECEIVED
MAR 31 1967
E *(Handwritten initials)*

UNITED STATES NAVAL ORDNANCE LABORATORY, WHITE OAK, MARYLAND

NOLTR 67-32

Distribution of this document is unlimited.

ARCHIVE COPY

F
45

NOLTR 67-32

Aerodynamics Research Report No. 285

MOLLIER DIAGRAM FOR NITROGEN

by

Richard L. Humphrey and Carolyn H. Piper

ABSTRACT: Thermodynamic data for nitrogen are presented in Mollier diagram form covering the temperature range of 30°K to 15,000°K and the density range of 10^{-7} to 10^3 amagat. Data for the solid and liquid regions are included. The diagram contains all available data of interest to the worker in fluid mechanics and aerodynamics. Speed of sound data are presented on separate charts.

U. S. NAVAL ORDNANCE LABORATORY
White Oak, Silver Spring, Maryland

NOLTR 67-32

14 March 1967

Mollier Diagram for Nitrogen

This report brings together in one large scale diagram most of the available data for nitrogen. The temperature range covered is 30°K to 15,000°K while densities from 10^{-7} to 10^3 are represented. This diagram is especially recommended for aerodynamicists and those engaged in aerodynamic facility design.

The authors acknowledge the assistance of Mr. John R. Bott who did the lettering of the diagram sheets.

E. F. SCHREIER
Captain, USAF
Commander

E. L. Harris
E. L. HARRIS
By direction

NOLTR 67-32

CONTENTS

	<u>Page</u>
INTRODUCTION.....	1
SOURCES FOR THE DIAGRAM.....	2
COMPILING THE NITROGEN MOLLIER DIAGRAM.....	5
USING THE MOLLIER DIAGRAM.....	5
SOURCES FOR THE ACOUSTIC VELOCITY CHARTS.....	6
REFERENCES.....	7
APPENDIX A - SYMBOLS LIST.....	A-1
APPENDIX B - STANDARD PROPERTIES AND CONVERSION FACTORS.....	B-1
APPENDIX C - DENSITIES CORRESPONDING TO THE DIAGRAMMED ARGUMENTS.....	C-1
APPENDIX D - CONVERSION FACTORS FOR F. DIN (REF. (1c)).....	D-1

ILLUSTRATIONS

	<u>Page</u>
Figure 1 - Skeleton Diagram Showing Sources of Data.....	3
Figure 2 - Index to the Nitrogen Mollier Diagram	
Figures 3-22 - The Mollier Diagram	
Figure 23 - Acoustic Velocity for Low Density Nitrogen	
Figure 24 - Acoustic Velocity for High Density Nitrogen	
Figure 25 - Acoustic Velocity for High Temperature Nitrogen	

INTRODUCTION

The demand for high Mach number low altitude flight simulation in wind tunnels has increased in recent years. Wind tunnel supply temperatures and pressures have increased tremendously. Tunnels now being planned require pressures to 5000 atmospheres and temperatures to 2800°K. At conditions such as these there are wide deviations from the ideal gas and such things as variable specific heat and intermolecular forces must be considered.

The need for adequate thermodynamic property data under these conditions is evident. The past ten years have seen an outpouring of works on the thermodynamic properties of air and these properties may now be considered to be well documented. However, the study of the properties of nitrogen has only recently resulted in adequate tables for high temperatures.

Thermodynamic diagrams have several advantages over tabulated tables. One of the principal advantages is convenience. The diagram allows trends to be seen at a glance and presents masses of data in a few sheets. The required information on most common thermodynamic processes can be obtained from the diagram without tedious interpolation in tables. In most cases the accuracy of the diagram is sufficient for engineering use.

The making of thermodynamic diagrams for gases has been a popular activity among thermodynamicists and chemists for the past 60 to 70 years. Din (ref. (1)) in his three volume work on gases for industrial use gives an excellent historical and critical review of such diagrams in general (ref. (1a)) and for particular gases as he discusses them individually. Generally, industrial and chemical users have preferred the temperature-entropy diagram, for example references (1) and (2), while aerodynamicists and power plant engineers used the Mollier or enthalpy-entropy diagram (refs. (3)-(7)). The many isenthalpic and isentropic processes encountered in fluid dynamics make the Mollier diagram popular in this field.

Most of the existing diagrams for nitrogen are limited in their coverage. Almost all do not include the high density-high temperature region that is now of growing interest. A recent report by Grabau and Brahinsky (ref. (8)) gives calculated properties of nitrogen for densities to 1000 amagat. This filled in a region for which no adequate data had been available.

NOLTR 67-32

The large amount of recent data that is now available and the limited scope of other diagrams made it advisable to compile a new diagram which would include as much of the available data as possible. It also afforded the opportunity to compare and study the various sources of thermodynamic properties. The new diagram is presented in this report. It covers a range from 30°K to 15,000°K and a density range from $\log \rho/\rho_0 = -7.0$ to 3.0; data for the solid, liquid, and vapor regions have been included.

The sources, the compilation, and the use of the diagram will be discussed. Appendices containing information helpful in the use of the diagram have been included.

SOURCES FOR THE DIAGRAM

A great many sources were used in the preparation of the diagram. Usually each source covered only a limited region. In some cases units and reference points had to be converted. Figure 1 gives a skeleton chart showing the scope of the diagram and reference numbers for each region. In some areas the regions overlap and several sources were used.

The bulk of the data from 100 to 1500°K and a density range from $\log \rho/\rho_0 = -7.0$ to 2.8 was taken from Little and Neel (ref. (9)). Their tables incorporate the work of Din (ref. (1c)) and Hilsenrath, et al (ref. (10)) for pressures down to 10^{-2} atmospheres. They used a perfect gas extrapolation for pressures below 10^{-2} atmospheres. At the high densities, the tabulated pressures range from 10^4 atmospheres at 300°K to 10^2 atmospheres at 1500°K.

The tables of Din are based on the best available experimental data. Din believes that his worst points are no more than 1.5 percent in error while most of the tables are good to within 0.5 percent. Din made an extensive comparison of the work of many experimenters and from these chose the best data for calculating his tables.

Below 100°K the ideal gas thermodynamic functions for molecular nitrogen of Hilsenrath, et al (ref. (1)) were used to determine enthalpy levels at zero pressure and entropy values at atmospheric pressure. Temperature lines were found by assuming that $(\partial H/\partial p) = 0$. The values of entropy at low pressures were found from the modified perfect gas relationship.

$$(S/R)_T = (S/R)_T - \ln p \\ p = 1 \text{ atm}$$




Figure 1 Skeleton Diagram Showing Sources of Data

NOLTR 67-32

The line connecting the critical point and the triple point was taken from Din (ref. (1c)). Some pressure and density lines near this region were taken from reference (2). This region defines the bounds between the saturated vapor and the saturated liquid. It is equivalent to the zero moisture line on a steam Mollier diagram. From the triple point to lower pressures the line of equilibrium between the solid and vapor phases (zero vapor line) was defined by the expression from Din (ref. (1c)) converted from mm Hg to atmospheres:

$$\log p = 3.61513 - \frac{(255.821)}{(T - 5.609)}$$

where T is in °K.

A discrepancy exists between the ideal gas data of reference (10) and the experimental triple point obtained from Din (ref. (1c)). The difficulty has not been resolved and caution should be used in interpreting the diagram near the zero vapor boundary below 100°K. Away from the boundary the ideal gas data should be adequate.

Data for the melting solid and the freezing liquid were taken from Din (ref. (1c)) and from reference (2). Extrapolations were made to extend these data to 1000 amagat ($\log p/p_0 = 3.0$). Properties at pressures above the critical point were taken from Din (ref. (2)) and from Little and Neel (ref. (9)). The trend of the data in this region indicates that a point is reached about 1000 amagat where the solid and the liquid regions coincide.

Properties for the high temperature low density region were taken from the tables of Hilsenrath and Klein (ref. (11)). These tables include the effects of dissociation, ionization, and intermolecular forces. Intermolecular forces are included to the second virial correction. Hilsenrath and Klein use the well-known procedure of listing all of the important chemical reactions taking place, determining the amount of reactants present at each condition and calculating the thermodynamic properties of the mixture. These properties are then corrected for the intermolecular forces. The tables have been widely used and are accepted as reliable.

Grabau and Brahinsky (ref. (8)) recently compiled a set of tables for high density nitrogen (to 1000 amagat) which includes third virial corrections. These tables extend to 5000°K and have been designed to blend well with the tables of Little and Neel (ref. (9)) at low temperatures. At the higher temperatures the property values of Hilsenrath and Klein (ref. (11)), and Smith (ref. (12)) at $\log p/p_0 = 0$ were used as points of departure. While Grabau makes no claims for accuracy, he feels that the tables are internally consistent and are adequate for engineering use.

COMPILING THE NITROGEN MOLLIER DIAGRAM

The convenient format of Little (ref. (3)) and Humphrey, Little, and Seeley (ref. (4)) was chosen for the diagram. The dimensionless forms, such as H/RT (enthalpy), S/R (entropy), $\log \rho/\rho_0$ (density in amagat units), and P (atmospheres) used in the National Bureau of Standards (NBS) tables (refs. (10) and (11)) and those based on the NBS work (refs. (3), (4), (6), (8), and (9)) were used whenever possible. The enthalpy function is shown as H/R in units of $^\circ K$. Conversion factors for various dimension systems are given in Appendix B. A table of densities corresponding to the values of $\log \rho/\rho_0$ is given in Appendix C.

Sections of the diagram are plotted on semilog paper. Each sheet covers one order of magnitude of enthalpy and seven units of entropy. An index to the sections is given in figure 2. This will aid in locating the desired sections. The diagram is cut off at a value of $S/R = 49$. The area of serious interest to workers in fluid dynamics lies in the region where values of entropy are low. A look at figure 2 shows that the diagram is beginning to taper to a long point bounded by $T = 15,000^\circ K$ and $\log \rho/\rho_0 = -7.0$. Thus only a small amount of useful information is lost by stopping the diagram at $S/R = 49$.

Whenever the work of Din (refs. (1c) and (2)) was used directly, the tabulated values were changed to the dimensionless values of NBS. The different reference points for zero entropy and enthalpy were also adjusted. The equations used are given in Appendix D.

The interpolation necessary to fill the low density region between 1500 and 2000 $^\circ K$ was done graphically. Slight differences between tables were smoothed by fairing a curve through several points on the curve.

USING THE MOLLIER DIAGRAM

This section is designed to help the user of the diagram and may be considered as independent of the remainder of the text.

The Mollier diagram contains values for the pressure, density, temperature, enthalpy, and entropy of nitrogen. Temperature ($^\circ K$) is represented by heavy solid lines and pressure (in atmospheres) by thin solid lines. The density ($\log \rho/\rho_0$, ρ in amagat units) is a dashed line. Enthalpy is in units of $^\circ K$ and the entropy is dimensionless. Pressure, temperature, and density lines are spaced at close enough intervals that linear interpolation is adequate in most cases. The symbols used are given in Appendix A and conversion factors to obtain other units in various dimension systems are in Appendix B.

NOLTR 67-32

The compressibility factor, Z , may be found from the expression, $Z = P/\rho RT$. This is especially easy as R is 3.661×10^{-3} ($1/(273.16^\circ\text{K})$) when P is in atmospheres, ρ in amagats, and T in $^\circ\text{K}$. If T is in $^\circ\text{R}$, R is 2.175×10^{-3} ($1/(459.69^\circ\text{R})$). These values of R are independent of the type of gas so long as atmosphere and amagat units are used.

The index sheet, figure 2, will help to locate the proper sheets within the diagram. The sheets are numbered in columns so that an isentropic process may be followed more easily.

SOURCES FOR THE ACOUSTIC VELOCITY CHARTS

The speed of sound data were taken from Lewis and Neel (refs. (13) and (14)). They calculated specific heats and acoustic velocities from the tables of Little and Neel (ref. (9)), Hilsenrath and Klein (ref. (11)), and Smith (ref. (12)). The tables were plotted at constant density as a function of temperature to check the matching of the various sources. The acoustic velocity blended smoothly from source to source except at the very high densities. At densities of $\log \rho/\rho_0 = 2.4$ and 2.6 discontinuities exist between acoustic velocities calculated from Little and Neel and those calculated from Smith. The discontinuities are modest at $\log \rho/\rho_0 = 2.4$ but are very large at $\log \rho/\rho_0 = 2.6$. The charts probably should not be used for densities greater than $\log \rho/\rho_0 = 2.4$. The acoustic velocities are given in terms of a/a_0 , where a_0 is the acoustic velocity at standard conditions. Values of a_0 are given in Appendix B. The curves are given at constant temperature as a function of $\log \rho/\rho_0$. The three charts cover the low temperature ($T < 2000^\circ\text{K}$)-low density region ($\log \rho/\rho_0 < 0$), the high temperature region ($T > 2000^\circ\text{K}$), and the low temperature ($T < 2000^\circ\text{K}$)-high density region ($\log \rho/\rho_0 > -1.0$).

NOLTR 67-32

REFERENCES

- (1) Din, F., Thermodynamic Functions of Gases, Butterworths, London
 - (1a) Vol 1, (1956), Thermodynamic Diagrams and Functions and their Preparation, Ammonia, Carbon Dioxide, Carbon Monoxide
 - (1b) Vol 2, (1956), Air, Acetylene, Ethylene, Propane, Argon
 - (1c) Vol 3, (1961), Methane, Nitrogen, Ethane
- (2) Din, F., Temperature-Entropy Diagram for Nitrogen, Butterworths, London, 1958
- (3) Little, W. J., "Mollier Diagram for Air," AEDC-TDR-63-190, Sep 1963
- (4) Humphrey, R. L., Little, W. J., and Seeley, L. A., "Mollier Diagram for Nitrogen," AEDC-TN-60-83, May 1960
- (5) Feldman, S., "Hypersonic Gas Dynamic Charts for Equilibrium Air," AVCO Research Laboratory, Jan 1957
- (6) Korobkin, I., and Hastings, S. M., "Mollier Chart for Air in Dissociated Equilibrium at Temperatures of 2000°K to 15,000°K," NAVORD 4446, May 1957
- (7) Keenan, J. H., and Keyes, F. G., Thermodynamic Properties of Steam, first edition, J. Wiley and Sons, New York, 1936
- (8) Grabau, M., and Brahinsky, H. S., "Thermodynamic Properties of Nitrogen from 300 to 5000°K and from 1 to 1000 Amagats," AEDC-TR-66-69, Aug 1966
- (9) Little, W. J., and Neel, C. A., "Tables of the Thermodynamic Properties of Nitrogen from 100 to 1500°K," AEDC-TDR-62-170, Sep 1962
- (10) Hilsenrath, J., et al, "Tables of Thermal Properties of Gases," National Bureau of Standards Circular 564, Nov 1955
- (11) Hilsenrath, J., and Klein, M., "Tables of Thermodynamic Properties of Nitrogen in Chemical Equilibrium Including Second Virial Corrections from 2000°K to 15,000°K," AEDC-TDR-63-162, Mar 1964
- (12) Smith, C. E., Jr., "Thermodynamic Properties of Nitrogen," LMSC L-90-62-111, Dec 1962
- (13) Lewis, C. H., and Neel, C. A., "Specific Heat and Speed of Sound Data for Imperfec. Nitrogen, I. T = 2000 to 15,000°K," AEDC-TDR-64-113, Jun 1964

NOLTR 67-32

- (14) Lewis, C. H., and Neel, C. A., "Specific Heat and Speed of Sound Data for Imperfect Nitrogen, II. $T = 100$ to 2200°K ," AEDC-TDR-64-114, Jun 1964

NOLTR 67-32

APPENDIX A

SYMBOLS LIST

a	acoustic velocity
a _s	acoustic velocity, S.T.P.
°C	temperature in degrees Centigrade
c.p.	critical point
°F	temperature in degrees Fahrenheit
H	enthalpy
°K	temperature in degrees Kelvin
P	pressure (atm)
p _s	reference pressure
R	gas constant
°R	temperature in degrees Rankine
S	entropy
T	temperature
t.p.	triple point
Z	compressibility factor
ρ	density
ρ _s	reference density

APPENDIX B

STANDARD PROPERTIES AND CONVERSION FACTORS

1. Standard Properties

molecular weight	28.016
density of the gas at S.T.P. (international atm. $g = 980.665$)	$0.0012525 \text{ grams/cm}^3$
molecular volume at N.T.P.	$22,403.5 \text{ cm}^3$
boiling point of liquid at 1 atm.	77.35°K
triple point: temperature	63.15°K
pressure	94.01 mm Hg
critical constants: temperature	126.2°K
pressure	33.5 atm.
volume	$90.094 \text{ cm}^3/\text{mole}$
density	248.668 amagat

2. Conversion Factors

Standard Atmospheric Pressure

$P_0 = 760 \text{ mm Hg}$
 29.921 in Hg
 10332 kg/m^2
 14.696 psia
 2116 psfa

Reference Density

$\rho_0 = 1.25046 \times 10^{-3} \text{ gram/cm}^3$
 $4.46338 \times 10^{-5} \text{ moles/cm}^3$
 $1.25050 \text{ gram/liter}$
 $4.51760 \times 10^{-5} \text{ lb/in}^3$
 $7.80461 \times 10^{-2} \text{ lb/ft}^3$
 $2.42435 \times 10^{-3} \text{ slugs/ft}^3$

Temperature

$T (^{\circ}\text{K}) \times 1.8 = T (^{\circ}\text{R})$
 $T (^{\circ}\text{K}) = T (^{\circ}\text{C}) + 273.16$
 $T (^{\circ}\text{R}) = T (^{\circ}\text{F}) + 459.69$

Acoustic Velocity

$a_0 = 1105.66 \text{ ft/sec}$
 $= 0.337006 \text{ mm}/\mu\text{sec}$
 $= 0.337006 \text{ km/sec}$

NOLTR 67-32

To Change	To	With Units of	Multiply By
H/R (°K)	H/RT	none	1/T (°K)
	H/R	°R	1.8
	H	ft ² /sec ²	3196.66
		BTU/lb	0.12768
		cal/gm	0.0709305
S/R	S	ft ² /sec ² -°K	3196.66
		ft ² /sec ² -°R	1775.92
		BTU/lb-°R	0.07093
		BTU/lb-°K	0.12678
		cal/gm-°K	0.0709305
ρ/ρ ₀	ρ	gm/cm ³	1.25046 x 10 ⁻³
		lb/in ³	4.51760 x 10 ⁻⁵
		lb/ft ³	7.80641 x 10 ⁻²

NOLTR 67-32

APPENDIX C

DENSITIES CORRESPONDING TO THE DIAGRAMMED ARGUMENTS

<u>Log ρ/ρ_0</u>	<u>ρ/ρ_0 (amagats)</u>
3.0	1000.000
2.9	794.333
2.8	630.957
2.6	398.107
2.4	251.189
2.2	158.489
2.0	100.000
1.8	63.0957
1.6	39.8107
1.4	25.1189
1.2	15.8489
1.0	10.0000
0.8	6.30597
0.6	3.98107
0.4	2.51189
0.2	1.584489
0.0	1.000000
-0.2	0.630957
-0.4	0.398107
-0.6	0.251189
-0.8	0.158489
-1.0	0.100000
-1.2	0.0630957
-1.4	0.0398107
-1.6	0.0251189
-2.0	0.0100000
etc.	etc.

NOLTR 67-32

APPENDIX D

CONVERSION FACTORS FOR F. DIN (REF. (1c))

Din's units are:

Entropy - joules/(mole-°K)

Volume - cubic centimeters/mole

Enthalpy - joules/mole

$\rho/\rho_0 = 2.24035 \times 10^4 / (\text{tabulated value})$

$S/R = 1.2173 \times 10^{-1} \times \text{tabulated value}$

$H/R = (1.2173 \times 10^{-1} \times \text{tabulated value}) - 848.0$




Figure 2 Index to the Nitrogen Mollier Diagram




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15

NOLTR 67-32




FIG. 16




FIG. 17

Approved for release by NSA on 05-08-2014 pursuant to E.O. 13526

Approved for release by NSA on 05-08-2014 pursuant to E.O. 13526




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23 ACOUSTIC VELOCITY FOR LOW TEMPERATURE NITROGEN




FIG. 24 ACOUSTIC VELOCITY FOR HIGH DENSITY NITROGEN




FIG. 25 ACOUSTIC VELOCITY FOR HIGH TEMPERATURE NITROGEN

UNCLASSIFIED
Security Classification

DOCUMENT CONTROL DATA - R&D		
<i>(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)</i>		
1 ORIGINATING ACTIVITY (Corporate author) U. S. Naval Ordnance Laboratory White Oak, Silver Spring, Maryland	2a REPORT SECURITY CLASSIFICATION Unclassified	
	2b GROUP	
3 REPORT TITLE MOLLIER DIAGRAM FOR NITROGEN		
4 DESCRIPTIVE NOTES (Type of report and inclusive dates) Final		
5 AUTHOR(S) (Last name, first name, initial) Humphrey, Richard L. Piper, Carolyn H.		
6 REPORT DATE 14 March 1967	7a TOTAL NO OF PAGES 37	7b NO OF REFS 14
8a. CONTRACT OR GRANT NO.	9a ORIGINATOR'S REPORT NUMBER(S) NOLTR 67-32	
b. PROJECT NO.	9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)	
c.	Aerodynamic Research Report No. 285	
d.		
10 AVAILABILITY/LIMITATION NOTICES "Distribution of this document is unlimited."		
11 SUPPLEMENTARY NOTES	12 SPONSORING MILITARY ACTIVITY	
13. ABSTRACT Thermodynamic data for nitrogen are presented in Mollier diagram form covering the temperature range of 30°K to 15,000°K and the density range of 10 ⁻⁷ to 10 ³ amagat. Data for the solid and liquid regions are included. The diagram contains all available data of interest to the worker in fluid mechanics and aerodynamics. Speed of sound data are presented on separate charts.		

DD FORM 1473
1 JAN 64

UNCLASSIFIED
Security Classification

14 KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
nitrogen						
thermodynamic properties						
gas properties						
Mollier diagram						
acoustic velocity						
sound speed						

INSTRUCTIONS

1. ORIGINATING ACTIVITY: Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (*corporate author*) issuing the report.

2a. REPORT SECURITY CLASSIFICATION: Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. GROUP: Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. REPORT TITLE: Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. DESCRIPTIVE NOTES: If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. AUTHOR(S): Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. REPORT DATE: Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.

7a. TOTAL NUMBER OF PAGES: The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. NUMBER OF REFERENCES: Enter the total number of references cited in the report.

8a. CONTRACT OR GRANT NUMBER: If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. PROJECT NUMBER: Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. ORIGINATOR'S REPORT NUMBER(S): Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. OTHER REPORT NUMBER(S): If the report has been assigned any other report numbers (*either by the originator or by the sponsor*), also enter this number(s).

10. AVAILABILITY/LIMITATION NOTICES: Enter any limitations on further dissemination of the report, other than those

imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. SUPPLEMENTARY NOTES: Use for additional explanatory notes.

12. SPONSORING MILITARY ACTIVITY: Enter the name of the departmental project office or laboratory sponsoring (*paying for*) the research and development. Include address.

13. ABSTRACT: Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. KEY WORDS: Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, roles, and weights is optional.