ESD-TR-67-91

ESD RECORD COPY

RETURN TO SCIENTIFIC & TECHNICAL INFORMATION DIVISION (ESTI), BUILDING 1211

				N	ATR-2	252	
ES	5D	A	CCES	SI	ON	LI	ST
ESTI	Call	No.	AL	5	720	1	
Сору	No.		1	of			cys.

THE INVERSE DIFFRACTION PROBLEM: ANALYSIS OF SPECULARS



ESD TR-67-91 FILE COPY

JUNE 1967

R. M. Lewis (Consultant)

Prepared for

SPACE DEFENSE SYSTEMS PROGRAM OFFICE DEPUTY FOR SURVEILLANCE AND CONTROL SYSTEMS ELECTRONIC SYSTEMS DIVISION AIR FORCE SYSTEMS COMMAND UNITED STATES AIR FORCE L. G. Hanscom Field, Bedford, Massachusetts



This document has been approved for distribution and sale; its distribution is unlimited. Project 4966 Prepared by THE MITRE CORPORATION Bedford, Massachusetts Contract AF19(628)-5165 When US Government drawings, specifications, or other data are used for any purpose other than a definitely related government procurement operation, the government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise, as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Do not return this copy. Retain or destroy.

ESD-TR-67-91

THE INVERSE DIFFRACTION PROBLEM: ANALYSIS OF SPECULARS

JUNE 1967

R. M. Lewis (Consultant)

Prepared for

SPACE DEFENSE SYSTEMS PROGRAM OFFICE DEPUTY FOR SURVEILLANCE AND CONTROL SYSTEMS ELECTRONIC SYSTEMS DIVISION AIR FORCE SYSTEMS COMMAND UNITED STATES AIR FORCE L. G. Hanscom Field, Bedford, Massachusetts



This document has been approved for distribution and sale; its distribution is unlimited. Project 4966 Prepared by THE MITRE CORPORATION Bedford, Massachusetts Contract AF19(628)-5165



ABSTRACT

Specular returns from radar targets contain large power which makes a technique based on the analysis of speculars attractive. Herein, the specular returns from a flat region and from a smooth surface tangent to a plane along a curve, which are the largest returns for reasonably sized bodies, are used to obtain information about the geometry of the target.

REVIEW AND APPROVAL

This technical report has been reviewed and is approved.

homas O. Wear

THOMAS O. WEAR, Colonel, USAF Director, Space Defense Systems Program Office Deputy for Surveillance and Control Systems



TABLE OF CONTENTS

	Page
INTRODUCTION	1
QUASI-MONOSTATIC SCATTERING	1
SPECULAR ANALYSIS OF A FLAT REGION	6
SOLUTION OF THE WIDTH PROBLEM	7
SPECULAR ANALYSIS OF A SMOOTH SURFACE WHICH IS TANGENT TO A PLANE ALONG A CURVE	10

LIST OF ILLUSTRATIONS

Figure No.		Page
1	Boundary of P Given by Two Functions	4
2	Illustration of a Multistatic System for Making Required Measurements Instantaneously	6
3	Rotated Axes	8
4	Smooth Surface Tangent to a Plane Along a Curve	11



INTRODUCTION

Specular returns from scattering targets may be classified according to the order of magnitude of the return. It can be shown that some typical returns are (after suitable normalization) of the following order in ka, where k is the wave-number and a is a typical target dimension:

	Order	Surface Geometry
0	$\left[\left(\mathrm{ka}\right)^{2}\right]$	flat region
0	$\left[\left(\mathrm{ka}\right)^{3/2}\right]$	smooth surface tangent to a plane along a curve
0	[(ka)]	Convex surface with non-zero Gaussian curvature
0	$\left[\left(\mathrm{ka}\right)^{1/2} ight]$	edge-diffraction
0	[1]	vertex-diffraction

Because of the large power of a specular return it would be convenient to use it to obtain information about the geometry of the corresponding specular region. In this paper we develop a method for doing this for the first two types of surface regions in the above table.

QUASI-MONOSTATIC SCATTERING

Let I be a unit vector in the direction of propagation of the plane wave

$$u_{i} = e^{ik\underline{I}\cdot\underline{X}} , \qquad (1)$$

which is incident on a target. If the total (scalar) field satisfies the boundary condition u = o on the surface of the target, then according to the Kirchhoff (physical optics) approximation, the scattered far-field is given by (see Equation (2, 25) of [1])

$$\mu_{\rm s} = \frac{\rm i \ e^{i k r}}{2 \ \pi \ k r} \ g, \tag{2}$$

where

$$g = -k^{2} \iint_{\ell} \underline{I} \cdot \underline{N} e^{ik (\underline{I} - \underline{J})} \cdot \underline{X} ds(\underline{X}).$$
(3)

Here k is the wave-number, r is the range. <u>N</u> is the outward unit normal vector on the surface of the target, <u>J</u> is a unit vector pointing from the target to the point of observation, and the surface integral of Equation (3) is taken over the illuminated portion ℓ of the target. A similar formula holds for the boundary condition $\partial u/\partial n = o$, and for scattering of an electromagnetic wave by a perfectly conducting target (see [1]).

A rectangular coordinate system such that $\underline{I} = (0, 0, -1), \underline{J} = (\sin \theta, 0, \cos \theta)$, and $\underline{X} = (x, y, z)$ is introduced. In the quasi-monostatic case $\theta \ll 1$ and $\underline{J} \sim (\theta, 0, 1)$. Then since $-\underline{I} \cdot \underline{N} ds = dxdy$. Equation (3) becomes

$$g(\theta) = k^{2} \iint_{P} e^{-ik[\theta x + 2z(x, y)]} dxdy , \qquad (4)$$

where P is the projection of ℓ onto the xy-plane.

[1] R. M. Lewis, Notes on the Kirchhoff Method in Scattering Problems.

For simplicity it is now assumed that the region P is intersected, at most, twice by each line parallel to the y-axis. Then its boundary is given by the two functions $y_1(x)$ and $y_2(x)$ as illustrated in Figure 1. These functions are defined so that they are continuous and have constant values outside of P. (Then $y_1 \equiv y_2$ outside of P). We take 2L greater than the largest diameter of P parallel to the x-axis and choose the origin so that the points $\pm L$ lie outside of P.

From Equation (4) we now see that

$$g(\theta) = k \int_{-L}^{L} \gamma(x) e^{-1k\theta x} dx, \qquad (5)$$

where

$$\gamma (\mathbf{x}) = \mathbf{k} \int_{y_1}^{y_2(\mathbf{x})} e^{-2i\mathbf{k}\mathbf{z}(\mathbf{x}, \mathbf{y})} d\mathbf{y}.$$
 (6)

From the theory of Fourier series it is known that if f(x) is piecewise smooth and if the Fourier coefficients

$$a_{n} = \frac{1}{2L} \int_{-L} f(x) e^{\frac{-in\pi x}{L}}, \qquad (7)$$





are introduced, then

$$f(x) = \sum_{\substack{n \\ n = -\infty}}^{\infty} a_n e \frac{in\pi x}{L} .$$
 (8)

Therefore, if

$$\theta = \frac{n\pi}{kL}$$
, $n = 0, \pm 1, \pm 2, \dots$ (9)

is set, then

$$\gamma (\mathbf{x}) = \sum_{\mathbf{n} = -\infty}^{\infty} C_{\mathbf{n}} e \frac{i \mathbf{n} \pi \mathbf{x}}{\mathbf{L}}$$
(10)

where

$$C_{n} = \frac{1}{2kL} g \frac{(n\pi)}{kL} .$$
 (11)

Thus if g can be measured for those values of θ given by Equation (9) γ (x) can be determined. The latter function is closely related to the geometry of the target as illustrated in the next section. A multi-static system for making the required measurements instantaneously is illustrated in Figure 2 (other measuring systems can obviously be used).

As illustrated in Figure 2, receivers are placed on a straight line at distances from the transmitter that are an integral multiple of τ . The system is characterized by four length parameters:

r range

 τ receiver spacing

- 2L body dimension (upper bound)
- $\lambda = 2\pi/k$ wave-length

Since r $\theta \sim n \tau$, we see from Equation (9) that the four parameters must satisfy the condition

$$\frac{\tau}{r} = \frac{\lambda}{2L} \quad . \tag{12}$$

In practice one would first choose 2L larger than the maximum expected dimension of the target and then set $\lambda = 2L\tau/r$.

Of course it is impractical to measure C_n except for small n, say n = o, ±1, ±2. Therefore, it is envisioned that measurements will be made only of specular returns. For such returns the larger Fourier coefficients will be negligible and a small number of terms in Equation (10) should give a very good approximation to γ (x). This is certainly true if γ (x) is smooth. If not, then a few terms will yield a smoothed approximation to γ (x).



Figure 2. Illustration of a Multistatic System for Making Required Measurements Instantaneously

SPECULAR ANALYSIS OF A FLAT REGION

The largest specular returns are produced by flat portions of a target. Assume that the region P in Figure 1 is a flat surface region normal to the direction of incidence I. Then one may take z(x, y) = 0 in Equation (6). Now

$$\gamma (\mathbf{x}) = \mathbf{k}\mathbf{w} (\mathbf{x}) \tag{13}$$

where w is the width function

$$w(x) = y_{2}(x) - y_{1}(x)$$
 (14)

Furthermore

g (0) = k
$$\int_{-L}^{L} \gamma$$
 (x) dx = k²A, (15)

where A is the area of P. Thus the monostatic specular return of a flat

region is of order $(ka)^2$ as noted in the introduction. Furthermore, since γ (x) is real, one sees from Equation (5) that $g^*(\theta) = g(-\theta)$. Hence $C_{-n} = C_n^*$. Thus, for a flat plate, the number of receiver sites can be reduced by a factor of two.

The function w(x) does not uniquely determine the shape of the region P, i.e., the functions $y_1(x)$ and $y_2(x)$, but we will see in the next section that if a second measurement is made corresponding to a rotation in the xy-plane, the shape of the region P can be found.

SOLUTION OF THE WIDTH PROBLEM

Let P be a region in the xy-plane whose boundary is intersected, at most, twice by each line parallel to the y-axis, as illustrated in Figure 1. We introduce a rotation

$$= x \cos \alpha + y \sin \alpha, \ \eta = -x \sin \alpha + y \cos \alpha.$$
 (16)

Then

 $y = \xi \sin \alpha + \eta \cos \alpha, x = \xi \cos \alpha - \eta \sin \alpha.$ (17) The rotated axes are illustrated in Figure 3.

Let $x_1 (\xi, \alpha)$ and $x_2 (\xi, \alpha)$ be the x-coordinates of the two boundary points on the dashed line ξ = constant parallel to the η - axis in Figure 3. From Equation (16) we see that the functions $x_i(\xi, \alpha)$ are defined implicitly by

$$\xi = x_j \cos \alpha + y_j (x_j) \sin \alpha, j = 1, 2.$$
 (18)

Let w (ξ , α) be the length of the dashed line joining the two boundary points, i.e., the width of the region P in the direction of the η - axis. Then from Equation (16)



Figure 3. Rotated Axes

w
$$(\xi, \alpha) = \eta_2 - \eta_1 = [-x_2 \sin \alpha + y_2 (x_2) \cos \alpha] - [-x_1 \sin \alpha + y_1 (x_1) \cos \alpha]$$

= $(x_1 - x_2) \sin \alpha + [y_2 (x_2) - y_1 (x_1)] \cos \alpha$. (19)

The following width problem is considered: Given w (ξ , α) for $\alpha = 0$ and a second value of α to determine the functions of y_1 (x) and y_2 (x). Actually the second value of α very near $\alpha = 0$ will be taken. More precisely, the function ω_{α} (ξ , 0) will be used.

At $\alpha = 0$, we see from Equation (18) that $x_j = \xi$, and by differentiating Equation (18) with respect to α we obtain

$$\frac{\partial \mathbf{x}_{j}}{\partial \alpha} = \mathbf{y}_{j}(\xi) .$$
⁽²⁰⁾

It follows from Equation (19) that at $\alpha = 0$

$$w(x, 0) = y_2(x) - y_1(x)$$
 (21)

and from Equations (4) and (5) one finds that

$$w_{\alpha}(\xi, 0) = y_{2}'(\xi) [-y_{2}(\xi)] - y_{1}'(\xi) [-y_{1}(\xi)] = -\frac{1}{2} \frac{d}{d\xi} [y_{2}^{2} - y_{1}^{2}] . \quad (22)$$

Since (see Figure 3)

$$y_2(x_0) = y_1(x_0)$$
 (23)

Equation (7) may be integrated to obtain

$$(y_2 + y_1) (y_2 - y_1) = y_2^2(x) = y_1^2(x) = q(x)$$
 (24)

where

.

$$q(x) = -2 \int_{\mathbf{x}_{0}}^{x} \mathbf{w}_{\alpha} (\xi, \mathbf{0}) d\xi.$$
(25)

From Equations (21) and (24) one sees that

$$y_2(x) + y_1(x) = \frac{q(x)}{w(x, 0)}$$
, (26)

and Equations (21) and (26) are easily solved to yield

$$y_{1/2}(x) = \frac{1}{2} \begin{bmatrix} \frac{q(x)}{w(x, 0)} & - \\ + & w(x, 0) \end{bmatrix}$$
 (27)

Thus Equations (25) and (27) provide a solution to the width problem.

SPECULAR ANALYSIS OF A SMOOTH SURFACE WHICH IS TANGENT TO A PLANE ALONG A CURVE

As a second example a regular surface which is tangent to the plane z = o along a curve $y = y_0(x)$ is considered. ^{*} Important examples are cylinders and cones; in these cases the curve is a straight line. The integral Equation (6) is evaluated by the method of stationary phase. A stationary point occurs at $y = y_0(x)$. If the phase function $\phi(y) = -2 z(x, y)$ is introduced, then at the stationary point $\phi = 0$, $\phi' = 0$, and $\phi'' = 2z_{yy}(x, y_0) > 0$. Hence

$$\gamma (x) \sim (\pi k)^{1/2} e^{i\pi/4} [-z_{yy} (x, y_0)]^{-1/2}.$$
 (28)

But $-z_{yy}$ is the curvature of the normal section of the surface in the direction of the y-axis. If we introduce the principal curvatures $K_1 = 0$ and $K_2 = K = 1/\rho$, then it can be shown that $-z_{yy} = K \cos^2 \beta$ where $\tan \beta = y'_0$ (x) (see Figure 4).

It follows that

$$\gamma (x) \sim e^{i\pi/4} \sqrt{\pi k\rho[x, y_0(x)] [1 + (y_0')^2]}$$
 (29)

Since the element of arc-length is ds = $\sqrt{1 + (y'_0)^2}$ dx it follows that

$$g(0) = k \int \gamma (x) dx \sim e^{i\pi/4} k \sqrt{\pi} \int \sqrt{k\rho} ds. \qquad (30)$$
-L

* It can be shown (by using the formula of Rodrigues) that the Gaussian curvature vanishes at each point of the curve and that the curve is a principal curve corresponding to the principal curvature K = o. Conversely if $K \equiv o$ along a principal curve, then that curve is a plane curve.



Figure 4. Smooth Surface Tangent to a Plane Along a Curve

Thus the monostatic specular return is of order $(ka)^{3/2}$ as noted in the introduction.

We see from Equation (29) that $\gamma(\mathbf{x})$ depends on the curve of tangency $\mathbf{y} = \mathbf{y}_0(\mathbf{x})$ and the non-zero principal radius of curvature ρ along this curve. These two functions characterize the geometry of the specular region in this case just as the two functions $\mathbf{y}_1(\mathbf{x})$ and $\mathbf{y}_2(\mathbf{x})$ determine the shape of the flat region on pages 6 & 7. On pages 7-9 it was proved how to determine \mathbf{y}_1 and \mathbf{y}_2 , given γ . The analogous problem for the determination of \mathbf{y}_0 and ρ , given γ , remains to be considered.



Security Classification				
DOCUM	ENT CONTROL DATA - R &	D	the overall report is standlind	
ORIGINATING ACTIVITY (Corporate author)	the the ang minoration must be en	2a. REPORT	SECURITY CLASSIFICATION	
The MITRE Corporation		U	NCLASSIFED	
Bedford, Massachusetts		2b. GROUP		
REPORT TITLE				
THE INVERSE DIFFRACTION PROP	TEM. ANALVSIS OF	DECUI	ADS	
THE INVERSE DIFFRACTION FROM	DEEM, ANALIDE OF	FLOUL	AIID	
DESCRIPTIVE NOTES (Type of report and inclusive day	(es)		_	
N/A				
AUTHOR(5) (First name, middle initial, last name)				
LEWIS, R. M. (Consultant)				
	A CONTRACTOR AND A CONTRACTOR			
REPORT DATE	78. TOTAL NO. OF	PAGES	7b. NO. OF REFS	
CONTRACT OR GRANT NO.	98. ORIGINATOR'S	REPORT N	UMBER(5)	
AF19(628)-5165	ESD	-TR-67-	.91	
ADCC				
4300	96. OTHER REPOR	T NO(5) (An	y other numbers that may be assigned	
	this report)	050		
1.	MTE	R-252		
DISTRIBUTION STATEMENT				
This document has been approved fo	r distribution and sale;	its dist	ribution is unlimited.	
1. SUPPLEMENTARY NOTES	12. SPONSORING M	ILITARY AC	CTIVLTY	
	Space Defens	Space Defense Systems Program Office, Deputy for Surveillance & Control Systems, Electronic Systems Division, L. G. Hanscom Field,		
	Systems Divi			
3. ABSTRACT	Bedford, Mas	sachuse	etts	
Specular returns from radar tar	gets contain large powe	r which	makes a technique based	
on the analysis of speculars attracti	ve. Herein, the specul	lar retur	rns from a flat region and	
from a smooth surface tangent to a	plane along a curve, wh	ich are	the largest returns for	
reasonably sized bodies, are used to	o obtain information abo	out the g	cometry of the target.	
D FORM 1470				
JU 1 NOV 65 4/3		UN	CLASSIFIED	

.

100

4

a second rest we want to be a second

•

UNC LASSIFIED Security Classification 14 LINK A LINK B LINK C KEY WORDS ROLE ROLE ROLE wт WT W T Specular Analysis ۲ Radar Targets Target Geometry UNCLASSIFIED Security Classification

à

- - -

