

AFAL-TR-68-51

AD 671 499

EFFECT OF A HEATED PLATINUM WIRE ON A SEALED CO₂ LASER SYSTEM

F. M. TAYLOR
A. LOMBARDO

Systems Research Laboratories, Inc.

and

W. C. EPPERS

Air Force Avionics Laboratory

TECHNICAL REPORT AFAL-TR-68-51

APRIL 1968



This document has been approved for public
release and sale; its distribution is unlimited.

AIR FORCE AVIONICS LABORATORY
AIR FORCE SYSTEMS COMMAND
WRIGHT-PATTERSON AIR FORCE BASE, OHIO

AFAL-TR-68-51

**EFFECT OF A HEATED PLATINUM WIRE
ON A SEALED CO₂ LASER SYSTEM**

F. M. TAYLOR
A. LOMBARDO

Systems Research Laboratories, Inc.

and

W. C. EPPERS

Air Force Avionics Laboratory

This document has been approved for public
release and sale, its distribution is unlimited

FOREWORD

This report was prepared by F. M. Taylor and A. Lombardo, Systems Research Laboratories, Inc., 500 Woods Drive, Dayton, Ohio, 45432, in conjunction with W. C. Eppers of the Air Force Avionics Laboratory, Wright-Patterson Air Force Base, Ohio, under Project No. 5237, Task No. 5237-10. The Systems Research Laboratories effort was performed under Contract F33615-67-C-1138 for the Air Force Avionics Laboratory, Wright-Patterson Air Force Base, under the technical cognizance of D. R. Nordstrom.

This report was submitted by the authors February 1968.

This technical report has been reviewed and is approved.



RAYMOND J. NORDLUND
Chief Scientist
Air Force Avionics Laboratory

ABSTRACT

A heated platinum wire was used in a sealed $\text{CO}_2\text{-N}_2\text{-He}$ laser system, resulting in increases in output power that were dependent on the initial fill pressure of CO_2 . The system was also filled with a $\text{CO}_2\text{-He}$ mixture and made to lase. Heating of the platinum wire caused a decrease in output power. It was tentatively concluded that the platinum catalyzes the reaction $\text{CO} + \text{O} \rightarrow \text{CO}_2$, permitting a higher concentration of CO_2 in a sealed system than is otherwise possible.

TABLE OF CONTENTS

SECTION	PAGE
I INTRODUCTION	1
II EXPERIMENTAL METHOD AND DATA	2
III CONCLUSION	9
REFERENCES	10

SECTION I INTRODUCTION

There has recently been some speculation (References 2 and 3) concerning the effect of decomposition of CO_2 in the plasma discharge of a sealed CO_2 laser. Such decomposition may result in the generation of new species of gases existing in some dynamic equilibrium population balance. In particular, CO , O , or O_2 are likely to result. The final specie concentration obtained in a sealed system could be dependent on numerous factors which often are only of incidental or minor importance in a flowing CO_2 system. Among these may be: electrode material, the type and quantity of impurities present in the original gases; or impurities resident in the system due to either a partial, or perhaps a total, lack of vacuum clean-out. Such impurities, in addition to the electrode material, may participate in the various chemical reactions promoted by the plasma either directly or catalytically. For instance, the free oxygen (O or O_2) may be precipitated out of the gaseous mixture in solid oxides, thus preventing reoxidation of C and CO . In general, the chemical activity going on will result in a steady or quasi-steady state in which the CO_2 percentage is lower than that of the initial fill.

Both Howe and Harrigan (References 2 and 3) report that CO may function as an intermediate gas in populating the upper laser level of CO_2 . However, in spite of such possible benefit, it would appear that the most desirable population specie balance in a sealed system would be as close as possible to the optimal for a flowing system where such specie population balance may, to a higher degree, be arbitrarily determined by the experimenter.

SECTION II

EXPERIMENTAL METHOD AND DATA

This report describes the beneficial effects of using a heated platinum wire in a sealed CO_2 system. Figure 1 shows the experimental setup. For all of the mixtures tried where N_2 was included as one of the fill gases, heating of the platinum wire resulted in a power increase. The loop structure shown was intended to provide a circulating convection flow of the plasma products over a heated Hopcalite catalyst (60% MnO_2 and 40% CuO). This procedure failed to produce a change in output power. It is suspected that the catalyst was poisoned by water that may have been in the commercial grade N_2 used. The platinum was #30 gauge thermocouple wire and was electrically heated to an estimated 850°C . The mirrors were fully aluminized with a pinhole method used for coupling. The platinum, as may be seen from Figure 1, was located external to the plasma and was not used as part of the electrodes. This was done to isolate the action of the heated platinum, since even when using "cold" cathodes, the surface temperature of the cathode may be elevated due to ion bombardment. W. J. Witterman (References 6, 7, and 8) has used platinum as electrodes to avoid reaction with the gas components and has achieved fairly high power output (20 watts) in a sealed $\text{CO}_2\text{-N}_2\text{-H}_2$ system.

Figure 2 illustrates the effect of the heated platinum on initial peak power values versus the initial percentage of CO_2 by pressure in the tube. Not shown in either Figure 2 or Figure 3 is a short-term (2 to 3 seconds) variation in the output power of about 10 to 15%. By monitoring the various lines that were lasing with a Perkin-Elmer infrared monochromator, it was determined that




Figure 1. Experimental Setup for Catalyzed CO₂ Laser System




Figure 2. Output Power for Varying Initial Fill Pressures of CO₂




Figure 3. Output Power for He - CO₂ Fill

this variation coincided with the appearance and disappearance of various P-branch transitions around P(20). Such line drift has been attributed by Rigden and Moeller (Reference 5) to variations in cavity length. This effect appeared independent of whether the platinum wire was heated or not. The specific lines lasing were P(18), P(20), P(22), and P(24). There was no discernible temperature change ($< 1^\circ\text{C}$) of the gases when the platinum was heated. The largest power increase obtained was at 15% CO_2 (1.05 torr CO_2 , 1.0 torr N_2 , 5.0 torr He). It had previously been determined that the optimal partial pressures for the same system under flowing conditions were approximately 1.0 torr CO_2 , 1.0 torr N_2 , 5.0 torr He (these pressures were uncorrected for flow error).

A mixture of He and CO_2 was admitted to the tube and made to lase. The results are shown in Figure 3. As may be seen from the curve, heating of the platinum in this case extinguished laser action. The two cases may be explained if the heated platinum is catalyzing the reaction $\text{CO} + \text{O} \rightarrow \text{CO}_2$. In the first case, with the N_2 present and performing the intermediate pump gas function of populating the upper laser level of CO_2 , a power increase is obtained as the detrimental effects of the free oxygen (Reference 4) are reduced and the CO_2 percentage is brought nearer the optimal. In the second case, the CO generated by the discharge is apparently functioning as the pump gas. Note in Figure 3 that the output of the laser was zero upon initial turn-on, and remained so until sufficient CO had been generated to create a population inversion in the CO_2 . Thus, activating the catalyst in this system caused a power reduction as the percentage of one of the essential ingredients (CO) in the energy scheme was reduced.

To further verify this hypothesis, the visible Angstrom bands of CO at 484 $m\mu$ (0-1) and at 520 $m\mu$ (0-2) (Reference 3) were monitored with a monochromator, photomultiplier, and phase-lock amplifier combination. The results in Figure 4 show an evident decrease in intensity of the CO lines each time the platinum wire was heated, indicating a decrease in the CO concentration in agreement with the above hypothesis. The power supply used was unregulated and there was a slight increase in current through the tube when the platinum was heated. In Figure 4d, however, the current was manually held constant. An additional check was made by filling the system with pure CO₂ and then with pure N₂. For a CO₂ fill having the same partial pressure as for the mixed fill, monitoring of the above CO Angstrom bands showed similar intensity decreases when the platinum was heated. For the pure fill of N₂, monitoring of the visible lines of N₂ showed no change upon heating the platinum.




Figure 4. Effect of Catalyst

SECTION III CONCLUSION

It thus appears that the gas compositions of sealed gas lasers with chemically active constituents may be substantially modified by the inclusion in the tube of catalysts. The catalyst and the reaction promoted may be chosen to bring the specie population balance nearer the optimal for the particular laser than might otherwise be possible in a sealed system. Such catalytic action of incidental or deliberate ingredients, such as nickel and H₂O (Reference 1) of CO₂ lasers may partially explain some of the often conflicting claims as to optimal gas percentages, flow rates, etc., that have characterized much of the CO₂ work reported in the literature.

REFERENCES

1. S. Beckman, J. Morrel, G. Egloff, 1946. Catalysis, Reinhold Publishing Co.
2. F. Harrigan, 1966. Raytheon Final Technical Report, Waltham, Mass., AD 637-023.
3. G. Herzberg, 1966. Molecular Spectra and Molecular Structure I, 2nd Ed., p. 35.
4. J. A. Howe, 1965. Appl. Phys. Letters 7, 12.
5. J. D. Rigden, G. Moeller, 1966. IEEE Journal of Quantum Electronics, Vol. QE-2, No. 9, 365.
6. W. J. Witteman, 1965. Phys. Letters 18, 125 - 127.
7. W. J. Witteman, 1966. Philips Research Repts., 21, 73 - 84.
8. W. J. Witteman, 1966. IEEE Journal of Quantum Electronics, Vol. QE-2, No. 9, 375.

UNCLASSIFIED

Security Classification

DOCUMENT CONTROL DATA - R&D		
<i>(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)</i>		
1. ORIGINATING ACTIVITY (Corporate author) Systems Research Laboratories, Inc. Dayton, Ohio and Air Force Avionics Laboratory, Wright-Patterson Air Force Base, Ohio		2a. REPORT SECURITY CLASSIFICATION Unclassified
		2b. GROUP
3. REPORT TITLE EFFECT OF A HEATED PLATINUM WIRE ON A SEALED CO ₂ LASER SYSTEM		
4. DESCRIPTIVE NOTES (Type of report and inclusive dates) Special Technical Report		
5. AUTHOR(S) (Last name, first name, initial) Taylor, F. M., and Lombardo, A., Systems Research Laboratories, Inc. Eppers, W. C., Air Force Avionics Laboratory, Wright-Patterson Air Force Base, Ohio		
6. REPORT DATE April 1968	7a. TOTAL NO. OF PAGES 16	7b. NO. OF REFS 8
8a. CONTRACT OR GRANT NO. F33615-67-C-1138	9a. ORIGINATOR'S REPORT NUMBER(S) SRL 11605 AFAL-TR-68-51	
b. PROJECT NO. 5237		
c. Task No. 5237-10		
d.	9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)	
10. AVAILABILITY/LIMITATION NOTICES This document has been approved for public release and sale; its distribution is unlimited.		
11. SUPPLEMENTARY NOTES	12. SPONSORING MILITARY ACTIVITY Air Force Avionics Laboratory Wright-Patterson Air Force Base, Ohio	
13. ABSTRACT A heated platinum wire was used in a sealed CO ₂ -N ₂ -He laser system, resulting in increases in output power that were dependent on the initial fill pressure of CO ₂ . The system was also filled with a CO ₂ -He mixture and made to lase. Heating of the platinum wire caused a decrease in output power. It was tentatively concluded that the platinum catalyzes the reaction CO + O → CO ₂ , permitting a higher concentration of CO ₂ in a sealed system than is otherwise possible.		

DD FORM 1473
1 JAN 64

UNCLASSIFIED

Security Classification

UNCLASSIFIED

Security Classification

14. KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
CO ₂ Laser						
Sealed CO ₂ Laser						
Catalytic Recombination of CO ₂						
Platinum Catalyzed Laser						

INSTRUCTIONS

1. **ORIGINATING ACTIVITY:** Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (*corporate author*) issuing the report.
- 2a. **REPORT SECURITY CLASSIFICATION:** Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.
- 2b. **GRCUP:** Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.
3. **REPORT TITLE:** Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.
4. **DESCRIPTIVE NOTES:** If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.
5. **AUTHOR(S):** Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.
6. **REPORT DATE:** Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.
- 7a. **TOTAL NUMBER OF PAGES:** The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.
- 7b. **NUMBER OF REFERENCES:** Enter the total number of references cited in the report.
- 8a. **CONTRACT OR GRANT NUMBER:** If appropriate, enter the applicable number of the contract or grant under which the report was written.
- 8b, 8c, & 8d. **PROJECT NUMBER:** Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.
- 9a. **ORIGINATOR'S REPORT NUMBER(S):** Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.
- 9b. **OTHER REPORT NUMBER(S):** If the report has been assigned any other report numbers (*either by the originator or by the sponsor*), also enter this number(s).
10. **AVAILABILITY/LIMITATION NOTICES:** Enter any limitations on further dissemination of the report, other than those

imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. **SUPPLEMENTARY NOTES:** Use for additional explanatory notes.

12. **SPONSORING MILITARY ACTIVITY:** Enter the name of the departmental project office or laboratory sponsoring (*paying for*) the research and development. Include address.

13. **ABSTRACT:** Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. **KEY WORDS:** Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.

UNCLASSIFIED

Security Classification