



JUNE 1968

DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION National Aviation Facilities Experimental Center Atlantic City, New Jersey 08405

WWY REAL PROPERTY AND A CONTRACT OF A CONTRACT OF

Reproduced by the CLEARINGHOUSE for Federal Scientific & Technical Information Springfield Va. 22151

"The Federal Aviation Administration is responsible for the promotion, regulation and safety of civil aviation and for the development and operation of a common system of air navigation and air traffic control facilities which provides for the safe and efficient use of airspace by both civil and military aircraft."

"The National Aviation Facilities Experimental Center maintains laboratories, facilities, skills and services to support FAA research, development and implementation programs through analysis, experimentation and evaluation of aviation concepts, procedures, systems and equipment."

FINAL REPORT

RECIPROCATING ENGINE AND EXHAUST VIBRATION AND TEMPERATURE LEVELS IN GENERAL AVIATION AIRCRAFT

PROJECT NO. 520-003-01X

REPORT NO. NA-68-27 (DS-68-8)

Prepared by: GERALD R. SLUSHER

for

AIRCRAFT DEVELOPMENT SERVICE

June 1968

This report is approved for unlimited availability. It does not necessarily reflect Federal Aviation Administration policy in all respects, and it does not, in itself, constitute a standard, specification, or regulation.

DEPARTMENT OF TRANSPORTATION Federal Aviation Administration National Aviation Facilities Experimental Center Atlantic City, New Jersey 08405

ABSTRACT

The engine and exhaust system vibration and exhaust gas and metal temperature levels were determined for flight and ground conditions on several single-engine aircraft for purposes of establishing exhaust system and heat exchanger design and test criteria. The temperature data were presented as a function of engine compression ratio and the vibration data were plotted against engine horsepower to foster the general utilization of the information.

Method of data presentation permits the estimation of exhaust gas temperatures for horizontally-opposed, reciprocating engines. Temperature measurements indicated uneven heating of the muffler outer wall (heat exchanger surface) reflecting uneven flow of the exhaust gases through and around the baffles and diffusers probably producing thermal stresses and contributing to failures. Baffles and diffusers within the mufflers of engines with compression ratios of 8.5:1 or higher are exposed to exhaust gas temperature levels under which standard construction materials (AISI 321 and AISI 347 stainless steels) become marginal with respect to high-temperature oxidation, carburization, and attack by lead compounds.

Vibration of general aviation aircraft engines was noted to increase with increased power rating and reached maximum intensities under takeoff conditions. The acceleration level of mufflers on engines of high power compared favorably with the MIL-STD-810A Vibration Test Specification for equipment mounted directly on aircraft engines. Recommended procedure for development of new exhaust system designs involved random vibration testing under operating thermal conditions.

TABLE OF CONTENTS

CONSULTANT,

Î

Same with the

A BUT COLLEGE TO MAN

_
Page

ABSTRACT	iii
INTRODUCTION	1
Purpose Background	1 1
DISCUSSION	2
Description of Equipment and Procedures General In-Flight Tests Ground Tests	2 2 3 3
Results and Analysis Exhaust Gas Temperatures Exhaust System Metal Temperatures Engine Vibration Intensity Muffler Vibration Intensity Power and Vibration Vibration Specification	6 8 8 14 20 20
CONCLUSIONS	27
RECOMMENDATIONS	28
REFERENCES	29
APPENDIX 1 Description of Instrumentation (4 pages)	1-1
APPENDIX 2 Basic Otto Engine Cycle Theory as Related to Exhaust Gas Temperature (6 pages)	2-1
APPENDIX 3 Engine Exhaust Cas and Metal Temperatures (8 pages)	3-1

v

LIST OF ILLUSTRATIONS

Figure		Page
1	Typical Temperature and Vibration Instrumentation, Engine and Exhaust System	4
2	Engine Stands, Ground Test	5
3	Engine Exhaust Gas Temperatures Within the Stack or Manifold Under Maximum Power Conditions	7
4	Engine Exhaust Gas Temperatures Within the Tailpipe Under Maximum Power Conditions	7
5	Stack Metal Temperatures Under Maximum Power Conditions	9
6	Manifold Metal Temperatures Under Maximum Power Conditions	9
7	Muffler Outer Wall Metal Temperatures Under Maximum Power Conditions	10
8	Tailpipe Metal Temperatures Under Maximum Power Conditions	10
9	History of Engine Broadband Vibration Intensity, Aircraft Code Model "B"	11
10	Vibration Wave Identification, Engine Crankshaft Speed 1306 RPM	13
11	Spectral Characteristics, Engine Vertical Vibration Intensity	15
12	Spectral Characteristics, Engine Lateral Vibration Intensity	16
13	Spectral Characteristics, Engine Longitudinal Vibration Intensity	17
14	Spectral Characteristics, Huffler Vertical Vibration Intensity, Separate Type Exhaust Systems	18
15	Spectral Characteristics, Muffler Vertical Vibration Intensity, Cantilevered Crossover Type Exhaust Systems	19

vii

LIST OF ILLUSTRATIONS (continued)

.

Figure		Page
16	Engine Vertical Acceleration Level Versus Horsepower	21
17	Engine Lateral Acceleration Level Versus Horsepower	22
18	Engine Longitudinal Acceleration Level Versus Horsepower	23
19	Muffler Vertical Acceleration Level Versus Engine Horsepower	24
20	MIL-STD-810A, Vibration Test Specification for Equipment Mounted Directly on Aircraft Engines	25
1.1	Instrumentation Location, Cross-Over Type Exhaust System	1-2
1.2	Instrumentation Location, Separate Type Exhaust System	1-3
2.1	Pressure-Volume Diagram, Otto Engine Cycle	2-2
3.1	Exhaust Gas and Metal Temperatures, Aircraft Code Model "A"	3-2
3.2	Exhaus: Gas and Metal Temperatures, Aircreft Code Model "B"	3∾3
3.3	Exhaust Gas and Metal Temperatures, Aircraft Code Model "C"	3-4
3.4	Exhaust Gas and Metal Temperatures, Aircraft Code Model "D"	3-5
3.5	Exhaust Gas and Metal Temperatures, Aircraft Code Model "E"	3-6
3.6	Exhaust Gas and Metal Temperatures, Aircraft Code Model "F"	3-7
3.7	Exhaust Gas and Metal Temperatures, Aircraft Code Model "G"	3-8

INTRODUCTION

Purpose

The purpose of this project was to measure and analyze the engine and exhaust system vibration and exhaust temperature levels in general aviation aircraft for use in establishing exhaust and heat exchanger design and test criteria in aircraft certification.

Background

The Federal Aviation Administration was angaged in a progress concerned with the safety and reliability of engine exhaust systems in light aircraft. The objectives of this program were: (a) to identify deficiencies in design and construction of engine exhaust systems which compromise safety through possible carbon menoxide poisoning, in-flight fire and power loss; (b) to develop an exhaust system qualification test and procedure suitable for use by manufacturers as a requirement for certification to enhance the reliability and integrity of these exhaust systems and to reduce the hazards associated with failures; (c) to investigate and develop cabin heaters designed to eliminate or minimize the carbon monoxide hazard; and (d) to evaluate low-cost carbon monoxide indicators to determine their performance and suitability for use in general aviation aircraft.

Published results of the program include technical reports listed under References 1, 2, and 3. The results reported here were directed toward identification of the operating environment.

The severe conditions under which engine exhaust systems and exhaust heat exchangers operate have been responsible for a large number of failures, some of which have resulted in fatal accidents. Malfunctions and defects in the exhaust system can create three separate hazards to flight safety: (a) fractures in the heat exchanger surface (muffler outer wall) may result in contamination of the cabin with exhaust gases containing carbon monoxide; (b) failed muffler baffles may restrict the exhaust gas path and effect engine power loss by creating excessive exhaust back pressure; and (c) when ruptured, the exhaust manifold or stacks may induce a fire hazard by failure to contain the exhaust flames.

The continual vibration upder corrosive and high-thermal operating conditions most likely will cause fatigue fractures, particularly following deterioration of the metal by carburization, high-temperature exidation, attack by isad compounds, and metallurgical phase changes. Accurate information concerning exhaust system vibration intensities and etheust temperature levels can be utilized as criteria by the designer the selection of the required material (alloy) and material thickness for a particular application. This information is also needed for realistic simulation of the operating conditions when evaluating exhaust assemblies on thermal-vibration test equipment. Accurate information concerning engine vibration intensities and exhaust temperature levels is also beneficial and valuable to the engine manufacturers for many purposes.

DISCUSSION

Description of Equipment and Procedures

General

The project endeavor was concerned with single-engine, two through six-place, general aviation sircraft incorporating exhaust gas-to-air heat exchangers. Aircraft powerplants were four or six-cylinder, horizontally-opposed, reciprocating engines ranging from 100 to 260 hp. Engine compression ratios varied from 6.75:1 to 8.6:1. The aircraft and engines were models manufactured in relatively large quantities by two light-aircraft companies and two engine companies, respectively. Aircraft and engine specifications are listed in Table I.

TABLE I

AIRCRAFT AND ENGINE INFORMATION

Aircraft Code <u>Model</u> A B C	Number of <u>Places</u>	Engine Rating (hp)	Number of <u>Cylinders</u>	Engine <u>Displacement</u> (cu in)	Engine Compression Ratio
A	4	250	6	540	8.5:1
B	6	260	6	470	8.6:1
с	4	180	4	360	8.5:1
D	4	145	6	300	7.0:1
E	2	100	4	200	7.0:1
r	2	108	4	235	6.75:1
C	4	160	4	320	8.5:1

The program consisted of two types of testing: (a) involving operating aircraft; and (b) testing on the ground involving aircraft engines and parts installed on engine stands.

The instrumentation for both types of testing was identical. The photograph of Figure 1 depicts typical engine and exhaust system instrumentation. A description of instrumentation is provided in Appendix 1.

Exhaust gas temperatures were measured within the stack or manifold and within the tailpipe. Metal temperatures were monitored at locations on the stack, manifold, tailpipe, and two places on the muffler outer wall (heat exchanger surface).

The engine vibration (required for testing exhaust systems) was measured (with accelerometers) in each of the three major axes of the engine at the exhaust flange locations or in proximity thereof. Vibration of the muffler or heat exchanger was recorded in the motionsensitive direction or in most instances the vertical axis with two accelerometers.

In-Flight Tests

Five aircraft were tested in flight to measure the vibration and the temperature levels of the engine and the exhaust system. Measurements were recorded during the takeoff, beginning at the start of the roll and ending at the altitude of 300 feet. Measurements were also recorded under stabilized engine speed conditions at altitudes of 4000 to 7000 feet. Transient measurements were recorded during changes of engine rpm under similar altitude conditions.

Ground Tests

Testing on the ground was accomplished on each of six engine installations mounted on stands, incorporating aircraft parts and configuration forward of the firewall, as shown in Figure 2. The engines were mounted on the a'rcraft vibration isolators and supported in cantilevered fashion from the firewall with the standard aircraft engine mount assembly.

Engine power was absorbed by the identical two-blade propellers as utilized in flight. The cowling and baffles were standard with the exception that the top cowling was modified for incorporation of air scoops to provide additional engine-cooling air from the flow induced by the propeller. Large oil coolers were placed in the propeller slip stream for cooling the engine oil as required for running the engines on the ground.



TYPICAL TEMPERATURE AND VIBRATION INSTRUMENTATION, ENGINE AND EXHAUST SYSTEM FIG. I



FIG. 2 ENGINE STANDS, GROUND TEST

Vibration measurements were recorded under both steady-state and transient conditions of engine speed. Inspection of the data revealed that the vibration waveform was composed of a large number of superimposed frequencies and a spectral analysis was performed for determination of vibration levels at discrete frequencies.

Information regarding the frequency and magnitude of acceleration was observed visually utilizing a vibration wave analyzer. The exhaust gas and metal temperatures were recorded from visual observations on a precision direct-reading potentiometer. A detailed description including the accuracy of the instrumentation systems is contained in Appendix 1.

Results and Analysis

Exhaust Gas Temperatures

Engine exhaust gas temperatures, measured within both the stack and tailpipe in various aircraft in flight and on the ground, were corrected to Standard Day conditions, and the corrected measurements at rated engine power were plotted against the engine compression ratio as depicted in Figures 3 and 4. Exhaust gas temperature is known to be a function of the fuel-to-air mixture and the engine compression ratio. The theory and the mathematical relationships concerning engine compression ratio as related to exhaust gas temperature are discussed in Appendix 2. Suffice to note here that the increase in exhaust gas temperature with compression ratio (Figures 3 and 4) reflects the heat of compression added when the gas was compressed to the higher pressures. The gas temperature information was prepared as a function of the engine compression ratio for presentation of the data in a form for generalized use. Maximum exhaust gas temperatures may be estimated for four-cycle, horizontally opposed, air-cooled engines when designed and constructed under present day state-of-the-art technology.

Exhaust gases within the stack, or downstream of the engine, approached temperature levels of 1600° F when engines with a compression ratio of 8.5:1 were operated at maximum power and lean fuel-to-air mixtures. When rich fuel-to-air mixtures were selected under similar conditions, the exhaust gas temperatures within the stack were reduced to somewhat less than 1500° F. Exhaust gases in the stacks or manifold of engines with a compression ratio of 7:1 and operated with lean mixtures were measured at temperature levels of 1480° F, and with rich mixtures, gas temperatures of 1380° F were indicated. The temperature of the exhaust gases in the tailpipe were 50 to 75° F less than the temperature of gases in the stack.

On a corrected basis and at maximum engine power, the exhaust gas temperature levels recorded on the ground were similar to the gas temperature levels recorded in flight. Exhaust gas temperature



FIG. 4 ENGINE EXHAUST GAS TEMPERATURES WITHIN THE TAILPIPE UNDER MAXIMUM POWER CONDITIONS ENGINE COMPRESSION RATIO

9:1

8:1

6:1

12001

THEORETICAL SLOPE

RICH MIXTURE

ৰৰ t

۱

١

T

T

as a function of engine crankshaft speed is presented in Appendix 3 for each aircraft in flight and engine installation on the ground.

Exhaust System Metal Temperatures

The metal temperatures of the stacks, manifolds, muffler wall, and tailpipe were corrected to Standard Day Conditions and were plotted as a function of the engine compression ratio in Figures 5 through 8. The spread in the data is in part attributed to the temperature extremes of rich and lean fuel-to-air mixtures. The stack metal temperatures were also affected by local variations of engine-cooling air existing between aircraft at the instrumented location. The deviations in metal temperatures of the muffler outer wall (heat exchanger surface), Figure 7, reflect the uneven flow of exhaust gases around and through the baffles and diffusers within the muffler, effecting uneven heating. Inspection of the thermal data in detail revealed general temperature variations of 300 to 400°F on specific mufflers. The problem of heat exchanger distortion and cracking has been aggravated by uneven flow and local overheating (Reference 1). Metal temperatures of 1200°F (maximum hot spot) were prevalent for exhaust systems of engines with a compression ratio of 8.5 to 1 when operated under maximum engine power. Exhaust systems of engines with a compression ratio of 7:1 operated at maximum temperatures of 1100°F. Metal temperatures were only slightly lower at downstream locations. Metal temperature measurements plotted as a function of engine crankshaft speed are included in Appendix 3.

Although metal temperatures of 1200°F maximum were measured on the outer surfaces of the exhaust system, the temperature of the baffles and diffusers inside the muffler were probably approaching the temperature of the gas. Since the baffles and diffusers are in contact with the exhaust gases and they are without the benefit of cooling, it was believed that their operating metal temperatures approximate 1500 to 1600°F on engines with a compression ratio of 3.5 to 1. Oxidation resistance of standard materials utilized in exhaust systems (AISI type 321 and type 347 stainless steels) become marginal for periods of extended operation at temperatures of 1500 to 1600°F. The standard material at these temperatures is subject to scaling and weight loss produced by severe oxidation and a combination of high-temperature carburization and attack by the products of combustion, particularly lead compounds. Type 310 (25 percent chromium 20 percent nickel) or Incoloy (21 percent chromium 34 percent nickel), with Incoloy perferred, was suggested for the parts that are exposed to high temperatures and the products of combustion (Reference 1).

Engine Vibration Intensity

Typical histories of broadband acceleration level and waveform for each of the three major axes of the engine are presented in Figure 9. Vibration intensity and waveform at maximum engine power is compared under conditions of: takeoff, in-flight, and ground test. A record of vibration under conditions of reduced engine power



ì.

ľ

FIG. 6 MANIFOLD METAL TEMPERATURES UNDER MAXIMUM POWER CONDITIONS



IG. 8 TAILPIPE METAL TEMPERATURES UNDER M POWER CONDITIONS





_

for ground test is included for reference. Examination of these records showed that the vibration wave was periodic; however, the wave was complex and composed of a large number of superimposed frequencies.

1

In operating aircraft, engine vibration levels were indicated highest during conditions of takeoff at maximum engine power. Vibration intensity at maximum power in flight between altitudes of 5000 to 7000 feet was indicated to be significantly less than the levels recorded during takeoff although vibration waveform was similar. This result was attributed to the engines developing less power under altitude conditions. Although they were not tested, supercharged engines develop high power and may effect high-vibration levels under altitude conditions. During ground test at high engine power, vibration levels were indicated to be somewhat higher than the levels recorded during takeoff; waveform was generally similar.

To identify the component parts of the engine vibration wave, the speed of the record was increased and the engine crankshaft speed was decreased. This expanded record is reproduced in Figure 10 with wave identification noted. The maximum excitation pulse occurred during combustion of the power stroke. Minor excitation occurred in phase with the opening and closing of the valves. The engine vibration wave was repeated in cycles of two rpm engine crapkshaft speed in phase with the events of the four-cycle engine. The vibration wave of each cylinder was phased in relation to the engine firing order. Thus the vibration of the cylinders at the exhaust flange location consisted of identical periodic, complex vibration waveforms, each out of phase with the other.

The complex wave with phase variance between cylinders effects a severe requirement for realistic vibration testing of engine exhaust systems. The simulation problem involves the use of a single vibration exciter with a rigid test fixture fastened to the exhaust flanges to support the exhaust system for vibration test. Random vibration testing may more closely simulate the actual conditions.

The following introductory paragraph on the definition or frequency spectrum was excerpted from Reference 4. "All signals can be thought of as existing in three dimensions. A sinewave is in reality an amplitude-time curve in the 'x-y' plane existing at some fixed point on the frequency axis 'z.' An examination or projection of the sinusoidal history on the amplitude-frequency 'x-z' plane would be a vertical line at the frequency 'f.' This is the true spectrum of a sinewave and can be viewed as the two-dimensional projection of the frequency parameters of a time-amplitude such a projection of the frequency parameters of a time-amplitude waveform is called a spectrum or frequency analysis."



FIG. 10 VIBRATION WAVE IDENTIFICATION, ENGINE CRANKSHAFT SPEED 1306 RPM

Characteristics of the engine vibration spectrum are illustrated in Figures 11, 12 and 13. These data were recorded from visual observations using a vibration wave analyzer incorporating tuneable one-third and onetenth octave filters. The one-third octave band divides each 10-to-1 tuning range into 10 bands. In each band, the ratio of the upper cutoff frequency to the lower cutoff frequency is 1.26 to 1. The narrow band (one-tenth octave) in effect divides the range into about three times as many bands. The bandwidths of the filters increase in cycles directly with the mean frequency of the band. Thus, as frequency increases, the bandwidth increases and acceleration amplitudes are indicated higher.

Waveform characteristics of engine vibration in the vertical axis were generally similar on each of five aircraft. Maximum acceleration amplitudes of the engines in the vertical axis were measured between 400 and 500 cps on each of four aircraft. The exact frequency is identified by the symbols denoting the center frequency of one-tenth octave filters, and is believed to be the natural frequency of the engine and mounting combination. Attention is called to the levels of acceleration measured with filters as opposed to the broadband levels. The indicated broadband vibration amplitudes were reduced significantly when the vibration signals were filtered.

Maximum acceleration of the engines in the lateral axis occurred between frequencies of 1300 to 1600 cps on five aircraft. The vibration was sensed in a direction parallel to both the piston and valve motion and the amplitude of acceleration was indicated higher. Further the natural frequency of the engine was increased significantly. Maximum acceleration levels of the engines in the longitudinal axis occurred between 1400 and 2000 cps. The high frequencies reflect the relative stiffness of the engine and mount assemblies in the longitudinal axis.

Huffler Vibration Intensity

Spectral characteristics of the muffler vertical vibration are depicted in Figure 14 for three separate or dual-type exhaust systems and in Figure 15 for two cantilevered crossover-type exhaust systems. Muffler vertical vibration of separate type exhaust systems reached a maximum acceleration level between 200 and 440 cps on each of three aircraft, the exact value depending on the particular configuration. Maximum acceleration amplitude was measured at approximately 10 g's rms on mufflers of engines developing 52.6 to 77 hp. Fourteen g's rms were indicated on a muffler of an engine developing 228 hp. A muffler of the cantilevered crossover-type exhaust system reached resonant conditions at a relative low frequency of 100 cps with a maximum rms acceleration of 15 g's. The engine was developing 214 hp when the data were recorded. Muffler vertical vibration levels, as measured with narrowband pass filters, were higher than the







.

16

.

LEGEND

▲ AVERAGE ACCELERATION - 1/3 OCTAVE FILTER
 ④ MAXIMUM ACCELERATION - 1/3 OCTAVE FILTER
 ④ AVERAGE ACCELERATION - 1/10 OCTAVE FILTER
 ■ MAXIMUM ACCELERATION - 1/10 OCTAVE FILTER









.

.

LEGEND

▲ AVERAGE ACCELERATION = 1/3 OCTAVE FILLER

MANIMUM ACCELERATION - 1/3 OCLAVE FULLER AVERAGE ACCELERATION - 1/10 OCLAVE FILLER 0 0

 \blacksquare -maximum acceleration = 1/16 octave filter

21			, c+	(1 \ F	ंग	Αŀ	1			Ţ	1-		_ A	T IRC	ĸА	E.I.	С() DF	т М		T El	ТС "С	L			Ľ	BR	OA OA	$\frac{1}{1}$	AN	D I	.E\	VE
1.5	5 - PC	98년) 98년 1997년	235 195	v Ri VEI	ΟP ΟP	ΕĐ		-		+	╉	┝	~	,	41 	 	131.1 	х R 	IGE I		F.N.,	, 	╀			+-,	8.2 8.5	2 G 5 G 1	'~` '_` ! !	A VI MA	ERC XIM L I	4U1 4U1	E M
10	>[-+-		+	┼┨		-			Ŧ	-			+	-+	-	-+	\downarrow	+	-	П				Ţ	F	1				\neg	
ę	5					Ļ					-			<u></u>	1					\ddagger		Ħ			<u> </u>		 	L					
			_ d	-	-	0			2		1	B			\$		9-1		de:	+		L		<u>Q</u> _		\$ - 7	ł		-4			-+	┝









corresponding engine vertical vibration levels. This increase was attributed to amplification effected by exhaust system resonance and probably excitation by the exhaust gas pressure pulsations.

Power and Vibration

Engine vibration intensity appeared to be a general function of the horsepower being developed at the time of observation as shown in Figures 16, 17 and 18. The illustrations show the broadband acceleration level, the maximum one-third octave band level, and the maximum one-tenth octave band level, all plotted against the horsepower developed by the various engines at the instant of data acquisition.

Narrowband vibration of engines in the vertical axis varied between 2 and 5 g's rms acceleration at 100 hp, while at 230 hp acceleration ranged from 5 to 9 g's rms. These data were maximum levels recorded with the center frequencies of one-tenth octave band filters tuned between 400 and 520 cps. The lateral acceleration level of engines developing 100 hp varied between 2 and 6 g's rms as measured with narrowband filters. Lateral vibration of engines developing 230 hp was indicated to be within limits of 5 to 12 g's rms. The data were recorded at maximum conditions observed with the filter center frequency tuned between 1300 and 1400 cps.

Considerable scatter of the data occurred when engine longitudinal acceleration was plotted as a function of horsepower. Factors such as resonance of the accelerometer mounting may have affected the results. The accelerometer was mounted on the flat of a special intake stud cap nut to sense longitudinal vibration.

Vibration Specification

Maximum acceleration amplitudes measured on the mufflers of seven aircraft were plotted regardless of design configuration in Figure 19 for purposes of forming a test specification. The top boundary of the envelope (one-tenth octave band pass filter) represents an indicated conventional vibration test specification wherein only one frequency exists at a given time, but wherein the frequency is varied progressively from the minimum to the maximum specified frequency.

When the rms levels were converted to peak acceleration, the indicated test specification compared favorably with the military standard for equipment mounted directly on aircraft engines (Figure 20). Test results indicated that the acceleration amplitudes and frequencies of MIL-STD-810A, Vibration Test Specification (Reference 5), were adequate for sinusoidal vibration testing of aircraft engine exhaust systems. Random vibration testing, however, is preferred, and broadband acceleration levels during vibration test should be comparable to those reported herein. It is suggested that the power spectral density relationships be shaped with peaks at the frequencies



















FIG. 20 MIL-STD-810A, VIBRATION TEST SPECIFICATION FOR EQUIPMENT MOUNTED DIRECTLY ON AIRCRAFT ENGINES

corresponding to the maximum measure. accelerations. For effective sinusoidal or random vibration testing, it is necessary that the exhaust system be heated to maximum operating temperatures as defined in this report.

Although the vibration excitation of the engine with respect to the exhaust system at the mounting flange locations was defined as a stationary process; i.e., its statistical properties do not change with time, random type vibration testing of engine exhaust systems was preferred only for the feature of testing under a continuum of frequencies. The engine excitation of the exhaust system consisted of periodic complex vibration waveforms; the waveforms, however, were out of phase at the exhaust mounting flanges as they were phased by the firing order of the engine. Since a rigid test fixture was required for mounting the exhaust systems on the vibration exciter, testing under broadband frequencies was believed to be more realistic than testing only under a single discrete frequency and varying that frequency from minimum to maximum.

CONCLUSIONS

Based upon the results of in-flight tests and ground tests reported herein on four-cycle, horizontally-opposed, air cooled engines, it is concluded that:

1. Engine exhaust gas temperatures may be estimated by utilizing the temperature data and the theoretical effects of compression ratio as presented in this report.

2. Baffles and diffusers within the mufflers of engines with high compression ratios on the order of 8.5:1 are probably operating under maximum temperatures (1500°F to 1600°F) that are marginal with respect to producing high temperature oxidation of currently used materials.

3. Maximum temperature of the exhaust system components exposed to cooling air on their outer surfaces was measured at levels of 1200°F and below. Rapid high temperature oxidation of the materials (AISI 321 and 347 stainless steels) from which these components were fabricated is not expected at this temperature level.

4. The observed wide variation in metal temperatures of the muffler outer walls reflect uneven heating. This can effect high thermal stresses that contribute to the initiation of crack type failures.

5. Increased horsepower tends to increase engine vibration intensity.

6. The engine vibration waveform is periodic but consists of a complex, continuous frequency spectrum with significant amplitudes in certain narrowband frequency limits.

7. The MIL-STD-810A, Vibration Test Specification, for equipment mounted directly on aircraft engines is appropriate for sinusoidal vibration testing of engine exhaust systems in the vertical axis or critical motion sensitive direction.

8. The complex engine vibration wave with phase variations between cylinders imposes a severe requirement for realistic vibration testing of exhaust systems. These conditions would be more closely simulated by random-type vibration testing as opposed to sinusoidal testing.

RECOMMENDATIONS

Based upon the results of the in-flight tests and ground tests reported herein, it is recommended that:

1. A material more resistant than AISI 321 and 347 stainless steels to high temperatures and the products of combustion be used for the muffler baffles and diffusers.

2. The thermal and vibration data be utilized for calculating the requirements of material and material thickness for engine exhaust system applications.

REFERENCES

- McCunn, T. H., <u>Metallurgical Evaluation of failed Aircraft</u> <u>Stainless Steel Exhaust System Components</u>, Federal Aviation Administration, Aircraft Development Service, Technical "report FAA-ADS-28. 1/65
- Slusher, G. R., <u>Analysis of Engine Exhaust System Failures</u> in General Aviation Aircraft, Federal Aviation Administration, Aircraft Development Service, Technical Report FAA-ADS-29. 9/64
- 3. Slusher, G. R., <u>Evaluation of Low-Cost Carbon Monexide</u> <u>Indicators</u>, Federal Aviation Administration, Aircraft Development Service, Technical Report FAA-ADS-80. 7/66
- Keller, A. C., <u>Considerations in the Analysis of Arbitrary</u> <u>Waveforms</u>, Spectral Dynamics Corporation of San Diego, California.
- 5. MIL-STD-810A, USAF, <u>Military Standard</u>, <u>Environmental Test</u> <u>Methods for Aerospace and Ground Equipment</u>.
- 6. Obert, Edward, F., <u>Thermodynamics</u>, McGraw-Hill Book Company, Inc.

APPENDIX 1

DESCRIPTION OF INSTRUMENTATION

Exhaust System Temperatures

Two types of chromel-alumel thermocouples were utilized for exhaust system temperature measurement. Metal-sheathed, ceramic-insulated thermocouples were immersed into the exhaust gas stream at the stack or manifold location and at the tailpipe location for measurement of the gas temperatures. Open tip thermocouples were installed either under metal clamps or welded to the surface for measurement of the exhaust system metal temperatures. Metal temperatures were monitored at locations on the stack, manifold, tailpipe, and two places on the muffler outer wall. Typical thermocouple locations are shown in Figures 1, 1.1 and 1.2 of this report.

The thermocouple signals or temperatures were recorded on an oscillograph when in flight; while on the ground, the temperatures were recorded manually from visual observations on a precision direct-reading potentiometer.

Accuracy of the temperature data reduced from the oscillograph records was $\pm 10^{\circ}$ F as calculated from reading accuracy. Temperature data were recorded to $\pm 5^{\circ}$ F reading accuracy utilizing the direct-reading potentiometer.

Engine and Exhaust System Vibration

Piezoelectric quartz accelerometers were utilized for engine exhaust system vibration measurement. The crystal transducers generate an electrical charge output signal proportional to the acceleration input. Basic sensitivity of these devices is "unit charge per unit acceleration" and is expressed as "picocoulombs per g (pCb/g)." A charge amplifer was required to convert the high-impedance charge output of the transducer to a low-impedance voltage current signal necessary for recording and display purposes.

The quartz accelerometers were selected for vibration measurement on the engines and exhaust systems because they feature high linearity up to temperatures of 500°F, and their high natural frequency permitted frequency response within 5 percent up to 8000 cps. Since accelerometer sensitivity was only one pCb/g, however, the accelerometers, amplifiers, cables and recording instruments were calibrated as systems on an electro-dynamic vibration test system.

Figures 1, 1.1 and 1.2 of this report shows the installation of typical vibration instrumentation on an engine and muffler. An accelerometer was installed on the head of a cap nut fabricated to fit the engine exhaust flange stud to measure the engine input vibration to the exhaust

LEGEND

- **ACCELERATION**
- EXHAUST GAS TOTAL TEMPERATURE

X METAL TEMPERATURE



FIG. 1.1 INSTRUMENTATION LOCATION, CROSS-OVER TYPE EXHAUST SYSTEM LEGEND

- **ACCELERATION**
- **0** EXHAUST GAS TOTAL TEMPERATURE





1-3

system in the vertical axis. Measurement of engine input vibration along the lateral axis was accomplished with an accelerometer installed on the head of a valve cover cap screw. Engine longitudinal vibration was monitored with an accelerometer installed on the flat of a special intake flange nut and stud. The accelerometer was positioned with the sensitive axis located 90° from the axis of the stud. Vibration was measured on both ends of the mufflers or heat exchangers with an accelerometer installed in the vertical axis.

The vibration signals were originally recorded on an oscillograph for analysis in the form of histories both in flight and on the ground. Because of high harmonic content, however, the ground data were also recorded from visual observations on a sound and vibration wave analyzer. The wave analyzer incorporated a tuneable one-third octave filter; for detail analysis, a tuneable one-tenth octave filter; and all-pass range for measurement of the total broadband signal. In addition, the vibration signals were recorded on magnetic tape for conventional spectral analysis.

APPENDIX 2

BASIC OTTO ENGINE CYCLE THEORY

AS RELATED TO EXHAUST GAS TEMPERATUPE

In the study of the factors influencing engine exhaust gas temperatures, a series of simplifying assumptions are made, the answers are calculated, and then compared with the observations. In this manner the important requirement for theory has been considered even though the calculations often produce quantitatively inaccurate results.

Four-cycle gasoline engine operation effects a cycle of pressure and temperature change on the gas which may be classified roughly as the Otto Cycle or constant volume cycle. A pressure-volume diagram for the Otto Engine Cycle is presented in Figure 2.1.

Assumptions.

- 1. Constant pressure intake.
- 2. Adiabatic compression.
- 3. Constant volume combustion.
- 4. Adiabatic expansion.
- 5. Constant volume pressure drop and rejection of gases and heat.
- 6. Constant pressure rejection of gases.



- 1-2 CONSTANT PRESSURE INTAKE
- 2-3 REVERSIBLE ADIABATIC COMPRESSION
- 3-4 REVERSIBLE CONSTANT VOLUME COMBUSTION
- 4-5 REVERSIBLE ADIABATIC EXPANSION
- 5-2 CONSTANT VOLUME REJECTION OF HEAT

2-1 CONSTANT PRESSURE EXHAUST

FIG. 2.1 PRESSURE-VOLUME DIAGRAM, OTTO ENGINE CYCLE

2-2

Definition of Equations and Symbols

```
P_v^k = C - equation for an adiabatic reaction
  = absolute pressure
P
  = specific volume
v
K = cp/cv = ratio of specific heats
С
   = constant
v_2/v_3 = r = compression ratio
     = volume before compression
v2
     = volume after compression
¥3
r
     = compression ratio
v_5/v_6 = e = expansion ratio
     = volume before expansion
ν4
     = volume after expansion
¥5
     = expansion ratio
e
PV = MRT = perfect gas law
M
    = mass of gas
   = ges constant
R
   = absolute temperature
Т
   = displacement
D
H
   = quantity of heat
   = heating value per lb. of charge
h
```

-section

Then:

$$\frac{v_2}{v_3} = r = compression ratio$$

and

 v_5 $v_6 = e = expansion ratio.$

For the Octo Cycle, e = r

A. For an adiabatic compression and expansion:

CompressionExpansion $P_3v_3^k = P_2v_2^k$ $P_4v_4^k = P_5v_5^k$ $\frac{P_3}{P_2} = r^k$ $\frac{P_4}{P_5} = e^k$ Perfect Gas Law $P_4v_4 = M R T_4$ $P_3v_3 = M R T_3$ $P_5v_5 = M R T_5$ $P_2v_2 = M R T_2$ $\frac{\Gamma_4}{T_5} = \frac{P_4}{P_5} \cdot \frac{1}{e} = e^{k-1}$ $\frac{T_3}{T_2} = \frac{P_3}{P_2} \cdot \frac{1}{r} = r^{k-1}$

and

Displacement = $D = v_2 - v_1$

and since $v_2 = r^{v_1}$

it follows that $v_1 = D$ $\overline{r} - 1$

B. Combustion temperature increase:

If H BTU's heat are added to "W" lbs. of gas:

H= ₩C_V △T

The amount of heat added is a function of the charge weight and:

 $\frac{H}{W}$ = h = Heating value (per lb. of charge)

Then:

$$\Delta T = \frac{h}{C_v}$$

The combustion temperature rise is calculated by dividing "h" heating value of the charge by " C_v " specific heat at constant volume. The combustion temperature rise is independent of the volume of the combustion chambers, of the amount of gas contained therein, and of the gas temperature and pressure of that gas.

At the start of the intake stroke, the clearance volume "v1" will be filled with exhaust gas which has no heating value. The mass of gas contained in "v2" cu. in. must be heated by (v_2-v_1) h where "h" is the heating value. If the temperature and pressure of the residual exhaust gas is also T₂ and P₂:

$$(v_2 - v_1) = v_2 cv \Delta T$$

 $\Delta T = \frac{v_2 v_1}{v_2} - \frac{h_2}{cv_2} = \frac{v_2 - v_1}{v_2} = \frac{h_0}{cv_0} = \frac{r - 1}{r} C$

 $\Delta T = \frac{r-1}{r} C$

The combustion temperature rise equals $\frac{r-1}{r}$ time a medium constant "C" where C = <u>Heating value</u> specific Heat

and:

$$T_5 = \frac{T_4}{r^{k-1}}$$

It was concluded that:

- a. The only engine factor having an influence on the combustion temperature and the exhaust gas temperature is the compression ratio.
- b. As far as the gas is concerned, only the heating value of the fuel and the specific heat influence the temperature rise; however, since they are generally constant under given condition, the fuelto-air mixture influences the temperature rise during combustion and ultimately the exhaust gas temperature.

c. Calculation of compression temperature rise from a compression ratio of 7.0:1 to 8.5:1.

$$T_3/T_2 = r^{k-1}$$

 $T_3 = r^{k-1} T_2$

 $\Delta T_3 = (T_{8.5} - T_{7.0}) = (r - \frac{k-1}{8.5} - r_{7.0}^{k-1}) T_2$

K = 1.392 at $800^{\circ}R$ average temperature $T_2 = 520^{\circ}R$ standard day $\Delta T_3 = (8.5 \ ^{1.392-1} \ _{-7.0} \ ^{1.392-1}) \ 520^{\circ}R$ $\Delta T_3 = 92^{\circ}F$

Test results agree with the theoretical change in compression temperature from a ratio of 7.0:1 to 8.5:1. The theoretical change in compression temperature was utilized for establishment of the curve slopes in Figures 3 and 4 of this report.

APPENDIX 3

ENGINE EXHAUST GAS AND METAL TEMPERATURES

Detail measurements of exhaust gas and metal temperatures were corrected to Standard Day conditions and plotted as a function of corrected engine crankshaft speed for five aircraft in light and for seven engine installations on the ground. Five illustrations (Figures 3.1, 3.2, 3.3, 3.5, and 3.7) compare exhaust gas and metal temperatures measured in flight with the identical temperatures as measured on the ground. The ground data include both rich and lean carburetor fuel-to-air mixtures. The exhaust gas and metal temperatures measured on the ground on two engine installations are presented in Figures 3.4 and 3.6 for both rich and lean carburetor fuel-to-air mixtures.

Operation of an engine-flight propeller combination on the ground, with the exception of constant speed-variable propeller pitch installations, is limited to an engine rotational speed less than maximum rated. In flight, the engine is unloaded somewhat by the ram airflow passing through the propeller and maximum rated speed is available. In addition, data recorded under conditions of ambient temperatures greater than 60°F corrects to engine speed levels less than those observed.

Because of these factors, it was necessary to extrapolate to maximum rated speed some of the curves plotted from data recorded on the ground. Since the plotted curves of the inflight data, in all cases, extended through rated speed conditions and since the ground data from constant speed engines (Figure 3.2) also plotted through rated conditions, the shape of the curves has been indicated. The extrapolations were accomplished by duplicating (familying) the shape of the curves in those cases where corrected data exists through conditions of maximum rated speed. In all occurrences, the continuous curve used to connect date points was broken and the extrapolation continued with dashed lines or curves.



FIG. 3.1 EXHAUST GAS AND METAL TEMPERATURES, AIRCRAFT CODE MODEL "A"



FIG. 3.2 EXHAUST GAS AND METAL TEMPERATURES, AIRCRAFT CODE MODEL "B"



FIG. 3.3 EXHAUST GAS AND METAL TEMPERATURES, AIRCRAFT CODE MODEL "G"



FIG. 3.4 EXHAUST GAS AND METAL TEMPERATURFS, AIRCRAFT CODE MODEL "D"



FIG. 3.5 EXHAUST GAS AND METAL TEMPERATURES, AIRCRAFT CODE MODEL "E"



FIG. 3.6 EXHAUST GAS AND METAL TEMPERATURES, AIRCRAFT CODE MODEL "F"



FIG. 3.7 EXHAUST (COMMETAL TEMPERATURES, AIRCRAFT CODE MODILIE) (19)