

1

l

Į

# CONFIDENCE INTERVALS FOR INDEPENDENT EXPONENTIAL SERIES SYSTEMS

by

GERALD J. LIEBERMAN and SHELDON M. ROSS

TECHNICAL REPORT NO. 130 AUGUST 1970

Supported by the Army, Navy and Air Force Under Contract N00014-67-A-0112-0052 (NR-042-002) with the Office of Naval Research

Gerald J. Lieberman, Project Director

Reproduction in Whole or in Part is Permitted for any purpose of the United States Government Distribution of this Document is Unlimited

> DEPARTMENT OF OPERATIONS RESEARCH and DEPARTMENT OF STATISTICS STANFORD UNIVERSITY STANFORD, CALIFORNIA



This document has been approved for public release and sale; its distribution is unlimited.

#### CONFIDENCE INTERVALS

#### FOR INDEPENDENT EXPONENTIAL SERIES SYSTEMS

by

Gerald J. Lieberman and Sheldon M. Ross

#### 1. Introduction and Summary

Suppose  $X_1, X_2, \ldots, X_n$  are independent identically distributed exponential random variables with parameter  $\lambda_1$ , i.e., the density function is given by

$$f_{X}(x) = \begin{cases} 0 , \text{ for } x < 0 \\ -\lambda_{1}x \\ \lambda_{1}e , \text{ for } x \ge 0 \end{cases}$$

Let  $Y_1, Y_2, \ldots, Y_m$  also be independent identically distributed exponential random variables but with parameter  $\lambda_2$ , and assume that the X's and Y's are independent. The problem is to estimate

$$R(t) = e^{-(\lambda_1 + \lambda_2)t}$$

The motivation behind this is that if one has a series system with two independent exponential components then R(t) represents the reliability of the system  $\epsilon$  time t, i.e., the probability that the system survives until time t.

In Section 2 we present some point estimates. In Section 3 we present a procedure for determining an exact  $(1-\alpha)$  level low-r  $-(\lambda_1+\lambda_2)t$ confidence bound for e . In doing so we also obtain an interesting characterization of the minimum of two independent gamma random variables. In Section 4 we compare our procedure with others presented in the literature. We show that our procedure always gives

1

smaller confidence intervals than the procedure presented by Kraemer [2] and that it dominates (in the sense of yielding stochastically smaller confidence intervals) a procedure due to Sarkar [4]. Other procedures are also considered. Section 5 is concerned with the same problem when the data is of a different form, including Type II censoring at r out of R. In the final section we point out that our results easily extend to the k-sample problem.

-S-E-C

Polisier -

E victorio - E

· Sumor

- united

2. Point Estimators

Since  $\overline{\mathbf{X}} = \sum_{i=1}^{n} \mathbf{X}_{i}/n$  and  $\overline{\mathbf{Y}} = \sum_{i=1}^{m} \mathbf{Y}_{i}/m$  are the "usual" estimators of  $1/\lambda_{1}$  and  $1/\lambda_{2}$  respectively, a "reasonable" estimator (the maximum likelihood estimator) or e is given by

(1) 
$$\exp\left\{-\left(\frac{\overline{X} \ \overline{Y}}{\overline{X}+\overline{Y}}\right)t\right\}.$$

Another possible point estimator is the unique minimum variance unbiased estimator (MVUE), which can be obtained as follows:

Letting

$$z = \begin{cases} 1, & \text{if } X_1 > t, Y_1 > t \\ 0, & \text{otherwise} \end{cases}$$

it follows that,

$$F(Z) = e^{-(\lambda_1 + \lambda_2)t}$$

i.e., Z is an unbrased estimator of  $e^{-(\lambda_1 + \lambda_2)t}$ . Now, since the joint statistic  $\left(\sum_{i=1}^n X_i, \sum_{i=1}^m Y_i\right)$  is both sufficient and complete, it follows from the Rao-Blackwell (also referred to as the Lehmann-

Scheffé) theorem that  $E\left(Z \middle| \sum_{i=1}^{n} X_{i}, \sum_{i=1}^{m} Y_{i}\right)$  is the unique MVUE. Now,  $E\left(Z \middle| \sum_{i=1}^{n} X_{i}, \sum_{i=1}^{m} Y_{i}\right) = P\left(X_{1} > t, Y_{1} > t \middle| \sum_{i=1}^{n} X_{i}, \sum_{i=1}^{m} Y_{i}\right)$   $(2) = \begin{cases} 0 , & \text{if } \sum_{i=1}^{n} X_{i} \leq t \text{ or } \sum_{i=1}^{m} Y_{i} \leq t \\ \left[\sum_{i=1}^{n} X_{i}^{-t}\right]^{n-1} \left[\sum_{i=1}^{m} Y_{i}^{-t}\right]^{m-1} , & \text{if } \sum_{i=1}^{n} X_{i} > t, \sum_{i=1}^{m} Y_{i} > t , \end{cases}$ 

where the last equation follows from the well known fact that given  $\sum_{i=1}^{n} X_{i}$ , then  $X_{i}$  is distributed as the smallest of (n-1) order statistics from a uniform distribution on  $\left(0, \sum_{i=1}^{n} X_{i}\right)$ . (A similar statement holds, of course, for the Y's.)

Thus, either (1) or (2) may be used as point estimators of  $-(\lambda_1+\lambda_2)t$ e . However, neither estimator is useful in obtaining a confidence interval for the reliability. This difficulty arises because the distributions of (1) and (2) depend on both  $\lambda_1$  and  $\lambda_2$  and not only on  $\lambda_1 + \lambda_2$ . In other words, a nuisance parameter would have to be eliminated. In the next section, we present a method  $-(\lambda_1+\lambda_2)t$  for obtaining an exact confidence interval for e

#### 3. Confidence Intervals

We shall use the notation

 $V \sim Gamma(\gamma,\beta)$ 

to indicate that the random variable V is distributed as a gamma

random variable with parameters  $\gamma$  and  $\beta$ , i.e., its density function is given by

ľ

Ľ

and the second sec

1

------

•••

4.

1.

...

-

-

-

ľ

$$f_{V}(v) = \begin{cases} \frac{\beta^{\gamma}}{\Gamma(\gamma)} v^{\gamma-1} e^{-\beta v}, & \text{for } v \ge 0\\ 0, & \text{, for } v < 0, \end{cases}$$

where  $\gamma, \beta > 0$ . Similarly, the notation

will indicate that the random variable V is distributed as a chisquare random variable with r degrees of freedom.

Now, let

$$U = \min\left(\sum_{i=1}^{n} X_{i}, \sum_{i=1}^{m} Y_{i}\right)$$

and let

$$K = \left\{ \text{largest } j \leq n; \quad \sum_{i=1}^{j} X_i \leq U \right\} + \left\{ \text{largest } j \leq m; \quad \sum_{i=1}^{j} Y_i \leq U \right\}$$

Note that

$$\min(m,n) \leq K \leq m + n - 1 .$$

We shall show that given K = k, then

$$U \sim Gamma (k, \lambda_1 + \lambda_2)$$
,

or equivalently, that given K = k, then

(3) 
$$2(\lambda_1 + \lambda_2) U \sim \chi^2_{2k}$$
.

Equation (3) enables us to determine an upper confidence bound for

 $\lambda_1 + \lambda_2$ , with confidence coefficient 1- $\alpha$ , namely

(4) 
$$x_{\alpha_{j}2k}^{2}/2U$$
,

where  $\chi^2_{\alpha_1 2k}$  is such that

and the state of the second second

$$P\{x_{2k}^2 > x_{\alpha;2k}^2\} = \alpha$$
.

From (4), we can easily obtain a lower confidence bound for  $R(t) = -(\lambda_1 + \lambda_2)t$ e , with confidence coefficient 1- $\alpha$ , namely

(5) 
$$\exp\{-x_{\alpha_{j}2k}^{2}t/2U\}$$

The remainder of this section will be devoted to showing that given  $K = k, U \sim Gamma$   $(k, \lambda_1 + \lambda_2)$ . To facilitate this we shall slightly change our notation and also make use of the equivalence between the partial sums of independent identically distributed exponential random variables and the Poisson process.

Let  $\{N_1(t), t \ge 0\}$  and  $\{N_2(t), t \ge 0\}$  be independent Poisson processes having respective rates  $\lambda_1$  and  $\lambda_2$ . Also, let  $N(t) = N_1(t) + N_2(t)$ . It follows from known results that  $\{N(t), t \ge 0\}$ is also a Poisson process but with rate  $\lambda_1 + \lambda_2$ . Now let  $T_i$  be the time between the (i-1)<sup>st</sup> and i<sup>th</sup> event in the N(t) process, and define

 $J_{i} = \begin{cases} 1 & \text{if the i}^{\text{th}} \text{ event in the } N(t) \text{ process comes from} \\ & \text{the } N_{1}(t) \text{ process,} \\ 2 & \text{if the i}^{\text{th}} \text{ event in the } N(t) \text{ process comes from} \\ & \text{the } N_{2}(t) \text{ process.} \end{cases}$ 

Finally, consider a new Poisson process  $\{N^*(t), t \ge 0\}$ , independent of the above, and having rate  $\lambda_1 + \lambda_2$ . Let  $T_1^*$  be the i<sup>th</sup>

5

interarrizal time for this process and let  $J_i^*$ , i = 1, 2, ... be an independent identically distributed sequence of random variables, independent of the above, and such that

Ĩ

No.

I

I

Ï

I

1

1

1

I

1

1

1

1

1

-

$$J_{1}^{*} = \begin{cases} 1 \text{ with probability } \frac{\lambda_{1}}{\lambda_{1} + \lambda_{2}}, \\\\ 2 \text{ with probability } \frac{\lambda_{2}}{\lambda_{1} + \lambda_{2}}. \end{cases}$$

<u>Theorem 1</u>: The two stochastic processes  $\{(T_i, J_i), i \ge 1\}$  and  $\{(T_i^*, J_i^*), i \ge 1\}$  have the same probability law.

# Proof:

The theorem will be proven by using induction to show that

$$P\{T_{1} \leq a_{1}, J_{1} = j_{1}, T_{2} \leq a_{2}, J_{2} = j_{2}, \dots, T_{n} \leq a_{n}, J_{n} = j_{n}\}$$
$$= P\{T_{1}^{*} \leq a_{1}, J_{1}^{*} = j_{1}, T_{2}^{*} \leq a_{2}, J_{2}^{*} = j_{2}, \dots, T_{n}^{*} \leq a_{n}, J_{n}^{*} = j_{n}\}$$

Let

$$j_{c} = \begin{cases} 2 & \text{if } j = 1, \\ 1 & \text{if } j = 2. \end{cases}$$

Now,

(6) 
$$P\{T_{1} \leq a, J_{1} = J\} = \int_{0}^{\infty} P\{T_{1} \leq a, J_{1} = J | Y_{1} = y\}\lambda_{j_{c}} e^{-\lambda_{j_{c}} J_{c}} dy$$
,

where  $Y_1$  is defined to be the first interarrival time of the process  $\{N_{j_n}(t), t \ge 0\}$ . Hence,

$$P\{T_{1} \leq a, J_{1} = j\} = \int_{0}^{a} (1 - e^{-\lambda_{j}y})\lambda_{j}e^{-\lambda_{j}c} dy$$
$$+ \int_{a}^{\infty} (1 - e^{-\lambda_{j}a})\lambda_{j}e^{-\lambda_{j}c} dy$$
$$= \frac{\lambda_{j}}{\lambda_{1} + \lambda_{2}} (1 - e^{-(\lambda_{1} + \lambda_{2})a})$$
$$= P\{T_{1}^{*} \leq a, J_{1}^{*} = j\} .$$

(7)

Note that the last equality follows since  $T_1^*$  is just the time of the first event of a Poisson process with rate  $\lambda_1 + \lambda_2$  and  $J_1^*$  is j with probability  $\frac{\lambda_j}{\lambda_1 + \lambda_2}$  (independently of anything else). Now by (7) we have that

$$P\{T_{1} \leq a_{1}, J_{1} = j_{1}, \dots, T_{n} \leq a_{n}, J_{n} = j_{n}\}$$

$$= \int_{0}^{a_{1}} P\{T_{2} \leq a_{2}, J_{2} = j_{2}, \dots, T_{n} \leq a_{n}, J_{n} = j_{n} | T_{1} = a, J_{1} = j_{1}\} \times \int_{a_{1}}^{a_{1}} \int_{a_{1}}^{a_$$

However, by the lack of memory of the Poisson Process it follows that at time  $T_1$  (which is the first time that an event from either  $N_1$  or  $N_2$  occurs) both the processes  $\{N_1(t), t \ge 0\}$  and  $\{N_2(t), t \ge 0\}$ ...start over again, and hence (8) equals

$$\int_{0}^{a} P\{T_{1} \leq a_{2}, J_{1} = j_{2}, \dots, T_{n-1} \leq a_{n}, J_{n-1} = j_{n}\}\lambda_{j_{1}} e^{-(\lambda_{1}+\lambda_{2})a} da$$

which by our induction hypothesis equals

7

$$\int_{0}^{a_{1}} P(T_{1}^{*} \leq a_{2}, J_{1}^{*} = J_{2}, \dots, T_{n-1}^{*} \leq a_{n}, J_{n-1}^{*} = J_{n}^{j}\lambda_{j_{1}}e^{-(\lambda_{1}^{+}\lambda_{2}^{})a_{d}}da$$

$$= \int_{0}^{a_{1}} \frac{n-1}{i=1} \left[ (1-e^{-(\lambda_{1}^{+}\lambda_{2}^{})a_{i+1}) \left(\frac{\lambda_{j_{i+1}}}{(\lambda_{1}^{+}\lambda_{2}^{})}\right) \right] \lambda_{j_{1}}e^{-(\lambda_{1}^{+}\lambda_{2}^{})a_{d}}da$$

$$= \frac{n}{i=1} \frac{\lambda_{j_{1}}}{\lambda_{1}^{+}+\lambda_{2}} (1-e^{-(\lambda_{1}^{+}\lambda_{2}^{})a_{i}})$$

$$= P(T_{1}^{*} \leq a_{1}, J_{1}^{*} = J_{1}, \dots, T_{n}^{*} \leq a_{n}, J_{n}^{*} = J_{n}^{j}) .$$

ľ.

Ľ

ľ

Ľ

Ī.

ľ

I

Principal P

E linder a

I

ľ

ľ

I

Torrest a

## Q.E.D.

Now consider the first event in the N(t) process such that to the left of (and including) that event there are either n events having their J's equal 1 or m events having their J's equal 2. Suppose this is the K<sup>th</sup> event and let  $U = T_1 + \cdots + T_K$  denote the time of this event (Note that these are the same K and U as were defined at the beginning of this section.)

<u>Theorem 2</u>: Given K = k, U has a gamma distribution with parameters k and  $2 - k_1 + k_2$ . That is, its conditional density is given by

$$f_{U|K=k}(u) = \frac{\lambda^{k}}{(k-1)!} u^{k-1} e^{-\lambda u}$$

# Proof

Define K\* and U\* in an equivalent manner for the N\*(t) process. Since the values  $J_i$  are determined completely at random for the N\* process the result follows for U\* and K\*. The result must then follow for U and K by Theorem 1.

Q.E.D.

Corollary 3: Let  $X \sim \text{Gamma } (n,\lambda_1)$  and  $Y \sim \text{Gamma } (m,\lambda_2)$ , where the X's and Y's are independent. Then

min (X,Y) ~ Gamma (K,
$$\lambda_1 + \lambda_2$$
)

where

$$P\{K = k\} = {\binom{k-1}{n-1}} \left(\frac{\lambda_1}{\lambda_1 + \lambda_2}\right)^n \left(\frac{\lambda_2}{\lambda_1 + \lambda_2}\right)^{k-n} + {\binom{k-1}{m-1}} \left(\frac{\lambda_1}{\lambda_1 + \lambda_2}\right)^{k-m} \left(\frac{\lambda_2}{\lambda_1 + \lambda_2}\right)^m$$
for min (m,n) < k < m + n - 1.

The correct way of interpreting Corollary 3 is that conditional on K = k, min(X,Y) ~ Gamma  $(k,\lambda_1 + \lambda_2)$ ; i.e., letting  $\Gamma_{k,\lambda}(a)$  be the probability that a gamma random variable with parameters  $(k,\lambda)$ is greater than a, then

$$P\{\min(X,Y) > a\} = \sum_{k=\min(m,n)}^{m+n-1} \Gamma_{k,\lambda_1+\lambda_2}(a)P\{K = k\}.$$

Proof:

The proof is immediate.

# 4. Comparison with Other Procedures

Sarkar [4] considered the case m = n and obtained an exact confidence bound for  $\lambda_1 + \lambda_2$  (and hence for e  $\begin{pmatrix} -\ell & 1 \\ 1 \end{pmatrix}$ ) by the following method. He defined  $Z_i = \min(X_i, Y_i)$ ,  $i = 1, \ldots, n$ , and based his confidence bound on the fact that the  $Z_i$  are independent identically distributed exponential random variables with mean  $1/(\lambda_1 + \lambda_2)$ . Hence,  $\sum_{i=1}^{n} Z_i \sim \text{Gamma } (n, \lambda_1 + \lambda_2)$ . His upper confidence bound for  $\lambda_1 + \lambda_2$ , with confidence coefficient  $1-\alpha$ , is thus

$$x_{\alpha_j 2n}^2 / 2 \sum_{l}^{n} z_l$$
.

The weakness of Sarkar's procedure is that he is throwing away a good deal of information. For instance, if  $X_1 < Y_1$  then he only uses  $X_1$  and makes no use of  $Y_1$ . However, given that  $X_1 < Y_1$  it follows (by the lack of memory of the exponential) that the excess,  $Y_1 - X_1$ , is exponentially distributed with mean  $1/\lambda_2$ . Hence by using the "excesses" one can generate more X's and Y's. This is equivalent to what the procedure of Section 3 does. Let us illustrate by an example.

<u>Example</u>: Independent random samples of size 4 are obtained on each of two components, X and Y. Assume that the X's are exponentially distributed with parameter  $\lambda_1$  and the Y's are exponentially distributed with parameter  $\lambda_2$ . Suppose the data are as follows:

> $(x_1, x_2, x_3, x_4) = (2, 7.1, 6, 3)$  $(x_1, x_2, x_3, x_4) = (5, 4, 2, 3.1)$ .

Sarkar would thus generate a random sample of size 4, namely, (2,4,2,3) from an exponential distribution having mean  $1/(\lambda_1 + \lambda_2)$ . Our procedure (described in Section 3) is equivalent to the following: Determine the minimum of  $X_1$  and  $Y_1$ , thereby obtaining the value of 2. However, note that the excess,  $Y_1 - X_1 = 3$ , yields another Y data point. Hence, after generating the value 2 we are left with the "random samples"

X: 7.1, 6, 3
Y: 3, 4, 2, 3.1.

Again, we determine the minimum of the first X and the first Y, i.e., min(7.1,3) = 3, thereby obtaining the "outcome" 3 and note that the excess, 7.1 - 3 = 4.1, yields another X data point. Having generated the value 3, we are left with the "random samples"

We determine the minimum of the first X and the first Y, i.e., min (4.1,4) = 4, thereby obtaining the "outcome" 4 and note that the excess, 4.1 - 4 = 0.1, yields another X point. Having generated the value 4, we are left with the "random samples"

The minimum of the first X and the first Y is 0.1, thereby obtaining the "outcome" 0.1. The excess, 2 - 0.1 = 1.9, yields another Y point. Having generated the value 0.1, we are left with the "random samples"

```
X: 6, 3Y: 1.9, 3.1.
```

Since  $\min(6,1.9) = 1.9$ , we obtain the "outcome" 1.9, and the excess of 4.1 yields another X point. Having generated the value 1.9, we are left with the "random samples"

> X: 4.1, 3 Y: 3.1

Since  $\min(4.1,3.1) = 3.1$ , we obtain the "outcome" 3.1, and the excess of 1 yields another X point. Having generated the value 3.1, we are left with the "random samples"

ŀ

Υ:

Since there are no more Y data points we must stop the procedure. If we treat the "outcomes" as the outcomes of a random sample of size 6 - namely 2, 3, 4, 0.1, 1.9, 3.1 - from an exponential distribution with mean  $1/(\lambda_1 + \lambda_2)$ , then the sum should behave as a gamma distributed random variable with parameters 6 and  $\lambda_1 + \lambda_2$ . However, note that the sum is just the random variable  $U = \min\left(\sum_{i=1}^{n} X_i, \sum_{i=1}^{m} Y_i\right)$ defined in Section 3, and 6 is just the value taken on by the random variable K also defined in Section 3. From the results of Section 5 these generated values can then, in fact, be considered as the outcomes of a random sample from an exponential distribution with mean  $1/(\lambda_1 + \lambda_2)$ . As indicated earlier our confidence bound would be arrived at by using the fact that  $U \sim \text{Jamma}(K = 6, \lambda_1 + \lambda_2)$ . Hence, our proreduce yields stochastically smaller confidence intervals than does Sarkar's since we are generating a larger random sample (i.e.,  $n \leq E \leq (n-1)$ .

The above example also points out some of the weaknesses of our procedure. First, since we had no Y points to compare them with, we had to throw out the final two X points. Also K, the number of data points used, is a function of the ordering of the X's and Y's. Thus, for instance, random samples  $(X_1, X_2, X_3)$ ,  $(Y_1, Y_2, Y_3)$  might produce a different value of K than would random samples  $(X_2, X_1, X_3), (Y_2, Y_1, Y_3).$ 

Another procedure is the one due to Kraemer [2]. Kraemer uses the fact that  $\sum_{1}^{n} X_{i} \sim \text{Gamma}(n,\lambda_{1})$  (or equivalently that  $2\lambda_{1}\sum_{1}^{n} X_{i} \sim X_{2n}^{2}$ ) and  $\sum_{1}^{m} Y_{i} \sim \text{Gamma}(m,\lambda_{2})$ . Thus, since the X's and Y's are independent it follows that

$$2\left[\lambda_{1}\sum_{1}^{n} X_{i} + \lambda_{2}\sum_{1}^{m} Y_{i}\right] \sim X_{2(n+m)}^{2}$$

Again, letting  $U = \min \left( \sum_{i=1}^{n} X_{i}, \sum_{i=1}^{m} Y_{i} \right)$  we have that

$$2(\lambda_1 + \lambda_2) \mathbf{U} \leq 2 \left[ \lambda_1 \sum_{i=1}^{n} \mathbf{x}_i + \lambda_2 \sum_{i=1}^{m} \mathbf{x}_i \right] .$$

However,  $2\left[\lambda_{1}\sum_{1}^{n} x_{1} + \lambda_{2}\sum_{1}^{m} Y_{1}\right] \sim \chi^{2}_{2(n+m)}$  so that an upper confidence bound for  $\lambda_{1} + \lambda_{2}$ , with confidence coefficient at least 1- $\alpha$ , is given by

(9) 
$$x_{\alpha_{j}^{2}(n+m)}^{2}/2U$$
.

Equation (9) expresses the confidence bound for Kraemer's procedure. However, our procedure (equation (4)) yields a smaller confidence interval since K < 2(n+m). This is intuitively clear since Kramer bases her estimate on U and gets a bound on its distribution while we base our estimate on both U and K and use the exact joint distribution of U and K.

Another procedure has been suggested by Lentner and Buehler [3].

Their procedure is based on the fact that given  $\sum_{i=1}^{n} X_{i} - \sum_{i=1}^{m} Y_{i}$ , then the distribution of  $\sum_{i=1}^{n} X_{i}$  depends on  $\lambda_{1}$  and  $\lambda_{2}$  only through  $\lambda_{1} + \lambda_{2}$ . They then use the Lehmann-Scheffe theory to obtain a conditional (on  $\sum_{i=1}^{n} X_{i} - \sum_{i=1}^{m} Y_{i}$ ) uniformly most powerful unbiased test for the hypothesis  $\lambda_{1} + \lambda_{2} = c$ . By inverting this test they obtain an upper confidence bound for  $\lambda_{1} + \lambda_{2}$ , with confidence coefficient  $1-\alpha$ .

Since the conditional distribution  $\sum_{i=1}^{n} X_{i}$  given  $\sum_{i=1}^{n} X_{i} - \sum_{i=1}^{m} Y_{i}$  is somewhat complicated it is not theoretically clear how good the Lentner-Beuhler procedure is. It should also be pointed out that their methods are computationally difficult.

Other relevant literature that should be mentioned is a procedure given by Grubbs [1] which obtains fiducial intervals for the reliability.

Another possible approach to the problem would be to assume prior distributions on  $\lambda_1$  and  $\lambda_2$ . It would then be straightforward to obtain the posterior distribution of  $\lambda_1 + \lambda_2$  and Bayesian probability intervals can then be obtained.

T

) •

## 5 Other Sampling Schemes

A common type of sampling used in proctice is type II censoring at r out of R  $(r \leq R)$  Type II censoring at r out of R refers to the situation where R itoms are tested simultaneously and the test is terminated when the first r out of R have failed. The time of failure of each item is recorded. This corresponds to recording the order statistics, i.e.,  $X_{(1)}, X_{(2)}, \dots, X_{(r)}$ . In the notation of this paper put N units of the first component (X) on test and terminate the test when the n<sup>th</sup> failure occurs. Similarly put M units of the second component (Y) on test and terminate the test when the m<sup>th</sup> failure occurs. Let  $X_{(i)}$  and  $Y_{(j)}$  be the respective order statistics (i = 1,2, ..., n and j = 1,2, ..., m). Denote by

$$\delta_{i} = (n-i+1)(X_{(i)} - X_{(i-1)}), i = 1, 2, ..., n (X_{(0)} = 0)$$

and

$$\tau_{j} = (m-j+1)(Y_{(j)} - Y_{(j-1)}), \quad j = 1, 2, ..., m \quad (Y_{(0)} \equiv 0) .$$

It is well known that the 5's and  $\tau$ 's are independent and identically distributed random variables with respective parameters  $\lambda_1$ and  $\lambda_2$ . Hence, the procedure of Section 3 is applicable.

Another type of sampling can be described as follows. For the first component (X) put one item on test. When it fails replace it. When this second item fails replace it. A similar procedure is followed for the second component (Y). Terminate the test when there have been either n failures of component 1 (X's) or m failures of component 2 (Y's). Follow the techniques outlined in  $-(\lambda_1 + \lambda_2)t$ . Note that in this case our procedure uses all the available information. The data can be represented by  $X_1, \dots, X_r$  and  $Y_1, \dots, Y_s$  where either r = n or s = m. Consider the case r = n, then the likelihood is given by

$$L(x_1, \ldots, x_n, y_1, \ldots, y_s) = e^{-\lambda_2 \left(\sum_{i=1}^n x_i - \sum_{i=1}^s y_i\right)} \left(\frac{n}{\prod_{i=1}^n \lambda_1 e^{-\lambda_1 x_i}}\right) \left(\frac{s}{\prod_{i=1}^n \lambda_2 e^{-\lambda_2 y_i}}\right),$$

where the first term arises since the next y value - namely  $y_{s+1}$  must be greater than  $\sum_{i=1}^{n} x_i - \sum_{i=1}^{s} y_i$ . Hence, I.

ľ

ľ

-----

i unitere i

.

4.

• •

• •

• •

• •

1

1

1

1

n

Letting  $\lambda = \lambda_1 + \lambda_2$  and  $\theta = \lambda_1$  we have

$$L(x_1, \ldots, x_n, y_1, \ldots, y_s) = \theta^n (\lambda - \theta)^s e^{-\lambda \sum_{i=1}^{n} x_i}$$

or

$$\log L(x_1, \ldots, x_n, y_1, \ldots, y_s) = n \log \theta + s \log (\lambda - \theta) - \lambda \sum_{i=1}^{n} x_i$$

Taking the partial derivatives and setting them equal to zero leads to

$$\frac{\partial}{\partial \lambda} \log L = \frac{s}{\lambda - \theta} - \sum_{l}^{n} x_{l} = 0$$

and

$$\frac{\partial}{\partial \theta} \log L = \frac{n}{\theta} - \frac{s}{\lambda - \theta} = 0 .$$

Solving these equations simultaneously results in the maximum likelihood estimate  $\stackrel{\Lambda}{\lambda}$  of  $\lambda$ , i.e.,

$$\lambda = \frac{s + n}{\sum_{i=1}^{n} x_{i}} \cdot$$

Also, in the case where s = m we have that

$$\hat{\lambda} = \frac{r + m}{\sum_{i=1}^{m} y_{i}}$$

16

Hence, in either case we arrive at  $\frac{A}{\lambda} = \frac{K}{U}$  where U and K are as given in Section 3.

# 6. Final Remarks

Port & was

PW THEOLOGIC PARTY

The results easily extend to a system consisting of C independent components connected in series. In this case U is defined as

$$U = \min \begin{bmatrix} n_{1} & n_{2} \\ \sum_{i=1}^{n} (X_{1i}), \sum_{i=1}^{n} (X_{2i}), \dots, \sum_{i=1}^{n_{C}} (X_{Ci}) \end{bmatrix}$$

and K is given by

$$K = \left\{ \text{largest } j \leq n_1: \quad \sum_{i=1}^{j} X_{ii} \leq U \right\} + \cdots + \left\{ \text{largest } j \leq n_C: \quad \sum_{i=1}^{j} X_{Ci} \leq U \right\}$$

It can be easily shown that

$$U \sim Gamma (K, \lambda_1 + \lambda_2 + \cdots + \lambda_c)$$
,

so that a confidence bound on  $\lambda_1 + \lambda_2 + \cdots + \lambda_C$  is obtainable.

#### REFERENCES

L

l.

Ł

Ł

- [1] Grubbs, F., "Approximate Fiducial Bounds for the Reliability of a Series System for Which Each Component Has an Exponential Time-To-Fail Distribution," unpublished paper.
- [2] Kraemer, H. C., "One-Sided Confidence Intervals for the Quality Indices of a Complex Item," <u>Technometric</u>, 5, 400-403 (1963).
- [3] Lentner, M. M., and Buehler, R. J., "Some Inferences about Gamma Parameters with an Application to a Reliability Problem," <u>Journal of the American Statistical Association</u>, 58, 670-677 (1963).
- [4] Sarkar, T. K., "An Exact Lower Confidence Bound for the Reliability of a Series System when Each Component Has an Exponential Time to Failure Distribution," Technical Report No. 117, Department of Operations Research and Department of Statistics, Stanford University (March 5, 1969).

· .					
UNCLASSIFIED			8		
Security Classification					
DOCUMENT C	ONTROL DATA - RAD		the emptition of a localitical		
(Security electrification of little, body of abolitati and inde	ting annotorian must be amore	Se. REPORT SECURITY & LASSIFICATION			
Dept. of Operations Research		Unclassified			
Stanford University	24	SROU			
Stanford, California					
Confidence Intervals for Independent E	cponential Series S	Syste	ms		
4. DESCRIPTIVE NOTES (Type of report and inclusive dense) Machanical Report					
AUTHOR(2) (Leet name, first name, initial)					
Lieberman, Gerald J. and Ross, Sheldon	м.				
- REPORT DATE	74. TOTAL NO. OF PAGE	8	75. NO. OF REFS		
August 1970	18		4		
A. CONTRACT OR GRANT NO. NO0014-67-A-0112-0052 A. PROJECT NO.	Se enicinator's report Numser() Technical Report No. 130				
NR-042-002					
•	hie report	V (ANY			
e.					
S. AVAILABILITY/LIMITATION NOTICES					
Distribution of this document is unlimit	ited.		2		
11. SUPPLEMENTARY NOTES	12. SPONSORING MILITARY ACTIVITY Logistics & Math. Statistics Branch Office of Naval Research Washington, D. C. 20360				
Suppose $X_1, X_2, \dots, X_n^{f_1}$ are independent	dent identically d	listr:	la fela 20 ibuted exponential		
random variables with parameter $\lambda_1$ .	et $Y_1, Y_2, \ldots, Y_m$	also	be independent iden-		
tically distributed exponential random that X's and Y's are independent.	variables with par The problem is to	esti	er $\lambda_2$ , and assume nate		
·	$(\lambda_1 + \lambda_2)^{\dagger}$				
The motivation behind this is that if $c$ exponential components then $R(t)$ repr time ., i.e., the probability that th	ne has a series sy esents the reliabi e system survives	tem u lity until	with two independent of the system at L time t.		
A procedure for determining an exa for R(t) is presented. In doing so a minimum of two independent gamma random procedure is then compared with others	ect $(1-\alpha)$ level 1 n interesting char variables is obta presented in the 1	ower acter ined.	confidence bound rization of the The suggested ature.		
Plane to Cartan	$\left( - \left( f - \right) \right) \right)$	+	(= (= ), <b>t</b> ) >		
KUT		1.01	,		
D					
	<u> </u>	Ree	UNCLASSIFIED		

l

I

And an an angle of

1 comments

-----

-----

Independent
 Independent
 Independent
 Independent
 Independent
 Independent

finneren erne enskel enskel

が日本には

A STATES AND A STATE

UNCLASSIFIED

14 KEY WORDS	LINKA		LINK D		LINKC		
	KEY WORDS	NOLE	#7	NOLE	WT	ROLE	WT
Reliability Series systems Exponential							
						[ [	

#### INSTRUCTIONS

1. ORIGINATING ACTIVITY: Enter the name and eddress of the contractor, subcontractor, grantee, Department of Defense activity or other organization (corporate author) issuing the report.

2a. REPORT SECURITY CLASSIFICATION: Enter the everall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in secondance with appropriate security regulations.

25. GROUP: Automatic dewngrading is specified in DoD Directive 5200, 10 and Armed Perces Industrial Manual. Enter. the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

J. REPORT TITLE: Enter the complete report title in all capital letters. Titles in all cases should be uncleasified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. DESCRIPTIVE NOTES if appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

S. AUTHOR(S): Enter the name(a) of author(s) as shown on or in the report. Enter last name, first name, middle initia'. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. REPORT DATE: Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.

7a. TOTAL NUMBER OF PAGES: The total page count should follow normal pegination procedures, i.e., enter the number of pages containing information.

76. NUMBER OF REFERENCES Enter the total number of references cited in the report.

Sa. CONTRACT OR GRANT NUMBER: If appropriate, enter the applicable number of the contract or grant under which the report was written.

86, 8c, 6 8d. PROJECT NUMBER: Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9e. ORIGINATOR'S REPORT NUMBER(S): Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. OTHER REPORT NUMBER(5): If the report has been ausigned any other report numbers (either by the originator or by the sponsor), also enter this number(s).

10. AVAILABILITY/LIMITATION NOTICES Enter any limitations on further dissemination of the report, other than those

imposed by security classification, using standard statements such as:

I

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Persign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain capies of this report directly from DDC. Other qualified DDC users shall request through
- (4) "U. 6. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fast and enter the price, if known.

11. SUPPLEMENTARY NOTES: Use for additional explanatory notes.

12. SPONSORING MILITARY ACTIVITY: Enter the name of the departmental project office or laboratory sponsoring (paying for) the research and development. Include address.

13. ABSTRACT: Enter an abstract giving a brief and factual summery of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall and with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However. the suggested length is from 150 to 225 words.

14. KEY WORDS: Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that as security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, reles, and weights is optional.

UNCLASSIFIED

Security Classification