

AD 726905

AD

RE-71-1

**LOW-TEMPERATURE LUBRICANTS  
FOR THE M134 AIRCRAFT MACHINE GUN (MINIGUN)**



**TECHNICAL REPORT**

**Fred Novekoff**

February 1971

D D C  
RECEIVED  
JUN 29 1971  
A

**SCIENCE & TECHNOLOGY LABORATORY  
RESEARCH & ENGINEERING DIRECTORATE**

**U. S. ARMY WEAPONS COMMAND**

This document has been approved for public release and sale; its distribution is unlimited.

Reproduced by  
NATIONAL TECHNICAL  
INFORMATION SERVICE  
Springfield, Va 22151

19

**DISPOSITION INSTRUCTIONS:**

Destroy this report when it is no longer needed. Do not return it to the originator.

**DISCLAIMER:**

The findings of this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

SEARCHED	INDEXED
SERIALIZED	FILED
APR 19 1954	
FBI - WASHINGTON	
BY	FILED
DISPATCHED	COPIES
DIST.	AVAIL. SOURCE CONTROL
A	

Unclassified

Security Classification

DOCUMENT CONTROL DATA - R & D

(Security classification of title, body of abstract and indexed information must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY (Corporate author) U. S. Army Weapons Command Research and Engineering Directorate Rock Island, Illinois 61201		2a. REPORT SECURITY CLASSIFICATION Unclassified	
3. REPORT TITLE LOW-TEMPERATURE LUBRICANTS FOR THE M134 AIRCRAFT MACHINE GUN (MINIGUN) (U)			
4. DESCRIPTIVE NOTES (Type of report and inclusive dates) Final Report 1 June 1970 - 30 November 1970			
5. AUTHOR(S) (First name, middle initial, last name) Fred Novekoff			
6. REPORT DATE February 1971		7a. TOTAL NO. OF PAGES 19	7b. NO. OF REFS 4
8a. CONTRACT OR GRANT NO. b. PROJECT NO. DA TG062105A107 c. AMS Code 502E.11.801 d.		9a. ORIGINATOR'S REPORT NUMBER(S) RE-71-1 9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)	
10. DISTRIBUTION STATEMENT This document has been approved for public release and sale; its distribution is unlimited.			
11. SUPPLEMENTARY NOTES Type N		12. SPONSORING MILITARY ACTIVITY U. S. Army Weapons Command	
13. ABSTRACT An investigation of low-temperature lubricants for the M134 Aircraft Machine Gun (Minigun) was requested by Aircraft Weapons System Laboratory (AMSWE-REW-G). The tests were conducted at Air Proving Ground Center, Eglin Air Force Base, Florida. Two lubricants, specifi- cations MIL-L-14107(LAW) and MIL-L-46150(LSA-T), and two experimental lubricants, AWC #1 and AWC #6 were investigated. The weapon used for this investigation was the Minigun, 7.62MM, Automatic Gun GAU-2B/A. The purpose of the test was to determine which lubricant was suitable under sustained firing conditions at ambient temperature, at 0°F, -30°F, and -65°F. Data were obtained concerning malfunctions, rate of fire, time to reach peak rate in seconds, oil application, rounds fired, barrel temperature, and receiver temperature. It was found that LAW, the currently authorized low-temperature (0° to -65°F) lubricant for many weapons, could not be recommended at any tempera- ture on the minigun. LSA-T performed better than either AWC #1 or AWC #6 at ambient temperature. At 0°F no significant difference occurred between these three compounds. However, at -30°F, AWC #1 was superior to the other three. At -65°F, AWC #1 and AWC #6 gave better performance than LSA-T. (U) (Novekoff, Fred)			

DD FORM 1473  
1 NOV 65

REPLACES DD FORM 1473, 1 JAN 64, WHICH IS  
OBSOLETE FOR ARMY USE.

Unclassified

Security Classification

Unclassified

Security Classification

14 KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
1. Lubricants						
2. Lubricants, Low Temperature						
3. Lubricants, Aircraft Weapons						
4. 7.52MM Automatic Gun GAU-2B/A (Minigun)						

Unclassified

Security Classification

AD

SCIENCE AND TECHNOLOGY LABORATORY  
RESEARCH AND ENGINEERING DIRECTORATE

U. S. ARMY WEAPONS COMMAND

TECHNICAL REPORT

RE-71-1

LOW-TEMPERATURE LUBRICANTS  
FOR THE M134 AIRCRAFT MACHINE GUN (MINIGUN)

Fred Novekoff

February 1971

DA 1G062105A107

AMS Code 502E.11 801

This document has been approved for public release and sale;  
its distribution is unlimited.

## ABSTRACT

An investigation of low-temperature lubricants for the M134 Aircraft Machine Gun (Minigun) was requested by Aircraft Weapons System Laboratory (AMSWE-REW-G). The tests were conducted at Air Proving Ground Center, Eglin Air Force Base, Florida. Two lubricants, Specifications MIL-L-14107(LAW) and MIL-L-46150(LSA-T), and two experimental lubricants, AWC #1 and AWC #6 were investigated. The weapon used for this investigation was the Minigun, 7.62MM, Automatic Gun GAU-2B/A.

The purpose of the test was to determine which lubricant was suitable under sustained firing conditions at ambient temperature, at 0°F, -30°F, and -65°F. Data were obtained concerning malfunctions, rate of fire, time to reach peak rate in seconds, oil application, rounds fired, barrel temperature, and receiver temperature. It was found that LAW, the currently authorized low-temperature (0° to -65°F) lubricant for many weapons, could not be recommended at any temperature on the minigun. LSA-T performed better than either AWC #1 or AWC #6 at ambient temperature. At 0°F no significant difference occurred between these three compounds. However, at -30°F, AWC #1 was superior to the other three. At -65°F, AWC #1 and AWC #6 gave better performance than LSA-T.

## FOREWORD

This work was performed in part under Project Directive 0019V001 and AMS Code 502E.11.801, under project title "Lubricants, Friction and Wear." The subtask title was "Weapons Lubricant Field Tests." Additional work was performed under AMS Code 5142.12.11209.15, project title "Development of Aircraft Gun Type Subsystem," with work unit title "Investigate Low-Temperature Lubricants for Use with the M134 Machine Gun."

## CONTENTS

	<u>Page</u>
Title Page	i
Abstract	ii
Foreword	iii
Table of Contents	iv
Objective	1
Introduction	1
Procedure	1
Results and Discussion	4
Conclusions and Recommendations	12
Literature Cited	13
Distribution	14
DD Form 1473 (Document Control Data - R&D)	18



## OBJECTIVE

The objective of this investigation was to determine which low-temperature (0° to -65°F) lubricant should be specified for use on the M134 Aircraft Machine Gun (Minigun).

## INTRODUCTION

The Science and Technology Laboratory was requested by the Aircraft Weapons Systems Laboratory (1) to investigate the possibility of using MIL-L-14107 for the M134 gun under sustained firing at temperatures below -30°F and (2) to develop a polytetrafluoroethylene (PTFE) lubricant for low temperature use.

Data were unavailable at all temperatures, and the data that were available led to conflicting recommendations on lubrication. Tests at Aberdeen Proving Ground<sup>1</sup> indicated that LSA-T was inadequate at -65°F. Lubrication Order 9-1005-257-12<sup>2</sup> recommends the use of LSA-T from above +32°F to -10°F. This recommendation conflicts with that of the Science and Technology Laboratory which recommended the use of LSA-T down to -30°F.

Firing tests were conducted in June 1969 at Eglin Air Force Base to evaluate and qualify nine LSA-T formulations received from various suppliers.<sup>3</sup> These formulations were tested on the Minigun at high temperature (180°F), at ambient temperature (40° to 100°F), and at low temperature (-30 to -65°F). Results of this test indicated that LSA-T is adequate to only -30°F. However, an experimental lubricant, AWC #6, performed adequately at -65°F. None of these formulations were tested under sustained firing conditions. Therefore, additional firing tests were needed.

## PROCEDURE

### A. Materials Used

The lubricants used in this investigation are briefly described below:

Lubricant MIL-L-14107B(LAW) is a fluid and is the authorized arctic preservative lubricant for small-arms weapons under cold-weather conditions (0° to -65°F). The

lubricating oil consists of a tetra-alkyl silicate into which additive materials have been incorporated to inhibit rust and oxidation.

Lubricant MIL-L-46150(LSA-T) is a semifluid compound with 25 per cent polytetrafluoroethylene (PTFE). This is a thickened synthetic diester lubricant with inhibitors that provide resistance to corrosion and oxidation.

Lubricant AWC #1 is a semifluid compound containing 10 per cent PTFE molding powder. This lubricant is a silicate ester thickened with lithium stearate and contains an antiwear additive, oxidation inhibitor, and a corrosion-inhibitor system, in addition to the PTFE powder.

Lubricant AWC #6 is a semifluid compound with 5 per cent PTFE added. This lubricant is a pelargonic acid ester thickened with lithium stearate, and contains an antiwear additive, oxidation inhibitor, and a corrosion-inhibitor system.

#### B. Weapon Used

Two Automatic Guns, 7.62MM, GAU-2B/A, mounted on Aircraft Machine Gun Module 7.62MM, Air Force Model MXU-470/A were used. The gun module drum for this weapon is capable of holding 2000 rounds. The 7.62MM Automatic Gun is an electrically driven, six-barrel, Gatling-type weapon with low (2000), medium (4000), and high (6000 rounds per minute) firing rates. It is air-cooled, can be belt- or drum-fed, and is fully automatic. The six barrels have a fixed head-space and are of the quick-change type. This weapon, commonly called the Minigun, is presently used in a helicopter armament function. The major components of this weapon are rotor assembly, six bolt assemblies, six removable track, gun housing, safing sector, housing cover, guide bar, rear gun support, six barrels, and barrel clamp.

The ammunition is a 7.62MM cartridge-linked, 4-ball; and 1-tracer M13 linked, covered by FSN 1305-926-3942-A165. The ammunition was obtained from Hill Air Force Base, Ogden, Utah, but shipped from Lexington Blue Grass Army Depot, Richmond, Kentucky.

#### C. Firing Tests

All firing tests were conducted with the weapons set for automatic fire at the high rate of 6,000 rounds per minute. Details of each test are outlined in the following paragraphs:

1. Firing Test at Ambient Temperature  
(40° to 100°F)

The weapons were disassembled and cleaned of all traces of lubricants and residues with Stoddard Solvent (PD-680 "Dry Cleaning Solvent"). The parts were then dried with the use of an air hose and moisture-free compressed air. The lubricant was then applied generously to the gun with a brush. The front and rear bearings of the weapon are lubricated with a special lubricant; these bearings were excluded from the test. After lubrication, the weapon was mounted on the stand and test fired. The two weapons were used alternately in these tests; while one was being fired, the other was being prepared for the next test. Sixteen 1,000 round-bursts were fired with each lubricant, except that the LAW was not used in this test. In each test, the weapon being fired was cooled for two minutes following each odd numbered burst and cooled to ambient temperature following each even-numbered burst. The rate of fire and the peak rate (reached within 0.5 second) were recorded. Barrel temperatures were determined for the ambient tests only. When the sixteen bursts were completed, the gun was examined for dry areas, wear, galling, carbon or other deleterious effects.

2. Firing Test at 0°F

The weapons were prepared in the same way as those for the ambient test, except for the following changes: (a) Each gun along with the ammunition was soaked at 0°F for four hours before firing. (b) The barrels were cooled to 100±10°F after each 2,000 rounds. Again, 16,000 rounds were fired for each lubricant except for LAW.

3. Firing Test at -30°F

The procedure was the same as above, except that the lubricated gun and the ammunition were soaked at -30°F for four hours before firing. Here, 16,000 rounds were fired for each lubricant, including the LAW.

4. Firing Test at -65°F

The procedure, outlined above, was again followed, except that the lubricated gun and the ammunition were soaked at -65°F for four hours. The weapon was expected to reach peak rate within 1.0 second at this temperature. Again, 16,000 rounds were fired for each lubricant.

## RESULTS AND DISCUSSION

Results of the firing tests are shown in Tables I through V. LSA-T performed better than AWC #1 or AWC #6 at ambient temperature on the basis that the weapon accelerated to the highest rate in the shortest time (Table I). No significant difference is apparent in the performance between these three compounds at 0°F.

The data at -30°F (Table III) show that the AWC #1 was superior to the other three lubricants tested; based on the highest rate. MIL-L-14107 is considered unsatisfactory since jamming occurred.

At -65°F, the AWC #6 gave slightly improved performance over the AWC #1 and the LSA-T (Table IV). Again, bolts jammed when MIL-L-14107 was used.

In Table V, average firing rates and barrel temperatures are itemized under the test conditions described. The barrel temperatures were taken at every 1000-round burst so that the maximum temperature reflected the end of the second 1000-round burst before cooling to ambient temperature. This temperature varied dependent on the type of day. The firing rate was also taken at every burst and reflects the average peak firing rates. Since the feed ammunition module held 2000 rounds, the load affected the firing rate. Current requirements for the rate of fire are based on a 100-round belt load which requires 6000 rounds per minute. This accounts for the lower firing rates recorded.

The Minigun, lubricated with MIL-L-14107, malfunctioned 3 times in 277 rounds (Table III footnote). To prove whether the malfunctions were caused by the lubricant, LSA-T was applied liberally to the rotor and bolts. The remainder of a 2000-round complement, or 1723 rounds, was fired in two bursts without a malfunction. MIL-L-14107 lubricant was then tried at -65°F. The bolts jammed at 57, 100, and 400 rounds (Table IV footnote). The gun was then removed and no further testing was conducted on MIL-L-14107. Recent lubricant friction and durability tests\* under simulated weapon conditions at ambient temperature also show that LAW has little or no lubricating ability compared with LSA-T.

TABLE I

## ACCELERATION AND FIRING RATES AT AMBIENT TEMPERATURE

<u>Time, second</u>	<u>Firing Rate, rounds/minute</u>		
	<u>LSA-T *</u>	<u>AWC #1 **</u>	<u>AWC #6 ***</u>
0.1	3514	3621	3736
0.2	5014	4621	4814
0.3	5657	5207	5242
0.4	6171	5478	5385
0.5	6271	5521	5407
0.6	6271	5521	5492
0.7	6271	5521	5529
0.8	6271	5521	5579
0.9	6271	5521	5621
1.0	6271	5521	5621

\*-Barrel temperature after 1,000-round burst: 920°F

\*\* -Barrel temperature after 1,000-round burst: 980°F

\*\*\*-Barrel temperature after 1,000-round burst: 1080°F

TABLE II

ACCELERATION AND FIRING RATES AT 0°F

<u>Time, second</u>	<u>Firing Rate, rounds/minute</u>		
	<u>LSA-T</u>	<u>AWC #1</u>	<u>AWC #6</u>
0.1	4221	4038	4108
0.2	5614	5638	6092
0.3	6179	6323	6446
0.4	6386	6469	6500
0.5	6436	6554	6546
0.6	6493	6554	6546
0.7	6514	6554	6546
0.8	6529	6554	6546
0.9	6543	6554	6546
1.0	6543	6554	6546

TABLE III

## ACCELERATION AND FIRING RATES AT -30°F

<u>Time, second</u>	<u>Firing Rate, rounds/minute</u>			
	<u>*MIL-L-14107</u>	<u>LSA-T</u>	<u>AWC #1</u>	<u>AWC #6</u>
0.1	3000	3950	4200	3900
0.2	3900	4700	6300	5100
0.3	5400	5750	6450	5700
0.4	5800	6200	6600	6090
0.5	5900	6200	6700	6090
0.6	--	6200	6700	6090
0.7	--	6200	6700	6090
0.8	--	6200	6700	6090
0.9	--	6200	6700	6090
1.0	--	6200	6700	6090

\*Malfunctions - bolts jammed after 120, 112, and 45 rounds  
in three trials

TABLE IV

## ACCELERATION AND FIRING RATES AT -65°F

<u>Time, second</u>	<u>Firing Rate, rounds/minute</u>			
	<u>*MIL-L-14107</u>	<u>LSA-T</u>	<u>AWC #1</u>	<u>AWC #6</u>
0.1	3000	3757	4050	3450
0.2	5200	4886	5400	5100
0.3	5700	5443	5850	5850
0.4	5800	5471	5900	5850
0.5	--	5529	5900	6000
0.6	--	5629	5900	6000
0.7	--	5743	5900	6000
0.8	--	5743	5900	6000
0.9	--	5743	5900	6000
1.0	--	5743	5900	6150

\*Malfunctions - bolts jammed after 57, 100, and 400 rounds  
in three trials



TABLE V

## AVERAGE FIRING RATES AND BARREL TEMPERATURES

<u>Lubricant</u>	<u>Barrel Temp., °F</u>	<u>Firing Rate/ rounds/minute</u>			
		<u>Ambient</u>	<u>0°F</u>	<u>-30°F</u>	<u>-65°F</u>
AWC #1	880 - 1080	5500	6520	6590	5625
AWC #6	810 - 960	5690	6700	5880	5850
LSA-T	900 - 910	5914	6460	6125	5640
MIL-L-14107	---	No Test	No Test	*	*

\*Malfunctions occurred. Bolts jammed because of deficient lubrication.

#### CONCLUSIONS AND RECOMMENDATIONS

Based upon the tests conducted, MIL-L-14107B lubricant cannot be recommended for use at any temperature on the 7.62MM Automatic Gun GAU-2B/A, known as the Minigun. MIL-L-46150(LSA-T) can be used from ambient temperature to -30°F. Lubricant AWC #1 or AWC #6 can be used satisfactorily from 0° to -65°F on this weapon.

It is recommended that a purchase description be prepared establishing requirements and test procedures for Experimental Lubricants AWC #1 or AWC #6. This document will make the materials readily available within the military supply system.

#### LITERATURE CITED

1. Steier, G. M., "Final Report on Comparison Test of Pod, Aircraft Gun 7.62MM, XM18E1 (Quality Assurance)," Aberdeen Proving Ground Report APG-MT-3431, January 1970.
2. "Armament Pod, Aircraft, 7.62 Millimeter Machine Gun: XM18 and XM18E1," Lubrication Order L09-257-12, 10 October 1969.
3. Novekoff, F., "RIAPD-688 Lubricant, Semifluid Low Friction (Automatic Weapons) for Automatic 7.62MM, GAU-2B/A," U. S. Army Weapons Command Science and Technology Laboratory Technical Report, in preparation.
4. Bornong, B. J., "Lubricant Friction and Durability Tests Under Simulated Weapon Conditions," U. S. Army Weapons Command Science and Technology Laboratory Technical Report RE-70-190, November 1970.

AD U. S. Army Weapons Command Science and Technology Laboratory  
Rock Island, Illinois 61201  
 LOW-TEMPERATURE LUBRICANTS FOR THE M134 AIR-CRAFT MACHINE GUN (MINIGUN), by Fred Novekoff

Report RE-71-1, Feb 71, 19 p. incl. illus. tables, (DA Project IG062105A107, AMS Code 502E.11.801) Unclassified report.

An investigation of low-temperature lubricants for the M134 Aircraft Machine Gun (Minigun) was requested by Aircraft Weapons System Laboratory (AMSWE-REM-G). The tests were conducted at Air Proving Ground Center, Eglin Air Force Base, Florida. Two lubricants, specifications MIL-L-14107(LAW) and MIL-L-46150(LSA-T), and two experimental

UNCLASSIFIED

1. Lubricants
2. Lubricants, Low Temperature
3. Lubricants, Aircraft Weapons
4. 7.62MM Automatic Gun GAU-28/A (Minigun)

DISTRIBUTION  
 Copies obtainable from DDC

(Cont.) over

AD U. S. Army Weapons Command Science and Technology Laboratory  
Rock Island, Illinois 61201  
 LOW-TEMPERATURE LUBRICANTS FOR THE M134 AIR-CRAFT MACHINE GUN (MINIGUN), by Fred Novekoff

Report RE-71-1, Feb 71, 19 p. incl. illus. tables, (DA Project IG062105A107, AMS Code 502E.11.801) Unclassified report.

An investigation of low-temperature lubricants for the M134 Aircraft Machine Gun (Minigun) was requested by Aircraft Weapons System Laboratory (AMSWE-REM-G). The tests were conducted at Air Proving Ground Center, Eglin Air Force Base, Florida. Two lubricants, specifications MIL-L-14107(LAW) and MIL-L-46150(LSA-T), and two experimental

UNCLASSIFIED

1. Lubricants
2. Lubricants, Low Temperature
3. Lubricants, Aircraft Weapons
4. 7.62MM Automatic Gun GAU-28/A (Minigun)

DISTRIBUTION  
 Copies obtainable from DDC

(Cont.) over

AD U. S. Army Weapons Command Science and Technology Laboratory  
Rock Island, Illinois 61201  
 LOW-TEMPERATURE LUBRICANTS FOR THE M134 AIR-CRAFT MACHINE GUN (MINIGUN), by Fred Novekoff

Report RE-71-1, Feb 71, 19 p. incl. illus. tables, (DA Project IG062105A107, AMS Code 502E.11.801) Unclassified report.

An investigation of low-temperature lubricants for the M134 Aircraft Machine Gun (Minigun) was requested by Aircraft Weapons System Laboratory (AMSWE-REM-G). The tests were conducted at Air Proving Ground Center, Eglin Air Force Base, Florida. Two lubricants, specifications MIL-L-14107(LAW) and MIL-L-46150(LSA-T), and two experimental

UNCLASSIFIED

1. Lubricants
2. Lubricants, Low Temperature
3. Lubricants, Aircraft Weapons
4. 7.62MM Automatic Gun GAU-28/A (Minigun)

DISTRIBUTION  
 Copies obtainable from DDC

(Cont.) over

AD U. S. Army Weapons Command Science and Technology Laboratory  
Rock Island, Illinois 61201  
 LOW-TEMPERATURE LUBRICANTS FOR THE M134 AIR-CRAFT MACHINE GUN (MINIGUN), by Fred Novekoff

Report RE-71-1, Feb 71, 19 p. incl. illus. tables, (DA Project IG062105A107, AMS Code 502E.11.801) Unclassified report.

An investigation of low-temperature lubricants for the M134 Aircraft Machine Gun (Minigun) was requested by Aircraft Weapons System Laboratory (AMSWE-REM-G). The tests were conducted at Air Proving Ground Center, Eglin Air Force Base, Florida. Two lubricants, specifications MIL-L-14107(LAW) and MIL-L-46150(LSA-T), and two experimental

UNCLASSIFIED

1. Lubricants
2. Lubricants, Low Temperature
3. Lubricants, Aircraft Weapons
4. 7.62MM Automatic Gun GAU-28/A (Minigun)

DISTRIBUTION  
 Copies obtainable from DDC

(Cont.) over

Lubricants, AMC #1 and AMC #6 were investigated. The weapon used for this investigation was the M1918, 7.62MM, Automatic Gun GAU-28/A. The purpose of the test was to determine which lubricant was suitable under sustained firing conditions at ambient temperature, at 0°F, -30°F, and -65°F. Data were obtained concerning malfunctions, rate of fire, time to reach peak rate in seconds, oil application, rounds fired, barrel temperature, and receiver temperature. It was found that LAM, the currently authorized low-temperature (0° to -65°F) lubricant for many weapons, could not be recommended at any temperature on the M1918. LSA-T performed better than either AMC #1 or AMC #6 at ambient temperature. At 0°F no significant difference occurred between these three compounds. However, at -30°F, AMC #1 was superior to the other three. At -65°F, AMC #1 and AMC #6 gave better performance than LSA-T.

Lubricants, AMC #1 and AMC #6 were investigated. The weapon used for this investigation was the M1918, 7.62MM, Automatic Gun GAU-28/A. The purpose of the test was to determine which lubricant was suitable under sustained firing conditions at ambient temperature, at 0°F, -30°F, and -65°F. Data were obtained concerning malfunctions, rate of fire, time to reach peak rate in seconds, oil application, rounds fired, barrel temperature, and receiver temperature. It was found that LAM, the currently authorized low-temperature (0° to -65°F) lubricant for many weapons, could not be recommended at any temperature on the M1918. LSA-T performed better than either AMC #1 or AMC #6 at ambient temperature. At 0°F no significant difference occurred between these three compounds. However, at -30°F, AMC #1 was superior to the other three. At -65°F, AMC #1 and AMC #6 gave better performance than LSA-T.

Lubricants, AMC #1 and AMC #6 were investigated. The weapon used for this investigation was the M1918, 7.62MM, Automatic Gun GAU-28/A. The purpose of the test was to determine which lubricant was suitable under sustained firing conditions at ambient temperature, at 0°F, -30°F, and -65°F. Data were obtained concerning malfunctions, rate of fire, time to reach peak rate in seconds, oil application, rounds fired, barrel temperature, and receiver temperature. It was found that LAM, the currently authorized low-temperature (0° to -65°F) lubricant for many weapons, could not be recommended at any temperature on the M1918. LSA-T performed better than either AMC #1 or AMC #6 at ambient temperature. At 0°F no significant difference occurred between these three compounds. However, at -30°F, AMC #1 was superior to the other three. At -65°F, AMC #1 and AMC #6 gave better performance than LSA-T.

Lubricants, AMC #1 and AMC #6 were investigated. The weapon used for this investigation was the M1918, 7.62MM, Automatic Gun GAU-28/A. The purpose of the test was to determine which lubricant was suitable under sustained firing conditions at ambient temperature, at 0°F, -30°F, and -65°F. Data were obtained concerning malfunctions, rate of fire, time to reach peak rate in seconds, oil application, rounds fired, barrel temperature, and receiver temperature. It was found that LAM, the currently authorized low-temperature (0° to -65°F) lubricant for many weapons, could not be recommended at any temperature on the M1918. LSA-T performed better than either AMC #1 or AMC #6 at ambient temperature. At 0°F no significant difference occurred between these three compounds. However, at -30°F, AMC #1 was superior to the other three. At -65°F, AMC #1 and AMC #6 gave better performance than LSA-T.