]

٦

)

Prepared for Office of Civil Defense Office of the Secretary of the Army Washington, D. C. 20310 SRI Subcontract No. 11599(6300A-090) OCD Work Unit 1215A

SHELTER ENVIRONMENTAL PREDICTION (SHEP)

COMPUTER CODE

MODIFICATION 3

USER'S MANUAL

GARD Final Report 1423

June 1958

This document has been approved for public release and sale; its distribution is unlimited.

> C. E. Rabhmann R. J. Baschlere

REVIEW NOTICE

This report has been reviewed in the Office of Civil Defense and approved for publication. Approval does not signify that the contents necessarily reflect the views and policies of the Office of Civil Defense.

GENERAL AMERICAN RESEARCH DIVISION

NATIONAL TECHNICAL INFORMATION SERVICE

DDC	Ĵ,
	I

RAPINIENT PAN	
DUCUMENT CUN (Security classification of title, body of obstract and indexin	i I KUL VAIA - K & V A consistion must be entered when the overall tenoti in classified;
ORIGINATING ACTIVITY (Corporate Author)	20. REPORT SECURITY CLASSIFICATION
General American Research Division	Unclassified
7449 N. Natchez Avenue	24. GROUP
Niles, Illinois 00040	
REPORT TITLE	
CONDUCTOR ENVIRONMENTAL FREDICTION (SHEF)	
COMPUTER CODE, MODIFICATION 5	· · · · · ·
RECEIPTIVE NATES (Trans of many and buckusing datas)	
Final Report	
AUTHOR(S) (First name, middle initial, last name)	
devil 7 Dethuene	•
Carl E. Katnuann Dereld I. Deschieve	
Konalu J. Baschlere	
NEP TRT DATE	TA. TOTAL NO. OF PAGES 75. NO. OF REFS
June 1900	100 Y
SRT Subcontract No. 11599(6300A-090)	IN GRIGINATOR'I REPORT NUMBER(I)
PROJECT NO.	
	GARD 1423
-	D. OTHER REPORT NOIS (Any other numbers that may be assigned
OCD Work Unit 1215A	
,	
DISTRIBUTION STATEMENT	
This document has been approved for publ	Lic release
and sale; its distribution is unlimited.	
· · · · ·	
. SUPPLEMENTARY NOTES	12. SPONSORING MILITARY ACTIVITY
SUPPLEMENTARY NOTES	12. SPONSORING MILITARY ACTIVITY Office of Civil Defense
BUPPLEMENTARY NOTES	12. SPONSORING MILITARY ACTIVITY Office of Civil Defense Office of the Secretary of the Army, Washington D. C. 20310
ABSTRACT	12. SPENSORING MILITARY ACTIVITY Office of Civil Defense Office of the Secretary of the Army, Washington, D. C. 20310
. SUPPLEMENTARY HOTES	Office of Civil Defense Office of the Secretary of the Army, Washington, D. C. 20310
ABSTRACT	12. SPONSORING MILITARY ACTIVITY Office of Civil Defense Office of the Secretary of the Army, Washington, D. C. 20310
The Shelter Environmental Predicti	12. SPONSORING MILITARY ACTIVITY Office of Civil Defense Office of the Secretary of the Army, Washington, D. C. 20310
The Shelter Environmental Predicti calculates the response of a shelt	12. SPONSORING MILITARY ACTIVITY Office of Civil Defense Office of the Secretary of the Army, Washington, D. C. 20310 ion (SHEP) Computer Code, Mod. 3, ter to thennal loads and inlet air
The Shelter Environmental Predicti calculates the response of a shelt conditions. The manual explains t	 is spensoning military activity <pre>Office of Civil Defense Office of the Secretary of the Army, Washington, D. C. 20310</pre> ion (SHEP) Computer Code, Mod. 3, ter to thennal loads and inlet air the various features of the code,
The Shelter Environmental Predicti calculates the response of a shelt conditions. The manual explains to presents the I/O formats, gives sa	 is sponsoning military activity <pre>Office of Civil Defense Office of the Secretary of the Army, Washington, D. C. 20310</pre> ion (SHEP) Computer Code, Mod. 3, ter to thennal leads and inlet air the various features of the code, ample date values and includes a
The Shelter Environmental Predicti calculates the response of a shelt conditions. The manual explains t presents the I/O formats, gives sa typical application.	 is sponsoning military activity <pre>Office of Civil Defense Office of the Secretary of the Army, Washington, D. C. 20310</pre> ion (SHEP) Computer Code, Mod. 3, ter to thennal loads and inlet air the various features of the code, ample date values and includes a
The Shelter Environmental Predicti calculates the response of a shelt conditions. The manual explains t presents the I/O formats, gives sa typical application.	 ia. sponsonine military activity Office of Civil Defense Office of the Secretary of the Army, Washington, D. C. 20310 ion (SHEP) Computer Code, Mod. 3, ter to thennal loads and inlet air the various features of the code, ample date values and includes a
The Shelter Environmental Predicti calculates the response of a shelt conditions. The manual explains t presents the I/O formats, gives sa typical application.	 12. SPONSORING MILITARY ACTIVITY Office of Civil Defense Office of the Secretary of the Army, Washington, D. C. 20310 10. (SHEP) Computer Code, Mod. 3, ter to thennal loads and inlet air the various features of the code, ample date values and includes a
The Shelter Environmental Predicti calculates the response of a shelt conditions. The manual explains t presents the I/O formats, gives sa typical application.	12. SPONSORING MILITARY ACTIVITY Office of Civil Defense Office of the Secretary of the Army, Washington, D. C. 20310 ion (SHEP) Computer Code, Mod. 3, ter to thennal loads and inlet air the various features of the code, ample date values and includes a
The Shelter Environmental Predicti calculates the response of a shelt conditions. The manual explains to presents the I/O formats, gives sa typical application.	 12. SPONSORING MILITARY ACTIVITY Office of Civil Defense Office of the Secretary of the Army, Washington, D. C. 20310 10. (SHEP) Computer Code, Mod. 3, ter to thennal loads and inlet air the various features of the code, ample date values and includes a
The Shelter Environmental Predicti calculates the response of a shelt conditions. The manual explains t presents the I/O formats, gives sa typical application.	 12. SPONSORING MILITARY ACTIVITY Office of Civil Defense Office of the Secretary of the Army, Washington, D. C. 20310 10. (SHEP) Computer Code, Mod. 3, ter to thennal loads and inlet air the various features of the code, ample date values and includes a
The Shelter Environmental Predicti calculates the response of a shelt conditions. The manual explains t presents the I/O formats, gives sa typical application.	 is spensoning military activity Office of Civil Defense Office of the Secretary of the Army, Washington, D. C. 20310 ion (SHEP) Computer Code, Mod. 3, ter to thennal loads and inlet air the various features of the code, ample date values and includes a
The Shelter Environmental Predicti calculates the response of a shelt conditions. The manual explains t presents the I/O formats, gives sa typical application.	 I. SPONSORING MILITARY ACTIVITY <pre>Office of Civil Defense Office of the Secretary of the Army, Washington, D. C. 20310</pre> ion (SHEP) Computer Code, Mod. 3, ter to thennal loads and inlet air the various features of the code, ample date values and includes a
The Shelter Environmental Predicti calculates the response of a shelt conditions. The manual explains t presents the I/O formats, gives sa typical application.	12. SPONSORING MILITARY ACTIVITY Office of Civil Defense Office of the Secretary of the Army, Washington, D. C. 20310 ion (SHEP) Computer Code, Mod. 3, ter to thennal loads and inlet air the various features of the code, ample data values and includes a
The Shelter Environmental Predicti calculates the response of a shelt conditions. The manual explains to presents the I/O formats, gives sa typical application.	12. SPONSORING MILITARY ACTIVITY Office of Civil Defense Office of the Secretary of the Army, Washington, D. C. 20310 ion (SHEP) Computer Code, Mod. 3, ter to thennal loads and inlet air the various features of the code, ample date values and includes a
The Shelter Environmental Predicti calculates the response of a shelt conditions. The manual explains t presents the I/O formats, gives sa typical application.	12. SPONSORING MILITARY ACTIVITY Office of Civil Defense Office of the Secretary of the Army, Washington, D. C. 20310 10. (SHEP) Computer Code, Mod. 3, ter to thennal loads and inlet air the various features of the code, ample date values and includes a
The Shelter Environmental Predicti calculates the response of a shelt conditions. The manual explains t presents the I/O formats, gives sa typical application.	12. SPONSORING MILITARY ACTIVITY Office of Civil Defense Office of the Secretary of the Army, Washington, D. C. 20310 ion (SHEP) Computer Code, Mod. 3, ter to thennal loads and inlet air the various features of the code, ample date values and includes a
The Shelter Environmental Predicti calculates the response of a shelt conditions. The manual explains t presents the I/O formats, gives sa typical application.	12. SPONSORING MILITARY ACTIVITY Office of Civil Defense Office of the Secretary of the Army, Washington, D. C. 20310 ion (SHEP) Computer Code, Mod. 3, ter to thennal loads and inlet air the various features of the code, ample date values and includes a
The Shelter Environmental Predicti calculates the response of a shelt conditions. The manual explains t presents the I/O formats, gives sa typical application.	13. SPONSORING MILITARY ACTIVITY Office of Civil Defense Office of the Secretary of the Army, Washington, D. C. 20310 ion (SHEP) Computer Code, Mod. 3, ter to thennal loads and inlet air the various features of the code, ample date values and includes a
The Shelter Environmental Predicti calculates the response of a shelt conditions. The manual explains to presents the I/O formats, gives sa typical application.	13. SPONSORING MULITARY ACTIVITY Office of Civil Defense Office of the Secretary of the Army, Washington, D. C. 20310 ion (SHEP) Computer Code, Mod. 3, ter to thennal loads and inlet air the various features of the code, ample date values and includes a
ABAVANCE The Shelter Environmental Predicti calculates the response of a shelt conditions. The manual explains to presents the I/O formats, gives sa typical application.	12. SPONSORING MILITARY ACTIVITY Office of Civil Defense Office of the Secretary of the Army, Washington, D. C. 20310 ion (SHEP) Computer Code, Mod. 3, ter to thennal loads and inlet air the various features of the code, ample date values and includes a
ABSYRACT The Shelter Environmental Predictical calculates the response of a shelt conditions. The manual explains to presents the I/O formats, gives satypical application.	12. SPONSORING MILITARY ACTIVITY Office of Civil Defense Office of the Secretary of the Army, Washington, D. C. 20310 ion (SHEP) Computer Code, Mod. 3, ter to thennal loads and inlet air the various features of the code, ample date values and includes a

THIS DOCUMENT WAS RECEIVED BY NTIS WITH PAGINATION MISSING ON SOME OR ALL PAGES AND COULD THEREFORE BE INCOMPLETE. TO PERMIT REPRODUCTION IN THE PROPER PAGE SEQUENCE, NTIS HAS ADDED PAGINATION WITHOUT IMPLYING THAT THE DOCUMENT IS COMPLETE. 0110111111111111

Ity Classification

		LIN	K A	LIN	K B	LIN	ĸç
	K 2 Y WORDS +	ROLE	WT	ROLE	WY	ROLE	WT
	ENVIRONMENT CONFINED ENVIRONMENTS FALLOUT SHELTERS COMPUTERS PROGRAMMING (COMPUTERS)						
			l				
					ļ		
						[
	· .			ļ		Į	
	· –						
		!					
				ļ			-
]	}			
			1 		Ì	ļ	
	· .						
-							
			UR	CIASSI	FJBD		
			Preselty	Cleasifi	esting		

FOREWORD

This user's manual was prepared by the General American Research Division of the General American Transportation Corporation for the Stanford Research Institute under Subcontract No. 11599(6300A-090). It explains in detail the procedure for using the computer code to calculate the response of a shelter to time-varying thermal loads and time-varying ventilation inlet psychrometric conditions. The code is based upon research performed between June 1963 and May 1968 on the Analysis of Shelter Ventilation Requirements which falls in the program area of OCD Work Unit 1215A.

The project was monitored by Mr. F. Allen (then rt OCD) and Mr. D. Bettge of OCD, and Messrs. C. Grubb and J. Halsey of SRI.

The authors wish to thank Messrs. H. Moy, M. Lokmanhekim, D. Liddell, and A. Kapil of GARD, Dr. J. Buchanan of OCD, Mr. P. Achenbach and Dr. T. Kusuda of the National Bureau of Standards, Mr. W. Spiegel, Consulting Engineer, and Messrs. F. Hughes-Jaley and T. Hori of SRI for their comments and criticism. The valuable cooperation of the personnel at the OCD computer facility in Olney, Maryland and the Control Data Corporation computer facility in Chicago, Illinois is acrnowledged.

It should be noted that the version of the SHEP code presented in this report (Mod. 3) has been superseded by a new modification (Mod. 6). This new code employs a slightly different sequence of calculation to decrease calculation time.

BENGRAL AMERICAN RESEARCH DIVISION

ABSTRACT

The Shelter Environmental Prediction (SHEP) Computer Code, Modification 3, calculates the response of a shelter to time-varying thermal loads and timevarying ventilation inlet psychrometric conditions. The code accommodates solar radiation, boundary surface heat transfer, moisture condensation on the boundaries, equipment and lighting loads, and air conditioning. The manual explains the various features of the code, presents the input and output formats, gives representative input data values, and includes an application of the code to a typical shelter structure.

The required inputs to the code and the outputs obtainable from it are given below:

Inputs

1.	Ventilation rate	1.	hourly temperatures
2.	Inlet psychrometric con- ditions	2.	Hourly air conditioning load
3.	Shelter geometric charac- teristics	3.	Hourly boundary heat transfer
4.	Shelter thermal charac- teristics	4.	Hourly metabolic loads
5.	Shelter latitude, longitude and altitude	5.	Average temperatures (dry-bulb, wet- bulb, effective) for the entire occupancy or specified hours of occupancy
6.	Period of occupancy	6.	Maximum and minimum temperatures (dry-bulb, wet-bulb, effective) during the occupancy.

The code is written in PORTRAN IV specifically for the CDC 3600 computer system and consists of approximately 780 cards. It requires a memory bank of at least 65^{k} words (each word of 48 bits) for the code and the accompanying matrices. For the CDC 3600 and for a problem comparable to the sample problem presented in the text, the compilation time is approximately 1 min., 45 sec. and the execution time approximately 1 sec. for each hour of shelter occupancy.

GENERAL AMERICAN REBEARCH DIVISION

¥

TABLE OF CONTENTS

Section		Page No.
	FOREWORD	. 111
	ABSTRACT	۷
1	Introduction	1-1
2	FEATURES OF THE PROGRAM	2-1
	2.1 Shelter Boundaries	2-1
	2.1 Solar Radiation	2-6
	2.3 Air Conditioning	2-10
	2.4 Moisture Condensation	- 2-11
	2.5 Metabolic Loads	2-13
	2.6 Auxiliary Loais	2-13
	2.7 Varying Inlet Conditions	2-13
	2,8 Error Messages	2-15
	2.9 Determination of Shelter Dry-Bulb Temperture	2-15
Ň	2.10 Determination of Shelter Effective Temperature	2-17
3	INPUT DATA	3-1
	Limitations on Input Values	3-6
4	HOM TO USE SHEP	4-1
5	INTERPRETATION OF OUTFUT	5-1
6	SAMPLE PROBLEM	6-1
7	REPERENCES	7-1

GENERAL AMERICAN RESEARCH DIVISION

7\$

TABLE OF CONTENTS (CONT'D)

1

٦

1

APPENDIX		Page No.
A	DETERMINATION OF SHELTER ENVIRONMENT	A-1
3	DETERMINATION OF SOLAR RADIATION INTENSITY	B-1
	B-1 Determination of the Sun's Altitude and Azimuth Angles	B -1
	B-2 Solar Declination Angle and Time Angle	B-3
	B-3 Angle of Surfact to Sun's Rays	B-3
	B-4 Sunrise and Sunset Values of Hour Angle	B-6
•	B-5 Intensity of Solar Radiation	_ B-7
C	BOUNDARY ENERGY TRANSFER AND NODAL TEMPERATURE COEFFICIENTS	C-1
D	MOISTURE CONDENSATION	D-1
B	ERROR INTRODUCED BY CONSIDERING THREE- DIMENSIONAL HEAT TRANSFER AS A ONE- DIMENSIONAL PHENOMENON	B-1
F	ESTIMATION OF ERROR ASSOCIATED WITH CALCULATION OF AIR-CONDITIONING LOAD	P-1
G	TYPICAL THERNAL PROPERTIES AND DENSITIES OF BUILDING MATERIALS, SOILS, ETC.	G-1
H	SHEP CODE, MODIFICATION 3, FLOW CHART AND LISTING	H-1

GENERAL AMERICAN REBEARCH DIVIBION

vii

LIST OF ILLUSTRATIONS

Migure No.	•	Page No.
2-1	A Typical Shelter Wall Consisting of Three Boundaries	2-3
2-2	Typical Nodal Point Arrangement in a Four-Layered Boundary	2-4
2-3	Equation of Time	2-8
2-4	Schematic Diagram of a Shelter Air- Conditioning System and the Corresponding Psychrometric Processes	2-12
3-1	Allowable Values c? the Shelter Latitude, ALAT	- 3-2
3-2	Input Data Format	3-7
3-3	Shelter Effective Temperatures Computed on Three Different Time Increments	- 3-11
4-1	Form Sheet for Organizing Imput Data	4-2
5-1	Output of Sample Problem	5-2
6-1	Sketch of Shelter Area Used in Sample Problem	6-7
A-1	Shelter Energy Transfer	¥-5
8-1	Geometry for Solar Radiation	B-2
B-2	Variation of Declination Angle, η , with the Day of the Year	Bak
B-3	Geometry for Tilted Surface	B-5
B-4	Direct Normal Radiation as a Function of $oldsymbol{eta}$	8-9
B-5	Ratio of Diffuse Sky Radiation Incident upon a Vertical Surface to that Incident upon & Horisontal Surface Luring Clear Days	B-10
3-6	Natio of Total to Diffuse Solar Rediction on a Norizontal Surface vs Direct Normal Radiation, I _{DN}	B-12
C-1	Various Positions of Boundary Hodal Points	C-5
B-1	Nodel Point Radii in a Cylindrical Shelter Used in Determining the BError	8- 3

GENELAL AMERICAN REBEARCH DIVISI

viii

LIST OF ILLUSTRATIONS (CONT'D)

Table No.		Page No.
I	Equation of Time	2-9
II	Saturation Pressures	2-14
III	Error Messages	2-16
IV	Sample Input Data	6-2
V	Errors of Considering Three-Dimensional Heat Transfer as One-Dimensional	B-4
VI	Estimation of Error Associated with Calculation of Air Conditioning Load	F- j

BENERAL AMERICAN REBEARCH BIVIDION

SECTION 1

INTRODUCTION

The Shelter Environmental Prediction (ShEP) code will calculate the environmental response of a shelter, or any large structure, to time-varying thermal loads and ventilation inlet psychrometric conditions. Shelter conditions computed by finite difference methods define the mistory of the shelter environment during occupancy.

The SHEP code accommodates solar radiation, boundary surface heat transfer, moisture evaporation or condensation on the boundaries, equipment and lighting loads, and air conditioning (derivations of the corresponding equations are given in the Appendices). Little technical knowledge of mass or energy transfer is required by a user of the SHEP code. Information that must be supplied includes shelter physical, thermal and geometrical characteristics, occupancy levels and durations, and hourly inlet conditions. The smount of required data is admittedly large, but is necessary so that the SHEP code will remain applicable to a wide variety of shelters.

The shelter model used in the code is based upon the assumptions that:

- Air within the shelter and ventilation air is completely and instantaneously mixed, so that one psychrometric condition will completely specify the shelter environment;
- Noisture condensation and evaporation is filmwith with the convective heat transfer coefficients constant over each boundary surface, but variable from boundary to boundary.
- Radiative energy transfer between the shelter boundaries is seglected.

GENERAL AMERICAN RESEARCH DIVISION

- 4. Shelter exhaust air is at the psychrometric condition of the shelter atmosphere; and
- 5. Thermal and physical properties of the air and of the structural materials are not temperature-dependent.

The SHEP code permits the analysis of an actual shelter with up to 20 different boundaries, enclosing a volume which has sensible and latent energy exchange with the environment external to the shelter.

This user's manual explains the various features of the SHEP code, presents the input and output formats, gives representative input data values, and includes an application of the code to a typical shelter structure.

The code is written in FORTRAN IV specifically for the CDC 3600 computer system and consists of approximately 780 cards. It requires a memory bank of at least 65^k words (each word of 48 bits) for the code and the accompanying matrices.

For the CDC 3660 and for a problem comparable to the sample problem presented in the text, the compilation time is approximately 1 min., 45 sec. and the execution time approximately 1 sec. for each hour of shelter occupancy.

PENERAL AMERICAN REBEARCH DIVIBION

SECTION 2

FEATURES OF THE PROGRAM

The shelter model used by the SHEP code is an accurate description of the actual shelter under analysis because of the methods which have been formulated in the code to handle the thermal processes which affect the shelter environment. These processes include:

1. solar radiation,

]

]

7

]

ני

]

]

]

J

]

]

2. air conditioning,

3. moisture evaporation and condensation,

4. time-varying inlet conditions, and

5. boundary heat transfer.

It has been found that during extreme hot weather, many actual shelters respond as if they had adiabatic boundaries. Thus, the code has the ability of analyzing a shelter with adiabatic or non-adiabatic shelter boundaries.

The complexity of the code has necessitated the printout of diagnostic error messages. These are included as a safeguard against using illegal variable values, or exceeding the inherent limits of the equations comprising the code.

2.1 Shelter Boundaries

An ectual shelter is bounded by walls, floor and ceiling, composed of several different kinds of materials (e.g., cement, glace, metal, etc.) and these can be at any orientation (slope and azimuth). In addition, the exterior boundary surface may be exposed to various media (e.g., air, soil, etc.). Therefore, a "boundary" is defined as a plane or approximately plane curved surfaces of the shelter enclosure consisting of a homogeneous inner layer and

"See Appendix E.

GENERAL AMERICAN REPEARCH DIVISION

successive homogeneous layers exposed to one external medium. If windows are included in one wall of the shelter and this wall is partially underground, then this wall consists of three boundaries (see Figure 2-1). A shelter volume may be defined by up to 20 boundaries. A curvilinear boundary should be considered plane, with its orientation that of the plane tangent to the boundary at its midpoint (see Appendix E).

An implicit finite-difference approach based upon a one-dimensional node array is used to compute temperature distribution across a boundary, with each boundary spanned by up to 40 nodal points. A boundary may consist of up to 5 layers, each having distinct thermal properties and nodal-point spacings. An air space within a boundary and-a soil media adjacent to a belowgrade boundary are considered as layers of the respective boundaries. Shelter tests have shown that 10 feet from the exterior boundary surface, the soil temperature is invariant. Thus the soil can be considered as a layer 10 feet thick whose exterior surface is at the undisturbed soil temperature.

Nodel point specing in a typical boundary consisting of 4 layers is shown in Figure 2-2. Each layer is divided into slab Δx_i thick and a model point is placed at the center of each slab. The innermost and outermost points are $\Delta x_i/2$ from the next inner nodel point and are placed at the surface of the layer (see Appendix C). It should be noted that there is a nodel point at each surface and at each interface, and that the nodel point numbering is continuous.

The number of nodal points in each layer is

$$\frac{\Delta_{k}}{k} = \frac{\text{Layer thickness}}{\Delta_{k}} + 1$$

which includes the node on the inner surface of the layer. The number of

BENERAL AMERICAN REBEARCH DIVISION



GENERAL ANSPICAN RESEARCH DIVISION



(

nodal points in a wall excluding the outermost point is $NMAX_{i}$ and must be supplied by the programmer. It is given by

$$\operatorname{NMAX}_{j} = \sum_{\operatorname{layers}} r_{j}$$

and the total number of nodal points is

$$N_{j} = RMAX_{j} + 1$$

Spacing between nodal points should vary inversely with conductivity. Suggested spacing in soil is one-half to one foot; in structural materials, one inch.

The nodal point approach to the temperature profile across the boundary permits an implicit representation of the temperature through the boundary via the simultaneous linear equations:

 $a_{11}T_1 + a_{12}T_2$

]

7

3

U

•21^T1 + •22^T2 + •23^T3

 $a_{32}T_2 + a_{33}T_3 + a_{34}T_4$

= b₂ * b3

- b_n

= b₁

 $a_{n-1,n-2}T_{n-2} + a_{n-1,n-1}T_{n-1} + a_{n-1,n}T_{n-1}$ = b n-1 a, n-l^Tn-l * a, n^Tn

obtained by applying an energy balance at each of a nodes. The a's are the coefficients of the temperatures at each node and the b's are the heat storage terms, which are time-dependent. In matrix form, the equations become:

 $\begin{bmatrix} A \end{bmatrix} \begin{bmatrix} T \end{bmatrix} = \begin{bmatrix} B \end{bmatrix}$

NERAL AMERICAN RESEARCH DIVISION

These equations may be solved for the nodal temperatures:

 $\begin{bmatrix} \mathbf{T} \end{bmatrix} = \begin{bmatrix} \mathbf{A} \end{bmatrix}^{-1} \begin{bmatrix} \mathbf{B} \end{bmatrix}$

and the heat transfer through a non-adiabatic boundary due to conduction may be computed based on the interior boundary surface temperatures. In addition, for non-adiabatic boundaries, heat loss due to moisture condensation or evaporation on the interior boundary surfaces is computed. The derivations of the equations for determining the [A] and [B] coefficients, and those for heat transfer due to condensation, are given in Appendix C. This implicit procedure does not have the stability considerations associated with the explicit method. Thus, longer time intervals can be utilized at each finite difference increment. If the boundaries are considered adiabatic, heat transfer both through the boundary and due to condensation or evaporation on the surface are considered zero.

2.2 Solar Radiation

If a surface is exposed to ambient air, it will normally be exposed to direct, diffuse and/or reflected solar radiation. If the surface is a shelter boundary, the incident radiation will serve to raise the shelter temperature in two ways. First, 'muident radiation will be partially absorbed by the boundary, thus raising its temperature and, in time, the temperature of the shelter. Second, radiation transmitted through the boundary will be incident on interior surfaces, similarly raising their temperatures and that of the shelter atmosphere.

SHEP makes several simplifying assumptions in treating the effects of solar rediation. One of these is that all reflected radiation, both that which falls onto the shelter surfaces from surrounding objects and that which

GENERAL AMERICAN REDEARCH DIVISION

is reflected from the shelter surfaces, is neglected. Also, radiation transmitted through a boundary is considered an instantaneous thermal load inside the shelter, similar to the lighting and equipment loads.

All calculations involving solar radiation are done using solar time, which differs slightly from Civil Time. The relation may be expressed as

Solar Time = Civil Time + Equation of Time + Δ_{long} Civil Time is that time assigned to a zone covering approximately 15° of longitude; it is the same as Standard Time. Since local time actually does not remain constant within each 15° zone, but varies by four minutes for each degree within the zone, a correction factor, Δ_{long} , takes this into account. The Equation of Time is the difference between mean solar time and apparent solar time and is given as the (12^h-Ephemeris Transit). See Reference 1. Solar time is computed in the program knowing the time of the start of occupancy, the longitude of the shalter, and the first day of occupancy.

Variation of the Equation of Time is shown in Figures 2-3 and the values used in the program are listed in Table I. The daily values of the Equation of Time change slightly from year to year, but the actual values remain within 0.3 min. of those listed (see Reference 2).

Solar rediction intensity is computed once each time increment for each exposed well (See Appendix B.) Although radiation will penetrate into a surface a certain distance before being absorbed, the SHEP code assumes this absorption phenomenon is a surface effect. Also, even though the transmittance of the boundary material may vary with incident wavelength, only a total transmittance value is used in the code.

GENERAL AMERICAN RESEARCH DIVISION



RENERAL AMERICAN RESEARCH DIVISION

TARLE I EQUATION OF TIME VALUES AS A FUNCTION OF DAY OF YEAR

-

IAY	VALKS	YNG I	VALUE	M	VAUE	λγα	VALLE	λM.	STIVA	INY	VALLE	λV	3075 /	LAY	VALUE	INY	VALUE	λγ	VALUE	MV	L SITVA	TAY 1	VALUE
-1	05	R	23	63	°	ネ	05	SET	05	3	60.	7 87	1.0	516	10	546	8	276	81.	ğ	1.2.	336	.18
~	8	8	23	-3	<u>,</u>	66	50	110	ઝ	157	50.	LAT	૪	212	- 10	247	.01	217	18	307	-27	337	.17
<u>~</u>	01	Ť	23	65	19	*	5	127	ઝ	158	8	168	8. 8	218	10	243	8	278	61.	308	.27	336	.17
.A 	8	35	23	8	19	5	3	128	8	5	ષ્ટ્ર	7 89	- °	219	10	249	8	5.19	61.	309	.27	339	.16
~	6 0 1 -	36	23	53	18	\$	ъ	23	8.	ञ्च	ક	67	88	220	8	250	0	280	50	310	23	340	.15
<u>و</u> ر	£.,	37	24	3	18	8	£0	130	8	161	.01	161	60 [.] -	ជ	60	251	£0.	281	-20	311	75.	341	77.
2	07	38	-,24	\$	18	100	03	151	8	SI SI	ö	192	60°-	222	8	252	રું	282	17.	दार्ट	.27	342	.14
30	11'	ž	24	2	27	101	3	132	8	£93	.01	193	- 60 -	223	60	253	5	283	-21	313	.27	343	.13
<i>9</i> .	12	9	2 ⁴	7	17	8	8	133	8	5	8	191	8	224		254	.05	58ř	.22	116	.2.1	.,,	P.
20	я.	77	24	2	16	103	01	2	8	165	8	195	8.	225	03	255	શ્રં	285	.22	315	.27	345	21.
1	ก:	F2	÷.24	2	•.16	ĩơ	-10	135	ş	<u>166</u>	8	8	10	226	08	256	8	286	.22	316	.26	346	11.
12	41	£4	- 24	*	15	ğ	8	736	8.	167	01	1.91	10 1	227	- 08	257	1.0.	287	.23	317	.26	747	.10
2		4	2h	22	15	3	8	โล	રુ	168	10	861	10	\$28	1.0	258	.07	268	.23	318	.26	348	8
74	- 15	45	24	2	- 14	101	8	951	8	F()	01	199	01	229	07	259	8	56 3	-24	319	.26	349	8
5	15	27	2h	4	14	8 <u>3</u>	5.	657	8	720	8.	ş	10	230	07	260	8	38	·24	320	.26	350	8
126	26	5	24	<u>6</u> 2	41	ğ	0	140	8	121	8	501	- 10	231	8	261	8	5 3 1	45.	125	5.	351	.07
17	17	3	2h	\$	13	110	10.	141	8	7.12	8	202	1 07	232	8	262	.10	292	.25	322	.25	352	8
18	17	67	24	8	13	Ħ	8	142	ષ્ટ	173	u3	ő	п	233	8	263	5	293	- 25	323	-24	353	.0
57	13	8	,.2 ⁴	8	a	वा	ક્	143	8	121		201	n	234	05	564	r .	đ,	.25	324	.24	35'i	<u>.</u> 05
8	18	2	23	8	ਕ	513	8	777	રુ	175		305	п -	235	05	265	ਸ਼.	295	-26	325	.24	355	રું
									,														
51	·19	X	23	8	11	114	0	145	8	22	·. 0	206 206	<u>н.</u> -	236	5	206	ส	8	.26	326	.23	356	03
8	61	2	23	వే	11 -	511	÷.	746	<u>8</u>	۲,	0	207	н	237	3	267	et.	762	.26	327	.23	357	8
<u>ສ</u>	61	£	23	જ	10	116	ю .	1.42	50 .	1.78	ъ. -	208		238	E0	2(8	ы .	2 9 6	.ç	328	8	358	<u>5</u> .
2	8.	22	23	8	10	117	ð	148	ઈ	5	05	503	.,11	239	03	5692	41.	5 3	<u>8</u>	6 25	8	3:59	8
\$	Q	8	22	5	8	877	5	149	ę	8	8.	210		540	8	270	.15	ğ	.27	330	.21	ğ	8
8	21	57	23	8	8	611	5	22	5	191	8	517		142	8	11.2	.15	301	.27	331	.21	361 -	5.
53		R	22	£	08	ซื	ð	151	đ	8 <u>3</u>	8	512	11	242	8	272	.16	ğ	.27	332	-20	સુ	8
ę,	4	\$	21	8.	08	121	<u>ې</u>	22	ð.	183	8	213	10	243	1.01	273	.16	303	.27	333	8.	363 -	÷.
<u>&:</u>		8	21	5	07	757	•••	153	3.	ซี	10	214	10	544	8	274	.17	ಕ್ಷ	.27	ηCE	61.	36	ō
8	22	61	21	8	8	123	<u>8</u>	757	ŧс.	185	1.0	225	10	245	8	275	.17	ğ	.27	335	61.	365 -	శే
ĩ	2	Ą	20	66	.o	421	.05	155	ю .					ļ]
+ 11r	_																						

•

GEVERAL AMERICAN RESEARCH DIVISION

2.3 Air Conditioning

In a typical air conditioning unit, warm air passes over cooling coils, thereby lowering its dry-bulb temperature through convective set exchange and lowering its moisture content through condensation. The temperature of the coils is not constant, but varies as a function of load. Typically, all the air passing through the air conditioner does not experience these heat and mass transfer processes due to flow turbulence.

The method the SHEP code utilizes to calculate the air conditioning load assumes that the temperature of the coils and the percentage of air unaffected by passing through the unit do not vary with the cooling load. An "effective coil surface temperature" is assumed as the design temperature of the coils; and a "coil bypass factor" is the design value of the percentage of air unaffected by the cooling units. If these two parameters are both assumed constant, the air conditioning performance of an actual unit can be estimated reasonably well. See Appendix F, which is based upon Reference 3.

A typical air conditioning system for a shelter may be represented by the schematic diagram of Figure 2-4; the various psychrometric states of the air in the system are indicated in the accompanying psychrometric chart. Note that "return air typass" refers to air <u>not</u> passing through air conditioning unit; "coil bypass factor" is a characteristic of the unit itself. Outside air at state point 1 enters the system and is adiabatically mixed with return air at the shelter condition, 3, to create state point 2. A portion of this air passes through the air conditioning unit, exiting with a lower dry-bulb temperature and a low humidity ratio, state point 3, and is then adiabatically mixed with the unconditioned air to give state point 4. Air at this condition is the inlet air to the shelter which is then used to compute the new shelter condition, S'.

DENERAL AMERICAN REDCARCH DIVISION

The ventilation rates of outside air entering the system, of air passing through the air conditioning unit, and of air entering the shelter must all be specified by the cole user. Therefore, the mixing processes can be altered, or even eliminated, by varying the various ventilation rates.

Air conditioning removes both sensible and latent energy. This energy removal, ΔQ , is given by

$$\Delta Q = c_n \pm \Delta T + h_{r_n} \pm \Delta W$$

where

1 - - - **3**

.....

]

= specific heat of air ~ 0.24 Btu/1b °F

ň.	æ	mass	flow	rate	of	dry	air	through	the	air	conditioning
		unit,	, 16/1	hr							

ΔT = temperature difference across the unit, *F

- h_{f,} = heat of condensation of water vapor, Btu/lb water
- ΔW = humidity ratio difference across the unit, 1b water/1b dry air

2.4 Moisture Condensation

Whenever the vapor pressure at the interior surface of a boundary is lower than the vapor pressure of the shelter atmosphere, moisture will migrate to and condense on the surface, thereby removing energy from the shelter environment. If, at another time, the vapor pressure at the boundary surface is higher than the vapor pressure of the shelter air, the process will be reversed and condensed water on the surface will re-evaporate and migrate into the shelter atmosphere.

If sufficient moisture condenses, it will run down the walls and accumulate on the floor of the shelter. Since the SHEP code assumes that condensation occurs in an even film on an interior surface, the effect of gravity is neglected.

GENERAL AMERICAN RESEARCH DIVISION





Figure 2-h Schematic Disgram of a Shelter Air-Conditioning System and the Corresponding Processes on a Skeleton Psychrometric Chart

GENERAL ASSERTANCE RESIGNING DIVIDION



In the code, the vapor pressure at the boundary surface is assumed to be the saturation pressure of water vapor at the temperature of the boundary surface. Values of saturation pressures as a function of dry-bulb temperature (see Table II) are a part of the standard input data. Only the range of temperatures from 50°F to 120°F are considered, since metabolic relations used in the SHEP code are invalid outside of this range.

2.5 Metabolic Loads

The metabolic expressions of Houghten⁵ are adopted in this study since they reflect effects of relative humidity in the shelter. They are given by

Q _{sensible}	12	$-0.06875(T_{db})^2 + 1.625(T_{db}) + 523.0$	for $T_{db} \ge 50^{\circ}F$
•		(-1.462 (ET) + 514.0	for $50^{\circ}F \leq ET \leq 87^{\circ}F$
Q _{total}	=	$-1.508 (\text{ET})^2 + 259.7 (\text{ET}) - 10795.2$	for $87^{\circ}F < ET \le 102^{\circ}F$
		0.0 (assumed)	for ET > 102°F

with $Q_{latent} = Q_{total} - Q_{sensible}$, assuming that the body is in thermal equilibrium with the shelter environment, and hence, neglecting the heat storage term.

2.6 Auxiliary Loads

Lighting and equipment loads are introduced as inputs and may be timevarying (on an hourly basis).

2.7 Verying Inlet Conditions

The psychrometric condition of the shelter atmosphere and of the entering ventilation air are considered by the code as a function of dry-bulb temperature and relative humidity.

Certain factors which affect the shulter stmosphere normally very with time; arbient temperature and relative humidity are chief smong these. Other factors which hay change during occupancy are:

Superscripts refer to references, p. 7-1.

GENERAL AMERICAN REBEARCH DIVISIÓN

TABLE II

SATURATION PRESSURE, P_S, AS A FUNCTION OF DRY-BULB TEMPERATURE, T_{db}

T _{db} *	P_**	T _{db}	PS	T _{db}	PS	T _{db}	PS	T _{db}	P _S
50	25.648	64	42.494	78	68.357	92	107.021	106	163.368
51	26.620	ó5	44.006	79	70.646	93	110.390	107	168.235
52	27.622	65	45.562	80	72.994	94	113.846	108	173.218
53	28.656	67	47.174	81	75.413	95	117.403	109_	178.330
54	29.724	68	48.816	82	77.904	96	121.061	110	183,571
55	30.830	69	50.530	83	20.467	97	124.819	111	188.942
56	31.968	70	52.286	84	83.102	98 *	128.664	112	194.458
57	33.149	71	54.086	85	85.810	99	132.624	113	200.102
58	34.35 8	72	55.958	86	88.589	100	136.685	214	205.891
59	35.611	73	57.873	87	91.454	101	140.846	115	211.809
60	36.9 07	74	59.846	88	94.406	105	145.123	116	217.872
61	38.232	75	61.891	66	91.430	103	149.501	117	224.107
62	39.614	76	63.979	90	100.541	104	154.008	118	230.486
63	41.0LO	77	66.139	91	103.738	105	158.630	119	237.010
			(*************************************					150	243.706

*T_{db}: *F **P_S: 1b/ft²

GUNDAL AREDITAN RESEARCH DISTURN

1. the number of occupants,

2. the ventilation rate, and

3. the lighting and equipment loads.

In the code, these factors may have different values for each hour of occupancy.

2.8 Error Messages

Since many of the relations used in SHEP are valid only over certain ranges, limits have been placed on the values of certain input data and of certain computed variables. If these limits are exceeded, diagnostic error messedes are printed, stating what variable is in error and what value it has at the time it exceeded its limit. If an input variable has an illegal value, this will be indicated and the run will terminate; if a computed variable is invalid, this fact will be printed and the run will continue. A third type of diagnostic message is generated through machine error; for instance, if an index has overrun its bound.

A list of the error messages is indicated in Table III. These error messages are incorporated into the SHEP code and are in addition to the compilation and execution diagnostic routines of the machine.

2.9 Determination of Shelter Dry-Bulb Tempersoure

All thereal loads and enthalpies are computed at the begining of a time increment based upon an estimate of what the shelter dry-bulb temperature will be. Then the not amount of energy added to the shelter system during that increment is calculated. With this value, the shelter dry-bulb temperature can be computed by equation 20 of Appendix A. Since the shelter dry-bulb temperature of the increment is initially estimated to be that of the last increment, an iteration procedure is used to perait each calculated temperature

GENERAL AMERICAN RESEARCH DIVISION

TABLE III

ERROR MESSAGES

1. Input Variables Illegal

- A. "Inclination Angle XI (___) is ___. This value must be 90° or less."
- B. "The latitude of the shelter is greater than the program can handle for this day of the year."

2. Celculated Variables Illegal

- A. "R during hour _____ is ____, which is less than 1.0. Therefore, the latent metabolic energy has been reduced."
- B. "Shelter effective temperature during hour _____ is ____ which exceeds the limits on the metabolic relations."
- C. "Shelter dry-bulb temperature during hour _____ is ____ which exceeds the limits on the metabolic relations."
- D. "The relative humidity in the shelter has exceeded saturation."

3. Procedural Errors

- A. "The limits on laymax or nmax of wall ____ have been exceeded."
- 3. "The number of shelter boundaries, NW, has been exceeded."
- C. "The number of iterations for an increment has exceeded the value of IDATA(3)."
- D. "The number of increments in an hour exceeds the value of IDATA(5)."
- E. "The hour numbers are not indexing properly."
- F. "The hour number has exceeded the length of occupancy."

GENERAL AMORIDAN RUBEARCH DIVISION

to be used as a new estimate to compute a more accurate shelter dry-bulb temperature.

The number of iterations for each increment is a function of the accuracy of the initial estimate. If the dry-bulb temperatures computed on two successive iterations are less than $1^{\circ}F$ apart, the last temperature computed is assumed to be the value for the increment and the iteration procedure is curtailed. Otherwise, the procedure is continued until the number of iterations reaches the value of IDATA(3), (see Section 3).

2.10 Determination of Shelter Effective Temperature

After the shelter dry-bulb temperature for an increment has been computed, wet-bulb temperature is determined via the Carrier equation (equation 41 of Appendix A). Using a linear approximation to the nomogram of Reference 4, the effective temperature is calculated from:

ET =
$$\frac{107.5 \text{ T}_{db} - 45.2 \text{ T}_{wb}}{\text{T}_{db} - \text{T}_{wb} + 62.3}$$
 for $\begin{cases} 45^{\circ} \text{F} \leq \text{T}_{db} \leq 110^{\circ} \text{F} \\ 30^{\circ} \text{F} \leq \text{T}_{wb} \leq 110^{\circ} \text{F} \end{cases}$

where

T_{db} = ary-bulb temperature, *F

T_{wh} = wet-bulb temperature, *F

The psychrometric condition of the shelter atmosphere at the beginning of the next increment is then set equal to that at the end of the last increment and calculations for the next increment are begun. When one hour's calculations have been completed, the values for the last increment of the hour are printed out as the conditions at the end of the hour.

GENERAL AMORICAN REPARCH DIVISION

SECTION 3

.

ľ

INPUT DATA

Input data consist of physical constants, hourly occupancy constants, geometrical and thermal characteristics of the shelter, and initial conditions. The input variables and their definitions are given below; where units are not indicated, the value is dimensionless.

- ALAT -Latitude of the shelter, degrees. The limits on the range of ALAT are a function of the time of the year, see Figure 3-1.
- ALANG -Longitude of the shelter, degrees. Only values in the range O° to 180° W are allowed.
- ALT -Altitude of the shelter, feet.
- AREA(j) -Area of boundary -j, ft². -
- ASOIL(j) -Control constant determining the media exterior to the outer surface of boundary j.

ASOIL(j) = -1 ambient air 0 interior air 1 .oi?

\$Z(j)

j) -Azimuth angle of boundary j. AZ(j) is measured in a clockwise direction from north to the outward-pointing normal to the boundary. Values between 0° and 360° are permitted. For a boundary facing east, AZ(j) = 30° ; if it faces west, AZ(j) = 270° .

RF

-Ccoling coll bypass factor of the sir conditioning unit. It is defined as

$$BF = \frac{c_{f} - c_{e}}{t_{d} - t_{e}}$$

where

t, = sir temperature leaving the coil, "F

e coil effective surface temperature, *F
(TCOIL)

 $t_A = air temperature entering the coil, "F$

The suggested value is 0.15.

GENERAL AMERICAL RESEARCH DIVISION





MORDING MEDIA PEDIA PENDERBANA JARANJA

. . CFMIN -Total ventilation rate through air conditioner, cfm. CON(k,j) -Thermal conductivity of material of layer k of boundary j. Btu/hr-ft-*F. CP(k, j)-Specific heat of material of layer k of boundary j, Btu/lb-*F. -Day number of the start of occupancy. Values in the range of 1-365 are D wilowed, e.g., for Jenuary 1, D = 1. DP(k, j)-Thickness of layer k of boundary j, feet. DT -Time increment of shelter history used in finite-difference equations, hrs. $0.00 < DT \le 0.500$ hours, DT = 0.167 is suggested. DX(k,j)-Nodal point spacing of layer k of boundary j, feet. -Equation of Time for day i, hours. See Table I. EQTIM(i) F1 -Total ventilation rate entering shelter, cfm. **F**2 -Total ventilation rate of outside air entering shelter system, cfm. -Equivalent interior length of shelter, feet. Equivalent dimensions GG are those of a parallelepiped approximating the shelter under analysis. ΗН -Equivalent interior height of shelter, feet. -Interior film heat transfer coefficient of boundary j, Rtu/hr-ft -°F. **汨**(j) HO(j) -Exterior film heat transfer coefficient of boundary j, Btu/hr-ft?-*F. HRS -Total number of continuous hours of shelter occupancy. -Sets initial boundary temperatures IDATA(1) 1 - all boundary nodes have different temperatures IDATA(1) 0 - all boundary nodes have same temperature IDATA(2) -Reference constant; IDATA(2) = 0 * suggested. IDATA(3) -Humber of iterations for computing incremental shelter dry-bulb temperature. INATA(3) = 4 is suggested. IDATA(4) -Number of shelters to be analyzed in the computer run.

GENERAL AMERICAN REPEARCH COVISION

.ATA(5) -1 hour/DT, rounded to the nearest integer. IDATA(6) -Sets type of boundary. IDATA(δ) = $\begin{cases}
1 - \text{ for all non-adiabatic boundaries} \\
0 - \text{ for all adiabatic boundaries}
\end{cases}$ IDATA(?) -Determines presence of air conditioning. $IDATA(7) = \begin{cases} 0 - no & ir conditioning \\ 1 - air conditioning is present \end{cases}$ IDATA(8) -Reference constant, $I^{T}ATA(8) = 0$ is suggested. IDATA(9) -Reference constant, IIATA(9) = 0 is suggested. IDATA(10) -Sets atmospheric condition for solar radiation. $IDATA(1C) = \begin{cases} 0 & - \text{ for clear atmosphere} \\ 1 & - \text{ for industrial atmosphere} \end{cases}$ IUATA(11) -Establishes format of printout. IDATA(11) = {1 - Standard output format 0 - Only maximum, minimum and average temperatures are printed temperatures are printed IDATA(12) -Establishes variability of occupancy values. IDATA(12) = $\begin{cases} 0 - P, Fl, CPMIN, QLITE, QEQUIP change for each hour.$ $1 - These variables are held constant for entire occupancy. \end{cases}$ IDATA(13) -Establishes variability of inlet values. INT(m) -Hour limits of the intervals for which average temperatures are desired, e.g., for average dry-bulb temperatures from hour number 3 to hour number 9 of occupinary, then INT(1) = 3, INT(2) = 9. INT(n), where m is an old integer, $1 \le n \le 59$ determines the start of an interval; and INT(a+1) determines the end of the interval. LAYNAX(j) -Number of Layers in boundary j. Boil back of a boundary or an air space within a boundary is considered a layer of the boundary. Value must be 5 or less. IST(1)-Local Standard Time at beginning of occupancy; defined in terms of military time (0-23 hrs).

GENERAL AMURICAN RESTARCE DIVISION

3-4

1

NMAX(j) Number of nodal points in boundary j. If a boundry is soilbacked, the nodal points extend into and through the soil, up to a suggested distance of JO feet. Integrel values up to 39 are permitted. The outermost nodal point is not included in this value. NOINT Number of time intervals for which average temperatures are desired, NOINT ≤ 30 . NW Number of boundaries in the shelter, $NW \leq 20$. P Number of occupants. Saturation pressure of water vapor at n °F, lb/ft². PSAT(n) See Table II. QEQUIP Sensible heat load due to mechanical and/or electrical equipment (excluding lighting), Btu/hr. QLITE Sensible heat load due to lighting, Btu/hr. - Density of material of layer k of boundary j, lb/ft³. ROW(k,j)**k11** Relative humidity of inlet air at beginning of occupancy. R12 Relative humidity of inlet air at end of each hour of occupancy. R2 Relative humidity in shelter at beginning of occupancy. TAL Dry-bulb temperature of air exterior to shelter structure at beginning of occupancy, "F. TA2 Dry-bulb temperature of air exterior to shelter structure at end of each hour of occupancy, "F. TCOIL Effective coil temperature of air conditioning unit, 'F. Suggested value is 55°F with WCOIL = 0.00921 15 water/1b dry air. **TD11** Dry-bulb temperature of inlet air at the beginning of occupancy, "F. Dry-buib temperature of inlet air at end of each hour of occupancy, TDIX ۲. SOT Initial shelter dry-bulb temperature, "F. TEFY(1) Initial shelter affective temperature, "F. TO Initial temperature of each boundary nodal point, "F. THATS () Total rediction transmittance of boundary j. TSOIL(3) Temperature of outermost nodal point when considering a soilbacked boundary j, "F.

CENERAL AMERICAL REPARCH DIVICION

- TWB(1) -Initial shelter wet-bulb temperature, "F.
- W -Equivalent interior width of shelter, feet.
- HCOIL -Humidity ratio at saturation corresponding to TCOIL, lb moisture/lb dry air. Suggested value is 0.00921 for TCOIL = 55°F.
- XI(j) -Inclination angle of boundary j, measured from the vertical, degrees. Values between 0° and 90° are allowed. For a vertical boundary, XI(j) = 0°.

Limitations on Input Values

Since relations exist between certain inputs, changing one necessitates adjusting related values. These related input values are:

- If the time increment DT is varied, adjust IDATA(5), since IDATA(5) =
 1 hour/DT, rounded to the nearest integer.
- For the NW boundaries, the boundary properties of AREA(j), ASOIL(j), AZ(j), HI(j), HO(j), LAYNAX(j), NNAX(j) must correspond.
- If the number of layers, LAYMAX(j), is changed, then layer properties must be added or deleted: CON, CP, DP, DX, ROW.
- 4. Equivalent dimensions CG, HH, W must correspond to the AREA(j) values.
- 5. The hour limits on the interval for which average temperatures are desired, INT(m), must not exceed the length of occupancy, HRS.
- 6. The values of $\sum (DP(j)/DX(j)) + 1$ must equal NMAX for each boundary.
- Y. Initial values of dry-bulb, wet-bulb, and effective temperature and relative humidity must correspond: TD2, TWB(1), TRFF(1), R2.
- 8. WOOLL must correspond to TCOLL, for the sir conditioning unit.

It is obvious that the size of the data dock is quite large; it is of utmost importance that the order of the data deck, so indicated in Figure 3-2, to maintain of . Proinch points and field widths of the variables are also

GUNERAL APTERIARE DESTABLES DIVISION



Figure 3-2 Input Into Ferrat.

Repair of the state of the state of the second state of the second






Figure 3-2 (Cont'd) Input Date Formet

indicated in the figure. Since data may be placed only in specific fields on each data card, the easiest method of keeping the data deck ordered is to punch an appropriate identifier anywhere outside of the specified fields.

Values for the matrices EQTIM and PSAT way be found in Tables I and II. The EQTIM values are those for the year 1958, and may be considered those for any year in this century. Values of the saturation pressure as a function of dry-bulb temperature are introduced as a table with a linear interpolation scheme included in the program. These two inputs comprise the first 436 cards of a standard data deck.

If the program is used to analyze an actual shelter under actual weather conditions, hourly ambient temperature and relative humidity values are required. Soil temperatures may be considered constant over a two-week occupancy period.

Various time increments (DT) were tested by the authors to determine a compromise between accuracy of computation and length of computation. It has been found that a time increment of ten minutes (0.167 hr) produces results which are, on the average, within $0.3^{\circ}F$ of the results calculated using 2-minute increments. The computation time is also decreased by approximately 60%, see Figure 3-3.

It should be noted that integer data values must be right-hand justified within their respective fields; if this is not the case, the machine will place zeroes in the field to the right of the right-most non-zero digit.

RECEIPTING CONTRACTOR EXCITING EXCITING



(

SECTION 4

HOW TO USE SHEP

4.1 The first step in the analysis of a shelter is to describe the shelter with all of its necessary characteristics. Answer these questions on a form sheet such as that of Figure 4-1.

- 1. Where is the shelter located? (ALT, ALAT, ALONG).
- What is the shelter geometry? How many separate "walls"?
 (NW, GG, HY, W).
- 3. How many occupants will be in the shelter and will this number change during the period of occupancy? (P).
- 4. What is the total ventilation airflow entering shelter and will it change with time? (F1).
- What is the lighting and equipment load and is it constant? (QLITE, QEQUIP).
- How long is the period of occupancy and when does it start (day of the year and time of day)? (D, HRS, LST(1)).
- 7. For each boundary, what are the values of the:
 - A. Area? (AREA).

1

7

- B. Number of layers and number of nodal points? (LAYHAX, NMAX).
- C. Interior and exterior film heat transfer coefficients? (HI, HO).
- D. Control number for the wall becking? (ASOIL).
- E. Solar radiation transmittance? (TRANS).
- F. Inclination and azimuth angles? (XI, AZ).
- 8. For each layer of each boundary, what are the values of the:

A. Thickness? (DP).

B. Nodal Point Spacet (IX).

BENERAL AMERICAN RESEARCH DIVISION



SEMERAL AMERICAN RESEARCH DOZEROS

4-2

AZ																				
ž																				
TRANS						••••					••••									
ASOIL	[]	[]	3	0	[]	[]	[]	[]]]	[]		[]	[]	[]	[]]	[]	3	
он Н													•							
Ŧ	•		•		••••		•										•			
NMAX	3	3	3	[]]	3	3	[]	3	3	[]	3	3		3	3	[]]	[]	G.
LAYMAX	[]	[]	[]		[]	[]	[]]			[]		[]		[]	[]	3]		[]
AREA																				
Boundary No.	-	2	м	4	2	9	۲	8	თ	ō	Ξ	2	13	4.	15	16	17	18	ହ	20

Figure 4-1 (Cont'd) Form Shect for Organizing Input Data

5-6-7 For each boundary

актацияль люн яналы посыллары долгособ.

windery: DP(H), DX(H), CON(Bhu/h-H-F), ROW(h/H ¹), CP(Bhu/h-F)	boundery	3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18			
DP(II), DX(II), CON		4	والمتعتد المتعدات	بالمتينة المتنبقا	American and the second se
each layer of each boundary:		-			
ğ					

Ø

2

Figure 4-1 (Cont'd) Form Sheet for Organizing Input Data

.....

OPHERAL AMERICAN REGARDER DIVERDIT



DEPUTIAL AMERICAN REPORTATION DIVISION

QEQUIP QLITE CFMIN Ē ۵. RIZ 1012 For each hour of occupancy. TA2 Hour No.

INITIAL INLET CONDITION: TAILLED'F, TAZ LILLE, TDII LILL' TDIZ LILL'F, RII LILL'ANDER CIENT

.

4

1

15-16

GUNERAL AMERICARI RESEARCH DIVITION

Figure 4-1 (Cont'd) Form Sheet for Organizing Input Data

C. Thermal Conductivity? (CON).

D. Density? (ROW).

E. Specific Heat? (CP).

- 9. If air conditioning is involved, what air flow is going through the cooler (CFMIN); what is the effective surface coil temperature (TCOIL) and the humidity ratic corresponding to this dewpoint temperature (WCOIL); what is the bypass factor (BF)? What is the amount of outside air entering the system (F2)?
- What are the initial conditions inside the shelter? (TD2, R2, TWB(1), TEFF(1). What are the initial wall temperatures? (TO).

11. What are the soil temperatures around the shelter? (TSOIL).

12. For computational purposes:

- A. How many intervals are there for which average temperatures are required, and what are their hour limits? (NOINT, INT).
- B. What time increment should shelter temperatures be calculated on? (Di).
- 13. What are the hourly values of inlet temperature and relative humidity duri occupancy? (TAP, TD12, R2). What are the values of publicancy variables (P, F1, CFMIN, QLIVE, QEQUIP)?

4.2 After the data is determined, options in the program suat be decided upon. Will the analysis include:

- 1. Initially isothermal boundaries: (IDATA(1)).
- 2. Adiabetic or non-adiatatic boundarier: (IDATA(6)).

3. Air conditioning: (IDAUA(7)).

4. Printout of the table of hourly valuest (DATA(11)).

GENERAL AMERICAN EXCERT ON BUSINGS

4.7

5. Constant or time-varying occupancy variables? (IDATA(12)).

6. Constant or time-varying inlet conditions? (IDATA(13)).

4.3 Once the data has been determined and the options have been chosen, initial conditions in the shelter system must be set. Four quantities must be given to specify the shelter atmosphere: dry-bulb, wet-bulb and effective temperatures, and the relative humidity. It is mandatory that these values correspond to each other.

Initial well temperatures should approximate the initial shelter drybulb temperature within a few degrees. While stability of solution is not a problem in the code, initial conditions should be fairly accurate so that the number of calculations required to eliminate the errors introduced by the incorrect estimate of the shelter and boundary temperatures is minimized. 4.4 After all values necessary for an analysis have been determined, the code user is ready to create the data deck. The format of each data card and the order of the cards is indicated in Figure 3-2. Of course, the order of the deck is of major importance and an identification on each data card will help keep it in its correct position.

4.5 The SHEP code is written in FORTRAN IV specifically for the CDG 3600 computer system and, therefore, utilizes certain library functions. These include:

Form	Definition
ABST (X)	Absolute value of X
ATAN(X)	Arctangent X rediens
cos(x)	Cosine X radians
EXP(X), EXPE(X)	e to the X- power
31K(X)	Sine X radians
SQRT(X)	Square root of X
TANF(X)	Tangent X redians

BENEMAL AMERICAN PERSANCH DIVERSON

If the code is re-written for another computer system, these library functions, or their equivalents, must be supplied.

..

....

4.6 If the values of certain input data and certain computed variables exceed specified ranges, error messages will appear in the output as per Table III, p. 2-16.

The SHEP code requires two memory banks (o, locations) for the code and the accompanying matrices; in fact, the AINV matrix, which contains the inverted matrices of the temperature coefficients in the boundary heat-transfer equations, fills one bank (76,400 out of 77,777 (octal) words). Thus, a BANK statement is another requirement. There are only two computer systems other than the 3600 that have this amount of storage known to the authors at the time of this writing; they are the CDC 6600 and the UNIVAC 1108. Although several smaller computers can be adapted and enlarged, this requires special facilities. Therefore, in terms of storage requirements, the SHEP code can be run on any of these three computing systems.

BENGTAL ANT HOAN BERGAROR DERING

4.9

SECTION 5

INTERPRETATION OF OUTPUT

The output of the SHEP program is a tabulation of the instantaneous values of the thermal loads affecting the shelter and the shelter psychrometric condition for the last increment of each hour of occupancy, see Figure 5-1. It must be remembered that these values are instantaneous and, while they reflect trends in the shelter system, interpolation between hourly values may be invalid. Also, hourly thermal loads determine the resultant shelter temperature, not vice versa. The 3600 computer system printer includes a procedure for rounding output to the format specified. Thus, the thermal loads are rounded in value to the nearest integer.

The air conditioning, boundary and condensation heat loads, when positive, represent energy lost from the shelter system; all other positive loads are energy additions. In the SHEP code, the assumptions associated with the calculations of the air conditioning, moisture condensation, and transmitted solar radiation loads generally lead to conservative estimates of these loads.

Naximum and minimum shelter temperatures and the hours of their occurrence are indicated. Average temperatures are computed for the entire occupancy period, for each full day of occupancy, and for specific intervals determined by the code user.

веневал амерноат навранан окушет.

							•	_					
· ···		41 ¥ 7		FOUPANS AC	TIVITY LEVE	L 40	9 B	ТU/НА -	-00	CUPANT			
· ·····				VALUES A	RE FOR LAST	TIPE INCR	емен	TOF	EACH	NOUR			
· · · · ·							ι	OADS	(87	U/HR}			, <u>.</u>
TIME HATE	Dal Deg	WST DEC	ET Deg	ALECOND	HOUNDARY	CONDEN	•.	TRAN: SCLI	S. M LR	ETABOLIC SENSIBLE	METABOLIC LATENT	LIGHTING	EDUIPHENT
2 15.0	71.0	70.4 70.4	71+1 71+4	240542 243428	-8124 -35143				:	281517	126522	6250	
4 15+6	71.4	79.4	71+0	211179	-7494	i				261365	126678	6250	
	71.3	70.1	76.8	204-11	-4419	6			:	296442 289>93	114649 127302	6250 6251	5000
	71.1	70.7	71.6	214427	-47117 3941				:	291142	118693	6250	5000 ⁻
\$ 15+8 9	71.0	70.4	71.2	249394	*18241	6			i	284033	129348	4250	9000
10 15.0	72.4	79.5	71.6	243330	5697				ů –	278060	129512	6250	5900
12 15.9	73.5	72.4	73-0	293154 321451	22807 34356	1				273733 278817	132668 135046	6250 6250	5040. <u>.</u> 5000
14 15.0	74.0	72.4	73.3 73.1	303465 322330	35375 52929	-3934 -11892			3	279558	135308	6250	
	74.7	72.4	73.6	334872	56870	0			i	265056	140358	6250	
	74.5	72.1	73.5	327599	59815	- 500 - 5			:	250239 264298	140971	. 6250	
10 17.0	74.4	72.3	73.5	329575 329452	73798	6			8	268685 267097	138600	6250 6250	5960
20 15.0 21 15.0	73.1 72.7	72.2	72.7 72.3	302115	36330	17841			i.	270315	135463	6250	5000
22 15.0	72.8	72.0	72.4	259#51	10388	0				276882	129757	6250	5000
24 15.0	71.9	71.2	71.6	247122	-0569	. 0	•		6	282276 281129	125301 126301	6250	
	R4".	DAY-BULB	TEMP.	BURING OC	UPANCY	74.7 AT	15 /	IOURS	AFTE	R BEGINNING	OF OCCUPA	NCT	A
· · · · · · · · · · · · · · · · · · ·	MIN.	041-3018	TEMP.	DURING DO	UPANCY	71.1 AT	7 1	OURS	AFTE	A BEGINNING	OF OCCUPA		
•••••••••••••••••••••••	MAX.	467-3UL&	TEMP.	DURINS DC	UPANCY	72.4 AT	16 4	IOURS	AFTE	R BEGINNING	OF OCCUPA	NCT	а а
•• •••••••••••••••••••••••••••••••••••	MIN,	¥£1-9518	TERP.	DURINS CO	UPANCY	70.1 AT	5 1	10URS	AFTE	R BESINAING	OF OCCUPA	NCY	1
*********	MAX (EFFECTIVE	TERP.	DURINS OC	UPANCY	73.6 AT	16 1	IOURS	AFTE	R BEGINNING	OF OCCUPA	NCY	м
•••••••••••••••••••••••••••••	R18	EFFECTIVE	TEXP.	DURING OCO	UPANCY	30.7 AT	7 1	-	AFTE	R BEGINNING	OF DCCUPA	NCY	a
					• • • • • • • • •								
					-								
*** · · · · · · · · · · · · · · · · · ·											•••	· · · • • • • • • • • • • • • • • • • •	
				• ••		÷							······
*************** *********************						•••							• • • • • • • • • • • •
•••••					· ····	• ••						••••••	
				• •••	• • • • • •								
•••••••				-	· ···· ·							•	
·····					VERACE TEPS		-			••••			••••
• • • • • • • • • • • • • • • • • • • •					. of of olday	englyns if	LÁL	, 		WPT			z
		-	~ 23-1-	E PURAIN;		4	-	7	2.8	71,4	72.2	·····	e
		ទីដូរ	R EACH	DAT OF OCC	UPANCT					74.4			
•••••	•				····	. UA		. 1	¢ • 0	1.1	****		e
		F DI	N SPESI	FIC INTERV	ALD		ن 6	7	1.8	75.4	71.2		c
************				· · ·			15 24	7	3,3	71.7 72.0	72.6 72.5		1
•••••	-						18	7	4.2	72.3	73.3		د
••••••						•••					•		\$
·····												• ··· •••	e
••••••						••					-		

Figure 5-1 Typical Output of SHEP Code

. •

GENERAL AMODELARS IT DEAMSTRE OF COMPANY

SECTION 6

SAMPLE PROBLEM

To illustrate the use of the SHEP code, a shelter defined by the values listed in Table IV is considered. A sketch of the sample shelter is shown in Figure 601; the rectangular shelter area is in the basement of a multistory building. It is defined by eight opaque boundaries, four of which are multi-layered; three are soil-oacked, two boundaries are exposed to ambient air, and the remaining three are exposed to interior spaces. See Figures 2-1 and 2-2. Occupancy is limited to 1000 persons for 24 hours at a constant ventilation rate of 15 cfm/occupant. The air conditioning system is assumed to be operating during occupancy with a unstant airflow rate of 8 cfm-occupant and the shelter lighting and equipment add a constant thermal load of 11,250 Btu/hr. The weather affecting the shelter is that which occurred at Montgomery, Alabama during 1 August, 1963.

The output of this shelter analysis is shown in Figure 501. It can be seen that the shelter temperatures wary in a diurnal cycle, as would be expected; they are lowest in the early norming and are highest in the late afternoon. Air conditioning also can be seen to wary directly with the shelter temperature. In the cooler hours of the day, i.e., from 10 PN to 9 AM, the shelter boundaries are warmer than the shelter atmosphere, and energy is transferred from the boundaries to the shelter air, as is indicated by the negative signs on the boundary heat losses for these hours. During the other hours of the day, the shelter is warmer than the boundaries and energy leaves the shelter.

If the value of condensation heat loss is negative, this corresponds to evaporation of the condensate on the walks, and an addition of energy to

BENERAL ARAUNDATE REPORTUSE DIVISION



TABLE IV (Cont'd)

SAMPLE INPUT DATA

For each boundary

. 27.90.0 11.80.0 1.1.1.1.1.1 -----10.1.1.1 ----Sec. A ----ALL LI 1911111 -----~ ~ ~ ~ ~ ~ -----Ϋ́ 0.0 0.0 -----...... ------------------------- $\tilde{\times}$ 0.000 0.000 111011 TRANS 1110111 Less -----11011 ---------ASOIL • ß S E B 1 3 ٦ 1 1 1 1.46 90-11 1 0 21-0 0.1 1 21.01 - 101 - 1 TUNT 1101 ę 20.11 31.46 1.946 1.46 1.46 1.9.46 1.00 5,01.LL ----11811 11.1 ---------1.011 Ī NMAX 30 **BT** 20 নি 3 61 F R 7 . LAYMAX [] $\left[\begin{array}{c} \bullet \\ \bullet \end{array} \right]$ 3 ß 2 F Π 1 -1 11 . 1 <u>0...57.6.</u> 6.70.0 . 67.0.0 0.0.0.0.1 1.3.40.00 0'-'0'5' 1.90.5,0,-0 ----191111 AREA -----191111 ----Boundory No 8 0 ω Ø N <u>m</u> g

A support of the second se

5-6-7

TABLE IV (Cont'd) SAMPLE INPUT DATA

8 For each lover of each buundary DP(H), DX(H), CON(Bhu/Nr-H-9F), ROW(Ib/H), CP(Bhu/Ib-9F)

			4 ·		•	
	1 2 3 4 5 6 7 6 9 10 11 12 0 4 15 16 17 18 18 18			IAA 83144. 48. 28. 28. 28. 28. 28. 18. 30. 19. 30. 19. 30. 1. 4. 4. 4. 4. 4. 4. 4. 4. 4. 4. 4. 4. 4.		
_		•				

.

1. Same 2.

saude i deve present termeter e la sistema de da la culture

TABLE IV (Cont'd) SAMILE INPUT DATA თ

NITIAL CONDITIONS' TD2 (81.00 F, R2 (0.173, TWB(I) (23.3 F, TEFF(I))23.0 F



. 0

GENERAL AMURICAN RECTARCH DIVICION

TABLE IV (Cont'd)

"The second state of the second state of the second s

SAMPLE INPUT DATA



GUNDHAL AMERICAN RECEARCH DRAFTER

15-16

4



Figure 6-1 Sketch of Shelter Area Used in Sample Problem

the shelter temperature. Positive value of the condensation heat load indicates moisture is condensing on the shelter boundaries and energy is being removed from the shelter air. There is a check in the code to prevent the amount of re-evaporated moisture from exceeding the amount previously condensed.

Metabolic loads are predicted, using the relations developed by Houghten⁽⁵⁾, based on both the shelter dry-bulb and effective temperatures. Since these vary by only a few degrees during occupancy, the total metabolic load for each hour is approximately constant.

GENERAL AMERICAN REPEARCH DIVISION

SECTION 7

REFERENCES

- 1. The American Ephemeris and Nautical Almanac, 1968, U. S. Government Printing Office, Washington, D.C., 1966, pp. 19-33.
- 2. International Critical Tables of Numerical Data, Physics, Chemisury, and Technology, McGraw-Hill, New York, 1926, p. 391.

×

- Breck, R. S., "Shelter Air-Conditioning Unit", Final Report, SRI Subcontract No. B81882(4949A-11)-US, OCD Work Unit 1425B, Carrier Air Conditioning Company, Syracuse, New York, February, 1967.
- 4. <u>ASHRAE Handbook of Fundamentals, 1967</u>, published by the American Society of Heating, Refrigerating & Air-Conditioning Engineers, Inc., New York, Cap. 7, p. 117.
- Houghten, F. C., et. al., "Heat and Moisture Losses From the Human Body and Their Relation to Air Conditioning Problems", American Society of Heating and Ventilation Engineers, <u>Transactions</u>, Vol. 35, 1929.
- 6. <u>ASHRAE Guide & Data Book, 1963</u>, published by the American Society of Heating, Refrigerating & Air-Conditioning Engineers, Inc., New York, Chap. 26, p. 469.
- Threlkeld, J. L., <u>Thermal Environmental Engineering</u>, Prentice-Hall, Inc., Eng. ewool Cliffs, N. J., p. 330.
- 8. Parmalee, G. V., "Irradiation of Vertical and Horizontal Surfaces by Diffuse Solar Radiation from Cloudless Skies", <u>Heating</u>, <u>Piping</u> and Air Conditioning, p. 133, August, 1954.
- 9. Jakob, Max, Heat Transfer, John Wiley & Sons, New York, 1949.

GENERAL AMERICAR REPRATICAL DIVIDICAL

APFENDICES

GENERAL AMERICAN RESEARCH DIVISION

RUCHUZ WURNISHIE HEBENHEN DIAID

APPENDIX A

.

LETERMINATION OF SHELTER ENVIRONMENT

The study of the interrelationships among ventilation rate, thermalload, and boundary losses in the shelter is based on the assumption that the shelter atmosphere may be represented by one psychrometric condition. A shelter model that will take into account the thermal effects of solar radiation, air-conditioning, moisture condensation and re-evaporation, and boundary losses is developed according to the following assumptions:

- 1) the air within the shelter is completely and instantaneously mixed;
- the film heat transfer coefficients are constant for any one boundary surface;
- 3) the radiative energy transfer within the shelter can be neglected;
- 4) the condition of the air exhausted from the shelter is the condition of the shelter atmosphere;
- 5) the thermal and physical properties of the structural materials and of air are not temperature-dependent;
- 6) the incident solar radiation is absorbed on the outer surface of the boundaries and appears as couducted energy or is transmitted into the shelter and is considered an instantaneous load with the lighting and equipment loads; and
- 7) the thermal loads and the psychrometric states of the inlet and exhaust air are constant over short time intervals.

The shelter model is therefore a volume enclosed by boundaries into which sensible and latent heat loads and ventilating air are introduced and from which air is exhausted and energy is lost, see Figure A-1. The governing equations of the enclosed volume are derived from the conservation of mass and the conservation of energy.

BENERAL AMERICAN RESEARCH DIVISION

A-1



Figure A-1 Shelter Shorgy Transfor

GENTRAL AMERICAT CORAREM DIVIDICIO

A-2

$$\frac{\partial}{\partial t} (H) + \frac{\partial}{\partial t} (H_g) + \frac{\partial}{\partial t} (Q_H + Q_L + Q_g) - \frac{\partial}{\partial t} (Q_W + Q_{AC}) = 0 \quad (1)$$

where H = enthalpy of the exchanged air, Btu

 H_g = enthaly; of the suelter, Btu

Q = metabolic energy of occupants, Btu

Q_r = energy due to shelter lighting, Btu

Q = energy due to other shelter equipment, Btu

Q, = energy conducted through shelter boundaries, Btu

 Q_{AC} = energy removed from shelter system by air conditioner, Btu Integrating equation (1) over the time increment S^{+} yields

$$(H_1 - H_2) + (H_{S,1} - E_{S,2}) + Q_M + Q_L + Q_E - Q_W - Q_{AC} = C$$
 (2)

where the subscripts-1 and 2 refer to	o the br	ing and the end of the
time increment, respectively. Althou	•	lysis is time-varying
in the sense that results up ug		increments represent
changing conditions, by assume	. •	ermal load values and the
psychrometric states of	``	in this equation are all
considered (×	increfore, there is no
best-storms terr		4 C = O.

Conservation was well option with the dry air and the vater vapor in the shull the vapor:

 $\frac{\partial f}{\partial t}(\mathbf{K}^{1}) + \frac{\partial f}{\partial t}(\mathbf{K}^{1/2}) \xrightarrow{\mathcal{I}_{1}} (\mathbf{M}^{1/2}) - \frac{\partial f}{\partial t}(\mathbf{K}^{1/2} \text{OMD}) = 0$ (3)

where

 N_V = mass of water wapor in the exchanged air, 1b.

NV,N • mass of vator vapor introduced by the shelter occupents, 1b.

N.S = mass of water wapor in the shelter air, 1b.

W, COND * mass of water vapor removed by condensation, 1b. Integration yields

$$(M_{V,1} - M_{V,2}) + (M_{V,3,1} - M_{V,3,2}) + M_{V,N} - M_{V,CORD} = 0$$
 (4)

DENERAL AMERICAN RESEARCH DIVIDION

The energy balance for dry air in the system is given by

$$\hat{\mathcal{F}}(M_a) + \hat{\mathcal{F}}(M_{a,a}) = 0 \qquad (5)$$

where

M = mass of dry air in the exchanged air, 1b. $M_{a,5}$ = mass of dry air in the shelter air, 1b.

$$(M_{a,1} - M_{a,2}) + (M_{A,3,1} - M_{a,3,2}) = 0$$
(6)
$$\delta Q = H_1 + H_{S1} + Q_1 + Q_2 - Q_3 - Q_{AC}$$
(7)

Let

or

$$M_{V,0} = M_{V,1} + N_{V,S,1} + V_{V,H} - M_{V,COND}$$
 (8)

(7)

$$M_{a,0} = M_{a,1} + M_{a,a,3}$$
 (9)

chen

å

$$Q = H_2 + H_{8,2}$$
 (10)

$$H_{V,0} = H_{V,2} + H_{V,8,2}$$
 (11)

$$= X_{a,2} + N_{a,3,2}$$
 (12)

Nov

$$H_{s,2} = M_{a,s,2} h_{u,s,2} + N_{v,s,2} h_{v,s,2}$$
 (13)

and

$$H_2 = M_{a,2} h_{,2} + M_{v,2} h_{v,2}$$
 (14)

where the lower case h's refer to specific enthalpies (Btu/1b).

Since the ventilating air locves at the shelter condition,

$$h_{A,2} = h_{B,8,2}$$
 (15)

and

$$h_{V,2} = h_{V,5,2}$$
 (16)

Substituting this value for the incremental energy 6 Q:

$$\delta Q = K_{a,0} h_{a,8,2} + K_{y,0} h_{y,8,2}$$
(17)

AMERICAN REBEARCH DIVISION

New specific enthalpies of dry air and water vapor may be given as functions of dry-bulb temperature:

$$\begin{array}{c} h_{a} = 0.24 \ T_{db} \\ \text{and} \\ h_{v} = 1061.0 + 0.444 \ (T_{db}) \end{array} \right\} \begin{array}{c} (18) \\ \text{for } 32.2^{\circ p} \leq T_{db} \leq 150^{\circ p} \\ (19) \end{array}$$

Combining equations (17) through (19) and solving for the dry-bulb temperature leads to

$$T_{db} = \frac{\delta Q - 1061 My_0}{0.444 M_{V,0} + 0.24 M_{H,0}}$$
 (20)

This represents the shelter dry-bulb temperature at the end of the time increment $\delta \tau$.

Expressions for $M_{a,o}$ and $M_{V,O}$ can be found, since

$$H_{a,2} = 60 \dot{F}_{2} \rho_{a,2} \delta \tau$$
 (21)

$$\mathbf{M}_{\mu \rho} = 60 \, \dot{\mathbf{f}}_{\rho} \rho_{\mu \rho} \, \delta \tau \qquad (22)$$

$$K_{a,a,2} = V_{\rho_{a,a,2}}$$
(23)

and $K_{V,S,2} = V \rho_{V,S,2}$ (24)

where V = shelter volume, ft³

 $P_{a,2} = \text{density of dry air leaving shelter, 1b/ft}^{3}$ $P_{v,2} = \text{density of water vapor leaving shelter, 1b/ft}^{3}$ $P_{a,3,2} = \text{density of dry air in shelter, 1b/ft}^{3}$ $F_{v,3,2} = \text{density of water vapor in shelter, 1b/ft}^{3}$

and $f_2 = \text{mass flow rate of exhaust air, 1b/hr.}$

SENVIAL AMERICAN PERSANCH DIVISION

A-5

We have assumed that

$$\rho_{\mathbf{x},2} = \rho_{\mathbf{x},\mathbf{s},2} \tag{25}$$

and

Pv,2 = Pv, s,2 (26)

Therefore, we obtain the expression:

$$M_{V,0} = \rho_{V,2} (60 \dot{F}_2 \delta \tau + V)$$
 (21)

and
$$k_{a,o} = \rho_{a,2} (60 \dot{F}_2 \delta \tau + V)$$
 (28)

Now, when these equations are solved for the ventilation rate \tilde{F}_{22}

$$\dot{\mathbf{y}}_{2} = \frac{\mathbf{x}_{a,0} - \rho_{a,2}\mathbf{v}}{600\tau \rho_{a,2}} = \frac{\mathbf{x}_{V,0} - \rho_{V,2}\mathbf{v}}{600\tau \rho_{V,2}}$$
(29)

It is assumed that the densities of dry air and of water wappr may be determined from the perfect-gas law: Therefore,

$$P_{V} = \frac{P_{V}}{R_{V} (T_{db} + 459.69)}$$
(30)

anó $P_{a} = \frac{P_{b} - P_{v}}{R_{a}(r_{db} + 459.69)}$ (31)

and

where P_b = barometric pressure, 1b/it²

 P_v = partial pressure of water vapor, lb/ft^2 R_ = gas constant for water waper, ft-lb/lb mole - "R R = gas constant for dry-air, ft-lb/lb mols - "R and P. = (9.8 x 10⁻⁷) A² - 0.0799 A + 2116.2 (32) with altitude, ft. vbere Now, the partial pressure of water wapor is expressible as Py + r Mg (32)r - relative humidity in the sheltor where Pg = saturation pressure of water wappr, 1b/ft²

BENETAL AMERICAN PUSEARCH CIVISION

Saturation pressure varies with dry-bulb temperature according to

$$P_{g} = 5.132 \exp(0.0329 T_{db})$$
 (34)

Using the values

 $R_a = 53.35 \text{ ft-lb/lb mole - }^{\circ}R$ and $R_c = 85.71 \text{ ft-lb/lb mole - }^{\circ}R$

leads to

$$P_v = r (5.132 \exp (0.0329 T_{db}))$$
 (35)

$$P_{v} = \frac{r}{(T_{db} + 459.69)} (0.05987 \exp(0.0329 T_{db}))$$
 (36)

and $\rho_{a} = \frac{1}{T_{db}^{-*} + 459.69} \int 1.84 \times 10^{-8} - 0.00142A$.

+
$$35.68 - r(0.0962 \exp(0.0329 T_{db}))$$
 (37)

Since

$$\frac{H_{a,c}}{\rho_{a,2}} = \frac{H_{v,o}}{\rho_{v,2}}$$
(37)

from equations (27) and (28), we can evaluate the last three equations to obtain

$$P_{v} = \frac{P_{b}}{1 + 0.6224 \left(\frac{B_{1}0}{P_{v,0}}\right)}$$
(39)

Relative humidity, as given by equation (33), becomes

$$\frac{P_{b}}{(5.132 * (0.059 * db)) (1 + 0.6224 (N_{b,0}/N_{1.0}))}$$
(40)

To summarize, the two equations permissary to compute the shelter condition are (20) and (40). The quantities in these equations may be computed as outlined above. Although the dry-bulk temperature and relative humidity uniquely determine the condition of the shelter air,

GENERAL AMERICAN REBEARCH STURNOW

A-7

it is desired to express this condition in terms of dry-bulb temperature and wet-bulb temperature.

The wet-bulb temperature can be determined using the Carrier equation:

$$P_{V} = P_{S}' - \left(\frac{(P_{b} - F_{s}')(T_{db} - T_{wb})}{2800.0 - 1.3 T_{wb}}\right)$$
(41)

where

P_S = saturation pressure at wet-bulb temperature, lb/ft² T_{wb} = wet-bulb temperature, *F

 P_{S} may be evaluated from equation (3⁴) as

$$P_{s} = 5.132 \exp(0.0329 T_{vb})$$
 (42)

 P_v is obtained from equation (39). Equation (41) is then a transcendental equation in T_{wb} and may be solved by an iteration procedure. After both the dry-bulb and wet-bulb temperatures are known, the effective temperature may then be calculated from

$$ET = \frac{107.5 T_{db} - 45.2 T_{wb}}{62.3 + T_{db} - T_{wb}} \qquad for \begin{cases} 45^{\circ}F \le T_{db} \le 110^{\circ}F \\ 30^{\circ}F \le T_{wb} \le 100^{\circ}F \end{cases}$$
(43)

GENERAL AMERICAN REBRARCH DIVISION

APPENDIX B

DETERMINATION OF SOLAK RADIATION INTENSITY

B-1 Determination of the Sun's Altitude and Azimuth Angles

Consider an earth-centered right-handed rectilinear coordinate system with the Y-axis directed toward the sun and with the X-Y plane that of the equator, see Figure B-1. The unit normal vectors \mathbf{i} , \mathbf{j} , and \mathbf{k} are parallel to the X, Y and Z axes, respectively. The rays of the sun are parallel to the unit vector \mathbf{s} . The unit vector \mathbf{n} at a point on the surface of the earth P is normal to the position vector of P and oriented toward the north pole. The position vector is parallel to the unit vector \mathbf{r} . The point P is located on the surface of the earth by the hour angle, Θ , and the latitude angle, \oint .

Now
$$\vec{r} = \cos \Phi \sin \Theta \vec{i} - \cos \Phi \cos \Theta \vec{j} + \sin \Phi \vec{k}$$
 (1)
 $\vec{i} = \cos \eta \vec{j} + \sin \eta \vec{k}$ (2)

where: $\tau_i =$ declination angle of the sun

The sun's remith angle, ψ , is given by

 $\psi = \operatorname{arc} \cos(\overline{r} \cdot \overline{s})$

= arc cos (sin Φ sin η = cos Φ cos θ cos η) (3) The sun's altitude angle, 3 , is

Thuc

 $\beta = \arcsin \left(\sin \phi \sin \eta - \cos \phi \cos \theta \cos \eta \right) (5)$

Now the vector n is

 $\vec{n} = -\sin \Phi \sin \Theta \vec{i} + \sin \Phi \cos \Theta \vec{j} + \cos \Phi \vec{k}$ (6) Tuking $\vec{n} \cdot \vec{s}$, since $\vec{n} \cdot \vec{r} = 0$, gives

 $\vec{n} \cdot \vec{s} = \sin \Phi \cos \phi \cos \eta + \cos \Phi \sin \eta \qquad (7)$

BENERAL AMERICAN RETEARCH DIVISION



٦,

.

Also $\vec{n} \cdot \vec{s} = \cos T \cos \beta$

where: T = sun's azimuth angle.

Therefore,

 $T = \arccos \left[\sec \beta (\cos \Phi \sin \eta + \sin \Phi \cos \Theta \cos \eta) \right]$ (9) Thus the sun's altitude and azimuth angles are determined as a function of latitude, Φ , solar declination angle, η , and time angle, Θ .

(8)

B-2 Solar Declination Angle and Time Angle

The solar declination angle, η , is given as a function of the day of the year, see Figure B-2. This variation was approximated by the following function, namely,

$$\eta = 0.410 \sin \left[\frac{\pi}{182.5}(-80)\right]$$
 (10)

where: D = day of the year, 1 to 365.

The time angle, Θ , is denoted by

$$\Theta = \frac{\pi}{12} \left(T_{\text{solar}} \right) \tag{11}$$

where

T_{solz} = solar time, hrs, see Section 2.2.

B-3 Argle of Surface to Sun's Rays

Consider a tilted plane surface at an angle, ξ , to a vertical surface at a point P on the surface of the earth, see Figure B-3. The unit normal to the tilted surface, \overline{n}_{g} , is at the angle ξ to the normal to the vertical surface which makes an angle, T - a, with respect to the projection of the sun's rays on a horizontal surface at point P. If a right-handed rectilinear coordinate system is defined at point P, such that the X-axis is parallel to the direction of the projection of the sun's ray, ξ , on the horizontal plane and the Y-axis is parallel to the vertical plane, the X-Z planeis the horizontal plane. Let the unit

B-3


B-4



•

B-5

vectors $\vec{1}$, \vec{J} and \vec{k} be directed along the X, Y and Z axes, respectively. Then the unit normal to the tilted surface, \hat{n}_{g} , is

 $\vec{n}_{a} \approx \cos(T-a) \cos \xi \vec{i} + \sin \xi \vec{j} + \sin(T-a) \cos \xi \vec{k}$ (12)a = azimuth of the normal to the vertical surfa Wile : 31 measured westward from north = azimuth of sun measured westward from north with $\vec{s} = \cos \beta \vec{1} + \sin \beta \vec{j}$ Then $\vec{s} \cdot \vec{n} = \cos \beta \cos(T-a) \cos \xi + \sin \beta \sin \xi$ (13) but $\vec{s} \cdot \vec{n} = \cos \alpha$ (14)where: α = angle between the normal to the tilted surface and the sun's rays Therefore $\alpha = \arccos \left(\cos \beta \cos(T-a) \cos \xi + \sin \beta \sin \xi \right)$ (15) B-4 Sunrise and Sunset Values of Hour Angle At sunrise, $\beta = 0$; then from equation (5) have $0 = \arcsin(\sin\phi\sin\eta - \cos\phi\cos\theta_{\rm cos}\eta)$ $\Theta_{\perp} = \arccos(\tan \phi \tan \eta)$ (16) or where: Θ_{p} = value of Θ at sunrise However, the relation $-1 \leq \tan \phi \tan \eta \leq 1$

must hold.

BENERAL AMERICAN HEBEARCH DIVISION

Now the calculation of solar radiation is restricted to the northern hemisphere:

$$0 \le \phi \le \frac{\pi}{2} \tag{17}$$

and, from Figure B-2, η varies as

$$-0.410 \le n \le 0.410$$
 (18)

Thus, to satisfy the restriction on the ${\mathscr Q}$ and η values, the ranges must be

$$\phi + \eta \leq \frac{\pi}{2} \tag{19}$$

$$\Phi \leq \frac{\pi}{2} \tag{20}$$

Since η is a function of the day of the year, these restrictions: indicated that there is a maximum value of latitude, Φ , that can be considered at each day of the year, see Figure 3-1.

The value of the hour angle for sunset, Q_{μ} , is

$$\Theta_{\mu} = 2\Pi - \Theta_{\mu} \tag{21}$$

Thus, for $\Theta_r \leq \Theta \leq \Theta_s$ there can be some form of solar radiation upon a surface as long as $0 \leq \beta \leq \frac{\pi}{2}$.

B-5 Intensity of Solar Radiation

The intensity of solar radiation that will be incident upon a surface is given by

$$I = I_{DIR} + I_{DIF} + I_{RFF}$$
(22)

where:

and

X_{DIR} = intensity of direct solar radiation

- IDIF = intensity of diffuse solar rudiation
- HEF intensity of solar radiation reflected from the ground and surrounding surfaces onto the surface -

GENERAL AMERICAN REPEARCH DIVIRION

The assumption is made that the reflected solar radiation from the surroundings is negligible, $I_{\text{REE}} = 0$.

Thus $I = I_{DIR} + I_{DIF}$

The direct solar radiation is given by

$$I_{DIR} = \begin{cases} I_{DN} \cos \alpha & 0 \le \alpha \le \pi/2 \\ 0 & \alpha > \frac{\pi}{2} \end{cases}$$
(24)

where: I = intensity of direct normal solar radiation; i.e., the direct radiation on a surface normal to the sun's rays.

The intensity of the direct normal solar radiation, I_{DN} , is given as a function of the sun's altitude angle, β , (from Reference 6), see Figure B-4. The data are approximated by the relationships

$$I_{DN} = \begin{cases} 294 \ (1-e \ \frac{7}{\pi}\beta) & \text{for clear air} \\ 200 \ (1-e \) & \text{for industrial air} \end{cases}$$
(25)

for $\beta > 0$.

The intensity of the diffuse solar radiation is assumed to be defined by

 $I_{DIF} = I_{DIF,V} + (I_{DIF,H} - I_{DIF,V}) \sin \xi$ (26)

where: $I_{BIF, V} =$ intensity of diffuse solar radiation on a vertical surface

IDIF,H = intensity of diffuse solar radiation on a horizontal surface.

The ratio of the intensity of diffuse solar radiation on a vertical surface to the intensity of diffuse solar radiation on a horizontal surface is given as a function of the cosine of the angle between the normal to the vertical surface and the sun's rays (from Reference 7), see Figure B-5.

GENERAL AMERICAN REGEARCH DIVIDION



GENERAL AMERICAN REPEARCH DIVISION

B-9



The results are approximated by

$$\frac{I_{DIF,V}}{I_{DIF,H}} = \begin{cases} 0.44 & \text{for } \cos\beta\cos(T-a) \leq -0.4 \\ 0.625 [\cos\beta\cos(T-a)]^2 + 0.525 \cos\beta\cos(T-a) + 0.55 & (27) \\ 0.35 [\cos\beta\cos(T-a)]^2 + 0.45 \cos\beta\cos(T-a) + 0.55 \\ 0.35 [\cos\beta\cos(T-a)]^2 + 0.45 \cos\beta\cos(T-a) + 0.55 \\ \text{for } \cos\beta\cos(T-a) + 0.55 \\ \text{for } \cos\beta\cos(T-a) \geq 0 \end{cases}$$

Then

$$I_{DIF} = I_{DIF,H} [(1 - \sin \xi) f (\beta, \gamma - a) + \sin \xi]$$
 (28)

The ratio of the total intensity of solar radiation, I_{TH} , on a horizontal surface, to the intensity of diffuse solar radiation on a horizontal surface, $I_{DIF,H}$ is given as a function of the direct normal solar radiation intensity (from Reference 8), see Figure B-6. The relationship can be approximated by

$$\frac{I_{\text{TH}}}{I_{\text{DIF},\text{H}}} = 0.667 \times 10^{-6} (I_{\text{DN}})^3 - 1.5 \times 10^{-4} (I_{\text{DN}})^2 + 0.0183 (I_{\text{DN}}) + 1 (29)$$

It may be assumed that

$$I_{TH} = I_{DIR,H} + I_{DIF,H}$$

= $I_{DN} \sin \beta + I_{DIF,H}$ (30)

Therefore,

$$I_{DIF,H} = \frac{I_{DN} \sin \beta}{I_{TH} - 1}$$
(31)

Combining equation (31) and equation (28) gives

$$I_{DIF} = \frac{\sin \beta \left[\left(\beta, T - a \right) \left(1 - \sin \xi \right) + \sin \xi \right]}{0.667 \times 10^{-6} \left(I_{DH} \right)^2 - 1.5 \times 10^{-4} \left(I_{DH} \right) + 0.0183}$$
(32)

with total radiation on a surface given by equation (22).

BENERAL AMERICAN RESEARCH DIVIBION

8-11



APPENDIX C

BOUNDARY ENERGY TRANSFER AND NODAL TEMPERATURE COEFFICIENTS

Beat transfer by conduction through the shelter boundaries is determined by the temperature of each boundary inner surface. To calculate these temperatures, the temperature profile through each boundary is determined by the solution of a set of implicit finite-difference equations. Since each boundary may be multi-layered (up to 5 layers), the nodal point coefficients must be determined individually for each layer.

For this solution, a layer is divided into slats δX thick. A temperature nodal point is assigned to the node of each slab; for the interior slats, this point is at the midpoint of each slab, and for the innermost and outermost slabs, there is another point at the surface of the slab. If the boundary under analysis is multi-layered, a similar nodal point array accompanies each layer.

Nodal point temperatures are determined by the appropriate heat transfer equation at each nodal point. There are four basic heat balances that can decur at a node; the one to be used depends on the position of the node in question. These four positions s = (1) at the inner surface of the boundary; (2) in the interior of any layer of the boundary; (3) at an interface between layers of the boundary; and (4) at the exterior surface of the boundary, see Figure C-1. Forsition 3 - at the inner surface of a boundary. The heat transfer

in this case is by convection with the shelter air and by conduction

BENERAL AMERICAN RERLARCH DIVISION

C-1



.

•

4

GENERAL AMERICAN RESEARCH DIVISION

c-s

with the next slab in the layer. Heat transfer due to moisture condensation may also be present, see Appendix D. The general heat balance for deriving the various nodal point temperature equations is

 $\begin{bmatrix} energy entering slab n \\ frcm preceding slab (n-1) \end{bmatrix} = \begin{bmatrix} energy leaving slab n \\ to succeeding slat (n+1) \end{bmatrix} = \begin{bmatrix} energy stored \\ in slab n \end{bmatrix}$

For position 1, the equation becomes:

$$q_{\text{condensation}} + q_{\text{convection}} = q_{\text{stored}}$$
 (1)

or
$$C + h_i (T_{ab,s} - T_n) - \frac{k}{\delta x} (T_n - T_{n+1}) = \frac{\rho O \delta x}{2 \delta \tau} (T_n - T_n')$$
 (2)

where

C = condensation term, see Appendix D.

 $h_i = interior film heat-transfer coefficient, Btu/hr-ft²-°F$

 T db,s = dry-bulb temperature of shelter, °F

 $T_n = temperature of node n, *F$

k = thermal conductivity of layer material, Btu/hr-ft - F

 $\delta x =$ thickness of slab in layer, ft.

 $T_{n+1} = temperature of node (n + 1), F$

 ρ = density of layer material, lb/ft³

 C_{p} " specific heat of layer material, Btu/lb

 $\delta \tau = time increment, hr.$

 $T_n = temperature of node n in preceding time increment, *F.$

The matrix solution of simultaneous equations requires that the coefficients of the nodal temperatures are dimensionless. Therefore, the transformed energy balance for the inner surface nodal point is

$$(1.0 + \frac{k}{h_{i}\delta x} + \frac{\rho c_{p}\delta x}{2 h_{i}\delta \tau}) T_{n} - (\frac{k}{h\delta x}) T_{n+1} = \frac{\rho c_{p}\delta x}{2 h_{i}\delta \tau} T_{n}$$

+ $T_{db,s} + \frac{C}{h_{i}}$ (3)

GENERAL AMERICAN REBEARCH DIVISION

which in matrix element notation is

$$a_{nn}T_n + a_{n,n+1}T_{n+1} = b_n$$
 (4)

cr, since the inner surface nodal point is indexed 1,

$$a_{11} T_1 + a_{12} T_2 = b_1$$
 (5)

Position 2 - in the interior of any layer of the boundary. In this case, conduction into and out of slab n is the only heat transfer. Therefore, the energy balance becomes

$$\frac{\mathbf{k}}{\delta \mathbf{x}} (\mathbf{T}_{n-1} - \mathbf{T}_n) - \frac{\mathbf{k}}{\delta \mathbf{x}} (\mathbf{T}_n - \mathbf{T}_{n+1}) = \frac{\rho \mathbf{c}_p \delta \mathbf{x}}{\delta \tau} (\mathbf{T}_n - \mathbf{T}_n')$$
(6)

where $T_{n-1} = temperature of node (n - 1), *F$

This becomes, in dimensionless quantities,

$$T_{n-1} + \left(\frac{\left(\delta x\right)^2 \rho c_p}{k \, \delta \, \tau} + 2\right) T_n - T_{n+1} = \frac{\rho c_p \left(\delta x\right)^2}{k \, \delta \, \tau} T_n$$
(7)

which is of the form

$$a_{n,n-1} T_{n-1} + a_{n,n} T_n + a_{n,n+1} T_{n+1} = b_n$$
 (8)

Position 3 - at an interface between layers (m, and (m+1)) of a boundary.Again, the only heat transfer is conduction, but since the successive layers will have different thermal properties, the energy balance is:

$$\frac{k_{m}}{\delta x_{m}} (T_{n-1} - T_{n}) - \frac{k_{m+1}}{\delta x_{m+1}} (T_{n} - T_{n+1}) = \left(\frac{\rho_{m} c_{p,m} \delta x_{m}}{(-2)} + \frac{\rho_{m+1} c_{p,m+1} \delta x_{m+1}}{2}\right) \left(\frac{T_{n} - T_{n}}{\delta \tau}\right) (9)$$

or, in dimensionless form,

$$-T_{n-1} + (1 + \frac{k_{n+1}\delta_{x}}{k_{n}\delta_{x}} + \frac{\rho_{n}c_{pn}\delta_{x}}{2k_{n}\delta_{T}} + \frac{\rho_{n+1}c_{pn+1}\delta_{x}\delta_{x}}{2k_{n}\delta_{T}} + \frac{\rho_{n+1}c_{pn+1}\delta_{x}\delta_{x}}{2k_{n}\delta_{T}} T_{n}$$

2 x 5 T

A OXB+1 BENERAL AMERICAN REPEARCH DIVISION C-h

n+1

(10)

....

. . .

. .

....

., . . .

• --

which is of the form:

$$a_{n,n-1} T_{n-1} + a_{n,n} T_n + a_{n,n+1} T_{n+1} = b_n$$
 (11)

<u>Position 4</u> - at the exterior surface of the boundary. This case has several variations, depending on whether the external surface boundary is exposed to either soil or air.

If the boundary is backed by soil, the only mode of heat transfer will be conduction. The only difference between position 4 and position 2 is that the unknown temperatures T_{n+1} in equation (7) is replaced by the known temperature of the soil, T_{soil} , and this term, being known, becomes part of the b coefficient:

$$T_{n-1} + \left(\frac{\rho c_{p}(\delta x)^{2}}{k \delta \tau} + 2\right) = \frac{\rho c_{p}(\delta x)^{2}}{k \delta \tau} T_{n} + T_{soil}$$
(12)

If the backing of the wall is ambient air, convection enters as well as solar radiation. The energy balance is

$$\frac{k}{\delta x} (T_{n-1} - T_n) + q_{\text{solar}} - h_o (T_n - T_a) = \frac{\rho c_p \delta x}{2 \delta \tau} (T_n - T_n) \quad (13)$$

where

q solar = solar radiation load on boundary, Btu/hr.

 $h_0 = exterior film beat transfer coefficient, Btu/nr-ft²-*F$ $T_a = dry-bulb temperature of ambient air, *F$

In dimensionless form,

$$\left(-\frac{k}{h_{o}\delta_{x}}\right)T_{n-1} + \left[\frac{k}{h_{o}\delta_{x}} + 1 + \frac{\rho c_{p}\delta_{x}}{h_{o}\delta_{T}}\right]T_{n} = \frac{q_{solar}}{h_{o}} + T_{a} + \frac{\rho c_{p}\delta_{x}}{2\delta Th_{o}}T_{n}$$
 (14)

Both equations (12) and (14) are of the form

$$a_{n,n+1} T_{n-1} + a_{n,n} T_n = b_n$$
 (15)

BENERAL AMERICAN REBEARCH DIVIBION

C-5

If the wall is backed by interior air, $q_{solar} = 0$, and T_{a} is the average of the shelter temperature and the ambient temperature.

After all coefficients of all nodal points in a boundary have been evaluated, the equations are solved simultaneously using a Causs-Jordan method of matrix inversion. Convection transfer through a boundary

is then computed as

$$q_{\rm b} = h_{\rm i} \left(T_{\rm db,s} - T_{\rm i} \right)$$

. 1

. . .

....

(16)

. . .

-.

where $T_1 = \text{temperature of the inner surface nodal point and the total$ $boundary heat loss is _____ (17)$

$$Q_b = \frac{\Sigma}{\text{walls}} Q_b$$

GENERAL AMERICAN REBEARCH DIVISION

APPENDIX D

MOISTURE CONDENSATION

The process of moisture condensing on, or re-evaporating from, a surface involves both a mass and an energy transfer. The analysis used in this study parallels that of Jakob⁽⁹⁾.

The following differential equations may be set up for moving fluids, relating thermal conduction and mechanical diffusion:

$$\frac{\partial T}{\partial t} + v_x \frac{\partial T}{\partial x} + v_y \frac{\partial T}{\partial y} + v_z \frac{\partial T}{\partial z} = \alpha \left(\frac{\partial^2 T}{\partial x^2} + \frac{\partial^2 T}{\partial y^2} + \frac{\partial^2 T}{\partial z^2} \right)$$
(1)

and

$$\frac{\partial p}{\partial t} + v_x \frac{\partial p}{\partial x} + v_y \frac{\partial p}{\partial y} + \bar{v}_z \frac{\partial p}{z} = \delta \left(\frac{\partial^2 p}{\partial x^2} + \frac{\partial^2 p}{\partial y^2} + \frac{\partial^2 p}{\partial z^2} \right)$$
(2)

bere	T = absolute temperature, °F V = velocity, ft/hr p = partial pressure of water wapor, 1b/ft ²	
	a = thermal diffusivity, ft ² /hr	
	δ = mechanical diffusivity, ft ² /hr	

Newton's Law yields

$$q^{r} = -k \frac{dt}{dn}$$

and Fick's Law gives

$$\dot{\mathbf{m}}^{"} = \dot{\mathbf{o}} \frac{\mathbf{d}\mathbf{c}}{\mathbf{d}\mathbf{n}}$$

where

re q" = rate of heat flow per unit area, Btu/ft²-hr

in = rate of mass flow per unit area, 1b/ft²-hr

n = direction of heat and mass flow, ft

k = thermal conductivity of the medium, Btu/hr-ft-*F

 $c = concentration, 1b/ft^3$

GENERAL AMERICAN REPEARCH DIVISION

D-1

(4)

(3)

Define
$$\mathbf{m} = \mathbf{m}_{\mathbf{v}} + \mathbf{m}_{\mathbf{a}}$$
 (5)
where $\mathbf{n}_{\mathbf{v}} = \max s$ of water vapor in shelter volume, lb
 $\mathbf{m}_{\mathbf{a}} = \max s$ of dry air in shelter volume, lb
Define $\rho = \frac{\mathbf{m}}{\mathbf{v}} = \frac{\mathbf{n}_{\mathbf{v}}}{\mathbf{v}} + \frac{\mathbf{m}_{\mathbf{a}}}{\mathbf{v}} = \rho_{\mathbf{v}} + \rho_{\mathbf{a}}$ (6)
where $\rho = \text{density}, 1b/tt^3$
 $\mathbf{v} = \text{volume of shelter, ft}^3$
Define $\mathbf{v} = \frac{\mathbf{m}_{\mathbf{v}}}{\mathbf{m}_{\mathbf{a}}}$ (7)
Define $\mathbf{v}_{\mathbf{v}} = \frac{\mathbf{m}_{\mathbf{v}}}{\mathbf{m}_{\mathbf{a}}}$ (7)
Define $\mathbf{v}_{\mathbf{v}} = \text{concentration of vapor in dry air (assumed to) = \rho_{\mathbf{v}}}$
 $\mathbf{c}_{\mathbf{a}} = \text{concentration of dry air in water vapor (assumed to) = \rho_{\mathbf{a}}}$
Now, from (th)
 $\mathbf{m}_{\mathbf{v}} = -\delta \int \frac{d\mathbf{c}_{\mathbf{v}}}{d\mathbf{n}} = \frac{-\delta}{-\delta} \frac{d(\mathbf{v}_{\mathbf{v}})}{d\mathbf{n}}$
 $= -\frac{\delta}{\sqrt{\mathbf{v}}} \frac{\mathbf{m}_{\mathbf{a}}}{d\mathbf{n}} = -\delta \left(\frac{\mathbf{m}_{\mathbf{v}}}{d\mathbf{n}}\right) \frac{d\mathbf{w}}{d\mathbf{n}}$
 $\mathbf{v}_{\mathbf{v}} = -\delta\rho_{\mathbf{p}} \frac{d\mathbf{w}}{d\mathbf{n}}$ (8)
From (3)
 $\int \Delta x_{\mathbf{v}} \int_{0}^{\infty} \mathbf{q} \, \mathbf{n} = -\frac{T_{\mathbf{v}}}{T_{\mathbf{o}}} \times d\mathbf{r}$ (9)
where $\Delta x_{\mathbf{v}}$ = thermal boundary layer thickness, ft.
 $T_{\mathbf{o}}$ = temperature of the environment, "R
 $Y_{\mathbf{a}}$ = temperature of the boundary surface, "R
which leads to
 $\mathbf{q}_{\mathbf{v}} = \frac{\delta}{\delta x_{\mathbf{v}}} (\mathbf{T}_{\mathbf{o}} - \mathbf{T}_{\mathbf{e}})$ (10)
Similarly, equation (^R) leads to
 $\mathbf{s}_{\mathbf{v}} = \frac{\delta \rho_{\mathbf{a}}}{\delta x_{\mathbf{v}}} (\mathbf{w}_{\mathbf{c}} - \mathbf{w}_{\mathbf{e}})$ (11)

;

- 1-

. L

-1

....

•

_, [

- 1

-

GENCIAL AMERICAN REREARCH DIVISION

D-2

-

-...

where

and

 Δx_{ij} = mechanical boundary layer thickness, ft.

$$W_{o}$$
 = humidity ratio of shelter environment, lb_{W}/lb_{a}
 W_{z} = humidity ratio at boundary temperature, lb_{u}/lb_{a}

Parallel expression to equations (10) and (11) are

$$q = h (T_0 - T_e)$$
 (12)

(13)

and

and

 $\dot{m}_{v} = \rho_{a} b (W_{A} - W_{a})$ b = a coefficient of mass transfer, which must be evaluated. where

A comparison of equation (10) with (12), and (11) with (13) shows

$$h = \Delta \frac{k}{x_{\rm T}}$$
(14)

$$b = \frac{\delta}{\Delta x_{e}}$$
(15)

It is assumed that the thermal and mechanical boundary layer thickness are very nearly equal:

> $\Delta x_{rr} = \Delta x_{rr}$ (16)

Theref

ore:
$$\frac{h}{b} = \frac{k}{\delta}$$
 (17)

or

 $\frac{h}{\rho_{a}c_{p}b} = \frac{k}{\rho_{a}c_{p}\delta} = \frac{\alpha}{\delta}$ (18)

where $\alpha =$ thermal diffusivity = $\frac{k}{\rho_{\alpha}c_{\beta}}$ $b = \frac{h}{\rho_a c_b} \left(\frac{\delta}{a}\right)$ Therefore, (19)

Now, for water diffusing into air, 😤 = 0.917 (Ref. 9)

since $a = 0.070 \text{ ft}^2/\text{hr}$ for eir

6 - 0.765 for water vapor and

et 0°C and 760 cm He.

BENENAL AMERICAN REPEARCH DIVISION

Therefore
$$b = \frac{h}{\rho_a c_p} \left(\frac{1}{0.917}\right)^{+}$$

= 1.09 $\left(\frac{h}{\rho_a c_p}\right)$ (20)
and $\dot{m}_v = \rho_a b \left(W_0 - W_s\right)$
= 1.09 $\left(\frac{h}{\rho_a c_p}\right) \left(W_0 - W_s\right)$ (21)
where c_p = specific heat of air-water vapor mixture
 ≈ 0.24 Btu/1b-*F
Since $q = \dot{m}_v \lambda$ (22)
where λ = heat of condensation, Btu/1b
 $q_{condensation} = \frac{1.09\lambda h}{\rho_a c_p} \left(W_0 - W_s\right)$ (23)
Now, since $W = 0.622 \frac{p'}{\rho_b - p'}$ (24)

_ |

..

-,

- • 2

.*

where W = humidity ratio

p' = partial pressure of water vapor,

p = barometric pressure,

we may approximate

$$W_{o} - W_{g} = 0.62? \left(\frac{P_{o}}{P_{b} - P_{o}} - \frac{P_{g}}{P_{b} - P_{g}}\right)$$
 (25)

Therefore the heat transfer due to condensation is expressible by:

$$s_{\text{condensation}} = 2.825 \frac{\lambda h}{\rho_a} \left(\frac{P_o}{P_b - P_o} - \frac{P_a}{P_b - P_a} \right)$$
(26)

and condensation is determined to be present if $p_0 > n_2$. This is the condensation term of equations (1) and (2) of Appendix C. Also, equation (26) expresses the heat transfer due to re-evaporation of the condensate, if the energy and mass transfer phenomena are assumed to be equivalent

GENERAL AMERICAN REPEARCH DIVISION

1 3

in the two processes. In the case of evaporation, $p_s > p_o$ and the $q_{condensation}$ term is negative (C < O). The value of ρ_a in equation (26) is assumed to be defined by

$$\rho_{a} = 3.25 \times 10^{-7} T^{2} - 1.86 \times 10^{-4} T + 0.0863$$
 (27)

where T = the average of the temperature of the boundary surface in question and the shelter dry-bulb temperature, *F.

GENERAL AMERICAN RED ARCH DIVISION

D-5

APPENDIX E

ERROR INTRODUCED BY CONSIDERING THREE-DIMENSIONAL HEAT TRANSFER AS A ONE-DIMENSIONAL PHENOMENON

If a shelter boundary is curved, such as in a tunnel, the one-dimensional heat transfer calculations introduce errors because the heat flow is no longer one-dimensional. But the one-dimensional analysis is applicable to such situations. A comparison of the relative rates of heat transfer will determine the error of the application.

For a flat boundary, the heat transmitted from the inner surface to nodal point n is

$$q = -kA \frac{T_1 - T_n}{\Delta x}$$
(1)

where

k = thermal conductivity of flat surface along a normal,

- Btu hr-ft²-F
- $A = area of the boundary, ft^2$

T₁ = temperature of inner surface of boundary, "F

- T_n = temperature of nth nodal point, ²F
- Δx = distance along a normal between nodal points i and n, ft.

Heat transfer through a spherical layer of the boundary from the inner surface of the boundary to nodal point n is:

$$\mathbf{q} = -\mathbf{k} \left(4\pi \mathbf{r}^2\right) \frac{\mathrm{d}\mathbf{T}}{\mathrm{d}\mathbf{r}} \tag{2}$$

which, for steady state, may be integrated to

$$q = k (4\pi) \frac{T_1 - T_n}{\frac{1}{r_1} - \frac{1}{r_n}}$$
 (3)

GENEDAL AMERICAN RELEARCH GIVIBION

E-1

 $r_1 = radius$ of curvature of the inner surface of the

7" **...** |-

boundary

 r_{n} = radius of curvature to the nth nodal point See Figure E-1.

This is equivalent to

$$q = \frac{1}{\beta} k A_{m} \frac{T_{1} - T_{n}}{\Delta r}$$
(4)

where Λ_m = heat conductance area at the average radius

$$A_{\rm m} = 4\pi \frac{(r_1 + r_n)^2}{2}$$
(5)

and

where

$$\beta = \frac{1}{2} + \frac{1}{4} \left(\frac{r_1}{r_n}\right) + \frac{1}{4} \left(\frac{r_n}{r_1}\right)$$
(6)

 β represents the difference in calculating heat transfer using the two analyses; it represents the percent departure of the one-dimensional analysis from the three-dimensional analysis. Values of β as a function of $\frac{r_n}{r_1}$ are shown in Table V.

Using a similar analysis for cylindrical coordinates, the expression for β becomes r

$$\beta = \frac{1}{2} \left(\frac{\frac{n}{r_{1}} + 1}{r_{n}} \right) \ln \left(\frac{r_{n}}{r_{1}} \right)$$
(7)
$$\frac{\frac{n}{r_{1}} - 1}{\frac{r_{n}}{r_{1}} - 1}$$

and its variation with ${\binom{r_n}{r_1}}$ is also given in Table V.

Now say a tunnel with a radius of ten feet were used as a shelter. Assume, too, that the boundary is soil-backed and therefore the maximum outermost nodal point is ten feet past the outer surface of the boundary.

GENERAL AMERICAN REBEARCH DIVISION

F--2



GENERAL ANDLIGHT PL GARGH LEVEL IN

E-3

TAPLE	V
-------	---

. . . .

ERRORS	of	CONSID	ERING	g three-dimensional	
HEAT	<u>r T</u>	PANE/ER	AS C	ONE-DIMENSIONAL	•

$\frac{r_n}{r_1}$	β (Cylindrical)	β (Spherical)
1.0	1.0	1.0
1.1	1.001	1.002
1.2	1.003	1.008
1.3	1.006	1.017
1.4	1.010	1.029
1.5	1.014	1.042
1.6	1.018	1.056
1.7	1.023	1.072
1.8	1.029	1.089
1.9	1.034	1.107
2.0	1.040	1.125
2.1	1.045	1.144
2.2	1.051	1.164
2.3	1.057	1.184
2.4	1.063	1.204
2.5	1.068	1.225

-

•••

- 1

**

....**•**

••

• •

GENERAL AMERICAN REBEARCH DIVISION

5-1

Therefore,

]

]

]

]

$$\frac{r_n}{r_1} = \frac{r_1 + \Delta p + 10}{r_1} = 2 + \frac{\Delta p}{10}$$
(8)

where p is the thickness of the boundary. A reasonable value of p would be 3 feet and thus the error in the heat flow due to using a onedimensional analysis method of a three-dimensional analysis is 5.7% using the cylindrical surface analysis or 18.4% using the spherical surface analysis. (See Table V.) Generally, a tunnel designed as a mass shelter can be expected to have a radius greater than ten feet; therefore, the error introduced would be correspondingly less. Hence a shelter boundary that is curvilinear can be treated as a flat surface with an error given by equation (6) or (7).

SENERAL AMERICAN REDEARCH DIVISION

AFPENDIX F

ESTIMATION OF ERROR ASSOCIATED WITH CALCULATION OF AIR-CONDITIONING LOAD

The performance of an air-conditioning system is a function of the environmental conditions, the psychrometric state of the air entering the unit, the performance characteristics of the components comprising the system, the flow field in the unit and the characteristics of the heat sink and source reservoirs. Procedures are required to define an air-conditioning system for primarily cooling the air introduced into the shelter. The operating principles for such a unit can be based upon a large number of choices. However, in almost every choice, a coil will be utilized for cooling and dehumidifying the air. Therefore, the SHEP code has been constructed so as to require only the specification of the coil. It is assumed that once the coil has been defined, the designer can develop a system to produce the specified coil performance.

In particular, the coil is specified by denoting

- 1) a coil bypass factor,
- 2) an effective coil surface temperature, and
- 3) an air flow rate across the coll.

It is known that the coil bypass factor and effective coil surface temperature are a function of the thermal load, i.e., the psychrometric state and flow rate of the air through the coil. In the SHEP code, this load dependence is neglected (since performance is a function of the design of the entire system) and the bypass factor and effective coil surface temperature are assumed constant.*

GENERAL AMERICAN RESEARCH DIVISION

+

[&]quot;This procedure is a generalization of a coil selection procedure presented in "Fundamentals of Psychrometrics - Part II", T200-20, Carrier Air Conditioning Company, page 19.

The accuracy of this procedure has been checked by comparison with the performance data of an actual air-conditioning unit, see Table VI. It was found that neither the deduced bypass factor nor the deduced effective coil surface temperature are constant. However, if median values of the range of each of these parameters are used to calculate the capacity of the unit, this calculated unit capacity differs from the actual unit capacity by at most 37% and generally by less than 12%. This agreement is considered sufficient for the inclusion of this simplified specification for the air-conditioning equipment in the SHEP code.

...

i

BENCHAL AMERICAN REBEARCH DIVISION

TABLE VI

]

]

]

]

]

]

]

]

]

]

l

1

Ĵ

J

j

1

ESTIMATION OF ZRROR ASSOCIATED WITH CALCULATION OF AIR CONDITIONING LOAD*

Air Tem	.peratures	at Evepora	tor	Deduced Effective Coil			Actual	Calculated	& Error in
Sntering Dry-Bulb	Entering Wet-Bulb	Leaving Dry-Bulb	Leaving Wet-Bulb (°F)	Surface Temperature (*F)	Deduced Bypass Factor	Eveporator Air Flow (cfm)	Unit Capacity (Btu/hr)	unic Capacity (Btu/hr)**	Capacity Capacity
		72.5	9.99	60.7	0.227	630	40 , 900	52,200	+27.7
4.6 <u>11</u> 2 cr.	7. B	66.3	60.3	54.1	4125.0	605	39,200	h2 , 500	+8.
		70.9	66.4	54.1	0.347	637	44,600	59, 500	+3.3
1.201		2 T	50.3	47.5	6/1.0	602	ψ1 , 600	43,600	+ 8.4+
	2.2		54.1	1.8.7	061.0	602	35,400	31,450	-11.2
	4.21	0.85	54.0	39.5	0.345	€∪ 2	10, 100	35,400	2.11-
9, 10 9, 10	6.69 9	51.7	1.7.4	l43.3	0.156	605	34,200	21,800	-36.3

*Data from report, "Shelter Air Conditioning Unit", Final Report, OCD Work Unit 1425B, Carrier Air Conditioning Company, February, 1967, p. 24.

extreme values) and a constant effective coil surface temperature of 50°F (median of deduced ##Unit capacity calculated by the use of a constant bypass factor of 0.252 (median of deduced extrate values). ;

F-3

APPENDIX G

TYFICAL THERMAL PROPERTIES AND DENSITIES OF BUILDING MATERIALS, SOILS, ETC.

BUILDING MATERIAL

]

]

]

]

]

)

				Thermal <u>Conductivity</u> CON (Btu/hr-ft-°F)	Specific <u>Heat</u> CP (Btu/lb-°F)	Density ROW (lb/ft ³)
I	Bui	lding	Board			
	1.	Asb	estos-cement Board	0.33	0.270	120.00
	2.	Gyp	sum or Plastic Board 3"	C.10	0.270	50.00
		•	" " " <u>1</u> "	0.09	0.270	50.00
•	3.	Ply	wood	0.07	0.500	31,.00
	4.	She	athing, Wood Fiber	0.03	0.500	20.00
	5.	Wcod	i Fiber Board	0.03	0.500	26.00
	6.	Wood	d Fiber, hardboard type	0.12	0.500	65.00
II	Fin	ish F.	looring Materials			
	1.	Corl	$k \text{ tile } - \frac{1''}{8}$	0.03	0.485	15.60
	2.	Ter	razzo - 1"	1.04	0.250	150.00
111	Ins	ulati	ng Materials			
	A .	B³ ⊿t	nket & Batt			
		1.	Cotton Fiber	0.02	0.362	J.8-2.0
		2.	Mineral wool, fibrous form processed from			
			rock, slag, or glass	0.03	0.30	0.5
				0.05	0.30	1.5-4.0
		3.	Wood Fiber	0.02	0.30	3.2-3.6

GENERAL AMERICAN RESEATCH DIVISION

G-1

			CON (Btu/hr-ft-°F)	(Btu/lb-*F)	$\left(\frac{ROW}{1b/ft^3}\right)$
в.	Boa	rd & Slabs			
	1.	Cellular Class	0.03	0.185	9
	2.	Corkboard	0.02	0.485	6.5-8.0
			0.02		12
	3.	Glass Fiber	0.02	0.185	4-9
	4.	Expanded rubber (rigid)	0.02	0.339	4.5
	5.	Expanded polyurethane (thickness 1 in. and greater)	0.02	0.20-0.25	1.5-2.5
	6.	Expanded polystyrene extruded	0.02	0.30-0.35	1.9
		molded beads	0.02	0.3 0-0.35	- 1.0
	7.	Mineral Wood with resin binder	0.02	د.3 0	15
с.	Loo	ce Fill			
	1.	Mineral wool (glass, slag or rock)	0.03	0.30	2.0-5.0
	2.	Perlite (expanded)	0.03	0.378	5.0-8.0
	3.	Sawdust or shavings	0.04	0.30	0.8-15
	4.	Silica Aerogel	0.01	0.205	7.6
	5.	Vermiculite (expanded)	0.04 0.04	0.30 0.30	7.0-8.2 4.0-6.0
	6.	Wood Fiber, redwood, hemlock, or fir	0.02	0.30	2.0-3.5
Nas	onry l	Natorials			
1.	Cen	ent Murtar	0.42	0.271	116.c
2.	Gyp 87 12	sum-fiber concrete -1/2% gypsum, -1/2% wood chips	0.01	0.25	51.0

• . •

į .

•#

GENERAL AMERICAN REPEARCH DIVISION

G-3

IV

		• (Btu/hr-ft-°F)	CP (Btu/lb-°F)	ROW (1b/ft 3)
3	· Lightweight aggregates	0.43	0.20-0.25	120
	slags; cinders; pumice;	0.30	0.20-0.25	100
	cellular concretes	0.21	0.20-0.25	80
		0.14	0.20-0.25	60
		0.10	0.20-0.25	ho
		0.08	0.20-0.25	30
		0.06	0.20-0.25	20
4.	Stucco	0.42	0.20-0.25	.16
Ma	sonry Units			
1.	Brick, common	0.42	0.20	
2.	Brick, face	0.75	0.20	120
3.	Clay tile, hollow			130
	l cell deep 3 in.	0.31	0.15	٥۶
	2 cells deep 6 in.	0.33	0.15	30
	2 cells deep 8 in.	0.36	0.15	30
	2 cells deep 10 in.	0.38	0.15	30
	3 cells deep 12 in.	0.40	0.15	30
<u>≯</u> .	Concrete blocks, rectangular core			
	and and gravel aggregate	0.15	0.25	30
2.	Stone, lime or sand	1.04	0.22	150
Pla	storing Naterials			
1.	Cement Plaster, sand aggragate	0.1.2	0.20	116
", ".	Gypsum Plaster			
	rerite estrogate	J.18	0.20	45
	Hamitante Hamitante	0.47	0.20	105
	vermiculite aggregate	0.01	0.20	45

3

ENERAL AMERICAN RESEARCH DIVISION

G-3

V

VI

		(Btu/hr-ft-*F)	CP (Btu/lb-*F)	$\left(\frac{ROW}{1b/ft^3}\right)$	
VII	Roofing				×
	1. Asbestos-cement shingle	es 0.40	0.20	120	-
	2. Asphalt roll roofing	0.54	0.20	70	• ·
	3. Asphalt shingles	0.19	0.20	70	
VII	I Siding Materials (on flat su	urfaces)			-
	1. Shingles - asbestos-cen	ment 0.40	0.20	120	-
	2. Siding				•
	asbestos-cement - $\frac{1''}{4}$	0.10	0.20	120	
	asphalt roll siding	G. 54	0.20	120	: ب ه
	3. Architectural glass	0.83	0.15-0.20	150-175	 • 1
IX	spook				. •
	 Maple, bat, and similar hardwoods 	0.09	0.50	45	- 1
	 Fir, pine and similar softwoods 	0.07	0.50	32	:1
	Ģ	ONFIGURATION			רי
	· · ·	Thermal Conductivity Unit Distance	Specific Heat	Densivy	1
		CON/DX (Btu/hr-ft-*F)	CP (Btu/1b-°F)	(16/EL3)	•
1	Vertical Space	1.03	0.24	0.075	•
11	Horizontal Space				
	1. Heat flow up	1.18	0.24	0.075	•
	2. Hest flow down	1.01	0.24	0.075	
m	45° In lined Space				4
	1. Hest flow up	1.31	0.24	0.075	
	2. Heat flow down	1.13	0.24	0.075	

n na ana ang sata sata sa Kapita sa S

à .

ſ

GENERAL AMERICAN REPEARCH DIVISION

r_h

		Thermal Conductivity	Specific <u>Heat</u>	Density
		(Btu/hr-ft-°F)	CP (Btu/lb-°F)	$\left(\frac{ROW}{1b/ft^3}\right)$
I	Crushed quartz	0.96	0.188	100.00
II	Graded sand	0.83	0.210	100.00
111	Gravel	0.75	0.200	110.00
IV	Crushed feldspar	0.50	0.190	100.00
V	Crushed granite	0.46	0.230	100.00
VI	Sandy loam	0.54	0.210	110.00
VIX	Crushed trap rock	0.42	0.195	100.00
VIII	Sand	0.37	0.210	100.00
IX	Clay	0.33	0.220	100.00
X	Silt loan	0.42	0.220	90.00
XI	Silty clay loam	0.42	0.200	90.00

SOIL.

ļ

]

]

.]

·]

٦

]

j

ń

.....

BOUNDARY ORIENTATION

		Direction of Heat Flow	Film Heat-Transfer <u>Coefficient</u>
			HI, HO (Btu/hr-ft ⁻ - [*] F)
I	Vertical	Into or out of shelter	1.46
11	Norizontel (ceiling)	Into shelter	1.08
		Out of shelter	1.63
111	Horizontal (floor)	Jnto shelter	1.63
		Out of shelter	1.08

DENERGA AMERICAN RESTARCH DIVISION

G-3

APPENDIX H

]

]

]

]

]

.]

[]

:]

ل

Ĵ

]

]

SHEP CODE, MODIFICATION 3

FLOW CHART AND LISTING

-

-

_

H-1

GINDLERS, ARTS CONTRACTOR SAME



PROGRAM SHEP

.

```
C
C SHELTER ENVIRONMENTAL PREDICTION CODE (SHEP--MOD. 3)
C GENERAL AMERICAN RESEARCH DIVISION
C GENERAL AMERICAN TRANSPOPTATION CORPORATION
C
C THIS CODE CALCULATES THE RESPONSE OF A SHELTER TO TIME-VARYING THERMAL LOADS
C
  AND VENTILATION INLEY PSYCHROMETRIC CONDITIONS. THE CODE ACCOMMODATES SOLAR
C RADIATION + BOUNDARY SURFACE HEAT TRANSFER + MOISTURE CONDENSATION ON THE
C BOUNDARIES COUIPMENT AND LIGHTING LOADS, AND AIR-CONDITIONING. THE USER
C MANUAL EXFLAINS THE VARIOUS FEATURES OF THE CODE + PRESENTS THE INPUT AND C OUTPUT FORMATS, GIVES REPRESENTATIVE INPUT DATA VALUES, AND INCLUDES AN
C APPLICATION OF THE CODE TO A TYPICAL SHELTER STRUCTURE.
C
      COMMON/MATRIX/AINV(40+40+20)
      DIMENSION TWALL(40,20) + A(40,40) + INDEX(40,2) + T(40)
      DIMENSION EQTIM(365) + TD2P(336) + TWB(336) + TEFF(336)
      DIMENSION PSAT(120), IN(5,20), DP(5,20), DX(5,20), ALPHA(5,20), CON(5,2
     10) +ROW(5+20) +CP(5+20) +CW(20)
      DIMENSION INT(60)+OS(2+20)+BB(40)+BMUL(40+20)+TDI(30)+TWI(30)+TEI(
     1301, TDIAV(3C), TWIAV(30), TEIAV(30), TSOIL(20)
      DIMENSION XI (20) +A2 (20) +LAYMAX (20) + OLATC(20) +HI (20) +HO(20) +NMAX (20
     1)+ITWALL(20)+25W(20)+0W(20)+AREA(20)+TDD(14)+TWD(14)+TED(14)+TDAVG
     2114) + TWAVG(14) + TEAVG(14) + IDATA(13) + LST(2) + TRANS(20) + ASOIL(20) +
     3AJIT(20)
      JJJJ=1
C
C
 INITIALIZE ALL MATRIX ELEMENTS TO ZERO.
C
 1311 DO 1 1=1.40
      DO 1 J=1+40
      DO 1 K=1:20
    1 AINV(1+J+K)=0+0
      DO 2 1=1+40
       T(1)=0.0
      DO 2 J=1+2
    2 INDEX(1+J)=0
      DO 3 1=1+40
      60 3 J=1+20
      BHUL (1.J)=0.0
    3 TWALL(1+J)=0+0
      00 5 1=1+365
    5 EQTIN(1)+0.0
      DO 6 1=1+336
      TD2P(1)=TWB(1)=TEFF(1)=0.0
      DO 7 1=1+120
    7 PSAT(1)=0+0
      00 8 1+1+5
      DO 8 J=1+20
       IN(1+J)=0
    8 DP(1+J)=DX(1+J)=ALPHA(1+J)=CON(1+J)=ROW(1+J)=CP(1+J)=0+0
      00 9 1-1+60
      INT1:-+0
      00 10 1=1+2
       00 10 J=1+20
   10 0511+11+0+0
      00 302 1=1.30
  302 TD1(1)+TW1(1)+TE1(1)+TD1AV(1)+TW1AV(1)+TE1AV(1)=0.0
      DO 303 1+1+20
      CHI11-0.0
```

. . .

• •

* *

20

47

+ +

- -

• •

L

ŝ.

A CONTRACTOR OF A CONTRACTOR OF A CONTRACTOR OF A CONTRACTOR OF A CONTRACTOR A CONT

New York Contraction

H-3
LAYMAX(I)=NMAX(I)=ITWALL(I)=0 303 X1(1)=A2(1)=QLATC(1)=H1(1)='{0(1)=QSW(1)=QW(1)=AREA(1)=TRANS(1)=AS0 00 304 1=1+14 304 TDD(1)=TWD(1)=TED(1)=TDAVG(1)=TWAVG(1)=TEAVG(1)=0.0 DO 305 I=1+13 305 IDATA(1)+0 DO 306 1=1+2 306 LST(1)=0 C C READ INPUT DATA AND SET CONSTANTS. C IF(JJJJ-1)307+307+308 307 DO 11 1=1+365 00 12 1=50,120 12 READ .1001+PSAT(:). 308 READ 1006, IDATA READ 1003+ALT+ALAT+ALONG+NW+GG+HH+W+P+F1+QLITE+QEQUIP+D+HRS+LST(1) 1+NO'NT _____DO__16__J=1+NW READ 1020+AREA(J)+LAYMAX(J)+NMAX(J)+HI(J)+HO(J)+ASOIL(J) IF (ASOIL(J))1312,15,15 1312 READ 1001+TRANS(J)+X1(J) IF (X1 (J1=90+0114+15+999 14 READ 1003+AZ(J) ... 15 LEMELAYMAXLUL DO 16 K=1.LEM 16 READ 1009+0P(K+J)+DX(K+J)+CON(K+J)+ROW(K+J)+CP(K+J) READ 1013+CFMIN+TCOIL+WCOIL+BF+F2+TD2+R2+TWB(1)+TEFF(1) IF (ASOIL(J))18+18+1703 1703 READ LOOB TSOIL (J) 18 CONTINUE __IF(10ATA(1))19+19+21 19 READ 1008.TO DO 20. J=1. NW NEN=NMAX(J)61 00.20 K=1.NEH__ 20 TWALL(K+J)=TO GO TO 23 21 DO 22 J=1+NW NEH=NHAX (J) 61 00 22 K=1.NEM READ 1008 . 10 22 TWALL(K+J)=TO 23 READ .1001+D.T 'HRS=HRS MODAY S= IMRS/24 IFINOINT11701+1701+1702 1702 NO0+2+NOINT -----00 17 1-1.NOO 17 READ 1006,141(1) 1701 10-0 LMN+25 KIND=0 PLH=Q.Q_ ADT=0.0 INSHO#1 H-4 NTAUND

. . .

1

٠ PI=3.14159265 OM=P1/12.0 ON=180./PI DR=0.1 R=1.0 MOND=1 GIL=7D2 VS=GG+HH+W READ 1021+TA1+TA2+TD11+TD12+R11,R12 C C CALCULATE INTENSITY OF SOLAR RADIATION FOR EACH EXPOSED BOUNDARY. C 25 LST(2)=LST(1)61 DO 53 1=1+2 LSTM=LST(1) 251 DO 53 J=1+NW IF (ASOIL (J))252+53+53 252 IF (IDATA(10))26+26+27 26 (2=294. C3=3.183 GO TO 28 27 C2=200. C3=2.228 28 IF(X1(J)-90,) 29,29,999 29 ETAR=0.410152+51NF((1D-80)+P1/182.5) S1=TANF(ETAR) S2=SINF(ETAR) S3=COSF(ETAR) PHIR=ALAT/ON \$4=TANF(PHIR) S5=SINF(PHIR) S6=COSF(PHIR) AZR=AZ(J)/ON XIR=XI(J)/ON S7=COSF(XIR) S8=SINF(XIR) IF (PHIR-(PI+0.5)) 30,998,998 30 IF (ETAR6PHIR-(PI+0.5)) 31.998.998 31 IF(ETAR) 34,34,32 32 IF (PHIR-(PI+0.5-ETAR)) 74.33.33 33 THETAR=0.0 GO TO 35 34 THETAR-ACOSF (S4+S1) 35 THETAS=2. +PI-THETAR IN=ALONG/15 TI=LSTNGEOTIN(ID)-ALC 5.061N THETA=ON=TI \$9+COSF(THETA) IFITHETA-THETARI 36+37+37 36 DIR=0.0 DIF=0.0 GO TO 52 37 IF (THETA-THETAS) 38.38.36 38 BETAR + ASINF (\$5+\$2-\$6+\$9+\$3) \$10+COSF (BETAR) \$11=SINF (BETAR) IF (BETAR) 36+39+39 39 IF (BETAR-(P]+0.5)) 392,391,392 391 GAMMAR+AAR 60 10 393

manage and the second strength of the second

•

...

~~,

· • •

. .

. .

. .

. .

. .

• •

۰. و

H-5

```
392 GAMMAR=ACOSF(1./510+(56+52655+59+53))
  393 IF (GAMMAR) 40+40+41
   40 GAMMAR=GAMMAREPI
   41 DIRNORM=C2+(1+-EXP(-C3+BETAR))
      S13=S10+COSF(GAMMAR-AZR)
      ALPHAR=ACOSF($13+576511+58)
      $12=COSF (ALPHAR)
      IF (ALPHAR-(PI+0.5)) 43,43,42
   42 DIR=0.0
      GO TO 49
   43 IF(513) 45+44+44
   44 FALPHA=0.35+513++2.60.45+51360.55
      GO TO 48
   45 IF(51360.04) 47.47.46
   46 FALPHA=0.625+513++2.60.525+51360.55
      GO TO 48
   47 FALPHA=0.4
   48 DIR=DIRNORM=512
   49 DIF1=511+(FALPHA+(1.-58)658)
      DIF2=0.677E-06+DIRNORM++2-1.5E-04+DIRNORM60.0183
      DIF=DIF1/DIF2
   52 TOT=DIRGDIF
      QS(1+J)=TOT
   53 CONTINUE
      QST=0.0
      QSOLAR=0.0
      DO 54 J=1+NW
      QSW(J) = QS(2+J)
      QSOLAR+TRANS(J)+QSW(J)+AREA(J)6QSOLAR
   54 OST=OST605(2+J)=AREA(J)
C
C FOR EACH HOUR OF OCCUPANCY AFTER THE FIRST. RESET HOUR NUMBER AND SET
C CONDITIONS AT THE END OF THE PRECEDING HOUR TO THOSE AT THE BEGINNING
C OF THE SUCCLEDING HOUR. READ THE INLET CONDITIONS FOR THE SUCCEEDING HOUR.
C
      IF (IHRNO-1)57,24,57
  55 DO 56 J=1+NW
   56 05(3+J)=Q5(2+J)
      LSTN=LSTMG1
      IHPNO=1HRNOG1
      1F(24-LSTM)5612+5612+251
 $612 LSTH=0
      10=1061
      IF (345-10)5611+251+251
 5611 10=1
      GO TO 251
  57 TD11+TD12
      R11+R12
      SAT+LAT
      10.104
      IF(IDATA(12))1#1.181.182
  181 READ 1018.P.F1.CFMIN.OLITE.OEQUIP
  182 IF (IDATA(13))183.183.60
  183 READ 1319+T012+TA2+R12
     60 10 60
  58 051+0.0
     OSOLAR#0.0
     050+05(1+J)6ADT+105(2+J)=0+(1+J))
     020+(L)#050
```

1

• }

4

H-6

```
QSOLAR=TRANS(J)=QSW(J)=AREA(J)6QSOLAR
   59 OST=0516050
¢
C FOR TIME INCREMENTS DURING THE HOUR, DETERMINE INLET CONDITIONS AS A
C LINEAR INTERPOLATION BETWEEN HOURLY VALUES.
C
   60 TD1=TD11=ADT+(TD11=TD12)
      R1=R11-ADT+(R11-R12)
      PG=5+132+EXP(0+0329+TD1)
      PGPP=R1+PG
      8P=0.98E-06+ALT++2-0.0759+ALT62116.2
      W1=10.622+PGPP1/182-PGPP1
      TA=TA1-ADT+(TA1-TA2)
     LL=1
C
C CALCULATE NEW INLET CONDITIONS WITH AIR-CONDITIONING. DETERMINE PROPERTIES
C OF THE INLET AIR FOR THE BEGINNING OF THE TIME INCREMENT.
      IF(IDATA(7))403+403+402
  402 TD1=TD26(F2/F1)+(TD1-TD2)
     PGPP=5.132+R2+EXP(0.0329+TD2)
      W2=[0.622+PGPP]/[8P-PGPP]
      W1=W26(F2/F1)=(W1=W2)
      ADMIX=(F1-CFM1N)/F16BF+(1+-((F1-CFMIN)/F1))
      TDA=TCOILGADMIX*(TD1-TCOIL)
      WA=WCOILGADMIX=(W1=WCOIL)
      E1=EXP(0.0329+TDA)
     PGPP=WA+BP/(WAG0+622)
     PG=5.132=E1
      R1=PGPP/PG
      WAC=60.0+CFM1N+DT+(0.018744+8P-0.0962+R1+E1)/(TDA6459.69)
      NF=1093+9-0.567=TCOIL
      PAIRCOND=0+24+WAC+(TD1+TDA)/DT6WAC+(W1+WA)+HF/DT
      TD1-TOA
      WI=WA
      GO TO $1
  403 PAIRCOND=0+0
   61 E1=EXP(0.0329+TD1)
      E2=EXP(0.0329+TD2)
      MAS1=0.24+TD2
      HV51=1061.060.444+TD2
      HA1=0.24+TD1
      HV1=1061.060.444+TD1
      MFG=1093.9-0.567+TD2
      WAS1+V5+10.018744+8P-0.0962+R2+E21/(TD26439.69)
      WV51=V5+(0.05987+R2+E2)/(TD26459.69)
      WA1+60.9+F1+DT+(0.018744+8P+0.0962+R1+E1)/(TD16459.69)
      WV1+60.C+F1+DT+10.05957+R1+E11/(T016459.69)
      HS1=WAS1=HAS1EWV$1=HVS1
     HI-WAI+HAIEWVI+HVI
      IZAW#IAW+CAW
C
C CALCULATE THE HEAT TRANSFER THROUGH THE BOUNDARIES DUE TO TEMPERATURE
C DIFFERENCES AND DUE TO HOISTURE CONDENSATION.
      1F ( 10ATA ( 4) 169 +69 +70
   69 GWC=0.0
      QLH=C.O
      NTAU-NTAUG1
      IMAN+ IMANO-1
                                        H-7
```

· · · •

_ 1

......

GO TO 146 70 00 71 J=1+NW ILL=0 LEM-LAYMAX(J) DO 71 K=1+LEM IN(K+J)=DP(K+J)/DX(K+J)6161LL71 ILL=IN(K+J) JWALL=1 LAY=1 1=1 72 NEM=NMAX(JWALL)61 DO 4 INA=1+NEM DO 4 JNA=1+NEM A(INA+JNA)=0.0 4 88(1NA)=0.0 721 ALPHA(LAY, JWALL)=CON(LAY, JWALL)/(ROW(LAY, JWALL)=CP(LAY, JWALL)) BASIL=1.06CON(LAY61.JWALL)=DX(LAY.JWALL)/(DX(LAY61.JWALL)=CON(LAY. 1JWALL) | 6ROW(LAY+JWALL) + CP(LAY+JWALL) + DX(LAY+JWALL) + + 2/(2+0+CON(LAY 2+JWALL 1+DT)GROW(LAYG1+JWALL)+CP(LAYG1+JWA'L)+DX(LAY+JWALL)+DX(LAY6 73_1F11=1176+76+82 76 1TD2=TD2 PS=PSAT(1102)6(102-1102)+(PSAT(110261)-PSAT(1102)) PO=PS=R2 ITWALL (JWALL) - TWALL (1.JWALL) IELF1=ITWALL(JWALL)-ELEZ-TWALL(1.JWALL) PSW=PSAT(!ELF1)&(ELF2-1ELF1)+(PSAT(1ELF161)-PSAT(1ELF1)) TENV=IID26TWALL(1+JWALL))/2+0 COAIR=3.25E-07+TENV++2.0-1.86E-04+TENV60.0863 77. C+2:)82494HFG+H1(JWALL)+(P0/(BP-P0)-PSW/(BP-PSW))/ROAIR CWIJWALL) + C+AREA (JWALL) + DT/HFG JEICHIJWALL11772+79+771 771 AJIT(JWALL)=AJIT(JWALL)6CW(JWALL) 60.10.79 772 IF (ABSF(CW(JWALL))-AJIT(JWALL))771.771.774 774 CHIJHALLI--AJITIJWALLI C=CW(JWALL)+HFG/(AREA(JWALL)+DT) <u>60 10 171</u> 79 QLATC(JWALL)=C IF (NTAU)80,80,81 80 A(1+1)=1+84CON(LAY+JWALL)/(H1(JWALL)+DX(LAY+JWALL))&ROW(LAY+JWALL) 1 CP(LAY+JWALL1+DX(LAY+JWALL)/(2+0+H1(JWALL)+DT) A(1+161)=-CON(LAY+JWALL)/(H1(JWALL)=DX(LAY+JWALL)) 01 BR(1)=ROH(LAY,JYALL)=CP(LAY,JYALL)=DX(LAY,JYALL)/(2=Q+H1(JYALL)=DT 1) TWALL(1.JWALL)6TD26C/H1(JWALL) 1-161 02 IF (1-1N(LAT, JWALL)) 03,03,06 43 [F (NTAU)84+84+85 \$4 A(1+1-1)=-1+0 ALLIDOXLLAY . WALLIGOZ/ (ALPHA (LAY) JWALLIGOT 162. A(1.161)=-1.0 \$5 BB([]=DX(LAY+JWALL)==2+TWALL([+JWALL)/(ALPHA(LAY+JWALL)=0T) 1-161 GO TO #2 06 1F(LAY-LAYNAX(JWALL))67:90:996 AT IFINTAULPENBOND ----\$8 A(1+1-1)=-1+0 ALI.II-DASIL A(1+15))--COX(LXY6)+JYALL)+DX(LXY+JYALL)/(DX(LXY5)+JYALL)+CON(LXY+ 1-MALL)) 89 C3{[]=(ROV(LAY')JXALL)*CP(LAY')JXALL)*DX(LAY')JVALL)**2*6ROV(LAY61*JV H-9

٠ 1ALL) #CP(LAY61+JWALL) #DX(LAY+JWALL) #DX(LAY61+JWALL)) #TWALL([+JWALL) 2/12.0.CON(LAY.JWALL)+DT) 1=161 LAY+LAY61 IF (LAY-LAYMAX (JWALL))721,721,90 90 IF (ASOIL (JWALL) 191+92+96 91 TAJ=TA GO TO 93 92 TAJ-0.5+(TO26TA) +4 AII+I-II=CONILAY+JWALLI/(HOIJWALLI+DXILAY+JWALLI) 93 IFINTAU 194.94.95 AII+II=-A(I+I-1)61+OGROWILAY+JWALL)+DXILAY+JWALL)+CPILAY+JWALL)/12 1.0"HOLJWALLIHDT) 951 BB(1)+(1+0-TRANS(JWALL))+OSW(JWALL)/HO(JWALL)STAJGROW(LAY+JWALL)+C 1PILAY + JWALLI + DXILAY + JWALLI/(2+0+DT+HOIJWALL) + TWALLI - JWALLI 952 BB(11=TAJGROWILAY, JWALLISCP(LAY, JWALLISDX(LAY, JWALL)/(2.0+DT+HO(JW JALLIJ+TWALL(I+JWALL) GC TO 103 96 IF (1-NMAX (JWALL)-1) 100,100,996 MARRY ROW (LAY + JWALL) + CP (LAY + JWALL) + DX(LAY + JWALL) + P2/ (CON(LAY + JWALL) 100 TWALL (I + JWALL) + TSOIL (JWALL) 114011 IF (NTAU) 101. 101 . 102 -101 A(1+1-11=1+0 ALI+II=2.06HARRY 102 BB(1)=HARRYOTWALL(1+JWALL)&TSOIL(JHALL) 103 IF (NTAU) 104+104+1351 105 NEM-NMAX (JWALL 161 DO 108 1=1=NEM 108 INDEX(1+1)=0 11=0 109 AMAX=-1+ DO 110 1=1.NEM IF (INDEX (1.1))110+111+110 111 DO 112 J=1+NEM IF(INDEX(J+1))112+113+112 113 TEMP+ABSFIA(1+J)) IF (TEMP-AMAX)112+112+114 114 IROW-1 1001 . . . AMAX=TEMP 112 CONTINUE 110 CONTINUE LF 1AMAX1223+115+116 115 PRINT 133 133 FORMATCIIN ZERO PIVOTI 60 10 69 116 INDEXILCOL 1711ROW-1COL1119+110+119 119 00 120 J-1-NEM TENP+ALTROWIJT ALIROVIJIALICOLIJI 120 ALICOLIJIOTENP 11-1161 INDEX[11:2)-ICOL 116 PIVOT+ALICOLISOLI ALICOL.ICOLI-1.0 4-9 PIVOI+1./PIVOT

Ŀ

.

.

.

10.00

```
DO 121 J=1+NEM
  121 A(ICOL+J)=A(ICOL+J)*PIVOT
      DO 122 1=1+NEM
      3F(1-1COL)123,122,123
  123 TEMP=A(I+ICOL)
      A(1+I(OL)=0+0
      00 124 J=1.NEM
  124 A(1,J)=A(1,J)=A(ICOL,J)+TEMP
122 CONTINUE
      GO TO 109
  125 ICOL=INDEX(11+2)
      IROW=INDEX(ICOL+1)
      DO 126 I=1+NEM
      TEMP=A(I+IROW)
      A(I+IROW)=A(I+ICOL)
  126 ALI.ICOLISTEMP
      11=11-1
  225 IF(II)125+127+125
  127 DO 235 1-1-NEM
      BMUL(1.JWALL)=BB(1)
      DO 135 J=1+NEM
  135 AINV(I+J+JWALL)=A(I+J)
 1351 IF(JWALL-NW)143+142+995
  143 JWALL+JWALL61
      1=1
      LAY=1
      GO TO 72
  142 DO 144 K=1+NW
  144 QUIKI-HIIKI+AREALKI+(TD2-TWALL(1+K))
      OWC=0.0
      OFH-0.0
      00 145 J=1+NW
      ONC=QWC6QW(J)
  145 QLH=QLH6QLATC(J)+AREA(J)
C
C CALCULATE METABOLIC HEAT ENERGIES.
C
      NTAU=NTAUE1
      IHRN=IHRNO-1
  146 IF(TEFF(IMRNO)-87.0)149.149.147
  147 IF (TEFF (IHRNO)-102+01348+148+994
  148 QT==1.508=TEFF([HRNO]==26259.7=TEFF(]HRNO]=10795.2
      GG TO 151
  149 IF (TEFF (IMRNO)-50.03993.150.150
  150 CT=-1.482+TEFF11HRH016514.0
  151 101702-50.01492.152.192
  152 QSENS=-0.06875+T02++261.625+T026523.0
      OSEN+OSENS+P
      QLA+OT-OSENS
      QL=QLA+P
٢
C CALCULATE THE SHELTER DRY-DULB TENPERATURE AND RELATIVE HUNIDITY C AT THE END OF THE TIME INCREMENT.
C
  153 IF (R-1.0)154+155+155
  150 QL-QL+R
      PRIMT 2001+1HRN+R
  155 DO-MSIGHIG COSENGOL + (HVSI/HFG)-QUCGOL TESPEQUIP-PAIRCONDEOSOLAR-OLN
     11101
      WVL=QL+DT/HFG
```

•

H-10

言語の意思を

1

```
WVCOND=QLH+DT/HFG
      WV0=WV16WVI
                     1-WVCOND
                     1554+1556
      IF (WVCOND) )
                    N=+1554
 1556 JF (WYO) 1553.
 1553 WV0+0.0
 1554 TD20([HRNO]=,00-1061.0+WVO)/(0.444+WVC6J.24+WAO)
      IF (ABSF (GIL-TD2P(IHRNO))-1.00)1552,1551.1551
 1552 LL=IDATA(3)
      GU TO 163
1551 IF(TD2P(IHRNO)-50.0)986.156.156
  156 IF (WVO) 1561 + 1561 + 1563
1561 PV2=0.0
      R2P=0.0
      GO TO 1562
1563 PV2=8P/(0.622+WA0/WV061.0)
      EPS=EXPF(0.0329+TD2P(1HRN0))
      R2P=PV2/15+132+EPS)
1562 IF (R-0.0)157,157,158
  157 R2P=1.0
      GO TO 1.3
 158 IF (MOND-2) 159.160.160
  159 MOND=2
      IF(R2P~1.0)163.163.160
  160 IF (R2P-1.0)162.162.161
  161 R=R-DR
      GO TO 153
 162 RERGOR
     DR=0.1+DR
      MOND=MONDG1
      IF (MOND-4)161+161+163
 163 IF (LL-IDATA(3))164+165,991
  164 TD2=0.5*(TD26TD2P(1HRNO))
      GIL=TD2
      R2=0.5+(R24R2P)
C
C CALCULATE THE SHELTER WET-BULB AND EFFECTIVE TEMPERATURES.
C
      DO 1641 1+1+NW
 1641 AJIT(I)=A.IIT(I)=CW(I)
      LL+LL61
      60 10 61
  165 DO 1555 K=1+NW
      NEH+RMAX(K)61
      DO 1555 1=1+NEM
      T(1)=0.0
      DO 1555 J=1+NEM
      A([+J)=AINV(I+J+K)
      BB(J)+BMUL(J+K)
      T(])=T(])&A(],J)=BB(J)
 1555 TWALLEL+K)=TET
      1F(R2P-1.0)167+166+990
  166 TWRIINRNOI=TD2P(IHRNO)
      TEFF (IHRNO1= TD2P (IHRNO)
      GO TO 168
  167 THONTOPPEINRNOS
      DwC+10.0
      MK+]
  148 P$5+5+132+EXPF(0+0329+TW0)
      TWB(1HRHO)+(( 8P +PS$)+TD2P(1HRHO)+2000-0+(PS$+PV2))/( 8P 61+3+P
     145-5-3+0221
```

Į

٠.

...

H-11

169 IF(TWB(IHRNO)-TWO)170+172+171 170 TWO=TWO-DWO GO TO 168 171 TWO=TWOGDWO DW0+0+1+DW0 MM=MM61 IF (MM-3) 170+170+172 172 TEF1=107.5+(TO2P(IHRNO)-TWB(IHRNO))662.3+TWB(IHRNO) TEFF(IHRNO)=TEF1/(62.36TD2P(IHRNO)-TWB(IHRNO)) ¢ C PRINT RESULTS FOR THE HOUR. C IF(KIND-IDATA(5))173+174+989 173 KIND=KIND61 GO TO 180 174 IF(IDATA(11))178+178+175 175 IF (1HRN0-1) 988+176+177 176 PRINT 2002 PRINT 2037 PRINT 2003 PRINT 2004 PRINT 2005 PRINT 2030 PRINT 2031 177 IF (IHRNO-LMN)1772+1771+1772 1771 LMN=LMN624 PRINT 2038 1772 F3-F1/P PPINT 2006+IMRNO+F3+TD2P(IMRNO)+TWB(IMRNO)+TEFF(IMRNO)+P4IRCOND+QW 1C+OLH+QSOLAR+QSEN+GL+QLITE+GEQUIP 178 IF (IHRNO- 1HRS) 179+187+987 179 KIND=1 150 TD2=TD2P(1(IRNO) R2=R2P AUT=ADTGOT TEFF(IHRNC&1)=TEFF(IHRNO) 24 (FIAD7-1-00001)58,55,55 C C ERROR NESSAGES 999 PRINT 2007+J+XI(J) GO TO 5000 998 PRINT 2005 GO TO 5000 997 PRINT 1009 1009 GO TO 5000 16 PRINT 2010 10 5000 995 1 2011 40 TO 5000 994 PRINT 2012+1455+TEFF(14810) GO TO 145 993 PRINT 2012: HRN. TEFFELHRNO: 60 10 131 992 PRINT 2014+1HRI.+TO2P(1FANO) GO TO 152 991 PRINT 2015 GO TO 165 990 PRINT 2016 H-12 GO TO 166

ŝ

A.M. De

Market Manual States of the

4

989 PRINT 2017 GO TO 174 988 PRINT 2018 GO TO 176 987 PRINT 2019 GO TO 187 986 PRINT 2036+TD2P(IHRNO)+IHRN . GO TO 156 _C _____C CALCULATE AND PRINT TIME-AVERAGE SHELTER TEMPERATURES. 187 TOMAX=T02P(1) INH=IHRS-1 LM=1 188 DO 190 L1=1+1HH IF (TCHAX-702P (L161))189,190,190 189 TOMAK=TD2P(L161) LM-1161 190 CONTINUE PRINT 2020 TOMAX . LH TDMIN=TD2P(1) LM=1 191 DO 193 L1=1, 1HH IF (TOMIN-TO2P (L161) 193,193,192 192 TOMIN=T02P(L161) LM=1161 193 CONTINUE PRINT 2032 TOMINILM TWMAX-TWB(1) LM=1 194 DO 196 L1=1, IHH IF (TWMAX-TWB (L161) 1195+196+196 195 TWMAX-TWB(L1G1) LM=L161 196 CONTINUE PRINT 2021+TWMAX+LH TWMIN=TWB(1) LM=1 197 DO 199 L1=1+1HH IF(TWMIN-TWB(L161))199+199+198 198 TWMIN=TWBILLGII LH=L161 199 CONTINUE PRINT 2033 TWNINGLM ETHAX=TEFF(1) LM=1 200 DO 202 L1=1+1HH IF (ETNAX-TEFF (L161) 1201+202+202 201 ETMAX + TEFFILIGI LM-L161 202 CONTINUE PRINT 2022 +ETHAX+LH ETMIN=TEFF(1) LM=1 203 DO 205 L1+1+1HH IFIETHIN-TEFFIL16111205+205+204 204 ETMIN-TEFFILIGIT LM=L161 205 CONTINUE PRINT 2034 (ETMINICH

Ţ

بي.

۰,

. .

• •

-

••

- -

• •

-

-

. .

H-13

	7
	PRINT 2023
	PRINT 2024
	TDW=0.0
	TWW=0.0
	TEW#0.0
	10 213 J-111083
	TwwsTww6TwB(J)
213	TEW=TEWGTEFF(J)
	TDS=TDW/HRS
	Tws=Tww/HRs
	TES=TEW/HRS
	PRINT 2039/TDS/THS/TES
206	17 (NUDATS/2000+207+206 LAm1
200	LF=24
	DO 2071 IDAY=1+NODAYS
	DO 207 J=LB+LE
	TDD(1DAY) = TDD(1DAY) & TD2P(J)
	TWD(IDAY)=TWD(IDAY)GTWB(J)
207	TED(ICAY)=TED(IDAY)6TEFF(J)
2071	LE-LC024 H9INT 2026
	DO 208 IDAYALENODAYS
	TDAVGIIDAYI=TDDIIDAYI/24.0_
	TWAVGIIDAYI=TWDIIDAY1/24.0
	TEAVG(ID),Y)=TED(IDAY)/24.0
208	PRINT 2026, IDAY, TDAVG(IDAY), TWAVG(IDAY), TEAVG(IDAY)
209	IF (NOINT 15000+5000+210
210	PRINI 2027 Nordencintet
	$DO 212 NI=1 \cdot ND \cdot 2$
	MM=(NIG1)/2
	ILT=INT(NJ)
	ILL=INT(NIG1)
	DO 211 MI=IL7+ILLL
	TO:(MM)=TO:(MM)GTO2P(M))
711	TELLMM) 4TELLMM) & TEELML)
	TDIAV(NM) = TDI(MM)/(INT(NIGI) = INT(NI)GI)
	TWIAV(MM)=TWI(MM)/(INT(NIG1)-INT(NI)61)
	TEIAV(NM)=TEI(MM)/(INT(NIG1)-INT(NI)61)
212	PRINT 2028+INT(NI)+INT(NIG1)+TDIAV(MH)+TWIAV(MH)+TEIAV(MH)
	IF (JJJJ-IDATA (4) 1186+5000+5020
100	
c	20.10.1311
č	
1001	FORMAT(F7.3.F7.1)
1003	FORMAT(F7+1+F4+1+F5+1+12+3F7+1+F5+0+F9+2+2F8+1+2F3+0+212)
1006	FORMATILISI
1007	FORMAT(F5+2)
1009	FORMATIFA(]) RADULTITA(), 254, 2454, 21
1014	FURMAISEFBEJEFUEEFFUEJE FORKATEF9, 2, FA, 1, FA, 5, FA, 2, F9, 2, F4, 1, FA, 2, 2F4, 1 }
1018	FORMAT(F5.0.2F9.2.2F8.1)
1019	FORMATIZFA.1.FS.21
1070	FORMAT(F7+1+213+2F5+2+F3+0)
1657	FORMAT(4F4+1+2F5+2)
	<i>H</i> _/Y
	<i>[' ' </i>

J

.]

]

[]

]

]

]

]

]

]

]

1

j j

2001 FORMAT(1H +*R DURING HOUR*+13+* IS *+F7+4+* WHICH IS LESS THAN 1+0 1. THEREFORE, THE LATENT ENERGY INTRODUCED BY THE OCCUPANTS HAS BEE 2N REDUCED +) 2002 FORMAT(1H1+25X++NOMINAL OCCUPANT ACTIVITY LEVEL++7X++400 BTU/HR 1-OLCUPANT+) 2003 FORMAT(1H0+68×++LOADS (BTU/HR)#) 2004 FORMAT(1H0+7X++VENT++59X++TRANS+ METABOLIC METABOLIC+) RATE 2005 FORMAT(1H SHTIME DBT ET BOUNDARY WBT AIRCOND SOLAR SENSIBLE LATENT CONDEN. LIGHTING EQUIPMENT 2+1 2006 FORMAT(1H +14+3X+4(F4+1+3X)+8(F8+0+3X)) 2007 FORMAT(1H ++INCLINATION ANGLE XI(++I2++) IS ++F6+2+++ THIS VALUE M IUST BE 90 DEG. OR LESS. #) 2008 FORMATCH ++THE LATITUDE OF THE SHELTER IS GREATER THAN THE PROGRA 1M CAN HANDLE FOR THIS DAY OF THE YEAR +) 2010 FORMATTIH ++THE LIMIT ON LAYMAX OR ON NMAX OF BOUNDARY ++12++ HAS 1BEEN EXCEEDED.+) 2011 FORMAT(1H ++THE NUMBER OF SHELTER BOUNDARIES, NW+ HAS BEEN EXCEEDE MACHINE ERROR +) 1D. 2012 FORMAT(1H ++SHELTER EFFECTIVE TEMPERATURE DURING HOUR+,14++ IS +F5 1.1.* WHICH EXCEEDS THE LIMITS OF THE METABOLIC RELATIONS.**) 2014 FORMAT(1M ++DRY-BULB TEMPERATURE DURING HOUR ++13++ IS ++F5+1++ WH IICH EXCEEDS THE LIMITS OF THE METABOLIC RELATIONS 2015 FORMAT(1H ++ THE NUMBER OF ITERATIONS FOR AN INCREMENT HAS EXCEEDE 1D THE VALUE OF IDATA(3).+) 2016 FORMAT(IN ++THE RELATIVE HUMIDITY IN THE SHELTER HAS EXCEEDED SATU 1RATION.#1 2017 FORMAT(1H ++THE NUMBER OF INCREMENTS IN THE HOUR EXCEEDS THE VALUE 1 OF [DATA(5)#) 2018 FORMAT(1H ++THE HOUR NUMBERS ARE NOT INDEXING PROPERLY++) 2019 FORMAT(1H ++THE HOUR NUMBER HAS EXCEEDED THE LENGTH OF OCCUPANCY++ 1) 2020 FORMAT(1H0+15X++MAX+ DRY-BULB TEMP+ DURING OCCUPANCY++6X+F4+1++ AT 1+,14,+ HOURS AFTER BEGINNING OF OCCUPANCY+) 2021 FORMAT(1H0+15. +MAX+ WET-BULB TEMP+ DURING OCCUPANCY++6X+F4+1+* AT 1++14++ HOURS ATTER BEGINNING OF OCCUPANCY+) 2022 FORMAT(1HC+15X+@MAX EFFECTIVE TEMP+ DURING OCCUPANCY++6X+F4+1+# AT 1+,14++ HOURS AFTER BEGINNING OF OCCUPANCY+) 2023 FORMAT(1H1+39X+*TIME-AVERAGE TEMPERATURE VALUES*) 2024 FORMAT(1H3+26X++FOR ENTIRE DURATION OF OCCUPANCY++16X++D3T++7X++WB \T++8X++ET+) 2025 FORMAT(1H0:26X: FOR EACH DAY OF OCCUPANCY +) 2026 FORMAT(1H +64X+*DAY *+12+3X+F5+1+2(5X+F5+1)) 2027 FORMAT(1H0+26X+*FOR SPECIFIC INTERVALS*+16X+*HRS*) 2028 FORMAT(1H +59%+14++++14+5%+F5+1+2(5%+F5+1)) CFM/ DEG DEG 2030 FORMAT(1H + MR DEG +) F+) 2031 FORNATIIN +8X++OCC F - **F** 2032 FORMAT(1H0+15x++MIN+ DRY-B)LB TEMP+ DURING OCCUPANCY++6x+F4+1++ AT 1++14++ HOURS AFTER BEGINNING OF OCCUPANCY+1 2033 FORMAT(1H0+15X++MIN+ WET-BULB TEMP+ DURING OCCUPANCY++6X+F4+1++ AT 1+.14.+ HOURS AFTER BEGINNING OF OCCUPANCY+) 2034 FORMATCINO+15X++MIN EFF2CTIVE TEMP+ DURING OCCUPANCY++6X+F4+1++ AT 1++14++ HOURS AFTER BEGINNING OF OCCUPANCY+1 2035 FORMAT(1H (73X+F5+1+2(5X+F5+1)) 2036 FORMATCH ++TO2P=++Flo+1++ AT ++131 2037 FORMATELHOISEXIPVALUES ARE FOR LAST TIME INCREMENT OF EACH HOURD 2038 FORMAT(1X) 5000 STOP END

H-15

779

• •

...

1.0

<pre>.lenerol American Transportation Corporation, Niles, Ill.</pre>	General American Transportation Corporation, Niles, Ill.
EFFIFER ENVIRONMENTAL PREDICTION (SHEP) CONFUTER CODE,	SHELTER ENVIRONMENTAL PREDICTION (SHEP) COMPUTER CODE,
NOLIFICATION 3	MODIFICATION 3
00D Work Unit 1215A	OCD Work Unit 1215A
Final Report 1423 (UNCIASSIFIED)	Final Report 1423 (UNCLASSIFIED)
by C. E. Rathmann, R. J. Baschiere	by C. E. Rathmann, R. J. Baschiere
June, 1968, pp. 108	June, 1968, pp. 108
The Shelter Environmental Prediction (SHEP) Computer Code,	The Shelter Environmental. Prediction (SHEP) Computer Code,
Mod. 3, calculates the response of a shelter to thermal	Mod. 3, calculates the response of a shelter to thermal
loads and inlut air conditions. The manual explains the	loads and inlet air conditions. The manual explains the
various features of the code, presents the I/O formats,	various features of the code, presents the I/O formats,
gives sample data values and includes a typical applica-	gives semple data values and includes a typical applica-
tion.	tion.
ENVIRONATINT, CONFINED ENVIRONMENTS, FALLOUT SHELTERS, COM-	ENVIRONMENT, CONFINED ENVIRONMENTS, FALLOUT SHELVERS, COM-
PUTEMS, PROGRAMMING (COMPUTERS)	PUTERS, PROGRAMMING (COMPUTERS)
General American Transportation Corporation, Niles, Ill.	General American Transportation Corporation, Niles, Ill.
SECTIER ENVIRONMENTAL PREDICTION (SHEP) COMPUTER CODE.	SHELTER FUNTRONNEWTAL PREDICTION (SHEP) COMPUTER CODE,
WODIFICATION 3	MODIFILATION 3
500 Work Unit 1215A	OCD Work Unit 1215A
Final Report 1423 (UNCLASSIFIED)	Final Report 1423 (UNCLASSIFIED)
by C. E. Rathmann, h. J. Baschiere	by G. E. Rathmann, R. J. Baschiere
June, 1959, pp. 108	June, 1968, pp. 108
The Shelter Environmental Prediction (SHEP) Computer Code,	The Shelter Environmental Prediction (SHEP) Computer Code,
Nod. 3, calculates the response of a shelter to thermal	Mod. 3, calculates the response of a shelter to thermal
loads and inlet air conditions. The manual explains the	loads and inlet air conditions. The manual explains the
various features of the code, presents the I/O formats,	various features of the code, presents the I/O formats,
gives sample data values and includes a typical applica-	gives sample data values and includes a typical applica-
tion.	tion.
TROMMENT, CONFINED ENVIRONMENTS, FALLOUT SHELTERS, COM-	ENVIRONMENT, CONFINED ENVIRONMENTS, FALLOUT SHELFERS, COM-
IS, PROGRAMMING (COMPUTERS)	PUTERS, PROGRAMMING (COMPUTERS)

-

•

÷.