NRL Report 7421

Infrasonic Far-Field Radiation From a Turbulent Wake

00 :

3

2

747

AD

JOHN A. DESANTO

Propagation Branch Acoustics Division

June 29, 1972



6



NAL ENALTECHNICA.

NAVAL RESEARCH LABORATORY Washington, D.C.

Approved for public release: distribution unlimited.

DOCUMENT	CONTRAL OVICE					
	CONTROL DATA - R	L E D				
Security classification of title, body of abstract and in	ndexing annotation must be	entered when the	overall report in classified)			
OP NATING ACTIVITY (Corporate author)		20. REPORT SECURITY CLASSIFICATION				
Naval Research Laboratory		UNULASSIFIED				
Washington, D.C. 20390		24 CHOUP				
REPORT						
INFRASONIC FAR-FIELD RADIATIO	ON FROM A TUR	BULENT W	AKE			
Interim report on a continuing problem.	•					
John A. DeSanto						
REPORT DATE	78. TOTAL NO	OF PAGES	IN NO OF HERS			
June 29, 1972						
NRL Problem S01-40	W. OWIGINATO	- J HENOHT NUV	n(-13)			
b. PROJECT NO	ND					
		NRL Report 7421				
RF 00-002-402	ST. OTHER REP		ther numbers that may be assigned			
	this report)					
d.						
O DISTRIBUTION STATEMENT						
Approved for public release; distribution	n unlimited.	ent of the N	vity avy parch			
	Arlington, Va. 22217					
The acoustic far-field pressure wake is calculated using Light radiation intensity is plotted a and of the ratio of wake wave	e and intensity due hill's free-turbuler as a function of th length to radiatin	e to a turbul nce theory. e Mach num g wavelengti	ent The aber a.			
D 100 1473 (PAGE 1)						

14	KEY WORDS	LINK A LINK B			ка	LINK C		
L		HOLE	47	ROLE	WT	ROLE	WT	
								ļ
							1	1
	Wakes							Į
	Turbulence							1
	Extremely low radio frequencies							
	Electromagnetic radiation							ł
	Far-field							ł
								ļ
								i
								1
			l I			ţ İ		ļ
			i i		· [·		ļ İ	Į
			(1			1		ļ
			{					Į
			(1	ļ
ĺ			t i					ł
							1	1
						1		ļ İ
							ţ l	
								1
								1
			1					
			ļ					ļ
		1						1
							ļ l	1
			ļ į					
		1	1					
			۱ I					
			1					
			ţ l					
DD	100 1473 (BACK)							
PAGE	· 2)	-	Security Classification					
•								
		5 V						

.

INFRASONIC FAR-FIELD RADIATION FROM A TURBULENT WAKE

INTRODUCTION

The problem considered in this short report is the calculation of the far-field intensity (or pressure) due to radiation from volume turbulence. The specific question to be answered is: What is this far-field intensity at extremely low frequencies (infrascund)?

In the second section the far-field pressure is calculated using Lighthill's relation for the pressure due to volume turbulence (1,2). To do this requires certain assumptions about the turbulent velocity field, namely, that it be isotropic and have the form of an outgoing spherical wave. The basic result of the second section is that the infrasonic farfield intensity is proportional to $M^4(\Lambda/\lambda)^6$ where M is the Mach number, Λ is the turbulent wavelength, and λ is the radiated wavelength. For infrasound (large λ) this factor is very small. A plot is given showing the intensity as a function of M and Λ/λ .

Finally, the last section contains a short summary of both assumptions and omissions.

THEORY

The spectral pressure $p(\mathbf{r})$ at the field point \mathbf{r} (in three dimensions), due to volume turbulence arising from a turbulent velocity field $v_m(\mathbf{r}_0)$ at the point \mathbf{r}_0 (m = 1, 2, 3), is given by Lighthill (1,2) as

$$p(\mathbf{r}) = \frac{\rho_0}{4\pi} \int \partial_{0m} \partial_{0n} v_m(\mathbf{r}_0) v_n(\mathbf{r}_0) \frac{e^{ik|\mathbf{r}-\mathbf{r}_0|}}{|\mathbf{r}-\mathbf{r}_0|} d\mathbf{r}_0$$
(1)

where

$$\partial_{0m} \equiv \frac{\partial}{\partial X_{0m}}$$

differentiates on the "zero" coordinate. The Einstein summation convention is assumed here. The density of the medium is ρ_0 and $k = 2\pi/\lambda$. Further manipulations of this volume integral yield (1,2)

$$p(\mathbf{r}) = \frac{\rho_0}{4\pi} \partial_m \partial_n \int d\mathbf{r}_0 v_m(\mathbf{r}_0) v_n(\mathbf{r}_0) \frac{e^{ik|\mathbf{r}-\mathbf{r}_0|}}{|\mathbf{r}-\mathbf{r}_0|}.$$
 (2)

In the far field (large r)

$$\frac{e^{ik|\mathbf{r}-\mathbf{r}_0|}}{|\mathbf{r}-\mathbf{r}_0|} \sim \frac{e^{ikr}}{r} e^{-ikr_0\cos\theta_0}$$
(3)

where $\mathbf{r} \cdot \mathbf{r}_0 = rr_0 \cos \theta_0$, and hence, for large r,

$$p(\mathbf{r}) \sim \left(\partial_m \partial_n \frac{\varepsilon^{ikr}}{r}\right) Q_{mn}$$
 (4)

where

$$Q_{mn} \equiv \frac{\rho_0}{4\pi} \int d\mathbf{r}_0 v_m(\mathbf{r}_0) v_n(\mathbf{r}_0) e^{-ikr_0 \cos\theta_0} . \qquad (5)$$

If the turbulence is assumed to be isotropic,

$$v_m(\mathbf{r}) = v_m(r) , \qquad (6)$$

and behaves like a spherical wave (with wavenumber K which could have a positive imaginar part), then

$$v_m(r) = v_m \frac{e^{iKr}}{Kr} . \tag{7}$$

 Q_{mn} then can be evaluated as $(K = 2\pi/\Lambda)$

$$Q_{mn} = \frac{\rho_0}{4\pi} \int_0^\infty dr_0 \int_0^\pi d\theta_0 \int_0^{2\pi} d\phi_0 r_0^2 \sin \theta_0 v_m(r_0) v_n(r_0) e^{-ikr_0 \cos\theta_0}$$
$$= \frac{i\rho_0 v_m v_n}{2kK^2} \ln\left(\frac{1+\frac{\Lambda}{2\lambda}}{1-\frac{\Lambda}{2\lambda}}\right)$$
(8)

where integral tables (3) have been used for the value of the r_0 integration. Introducing the adiabatic compressibility K_s , defined by

$$K_{s} = (\rho_{0}c^{2})^{-1}$$

where c is the velocity of sound in water, Eq. (8) becomes

$$Q_{mn} = \frac{iv_m v_n}{K_s c^2} \frac{1}{2kK^2} \ln \left(\frac{1 + \frac{\Lambda}{2\lambda}}{1 - \frac{\Lambda}{2\lambda}} \right).$$

Further approximation of this quadrupole term by its diagonal values yields (δ_{mn} is the Kronecker delta)

$$Q_{mn} \approx \frac{iM^2}{2K_s k K^2} \delta_{mn} \ln \left(\frac{1 + \frac{\Lambda}{2\lambda}}{1 - \frac{\lambda}{2\lambda}} \right)$$
(9)

NRL REPORT 7421

where M = v/c is the Mach number and $v = v_m$. In addition, in the far field, the term in brackets in Eq. (4) can be written as

$$\partial_m \partial_n \left(\frac{e^{ikr}}{r}\right) \sim (ik)^2 \left(\frac{e^{ikr}}{r}\right) \frac{\partial r}{\partial x_m} \frac{\partial r}{\partial x_n}$$

Using the approximation

$$\frac{\partial r}{\partial x_m} \frac{\partial r}{\partial x_n} \approx \delta_{mn}$$

with Eq. (9), and the result $\delta_{mn}\delta_{mn} = \delta_{nn} = 3$, it is possible to write Eq. (4) as

$$p(\mathbf{r}) \sim \frac{-3i}{2} \frac{e^{ikr}}{kr} \frac{M^2}{K_s} \left(\frac{\Lambda}{\lambda}\right)^2 \ln\left(\frac{1+\frac{\Lambda}{2\lambda}}{1-\frac{\Lambda}{2\lambda}}\right)$$
(10)

and the far-field intensity I as

$$I(r) \sim \frac{9}{8} \frac{cM^4}{(kr)^2 K_{\varepsilon}} \left(\frac{\Lambda}{\lambda}\right)^4 \left[\ln \left(\frac{1 + \frac{\Lambda}{2\lambda}}{1 - \frac{\Lambda}{2\lambda}} \right) \right]^2 . \tag{11}$$

For very low frequencies (infrasound, λ large), Eq. (11) can be written

$$l(r) \sim \frac{9}{8} \frac{cM^4}{(kr)^2 K_s} \left(\frac{\Lambda}{\lambda}\right)^6 .$$
 (12)

a

Hence, in addition to the usual spherical spreading loss, there is a dependence on the Mach number M raised to the fourth power, and to the ratio of turbulent wavelength to radiated wavelength raised to the sixth power. There is also a factor of λ in kr. Figure 1 is a plot of the ratio $I(r)/I_0$ versus Λ/λ from Eq. (12). The reference level is a comparison source I_0 having an output of 0.64×10^{-12} watts/cm² (a pressure level of 1 dyne/cm²). The quantity I/I_0 is plotted in decibels at a range r of 1 naut mi and for an infrasonic wavelength $\lambda = 500$ ft (or a frequency of 10 Hz). The intensity at a new wavelength λ_1 can be found from the relation $I_1 = I(\lambda/\lambda_1)$. For example, doubling the wavelength ($\lambda_1 = 2\lambda$, frequency = 5 Hz) decreases each of the 10-Hz curves by 12 dB. Halving the wavelength (20 Hz) increases the curves by the same amount.

REMARKS

There are several assumptions and omissions in this calculation which should be restated. They are

a. Lighthill's turbulence theory for *free turbulence* is assumed valid, as is the farfield assumption. Effects due to boundary layer turbulence have been omitted. JOHN A. DeSANTO



Fig. 1—Relative plot of radiation intensity I/I_0 vs the ratio of turbulent to radiated wavelength Λ/λ for several values of the Mach number M at a range r of 1 naut mi. For the corresponding values at 1 yd add 66 dB.

- b. The turbulence was assumed to be *inotropic* and to radiate as a spherical wave without decay.
- c. No attempt was made to treat the *time dependence* of the pressure or turbulent velocity fields.

REFERENCES

- 1. Lighthill, M.J., Proc. Roy. Soc. A222:1 (1954).
- 2. Morse, P.M., and Ingard, K.U., "Acoustics 1," in "Encyclopedia of Physics," S. Flügge, ed., Berlin: Springer, 1961.
- 3. Burington, R.S., "Handbook of Mathematical Tables and Formulas" 4th Ed., New York: McGraw-Hill, 1965.

4