

THE INTELLIGIBILITY OF HYDROGEN-SPEECH
AT 200 FEET OF SEAWATER EQUIVALENT


by

Russell L. Sergeant, Ph.D.

NAVAL SUBMARINE MEDICAL RESEARCH LABORATORY
NAVAL SUBMARINE MEDICAL CENTER REPORT NO. 701


Bureau of Medicine and Surgery, Navy Department
Research Work Unit M4306.03-2020D.09

Transmitted by:



J.D. Harris, Ph.D.
Head, Auditory Research Branch

Reviewed and Approved by:



Charles F. Gell, M.D., D.Sc. (Med)
Scientific Director
NAVSUBMEDRSCHLAB

Reviewed and Approved by:



J. D. Bloom, CDR MC USN
Officer in Charge
NAVSUBMEDRSCHLAB

Approved and Released by:



J.E. Stark, CAPT, MC, USN
COMMANDING OFFICER
Naval Submarine Medical Center

Approved for public release; distribution unlimited.

SUMMARY PAGE

THE PROBLEM

To evaluate the effect of a hydrogen breathing mixture on the intelligibility of a talker's speech.

FINDINGS

Mean intelligibility scores at a simulated depth of 200 feet of salt water were approximately the same for speech produced breathing 97 per cent helium or 97 per cent hydrogen mixtures. The speech production in both gas mixtures was approximately 35 percentage points less intelligible than speech produced in air at one atmospheric pressure (1 ATA) and 25 percentage points less than speech produced in air at 7 ATA.

APPLICATION

Information contained in this report is useful to the design of communication systems intended to improve production of speech by divers during deep-submergence operations.

ADMINISTRATIVE INFORMATION

This investigation was conducted as part of Bureau of Medicine and Surgery Work Unit M4306.03-2020D - Evaluation of Underwater Communications Systems for Navy Divers. The assistance of Dr. Harry Cooker was furnished under ONR Contract with the University of Connecticut (N00014-67-A-0197-0001). The present report is No. 9 on this Work Unit. It was approved for publication on 1 March 1972, and designated as Naval Submarine Medical Research Laboratory Report No. 701.

PUBLISHED BY THE NAVAL SUBMARINE MEDICAL CENTER

ABSTRACT

The purpose of this study was to evaluate the effect of breathing hydrogen on the intelligibility of speech. Taped recordings were made of a talker breathing normal air within one atmospheric pressure absolute (ATA) and also breathing successively, hydrogen, helium, and air, at 7 ATA. Responses to the recordings by six panels of listeners were analyzed. As expected, the speech in air at 1 ATA was the most intelligible, and the speech in air at 7 ATA was next best. There was no appreciable difference in mean intelligibility between the helium and hydrogen gas mixtures. These results indicate that any decision in favor of using either hydrogen or helium mixtures in deep sea diving should not depend upon differences in intelligibility of unprocessed helium - versus hydrogen-speech.

1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025

THE INTELLIGIBILITY OF HYDROGEN-SPEECH AT 200 FSW EQUIVALENT

INTRODUCTION

This and other laboratories have considered the effects upon speech intelligibility of different gas mixtures which might be used by deep sea divers⁸. The simple effects of breathing helium-mixtures are striking. In addition to obvious changes in the quality of the speaker's voice, the intelligibility is reduced, especially under the restraints of hyperbaric environments. Theoretical explanations of helium-speech lead one to conclude that intelligibility would be even more seriously affected if divers breathed mixtures rich in hydrogen.

At the present time very little is known about the physiological effects of breathing hydrogen-oxygen (hydrox) mixtures. Although hydrogen is available in large quantities (i. e., H_2O), most researchers shy away from the mixture due to the extremely high possibility of explosion. Edel¹ points out that under hyperbaric conditions the amount of oxygen required for breathing by the diver can be made small enough to eliminate hazards of explosion for hydrox mixtures. It seems plausible to him that hydrogen could be the common breathing mixture used in dives at levels deeper than 200 feet. If the disadvantages of decompression requirements, bends, and other physiological factors, which are present with diving gases currently in use, do not exist or are less for hydrogen-rich mixtures, then hydrogen might well replace helium as the deep sea diver's

desired breathing mixture at great depths. One of the primary considerations in the decision to use hydrox mixtures would be the effect it has on diver communication by voice.

The purpose of the present study was to evaluate the effect of breathing hydrogen on the intelligibility of speech.

PROCEDURE

Tape recordings were made of speech produced while the talker breathed air at 1 ATA and air, hydrogen, and helium mixtures compressed to 7 ATA during an experimental dry chamber dive conducted at the J & J Marine Diving Company in Pasadena, Texas. Appendix I is the dive-protocol followed during the collection of speech samples. Responses by listening panels to the recordings were later obtained and analyzed.

Recording of Stimulus Material. Recordings were made within a small pressure chamber of several 50-word lists of the Modified Rhyme Test (MRT)³ using a General Radio 1550-P5 piezoelectric microphone (see Ref. 7 for a description of the characteristics of this microphone under hyperbaric conditions). The recording system included a Uher professional quality portable tape recorder which was outside the chamber during actual recording. An adult male talker read the word lists while sitting inside the chamber. He had received training in reading the intelligibility testing materials prior to the experiment.

The gas mixtures which the talker was breathing when his speech was recorded were as follows:

- a) Air at 1 ATA. Immediately prior to pressurizing the chamber, talker breathing normal air mixture assumed to be 80% N₂ and 20% O₂ inside the chamber. Ambient pressure was 1 ATA.
- b) Hydrogen. Immediately upon reaching pressure of 7 ATA, chamber atmosphere approximately 97% N₂ and 3% O₂, diver breathing mixture of 97% H₂ and 3% O₂ through oral-nasal mask.
- c) Helium. Same conditions as above except breathing mixture in diver's mask changed to 97% He and 3% O₂.
- d) Air at 7 ATA. Diver's breathing mixture in mask changed to 80% N₂ and 20% O₂.

Presentation of Stimulus Material to Listeners. Listeners heard the recorded speech in a group audio-testing room that was equipped with 50 matched TDH-39 earphones embedded in circumaural cushions. The stimulus tapes were presented to 90 normal-hearing Navy enlisted men divided into six listening panels of 15 each. Table 1 shows which gas the talker was breathing when he spoke and which MRT List he was reading for each group of listeners. The words were presented at an average level of 75 dB Sound Pressure Level (SPL) to panels 1 through 4, and 65 dB SPL to panels A and B. The output of a Grason-Stadler 901A Noise Generator was combined

with the speech signals in order to produce a -10 dB speech-to-noise ratio (S/N). Measurements of SPL at the ear were obtained using a flat-plate acoustic calibration coupler. Listeners responded on IBM answer sheets specially constructed for use with the MRT word lists.⁵

RESULTS AND ANALYSES

Table 1 shows the mean per cent correct responses for each word list. The poorest score was 28% for the helium condition, while the best performance was obtained as expected for the two pre-dive lists when the talker was breathing a mixture of air at 1 ATA. Two basic analyses were performed with the data, one to test the equivalency of listening panels and word lists, the other to consider the effects of breathing mixture on the talker's overall intelligibility.

Listeners and Word Lists. Listeners were randomly selected from Navy enlisted men who had passed the physical requirements for entrance into Submarine Service. In order to assess effects which might have been caused by differences in either the particular panels of listeners tested or the specific 50-word lists used as the testing material, an analysis of variance was made of the responses by listening Panels A and B. The ambient pressure and gas mixture for the talker was identical for these tests, i. e., air at 7 ATA. Results of a Lindquist Type 1 two-factor mixed design⁴ indicated that there was no difference (at the 95 per cent level of statistical confidence) between the lists nor between the panels. Interaction between panels and lists also was not statistically significant. We conclude

Table 1. Mean Per Cent Correct Responses by Listening Panels According to MRT List Heard and the Gas Mixture which the Talker was Breathing

Panel	Breathing Mixture	MRT List	Per Cent Correct
A	Air at 7 ATA	E	56
		A	55
B	Air at 7 ATA	E	54
		A	53
1	Air at 1 ATA	B	69
		A	70
2	Hydrogen at 7 ATA	C	38
		A	34
3	Helium at 7 ATA	D	28
		A	35
4	Air at 7 ATA	E	59
		A	59

from these data that analysis of responses by Panels 1 through 4 to the recordings of speech which represents the different types of breathing mixtures could be safely made without undue errors arising from effects of either listening panels or word-lists.

Breathing Mixtures. Table 2 summarizes a Lindquist Type 1 analysis of the responses by Panels 1 through 4. Neither the interaction between gas-mixture and Lists nor the main effects of the MRT Lists were statistically significant. The main effect of the gas

mixture on the other hand revealed significant differences ($F = 245$; $df = 3,56$). The mean intelligibility scores in Table 1 show that the speech produced in air at 1 ATA was most intelligible with 69 and 70% correct responses. The responses to speech produced in the hydrogen and helium mixtures under pressures of 7 ATA were equally poor, yielding mean scores ranging from 28 to 38%. The results for speech in air at 7 ATA lie between the higher scores for air at 1 ATA and the scores for the hydrogen and helium conditions at 7 ATA. The difference

between scores obtained for air at 1 ATA and at 7 ATA for Panels 1 and 4 (Speech playback level consistently 75 dB SPL) can be attributed solely to effects of increased ambient pressure upon the intelligibility of the talker's speech. This finding supports other reports^{2,9} of deterioration in the intelligibility of speech in air under hyperbaric conditions.

DISCUSSION

The similarity of mean responses for the hydrogen and helium conditions was not expected. Differences between the physical properties of hydrogen and air are in the same direction,

but to a much greater degree, than differences between helium and air. For example, the velocities of sound for air, helium and hydrogen are respectively 331, 970 and 1270 meters/sec. Since the quality of helium-speech is noticeably different than the quality of speech in air, it was assumed that the difference in quality for hydrogen-speech would be even greater.

Concentrations of energy around certain frequency areas in a speech signal called "formants" are dependent upon characteristics of the human resonators for speech. One of the basic physical parameters which determines the frequency characteristics of any resonator

Table 2. Summary of Analysis of Variance

Source	df	ms	F-Ratio
BETWEEN SUBJECTS	59	134	
B-Gas Mixture	3	2450	245.3*
Error Term (b)	56	10	
WITHIN SUBJECTS	60	17	
A-MRT Word List	1	11	1.5
AB-Gas/List Interaction	3	42	2.6
Error Term (w)	56	16	
TOTAL	119		

* Significant beyond 99% level of confidence.

is the velocity of sound through the gas that is inside the resonator. Quite probably, the primary effect of both helium and hydrogen gas mixtures on the intelligibility of speech is due to changes in the resonating characteristics of the human mechanism for producing speech. Both helium and oxygen cause an increase in the velocity of sound as compared with the velocity in air, and consequently there is the same type of distortion for both gas mixtures, i. e., an upward shift of the frequency of the formants of speech (see Ref. 6 for a more detailed explanation of relations between breathing mixtures and the resonators for speech). As a result, other clues than frequency characteristics, such as prosodic features and temporal patterns, probably assume more prominent roles in overall talker intelligibility. These results indicate that factors associated with the intelligibility of unprocessed speech should not be used in arguments influencing a decision to use hydrogen in lieu of helium in breathing mixtures for deep sea divers.

Speech produced while the talker was breathing hydrogen or helium was compared in this study from the point of view of overall intelligibility of the resultant unprocessed vocal output. Future evaluations of speech with these gases should (1) relate perceptual aspects of the speech with its acoustic characteristics, (2) specify what particular features of the speech signal can be used to determine how intelli-

gible different talkers are, and (3) evaluate effects of processing upon the intelligibility of speech in hydrogen. The first area would provide information which could help redefine specifications for the design of voice communications systems, including processing devices, for hydrogen and helium atmospheres. The second effort would provide clues which are pertinent to the selection of the best talkers for either gas mixture. The last area for investigation concerns the important question of whether or not the intelligibility of hydrogen speech can be successfully improved with presently available processors which were originally designed for use with helium-speech.

SUMMARY

Tape recordings were made of a talker's speech while he breathed air within 1 atmospheric pressure absolute (ATA) and successively, hydrogen, helium, and then air at 7 ATA. The recordings were later presented to panels of listeners. As expected, the speech in air at 1 ATA was most intelligible, that in air compressed to 7 ATA was next best. There was no appreciable difference in overall intelligibility between the helium and hydrogen conditions but both gases yielded worse intelligibility than air. These results indicate that any decision to use hydrogen or helium mixtures in deep sea diving should not depend upon differences in the intelligibility of unprocessed speech produced therein.

REFERENCES


1. Edel, P. Personnel Communication, November 1971.
2. Hollien, H. Speech Intelligibility in High Ambient Pressures. In Quarterly Report, Communication Sciences Laboratory, Vol. 7, No. 2, July 1969.
3. House, A.A., Williams, C., Hecker, M.H.L., & Kryter, K.D. Psychoacoustic Speech Tests: A Modified Rhyme Test. Electron Systems Division, USAF Sys. Com., Hanscom Field, Bedford, Mass., Tech. Documentary Report No. ESD-TDR-63-403, 1963.
4. Lindquist, E.F. Design and Analysis of Experiments in Psychology and Education. Boston: Houghton Mifflin Co., 1956.
5. Russotti, J.S. & Duffy, J.F. An Evaluation of Three Methods for Unscrambling Helium Speech Produced at Depths of 800 and 1000 Feet. NAVSUBMEDRSCHLAB Report No. 602, October 1969.
6. Sergeant, R.L. Speech During Respiration of a Mixture of Helium and Oxygen. Aerospace Med., 1963, 34, 826-829.
7. Sergeant, R.L. & Murry, T. Reciprocity Calibration of Microphones under High Ambient Pressures. NAVSUBMEDRSCHLAB Report No. 671, July 1971.
8. Sergeant, R.L. & Murry, T. (Eds.). Summary Proceedings of a Workshop on Helium Speech Processing. NAVSUBMEDRSCHLAB Report (in Press), 1972.
9. White, C.E. Effect of Increased Atmospheric Pressures upon Intelligibility of Spoken Words. Medical Research Laboratory, Memo Report 55-8, Groton, Conn. December 1955.

APPENDIX I
TRI-INERT DIVE

<u>Time (min)</u>	<u>Depth (fsw)</u>	<u>Breathing Mixture</u>	<u>Remarks</u>
-10	0	Air	Final systems checks. Diver enters chamber. Start Pre-dive speech recordings.
-2	0	Air	All cigarettes and open flames extinguished. Stop speech tests.
-1	0	Air	Hatch closed.
0	0	80He-20 O ₂	Start compression with N ₂ (diver breathing He-O ₂)
1/4	25	80He-20 O ₂	
1/2	50	80He-20 O ₂	
3/4	75	80He-20 O ₂	
1	100	97He-3 O ₂	Switch to 97% He-3% O ₂ (signal diver to vent) 1 rap
1 1/4	125	97He-3-O	
1 1/2	150	97He-3-O ₂	
1 3/4	175	97He-3-O ₂	
2	200	97H ₂ -3% O ₂	Arrive on bottom; switch to hydrogen-oxygen
3	200	97H ₂ -3% O ₂	Start communications tests
6	200	97H ₂ -3% O ₂	Dr. Alexander enters outer lock
7	200	97H ₂ -3% O ₂	Outer lock door closed

<u>Time (min)</u>	<u>Depth (fsw)</u>	<u>Breathing Mixture</u>	<u>Remarks</u>
8	0 OL	97H ₂ -3% O ₂	Start compression with N ₂ : Dr. breathing 80He-20 O ₂
8 1/4	25 OL	97H ₂ -3% O ₂	
8 1/2	50 OL	97H ₂ -3 O ₂	
8 3/4	75 OL	97H ₂ -3% O ₂	
9	100 OL	97H ₂ -3% O ₂	Switch Dr. to 97He-3 O ₂ (signal one rap for switch)
9 1/4	125 OL	97H ₂ -3% O ₂	
9 1/2	150 OL	97H ₂ -3% O ₂	
9 3/4	175 OL	97H ₂ -3% O ₂	
10	200 OL	97H ₂ -3% O ₂	Both locks equalized; stop communication test
11	200	97H ₂ -3% O ₂	Dr. Alexander takes blood sample
12	200	97He-3 O ₂	Switch diver to 97He-3 O ₂
12 1/2	200	97He-3 O ₂	Dr. Alexander in outer lock
13	200	97He-3 O ₂	Drop outer lock; start purge with N ₂
13 1/4	187 1/4 OL	97He-3 O ₂	
13 1/2	175 OL	97He-3 O ₂	
13 3/4	162 1/2 OL	97He-3 O ₂	
14	150 OL	97He-3 O ₂	Dr. Alexander shifts to 80 He-20 O ₂ (signal one rap)
14 1/4	137 1/2 OL	97He-3 O ₂	
14 1/2	125 OL	97He-3 O ₂	

<u>Time (min)</u>	<u>Depth (fsw)</u>	<u>Breathing Mixture</u>	<u>Remarks</u>
14 3/4	112 1/2 OL	97He-3 O ₂	
15	100 OL	97He-3 O ₂	Diver starts He-O ₂ speech test
15 1/4	87 1/2 OL	97He-3 O ₂	
15 1/2	75 OL	97He-3 O ₂	
15 3/4	62 1/2 OL	97He-3 O ₂	
16	50 OL	97He-3 O ₂	Dr. Alexander arrives at 50 feet. Hold for 1 minute.
17	50 OL	97He-3 O ₂	Start Dr. Alexander to next stop
17 1/3	40 OL	97He-3 O ₂	
17 2/3	30 OL	97He-3 O ₂	
18	20 OL	97He-3 O ₂	Dr. Alexander arrives at 20 feet. Hold for 4 3/4 minute
22	200 IL	Air	Diver switches to air: One rap to vent. Purge 11 with air
22 3/4	20 OL	Air	Start Dr. Alexander to 10 feet.
23	10 OL	Air	Dr. Alexander arrives at 10 feet. Hold for 5 minutes.
24	200 IL	Air	Stop air purge; start final communication tests.
28	10 OL	Air	Start Dr. Alexander to surface
29	0 OL	Air	Dr. Alexander arrives on surface.
31	200 IL	Air	Stop communication tests: Prepare for ascent to 1st stop.



UNCLASSIFIED

Security Classification		
DOCUMENT CONTROL DATA - R & D		
<i>(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)</i>		
1. ORIGINATING ACTIVITY <i>(Corporate author)</i> NAVAL SUBMARINE MEDICAL CENTER Naval Submarine Medical Research Laboratory		2a. REPORT SECURITY CLASSIFICATION UNCLASSIFIED
		2b. GROUP
3. REPORT TITLE THE INTELLIGIBILITY OF HYDROGEN-SPEECH AT 200 FEET OF SEAWATER EQUIVALENT		
4. DESCRIPTIVE NOTES <i>(Type of report and inclusive dates)</i> Interim Report		
5. AUTHOR(S) <i>(First name, middle initial, last name)</i> Russell L. Sergeant, Ph.D.		
6. REPORT DATE 1 March 1972	7a. TOTAL NO. OF PAGES 9	7b. NO. OF REFS 9
8a. CONTRACT OR GRANT NO. N00014-67-A-0197-0001	9a. ORIGINATOR'S REPORT NUMBER(S) NAVSUBMEDRSCHLAB RPT. #701	
b. PROJECT NO. M4303.03-2020D	9b. OTHER REPORT NO(S) <i>(Any other numbers that may be assigned this report)</i>	
c.		
d.		
10. DISTRIBUTION STATEMENT Approved for public release; distribution unlimited.		
11. SUPPLEMENTARY NOTES	12. SPONSORING MILITARY ACTIVITY Naval Submarine Medical Center Box 600 Naval Submarine Base New London, Groton, Conn. 06340	
13. ABSTRACT The purpose of this study was to evaluate the effect of breathing hydrogen on the intelligibility of speech. Taped recordings were made of a talker breathing normal air within 1 atmospheric pressure absolute (ATA) and also breathing hydrogen, helium and air at 7 ATA. Responses to the recordings by six panels of listeners were analyzed. As expected, the speech in air at 1 ATA was the most intelligible, and the speech in air at 7 ATA was next best. There was no appreciable difference in mean intelligibility between the helium and hydrogen gas mixtures. These results indicate that any decision in favor of using either hydrogen or helium mixtures in deep sea diving should not depend upon differences in intelligibility of unprocessed helium - versus hydrogen-speech.		

UNCLASSIFIED

Security Classification

14. KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
Hydrogen Speech						
Speech Intelligibility						
Underwater Communication						
Hyperbaric Speech						
Voice Communication Systems						
Divers' Speech						

UNCLASSIFIED

Security Classification