AD-754 336

- Trone

TESTS OF ROCK CORES, WARREN SITING AREA, WYOMING

Kenneth L. Saucier, et al

Army Engineer Waterways Experiment Station Vicksburg, Mississippi

March 1969

in sinds (15)

And the second states of the

**DISTRIBUTED BY:** 



U. S. DEPARTMENT OF COMMERCE 5285 Port Royal Road, Springfield Va. 22151 ar or a build a strategy of the set was the first that the set of the set of

the states descent of the detted States Gavernand

MISCELLANEOUS PAPER C-69-3

# TESTS OF ROCK CORES WARREN SITING AREA, WYOMING

Ьу

K. L. Saucier D. L. Ainsworth



March 1969

DODARD FEE OF FUT IN STATE THE THE PLANE UP 3)

. r vala led.

Approven

Sponsored by

Space and Missile Systems Organization U. S. Air Force Systems Command

Conducted by

U. S. Army Engineer Waterways Experiment Station CORPS OF ENGINEERS

Vicksburg, Mississippi

Each transmittal of this document entside the Department of Defense must have prior approval of the Space and Missile Systems Organization (SMQHF-2)

US ARMY INCLUEED, WATERWAYS EXPERIMENT STATION VOIDEBURG, MISSINSIPPI

# PAGES ARE MISSING IN ORIGINAL DOCUMENT

# Best Available Copy

A CONTRACTOR OF THE ADDRESS OF THE A		
For use of this form, see AR 340-15; the	AL CONVERSATION RECORD	
SUDJECT OF CONVERSATION		<u>29 February 1972</u>
		· .
Distribution Statement	on Reports	
PERSON CALLING	ADERESS	PHONE NUMBER APO EXTENSION
		•
PERSON CALLED	OFFICE .	PHONE NUMPER AND EXTENSION
	<u>.</u>	
	OUTGOING CALL	
-Euron Carling	OFFICE	PHONE NUMBER AND EXTENSION
Mr. James M. Polatty	Concrete Division	
PERSON CALLED	ADDRESS	PHONE NUMBER AND EXTENSION
Cantain R. U. Rullard	Space & Missile Systems Areast	atton
UNMARY OF CONVERSATION	Lopace & MISSILE Systems Urgani	.69 LIVII
		. •
I called SAMSO and tall	ked to CPT Bullard. CPT Bullard	was familiar with :
of AR 70-31. He agreed	that Statement A should be util	ized on all of the
SAMSO rock test reports	3.	
	· · · · · ·	
•		Davis
•	James M.	Palattylens
•	James M. POLATTY,	Palatte leger Chief
•	JAMES M. POLATTY, Engineering Mechan	Palatty lyw Chief nics Branch
•	JAMES M. POLATTY, Engineering Mechan Concrete Division	Palatte figue Chief nícs Branch
	JAMES M. POLATTY, Engineering Mecha Concrete Division	Palatty Lyw Chief nics Branch
Copy furnished:	JAMES M. POLATTY, Engineering Mecha Concrete Division	Palatty lyw Chief nics Branch
Copy furnished: Publications-Distributi	JAMES M. POLATTY, Engineering Mecha Concrete Division	Palatty Legu Chief nics Branch
Copy furnished: Publications-Distributi	JAMES M. POLATTY, Engineering Mecha Concrete Division	Palatty lyw Chief nics Branch
Copy furnished: Publications-Distributi Laura Hanisee said fol	JAMES M. POLATTY, Engineering Mecha Concrete Division	Palatty Legu Chief nics Branch for SAMSO Statement A :
Copy furnished: Publications-Distributi Laura Hanisee said fol C-69-3	JAMES M. POLATTY, Engineering Mecha Concrete Division ion covering rock tests f lowing MP's/were bo be changed to ;	Folatty Lyw Chief nics Branch For SA%SO Statement A :
Copy furnished: Publications-Distributi Laura Hanisee said fol C-69-3 C-69-12	JAMES M. POLATTY, Engineering Mecha Concrete Division	Palatty Leve Chief nics Branch for SAMSO Statement A :
Copy furnished: Publications-Distributi Laura Hanisee said fol C-69-3 C-69-12 C-69-16 C-20-6	JAMES M. POLATTY, Engineering Mecha Concrete Division ion covering rock tests f lowing MP's/were bo be changed to	Palatty lyw Chief nics Branch For SAMSO Statement A :
Copy furnished: Publications-Distributi Laura Hanisee said fol C-69-3 C-69-12 C-69-16 C-70-4 C-70-4	Jameo M. JAMES M. POLATTY, Engineering Mecha Concrete Division ion covering rock tests f lowing MP's/ware bo be changed to	Palatty Leve Chief nics Branch For SAMSO Statement A :
Copy furnished: Publications-Distributi Laura Hanisee said fol C-69-3 C-69-12 C-69-16 C-7C-4 C-7C-5 C-7C-7	JAMES M. POLATTY, Engineering Mecha Concrete Division ion covering rock tests f lowing MP's/were bo be changed to	Palatty lyw Chief nics Branch For SAMSO Statement A :
Copy furnished: Publications-Distributi Laura Hanisee said fol C-69-3 C-69-12 C-69-16 C-70-4 C-70-4 C-70-7 C-70-9	Jameo M. JAMES M. POLATTY, Engineering Mecha Concrete Division ion covering rock tests f lowing MP's/were bo be changed to	Palatty Lyn Chief nics Branch For SAMSO Statement A :
Copy furnished: Publications-Distributi Laura Hanisee said fol C-69-3 C-69-12 C-69-16 C-70-4 C-70-5 C-70-7 C-70-9 C-70-10 C-20-11	JAMES M. POLATTY, Engineering Mecha Concrete Division ion covering rock tests f lowing MP's/were bo be changed to	Palatty lyw Chief nics Branch For SA%SO Statement A :
Copy furnished: Publications-Distribut Laura Hanisee said fol C-69-3 C-69-12 C-69-16 C-7C-4 C-7C-6 C-7C-7 C-7C-7 C-7C-9 C-7C-10 C-7C-11 C-7C-14	Jameo M. JAMES M. POLATTY, Engineering Mecha Concrete Division ion covering rock tests f lowing MP's/were to be changed to :	Palatty lyw Chief nics Branch For SAMSO Statement A :
Copy furnished: Publications-Distributi Laura Hanisee said fol C-69-3 C-69-12 C-69-16 C-70-4 C-70-6 C-70-7 C-70-7 C-70-9 C-70-10 C-70-11 C-70-14 C-70-16	JAMES M. POLATTY, Engineering Mecha Concrete Division ion covering rock tests f lowing MP's/were bo be changed to	Palatty lyw Chief nics Branch For SAMSO Statement A :
Copy furnished: Publications-Distribut Laura Hanisee said fol C-69-3 C-69-12 C-69-16 C-7C-4 C-7C-6 C-7C-7 C-7C-9 C-7C-10 C-7C-10 C-7C-11 C-7C-14 C-7C-16 C-7C-16 C-7C-17	JAMES M. POLATTY, Engineering Mecha Concrete Division ion covering rock tests f lowing MP's/were to be changed to :	Palatty lyw Chief nics Branch For SAMSO Statement A :
Copy furnished: Publications-Distributi Laura Hanisee said fol C-69-3 C-69-12 C-69-16 C-70-4 C-70-5 C-70-7 C-70-9 C-70-10 C-70-11 C-70-14 C-70-14 C-70-16 C-70-17	JAMES M. POLATTY, Engineering Mecha Concrete Division ion covering rock tests f lowing MP's/were bo be changed to	Palatty lyw Chief nics Branch For SAMSO Statement A :
Copy furnished: Publications-Distributs Laura Hanisee said fol C-69-3 C-69-12 C-69-16 C-70-4 C-70-6 C-70-7 C-70-9 C-70-10 C-70-11 C-70-14 C-70-16 C-70-17	Jameo M. JAMES M. POLATTY, Engineering Mecha Concrete Division ion covering rock tests f lowing MP's/were to be changed to	Palatty lyw Chief nics Branch For SAMSO Statement A :
Copy furnished: Publications-Distributi Laura Hanisee said fol C-69-3 C-69-12 C-69-16 C-70-4 C-70-6 C-70-7 C-70-9 C-70-10 C-70-11 C-70-14 C-70-14 C-70-14 C-70-16 C-70-17 NH SACES EDI	JAMES M. POLATTY, Engineering Mecha Concrete Division ion covering rock tests f lowing MP's/were bo be changed to	Palatty lyw Chief nics Branch For SAMSO Statement A :
Copy furnished: Publications-Distributs Laura Hanisee said fol C-69-3 C-69-12 C-69-16 C-70-4 C-70-6 C-70-7 C-70-9 C-70-10 C-70-11 C-70-14 C-70-14 C-70-16 C-70-17 NH SCESEDING	JAMES M. POLATTY, Engineering Mecha Concrete Division lon covering rock tests f lowing MP's/were to be changed to :	Palatty Lyn Chief nics Branch For SAMSO Statement A :
Copy furnished: Publications-Distributi Laura Hanisee said fol C-69-3 C-69-12 C-69-16 C-70-4 C-70-6 C-70-7 C-70-9 C-70-10 C-70-11 C-70-14 C-70-14 C-70-16 C-70-17 NH CACES EDI	JAMES M. POLATTY, Engineering Mecha Concrete Division Ion covering rock tests f lowing MP's/were bo be changed to 	Palatty lyw Chief nics Branch For SAMSO Statement A :

MISCELLANEOUS PAPER C-69-3

Q

ი თ

754

44

# TESTS OF ROCK CORES WARREN SITING AREA, WYOMING

by

K. L. Saucier D. L. Ainsworth



March 1969

Reproduced by NATIONAL TECHNICAL INFORMATION SERVICE U S Department of Commerce Springfield VA 22151

Sponsored by

Space and Missile Systems Organization U. S. Air Force Systems Command

Conducted by

U. S. Army Engineer Waterways Experiment Station CORPS OF ENGINEERS

Vicksburg, Mississippi

Each transmittal of this document outside the Department of Defense must have prior approval of the Space and Missile Systems Organization (SMQHF-2)'

ABSTRACT

Laboratory tests were conducted on rock core samples received from ten core holes drilled in the Laramie range, Wycming, to determine the integrity and mechanical behavior of the materials. The results were to be used to determine the usefulness of the Warren Siting Area for potential missile sites. Series I tests (relative hardness, specific gravity, compressive strength, sonic velocity, etc.) indicated the materials to be relatively uniform, competent granite, diorite, and gneiss rock. Series II tests (triaxial, hydrostatic, and confined compression) indicated the rock to be rather incompressible and brittle up to 36,000-psi triaxial stress. Series III tests indicated that the granite and diorite had Hugoniot elastic limits of 50 kilobars or more and the gneiss approximately 20 kilobars. In order to better define the physical and mechanical behavior of the rock, triaxial tests to approximately 150,000 psi on intact and jointed specimens and equation of state tests at pressures to approximately 600 kilobars should be conducted.

FREFACE

This study was conducted in the Concrete Division of the U.S. Arry Engineer Waterways Experiment Station (WES) under the sponsorship of the U. C. Air Force Space and Missile Systems Organization (SAMSO) of the Air Porce Systems Command. The study was coordinated with 11T Rupert G. Tart, Jr., SAMSO Project Officer. and Mr. Norman P. Langley of Aerospace Corporation, San Bernardino. California. The work was accomplished during the period June 1968 to February 1969 under the general supervision of Mr. Bryant Mather. Chief, Concrete Division, and under the direct supe. ision of Messrs. J. M. Polnity, Chiof, Engineering Mechanics Branch, W. O. Tynes, Chief, Concrete and Rock Properties Section, and K. L. Saucier, Project Officer. Project leaders were Mr. D. L. Ainsworth for the special (Series III) tests, Mr. A. D. Buck for the petrography work, and Mr. E. E. McCoy for the thermal and sonic work. Mr. Saucier performed the majority of the program analysis, and prepared this report with the assistance of Mr. Ainsworth.

Directors of the WES during the investigation and the preparation and publication of this report were COL John R. Oswalt, Jr., CE, and COL Levi A. Brown, CE. Technical Director was Mr. J. B. Tiffany; Assistant Technical Director was Mr. F. R. Brown.

#### CONTRIPTS

i

.

ł

<sup>7</sup> પૈત્રની મહત્વ તેઓ જે છે. આ ગામ છે. આ ગામ આ

da sa kangang sa kanga

ABSTRACT	3
PREFACE	1
CONVERSION FACTORS, BRITISH TO METRIC UNITS OF MEASUREMENT	7
CHAPTER 1 INTRODUCTION	8
1.1 Background	8
1.2 Objective	- 8
1.3 Scope	8
1.4 Samples	9
1.5 Report Requirements	10
CHAPTER 2 TEST METHODS	12
2.1 Schmidt Number	12
2.2 Specific Gravity and Porosity	12
2.3 Tensile and Shear Strengths	13
2.4 Dynamic Properties	าโ
2.5 Petrographic Examinati m	14
2.6 Strength Tests	71
2.7 Shock Response	15
CHAPTER 3 SERIES I TEST RESULTS	17
3.1 Diorite	17
3.2 Granite	10
3.3 Gneiss	22
CHAPTER 4 SERIES II TEST RESULTS	25
4.1 Laramie Core	25
4.2 CR-42 Core	26
4.3 CR-10 Core	28
4.4 Thermal Property Tests	30
CHAFTER 5 SERIES III TEST RESULTS	31
5.1 Tests	21
5.2 Discussion of Results	- 35 21

chapter 6	CONCLUSIONS AND RECOMMENDATIONS	34
6.1 ( 6.2 I	ConclusionsRecommendations	34 35
APPEIDIX A	SERIES III TESTS, 13 FEBRUARY 1969	37
APPEIDIX B	DATA REPORT - LARAMIE CORES, 16 AUGUST 1968	67
APPENDIX C	DATA REPORT - HOLE CR-19 CORES, 11 OCTOBER 1968	105
APPENDIX D	DATA REPORT - HOLE CR-32 CORES, 15 OCTOBER 1968	127
APPEIDIX 'E	DATA REPORT - HOLE CR-4 CORES, 4 OCTOBER 1968	139
APPENDIX F	DATA REPORT - HOLE CR-35 CORES, 25 OCTOBER 1968	159
APPENDIX G	DATA REPORT - HOLE CR-39 CORES, 21 OCTOBER 1968	171
APPEIDIX H	DATA REPORT - HOLE CR-42 CORES, 27 SEPTEMBER 1968	185
APPEIDIX I	DATA REPORT - HOLE CR-48 CORES, 24 OCTOBER 1968	217
APPENDIX J	DATA REFORT - HOLE CR-10 CORES, 23 OCTOBER 1968	229
APPENDIX K	DATA REPORT - HOLE CR-15 CORES, 29 OCTOBER 1968	265
APPENDIX L	THERMAL PROPERTY TESTS, 11 FEBRUARY 1969	285

and the second second

and de samere de la service de la s

キャイト うんてん ちょういい しんかん かんない 御天 御子 御子 御子 かいせん かいしょう かんしょう しんしょう しんしょう しょうしょう ちょう

.

hpulina k

fs. "All of a physician in the "A

a bet from a set of the

3

.

یں مرب

ž

# CONVERSION FACTORS, BRITISH TO METRIC UNITS OF MEASUREMENT

化存金

のないで、「ないない」

1.

British una configurement used in this report can be converted to metric units as follows.

Multinly		
	Ву	To Obtain
inches	2.54	centimeters
levi	<b>D.3048</b>	meters
feet per sacond	0.3048	meters per second
pound-	0.45359237	kilograms
pounds per square inch	0.070307	kilograms per square centimeter
vos per square inch	70.307	kilograms per square centimeter
pounds yer cubic foot	16.0185	kilograms per cubic meter

7

#### CHAPTER 1

#### INTRODUCTION

国家語言語を見たれたがとれたが、人間間であたなな思想が必要なないである。などのないであったが、日本ではないであったのである。などのないであるのであるのである

#### 1.1 BACKGROUND

The purpose of this study was to supplement the information being obtained for the hard rock missile-siting investigation by the U. S. Air Force Space and Missile Systems Organization (SAMSO). It was necessary to define the properties required on the specific materials for utilization in the various computer codes for groundmotion predictions and as necessary for design of structures in the medium. Results of tests on cores from the Laramie range near Warren AFB, Wyoming, are reported herein.

#### 1.2 OBJECTIVE

The objective of this investigation was to conduct laboratory tests on samples from potential missile sites to determine the integrity and the mechanical behavior of the materials as completely as possible, analyze the data thus obtained, and report the results  $\div$ o appropriate users.

#### 1.3 SCOPE

Laboratory tests were conducted as indicated on the following page on samples received from the field. Table 1.1 gives pertinent information on the various tests.

Series I tests, conducted to determine the general quality, uniformity, and integrity of the rock in the area sampled: (1) relative hardness (Schmidt number), (2) specific gravity, (3) porosity, (4) indirect tension, (5) unconfined shear, (6) unconfined compression, (7) cyclic compression, (8) dynamic moduli, (9) sonic velocity, and (10) petrographic examination.

Series II tests, conducted to define the elastic properties of selected types of rock under various states of stress: (1) triaxial compression, (2) hydrostatic compression, and (3) confined compression.

Series III tests, conducted to define the pressure-volume relation of selected types of rock at very high rates of load: (1) low pressure (air gun) and (2) high pressure (explosives).

#### 1.4 SAMPLES

Samples were received from 10 holes in the Warren Siting Area designated as Laramie and CR-4, -10, -15, -19, -32, -35, -39, -42, and -48. All samples were NX size cores  $(2-1/8-inch^{1} diameter)$ except the Laramie core which was 1-7/8 inches in diameter. Test specimens of the required dimensions as given in Table 1.1 were <sup>1</sup> A table of factors for converting British units of measurement to metric units is presented on page 7. prepared for the individual tests. Series I tests were conducted on selected specimens from all holes. Series II and III tests were conducted on specimens of the Laramie core and core from Holes CR-1/42 and CR-10.

#### 1.5 REPORT REQUIREMENTS

The immediate need for the test results required that data reports be compiled and forwarded to the users as work was completed on each hole. The data reports of the individual test results are included herein as Appendixes A through L. And the sublidies of

24973 1°T Trivers	ទាទ				
Jast	Specimon Size	Test Equipment.	Recording Eaulyzent	Hensured Properties	Complete Tropper in
Serina I:					
Relative hardness	1 diam by 2 diam	Schridt harmer	:	Relative hurdness	:
Specific gravity		Sunles	:	Specific Cruvity	Density
Poresity	<u></u>	Prossure pyenceter	Scales	Foresity, percent	ł
Indirect tension		him,000-pound test machine	:	Tenailo strength	:
Uncertinel shear		Shear test apparatus	Testing machine	Shear strength	:
Unconflued compression		440,000-pound test rachine	X+Y recordsr	Compressive strength	8
Cyclic confression		-			Young's, shear, and bulk modulf and Foisson's ratio
Dymarde sectuti	l dium by 3 diam	Sonie drivor, piekup, amplifiors	Oscilioscope display	Fundamental Trequencies	
Sonie velweity		Ultrasonic transducers		Compressional Velocity	Shear velocity
istregraphic examination	V <b>a</b> riable	Microsurpos, X-ray diffraction	:	Appeurance, texturo, nul mineralogy	:
Jortes II:					
Prinxial compression	: Ilan by 2 diam 	Triaxial chamber, 440,000- pound test machine	X=Y recorder	Triaxial strength	Failure envelope
lydrestatic compression				Deformatility	Bulk motulus
Conflued compression				<b></b>	Construined modulus
erles [1]:				-	
or pressure	l diam by l inch	Air gun	Oscilloscopes	Particle velocity, shock velocity	frassure, volume change
ld gh preasuro	1 diam by 1/2 luch	Explor",ves		-	-4
	TABLE 1.1 SUPPARY by TE That In SUPPARY by TE Peries I: Relative hardness Jperific gravity Pondrect fension Uncenfined compression Jymarks moduli Domio valueity Ponio valueity Poni	TABLE 1.1 SUPPARY OF TESTS That Specimen Size Series I: Relative hardness Jocufie gravity Poresity Salice tension Uncanfined compression Sysile compression Sysile compression Ponde valueity Prioximi compression Prioximi compressio	Trail 1.1 SUCCARY OF TEXTS    That  Specimen Size    That  Specimen Size    That  Specimen Size    That  I diam by 2 diam    Series I:  Series I:    Series I:  I diam by 3 diam    Series I::  I diam by 2 diam    Series I::  I diam by 1 lineh    Nicreacopes, X-ray    Series I::  Series I:    Series I::  I diam by 1 lineh    Series I::  I diam by 1 lineh    Series I::  I diam by 1/2	Table 1.1 SUCONNY OF TESTS  Test Equipment  Recording Equipment    Carles I:  Specteon Size  Test Equipment  Recording Equipment    Series I:  1 diam by 2 diam  Schles	Trat:    Recording: Dublecant.    Record: Recording: Dublecant.      Section    1 <t< td=""></t<>

#### CHAPTER 2

#### TEST METHODS

#### 2.1 SCHMIDT NUMBER

The Schmidt number is a measure of the relative degree of hardness as determined by the degree of rebound of a small mass propelled against a test surface. Twenty-four readings per specimen were taken as suggested by Deere and Miller.<sup>1</sup> The average of these readings is the Schmidt number or relative hardness. The hardness is often taken as an approximation of rock quality, and may be correlated with other physical tests such as strength, density, and modulus.

#### 2.2 SPECIFIC GRAVITY AND POROSITY

The specific gravity of the "as-received" samples was determined by the loss of weight method conducted according to method CRD-C 107 of the "Handbook for Concrete and Cement."<sup>2</sup> A pycnometer is utilized

<sup>1</sup> Deere, D. U. and Miller, R. P.; "Engineering Classification and Index Properties for Intact Rock"; Technical Report No. AFWL-TR-65-116, December 1966; Air Force Weapons Laboratory, Kirtland Air Force Base, N. Mex.; Unclassified. 留計は日本のためには、現代のためであるでは、19月1日には、19月1日に、19月1日に、19月1日に、19月1日には、19月1日に、19月1日日に、19月1日日に、19月1日日に、19月1日に、19月1日に、19月1日に、19月1日日に、19月1日に、19月1日に、19月1日に、19月1日日に、19月1日に、19月1日に、19月1日日に、19月1日に、19月1日日に、19月1日日に、19月1日日に、19月1日に、1

<sup>2</sup> U. S. Army Engineer Waterways Experiment Station, CE; "Handbook for Concrete and Cement"; August 1949 (with quarterly supplements); Vicksburg, Miss.; Unclassified. to determine the loss of weight of the sample upon submergence. The specific gravity is equal to the weight in air divided by the loss of weight in water.

Porosity, herein defined as the volume of void: expressed as a percentage of total volume, was determined after the samples utilized for the specific gravity test had been dried to constant weight. The amount of water forced into the test sample under 1200-psi fluid pressure in a pressure pychometer was carefully measured. Utilizing the known density of the water, the void space in the test sample was calculated. For very dense material, the sample was broken into small pieces to allow the fluid to saturate it. 

#### 2.3 TENSILE AND SHEAR STRENGTHS

The tensile strength was determined by the indirect method, commonly referred to as the tensile splitting or Brazilian method, in which a tensile stress is induced in a cylindrical test specimen by a compressive force applied on two diametrically opposite line elements of the cylindrical surface. The test was conducted according to method CRD-C 77 of the "Handbook for Concrete and Cement".<sup>2</sup>

The shear strength was determined directly by the single-plane method described in CRD-C  $90.^2$  The method consists essentially of forcing a shear plane by holding one end of a test specimen

stationary and moving the other end perpendicular to the axis of the specimen.

#### 2.4 DYNAMIC PROFERTIES

Bulk, shear, and Young's moduli, Poisson's ratio, and shear velocity were determined on selected rock samples by use of the method of vibrating unconfined samples in the fundamental modes of vibration. The resonant frequencies were utilized to compute the aforementioned elastic properties as given in CRD-C 18.<sup>2</sup>

The velocity at which a compressional wave travels through an isotropic solid is often used as a relative measure of the competency of the material. Compression wave velocities were determined on selected rock core samples by the method given in CRD-C 51.<sup>2</sup>

#### 2.5 FETROGRAPHIC EXAMINATION

A limited petrographic examination was conducted on samples selected to be representative of the material received. The examination was limited to identifying the rock, determining general condition, identifying mineralogical constituents, and noting any unusual characteristics which may have influenced the test results.

#### 2.6 STRENGTH TESTS

The uncontined, cyclic, triaxial, hydrostatic, and confined compression test specimens were prepared according to the American

14

Society for Testing and Materials and Corps of Engineers standard method of test for triaxial strength of unirained rock core specimens, CRD-C 147.<sup>2</sup> Essentially, the specimens were cut with a diamond blade saw, and the cut surfaces were ground to a tolerance of 0.001 inch across any diameter with a surface grinder prior to testing. Electrical resistance strain gages were utilized for strain measurements, two each in the axial (vertical) and horizontal (diametral) directions. Static Young's, bulk, shear, and constrained moduli were computed from strain measurements. Stress was applied with a 440,000-pound-capacity universal testing machine. The stress conditions are:

- 1. Unconfined strength,  $\sigma_1 : \sigma_2 = \sigma_3 = 0$
- 2. Triaxial strength,  $\sigma_1 : \sigma_2 = \sigma_3 \neq 0$
- 3. Hydrostatic stress,  $\sigma_1 = \sigma_2 = \sigma_3$
- 4. Confined stress,  $\sigma_1 : \sigma_2 = \sigma_3$ , variable, to maintain  $\epsilon_2 = \epsilon_3 = 0$

#### 2.7 SHOCK RESPONSE

The shock-loading characteristics of the rock at relatively low dynamic pressures were studied by observing the action of a shock wave produced by the impact of a projectile on a rock specimen. The system, given in the Addendum to Appendix A, "System for Studying the Shock Response of Rock and Other Nonferromagnetic Materials at Pressures Below 40 Kilobars," loads the sample in a one-dimensional state in approximately 1 µsec.

The Hugoniot equation of state was determined on selected samples in the pressure range of 50 to 500 kilobars by an explosive system consisting of a plane-wave lens and high explosive charge as given in the Addendum to Appendix A, "System for the Determination of the Hugoniot Equation of State of Rock and Grout."

16

いたがないないであるというないであるというないで、ないで、ないないないで、ないないないないであるというないであるというないで、

#### CHAPTER 3

#### SERIES 1 TEST RESULTS

#### 3.1 DIORITE

Core samples received from three of the holes were identified as diorite: soda diorite from Laramic and CR-19 and lime diorite from Hole CR-32. Detailed results are given in Appendixes B, C, \_ and D; a summary of the results is given below:

Property		Hole	Number	
	Laramie	CR-19 (top)	CR-19 (bottom)	CR-32 <sup>a</sup>
Data, Appendix	В	C	٠C	D
Schmidt number	50.1	54.1	56.4	54.8
Specific gravity	2.72	2.82	2.88	2.76
Porosity, percent	0.0	0.0	0.1	0.1
Tensile strength, psi	1,400	1,130	1,350	1,440
Shear strength, psi	2,420	1,060	1,560	
Compressive strength, psi	21,580	25,070	24,670	27,470
Compression wave velocity, fps	19,790	20,400	20,800	15,480
Shear wave velocity, fps	11,270	11,400	11,360	1.0,980
(Co:	ntimued)			

<sup>a</sup> Overall quality very poor due to fragmentation.

17

5

stern flation is

Property		He	ole Number	
	Laramie	CR-19 (top)	CR-19 (bottom)	CR-32
Dynamic moduli, millions of psi				
Young's Bulk Shear	11.8 8.2 4.5	12.4 9.4 4.9	13.7 14.2 5.1	9.6 3.6 <sup>0</sup> 4.5
Dynamic Poisson's ratio	0.26	0.28	0.34	0.06 <sup>b</sup>
Static moduli, millions of psi				
Young's Bulk Shear	11.8 8.6 4.6	13.7 11.6 5.3	13.8 11.7 5.5	12.0 8.8 4.7
Static Poisson's ratio	0.26	0.30	0.30	0.27

<sup>b</sup> Doubtful result.

The material from two of the three diorite holes sampled, Laramie and CR-19, appeared to be very competent, relatively uniform rock with little fracturing or jointing. The lime diorite from Hole CR-32 was badly fragmented due to the presence of numerous horizontal, vertical, and steeply dipping fracture surfaces, almost all of which were present prior to drilling. The Laramie core was the coarsest grained and, surprisingly, the most uniform. The CR-19 core was slightly more competent than the Laramie core, but quite variable. Compressive strength ranged from 20,000 to 30,000 psi although the large variation is not evident in the averages reported above. The soda diorite is apparently a very rigid rock as indicated by the high moduli and negligible hysteresis of the stress-strain curves. The lime diorite was significantly poor when compared with all other cores received from the Warren area. The indication of high quality by the basic tests reported above should not be construed as evidence of a competent material throughout. The entire length of samples received was highly fractured; locating sufficient core for test specimens was difficult. As indicated by the basic tests, the core which was not fractured was a relatively competent material.

#### 3.2 GRANITE

Samples received from five of the holes, CR-4, -35, -39, -42, and -48, were identified as medium- to coarse-grained granite. The core from the lower depth of Hole 4 was identified as tonalite. Detailed results are given in Appendixes E through I; a summary of the results is given below: 

Property			Hole N	umber CR.	•	
	4(top)	4(bot- tom)	35	39	42	48
Data, Appendix	E	E	F	G	Н	I
Schmidt number	53.5	56.6	52.7	52.2	50.0	57.3
Specific gravity	2.63	2.69	2.69	2.71	2.67	2.66

(Continued)

「ないでないでないです」

÷

۰,

Property			Hole N	umber CR	<del></del>	
	4(top)	4(bot- tom)	35	39	42	48
Porosity, percent	0.0	0.0	0.1	0.6	0.4	0.4
Tensile strength, psi	1,120	1,380	870	815	780	1,200
Shear strength, psi	~~	2,030	1,000	1 <b>,</b> 370	1,910	1,450
Compressive strength, psi	24,300	30,950	21,960	20,940	18,060	21,870
Compression wave velocity, fps	14,600	18,360	12,550	17,030	15,340	18,260
Shear wave velocity, fps	8,780	10,640	7,350	10,180	9,070	10,880
Dynamic moduli, millions of psi						
Young's Bulk Shear	5.7 2.1 2.7	10.0 5.0 4.3	4.8 3.1 1.9	8.4 3.7 3.7	7.1 3.4 3.1	9.8 5.0 4.2
Dynamic Poisson's ratio	0.05 <sup>a</sup>	0.17	0.24	0.12	0.14	0.17
Static moduli, millions of psi						
Young's Bulk Shear	10.0 6.0 4.1	10.6 7.1 4.3	7.9 4.8 3.2	7.9 6.4 3.1	10.0 7.3 4.1	9.7 6.8 3.8
ratio	0.22	0.25	0.22	0.29	0.27	0.26

a Doubtful result.

AND ALL SALES AND ALL SALES

Shiphed are areadoniated

1 . A

The granite from the five holes sampled is composed generally of quartz, plagioclase and potassium feldspars, and biotite with smaller amounts of hornblende, pyroxene, and several other minerals. The rock is quite similar from hole to hole, and possibly may all have been taken from the same igneous body. The tonalite from Hole 4 was obviously different in appearance and was apparently slightly more competent than the reddish granite. All of the rock tested appeared to be competent material, and relatively uniform in physical properties within drill holes and between holes.

The compressive strength of samples tested from Holes 35, 39, and 48 was unusually consistent for a rocklike material. The rock in Hole 42 was the most variable material reported above and also the least competent, due probably either to the small amount of montmorillonitic clay or the numerous small fractures present throughout the core. Most of the compression test specimens from all holes, but especially Hole 42, exhibited a slight plastic-elastic stress-strain relation associated with initial crack closing, followed by a steeper linear relation. The hysteresis loops were essentially closed; little residual strain was evident. The small fractures might also be the cause for apparently lower moduli determined dynamically, since the static moduli were determined under stress while the dynamic moduli were determined on unstressed specimens.

#### 3.3 GNEISS

The cores received from Holes CR-10 and CR-15 were identified as gneiss. Gneiss is the rock name for a metamorphic rock that shows alternating layers of light- and dark-colored minerals. Detailed results are given in Appendixes J and K. A summary of the results is given below:

Property		Но	ole Numbe	er CR-	
	10 (top)	10 (bottom)	15 (top)	15 (middle)	15 (bottom)
Data, Appendix	J	J	K	K	ĸ
Schmidt number	57.3	54.4	52.5	57+5	53•9
Specific gravity	2.63	2.73	3.06	2.69	2.93
Forosity, percent	0.4	0.4	0.0	0.0	0.0
Tensile strength, psi	1,360	1,030	2,260	1,140	2,220
Shear strength, psi		1,370			1,220
Compressive strength, psi	29 <b>,</b> 930	15,300	30,770	29,200	32,900
Compression wave ve- locity, fps	15,590	18,060	18,980	15,900	18,280
Shear wave velocity, Ps	9,420	10,880	12,700		12,130

(Continued)

22

.

「「ないない」というないでないないできょうないです。このない、

というないであるというよう

いたのとうないとなる人間を支払うというのないがあったのである。

Property		Нс	le Numbo	er CR-	
	10 (top)	10 (bottom)	15 (top)	15 (middle)	15 (bottom)
Dynamic moduli, millions of psi			<u>, , , , , , , , , , , , , , , , , , , </u>		
Young's Bulk Shear	6.9 2.9 3.1	10.0 5.2 4.2	15.2 7.7 6.5		13.5 6.8 5.8
Dynamic Poisson's ratio	0.11	0.18	0.17		0.17
Static moduli, millions of psi					
Young's Bulk Shear	8.8 4.9 3.7	9.3 7.3 3.7	14.7 10.3 5.8	11.8 6.8 4.8	14.4 9.1 5.8
Static Poisson's ratio	0.20	0.27	0.26	0.21	0.24

The gneissic rock from the two holes sampled is apparently competent but quite variable material. Two distinct types of material were evident in the core received from Hole 10, a light-colored gneiss at the top or upper elevation, and dark banded rock in the lower depths. The light-colored rock had an unusually high compressive strength (approximately 30,000 psi) and Schmidt number (57.3) for a moderately dense material. Conversely, the banded material, although somewhat heavier and with a significantly higher velocity, yielded a compressive strength only half that of the light-colored rock due to failure along the bands.

Three types of material were evident in the core received from Hole 15: a dark amphibolite in the upper portion, a white pegmatite in the middle, and banded amphibolite and pegmatite in the lower. The range in individual compressive strength tests was rather large, 23,000 to 40,000 psi (Appendix K); however, the averages of the three groups were approximately equal. Significantly, the test results obtained on the white pegmatite, at the middepth in Hole 15, compare closely with the results obtained on the light-colored rock from the top of Hole 10. The relatively high tensile strengths indicated for the upper and lower elevations of Hole 15 were determined perpendicular to the banding; actually the shear strength (approximately 1,200 psi), determined with the banding, is more indicative of the lower failure stress level of the material. Stressstrain curves for rock from both holes show negligible hysteresis. 

### CHAPTER 4 SERIES II TEST RESULTS

1.1 LARAMIE CORE

The Laramic core was selected to represent the diorites for the Series II tests. Hydrostatic compression tests were conducted on three specimens, one each to pressures of 8,000, 20,000, and 36,000 psi. Triaxial tests were then conducted utilizing the same specimens at confining pressures equal to the hydrostatic pressures previously applied. Two confined compression tests were conducted on separate specimens, the confining pressure being applied to prevent lateral straining as axial load was applied by the piston in the triaxial chamber. Results are given in Appendix B. Young's, bulk, and constrained moduli may be compared for the unconfined (Series I) and confined (Series II) tests as follows:

「「大学などないなどのなどのない」

10.0

		Moduli, mill	ions of psi	
	Series	I	Series	II
-	Computed From	Result	Computed From	Result
Young's	Unconfined test	11.8	Triaxial test	12.2
Bulk	Poisson's ratio	· 8.6	Hydrostatic test	9.1
Constrained	Theory of elasticity	16.9	Confined test	16.3

Good correlation is, therefore, indicated between the unconfined and confined tests.

The Mohr envelope for the triaxial tests is apparently a straight line up to the 20,000-psi confining pressure level and then assumes a curvilinear relation with increased confining pressure. Pronounced shear planes developed in the specimens tested at 8,000- and 20,000-psi confining pressures; however, initial failure apparently occurred along a crystal face in the 36,000-psi test. Thus, the curvature of the envelope may be due to premature yielding along the crystal interface. The compression wave velocity was recorded during test to failure of two triaxial test specimens. The results indicated that the velocity increased initially under load, probably due to closure of small cracks, and then remained rather constant up to failure.

4.2 CR-42 CORE

The CR-42 core was selected to represent the granites for the Series II tests. Hydrostatic compression tests were conducted on three specimens, one each to pressures of 9,000, 18,000, and 36,000 psi. Triaxial tests were then conducted utilizing the same specimens at confining pressures equal to the hydrostatic pressures previously applied. Two confined compression tests were conducted on separate specimens, the confining pressure being applied to prevent lateral straining as axial load was applied by the piston in the triaxial chamber. Results are given in Appendix H. Young's, bulk, and

いたいない、なたないとい

A had been

constrained moduli may be compared for the unconfined (Series I) and confined (Series II) tests as follows:

. 7,0 AZ 35,0 V

**NATIONAL PROPERTY** 

	Moduli, millions of psi				
	Series I		Series II		
	Computed From	Result	Ccmputed From	Result	
Young's	Unconfined test	10.0	Triaxial test	12.0	
Bulk	Poisson's ratio	7.3	Hydrostatic test	5.8	
Constrained	Theory of elasticity	14.4	Confined test	15.0	

Significantly, the Young's modulus is lower for the unconfined test, and the bulk modulus higher, compared with the confined tests. A possible explanation is the closure of the small fractures under load. If the fractures close predominantly under initial load, as is usually the case, the unconfined Young's modulus would be lower, as it is, than the triaxial Young's modulus which is determined after the confining pressure has been applied. Also, the hydrostatic bulk modulus could be expected to be lower than the static bulk modulus which is computed at approximately one-half the ultimate strength in the unconfined test.

Due to the variability of the CR-42 core, two Mohr envelopes were constructed utilizing the results of the unconfined and triaxial compression tests. The more competent material had an initial angle of shearing resistance of approximately 52 degrees, the less competent rock, 45 degrees. Also, the envelope of the less competent material appeared to be assuming a curvilinear relation at 36,000-psi confining pressure, the maximum available for these tests. The compression wave velocity was recorded during test to failure of two triaxial test specimens. As in the tests on the diorite core, the velocity increased slightly under load, probably due to closure of small cracks. ないため、たちなない、いちろうです

ş

这次

見るを

は言う、水学語が

#### 4.3 CR-10 CORE

The CR-10 core was selected to represent the gneiss for the Series II tests. Hydrostatic compression tests were conducted on three specimens, one each to pressures of 9,000, 18,000, and 36,000 psi. Triaxial tests were then conducted utilizing the same specimens at confining pressures equal to the hydrostatic pressures previously applied. Two confined compression tests were conducted on separate specimens, the confining pressure being applied to prevent lateral straining as axial load was applied by the piston in the triaxial chamber. Results are given in Appendix J. Young's, bulk, and constrained moduli may be compared for the unconfined (Series I) and confined (Series II) tests as follows:

	Moduli, millions of psi			
	Series I		Series II	
	Computed From	Result	Computed From	Result
Young's	Unconfined test	9.2	Triaxial test	12.0
Bulk	Foisson's ratio	6.5	Hydrostatic test	7.0
Contrained	Theory of elasticity	13.9	Confined test	15.0

Reasonably good correlation is indicated between the unconfined and confined tests.

The Mohr envelope for the triaxial tests is initially a straight line at an angle of shearing resistance of approximately 45 degrees. The envelope develops a pronounced curvilinear relation with increased confining pressure and appears to be approaching linearity at 36,000-psi confining pressure. However, the apparent approaching linearity should not be considered a Von Mises yield, but probably is the result of the bedding and stratification. Pronounced shear planes developed in the specimens along the bedding planes. The compression wave velocity recorded during test to failure of two triaxial test specimens increased slightly under load as for the diorite and (ranite specimens.

いたのではないであった。「「ないない」では、「ないない」で、「ないない」では、「ないない」では、「ないない」で、「ないない」で、「ないない」で、「ないない」で、「ないない」で、「ないない」で、「ないない

# 4.4 THERMAL PROPERTY TESTS

Thermal property tests on selected cores were added to the test program as testing was nearing completion. Thermal diffusivity, specific heat, and thermal conductivity tests were conducted on samples from four holes, CR-4, -15, -19, and -35. Test methods and results are given in Appendix L.

の時期代は時代を見ていた。

and a subsection of the state o

## CHAPTER 5 SERIES III TEST RESULTS

and the state of the state of

#### 9.1 TESTS

Equation of state tests were performed on the three rock types from the Warren Siting Area. A minimum of three low pressure tests (pressures less than 40 kilobars) and three high pressure tests (pressures to 400 kilobars) were conducted on each rock. The techniques and test equipment used in these tests are explained in the Addendum to the detailed results, Appendix A. A surmary of the results is given below:

Core	Shock Velocity	Particle Velocity	Pressure	Specific Volume $\left(\frac{V}{V_o}\right)$
	mm/µsec	mm/µsec	kilobars	
Low Pressur	e Tests:			
Laramie	4.45	0.037	4.7	0.992
	4.99	0.139	18.7	0.972
	7.00	0.166	31.7	0.976
	6.10	0.263	43.4	0.957
CR-42	4.80	0.072	9.5	0.985
	5.00	0.090	11.9	0.982
	5.00	0.158	21.1	0.968
CR-10	4.15	0.081	9.2	0.980
	4.50	0.154	18.6	0.966
	3.22	0.268	28.9	0.930
	5.04	. 0.138	18.7	0.973

(Continued)

Specific Particle Pressure Cor Chock Volume Velocity Velocity  $\left(\frac{V}{V_{o}}\right)$ mm/µsec mm/µsec kilobars itigh Pressure Tests: 4.42 0.851 Laramie 0.71 95 0.704 5.19 1.51 215 5.80 2.17 340 **0.61**0 CR-42 0.842 4.17 0.72 91 1.48 0.724 5.51 216 5.69 2.18 0.600 328 CE-10 4.03 0.74 89 0.832 5.34 1.50 0.708 213 2.18 0.603 5.79 333

and here the second of the second of the second of the second

÷.

1

- 24、、、したいので、 44、 44、 44、

#### 5.2 DISCUSSION OF RESULTS

All three cores exhibited considerable data scatter due to the large grain size and material nonhomogeneity with respect to this type of test. The Laramie and CR-42 cores had Hugoniot elastic limits of 50 kilobars or more. The CR-10 core had an elastic limit of approximately 20 kilobars. The Laramie, CR-42, and CR-10 cores had elastic wave velocities of approximately 6.06, 6.03, and 5.68 mm/µsec, respectively. The second wave velocity, of course, is dependent upon the final pressure level attained in the material. All three high pressure tests for each material reached a final state which was still in the upstable or multiple wave region with the
Acception of possilly the highest pressure test for CR-10. This particular data point appears to have just exceeded the multiple wave region.

Comparison of test results from the three test series is difficult due to the differences in test mothods and properties determined. Moduli of deformation may be compared below as a matter of interest if one is mindful of the differences mentioned above.

	Moduli, millions of psi		
	Series I	Series II	Series III
State of stress	Unconfined	Confined	Confined
Rate of load	Static	Static	Shock
Modulus type	Young's	Constrained	One-Dimensional
Moduli for:		-	
Laramie	ш.8	16.3	13.3
CR-42	10.0	15.0	9.3
CR-10	9.2	15.0	8.7

તા હિંદી દિવ્યત્વેય પ્રતિકોર્ટ વેશો સાથે છે. આ પ્રતિકેટ સાથે જેવી છે. આ પ્રતિકેટ છે છ

# CHAPTER 6

### CONCLUSIONS AND RECOMMENDATIONS

# 6.1 CONCLUSIONS

The core received from the Warren Siting Area represented three hypes of rock: diorite, granite, and gneiss. Generally all samples received indicated relatively uniform, unweathered, hard rock with the exception of one hole, CR-32, which contained highly fractured lime diorite. Maximum crystal size of the other two diorite holes appreached 2 inches, and that for the five granite holes, 1/2 inch. Stress-strain curves generally exhibited little hysteresis. Typically, basic properties for the rock from the nine competent holes would be approximately: (1) Unconfined compressive strength, 20,000 psi, (?) Specific gravity, 2.70, (3) Porosity, <1.0 percent, (4) Comprescion wave velocity, 15,000-17,000 fps, (5) Young's modulus,  $10.0 \times 10^6$ psi.

Multiaxial tests indicated that bulk moduli would approximate  $8.0 \times 10^6$  psi and constrained moduli,  $15 \times 10^6$  psi. The maximum confining pressure available, 36,000 psi, did not allow definition of the Von Misses yield condition.

er er som som state som er störer som er störe bygger av er er som som er som er som er som er som er som er s Ar state som att som er störer av att som er störe bygger av er av er som er som er som er som er som er som er

The low pressure shock tests indicated that the diorite and granite had Hugoniot elastic limits of 50 kilobars or more, and the gneiss an clartic limit of approximately 20 kilobars. The high pressure

tests for each material reached a final state which was still in the unstable or multiple wave region at the limit of the test equipment.

# 6.2 RECOMMENDATIONS

In order to better define the physical and mechanical behavior of the rock, it is recommended that the following additional tests be conducted on representative samples of the three materials: (1) Tests on specimens with joint planes under confining pressure to determine the yield envelope of the jointed rock. (2) Triaxial tests to approximately 150,000-psi confining pressure to determine the plastic yield limit of the intact rock. (3) Equation of state tests at pressures to approximately 600 kilobars to define the stable region and release adiabatic tests in the low pressure region to establish the shock unloading characteristics of the rock.

35-36

# APPENDIX A

2

SERIES III TESTS

13 FEBRUARY 1959

### Introduction

1. Series III equation of state tests were conducted on three cores from the Warren Siting Area. The low-pressure equation of state into were obtained using an induction wire technique in conjunction with a compressed-air gun facility. The high-pressure equation of state data were obtained using a pin technique in conjunction with a high explosive system. These techniques are explained in detail in the indication. Plate 1 is a photograph of a typical specimen for both systems.

#### Material Description

2. a. Core No. 1 - Laranie.

(1) Rock type: soda diorite.

- (2) Piece number and depth: 10 and 11; 59 to /0 ft.
- (3) Density: 2.71 g/cc.

(4) Remarks: Grains were large (up to 1/2 in.) and nonuniform in size.

b. Core No. 2 - CR-42.

(1) Rock type: granite.

(2) Piece number and depth: 10 and 11; 85 to 87 ft.

(3) Density: 2.54-2.57 g/cc.

(4) Remarks: Large quartz crystals throughout specimen.

c. Core No. 3 - CR-19.

(1) Rock type: gneiss.

(2) Piece number and depth: 3 and 4; 55 and 59 ft.

(3) Density: 2.57-2.70 g/cc.

(4) Remarks: Large quartz crystals throughout specimen.

## Low-Pressure Tests

### 3. Laramie (soda diorite).

a. Five tests were conducted on the Laramie core. SAMSO No. 2 and No. 5 were tested at pressures of approximately 4.7 and 4.2 kilobars, respectively. The rise times of the particle velocitytime records ranged from 0.9 to 1.5 microsec. SAMSO No. 3 was tested at a pressure of approximately 18.8 kilobars with particle velocitytime rise times of 0.51 to 0.58 microsec. SAMSO No. 4 was tested at a pressure of approximately 31.7 kilobars and had rise times of 0.41 to 0.9 microsec. SAMSO No. 15 was tested at a pressure of approximately 43.4 kilobars and had a rise time of approximately 1.2 microsec.

b. Figures 1 and 2 show the pressure-particle velocity and pressure-strain relationship obtained from the five tests. Test Nos. 3, 4, and 15 yielded separate and distinct curves. The data from tests 2 and 5 were essentially the same and are, therefore, plotted as one set of data. Since the grains were large (up to 1/2 in.) and nonuniform in size, a great amount of material scatter was expected which would yield a considerable scatter in the data. However, the scatter should not be large enough to yield curves with as large a separation as indicated by tests 3 and 4. Material scatter could possibly account for the difference between tests 4 and 15. It is believed that possibly interface slippage is occurring in the lower pressure tests due to the large grain size causing lower shock velocities and, consequently, a lower pressure-particle velocity relationship. The shock velocity was less than the sonic velocity for tests 2, 3, and 5. Most of the records from these tests indicated some degree of instability. Apparently, tests 4 and 5 were conducted at pressures above this unstable region; therefore, the shock velocity was greater than the sonic velocity and increased with pressure.

c. The peak pressure point from tests 4 and 15 are shown on figures 7 and 8 along with the high-pressure test points. From an extrapolation of these points, it appears that the Hugoniot elastic limit is around 50 kilobars, although this was not determined.

#### 4. CR-42 (granite).

a. Three low-pressure tests were conducted on cores from CR-42. Peak pressures of 9.5, 11.9, and 21.1 kilobars were obtained in SAMSO Nos. 5, 7, and 8, respectively. The rise times of the particle velocity-time records ranged from 0.6 to 0.8 microsec. The large quartz crystals caused considerable noise on the oscilloscope records (piezoelectric effect) which made the data reduction rather difficult. However, the reduced data from the three tests plotted essentially as one line on

39

करतीय के स्वतित के दिया

AND SCALES AND STREET

the pressure-particle velocity (figure 3) and pressure-strain (figure 4) plots. The data indicate that the shock wave in the material is stable to 21 kilobars. Higher pressures were reached with the air gun; however, the noisy oscilloscope records made data reduction above 21 kilobars virtually impossible. It is believed that this problem can be overcome on future tests of materials containing large quartz crystals.

b. The peak pressure point from test No. 8 is shown on figures 9 and 10 along with the high-pressure test points. Extrapolation of the high-pressure points indicates that the Hugoniot elastic limit is around  $50^{+}$  ilobars.

المراجب المراجب

#### 5. CR-10 (gneiss).

a. Three low-pressure tests were conducted on cores from CR-10. Peak pressures of approximately 9.1, 29.0, and 18.6 kilobars were obtained in SAMSO Nos. 11, 12, and 14, respectively. The rise times of the particle velocity-time records ranged from 0.2 to 1.2 microsec. These specimens also had large quartz crystals throughout; however, the noise was not as significant as for the CR-42 cores. Figures 5 and 6 are plots of pressure-particle velocity and pressure-strain for this material. As can be noted from these plots, there is considerable scatter in the data. It is not quite as severe as for the Laramie core, and most of it can probably be due to material scatter or nonhomogeneity of the material.

b. Test Nos. 12 and 14 showed a definite second wave forming at approximately 18-19 kilobars indicating some sort of yielding. There is some question as to whether or not this is t: Hugoniot elastic limit since this second wave is evidenced only on the second induction wire of each test. Since the first induction wire did not exhibit two waves, there is possibly more error associated with the second wave peak amplitude data point for test 14 shown on figures 5 and 5 than for the other points shown. Plate 2 is a photograph of the second induction wire oscilloscope record of test 12 showing the two-wave structure.

c. A test was also conducted on this material in which a quartz crystal was placed on the back of a 7.44-mm-thick specimen and impacted with a projectile having a velocity of approximately 1100 fps. The output of the quartz also indicated a two-wave structure with the first wave having an amplitude of approximately 18 kilobars.

d. The peak pressure points of first and second waves from test No. 12 are plotted on figures 11 and 12 along with the high-pressure test points. Extrapolation of the high-pressure points seems to confirm a low Hugoniot elastic limit although the data point around 90 kilobars has the largest uncertainty associated with it and, therefore, would influence the point of intersection of the two curves.

### High-Pressure Tests

理論理解がないないないない かんちょう かいしょう しゅうしょう しょうしん しょうしょう しょうしょう

5. Three data points were determined on cores from the Warren Siting Area at three pressures as shown in table 1. Since eristing granite data showed a precursor shock of around 50 kilobars, some alteration to the standard pin technique was necessary to prevent a precursor from shorting the time of arrival pins prior to the arrival of the main shock wave. This was accomplished by providing a 'mown gap or standoff distance for the shock velocity pins to allow for the motion due to the precursor. Therefore, the shorting times of the pins correspond to the velocity of the main shock. This technique requires an assumption of the precursor shock level since no provision is made for measuring the elastic free surface velocity.

7. A simple computer program was used to compare the influence of the assumed precursor level on reducing the experimental data to the final data points. The precursor levels used ranged from 50 to S0 kilobars as shown in table 2 for soda diorite. These computations did not utilize a least squares fit of the experimental points and, therefore, do not extrapolate exactly to the final data in table 1. This assumption has a negligible effect on the two higher pressure tests, but is more pronounced on the data points at approximately 100 kilobars since this level is approaching the possible range of the precursor pressure.

8. The elastic precursor shock velocities as determined on the two higher pressure tests were used in the data reduction on all three tests. Some difference in the elastic precursor shock velocities is noted between these and the lower pressure air gun experiments; however, this is reasonable considering the large difference in peak pressure attained in the respective tests.

9. These data points are shown in graphical form in figures 7 through 12 along with an approximate fit throughout the pressure range.

## Discussion

de

10. Equation of state data on polycrystalline rocks typically show significant scatter; for example, the work by Stanford Research Institute.\* The precursor level ranged from 29 to 58 kilobars for anorthosite. Additional data points would thus be desirable for the rocks tested and would increase the confidence bevel of a curve fitted to the data for use

\* Ahrens, T. J., Rosenberg, J. T., and Ruderman, M. H., "Dynamic Properties of Rocks," DASA 1858, 30 September 1955, Stanford Research Institute.

in free-field codes. The assumption of a precursor level for these rocks is not considered to be significant except at final pressures of around 100 kilobars; however, an extension of the pin technique is being prooftested for use in two-wave regions which should eliminate the necessity of this assumption providing simultaneous measurements on both shock waves.

11. Since in this region the second wave travels at subsonic velocity depending on pressure, provision must be made for measuring this velocity. In addition, the locus of the Hugoniot elastic limit must be mown in order to calculate the final Hugoniot point.

12. The magnitude of four variables, namely, elastic precursor and second-wave shock velocity and precursor and second-wave particle velocity, must be determined experimentally. The method to be used incorporates the principles of the inclined mirror-high-speed photography method modified to the use of self-shorting pins and presently used electronics. A CONTRACTOR OF A CONTRACT

こととろう かっていいとうないというで、うちょうとうべいいが、ちょうちょう

------

13. The necessary data will be obtained as follows. One set of pins will be used to determine precursor velocity based on transit time through the sample. When the precursor overtakes the sample free surface, this surface is accelerated to velocity  $u_{f.S.1}$ . This free surface motion will be measured by a portion of a group of bins placed at small incremental distances from the surface. As the second shock eventually overtakes the free surface traveling at  $u_{f.S.1}$ , it accelerates the free surface to velocity  $u_{f.S.2}$  of which this free surface motion will be measured by the remainder of the free surface pins. On an x-t plot the free surface velocities will intersect at the point that represents the arrival of the second wave at the free surface. This x, t point yields the shock velocity of the second wave. The impedance mismatch method is used to calculate the necessary Hugoniot information remaining based on these experimental data.

14. A high explosive flying plate technique is being prooftested and should enable the Waterways Experiment Station to extend the capability of this system by several hundred kilobars.

15. The compressed-air gun system and techniques are continually being modified to enhance the research capability of the system. The projectiles are being modified to aid in increasing the maximum velocity capability and, therefore, increasing maximum pressure capability. Projectile velocities are being measured more accurately. A technique for measuring planarity of impact is being investigated. An investigation

42

Print Contraction of the second

is being conducted to determine the feasibility of sputtering or vacuum deposition of a thin film to replace the small induction wires. Also, the technique of using quartz gages to measure or monitor the pressure-time profile in rock specimens is being investigated. 「「「「ない」を、「ない」ないないで、「ないない」で

そうしょうかいたいです。 とうちょうがい ちょうちょう ない ちょうちょう ちょうちょう ちょうちょう ちょうちょう しょうしょう しょうしょう

No. of additional strength

SAMPA CHAIN

# Summary

16. Equation of state tests were performed on three cores from the Warren Siting Area. A minimum of three low-pressure tests (pressures less than 40 kilobars) and three high-pressure tests (pressures to 400 kilobars) were conducted on each core. The techniques and test equipment used in these tests are explained in the addendum hereto.

17. All three cores were susceptible to considerable data scatter due to the large grain and material nonhomogeneity. We Laramie and CR-42 core had Hugoniot elastic limits of 50 kiloba. or more. The CR-10 core had an elastic limit of approximately 20 kilobars. The Laramie, CR-42, and CR-10 cores had elastic wave velocities of approximately 5.05, 5.03, and 5.53, respectively. The second wave velocity, of course, is dependent upon the final pressure level attained in the material.

18. All three high-pressure tests for each material reached a final state which was still in the unstable or multiple wave region with the exception of possibly the highest pressure test for CR-10. This particular data point appears to have just exceeded the multiple wave region.

教室経済が利用があた。

TABLE I

Specimen	Assumed Hug	oniot Elasti	c Limit			S lunig	tato	
Description and Density (g/cc)	Pressure (kilobars)	Particle Velocity (mm/usec)	> <sup>~</sup> />°	Flastic Velocity (mm/usec)	Shock Velocity (mm/usec)	Particle Velocity (mu/uscc)	Fressure (kilobars)	>  >°
Soda Dioríte 2.71	20 20 20	0,304 0,304 0,304	0.950 0.950 0.950	5.05 5.05 5.05	4.42 5.19 5.80	0.711 1.51 2.17	95.1 215 340	0.851 0.704 0.510
CR-42 2.54	50 50	0.314 0.314 0.314	0,9448 0,9448 0,9448	ь.03 5.03 5.03	4.17 5.51 5.59	0.722 1.48 2.19	91.2 216 329	9.842 0.724 0.400
CR-10 2.57	50 0 50 0	0.330 0.330 0.330	0.942 0.942 0.942	າ ເ ເ ເ ເ ເ ເ ເ ເ ເ เ เ เ เ เ เ เ เ เ เ	4.03 5.34 5.79	0.735 1.50 2.18	ξ9,4 213 333	0.832 0.708 0.503

「「「「「」」」、「」、「」」、「」」、「」」、「」、「」、「」、「」、「」、」、「」、」、

المعالية المعامية المناعية المعافيا

a Barter a state & a war a strategy and

а 4 м

Mirandest subscriptionally contenes on union or a

2

~ こうれたれいろ

(California)

1

こうちょう とうそうないないないないないない たちちょう ちょうちょう

.

~ \*\*\*

-

\*\*\*\*

Ϊ,

r	٩B	LE	2
•	-w		-

-

: : : A.

<u>م</u> الد

San Bachen Schultzbergeren

- 10 P

No.

١.

Stecimen			Final State	
Description and Density (g/cc)	HEL Pressure (kilobars)	Shock Velocity (mm/usec)	Particle Velocity (mm/usec)	Pressure (kilobars)
Soda Diorite	50	5.55	0.67	102
2.71	60	5.46	0.58	102
	70	5.30	0.68	101 -
	80	4.96	0.69	99.5
Soda Diorite	50	5.10	1.51	213
2.71	60	5.08	1.52	213
	70	5.05	1.52	212
	80	5.04	1.53	212
Soda Diorite	50	5.79	2.17	339
2.71	50	5.78	2,17	339
	70	5.78	2.18	338
	80	5.78	2.18	337

45







÷ : \*: 1 48 1 :**|**:::: 40 32 kilobars Shock Pressure, 24 -16 SANSO No O BDC No Ð AXSO 8 NO SAMSO 0 3.0 4.0 1.0 2.0 0 Percent Strain FRESSURE VS STRAIN SAMSO LARAMIE FIGURE 2  $h\gamma$ 

- 46-5

. 5

č

And the set of the second

10.41 +

E.

「「「「」」」をいていていています。



<u></u>50



And a second sec

، معندي موتي الم

51

FIGURE 4

Ż

-11-50

7





の言語でで、語言語をついて

**这些主要的这些事件。在这些实际的资源的资源的资源** 

المكميمية سالا كالمعترية المعهدية متراجع المالكة المراجع المراجع المراجع المراجع المعامين والمالية المالية المالية المنافع الم

A SALAR AND A SA

i



.

Station 1





. .

HALL DE DE LA COURSE OF

£3

44

7

÷

56

----

あいとう あいがい うちょうちんたい

そうろ とうか まい



ş



ş

ostakalaisertvaltevelintaan

799 Î

5

FIGURE 11

58

いたが、していた。

こともとうちょう

ż



£

Name and Associated and Associated Street, Stre

秋戸村 におかんこう たちょう

マインデー あなかるななのでしたがっていたかないないない

72

ADDENDUM: DESCRIPTIONS OF

12

国家のないないないので、「「「「「「」」

SYSTEM FOR STUDYING THE SHOCK RESPONSE OF ROCK AND

OTHER NONFERROMAGNETIC MATERIALS AT PRESSURES BELOW 40 KILOBARS

AND

SYSTEM FOR THE DETERMINATION OF THE HUGONIOT

EQUATION OF STATE OF ROCK AND GROUT

# System for Studying the Shock Response of Rock and Other Nonferromagnetic Materials at Pressures Below 40 Kilobars

1. The Waterways Experiment Station (WES) has developed a system for continuous measurements of both the velocity of propagation of a shock wave and particle velocities in rock and other nonferromagnetic materials from the bassage of a shock wave produced by a flat-plate impact. A stress-strain relationship is deduced from the wave and particle motion data. The system has an upper limit of approximately 40 kilobars.

2. The experimental method is primarily based on a technique used by Frasier and Karpov for directly measuring the particle velocity in a material. In this technique a fine wire is embedded in the material and placed in a magnetic field. Any subsequent movement of a portion of the wire which cuts the magnetic-flux lines produces an electromotive force (e) proportional to the instantaneous velocity as shown in the following equation:

 $e = \beta lv$ 

where

g = the magnetic field strength,

1 = the length of wire cutting the flux lines,

v = the velocity of the wire (particle velocity).

3. Several wires are placed in a test specimen and the voltages monitored on oscilloscopes and recorded on photographs. The velocity

of propagation can be determined from the initial rises of the voltage signals from the induction wires.

4. The specimen is mounted at the end of the compressed-air gun barrel in a magnetic field and the barrel evacuated to approximately 15 microns. The stress waves will be produced by impacting the specimens with an aluminum projectile. Impact velocities can be obtained up to 1200 ft/sec.

5. The final state behind the stress wave is determined by the application of the conservation equations. Conservation of mass and momentum across the shock front requires that:

 $\rho_0 U_s = \rho_1 (U_s - U_{p1})$  (Conservation of mass)  $P_0 + \rho_0 U_s^2 = P_1 + \rho_1 (U_s - U_{p1})^2$  (Conservation of momentum)

where

 $U_s = shock velocity,$ 

U<sub>p1</sub> = particle velocity behind the shock wave,

 $P_0$  = initial pressure,

 $p_0$  = initial density

the pressure behind the shock wave

and the corresponding strain

 $P_{1} = \rho_{0} U_{s} U_{p1} + P_{0}$  $e_{1} + 1 - \rho_{0}/\rho_{1} = U_{p1}/U_{s}$ 

These equations are based on the assumption that an equilibrium state of stress is reached behind the shock wave. In this simple form, they are valid only in the region of uniaxial strain. These equations correspond to the Hugoniot or the locus of shocked-end states reached.

25 January 1968

# System for the Determination of the Sumoniot Equation of State of Soch and Grout

The Materways Emperiment Station (MES) has the facility and capability to perform Eugoniot equation-of-state studies for rock and rock-matching grout over the pressure range of 50 to 500 kilobars. A number of shockindicating pins are embedded in the specimen to measure the shock-wave velocity and another group is arranged over the free surface of a driver plate of known equation of state to measure the free-surface velocity. When these pins are struck by a shock, fast-rising pulses are produced which are displayed on high-speed oscilloscopes. The shock is produced in the material using an explosive system consisting of a plane-wave lens and a high-emplosive charge. The shock and free-surface velocities are derived from the loscilloscope traces. Using the velocity data, the pressure and specific volume can be computed by means of the Nankine-Engoniot equations.

In the test system, the pins which serve as the shock-arrival indicators comprise an outer coaxial conductor and an inner conductor, and have a cap on one end and a shielded cable on the other. The shock wave closes the pin by compressing the cap against the inner conductor, producing a short circuit which discharges a resistor-capacitor (RC) combination in the pulseforming network. Each RC combination is given one of two polarities and pulse heights, and any one of four decay times to allow identification of a particular pin. The outputs from RC networks are recorded on high-speed oscilloscopes.

If the ambient density, shock velocity, and particle velocity are known, the pressure and specific volume of the shocked specimen can be determined from the following equations:

$$21 = \ell_0 U_p U_s$$
  
 $V_1/V_0 = 1 - U_s/U_p$ 

where

 $U_s$  = the velocity of the shock wave  $U_p$  = the particle velocity  $C_o$  = the density of the ambient material  $V_o$  =  $1/c_o$  = the specific volume of the ambient material  $V_1$  =  $1/c_1$  = the specific volume of the material behind the shock front The shock velocity is determined directly by embedding pins at known distances in the specimen; these distances, along with the arrival times, can be used to compute the velocity.

The particle velocity is indirectly inferred from the free-surface velocity of the driver plate. This approximation is derived on the basis of the interaction of the shock wave with the rarefaction wave which is formed at the free surface and which propagates back into the shocked specimen. This interaction causes the free surface to move with a velocity which is the sum of the particle velocity of the shock and the particle velocity of the rarefaction wave. It has been shown that the two particle velocities are very nearly equal; hence, the particle velocity of the shock can be approximated by taking one-half the value of the measured velocity of the free surface ( $U_{fs}$ );

 $v_p = 1/2 v_{fs}$ 

The free-surface velocity is measured on a surface located midway between the first and last block-velocity pins since the shock velocity will be an is rearage value due to attenuation of the shock in passing through the shocking passing through the shocking whereas the free-surface velocity will not be appreciably attenuated by the mir.

As with other high-explosive methods for determining the Hugoniot equation of state, only one point on the pressure-specific volume curve is obtained for each test. Nowever, it should be noted that with the WES system data can be obtained from three materials in one test. 目の語言語をないな



# WARREN SITING AREA

「またり」、いたでいいないないないたちというと

12.10

#### Core No. 1 (Laramie)

1. Twenty pieces of core were received from the Wyoming site, designated "Laramie" core. Numbers were assigned as indicated.

	Specimen	Approximate
Sample	Designation	Depth, ft
в	1	50
В	2	51
В	3	52
В	4	53
В	5	54
В	6	65
В	7	55
В	8	67
В	9	68
В	10	69
В	11	70
В	12	71
В	13	72
В	14	73 ·
B	15	74
A	16	17
A	17	18
C	18	151
C	19	152
С	20	153

2. The hole from which the core was taken was located in Albany County, Wyoming, longitude 105° 26.5', latitude 41° 31.5', township 19N, range 72W, section 23. All core was drilled vertically. Specimens were cut as required for the various tests; each segment of the specimen was given a letter designation signifying the section cut; for example, specimen 17a was the first test piece cut from specimen 17.

Jarren Siting Area: Core No. 1 (Laramie); Sample A; Series I

#### Results

1. Only two tests were conducted on sample A, one compressive strength test and a petrographic examination.

#### Compressive strength

2. The stress-strain curve for the compressive strength test of specimen 17a is given in plate 1. A strength of 20,100 psi was indicated.

#### Petrographic examination

3. Fifteen feet of NY core from three depths from hole No. 1, Project S-11, 100, Albany County, Wyoming, was received on 19 March 1968. The core is identified below:

CD Serial No.	Length, ft	No. of Fieces	Depth, ft
WY0-1 DC-1(A)	2	2	17.0 - 18.9
WYO-1 DC-1(B)	14.5	15	60.5 - 75.0
WY0-1 DC-1(C)	2.5	3	150.5 - 153.0

4. All of the sample appeared to be homogeneous. The petrographic sample was taken from the 18.2-ft depth and was 2.7 in. long.

5. a. The 2-3/4-in. core was sawed axially. One of these sawed surfaces was polished and photographed.

b. A thin section, made from the other half of the piece, was examined with a polarizing microscope.

c. A composite sample of the 2-3/4-in. length was ground to pass a No. 325 sieve. A tightly packed portion of this powder was examined by X-ray diffractometry using nickel-filtered copper radiation.

d. The polished surface and fracture surfaces were examined with a stereomicroscope.

e. Some of the powdered rock was examined as an immersion mount with a polarizing microscope to determine the refractive index of the plagioclase feldspar.

.5. The material examined is a medium dark gray (N 4)<sup>1</sup> coarsegrained igneous rock (photograph 1) composed largely of black and green

The Rock Color Chart Committee, Rock Color Chart, National Research Council, Washington, D. C., 1948. Warren Siting Area: Core No. 1 (Laramie); Sample A; Series I

minerals. It is estimated that 80 percent or more of the rock is plagioclase feldspar; there are small amounts of chlorite and of other greenish mica and even smaller amounts of calcite, quartz, and opaque minerals, probably pyrite, leucoxene, and hematite. Optical determinations of refractive index and of extinction angles indicated that the composition of the plagioclase is about Ab<sub>56</sub> An<sub>44</sub>, and it is therefore andesine.

7. Examination of the thin section shows that the rock suffered some deformation and fine fracturing. These fractures are now filled with a variety of materials, mostly micaceous. There is no pyroxene nor any definite evidence that pyroxene was ever present. There are scattered small patches of fine-grained mica, chlorite, carbonate, and opaque minerals in the rock. Much of the feldspar contains small oriented rodlike inclusions, possibly rutile.

8. This rock would be classified as a soda diorite by the classification system of Shand<sup>2</sup> rather than an anorthosite because the feldspar is not quite calcic enough to classify the rock as anorthosite by Shand's definition. He notes that soda diorite in his classification includes the more sodic anorthosites.

9. The core log identifies the rock as noritic anorthosite and indicates that fuchsite, a green chrome mica, is present. Portions of the log for material not sent to this laboratory indicate the presence of pyroxene crystals up to 2 in. in size. The term noritic indicates pyroxene; there was no detectable pyroxene in the sample examined. We did not attempt to confirm the presence of fuchsite, but much of the green color in the rock is accounted for by chlorite.

10. The petrographic data in this report refer only to the 2-3/4-in. length of core which was examined. A quick visual inspection of the 19 ft of core received indicated that it was homogeneous. However, there is no assurance that the material examined is typical of all the core, especially if 2-in. pyroxene crystals are actually present in some of the core.

#### Conclusions

11. Sample A, apparently representative of the whole core, yielded a slightly lower compressive strength on the one specimen tested, but the difference is not significant. The rock was identified as soda diorite.

<sup>2</sup>S. J. Shand, <u>Eruptive Rocks</u>, 3d edition, John Wiley & Sons, New York, N. Y., 1947.


Warren Siting Area: Core No. 1 (Laramie); Sample B; Series I

### Results

### Schnidt number, specific gravity, porosity

12. Three samples were selected for the basic identification tests, relative hardness, specific gravity, and porosity. Results are given below:

REPRESENTATION OF A CARACTERIA CONTRACTOR OF A CARACTERIZATION OF A CARACTERIZATION OF A CARACTERIA CARACTERIZA

	Schmidt			
	Rebound	Standard	Specific	
Core	Number	Deviation	Gravity	% Porosity
8a	48.9	2,45	2.715	0.0
8b	50.3	2.70	2.715	0.0
9	51.1	2.83	2.728	0.0
Avg	50.1	2.55	2.720	0.0
Marble <sup>3</sup>			2.87	0.5
Granite <sup>3</sup>		~~	2.56	0.9
Sandstone <sup>3</sup>		~-	2.05	15.0

Examination of the data reported by Obert<sup>3</sup> reveals that the Laramie core is roughly comparable to a typical granite.

13. An extensive study of rock properties and tests by Deere and Miller<sup>4</sup> indicated a good correlation could be obtained between the compressive strength and the Schmidt number when the unit weight (specific gravity) was taken into consideration. The above data, plotted in fig. 1 as a circled dot, agree quite well with the aforementioned work.

## Tensile and shear tests

14. Tensile 'ests were conducted by the indirect, or tensile splitting, method. Two series of single plane shear tests were conducted, one utilizing the standard NX size shear blocks (2.38 in. in diameter) and one utilizing smaller blocks (2.12 in. in diameter) fabricated for the small core (1.84 in. in diameter). Results are given below:

<sup>3</sup>Obert, Leonard, and Duvall, W. I., <u>Rock Mechanics and the Design of</u> <u>Structures in Rock</u>, 1st editio John Wiley & Sons, New York, N. Y., 1967. <sup>4</sup>Deere, D. U., and Miller, R. P., "Engineering Classification and Index Properties for Intact Rock," Technical Report No. AFWL-TR-65-116, University of Illinois, Dec 1955.



ţ.

-

۰. ÷.,

1.0911

200

÷

### Warren Siting Area: Core No. 1 (Laramie); Sample B; Series I

Core		
No.	Test	Strength, psi
3a	Tensile	1370)
3Ъ	Tensile	1420) 1490
3c	Tensile	1410)
5a	Shear (2.38-in. diam	meter) 1770)
SD	Shear (2.38-in. diam	neter) 2070) 1890
5c	Shear (2.38-in. diar	neter) 1830)
4a	Shear (2.12-in. dia	neter) 2330)
15a	Shear (2.12-in. diam	eter) 2080)2420
15Ъ	Shear (2.12-in. dia	neter) 2860)

Examination of the tensile strength data reported by Wuerker<sup>5</sup> reveals that the tensile strength of the Laramie core is comparatively high due possibly to the indirect method of testing. The large blocks yielded a rather low shear strength, indicating other stresses, probably including flexural, affected the results. Even the small shear blocks yielded shear strengths somewhat lower than the strength determined in the triaxial test (2420 versus 3100 psi). Posttest photographs of tensile and shear specimens are given in plates 2 and 3.

# Unconfined compressive tests

15. Three conventional unconfined and one cyclic unconfined compressive tests were conducted. All specimens had two vertical and two horizontal electrical resistance strain gages affixed in order to measure strain during testing. Stress-strain curves for the conventional tests are given in plates 4, 5, and 6. The average strength was 21,700 psi for the conventional tests. a terre a la forma de la la la comprese de la construction de la construction de la construction de la constru La construction de la la la construction de la construction de la construction de la construction de la constru

16. The cycled specimen was unloaded at 5000 psi intervals, but no hysteresis was detected until unloading at 20,000 psi (plate 7). The small amount of hysteresis indicates that the Laramie rock is a comparatively "stiff" material.

17. The average strength for the three cyclic tests, one each from samples A, B, and C, was 21,500 psi. The average strength, standard deviation, and coefficient of variation for all unconfined compressive tests were 21,580 psi, 490 psi, and 2.3 percent, respectively. Statistically, the variability is extremely small for a material such as rock.<sup>3</sup> One specimen, No. 7a, experienced a premature slippage along a healed fracture.

Wuerker, R. G., "The Shear Strength of Rocks," <u>Mining Engineering</u>, vol 11, Oct 1959.

# versen Siting Area: Core No. 1 (Laramie); Sample B; Series I

Atthough the fracture had little apparent effect on the results of this particular specimen, such fractures could affect strength and deformation properties on subsequent tests. Posttest photographs of the propressive test specimens, plate 8, show evidence of vertical splitting, often prevalent in compressive tests of brittle material. -14974

# weduli of efformation

18. Young's modulus, shear modulus, bulk modulus, and Poisson's ratio were computed on three samples hy the dynamic<sup>3</sup> (fundamental frequency) method and on the six unconfined compressive strength specimens statically using theory of elasticity. Results are given below:

		Young's Modulus	Shear Modulus	Bulk	
Pale	Core	of Elasticity,	(Modulus of Rigidity)	Modulus,	Poisson's
gh	No.	psi x 10'	psi x 10''	psi x 10°	Ratio
1.5.9.5.1.5.1.5.1.5.1.5.1.5.1.5.1.5.1.5.			Dynamical ly		
101 100 100 100 100 100 100 100 100 100	10	11.91	4.90	7.09	0.22
gth	12	11.56	4.54	8.38	0.27
	14	12.04	4.70	9.12	0.28
nd 3.					
·			Statically		
	7a	11.75	4.56-	9.18	0.24
	7b	11.71	4.32	9.28	0.30
ind	7c	11.12	4.43	7.63	0.25
to	10a	12.50	4,88	9.52	0.25
tional	17a*	9.00	3.52	4.64	0,28
,/00 psi	20a**	11.58	4.55	8.52	0.25
	Avg	11.77	4.51	8.59	0.26
l lat no	* Fr	alab · A alames mo.	ted from average	*····	
he	** Fr	rom sample A, dere	ted from average.		
fun Mildela A		in the pro-			
Lucannet L'	A curs	ory examination o	f the results reveals t	that correla	tion between
	the tw	no methods is good	. Therefore, the avera	ige values g	iven may be
Irom	consid	lered representati	ve for the deformation	properties	of the core.
	Veleed				
listically	Veroci	ty measurements			
	1	9 Compressive a	nd chase valocities us	heruseen ~	on three
cture	enecim	ione of sample R a	e indicated below.	r measuleu	
	aberin	THE VE SOMPLE D A	J ANGELELE VELVW.		
	•				
鬟ol 11,					

75

anter a state -

### Warren Siting Area: Core No. 1 (Laramie); Sample B; Series I

	Compressional	Shear
Core	Pulse Velocity,	Velocity,
No.	fps	fps
10	19,765	11,485
12	19,500	11,095
14	20,100	11,235
Avg	19,790	11,270

sti asee krowa në tekunika ë mkë dhe kretetisë bitështë bitë bita bërdhet dhe sh

bestare. Arises arrentificationales and arreations interaction data in the interaction of the factor of the man

The compressional velocity was determined directly as the sonic propagation velocity, and the shear velocity was determined from the torsional frequency obtained in the moduli determinations. The shear velocity is approximately 57 percent of the compressional velocity, which is a reasonable percentage for most rocklike materials.

### Marren Siting Area: Core No. 1 (Laramic); Sample C; Series I

#### Results

20. Only one test, a compressive strength test, was conducted on sample C. The specimen, from a depth of 153 ft, had a compressive strength of 22,300 psi. The stress-strein curve is given in plate 9.

### Conclusions

21. The compressive strength is approximately equal to the strength of spacimens at the other depths; therefore, the rock apparently is rather homogeneous throughout the interval tested.

warren Siting Area: Core No. 1 (Laramie); Sample B; Series II

### Results

# Hydrostatic compression

22. Hydrostatic compressive tests were conducted on three specimens, one each to pressures of 8000, 20,000, and 35,000 psi. The specimens were prepared in a manner similar to the unconfined compressive tests except that 1/2-in. foil gages affixed with epoxy were utilized rather than wire gages. Tests on a steel specimen and literature indicated negligible effects of confining pressure on foil strain gages. Stress-strain curves for the horizontal and vertical deformations for the three tests are given in plates 10-15. Utilizing the results of the best three loading cycles, the bulk modulus, K, was computed from the relation: 化过去分析 氯化化医氯化氯化 医外丛 化己酮 医白细胞 氯化化医己酮

MARKAGENYANDERKANDARENGANDARENG KONDARENG PARKEN ALA DELENARENG HANDEL SER ORDER BERTANDERAL GODERENAL ADDER KENKARDEN KENKARDER KEN

$$K = \frac{\sigma}{\epsilon_1 + \epsilon_2 + \epsilon_3}$$

where:

薏he

**R**ear

ive 9.

 $\sigma$  = hydrostatic stress

 $e_1 = vertical strain$ 

 $\epsilon_2 = \epsilon_3 = horizontal strain$ 

Specimen <u>No.</u>	Maximum Stress, psi	Bulk Modulus, <u>K,</u> p <b>si</b>
14d	8,000	11.19
14a	20,000	8.39
2a	36,000	9.77

The bulk moduli agree quite well with the dynamically determined moduli except for specimen No. 14d. The unusually high result may be due to testing error. The erratic behavior of the horizontal gages on specimen 14a during the first loading cycle is believed to be due to seating of the gages rather than actual deformation of the specimen.

### Triaxial compression

23. Triaxial tests were conducted on the same specimens utilized for the hydrostatic tests at confining pressures equal to the hydrostatic pressures previously applied. Stress-strain curves are given in plates 16, 17, and 18. Young's modulus, computed as the initial tangent, and Poisson's ratio are given below:

<sup>5</sup>Milligan, R. V., "The Effects of High Pressure on Foil Strain Gages," Experimental Mechanics, 4 (2), 25-36, 1964. Warren Siting Area: Core No. 1 (Laramie); Sample B; Series II

「東京学」ちょくたらないの情報をたちょく、

Specimen No.	σ <sub>3</sub> , psi	<u>E, psi x 10<sup>5</sup></u>	Poisson' <b>s</b> Ratio
14d ·	8,000	13.5	0.33
14a	20,000	11.0	0.31
2a	36,000	12.0	0.29

The results are not significantly different from those obtained in the unconfined compressive tests.

24. The Mohr's circles for the lower stress range, given in plate 19, indicate an unconfined shear strength of approximately 3100 psi. The circles for all tests are given in plate 20. The envelope is apparently straight line up to the 20,000 psi confining pressure level at an angle of 41.5 deg and then assumes a curvilinear relationship with increased confining pressure; however, pronounced shear planes developed in the specimen tested at 8000 and 20,000 psi confining pressure, and initial failure occurred along a crystal face in the 36,000 psi test specimen. Thus, the curvature of the envelope may be due to premature yielding along the crystal interface. Preand posttest dimensions for the 20,000 and 36,000 psi tests are given in plates 21 and 22, respectively. Posttest photographs are given in plate 23.

25. The compressional wave velocity was recorded during test to failure of two specimens, 2a and 14d. The results in plates 15 and 17 indicate that the velocity increases initially under load probably due to closure of small cracks and then remains rather constant up to failure.

#### Confined compression

26. Confined compression tests were conducted on two specimens preparel essentially as the triaxial test specimens. Confining pressure was applied to prevent lateral straining as axial load was applied by the piston. Therefore, a pseudo one-dimensional state of stress was induced, from which can be computed a constrained modulus. The axial stress-strain curves are given in plates 24 and 25. The lateral stress required to maintain a condition of no lateral strain is given on the far left of the curves.

27. The constrained modulus,  $M_c$ , may be computed from theory of elasticity:

$$M_{c} = \frac{E(1-u)}{(1+u)(1-2u)}$$

" where:

AND DEPARTMENT OF THE PARTY OF

E = Young's modulus

u = Poisson's ratio

# Warron Siting Aroa: Coce No. 1 (Laramia); Sample B; Series II

Using the results from the triaxial tests ( $I = 12.2 \times 10^6$  psi; u = 0.31), the constrained modulus theoretically would average 16.9 × 10<sup>6</sup> psi. The constrained moduli computed as the initial tangent to the stress-strain curves are 17.0 × 10<sup>6</sup> and 15.5 × 10<sup>6</sup> psi for specimens 1a and 14c, respectively. Good correlation is, therefore, indicated between the theoretical and expansiontal results.

### Conclusions: Laranie Core

28 The Lacasie core is a rather brittle material classified as soda diorite with an estimated 30 percent of the rock plagioclase feldspar. consensus results of some physical properties include: compressive strength, 21,600 psi; Young's modulus, 11.3 x 105 psi; bulk modulus, 3.6 x 106 psi; specific gravity, 2.72; compressional wave velocity, 19,600 fps. The rock was very homogeneous with depth for the length sampled 17 to 150 ft. The large crystal size, estimated to be 2 in. or larger in the core log, apparently did not significantly affect the results. The variations in test properties were very small for a material such as rock. The triaxial tests indicated that the Mohr's envelope was straight line at an angle of 41.5 deg up to at least 20,000 psi confining pressure. The highest pressure available for these tests, 36,000 psi, did not allow full definition of the envelope. Little hysteresis was evident in the stress-deformation tests, indicating very little energy absorptive capacity for the intact rock.

in the

n n

şing

ced

Sinear

psi

face

lope

iven

n in

to d 17 due

s ssure by the uced, strain o f the

e-

ĨI





÷. ÷. ī, . . . たいの方形をつけてい ÷Ŧ. -おうごう ラインバック 1 A state of the state of th į TX : -/ 15 A Posttest photographs PLATE 3 82 

「ALLINY」、加速的よ加速型に成功である。 主要





dan terki









1.1

ŝ

পাল, ইননা মনি না মাতে মান পাল কি নিমালি হৈ জিলা এন বিশিষ্ঠ কি পাল প্ৰতিপোষ্ঠা দি মানি লানি পিউনি লিখিয়া হৈ দি নাম পাল পিউনি বিশিষ্ঠিয়ি বিশিষ্ঠ বিশিষ্ঠিয়ি বিশিষ্ঠ বিশ



-X. 1

••• ÷.,

2.44 .









----



or thur have by the ball debut had a





÷

いたいいわかりというとう

2010

しんどこう しょうちんどうちん しんたいろうし

ř,

1. Jac . 2. 2. 2

Sec. 1

1.10

N 335

7.7

.

1日の日にやいた。

માં કે બેન્ટ કે પ્રાયક્તિ છે. જે આવ્યું છે તે આવ્યું હતું છે. આ પ્રાયક્તિ કે પ્રાયક્તિ કે બિને ડિલેન્ડિસ કે પ્રિયક્ત કે પ્રાયક્ત

ሲለት። ከተሰደች ተቆጠቀም ላይ በብለት በቆጠቀም በተለያከት ማድምር በቆጠቀም የሚሰራቸው የአስት የአመስት ላይ ከሆኑ በማስት የአስት የአስት በበላ በ በ በ በ በ በ በ በ በ













às 🖘

# APPENDIX C

DATA REPORT - HOLL CR-19 CORES

11 OCTOBER 1958

5.0

### WARREN SITING AREA

# Core No. 4 (Hole CR-19)

. .

1. Sixteen pieces of core were received from the Warren area on 20 September 1958, designated CR-19 core. Numbers were assigned as indicated.

Sample	Specimen Designation	Approximate Depth, ft
Α	. 1	14
A	2	15
A	3	17
A	4	18
В	5	83
В	6	84
В	7	85
В	8	85
В	. 9	85 .
В	- 10	87
В	11	88
С	12	190
С	13	191
С	14	192
- C	15	193
С	15	194 .

2. The hole from which the core was taken was located in Albany County, Wyoming, township 19N, range 72W, section 3.

Warren Siting Area: Core No. 4 (Hole CR-19); Series I Tests

### Results

### Petrographic report

1. About 15 ft of NX rock core from three depths in hole CR-19  $_{\rm MA3}$  received in September 1948 for testing. The four pieces of core ged for petrographic examination are identified below:

CD Serial No.	Piece No.	Depth, ft	Length, ft
SANSO-2 DC-4	· 1 (Pottom hart)	15,0	1,/3
54150-2 DC-4	<u>.                                    </u>	35.4	1/3
SA150-2 DC-4	13 ' 1 par*)	191.0	1/3
5A1150-2 DC-4	15 (west in part)	194 9	1/3

2. All of the rock i = coarse-gamma ind but variations in crystalsize caused variations in the appearant of the core. Pieces 5 through15 had maximum crystal size, while pieces 1 and 2 had the smallestcrystals and pieces 3 and 4 were intermediate in grain size. Piece 15was unique in that the bottom portion was reddish rock instead of darkgreenish gray rock.

3. The petrographic work was performed as described in reports on previous samples that have been examined (SAMSO-2 DC-1 through 3). 4. The core consists of coarse-grained dark-colored rock which consists largely of plagioclase feldspar with small amounts of biotite and what is probably a pyroxone mineral; there are even smaller amounts of iron-rich olivine, chlorite, kaolinite, quartz, calcite, magnetite, iron sulfide, muscovite, and possibly other unidentified minerals. The plagioclase occurs as euhedral phenocrysts; most of these are about 1/2 in. by 1/15 to 1/8 in. The other minerals in the rock have less well developed crystal shapes; except for a few plagioclase crystals forming inclusions in pyroxene or olivine.

5. This rock is classified as soda-diorite rather than anorthosite because the plagioclase is andesine rather than a more calcic type, which would justify the name anorthosite. The rock is essentially identical to the previous sample of soda-diorite from hole 1, Project S-11, 100 (laramie core). The major difference in the rock from the two holes is that the present rock is not as coarse grained. Photographs 1 and 2 illustrate the appearance of this rock at 2X and at 1X.

<sup>6</sup>. There is an unusually large amount of magnetite in the lower portion of piece 16 just above the contact with the reddish rock.

7. The fine-grained, reddish igneous rock in piece 15 contains potassium feldspar, plagioclase feldspar, quartz, mica, and haolinite. It is a rock of granitic composition, different from the soda-diorite (photograph 3).



1

ereller.



Photograph 1. Sawed surface of piece 8 of SAMSO-2 DC-4. Magnification, ?.




Warren Siting Area: Core No. 4 (Hole CR-19); Series I Tests

8. Some of the fracture surfaces are coated with a thin layer of blackish material. A sample from the fracture ending piece 13 was identified as vermiculite.

9. Thin sections and ground surfaces of the rock examined in polarized light or with a stereomicroscope show fairly extensive alteration of all of the constituents except the predominant andesine feldspar.

#### Schmidt number, specific gravity, porosity, and tensile strength

10. Three specimens from each depth interval were selected for the basic tests. Results are given below:

-	Sci	hmidt			Tensile
	Rebound	Standard	Specific	95	Strength,
Core	Number	Deviation	Gravity	Porosity	psi
		Sample A -	15-ft Depth		
15	55.8	4.16	2.787	0.0	1300
25	51.9	3.74	2.864	. 0.1	1070
<b>4a</b>	54.5	4.30	2.811	0.0	1030
۸vg	54.1	4.07	2.821	0.0	1130
		Sample B -	85-ft Depth		
5a	60.5	4.02	2.846	0.1	1170
7a	59.1	4.03	2.895	0.0	1240
9a	58.9	3.30	2.887	0.1	1530
Avg	59.5	3.78	2.875	0.1	1310
		Sample C -	190-ft Depth		
12Ъ	55.0	5.90	2.848	0.1	1930
13a	56.7	5.73	2.873	0.0	1140
15b	57.4	5.08	2.906	0.1	3250
Ave	56.4	5.58	2.875	0.1	1350

11. Indications are that the CR-19 core is a very hard, strong material. Schmidt numbers of 60 are encountered only with the trughest of rock. The rock in the upper elevation (15-ft depth) is only slightly different from that from the lower two intervals tested.

111.

Warren Siting Area: Core No. 4 (Hole CR-19); Series I Tests

#### Shear tests

12. Direct single plane shear tests were conducted on three samples from the 85-ft depth interval and one sample from the 15-ft depth interval. Shear strengths of 1530, 1580, and 1510 psi (average 1560) were obtained on samples 9a, 9b, and 11a, respectively. One test, on sample 3b, from the upper elevation resulted in a shear strength of 1060 psi. A posttest photograph of the test specimens is given in plate 1. 

#### Unconfined compressive strength tests

13. Conventional unconfined compressive strength tests were conducted on specimens from the upper and lower depth intervals and cyclic compressive tests on specimens from the middle depth interval. Results are given below:

		Unconfined		
Core	Depth,	Compressive		
No.	ft	Strength, psi		
la	14	24,500		
2a	16	30,600		
3a	17	20,100		
Avg	15	25,070		
5Ъ	83	27,700		
7Ъ	85	30,900		
9Ъ	85	27,900		
Avg	85	28,830		
12a	190	25,400		
13Ъ	191	25,700		
15a	193	22,900		
Avg	191	24,570		

There is no significant change of strength with depth; however, the material is quite variable as indicated by the wide range of strengths (20,500 to 30,000 psi).

14. All specimens had two vertical and two horizontal electrical resistance strain gages affixed in order to measure strain during testing. The cycled specimens were unloaded at 5000-psi intervals. Stress-strain curves are given in plates 2-10. The stress-strain

Marren Siting Area: Core No. 4 (Hole CR-19); Series I Tests

relationships were linear almost to failure; hysteresis was negligible. To compute the deformation moduli, a tangent at 50 percent of the ultimate strength was constructed as a dashed line on the stress-strain curves. A posttest photograph of the test specimens, plate 11, shows the nature of failure, steep sided coning.

: 3ir.

人物をなななない。

#### soluli of deformation

- 15. Young's modulus, shear modulus, bulk modulus, and Poisson's ratio were computed on three samples by the dynamic (fundamental frequency) method and on the unconfined compressive strength specimens statically at approximately 50 percent of the ultimate strength. Results are given below:

Core No.	Young's Hodulus of Elasticity, <u>psi x 10<sup>6</sup></u>	Shear Modulus (Modulus of Rigidity), psi x 10 <sup>6</sup>	Bulk Modulus, psi x 10 <sup>4</sup>	Poisson's Ratio
		Dynamically		
ŀ	12.43	4.87	9.42	9.28
10	15.73	5.75	20.17	<b>3.37</b>
15	13.55	5.11	14.23	0.34
•		Statically	•	
la	14.20	5.55	10.75	0.28
2a	13.60	5.27	10.79	0.29
3a	13.40	5.04	13.14	0.33
5b	13.20	4,92	13.75	0.34
7ъ	14.50	5.53	12.72	0.31
95	15.50	5.92	13.50	0.31
12a	13.90	5.39	11.03	3.29
13b	15.10	5,94	10.94	0.27
15a	13,40	5.04	13.14	0.33
Avg Stat	ic 14.09	5.40	12.21	0.30

15. The static and dynamic results agree well with the exception of the dynamic bulk modulus for core No. 10 which is unusually high. The moduli are significantly high for rock, higher than many rocks of comparable strength. Apparently this is a very rigid material.

#### Velocity measurements

17. The compressional wave velocity was determined directly as the sonic propagation velocity, and the shear wave velocity was determined from the tersional frequency obtained in the moduli determinations. Marren Siting Area: Core No. 4 (Hole CR-19); Series I Tests

1.

Core No.	Compressional Velocity, fps	Shear Velocity, <u>fps</u>
1	20,405	11,405
10	20,490	11,720
15	20,825	11,355
Avg	29,570	11,490

The shear velocity is approximately 56 percent of the compressional velocity.

#### Conclusions

18. The CR-19 core is identified as a suda-diorite, essentially identical to the Laramie core except that it is not as coarse grained as the Laramie core. The CR-19 core is an unusually heavy, rigid material which is rather variable in strength throughout the intervals tested. Consensus results of some physical properties compared to the Laramie core are: 

Property	Laramie Core	CR-19 Core	
Specific gravity	2.72	2.85	
Percent porosity	0.0	0.1	
Compressive strength, psi	21,500	26,190	
Tensile strength, psi	1,400	1,270	
Young's modulus, psi x 10"	11.8	14.1	
Compressional wave velocity, fps	19,800	20,570	









ሙስ ቆይነት ታቸውን ውስ ማሪትሪያውን ተውስብ በሰብ የሰብ የሆኖት አንድቶ አውስ የመስለኛው እንደችለው በመስለው የአውስ እንደት በብራ እንደ አውስ እንደት እንደ እንደት እንደት በእንደ መስለ እንደ





- merciale

í é -



.



au + 100 × 2010年1月1日的新聞的品牌的 副的名式名词的 计用力分子存在的分子 法上的







# APPENDIX D

Des Contra

DATA REPORT - HOLE CR-32 CORES

15 OCTOBER 1968

#### WARREN SI'TING AREA

#### Core No. 5 (Hole CR-32)

1. Eleven pieces of core were received from the Warren area, designated CR-32 core, on 23 September 1958. Numbers were assigned as indicated.

ニステレの事物がなることです

のいたいないたいたいないないないというのできのないたちがいたらいないないないない

Sample	Specimen Designation	Approximate Depth. ft
A	• 1	158
A	2	159
Α	3	160
A	. 4	161
A	5	152
A	5	153
A	7	154
A	8	155
Α	9	168
A	10	170
A	11	174

2. The hole from which the core was taken was located in Albany County, Wyoming, township 17N, range 72%, section 35. All core was drilled vertically. Specimens were cut as required for the various tests; each segment of the specimen was given a letter designation signifying the section cut; for example, specimen 7a was the first test piece cut from specimen 7. Tests ware conducted identical to previous tests on the Warren area core. warren Siting Area: Core No. 5 (Hole CR-32); Series I Tests

#### Results

- - Ex +

#### petrographic examination

3. One box of NX rock core fragments representing depths 157.9 through 176.5 ft from hole CR-32 was received in September 1968 for testing. The pieces used for the petrographic examination are shown below:

CD Serial No.	Piece No.	Depth, ft	Length, ft
SAMSO-2 DC-5.	3B	161	1/3
SAHSO-2 DC-5	4∧	151.4	1/3
SAMSO-2 DC-5	<b>4</b> B	161.7	1/3
SAMSO-2 DC-5	8	162	1/4

4. The test procedure was similar to that followed for previous samples in this series.

5. The core consisted of light-colored, grayish igneous rock and of black schist. The approximate disposition of these materials is shown below:

Interval, ft	Description		
157.9 - 161	Igneous rock.		
161 - 162	Black-schist and contact with igneous rock; the contact surface is dipping about 45 degrees.		
162 - 166,4	Igneous rock.		
165.4 - 175.5	Black schist.		

5. All of the core is badly fragmented due to the presence of numerous horizontal, vertical, and steeply dipping fracture surfaces. Some of these fractures are open and some are not, but almost all of them were present prior to drilling; the presence of a thin coating of white or pinkish calcite on most of these broken surfaces is proof of their age. The core fragments of schist tend to be about 1 to 2 in. long, and the core fragments of the igneous rock tend to be about 4 in. long, although there are longer pieces of both types.

7. The rock described in the field log as coarse-grained, medium gray anorthosite is the grayish igneous rock and the material described as some combination of the terms fine-grained, black, sandstone texture, or broken is the black schist. Marren Siting Area: Core No. 5 (Hole CR-32); Series I Tests

8. Photograph 1 illustrates the appearance of the two rock types, and photograph 2 shows the joint or fracture patterns in the igneous rock.

ころうちょうでいろいろう

くろうちょうかん かんかん そうちょう ちょうちょう しゅうてん ちゅうかい あいてんてい あいちょう ちゅうちゅう かんない あいちゅう 日本 かんせいせい ないない ないない ないない

ころうろうちちちちちちちろうちちちちちちちちちち つろちちちちょうろう

9. The igneous rock is medium-grained with some grains ranging up to 1/4 in., but most are more like 1/15 in. in size. The rock is composed largely of plagioclase feldspar with smaller amounts of hornblende and biotite; there is also some chlorite and an opaque mineral and perhaps some kaolinite. Most of the plagioclase shows some alteration. The plagioclase is labradorite with a composition of about Ab40An50. This rock is a lime-diorite by the terminology of Shand.\* This material was logged as anorthosite in the field. Shand prefers to restrict the term anorthosite to rochs "composed almost entirely of feldspar."

10. The black schist is composed largely of hurnblende, chiorite, and montmorillonitic clay; there is also a little plagioclase feldspar, and there may be some kaplinite. There is probably some mica, but it is very minor in amount.

11. It is not possible to determine which is the host rock and which the intrusive rock from the limited structure shown by the core. All of the specimens selected for the physical tests were lime-diorite; none of the black schist samples were large enough to secure test specimens.

#### Schmidt number, specific gravity, porosity, and tensile strength

12. Due to the highly fractured nature of the samples, only three specimens could be secured for the basic tests. Results are given below:

	Schmidt				Tensile
Specimen	Rebound Number	Standard Deviation	Specific Gravity	7 Porosity	Strength, psi
4d	54.5	4.56	2.753	0.0	1290
5b	55.9	5.19	2.754	0.2	1460
ճЪ	53.1	5.03	2.756	0.0	1580
Avg	54.8	4.96	2.758	0.1	1440

The rock tested is apparently a hard, dense material. However, the indication of high quality rock by these basic tests should not be

Shand, S. J., Eruptive Rocks, 3d edition, John Wiley and Sons, New York, N. Y., 1947.



Warren Siting Area: Core No. 5 (Hole CR-32); Series I Tests

and the second second



Photograph 2. Sawed surface of piece 8 from core hole CR-32, depth about 156 ft, natural size. Ends of core indicate pair of intersecting joint systems. warren Siting Area: Core No. 5 (Hole CR-32); Series I Tests

construed as evidence of a competent material throughout. The entire each of sample received was highly fractured; locating sufficient for test specimens was difficult.

## tests

sts

### reconfined compressive tests

14. Conventional unconfined compressive tests were conducted three specimens. Results are given below: and the interview states of the states of the

Specimen		Unconfined Compressive		
No.	Depth, ft	Strength, psi		
5 <b>a</b>	162	29,900		
ба	163	21,700		
7a	164	30,800		
Avg	163	27,470		

is indicated in the basic tests, the material tested is fairly impetent, although quite variable. Specimen No. 5a was only i-1/2 in. long; therefore, the indicated strength may be high for this particular test. A posttest photograph of the test specimens, ilate 1, shows the nature of failure, steep sided coning.

#### Soli of deformation

15. Stress-strain curves for the unconfined compressive tests if given in plates 2, 3, and 4. The axial (vertical) stress-strain flationship is virtually linear. Young's modulus, shear modulus, istic modulus, and Poisson's ratio were computed on specimen 6 by the franic (fundamental frequency) method and on the unconfined compressive itensth specimens statically at approximately 50 percent of the ultimate friength. Results are given below:

No.	Young's Modulus of Elasticity, psi x 10 <sup>6</sup>	Shear Modulus (Modulus of Rigidity), psi x 10 <sup>5</sup>	Bulk Modulus, psi x 10 <sup>5</sup>	Poisson's Ratio
		Dynamically		
٢	9.63	4.54	3.55	0.05
		(Continued)		

Warren Siting Area: Core No. 5 (Nole CR-32); Weries I Tests

#### (Continued)

Specimen No.	Young's Modulus of Elasticity, psi x 10 <sup>5</sup>	Shear Modulus (Modulus of Rigidity), psi x 10 <sup>6</sup>	Bulk Modulus psix 10 <sup>6</sup>	Foisson's Ratio
		Statically		
5a	12.50	5.04	8.01	0.24
бa	12.00	4.62	10.00	0.30
7a Avg Stat	tic $\frac{11.50}{12.00}$	<u>4.53</u> . <u>4.73</u>	<u>8.33</u> 8.78	0.27 0.27

#### Velocity measurements

16. The compressional velocity was determined directly on specimen No. 6 to be 15,480 fps. The shear velocity, 10,980 fps, determined from the torsional frequency, is 71 percent of the compressional velocity. 

#### Conclusions

17. The rock from hole CR-32 was a highly fractured material consisting of a light igneous rock, lime-diorite, and black schist. Locating sufficient samples for testing was difficult: Consensus results of tests on the lime-diorite, given below, do not reflect the incompetent nature of the material as a whole.

Property	Lime-Diorite	
Specific gravity	2.75	
Percent porosity -	0.1	
Compressive strength, psi	27,470	
Tensile strength, psi	1,440	
Young's modulus, psi x 10 <sup>6</sup>	12.00	
Compressional wave velocity, fps	15,480	

1.34

		a si si secondari su secondari s
		blate surface
es 1 Tests		-
	<u>.</u>	- 99. F. F.
		- -
Bulk		
Modulus, Poi six 19 <sup>5</sup> Cr		
8.01 0.1 10.00 0.2		
8.33		
		-
directly on such is for determined a		
essional velocit;		•
андана О Салана В Салана Салана С		
etured material		
nd black schist.		
eflect the incr		
ž		
Diorite		
.75	SA GA 7A	
470		
440		
480		
	Posttest Photograph	
	135 DT ATT: 7	
A CONTRACTOR		



decision -

7 1 4

And the second states of the s

ころがないいたいないたいないないないないないないないないないです。 いろいろい





というなどのなどのである。



#### MARREN SITING AREA

#### Core No. 3 (Hole CR-4)

1. Eighteen pieces of core were received from the Warron area, designated CR-4 core, on 17 September 1958. Numbers were assigned as indicated.

	Specimen	Approximate
Sample	Designation	Depth, ft
Ύ <b>Α</b>	- 1	21
Α	2.	. 22
. A	3	27
Λ	4	32 ′
A	5	33
А	<i>ፍ</i> .	34
В	7	55
В	. 8	55
В	9	55
В	10	. 67
В `	11	58
В	12	59
. C	13	181
С	14	182
C	ነ <del>ን</del> '	- 183
C	15	184
С	· 17	184
С	18	1.85

2. The hole from which the core was taken was located in Albany County, Wyoming, township 27N, range 74%, section 3. All core was drilled vertically. Specimens were cut as required for the various tests; each segment of the specimen was given a letter designation signifying the section cut; for example, specimen 7a was the first test piece cut from specimen 7. Tests were conducted identical to previous tests on the Warren area core.

.140

garren Siting Area: Core No. 3 (Hole CR-4); Series I Tests

#### **Pesults**

## strographic examination

bany

1. About 15 ft of NX rock core from three depths in hole CR-4 Albany County, Wyoming, was received in September 1958 for testing. 3. specimens used for petrographic examination are identified below:

CD Serial	Piece	Depth,	length,
No.	No.	ft	ft
SAMSO-2 DC-3	1	20.8	1/3
SAMSO-2 DC-3	9	55.7	1/3

2. The rock in pieces 1 through 5 was medium-grained and pink, while that in the rest of the pieces (7 through 18) was more gray than bink in color. One end of piece 18 was transitional back to pink, coarse-grained material.

3. The petrographic work consisted of photography, X-ray diffraction examinations, and microscopical examinations using samples and procedures as described in previous reports for the samples from core hole 1, project S-11, 100 and from core hole CR-42.

4. Pieces 4 and 6 each contained nearly vertical open fractures. The fragmented condition and appearance of piece 4 indicated that it was quite weathered.

5. Piece 1 is composed primarily of quartz and plagioclase and microcline feldspars with minor amounts of biotite and chlorite and mrobably trace amounts of a pyroxene. Piece 9 differs from piece 1 in that potassium feldspar (microcline) is only a minor constituent. All of the rock except the bottom of piece 13 is medium-grained. The individual grains do not show crystal faces, with a few exceptions, and range from about 1/16 to 1/4 in. in maximum dimension (photograph 1).

5. All of the plagioclase feldspar shows some alteration, probably to sericite. There is little or no alteration of the potassium feldspar.

7. All of the rock was logged in the field as granite. The laboratory work indicates that, while granite is a suitable name for the pinkish rock of pieces 1 through 6, the grayish rock of pieces 7 through 17 is tonalite according to the classification of Shand\* rather than granite, because there is not enough potassium feldspar (microcline) to justify the name granite.

Shand, S. J., Eruptive Rocks, 3d edition, John Wiley and Sons, New York, N. Y., 1947.



# garren Siting Area: Core No. 3 (Hole CR-4); Series I Tests

and the second secon

c. The decrease in the amount of pinkish potash feldspar is also promisible for the color change from pink to gray. The difference in the loss not necessarily mean that the physical properties of the gray and the pink rock are different. They may or may not differ; the is all tests will determine this.

a. The results of comparing the present sample with the previous a from core hole CR-42 are listed below:

a. Texture. The present sample is finer grained. The settrum size of the feldspar phenocrysts is about 1/4 in. as compared about 1/2 in. for the rock from hole CR-42.

b. <u>Composition</u>. Both samples contain quartz and feldspars. represent sample contains biotite mica and chlorite while the rock re- hole CR-42 contains hornblende and montmorillonitic clay. The resent sample contains less potassium feldspar.

c. <u>Physical condition</u>. There are more steeply dipping old excluses in the core from hole CR-42 than in this core. More of the inicclase crystals show alteration in this rock than in the rock from the CR-42. Both cores contain roc', that appears fresh and rock that events to be weathered.

## smallt number, specific gravity, merosity, and tensile strength

1°. Three specimens from each depth interval were selected for the suic tests. Results are given below:

	Schwidt				Tensile
<u>Tre</u>	Rebound Number	Standard Deviation	Specific <u>Gravity</u>	3 Porosity	Strength, psi
		Sample A -	37-ft Depth		
34	55.4	4.11	2.637	0.0	1400
15	55.1	3.59	2.633	0.0	990
ʻ 3	49.0	5.48	2.627	0.0	97.0
, -	53,5	4.39	2.532	0.0	1120
		Sample B -	50-ft Depth		
.,	55.2	4,54	2,681	0.0	1210
•	54.8	4,92	2.587	0.0	1460
-	56.6	5.09	2.692	0.0	1340
`. e	55.9	4.85	2.687	0.0	1340

(Continued)

#### Warren Siting Area: Core No. 3 (Nole CR-4); Series I Tests

#### (Continued)

Schmidt					Tensile
Core	Rebound Number	Standard Deviation	Specific <u>Gravity</u>	y Porosity	Strength, psi
		Sample C -	180-ft Depth		
13b	57.5	3.35	2.680	0.0	1550
14b	57.9	4.09	2.708	0.0	1350
1Sc	55.0	5.54	2.599	0.0	1350
Avg	57.2	3.99	2.595	0.0	1420

The results, with the exception of the porosity tests, indicate that the rock in the upper elevations (30 ft) is somewhat less competent than that tested from the other elevations. There is very little difference in the materials from the 50- and 180-ft depths.

#### Shear tests

11. Direct, single plane shear tests were conducted on three samples from the 50-ft depth interval. Shear strengths of 2030, 1970, and 2100 psi were obtained on samples 7a, 8a, and 8b, respectively. The average strength was 2030 psi. Posttest photographs are given in plate 1.

#### Unconfined compressive tests

12. Conventional unconfined compressive tests were conducted on specimens from the upper and lower depth intervals and cyclic compressive tests on specimens from the middle depth interval. Results are given below:

		Unconfined Comp <b>res</b> sive		
Core No.	Depth, ft	Strength, psi		
2a	22	22,200		
35	27	25,000		
6a	34	25,700		
Avg	28	-24 , 300		
10a	57	32,800		
11a	68	30,100		
12a	69	26,500		
Avg	58	29,830		

(Continued)

arren Siting Area: Core No. 3 (Hole CR-4); Series I Tests

### (Continued)

Core No.	Depth, ft	Unconfined Compressive Strength, psi	
13a	191	32,300	
14a	1 92	31,900	
15a	183	32,000	
Avg	182	32.070	

with, the material from the upper elevation proved to be less competent are that from the lower elevations.

#### stali of deformation

ななのでないないないないないないないないないないないないで、ないないないない

「たかるとう」というまた

ちろうごちょうとうなるなかったいというちょうないないないでいたとうごちょうちょうないないないないないないないないない

14. Young's modulus, shear modulus, bulk modulus, and Poisson's Figure computed on three samples by the dynamic (fundamental "requency) method and on the unconfined compressive strength specimens "thically at approximately 50 percent of the ultimate strength. Results #is given below:

ेल्ट <u>३०,</u>	Young's Modulus of Elasticity, psi x 10 <sup>5</sup>	Shear Modulus (Modulus of Rigidity), psi x 10 <sup>5</sup>	Bulk Modulus, psi x 10 <sup>6</sup>	Poisson's <u>Ratio</u>
		Dynamically		
• :	5.68	2.71	2,10	0.05
3	9.59	4.14	4,70	0.16
4	10.49	4.49	5.30	0.17
		<b>Statically</b>		
12	9.10	3.78	5.23	0.21
12	10.50	4.41	5.65	0.19
<u>`</u> \$	10.40	4.13	7.22	0.25
-	10,80	4.50	6.00	9.20
<b></b>	10.40	4.30	5.98	0.21
543 53.	10.50	4.13	7.61	0.27
-1	10.70	4.18	8.11	6.28
<b>4</b> 8 	10.80	4.39	6.67	0,23
224 1950 - 1	10.60	4.11	8.41	0.29
TT Sta	tic 10.40	4.21	6.76	0.24
		145		
Warren Siting Area: Core No. 3 (Hole CR-4); Series I Tests

#### Velocity measurements

Lungal the 200

Ţ,

15. The compressional velocity was determined directly as the sonic propagation velocity, and the shear wave velocity was determined from the torsional frequency obtained in the moduli determinations.

	Compressional	Shear
Core	Pulse Velocity,	Velocity,
No.	fps	fps
2	14,605	8,785
7	17,930	10,045
14	18,795	11,230
Avg	17,110	10,020

The shear velocity is approximately 59 percent of the compressional velocity.

#### Conclusions

16. The CR-4 core is identified as granite in the upper elevations and tonalite in the lower elevations. The granite is less competent than the tonalite. Consensus results are given below:

Property	Granite	Tonalite	
Specific gravity	2.53	2.69	
Percent porosity	0.0	0.0	
Compressive strength, psi	24,300	30,950	
Tensile strength, psi	1,120	1,350	
Young's modulus, psi x 10 <sup>5</sup>	10.0	10.6	
Compressional wave velocity, fps	14,505	18,350	



PLATE 1



12017

×111-

0.00







151

いたが教育ないななななななないとう

このでのでのない、このであるのでの「「「「」」」」

الم الاستقال ما يعالمه المناصط والمعصوص والإليام المالية الم

4

- 1919年 日本語の書 日本の



ાસ્ટાન્ટ છે. La ન પ્રેસિસ જિલ્લે જે સાલભ છે. જે પ્રેસ લેવ છે જે વધુની જે છે છે. છે. તે છે જે છે જે છે. છે તે છે આ ગામ છે. છે La ન પ્રેસિસ જિલ્લે છે સાલભ છે. જે ખેતુ છે છે જે બધુની જે છે છે છે. છે છ Ż









いいいいいいのである

} +

はなない、つたとい

A 12 G.

and have a strategy of the second

i



THE SAFETY

SAPR -

-CONTRACTOR AND



ないないできない うちょうちょうちょう

ż

and the second second

Artheritation and a state of the second s

NEW CONTRACTOR

Posttest Photograph

PLATE 11

and a state of the state of the

the second s

などすい、などでや

### APPENDIX F

のためのかか

大学の言語に

DATA REPORT - HOLE CR-35 CORES

25 OCTOBER\_1968

#### WARREN SITTING AREA

#### Core No. 9 (Hole CR-35)

のないため、大学的なななないないないである

1. Eighteen mierces of core from one depth interval were received from the Warren area on 11 October 1965, designated CR-35 core. Numbers were assigned as indicated.

	Specimen	Approximate
Sample	Designation	Denth, ft
A	1	17
A	2	17
A	3	<u>! S</u>
A	4	19
А	5	20
A	5	21
A	7	22
Α	8	23
A	9	24
Α	10	25
A	. 11	25
A	12	25
Α	13	27
Α	14	28
A	15	25
A	15	29
A	17	29
A	18	30
•-	• •	

2. The hole from which the core was taken was located in Albany County, Myoming, township 15N, range 71W, section 2.

Warren Siting Area: Core No. 9 (Hole CR-35); Series I Tests

#### Results

Petrographic examination

3. About 13 ft of NX rock core from depths of 17.1 through 30.3 ft in hole CR-35 was received in October 1958 for testing. The petrographic specimen is identified below:

CD Serial No.	Piece No.	Depth, ft	Length, ft
SAMSO-2 DC-9	15	28	1/4

4. All of the pieces of core were similar in appearance except that the bottom portion of piece 16 and the top portion of piece 17 were unusually coarse grained. Most fracture surfaces were fresh and apparently were produced in drilling.

5. The test procedure was the same as that for the other rocks in this series.

6. The rock is coarse-grained, pink granite with white and black patches composed of pink microcline, white plagioclase, colorless quartz, and black biotite with smaller amounts of hornblende, kaolinite, pyroxene, and several other minerals. The plagioclase is either albite or oligoclase. There is some alteration of the feldspars, especially of the plagioclase.

7. The rock in this core is similar to the reddish granites from holes CR-42 and CR-48; all three cores may have been taken in the same igneous body.

8. The size of the pinkish microcline phenocrysts decreased from a maximum over 1 in. in CR-42 to about 3/4 in. in CR-48 to about 1/2 in. in the present core (photograph 1). As the size of the microcline phenocrysts decreased, the white plagioclase phenocrysts increased in size until they reached a maximum size of about 1/2 in. in the present core.

9. If there are significant differences in physical properties between these three cores, they may relate to the textural variations just described.

#### Schmidt number, specific gravity, porosity, and tensile strength

10. Three specimens were selected for the basic tests. Results are given below:

Warren Siting Area: Core No. 9 (Hole CR-35); Series I Tests

1. D K

14.50

، <sup>م</sup>تحصيلا الشاهداتين

Shi ukan Diskan Ababa



Photograph 1. Sawed surface of piece 15 from core hole CR-35, depth 28 ft, natural size.

darren	Siting	Area:	Core	No.	9	(Hole	CR-35);	Series	I Tests
1101							the second s	And in case of the local division of the loc	Statement of the local division of the local

	Sc	hmidt			<b>Tensile</b>
	Rebound	SLandard	Specific	73	Strength,
[:re	Number	Deviation	Gravity	Porosity	psi
30	54.5	2.77	2.656	0.4	955
175	53.3	3.29	2.596	0.0	990
:75	50.2	2.15	2.598	0.0	560
1.15	52.7	2.74	2.587	$\overline{0.1}$	870

#### wear tests

11. Direct single plane shear tests conducted on specimens 2a, 7b, in: 18a yielded shear strengths of 935, 1080, and 985 psi, respectively. The average, 1000 psi, is somewhat lower than that of the other granite from the Warren area.

#### meonfined compressive strength tests

12. Unconfined compressive strength tests were conducted on five recimens, three cyclic tests and two conventional tests. The results, given below, indicate good uniformity of the CR-35 core and comparable rength to the other Warren area granite.

		Unconfined Compressive		
Core No.	Depth, ft	Strength, psi		
3a	18	21,300		
7a	22	21,700		
10a	25	21,740		
14a	28	21,350		
17a	29	23,709		
Ave	24	21,960		

13. Specimens 3a, 7a, and 17a had two vertical and two horizontal "ictrical resistance gages affixed in order to monitor strain during "ading. Unloading cycles were made at 5000-psi intervals up to 15,000 psi. "ress-strain curves are given in plates 2, 3, and 4. The hysteresis """"s were small and closed. The peculiar shape of the third cycle curve "" smecimen 17a is unexplained. Possibly the strain gage loosened during "ading. A posttest photograph of the test specimens, plate 5, shows the """ ure of failure, steep sided coning.

#### inli of deformation

14. Young's modulus, shear modulus, bulk modulus, and Poisson's '\*: to were computed on three samples by the dynamic (fundamental Warren Siting Area: Core No. 9 (Hole CR-35); Series I Tests

frequency) method and on three unconfined compressive strength specimens statically at approximately 50 percent of the ultimate strength. Results are given below:

Core No.	Young's Modulus of Elasticity, 	Shear Modulus (Modulus of Rigidity), psi x 10 <sup>5</sup>	Bulk Modulus psi x 10 <sup>5</sup>	Poisson's Ratio
		Dynamically		
9	4.78	1.93	3.05	0.24
		Statically		
3a	7,80	3.28	4,19	0.19
7a	7.90	3.24	4.70	0.22
17a	8.10	3.24	5.40	0.25
Avg S	Static 7.93	3.25	4.76	0.22

#### Velocity measurements

15. The compressional wave velocity was determined directly as the sonic propagation velocity on specimen No. 9 to be 12,545 fps. The shear wave velocity was determined from the torsional frequency obtained in the moduli determinations to be 7350 fps.

#### Conclusions

15. The CR-35 core is identified as a coarse-grained, pink granite similar to the rock from holes CR-42 and CR-48. Consensus results of physical properties are:

. Property	Result
Specific gravity	2.69
Percent porosity	0.1
Compressive strength, psi	21,960
Tensile strangth, psi	870
Young's modulus, psi x 10 <sup>h</sup>	7.9
Compressional wave velocity, fps	12,545

3 5 T. 1 301555 . -: منيو. مرتبع م Ť . 1.1 الفران المراجع مع الحالي ، ما المراجع المراجع المراجع المراجع المراجع ، المراجع من مع المرجع من من م Postiest Photographs 165 PLATE 1

1.1.1.1.1.1.1.1.1.1









## APPENDIX G

「「「「「「「」」」」」

1. 8 A. 1. 1. 18 1

DATA REPORT - HOLE CR-39 CORES

21 OCTOBER 1968

bis a reinharisere evar vedra motorus senariserentas r

Í

AND IN

#### WARREN SITING AREA

#### Core No. 5 (Hole CR-39)

1. Fourteen bicces of core were received from the Warren area on 7 October 1958, designated CD-39 core. Numbers were assigned a indicated.

	Spacimen	Artroximate
Sanr le	Designation	Depth, ft
		55
n	-	
A	2	5/
A	3,	58
А	4	59
Α	5	50
B	4	144
В	7	145
В	8	145
В	9	147
С	10	192
С	11	• 193
С	12	195
С	13	195
С	14	197

2. The hole from which the core was taken was located in Alber County, Wyoming, township 14N, range 71W, section 23. both ] show:

東西なな大学の文明のたち

Fe

- -

pr: sim

rec is

pl+ A= F=c Warren Siting Area: Core No. 5 (Hole CR-39); Series I Tests Results . Petrographic examination 3. About 15 ft of NX rock core from three depths in hole CR-39 in Albany County, Wyoming, were received on 7 October 1968 for testing. The petrographic specimens are identified below: CD Serial No. Piece No. Length, ft Depth, ft SAMSO-2 DC-7 5 (bottom portion) 1/3 144 SAMSO-2 DC-7 12 (bottom portion) 195.3 1/3 4. All of the pieces of core were similar in appearance and no pre-existing fracture surfaces were seen. The petrographic work was similar to that done for all of the previous rocks in this test series. 5. The core is composed of coarse-grained, light-colored grayish rock which was logged as granite. The petrographic data indicate granite is a suitable name. 6. The rock is composed largely of quartz, potassium feldspar, plagioclase feldspar (probably oligoclase), and biotite with a lesser "ount of hornblende and a little kaolinite. The appearance of the rock 1 . wh by photograph 1. 7. This core was compared with the core from hole CR-42 since both were coarse-grained granites. The results of this comparison are Albany shown below. Core from Hole CR-39 Core from Hole CR-42 Coarse-grained light-Coarse-grained colored granite reddich granite All breaks in core Old limonite coated frac-うちたちないまではないないのいいとうないない こことを見たない、人にないないでいいい appear to be fresh. tures are non-erous. Abundant biotite. Practically no blotite No montmorillonitic clay Some montantfitenitic clay More quartz in this core



÷

Photograph 1. Sawed surface of piece 6 from core hole CE-39, depth 144 ft. Slightly larger than natural size.

# urren Siting Area: Core No. 5 (Hole CR-39); Series I Tests

The presence of the montmorillonitic clay and the old fracture first in the core from hole CR-42 indicates that there has been more institution of this rock and that it is more broken. The presence of institution fracture systems in the rock from core hole CR-42 may well in only difference of any importance between the cores from the two institutions of the cores from the two

## stilt number, specific gravity, porosity, and tensile strength

9. Three specimens from each depth interval were selected for the set it test. However, due to the apparent uniform nature of the rock, with three samples from the middle interval were subjected to all set. Results are given below:

	Sci	hmidt			Tensile
	Rebound	Standard	Specific	70	Strength,
	Number	Deviation	Gravity	Porosity	psi
		Sample A -	50-ft Depth		
	52.1	3.32	2.706	-	-
3 <b>a</b>	53.4	3.11	2.711	-	-
44	54.5	3.65	2.717	~	-
=1	53.3	3.36	2.711		
		<u>Sample B -</u>	145-ft Depth		
••	52.5	3.08	2.718	0.8	775
ia 👘	51.2	2.90	2.712	0.7	845
持	49.9	2.78	2.708	0.4	825
244 144	51.2	2.92	2.713	0.5	815
		Sample C -	195-ft Depth		
.)	52.0	2.55	2.720	-	-
	52.8	3.38	2.705	-	-
1.	51.8	2.84	2.712	-	-
113	52.2	2.96	2.712		

Sications are that the CR-39 core is a hard, uniform material through-

## tests

13. Direct single plane shear tests were conducted on one specimen in each of the three depth intervals as indicated:

Warren Siting Area: Core No. 5 (Hole CR-39); Series I Tests

Specimen	Depth,	Shear
No.	ft	Strength, psi
4Ъ	59	1340
55	44	1305
12a	195	1450
Avg		1370

#### Unconfined compressive strength tests

11. Conventional unconfined compressive strength tests were conducted on specimens from the upper and lower depth intervals and cyclic compressive tests on specimens from the middle depth interval. The results, given below, again indicate the uniform nature of the CR-39 core.

		Unconfined
Core	Depth,	Compressive
No.	ft	Strength, psi
2a	57	21.850
3Ъ	58	21,200
4Ъ	59	20,240
Avg	58	21,100
7b	145	20,400
8Ъ	146	21,000
9a	147	<b>~ 20,000</b>
Avg	145	20,470
10a	192	20,480
11a	193	21,770
13a	195	21,510
Avg	194	21,250

12. The specimens from the middle depth interval had two vertical and two horizontal electrical resistance gages affixed in order to monitor strain during loading. Unloading cycles were made at 5000-psi intervals up to 15,000 psi. Stress-strain curves are given in plates 2, 3, and 4. The hysteresis loops were small and closed. A posttest photograph of the test specimens, plate 5, shows the nature of failure, steep sided coning.

Vel the mir

È.

Hod.

rat: fre st. arc

Cor

No

1

7b 8b 9a

> The vel

# varren Siting Area: Core No. 5 (Hole CR-39); Series I Tests

## where of deformation

13. Young's modulus, shear modulus, bulk modulus, and Poisson's rise were computed on three samples by the dynamic (fundamental requency) method and on the unconfined compressive strength specimens rically at approximately 50 percent of the ultimate strength. Results 「おかちちろ」「おくないなくなられる」またち、おおいてあいないます」」

(see <u>55.</u>	Young's Modulus of Elasticity, psi x 10 <sup>6</sup>	Shear Modulus (Modulus of Rigidity), psi x 10 <sup>5</sup>	Bulk Modulus, psi x 10 <sup>0</sup>	Poisson's Ratio
		Dynamically		
i	8.85	3,95	3 80	
5	8.38	3 88	2.07	0.12
14	8.06	3 44	3.33	0.08
-	-	3.49	3.95	0.15
		Statically		
13	8.00	3.03	7 41	0.22
Ð	7.30	3.12	5 20	0.32
s.	7.90	2 00	5.20	U.25
		3.04	6.58	0.30

### Hircity measurements

14. The compressional wave velocity was determined directly as sonic propagation velocity, and the shear wave velocity was detersind from the torsional frequency obtained in the moduli determinations.

Core No.	Compressional Velocity, fps	Shear Velocity, fps	
1	17,360	10,440	
6	17,100	10.365	
14	16,530	9,755	
lvg	17,030	10,185	

s ver' -== r t' 501 -== a plater test #== ure, ===

のいたのためのというための

IC

ervs thi

Se shear velocity is approximately 50 percent of the compressional viscity.

### warren Siting Area: Core No. 5 (Hole CR-39); Series I Tests

.

#### Conclusions

15. The CR-39 core is identified as a coarse-grained granite somewhat similar to the core from hole CR-42. The core is very uniform in physical properties throughout the samples tested. Consensus results of physical properties are:

Property	Results	
Specific gravity	2.71	
Percent porosity	0.6	
Compressive strength, psi	20,940	
Tensile strength, psi	815	
Young's modulus, psi x 10 <sup>5</sup>	8.0	
Compressional wave velocity, fps	17,030	







でするな話したかです。



6.4.8 × 20

182

विज्ञीत्वरियाच्याक्षित्रां मेन्द्रियां मुन्द्रीय होत्ये आह्य आहः द्वतिविद्यां संदेश्वेर संवर्धतायां क्यांग्रिक

いっていたい ちょうちょう かんちょうかんかん かんない ないたい ひょうしん


## APPENDIX H

ANA REPORT - HOLE CR-42 CORES

27 SEPTEMBER 1968

### WARREN SITING AREA

## Core No. 2 (Hole CR-42)

1. Twenty pieces of core were received from the barren area, designated CR-42 core. Numbers were assigned as indicated.

	Specinen	Approvinate
Sample	Designation	<u>`k. , ft</u>
A	. 1	૩વ
λ	?	3९
Λ	3	30
A	<u>'</u> 4	40
<u>A</u>	5	41
А	5	41
A	7	42
В	8	94
В	9	85
r.	10	९९
В	11	97
B	•	88
R	13	e9
В	14	90
В	15	<b>a</b> Ŋ
В	15	91
Ç	17	195
C	18	185
С	19	136
С	20	167

2. The hole from which the core was taken was located in Albany County, Myoming, township 13N, range 72V, section 9. All core was drilled vertically. Specimens were cut as required for the various tests; each segment of the specimen was given a letter designation signifying the section cut; for example, specimen Ta was the first test piece cut from specimen 17. terren Siting Area: Core No. 2 (CR-42); Series I Tests

સહાલ છે. દ્વેતી આહેલ કે પ્રેસ્ટે પ્રેસ્ટે કે જે જે જે જે જે આજે તે આ વિદ્વાર્થ છે. જે છે છે છે છે છે છે છે છે છ

A)お本 おい、

「空間に

-

#### Results

# recraphic examination

統計のこれが、自己になるためで、など地となどの言語を見た。

- いろうち ちちち ちょう あんないのでんちょう

CD Serial No.	Piece No.	Depth, ft	Length, ft
SAMSO-2 DC-2(A)	1	37.9	About 1/2
SAMSO-2 DC-2(M)	13	89.5	About 1/3
SAMSU-2 DC-2(T)	20	188.0	About 1/2

3. Representative portions of piece 1 and of piece 13 were ground pass a No. 325 sieve  $(44\mu)$  and examined by X-ray diffractometry using scel-filtered copper radiation.

4. Two thin section. were made from piece 13 and examined with a colarizing microscope.

5. Piece 20 was sawed axially, and this surface was photographed.

5. All of the rock was logged in the field as red granite with imposite staining numerous fractures. Additional examination in the importance is a suitable name for this rock.

7. There were numerous near vertical iron-stained open joints i nany horizontal fractures in the core that was tested in this shoratory. Most of the horizontal breaks were fresh and appeared to i due to the drilling. The iron staining on joint surfaces indicated i'st these were old breaks. Most of the iron staining was due to itonite (tan) but that on piece 13 was due to hematite (red). This ifference in color indicates less weathering in piece 13.

8. The rock is composed of contmorillonitic clay, quartz, potash Adspar (microcline), plagioclase feldspar, hornblende, and small Maints of mica and an opaque mineral. Some of the leldspars, mostly "I plagioclase, show some alteration to a clay mineral. Warren Siting Area: Core No. 2 (CR-42): Series I Tests

北方が変化されたいとのででであっているのでものできたのでものできます。 へん きまんがって しゅぎんた

9. The presence of more montmorillenitic clay in piece 1 than in piece 13 confirms the visual impression that piece 13 is fresher rock.

10. The rock is coarse-grained with the maximum grain dimension ranging up to about half an inch (photograph 1).

11. An estimated composition for this roch is shown below:

	<u> </u>
Quartz .	20
Microcline	30
Plagioclase	49 - 45
Hornblende	5
Clay	up to 5 - 10

These numbers were obtained by comparison with an X-ray pattern of U. S. Geological Survey standard granite G-2 and by consideration of its composition.\*

## Schmidt number, specific gravity, porosity, and tensile strength

12. Three specimens from each depth interval were selected for the basic tests. Results are given below:

	Sch	midt			Tensile
	Rebound	Standard	Specific	<del>بر</del> ه	Strength,
Core	Number	Deviation	Gravity	Porosity	psi
	Sample A -	40-ft Depth			
25	46.9	6.79	2,554	0.7	600
36	48.3	4.25	2,554	0.5	720
76	52.6	6.07	2.574	0.0	8 <b>2</b> 0
Avg	49.3	5.70	2.657	0.4	710
	Sample B -	90-ft Depth			
9a	49.5	4.65	2.574	0.4	<b>S2</b> 0
12c	51.9	3.37	2.668	0.4	850
156	51.2	4.77	2,569	0.5	950
Avg	51.0	4.25	2.571	0.4	890
		(Cont	inued)		

\* Chayes, F., "Modal composition of U.S.G.S. reference sample G-2." Geochimica et Cosmochimica Acta, vol 31, No. 3, pp 453-54 (1967).



### Warren Siting Area: Core No. 2 (CR-42); Series I Tests

#### (Continued)

WAR WAR

	Sch	midt			Tensile
Core	Rebound Number	Standard Deviation	Specific Gravity	3 Porosity	Strength, psi
	Sample C-	185-ft Depth			
17ь	47.5	3.87	2.650	0.5	5 90
1 Sa	48.7	4.83	2.669	0.0	700
2)a	52.8	3.44	2.550	1.0	890
Avg	49.7	4.05	2.553	0.5	750

13. The results indicate that the CR-42 core is less dense and more porous than the Laravie core; however, it may be considered a hard, dense rock. Difference in the core with depth is not pronounced in the data from the basic tests. The variation, as indicated by the standard deviation of the rebound number, is greater than the Laramie core, due possibly to the numerous small fractures and/or constituents of the rock. The tensile strength is very much lower than the Laramie core (780 versus 1400 psi), possibly due also to the numerous small fractures. Posttest photographs of the test specimens are given in plate 1.

#### Shear tests

14. Direct, single place shear tests were conducted on three samples from the 90-ft depth interval. Due to the larger diameter of the CR-42 core, the 2.38-in.-diameter shear blocks were used. Shear strengths of 2150, 1700, and 1970 psi were obtained on samples 8, 9b, and 9c, respectively. Again, the average strength, 1910 psi, was somewhat lower than the Laramie core (2420 psi).

#### Unconfined compressive tests

15. Conventional unconfined compressive tests were conducted on specimens from the upper and lower depth intervals and cyclic compression tests on specimens from the middle depth interval. Results are given below:

Core No.	Depth, ft	Unconfined Comp. 255ive Strength, psi
2a	35	13,200
3a	39	13,300
7a	42	16,300
Avg	40	14,270

(Continued)

arren Siting Area: Core No. 2 (CR-42); Series I Tests

(Continued)

Core No.	Depth, ft	Unconfined Compressive Strength, psi
12a	88	23,000
13a	89	20,200
15a	90	22 300
Avg	39	21,930
17a	185	17 100
18a	186	19 900
19a	185	17 200
Avg	185	18,070

the petrographer--the core from the 90-ft depth is somewhat better the upper or lower areas sampled.

15. All specimens had two vertical and two horizontal electrical mistance strain gages affixed in order to measure strain during ming. The cycled specimens were unloaded at 5000-psi intervals. miss-strain curves are given in plates 2-10. Most of the specimens mitted a stress-strain relationship of the plastic-elastic type, i.e., mill "plastic" crack closing, followed by a definite steeper linear mitten. The hysteresis loops were essentially closed; little residual minutes and the ultimate strength was constructed as a dashed line the stress-strain curves. A posttest photograph of the test speciminutes and the ultimate of failure, steep sided coning, millent in compressive tests of brittle rock.

# -.li of deformation

17. Young's modulus, shear modulus, bulk modulus, and Poisson's severe computed on three samples by the dynamic (fundamental sevency) method and on the unconfined compressive strength specimens stically at approximately 50 percent of the ultimate strength. Results

; ]	Young's Modulus of Elasticity, psi x 10 <sup>6</sup>	Shear Modulus (Modulus of Rigidity), psi x 10 <sup>5</sup>	Bulk Modulus, psix 10 <sup>K</sup>	Po <b>isson's</b> Ratio
		Dynamically		
• • • •	8.19 7.82 5.32	3.40 3.53 2.37	4.55 3.34 2.27	0.20 0.11 0.11

(Continued)

### Warren Siting Area: Core No. 2 (CR-42); Scries I Tests

「「ないろうろうちょう

「たいでも、ともちないたいうちちょうろう

ハアイオンデレンションないがい ろうろう

## (Continued)

Core No.	Young's Modulus of Elasticity, psi x 10 <sup>5</sup>	Shear Modulus (Modulus of Rigidity), psi x 10 <sup>5</sup>	Bulk Modulus, psi x 10 <sup>6</sup>	Poissen's Ratin	
		Statically			
2a	10.21	4.16	5.18	0.22	
3a	8.48	3.73	3.92*	0.14*	
7a	10.52	4.11	8.39	0.29	
12a	9.75	. 4.06	5.42	0.20	
13a	9,89	3.77	8.58	0.31	
15a	10.25	4.19	5.18	0.22	
17a	9.21	4.05	4.22*	0.14*	
18a	9.80	3.74	8.61	0.31	
19a	11.77	4.72	7.87	0.25	
Avg Sta	atic 10.00	4.05	7.33	0.27	

\* Deleted from average.

18. The moduli are comparable to those obtained on the Laramie core. Computation of static results at 50 percent of the ultimate strength results in higher moduli compared to the dynamic results due to the higher stress levels involved. Low bulk moduli on specimens 3a and 17a are the result of low Poisson's ratio obtained on these two specimens.

#### Velocity measurements

19. The compressional velocity was determined directly as the sonic propagation velocity, and the shear wave velocity was determine' from the torsional frequency obtained in the moduli determinations.

	Complessional	Shear
Core	Pulse Velocity,	Velocity,
No.	fps	fps
4	16,780	9550
12	15,610	9580
17	13,615	7980
Avg	15,340	9070

The shear velocity is approximately 59 percent of the compressional velocity.

## Warren Siting Area: Core No. 2 (CR-42); Series I Tests

2 W

A Construction of the Cons

PLANA AND THE PLANA PLAN

## Conclusions

20. The CR-42 core is identified as a granite with limonite , aning numerous fractures. The rock was not as homogeneous with , th nor as competent as was the Laramie core. Consensus results ; one physical properties for the core tested compared to the granie core are:

Property	Laramie Core	CR-42 Core	
ecific gravity	2.72	2.57	
arcent porosity	0.0	0.5	
moressive strength, psi	21,600	18,000	
insile strength, psi	1,400	780	
fring's modulus, psi x 10 <sup>0</sup>	11.8	10.0	
mepressional wave velocity, fps	19,800	15,300	

imate ilts speciar these tr

Laramie

a oisse,

Rat !-

0.22

0.14\* 0.29 0.23 0.31

 $\begin{array}{c} 0.22 \\ 0.14^{*} \\ 0.31 \\ \underline{0.25} \\ 0.27 \end{array}$ 

as the eterniant tions.

isional .

Warren Siting Area: Core No. 2 (CR-42); Series II Tests

#### Results

#### Hydrostatic compression

21. Hydrostatic compressive tests were conducted on three specimens, one each to pressures of 9000, 18,000, and 36,000 psi. The specimens were prepared in a manner similar to the unconfined compressive tests except that the tests at 18,000 and 36,000 psi were conducted on 1.5-in.-diameter specimens recored from the NX size cores so as to have sufficient axial load capacity to fracture the specimens. Some difficulty was experienced with the gages on the CR-42 cores. The vertical gages on the specimen tested to 9000 psi (12b) and both vertical and horizontal gages on the specimen tested to 36,000 psi (4b) failed under the hydrostatic pressure. Stress-strain curves for the horizontal and vertical deformations for specimen 4s and the horizontal deformation for specimen 12b are given in plates 12, 13, and 14, respectively. Utilizing the results of loading cycles 3 and 4, the bulk modulus, K, was computed for specimen 4s from the relation: Ē

¢

2-

f 5

3.

C A1 01 Hc

**\$**1

Cc

Dr

$$K = \frac{\sigma}{\epsilon_1 + \epsilon_2 + \epsilon_3}$$

where:

 $\sigma$  = hydrostatic stress

 $\epsilon_1 = vertical strain$ 

 $\epsilon_2 = \epsilon_3 = horizontal strain$ 

The bulk modulus was computed for specimen 12b by using the horizontal strain thrice.

Specimen	Maximum	Bulk Modulus,
No.	Stress, psi	K, psi
125	9,000	5.00
4 <b>a</b>	18,000	6.67

The bulk moduli agree quite well with the dynamically determined moduli (paragraph 17). The almost equal strains obtained in the vertical and horizontal directions on specimen 4a indicate isotropy in this particular specimen.

# Warren Siting Area: Cure Nc. 2 (CR-42); Series II Tests

## riaxial compression

22. Triaxial tests were conducted on the same specimens utilized for the hydrostatic tests at confining pressures equal to the hydrostatic measures previously applied. Stress-strain curves are given in plates is and 16 for specimens 4a and 12b, respectively. Young's modulus, computed as the initial tangent, and Poisson's ratio for specimen 4a are 12.0 x  $10^6$  psi and 0.25, respectively.

23. The Mohr's circles for all tests are given in plate 17. The envelope was constructed utilizing the results of the unconfined, the 15,000, and the 36,000 psi triaxial tests of the weaker rock. An initial angle of shearing resistance of approximately 45 degrees and a slightly turving envelope are indicated for the less competent material. The saconfined strength (22,000 psi) and the one triaxial test at 9000 psi confining pressure on the better rock indicate a higher initial envelope mgle, 52 degrees.

24. The compressional wave velocity was recorded during test to failure of two specimens, 4a and 4b. Equipment malfunction prevented masurements during test of specimen 12b. Results are given below:

Specimen 4s		Specimen 4b	
Axial Stress, psi	Wave Velocity, fps	Axial Stress, psi	Wave Velocity, fps
0 15.000 (hydrostatic) 30.000 50.000 75.000 .20.000	18,940 20,830 21,930 23,140 24,500 24,500	0 36,000 (hydrostatic) 50,000 75,000 100,000 125,000 150,000	18,940 20,830 21,930 23,140 24,500 26,040 26,040

Semiderable difficulty was experienced in obtaining a valid wave picture. When the results should be considered only approximate due to the necessity of using the extremely small specimens (1.5 in. diameter, 3 in. long). However, indications are that the velocity does change somewhat under eress. A posttest photograph of the test specimen is given in plate 18.

# artined compression

25. Confined compression tests were conducted on two specimens <sup>Prepared</sup> essentially as the triaxial test specimens. Confining pressure <sup>At</sup> applied to prevent lateral straining as axial load was applied by the

ac speci. The Compressing ducted ce as to have me difficulture cal gages of the hydron livertics: lor species ting the computed

ned nothing ticsl saf

orizontal

is particula

## Warren Siting Area: Core No. 2 (CR-42); Series II Tests

piston. Therefore, a pseudo one-dimensional state of stress was induced, from which can be computed a constrained modulus. The axial stressstrain curves are given in plates 19 and 20. The lateral stress required to maintain a condition of no lateral strain is given on the far left of the curves. The gages failed after 7500 psi lateral pressure had been applied to specimen 14g.

26. The constrained modulus,  $\rm M_{C}$  , may be computed from theory of elasticity:

$$M_{c} = \frac{E(1-u)}{(1+u)(1-2u)}$$

where:

E = Young's modulus

u = Poisson's ratio

Using the results from the triaxial test of the more competent material  $(E = 12.0 \times 10^6 \text{ psi}; u = 0.25)$ , the constrained modulus is computed to be 14.4 x  $10^6$  psi. The constrained modulus computed on the linear portion of the stress-strain curve for specimen 16a is approximately 15.0 x  $10^6$  psi. Good agreement is, therefore, indicated between the theoretical and experimental results.

لملعا العادية الملعانية الملها بطالها بالماسانية بليام البال مدالم وطايدا فالهادا والمارية الإمادا وومواد ومنعا

and the set of a strategy and the set of the 1 CT C HER WAR ÷ のためになる。 第二、日本のために、 第二、日本のたのに、 二、日本のたのに、 二、日本のたのに、 二、日本のたのに、 二、日本のたのに、 二、日本のたのに、 二、日本のたのに、 二、日本のたのに、 二、日本のたのに、 二、日本のたのに、 二、日本のたのに、日本のたのに、 二、日本のたのに、 二、日本のたのに、 二、日本のたのに、 二 s h -----657.7 や、私、学、記録の発展を発展 Ċ. ALL AND ALL AN Į · ANTOPOLISTIC RULE - τ. t ・・・・ ちょうかん ちゅうちょうかん しょうしん しゅうせいしょう ちゅうたいちょうちょう あいまん ちゅうちん あいまん ちょうちょう ちょう 冒限 ەرك  $\varepsilon$ 2 Posttert Photosraphs ÷, 107 PLATE 1.

\$



CITY WILLIAM

New Providence

はたなである



如此不是,如此是我们的这些是是我们的事情的的是,这些是我们,不是有了这个时,不是有一个的人,不是有一个,这个时间,也是有这些人的事情,也是有一些的事情,也是这些我们的事情,也能能是我们的事情,也能能



-5





STRESS-STRAIN CURVE Unconfined Compression CR-42 Core Specimen - 19a 17,200 psi 24000 ; \$ 20000 Verbige1 16000 (ING) COMME ł 12000 8000 4000 ٥ 0 800 1600 2400 3200 STRAIN (microin./in.) PLATE 7 203

ロントの語言となるなどであるとなったとう





 $\overline{U}$ 



· information

Particular and the second second second second second

""下出来这些不能是这个的变化的学校也是我



LEARNING STATES たのであるのである







うちょうちょうちょう しょうちょうちょう ちょうちょうちょう しょうちょう ちょうちょう

 $\sim 10$ 



**CULTURE CONTRACTOR** 「なななないないないないないないない」とないのとうと たちまたまであるない í, 

.

-

and a second of the second of the second s





いたいやいろうち ちょうちょうてい

بالمرافع بلاعا لأدمام بالرمام المرام والمرافع والمرافع والمرافع

N. 4.4 1.4 2.4 4.4 4. 5 4.4

スシンシングジンシー





NALES NEW CON







HAM CONSTRUCTION OF CONSTRUCTURE OF

as sets as a left of points to the result of the balance of the set のたちないないないというできたいであったちをもんできたい

# APPENDIX I

というなかもあい

CONFINED COMPRESSION TEST

DATA REPORT - HOLE CR-48 COR 55

24 OCTOBER 1958

217

## WARREN SITING AREA

## Core No. 8 (Hole CR-48)

1. Fourteen pieces of core were received from the Warren area on 12 October 1968, designated CR-48 core. Numbers were assigned as indicated.

Somple	Specimen	Approximate
Sample	Designation	Deptil, It
Λ	1	27
A	2	28
٨	3	29
A	4	30
B	5	95
В	5	95
В	7	97
R	8	98
С	9	182
С	10	183
· C	11	184
С	12	185
С	13	185
С	14	187

2. The hole from which the core was taken was located in Larimer County, Colorado, township 12N, range 70W, section 20.

いたいで、ためていていたい。

<u>s</u>

5 ti Warren Siting Area: Core No. 8 (Hole CR-48); Series I Tests

#### Results

#### Petrographic examination

3. About 15 ft of NX rock core in 14 pieces, representing three denths in hold CR-49, were received in October 1968 for testing. The petrographic sample is identified below:

CD Serial No.	Piece No.	Depth, ft	Length, ft
SAMEO-2 DC-10	8 (top portion)	98	1/3

4. All 14 pieces of core were similar in appearance except that the patches of black hornblende and biotite in the middle portion of " piece 8 were smaller in size and more numerous than in the rest of the pieces.

5. The broken surfaces of the pieces of core appeared to represent fresh fractures associated with the drilling procedure rather than old fractures.

5. The test procedure was similar to that followed in examining the other samples of this series.

7. The rock in this core is coarse-grained, reddish granite (photograph 1) composed of pink microcline, white plagioclase feldspar, quartz, and biotite, with smaller amounts of hornblende, kaolinite, myroxene, calcite, muscovite, and an opaque mineral. The plagioclase is either albite or oligoclase. There is some alteration of the feldspars, mainly of the plagioclase, to kaolinite. 8. Comparison with the reddish granite from core hole CR-42indicates that the rock in the two cores is similar except that the CR-48 cores contain abundant biotite which was virtually absent in CR-42 cores. The CR-48 cores do not contain the limonite-coated fractures which were common in CR-42.

## Schmidt number, specific gravity, porosity, and tensile strength

9. Three specimens from each depth interval were selected for the basic test. Due to the apparent uniform nature of the rock, only the three samples from the middle interval were subjected to all tests. Securits are given below:


warren Siting Area: Core No. 3 (Hole CR-48); Series I Tests

	Sc Rebound Number	hmidt Standard Deviation	Specific Gravity	z Porosity	Tensile Strength, DSI
		Sample A -	30-ft Depth		· · ·
); ; 8 44 877 - 2	57.4 57.3 55.0 55.5	4.91 4.95 <u>3.64</u> 4.50	2.558 2.558 2.654 2.557		1065 1260 <u>1350</u> 1230
		Sample B -	95-ft Depth		
45 45 75 197	59.1 59.3 57.9 58.4	4.25 3.54 <u>4.41</u> 4.10	2.552 2.674 2.552 2.555	0.5 0.0 <u>0.6</u> 0.4	1205 1235 1080 1175
		Sample C -	185-ft Denth		
	54.9 57.9 58.1 57.0	3.21 3.43 4.50 3.71	2.652 2.553 2.555 2.554	-	1295 1125 <u>1185</u> 1200

\*ications are that the CR-48 core is a relatively uniform, moderately

## he ut tests

1). Direct single plane shear tests were conducted on one sample reach of the three depth intervals. Shear strengths of 1310, 1460, 59) psi (average 1450 psi) were obtained on specimens 2c, 7c, and respectively. A posttest photograph of the test specimen is given the 1.

# resided compressive strength tests

**Best Available Copy** 

arren Siting Area: Core No. 3 (Hole CR-48); Series I Tests

Core No.	Depth, ft	Unconfined Compressive Strength, psi
่าก	<sup>2</sup> 27	17,110
2b	<b>2</b> 8	20,170
4b	30	21,310
Avg	29	19,530
5a	9Ŝ	21,300
56 .	95	21,900
7a	. 97	23,000
Avg	95	22,070
'0a	183	24,230
1]a	194	23,030
13b	186	24,810
Avg	185	24,020

Only a slight change of strength is evident with depth, hardly sufficient to be of consequence in a material such as rock.

12. The specimens from the middle depth interval had two vertical and two horizontal electrical resistance strain gages affixed in order to measure strain during testing. Unloading cycles were made at 500.3-1851 intervals up to 15,000 psi. Stress-strain curves are given in plates 2, 3, and 4. The stress-strain relationships were linear almost to failure; hysteresis was negligible. To compute the deformation moduli, a tangent at 50 percent of the altimate strength was constructed as a dashed line on the stress-strain curves. A posttest photograph of the test specimens, plate 5, shows the nature of failure, steep sided coning.

فالملاية والمسالم والمراقب والملمة والملائح والمراقب والمسالمات والمعالمة

Bruchlink

#### Moduli of deformation

13. Young's modulus, shear modulus, bulk modulus, and Poisson's ratio were computed on sample No. 8 by the dynamic (fundamental frequency) method and on the unconfined compressive strength specimens statically at approximately 50 percent of the ultimate strength. Results are given below:

Core No.	Young's Modulus of Elasticity, psi x 10 <sup>5</sup>	Shear Modulus (Mcdulus of Rigidity), psi x 10 <sup>5</sup>	Bulk Modulus, psi x 10 <sup>6</sup>	Poisson's Ratio
	-	Dynamically	•	
8	9.81	4.21	4.95	6.17
		(Continued)		

larren Siting Arca: Core No. 8 (Hole CR-48); Series I Tests

### (Continued)

Core No.	Young's 'lodulus of Elasticity, psi x 10 <sup>5</sup>	Shear Modulus (Modulus of Rigidity), psi x 10 <sup>5</sup>	Bulk Nodulus, Dsi x 10 <sup>6</sup>	Poisson's Ratio
. *		Statically		
. 5a .	9.90	3.93	5.88	0.26
5b	9.80	3.83	7.42	0.28
7a	9.40	3.75	5.27	· C.25

## Velocity measurements

a na harda a bada a bada a bada a bada

14. The compressional wave velocity was determined directly as the sonic propagation velocity on specimen No. 3 to be 18,260 fps. The shear wave velocity was determined from the torsional frequency obtained in the moduli determinations to be 10,885 fps, 60 percent of the compressional velocity.

## Conclusions

15. The CR-48 core is identified as a coarse-b. ined, reddish granite similar to the core from hole CR-42 except that the CR-48 cores contain abundant biotite which was virtually absent in CR-42 cores. The core is relatively uniform with depth, although not as uniform as the core from hole CR-39. Consensus results of physical properties are:

Froperty	Result	
Specific gravity	2.65	
Percent porosity	0.4	
Compressive strength, psi	21.870	
Tensile strength, psi	1,200	
Young's modulus, psi x 10 <sup>6</sup>	9.7	
Compressional wave velocity, fps	18,250	





ÿ

...







以来的特徴性的に

ารัฐปฏณฑีมีให้สามหารถนี้สู่ในมาร่าได้มา มาราช ตรณ์นารที่ได้สามาร

1

4.1

Ì



## APPENDIX J

DATA REPORT - HOLE CR-10 CORES

1. ...

 $\frac{1}{2} \sum_{i=1}^{n} \frac{1}{2} \sum_{i=1}^{n} \frac{1}$ 

23 OCTOBER 1958

### WARREN SITING AREA

#### Core No. 7 (Hole CR-10)

100 C

1. Thirteen pieces of core were received from the Warren area on 7 October 1958, designated CR-10 core. Numbers were assigned as indicated.

Sample	Specimen Designation	Approximate Depth, ft
A	1	28
A	2	29
Ā	3	55
A	4	59
В	5	140
B	5	141
В	7	143 .
В	8	144
С	<b>9</b> .	· 190
С	10	191
С	11	192
С	12	194
C	13	.195

2. The hole from which the core was taken was located in Albany County, Wyoming, township 24N, range 73W, section 14.

arren Siting Area: Core No. 7 (Hole CR-10); Series I Tests

#### Results

## wtrographic examination

lin halangan diser unit manda higu partaagan daha ang mu

3. About 15 ft of NX rock core from three depths in hole CR-10 wre received 7 October 1968 for testing. The petrographic sample is described below:

CD	Serial No.	Piece No.	Depth, ft	Length, ft
SA	150-2 9C-5	8 (top portion)	143	1/3

4. The test procedure was similar to that used for previous samples in this series.

5. The two pieces of core representing depths between 27.9-29.9 ft were white pegmatite like that shown in the central portion of photograph 1. All of the other 11 pieces were more like the top and bottom parts of the core length shown in photograph 1.

5. The piece of core shown in photograph 1 is not a typical length of core, but it does have the advantage of showing the extremes of appearance in one piece of core. The black rock at each end of this piece is typical of nost of the rock in this core. However, alternations in composition and appearance as evidenced by photograph 1 are common in rocks of this type.

7. The core was logged in the field as gneiss, and this is a suitable designation for this rock. Gneiss is the rock name for a metamorphic rock that shows alternating layers of light and dark colored minerals. This was originally an igneous rock, probably a tonalite.

8. The typical black gneiss in this core is composed of quartz, plagioclase feldspar, and biotite with much smaller amounts of emphibole (colorless), microcline, and kaolinite. The plagioclase is albite or pligoclase and is not much altered to clay or sericite.

9. The white pegmatite contains the same minerals as the black reciss but in different amounts. There is less biotite and more quartz and microcline in the white rock than in the black material.

10. All of the rock is medium grained and fairly equigranular with little development of crystal outline by individual grains.



an and a state

行いていたが時代は、日本の国家をある

Photograph 1. Sawed surface of piece 8 (top portion) from core hole CR-10, depth 143 ft, natural size. The dark part of the core is typical of most of the rock in the whole core while the white portion typifies small areas of pegmatite. Ξ.

garren Siting Area: Core No. 7 (Hole CR-10); Series I Tests

## schuldt number, specific gravity, porosity, and tensile strength

11. Three specimens from each depth interval were selected for the basic tests. Results are given below: ፚዸኯጜዸቑዸዸጜ፝ዻ፟ፚዄፙዸኯዸዾዾኯዾኯዸዾፚ፟ፙጜኯዸፚ፝ቚዸ፟ጜ፝ፚኯዸኯኯፚ

AND A SHALL AND

	Sci	haidt			Tensi le
	Rebound	Standard	Specific	- <del>7</del>	Strength,
Core	Number	Deviation	Gravity	Porosity	psi
	•	Sample A -	30-ft Depth		
16	58.9	5.03	2.535	0.0	1290
2a	55.7	4.45	2.533	0.4	1435
2c	*	*	2.527	0.9	*
Avg	57.3	4.74	2.532	0.4	1350
		Sample B -	140-ft Depth		
ба	52.5	3.87	2.753	0.0	850
7a	54.7	3.97	2.724	0.0	1140
95	55.7	4.55	2.712	0.6	1225
Avg	54.6	4.15	2.730	0.2	1070
		Sample C -	195-ft Depth		
19р	.54.8	4.63	2.752	0.4	1160
12c	55.0	3.76	2.722	0.7	975
13c	52.9	4.04	2;744	1.1	800
Avg	54.2	4.14	2.739	0.7	980

\* Specimen too short to test.

12. The light-colored gneiss from the upper elevation is not as dense as the other material, but has a higher rebound number and tensile strength. This may be explained by the foliation in samples from the lower elevations which could be expected to result in lower strength indications.

#### Shear tests

ren har and a state and a state and a state and a state and the state and the state of the

BARNAL AGOLA MANA ANA BARNA

by the state of th

13. Direct single plane shear tests were conducted on three samples of the foliated gneiss. Shear strengths of 1370, 1220, and 1540 psi (average 1370) were obtained on samples fd, 8c, and 12a, respectively. A posttest photograph of the specimens is given in plate 1.

**<sup>2</sup>233** 

Warren Siting Area: Core No. 7 (Hole CR-10); Series I Tests

#### Unconfined compressive strength tests

14. Conventional unconfined compressive strength tests were conducted on specimens from the upper and lower depth intervals and cyclic compressive tests on specimens from the middle depth interval. Results are given below:

		Unconfined
		Compressive
Core No.	Depth, ft	Strength, psi
la	. 28	28,000
lc	28	30,700
2Ъ	29	31,100
Avg	28	29,930
5a	140	15,800
5c	141 °	12,100
8a	144	23,100
Avg	142	17,330
9a	190	12,000
10a	191	14,300
13b	195	13,500
Avg	192	13,270

15. All specimens had two vertical and two horizontal electrical resistance gages affixed in order to monitor strain during loading. Unloading cycles were made at 5000 and 10,000 psi on the cyclic tests. Stress-strain curves are given in plates 2-10. The hysteresis loops were small and closed. A posttest photograph of the test specimens, plate 11, shows the nature of failure, steep sided coning, prevalent in the more solid specimens from the upper elevation. The foliated specimens failed along the bands of dissimilar material in most every case; thus, the lower indicated strengths for the lower elevations.

#### Moduli of deformation

16. Young's modulus, shear modulus, bulk modulus, and Poisson's ratio were computed on three samples by the dynamic (fundamental frequency) method and on the unconfined compressive strength specimens statically at approximately 50 percent of the ultimate strength. Results are given below:

大学の主要な生活の製品なのが、自然のなどのようで、大学の

Marren Siting Area: Core No. 7 (Hole CK-10); Series I Tests

Core -No.	Young's Modulus of Elasticity, psi x 10 <sup>5</sup>	Shear Modulus (Modulus of Rigidity), 	Bulk Nodulus, psix 10 <sup>6</sup>	Poisson's Ratio
		Dynamically		
2	5.87	3.10	2.94	0.11
8	9.88	4.30	4.70	0.15
13	10.08	4.20	5.60	0.20
		Statically		
la	8.80	3.55	4.98	0.20
lc	9.77	3.68	4.72	0.19
2Ъ	8.81	3.54	5.05	0.21
5a	9.33	3.73	5.22	0.25
ĥc	9.37	3,47	10.41	0.35
Sa	10.00	4.07	6.17	0.23
9a	8,57	3.17	9.52	0.35
19a	9.00	3.78	4.34	0.19
135	9.72	3,85	6.75	0.25
Avg S	tatic 9.15	3.57	5.51	0.25

17. The Young's and shear moduli are relatively consistent between the solid and foliated material. However, the Poisson's ratio for the foliated rock (samples 5a through 13b) is quite variable which results in high variability of the bulk modulus.

### "elocity measurements

いたいというというできたが、

u)

19. The compressional wave velocity was determined directly as the sonic propagation velocity; and the shear wave velocity was deterrimed from the torsional frequency obtained in the moduli determinations.

	Compressional	Shear
Core	Velocity,	Velocity,
No.	fps	fps
2	15,590	9,415
8	17,890	10,915
13	18,225	10,835
Avg	17,240	10,390

The shear velocity is approximately 60 percent of the compressional velocity,

Warren Siting Area: Core No. 7 (Hole CR-10); Series I Tests

たいというである

HAN true

## Conclusions

19. The CR-10 core is identified as a gneiss. The light-colored material (here from the upper elevation) is significantly different from the foliated rock. The lower strength of foliated rock is due to the nature of failure--along the bands of dissimilar material.

Property	Light Colored	Foliatco
Specific gravity	2.53	2.73
Percent norosity	0.4	0.4
Comprossive strength DSi	29,930	15,300
Tongilo strength ngi	1,360	1,025
Voungto modulue pei r 10 <sup>5</sup>	8.8	9.3
· Compressional wave velocity, fps	15,590	18,043

ALEXANDER SALES AND ALEXANDER S

Warren Siting Area: Core No. 3 (CR-10); Series II Tests

#### Results

## #instatic compression

20. Hydrostatic compressive tests were conducted on three speciwere one each to pressures of 9000, 18,000, and 36,000 psi. The specimens were prepared in a manner similar to the unconfined compressive were except that the test at 36,000 psi was conducted on a 1.5-in.preter specimen recored from the NX size cores so as to have sufficient will load capacity to fracture the specimens. Some difficulty was rewrienced with the gages on the specimen tested to 36,000 psi. utilizing the results of loading cycles 3 and 4, the bulk modulus, K, we computed from the relation:

$$K = \frac{\sigma}{e_1 + e_2 + e_3}$$

Aste:

のであるとなるというない

and the state of the state of the second second

 $\sigma$  = hydrostatic stress

f1 = vertical strain

 $e_2 = e_3 = horizontal strain$ 

21. Information for the specimens is given below:

ser inen	Maximum Stress, psi	Stress-Strain Curves in Plates	Bulk Modulus K, psi	
15	9,000	12, 13	6.33	
35	18,000	14, 15	7.43	
4	35,000	15, 17	7.22 (nt 18,000 psi)	

Artistic of the strained almost equally in the two mutually perpenderian directions; however, inisotropy is indicated in specimen 5b by a snequal strains measured in the two different directions. However, the total strain in all three directions for the two specimens tested to the balk modulus, i.e., the three mutually perpendicular strains may vary for the bulk modulus, i.e., the three mutually perpendicular strains may vary for the bulk modulus, i.e., they yield a bulk modulus comparable to a for the bulk modulus are in which has strained equally in all directions. The moduli are in trable to those obtained in the Series I tests. Warren Siting Area: Core No. 3 (CR-10); Series II Tests

#### Triaxial compression

のないないのないないない

AND PART DURING MARKED BUILDING

22. Triaxial tests were conducted on the same specimens utilized for the hydrostatic tests at confining pressures equal to the hydrostatic pressures previously applied. Stress-strain curves are given in plates 18, 19, and 20. The maximum deviator stress, Young's modulus, computed as the initial tangent, and Foisson's ratio are given below:

Sp <b>eci</b> men No.	Confining Stress, psi	Deviator Stress, psi	Young's Modulus psi x 10 <sup>6</sup>	Poisson's Ratio
бЪ	9,000	58,000	13.0	0.25
5Ъ	18,000	90,000	12.0	0.23
6đ	35,000	105,000	11.0	0.21

Young's moduli determined on the triaxial tests are apparently somewhat higher than the moduli previously determined on the unconfined tests. Possibly the lateral pressure in the triaxial tests reduces the tendency of the bedding planes to move under load, resulting in less strain and, hence, higher moduli. たちのにかんはちゃ ころがんちゅうひゃちやかちやちち ちょうちょうちょう ちょう

23. The Mohr's circles for all tests are given in plate 21. An initial angle of shearing resistance of approximately 45 deg is indicated. However, the Juliure envelope develops a pronounced curvature above 9000 psi confining pressure and appears to be approaching linearity at 35,000 psi confining pressure. Discretion must be used in interpreting the results of the triaxial test for the CR-10 core. The stratified nature of the rock violates the first requirement for a triaxial test, homogeneity of the test specimen. Therefore, the apparent approaching linearity of the envelope should not be considered the yield limit of the rock in the Von Mises tradition, but probably is a result of the bedding and stratification.

Specimen St	•	Specimen 6b		
Axial Stress, psi	Wave Velocity, fps	Axial Stress, psi	Wave Velocity, fps	
0	17,000	0	18,000	
9,000 (Hydrostatic)	18,570	18,000 (Hydrostatic)	19,500	
20,000	19,000	20,000	20,000	
30,000	21,000	40,000	20,700	
40,000	22,500	50,000	23,400	
50,000	23,700	80,000	25,000	
60,000	24,500	90,000	25,000	

24. The compressional wave velocity was recorded during test to failure of two specimens, 5b and 5b. Equipment malfunction prevented measurements during test of specimen 6d. Results are given below:

#### Warren Siting Area: Core No. 3 (CR-10); Series II Tests

considerable difficulty was experienced in obtaining a valid wave steture, however, indications are that the velocity does change arewhat under success. A posttest photograph of the test specimens is given in plate 22.

## confined compression

25. Confined compression tests were conducted on two specimens, ie and 12b, prepared essentially as the triaxial test specimens. Confining pressure was applied to prevent lateral straining as axial read was applied by the piston. Therefore, a pseudo one-dimensional atate of stress was induced, from which can be computed a constrained ordulus. The axial stress-strain curves are given in plates 23 and 24. The lateral stress required to maintain a condition of no lateral strain is given on the far left of the curves.

25. The constrained modulus, Mr, may be computed from:

$$P_{1}^{\prime} c = \frac{E(1-u)}{(1+u)(1-2u)}$$

shere: '

Ş

のないのないないないないので

E = Young's modulus

u = Poissen's ratio

Sing the average results from the triaxial tests ( $E = 12.0 \times 10^5$  psi: i = 0.23), the constrained modulus is computed to be  $13.9 \times 10^5$  psi. The constrained modulus computed as a tangent at the midpoint of the stress-strain curves for specimens 5e and 12b is approximately  $15.0 \times 10^5$  psi for both specimens. Reasonably good agreement is, therefore, indicated between the theoretical and experimental results. Significantly, the stress-strain curves for this rock are nonlinear at the 30,000 psi lateral pressure level as were those for the soda diorite from the Laramie area. The CR-42 material, however, developed a linear stress-strain relationship at higher lateral pressure.





A result to Survey (Substitution of a survey)

مدامه المستكمان والمالية المالية المالي



. . 化



ころうちょうないなんがって なかなかっ 28,000 2 anta المالية والمحاطية الم 24,000 3 . متامعه الهانا الأليان وا 20,000 16,000 - こう ふんなんし 12,000 STRESS (ps1) 8000 STRESS-SIRAIN CURVE Unconfined Compression CR- 10Core 4000 Specimon 25 31,100 psi 2000 3000 STRAIN (microin./in.) 4000 0 1000 0 ż こうちょうちょう こうちょう ちょうちょうちょう PLATE 4 243



PLATE 5

i



Land design to a later

.



999.43 · ì ., 1::: 1:. . **i:** .: -1 , . **:** 2\* i. 28,000 4 24,000 ::::**:**: 5 ÷ 1.1 11 20,000 κ. . . - Subartante - - -:::1: 16,000 . . the part is a T 12,000 ŕ STRESS ŗ 8000 . :: ιEΤ. いいいい ごうちょう 4000 STRESS-STRAIN CURVE Unconfined Compression CR-10 Core : Specimen 9a 12,000 psi いろう かんちご ふちってんちょう 0 2000 3000 STRAIN (microin./in.) 3000 4000 1000 0 PLATE 8 247

and the second secon





i the second sec

なないたいないないないないないないであるというないないで

こ、ふない、このないないない、ないないないないで、 . . . . بسعيه Same a station

> ---





.

ast and areastiched to a state of the assurement of the second of the second of the second of the second of the

and the second second



•2

### PLATE 13

ŝ

ないていていていました

252

. -.

A Marine



3

7.

?

;

1.

2

a is the second of the second

1111

÷

うちます いたないのないのでのないのです。

.....

. .



Sector Sector

.

÷.,

Ĩ

Shoe Shoell

「ない」で、「ないないない」のないにある」のので、よいない

SUSPICE SUPPORT

D. All Carles

SALAN SALAN



AN ADDITION DESCRIPTION OF A

3

;

NART THE ARTICLES


-5

...

E the second

5.852

123 296

-41. ISS

1. Car 198Bart

· · · · · · · · · ·

小子 人名英格兰人姓氏格尔的变体

1. 1. 1. 1. A.

and the standard





in the second

1

-----

Self-charles of the Million

terroristica verticationstation

• : .:: . . 140 . 1 >ボッキ • 120 1.11.21 -. : 100 121 /21 ÷ Deviator Stress, psi x 1000 QN CR. TAI And interest in 13 80 л? 50 - : VERTICEL 40 . じゅどう TRIAXIAL TEST SPECIMEN-60 こうしょうかんないないできょうかい しょうちょうかん ないないないないないないないない DEPTH 141 46; 0 3 = 36,000 psi 20 106,000 psi 0 8000 0 2000 4000 6000 Strain, microin./in. PLATE 20 259

A Construction of the second state of the seco

のないであるというで、



£.•

ر پر مهمه مارو او در مارونه او میراند. این میروم میرود او در مارونه او در مارونه و او در ای در در داده و مردو ا

1 × 1 × 1 × 1 × 1

PLATE 21

referen herren er an herren herren herren herren herren er herren herren herren herren herren herren herren her

na para pana mangana na kana na kana na kana ka ka ka kana na kana na kana na kana kana kana kana na pana na p

the second star site





• ,

5

27.75 F. 57 F



が行けるがある

.....

•

## APPENDIX K

DATA REPORT - HOLE\_CR-15 CORES

29 OCTOBER 1968

### WARREN SITING AREA

- 1

## Core No. 10 (He le CR-15)

Ξ.

d all

1. Nineteen pieces of core were received from the Warren  $\epsilon$  ea on 11 October 1958, designated CR-15 core. Numbers were assigned as indicated.

-

	Specimen	Approximate
Sample	Designation	Depth, ft
А	. 1	75
Α	2	75
A	3	78
Α	4	80
A	5	93
A	አ	94
A	7	95
В	8	109
В	9	110
В	10	111
С	11	119
С	12	120
С	13	120
С	14	121
С	15	188
С	16	189
С	17	190
С	18	191
С	19	192
		•

2. The hole from which the core was taken was located in Albany County, Wyoming, township 21N, range 72W, section 8.

warren Siting Area: Core No. 10 (Hole CR-15); Series I Tests

### Results

# etrographic examination

「日本のない」としていたが、

14.00

14.14

STOLING TAPLES

1. 1. C.

Contraction of the

したいとうでいたいできょうできょう

3. About 13 ft of NX core from several depths in hole CR-15 was received in October 1968 for testing. The petrographic specimens are initial below:

<u>CU Serial No.</u>	Piece No.	Depth, ft	Length, ft
SAMSO-2 DC-8	2	76	1/4
SAMSO-2 DC-8	9 (top portion)	110	1/3
SAMSO-2 DC-8	17 (top portion)	190	1/3

4. The core sample included banded pegmatitic gneiss as well as ""Hum-grained amphibolite. The distribution in the core samples is them below:

Piece No.	Approximate Length, ft	Rock Type
1-7 11-13	4) 2)	Medium-grained amphibolite
8-10	2	White gneissic pegmatite
14-19	5-1/2	Banded amphibolite and pegmatite

5. The entire core is metamorphic rock. Most of the fracture enfaces appeared to be fresh, but a few were old breaks, partially exered with a thin layer of calcite.

5. The test procedure was generally similar to that followed for "te other samples in this test series. X-ray diffraction patterns of "te dark amphibolite and of the pale gray pegmatitic gneiss were made. "te banded rock was examined on sawed and broken surfaces. Two thin "ctions of amphibolite were examined.

The typical rock of this core is medium-grained amphibolite
\*\*tosed largely of hornblende and plagioclase, with some quartz and
\* 'le chlorite, biotite, yellow iron sulfide, and probably pyroxene.

B. The white gneissic pegmatite in pieces 8-10 is coarser grained
a the amphibolite and consists largely of plagioclase and quartz with
\* little biotite.

9. The material in pieces 14-19 is predominantly amphibolite with "my narrow bands of white gneissic pegmatite.

## Warren Siting Area: Core No. 10 (Hole CR-15); Series 1 Tests

10. Photograph 1 shows the well-developed foliation and the grain size of the amphibolite. Photograph 2 illustrates the appearance of the banded amphibolite gneiss.

### Schmidt number, specific gravity, porosity, tensile strength

11. Three stecimens from each depth interval were selected for the basic tests. Results are given below:

المراجع المراجع

و مارد مارد. مارد مارد مارد

ž

	Sci	miit			Tensile
Core	Rebound	Standard	Specific	3	Strength,
	Number	Deviation	Gravity	Porosity	psi
		Sample A -	S9-ft Depth		
2a	50.7	2.53	3.053	0.0	2260
3b	52.7	3.70	3.078	0.0	2150
7b	54.2	4.17	3.062	0.0	2375
Avg	52.5	3.50	3.064	0.0	2250
		Sample B -	110-ft Depth		
8a	57.0	3.20	2.674	0.0	1070
8c	55.7	5.03	2.704	0.0	1240
10b	59.9	<u>4.02</u>	2.691	<u>0.0</u>	1095
Avg	57.5	4.08	2.690	0.0	1135
		Sample C -	190-ft Depth		
14b	53.2	3.47	2.898	0.0	1795
16b	54.8	4.51	2.965	0.0	2575
18a	53.7	<u>4.42</u>	2.931	<u>0.0</u>	2300
Avg	53.9	4.17	2.931	0.0	2220

12. The light-colored gneiss from the 110-ft depth is substantially different from the darker material. The banded rock from the 110-ft depth apparently represents an average combination of the two extremes. The unusually high indicated tensile strengths from the upper and lower depths should be considered with respect to the nature of the rock. Tested across the bands, as done here, foliated specimens would be expected to give a higher indicated strength than specimens tested along the foliation.





E I

Photograph 1. Sawed surface of piece 2 from core hole CR-15, depth 75 ft, natural size.





Photograph 2. Banded amphibolite gneiss, natural size, from piece 17a.

3 here to be a

Warren Siting Area: Core No. 10 (Hole CR-15); Series I Tests

### Shear tests

3

• 3

1

Sec. asstration and

13. Direct single plane shear tests were conducted on samples of the foliated roc'. Shear strengths of 1140, 1225, and 1285 bsi (average 1215 psi) were obtained on specimens 13a, 15a, and 18b, respectively. The shear strengths are unusually low when compared to the tensile and compressive strengths. However, they are probably representative of the shear strength of the material since the shearing force was applied almost parallel to the foliation. A posttest photograph of the test specimens is given in plate 1.

## Unconfined compressive strength tests

14. Unconfined compressive strength tests were conducted on three specimens each from the three depth intervals. One of each group was a cyclic test. Results are given below:

		Unconfined
		Compressive
Core No.	Depth, ft	Strength, psi
3-	70	37 500
Ja	75	27,500
5a*	93	27,700
7a	95	37,100
Avg	89	30,770
85*	109	27,200
9Ъ	110	23,200
10a	111	37,200
Avg	110	29,200
135*	120	49,700
14c	189	30,900
17Ъ	190	27,100
Avg	155	32,900

<sup>k</sup> Cycled.

15. The difference in material is not perceptible in the compressive strength results; however, the strength is quite variable which could be attributed to the foliated nature of the rock. All specimens had two vertical and two horizontal electrical gages affixed in order to monitor strain during loading. Unloading cycles were made at 5000-psi intervals in to 15,000 psi on the cyclic specimens. Stress-strain curves are given in plates 2-10. The hysteresis loops were small and closed. A posttest photograph of the test specimens, plate 11, shows the nature of failure, steep sided coning.

## Warren Siting Area: Core No. 10 (Hole CR-15); Series I Testa

### Moduli of deformation

15. Young's modulus, shear modulus, bulk modulus, and Poisson ; ratio were computed on three samples by the dynamic (fundamental frequency) method and on the unconfined compressive strength specimens statically at approximately 50 percent of the ultimate strength. Results are given below:

Core No.	Young's Modulus of Elasticity, psi x 10 <sup>5</sup>	Shear Modulus (Modulus of Rigidity), psi x 10 <sup>5</sup>	Bulk Modulus, psi x 10 <sup>6</sup>	Poisson'e Ratio
		Dynamically		
5	15.22	6.50	7.59	0.17
8	*	*	*	*
15	13,52	5.80	5,83	0.17
		<b>Statically</b>		
3a	13.10	5.24	8.73	0.25
5a	15.20	5.98	11.01	0.27
7a	15.00	6.35	11.11	0.24
8ъ	11.20	4.66	6.22	0.20
9Ъ	11.60	4.79	6,65	0.21
10a	12.60	4.88	7.41	0.23
13Ъ	15.30	5.57	10.45	0.24
15c	13.30	5.32	8.87	0.25
175	13.50	5.53	8.04	9,22

s p.

ץ כ-

\* Could not be determined.

17. A cursory examination of the data reveals that the rock from the middle interval, specimens 8b, 9b, and 10a, is slightly more deformation than the other material.

### Velocity measurements

and the second second

18. The compressional wave velocity was determined directly as the sonic propagation velocity, and the shear wave velocity was determined from the torsional frequency obtained in the moduli determinations.

Warren Siting Area: Core No. 10 (Hole CR-15); Series I Tests

States of the second

the attraction and the second second

Core No.	Compressional Velocity, fps	Shear Velocity, <u>fps</u>
5	18,975	12,705
8	15,905	*
15	18,280	12,130

Could not be determined.

The shear velocity is approximately 57 percent of the compressional velocity.

### Conclusions

19. The CR-15 core is identified as an amphibolite. The three samples received from three depth intervals were different in physical properties as indicated below:

Property	Upper	Middle	Lower	
Color	Dark	Light	Banded	
Specific gravity	3,05	2.69	2.93	
Percent porosity	0.0	0.0	0.0	
Compressive strength, psi	30,770	žy,200	32,900	
Tensile strength, psi	2,250	1,135	2,220	
Young's modulus, psi x 10 <sup>5</sup>	14.8	11.5	14.4	
Compressional wave velocity, fps	18,975	15,905	18,280	

સહીતાંકાયકો પંચીહરહી હતેલા મહેલ મેકેલ

-the fold of the burger

No. of Contract -. . . ٠, 34 Postiest Photographs 274 PLATE 1



•





r.



arabisa di kuru du du sa sa karabara karabara da karabara da karabara da karabara karabara karabara karabara k

STRE3S (pat)



.1

í





£.

A Lot Lines

S. Brief Brief

ระสารมีรับวิทย์สารรับสระสารมีระชาตรรฐการเสียง สารมีการสารรับวิทย์สารรับสระชาตรรฐการสาร

the relation

「ころう、そうなんなな

うちょう ちょうちょう ちょうちょう

Υ.





PLATE 10



.

AND DEALAR

-

ž

Posttest Photograph

PLATE 11

Secold States in

2200.0

and the second second

Party of the second second second

.....

APPENDIX L

THERMAL PROPERTY TESTS

11 February 1959

57 - Que

.

1

the state of the s

a shink a shink a further was a shink a

## U. S. ARMY ENGINEER WATERWAYS EXPERIMENT STATION CORPS OF ENGINEERS

AIR MAIL

OFFICE OF THE DIRECTOR VICKSBURG, HISSISSIPPI 39181

HEFER TO WESCO

11 February 1959

S1-

3. 12

£c.

4.

PT Ch

FO:

3.

85

Cop

N. J. S. P. M.

P.

SUBJECT: Thermal Property Tests of Warren Area Cores

Commander Space and Missile Systems Organization ATTN: 1Lt R. G. Tart, Jr. (S:QNF) Norton Air Force Base, California 92409

1. As requested by 1Lt R. G. Tart, Jr. of your office and Mr. M. V. Anthony of TRW, Inc., thermal property tests were conducted on samples of core from four holes in the Warren Siting Area: CR-4, 15, 19, and 35. The thermal diffusivity and specific heat were determined by test, and the thermal conductivity was calculated for each of the samples.

2. The ores were saved to 5-in. lengths and drilled axially with shall diamond drills. An iron-constantan thermocouple coated with waterproof cement was placed at the center of each core and grouted in place. The thermocouple was connected in suries with a similar thermocouple placed in a cooling bath to form a differential thermocouple system which was connected to a potentioneter. The cores were placed in heating baths and brought to equilibrium. At the 120 F equilibrium temperature, readings were taken and the specimen suddenly immersed in a cooling bath of running water at about 50 F. Temperature readings accurate to 0.02 F were taken at various times during the cooling period. The times were noted to within a few thousandths of a minute. The time-temperature cooling curves were then graphed. The thermal diffusivities of the cores were computed from the time-temperature curves by use of the following formula:

$$T/T_0 = C(h^2 t) \times S(h^2 t)$$
  
( $50 g^2$ )  $\times S(h^2 t)$ 

where:

T = temperature difference at time t, F

- T. = initial temperature difference, F
- $h^2 = diffusivity, ft^2/hr$
- R = radius of core, ft

(Continued)

236

CARLON CONTRACTOR

WESCC

Ξ.

2

and the second second states and the second second states and the second s

- \*

88

11 February 1959

----

SUBJECT: Thermal Property Tests of Warren Area Cores

(Continued)

t = time after immersion in cooling bath, min

L = length of specimen, ft

C(X) and S(X) are functions expressing a solution of the diffusion equation for a finite cylinder. Explanation of and values for these functions are given in Heat Conduction, Ingersoll, L. R., Zobel, O. I., and Ingersoll, A. C., pp 183-5, 255, 250, McGraw-Hill Book Co., 1948.

3. The specific heat was determined according to the test mothod CRD-C 124-72 (Incl 1). The thermal conductivity was computed from the relation for concrete given in method CRD-C 44-63 (Incl 2).

4. The results are given in table 1 (Incl 3). Apparently, the thermal properties of all the rock types examined are quite similar with the exception of the rock from hole CR-19 previously identified as soda diorite.

FOR THE DIRECTOR:

3 Incl (quad)

BRYANT MATHER Engineer Chief, Concrete Division

Copies w/incl furnished: M. P. Langley, Aerospace Corp.

- J. Isenberg, AJA
- 5. Schuster, Applied Theory, inc.
- P. Pieper, TEW, Inc.
- M. V. Anthony, TRN, Inc. (dupe)
- P. Gallo, Ken O'Brien & Assoc.

287

#### (Issued 1 Sept. 1962)

#### CRD-C 124-62

#### METHOD OF TEST FOR SPECIFIC HEAT OF AGGREGATES (Method of Mixtures)

### Scope

17572

on dia kaominina dia mampina dia kaominina mpikambana dia kaominina dia kaominina dia kaominina dia kaominina d

1. This method of test covers a procedure for determining the mean specific heat of aggregates by the method of mixtures using particles smaller than 1 in. in size.

Note.- When more precise values are desired and thespecimen may be pulverized or ground to pass a No. 20 sieve the method given in CRD-C242-should be used.

#### App3ratus

2. The apparatus used in this test Procedure shall consist of:

(a) Calorimeter.- A calorimeter of the vacuum-flask type with external insulation, large enough to accommodate samples of approximately 21b in weight placed in a wire basket, and provided with an insulated cover in which are openings for thermometer and stirrer.

(b) Thermometer.- A thermometer graduated to 0.1 F, in the range 32-150 F.

(c) Constant Temperature Bath, Hot.- An electrically heated constant temperature bath with thermostat set at approximately 125 ± 1 F.

(d) Constant Temperature Bath, Cold.- A refrigerated bath, with refrigeration thermostatically controlled at approximately 35 ± 1 F.

(e) Lasket.- A wire-mesh basket, of material of known specific heat, approximately 4 in. in diameter b 4 in. high.

(f) Balance.- A balance capable of weighing 5 lb with an accuracy of ± 0.005 lb.

(g) Standard Specimen. - A specimen of material of known specific heat, with the product of mass times specific heat equal to approximately 0.4 B/lb. (h) Timer.- A timer reading in

minutes and seconds.

#### Specimen

Incl (1 of 2 sheets)

specific heat of aggregates according to the method outlined herein the specimen to be used shall consist of approximately 2 lb of the aggregate to be tested. The specimen shall contain no particles larger than 1 in. in size. When the material to be tested includes larger particles they shall be crushed before testing.

Note.- If a larger calorimeter is used the weight of the specimes may be increased proportionally.

4. (a) Determination of the Water-Equivalent of the Calorimeter.- Approximately 2 lb of water, weighed to the nearest 0.01 lb shall be placed in the calorimeter. The calorimeter shall be placed in the constant temperature room until temperature equilibrium is attained. A weighed standard specimen of known specific heat shall be placed in the wire basket, the basket shall then be suspended by a fine wire in either the hot or the cold constant temperature bath until equilibrium is reached (about 15 minutes). The specimen shall have been weighed previously both dry, and in a dripping condition after immersion. The water carryover shall be treated as described in Paragraph 5 below. The temperature of the constant temperature bath and of the water in the calorimeter shall be recorded to 0.05 F, and the standard sample shall be placed inside the calorimeter. The water in the calorimeter shall be stirred by manually raising and lowering the wire attached to the specimen. This supporting wire shall pass through a minute hole in the cover. Temperatures shall be recorded each minute during the temperature change, and for several minutes after the maximum change has occurred. The time-temperature curveshall then be 3. For determinations of mean plotted as indicated by the example

C 124

-----

والمواجعا والمنافقة والمراقع والمراجع والمراجع

### (Issued 1 Sept. 1962)

### 2 METHOD OF TEST FOR SPECIFIC HEAT OF AGGREGATES (C 124-62)

given in Fig. 1 and the curve shall be extrapolated as described below to correct for the heat lost during the time the measurements were being taken. The line EGF shall be so drawn that the area BFG is equal to the area EGC. The approximate position of line EGF shall be determined by inspection. The line between points E and F gives the maximum temperature change which the specimen would have attained had there been no heat loss from the calorimeter. This temperature change shall be used in the calculations described in Paragraph 5 below.

nennen an ward an antan 1990) fan de de binder om de biege gener fer ten sen te sen en ser an de bieren en en

市合いたう

calculations described in Paragraph 5 below. At least seven determinations shall be made. Hot and cold specimens shall be tested alternately in order to prevent the temperature of the water in the calorimeter from becoming greatly different from the room temperature, so that heat losses will be small or negligible.

#### Calculations

5. The water equivalent of the calorimeter and the mean specific heat of the sample of aggregate shall be calculated from the following formulas:

(a) Water Equivalent .-



#### Fig. 1. Time-temperature history, specific heat determination

(b) Determination of the Mean Specific Heat of Aggregates .- The mean specific heat of an aggregate shall be determined by placing a weighed sample in either the hot or the cold water bath, and proceeding as in sub-paragraph 4(a). The sample shall have been weighed previously both dry, and in a dripping condition immediately after removal from the bath, and the water carry-over shall be treated in accordance with the



where:

- Me = water equivalent of calorimeter, 1Ъ,
- cs = mean specific heat of standard, B/lb-deg F,
- M1 = weight of water placed in calorimeter, 1b,
- $c_1 = mean$  specific heat of water, B/lb-deg F,

Note .- The specific heat of water may be assumed to be 1.000 Btu/ib-deg F without significant error.

- $T_1 = temperature change of water,$ corrected for heat loss, deg F,
  - = weight of sample, lb,
- corrected for heat loss, deg F,
- c = specific heat of basket, B/lb-deg F, and
- $M_{h} = weight of basket, lb.$

(b) Mean Specific Heat, -

$$c_{s} = \frac{(M_{1} + M_{e})c_{1}T_{1} - (M_{o}c_{1} + M_{b}c_{b})T}{M_{s}T}$$

where:

 $c_{s} = mean specific heat of specimen,$ B/lb-deg F, and

the remaining symbols have the same meaning as above.

Incl 1 (2 of 2 sheets)



ſ

### (Issued 1 June 1963)

A STATE OF A STATE OF A

### CRD-C 44-63

#### METHOD FOR CALCULATION OF THERMAL CONDUCTIVITY OF CONCRETE

#### Scope

ร้อยารครั้งกระสุขณร์สุขารครั้งกระสุขารครั้งกระสุขารครั้งกระสุขารครั้งกระสุขารครั้งสุขารครั้งสุขารครั้งกระสุขาร

ward the balance of the second states of the

1. This method is suitable for calculating the thermal conductivity of concrete from results of tests for diffusivity and specific heat.

#### Calculation

2. (a) The thermal conductivity of concrete shall be calculated from the following equation:

#### k = asW

where:

- k = thermal conductivity, Btu/st-hrdeg F,
- $\alpha$  = thermal diffusivity, ft<sup>2</sup>/hr,
- s = specific heat, Btu/lb-deg F,
- W = actual unit weight,  $1b/ft^3$ .

The thermal diffusivity of concrete shall be determined using either Method CRD-C 36 or CRD-C 37. The specific heat of the concrete shall be determined according to the procedure of Method CRD-C 124. The unit weight of concrete shall be determined using the procedures of Method CRD-C 7.

(b) The thermal conductivity of lightweight concrete and similar materials at various moisture contents shall be calculated from the following equation:<sup>1</sup>

<sup>1</sup>Procedure based on paper: "Tests for Thermal Diffusivity of Granular Materials" by William L. Shannon and Winthrop A. Wells, published in *Freecedenge* of the American Society for Testing Materials, Vol 47, 1947. k = aC

÷,

wnere:

- k = thermal conductivity, Btu/ft-hrdeg F,
- $\sigma$  = thermal diffusivity, ft<sup>2</sup>/hr,
- C = volumetric heat capacity, Btu/ft3. deg F.

The thermal diffusivity shall be determined using method of test for thermal diffusivity of lightweight concrete and similar materials. A curve shall be made of diffusivity versus moisture content for the range used. The volumetric heat capacity shall be calculated from the following equation:

$$C = \gamma(c_1 \div \frac{w}{100})$$

where:

- C = volumetric heat capacity, Btu/it<sup>3</sup>deg F,
- $\gamma = dry$  unit weight, 1b/ft<sup>3</sup>,
- c1 = specific heat of dry sample,
- w=moisture content, percent dry weight.

The specific heat of material removed from diffusivity specimen shall be determined according to the procedure of Method CRD-C 242.

### Report '

3. The calculated value for thermal conductivity shall be reported to two decimal places, e.g., k = 1.35Btu/ft hr-deg F.

Incl 2

Nole	Core	Denth	Dencity	Diffneivity	Specific	Cond	uctivity*
No.	No.	ft	1b/ft3	$ft^2/hr$ (1)	BTU/16-F (2)	FPH	$CGS \times 10^3$
CR-4	14	182	167.4	0.053	0.1936	1.72	7.104
CR-15	19	192	179.8	0.049	0.1878	1.65	6.814
CR-19	2	16	176.8	0.032	0.1893	1.07	4.419
CR-35	8	23	166.4	0.051	0.1897	1.61	6.649

## Thermal Properties of Warren Area Cores

TABLE 1

FPH = BTU/(hr)(ft<sup>2</sup>)(deg F per ft); CGS = cal/(sec)(cm<sup>2</sup>)(deg C yer cm).

NOTE: (1) Average of two tests. (2) Average of seven tests.

10.00

2

13

Incl 3

291

## DISTRIBUTION LIST

Address	No. r Copins
Commander Space and Missile Systems Organization ATTN: 11JT R. G. Tart. Jr. (SMOHE)	20
Norton Air Force Base, California 92409	
Mr. N. P. Langley Aerospace Corporation San Bernardino Operations P. O. Box 7308 San Bernardino, California 92402	1
CPT J. L. Bratton Air Force Weapons Laboratory Kirtland Air Force Base, New Mexico 87117	3
Dr. J. Isenberg Agbabian-Jacobsen Associates 8939 South Sepulveda Boulevard Los Angeles, California 90045	1
Mr. S. Schuster Applied Theory, Inc. 1728 Olympic Boulevard Santa Monica, California 90404	1
Mr. F. Pieper TRV, Inc. Norton Air Force Base, California 92409	1
Mr. M. V. Anthony TRW, Inc. Room 710, Building 527 Norton Air Force Base California 62400	1
Mr. Pat Gallo Ken O'Brien and Associates 3745 Long Beach Boulevard	1

292

dista b
CONTRACTOR AND A CONTRACT IN THE PROPERTY OF THE PROPERTY OF	Martin				
		and the star first	and the second of the second		Now along the standard
And Anna Anna Anna					
	• .				
	A	Contra PHE	and the second second second second	a serve discriminant at a similar	
				₩	
•					,
<i>,</i> · · ·					
Unclassified					
Security Classification			والمراجع والتراج والمراجع والمتع		
DOCUMENT CONT	ROL DATA - R	& D			
(Security classification of tills, body of abstract and induzing of 1. ORIGINATING ACTIVITY (Corporate author)	mnetation must be a	20. REPORT SE	CURITY CLASSIFICATION		•
U. S. Army Engineer Waterways Experiment S	tation	Unclass	ified		·
Vicksburg, Mississippi		26. GROUP		-1	
S. REPORT TITLE		]			
TESIS OF ROCK CORES, WARREN STUTES AREA. W	YONTUG				
	10.2.00				, , , , , , , , , , , , , , , , , , ,
4. DESCRIPTIVE NOTES (Type of report and inclusive dates) Final report					
S. AUTHORISS (First name, middle Initial, Jast nome)	····		·-····		
Kenneth L. Saucier					
Donnie L. Ainsworth				1	1
. REPORT DATE	TA. TOTAL NO. O	P PAGES	78. NO. OF REFS		4
March 1969	285		9	1	
SE, CONTRACT OR GRANT NO.	Se. ORIGINATOR	REPORT NUM	ER(\$)	-1	4
A PROJECT NO.	Miscellar		eous Paper C-67-3		1
e.	Db. OTHER REPORT HOIS (Any suber numbers that may be scalgred		-1		
	]			1	
TO DISTRIBUTION STATEMENT	L				i și
Each transmittal of this document outside	the Departme	nt of Defe	nse must have prior	1	4
approval of the Space and Missile Systems	Organization	(SMQHF-2)	•		
1. 1. B	1		·		
II. PUPPLEMENTART NOTES	12. SPONSORING MILITARY ACTIVITY II S Air Forge Sugge and Migeile Systems			k i	

20.0.00

1. N. - 3.26 A.

	U. S. Air Force Space and Missile Systems Organization, Air Force Systems Command
IL ABITRACT	

Laboratory tests were conducted on rock core samples received from ten core holes drilled in the Laramie range, Wyoming, to determine the integrity and mechanical be-havior of the materials. The results were to be used to determine the usefulness of the Warren Siting Area for potential missile sites. Series I tests (relative hardness specific gravity, compressive strength, somic velocity, etc.) indicated the materials to be relatively uniform, competent gramite, diorite, and gneiss rock. Series II tests (triaxial, hydrostatic, and confined compression) indicated the rock to be rather incompressible and brittle up to 36,000-psi triaxial stress. Series III tests indicated that the granite and diorite had Hugoniot elastic limits of 50 kilobars or more and the gneiss approximately 20 kilobars. In order to better define the physical and mechanical behavior of the rock, triaxial tests to approximately 150,000 psi on intact and jointed specimens and equation of state tests at pressures to approximately 600 kilobars should be conducted.

DD, 1473 SELASTE Para 4 1478. 1 293

A CONTRACTOR OF THE

CONTRACTOR OF THE OWNER OWNE OWNER OWNER OWNER

or share the second second to superint and the second second second second second second second second second s

and the second and a second second

Security Classification	n							
f.	KEV #0408		LIN	K A	LIN	K 8	LIN	ĸc
Pook cores			ROLE	<u> </u>	7.01 1	WT	ROLE	
Rock properties							1	
Rock proper ties			1					
Nock vesus Verron Siting Area 1	tirm		1			1		
Marien Steing Area, 1	KyU.							
						l i		
					ļ			
			}					
								Į
				•				ĺ
			1					
•					1			
							1	
							İ	
							{	
								]
							l	
							ł	
	ويتواجز كوالجواب كالأكور بوجابها			The second second		in succession of		
		SOF		TING		انته		
	A Rock cores Rock properties Rock tests Warren Siting Area, 1	Rock cores Rock properties Rock tests Warren Siting Area, Wyo.	<pre>kev toons Rock cores Rock properties Rock tests Warren Siting Area, Wyo.</pre>	A KET 10-00 CONSTRUCTION ROLE Rock cores Rock tests Warren Siting Area, Wyo.	KEY ED"DA     KEY ED"DA	LINK A         LINK A         LINK A           Rock cores         Rock groperties         Rock tests         NT         Four A           Rock tests         Warren Siting Area, Wyo.         Image: State A         Image: State A	HEV ICTOR     LINK A     LINK B       Rock cores     Rock properties     Rock tests     I     I     I     I       Rock tests     I     I     I     I     I     I       Warren Siting Area, Wyo.     I     I     I     I     I	LIMK #     LIMK #     LIMK #     LIMK #       Rock cores     Rock properties     Rock tests     Warren Siting Area, Wyo.     I

936

2000 - 100 -

2

ر الم مالية

. .

4 4 st.

and the second second

the state of the second

and the second of the the second of the second s

Sec. A

and state at the state of the second state of the second state of the second state of the second second second