

AD-756 412

INVESTIGATION OF UNDERSEEPAGE AND ITS  
CONTROL, LOWER MISSISSIPPI RIVER LEVEES.  
APPENDIX E: ANALYSIS OF 1961 PIEZOMETRIC  
DATA

Army Engineer Waterways Experiment Station  
Vicksburg, Mississippi

May 1964

DISTRIBUTED BY:


**NTIS**

National Technical Information Service  
U. S. DEPARTMENT OF COMMERCE  
5285 Port Royal Road, Springfield Va. 22151

AD 756412

# INVESTIGATION OF UNDERSEEPAGE AND ITS CONTROL, LOWER MISSISSIPPI RIVER LEVEES

APPENDIX E: ANALYSIS OF 1961 PIEZOMETRIC DATA



TECHNICAL MEMORANDUM NO. 3-424

May 1964

NATIONAL TECHNICAL  
INFORMATION SERVICE

This document has been approved  
for public release and sale; its  
distribution is unlimited.

Prepared for

The President, Mississippi River Commission

by

U. S. Army Engineer Waterways Experiment Station  
CORPS OF ENGINEERS  
Vicksburg, Mississippi

62 R

# INVESTIGATION OF UNDERSEEPAGE AND ITS CONTROL, LOWER MISSISSIPPI RIVER LEVEES

## APPENDIX E: ANALYSIS OF 1961 PIEZOMETRIC DATA



TECHNICAL MEMORANDUM NO. 3-524

May 1963

Prepared for

The President, Mississippi River Commission

by

U. S. Army Engineer Waterways Experiment Station  
CORPS OF ENGINEERS

Vicksburg, Mississippi

ARMY-MRC VICKSBURG, MISS

I

## Preface

In September 1940 the Mississippi River Commission initiated a general study of the phenomena of underseepage and its control along Lower Mississippi River levees. The study was prompted by the occurrence of heavy underseepage and sand boils along numerous reaches of these levees during the 1937 flood. The results of this investigation, which utilized the combined efforts of the Memphis, Vicksburg, and New Orleans Districts and the U. S. Army Engineer Waterways Experiment Station (WES), are contained in WES TM No. 3-424, Investigation of Underseepage and Its Control, Lower Mississippi River Levees, October 1956. Appendices A through D, describing studies related to the problem of underseepage, were bound with the report.

This report, Appendix E, contains an analysis and summary of piezometric data obtained during the 1961 high water. The relatively high river stage which occurred in 1961 provided an opportunity for checking the previous high-water analysis and determining whether any significant changes in seepage boundary conditions had occurred since that time. The study reported herein was authorized by the Mississippi River Commission in 1st indorsement dated 16 June 1961 to WES letter dated 1 June 1961, subject "Status of Soils Division Projects for MRC and LMWD for FY 1961 and Request for Funds for Projects for FY 1962."

The piezometric data obtained during the 1961 high-water period were furnished by the Memphis, Vicksburg, and New Orleans Districts. The analysis of data contained herein was made by Messrs. W. C. Sherman and C. C. Trahan, and the report was prepared by Mr. Trahan under the

general direction of Messrs. W. J. Turnbull, W. G. Shockley, J. R. Compton, and W. C. Sherman, Soils Division, WES.

Director of the WES during the course of this investigation was Colonel Alex G. Sutton, Jr., CE, and Technical Director was Mr. J. B. Tiffany.

## Contents

	<u>Page</u>
Preface . . . . .	iii
Introduction . . . . .	E1
Description of Piezometer System . . . . .	E2
1961 Piezometer Data . . . . .	E2
Method of Analysis . . . . .	E4
Analysis of Data from Piezometer Sites . . . . .	E8
Caruthersville, Mo. . . . .	E8
Gannon, Ark. . . . .	E8
Commerce, Miss. . . . .	E10
Trotters 51, Miss. . . . .	E11
Trotters 54, Miss. . . . .	E11
Stovall, Miss. . . . .	E13
Farrell, Miss. . . . .	E14
Upper Francis, Miss. . . . .	E15
Lower Francis, Miss. . . . .	E16
Bolivar, Miss. . . . .	E16
Bataw, Miss. . . . .	E17
L'Argent, La. . . . .	E18
Hole-in-the-Wall, La. . . . .	E19
Kelson, La. . . . .	E19
Baton Rouge, La. . . . .	E20
Conclusions and Recommendations . . . . .	E21
Conclusions . . . . .	E21
Recommendations . . . . .	E22
<b>TABLES</b>	<b>23 - 55</b>

### List of Tables

<u>Table</u>	<u>Title</u>
E1	Piezometers Functioning Improperly or Submerged During 1961 High Water
E2	Summary of 1950 and 1961 High-Water Data at Piezometer Sites
E3	Comparison Between Elevations of Project Flood Flow Line in Main Report and Present (1956) Project Flood Flow Line for Lower Mississippi River Levees

### List of Illustrations

<u>Figure</u>	<u>Title</u>	<u>Page</u>
E1	Alluvial Valley of the Lower Mississippi River and locations of piezometer installations . . . . .	E3
E2	Nomenclature for determination of $s$ and $x_3$ from piezometer readings . . . . .	E6
E3	Distance to effective seepage source and exit, Caruthersville, Mo. . . . .	E9
E4	Distance to effective seepage source and exit, Garnon, Ark. . . . .	E9
E5	Distance to effective seepage source and exit, Commerce, Miss. . . . .	E10
E6	Distance to effective seepage source and exit, Trotters 51, Miss. . . . .	E11
E7	Distance to effective seepage source, Trotters 54, Miss.	E12
E8	Distance to effective seepage source and exit, Stovall, Miss. . . . .	E13
E9	Distance to effective seepage source and exit, Parrell, Miss. . . . .	E14
E10	Distance to effective seepage source and exit, Upper Francis, Miss. . . . .	E15
E11	Distance to effective seepage source and exit, Lower Francis, Miss. . . . .	E16
E12	Distance to effective seepage source and exit, Bolivar, Miss. . . . .	E17
E13	Distance to effective seepage source and exit, Eutaw, Miss. . . . .	E18
E14	Distance to effective seepage source and exit, Hole-in-the-Wall, La. . . . .	E19
E15	Distance to effective seepage source and exit, Kelson, La. . . . .	E20
E16	Distance to effective seepage source and exit, Baton Rouge, La. . . . .	E21

### List of Plates

<u>Plate</u>	<u>Title</u>
E1	Piezometer Observations, 1961, Caruthersville, Mo.
E2	Hydraulic Grade Lines, 1961, Caruthersville, Mo.
E3	Piezometer Observations, 1961, Garnon, Ark.
E4	Hydraulic Grade Line, 1961, Garnon, Ark.
E5	Piezometer Observations, 1961, Commerce, Miss.
E6	Hydraulic Grade Line, 1961, Commerce, Miss.
E7	Piezometer Observations, 1961, Trotters 51, Miss.
E8	Hydraulic Grade Line, 1961, Trotters 51, Miss.
E9	Piezometer Observations, 1961, Trotters 54, Miss.
E10	Hydraulic Grade Line, 1961, Trotters 54, Miss.

List of Plates (Continued)

<u>Plate</u>	<u>Title</u>
E11	Piezometer Observations, 1961, Stovall, Miss.
E12	Hydraulic Grade Line, 1961, Stovall, Miss.
E13	Piezometer Observations, 1961, Farrell, Miss.
E14	Hydraulic Grade Line, 1961, Farrell, Miss.
E15	Piezometer Observations, 1961, Upper Francis, Miss.
E16	Hydraulic Grade Lines, 1961, Upper Francis, Miss.
E17	Piezometer Observations, 1961, Lower Francis, Miss.
E18	Hydraulic Grade Lines, 1961, Lower Francis, Miss.
E19	Piezometer Observations, 1961, Bolivar, Miss.
E20	Hydraulic Grade Line, 1961, Bolivar, Miss.
E21	Piezometer Observations, 1961, Eutaw, Miss.
E22	Hydraulic Grade Line, 1961, Eutaw, Miss.
E23	Piezometer Observations, 1961, L'Argent, La.
E24	Hydraulic Grade Line, 1961, L'Argent, La.
E25	Piezometer Observations, 1961, Hole-in-the-Wall, La.
E26	Hydraulic Grade Lines, 1961, Hole-in-the-Wall, La.
E27	Piezometer Observations, 1961, Kelson, La.
E28	Hydraulic Grade Line, 1961, Kelson, La.
E29	Piezometer Observations, 1961, Baton Rouge, La.
E30	Hydraulic Grade Line, Baton Rouge, La.



INVESTIGATION OF UNDERSEEPAGE AND ITS CONTROL  
LOWER MISSISSIPPI RIVER LEVEES

APPENDIX B: ANALYSIS OF 1961 PIEZOMETRIC DATA

Introduction

1. In 1940 the Mississippi River Commission initiated a comprehensive study of underseepage and its control along the Lower Mississippi River levees. The purpose of this study was to provide data on the relation of soil conditions, geologic features, and underseepage and to improve methods for analyzing subsurface seepage. The results of this investigation are contained in W2S TM No. 3-424, Investigation of Underseepage and Its Control, Lower Mississippi River Levees, October 1956. One phase of the investigation consisted of installation of piezometers at selected sites along the Lower Mississippi River to obtain data on the development of substratum hydrostatic pressures, and distances from the levee to the effective source of seepage entry. Analysis of piezometric data was based primarily on the 1950 high-water data.

2. It was recommended in the above-mentioned study that the piezometer systems be maintained and observed during periods of significant high water, and that the data be analyzed as they became available. The project flood stage at most of the sites is considerably higher than the river stages experienced since installation of the piezometers; therefore, valuable information is still to be gained at higher river stages. Since completion of the referenced study, a relatively high water occurred in 1961 which provided an opportunity for checking the previous high-water analysis and determining whether any significant changes in the seepage boundary conditions had occurred since that time.

3. During the 1961 high water, the Mississippi River reached a maximum stage of the same order of magnitude as that recorded during the 1950 high water, resulting in leads ranging from 6 to 14 ft on the levees at the piezometer sites. As the 1961 high water was only the second major high water that had occurred at a majority of the sites since the piezometers were installed, it was considered that data obtained during this

high water would provide a check on the analysis made of the 1950 high water. This appendix presents the analysis of the piezometer data obtained during the 1961 high water and a comparison with the 1950 high-water analysis.

#### Description of Piezometer System

4. Installation of piezometers was initiated in 1943 and completed in 1948. The sites of the piezometer systems are shown in fig. E1 and are as follows:

<u>Memphis District</u>	<u>Vicksburg District</u>	<u>New Orleans District</u>
Caruthersville, Mo.	Upper Francis, Miss.	Kelson, La.
Gannon, Ark.	Lower Francis, Miss.	Baton Rouge, La.
Commerce, Miss.	Bolivar, Miss.	Cotton Bayou, La.
Trotters 51, Miss.	Eutaw, Miss.	
Trotters 54, Miss.	L'Argent, La.	
Stovall, Miss.	Hole-in-the-Wall, La.	
Farrell, Miss.		

All of the above-listed piezometer sites are located along the Mississippi River with the exception of Cotton Bayou, La., which is located on the Red River.

5. Piezometer data were obtained from four of the above-listed sites during the 1943 high water. During the 1950 high water, when the Mississippi River reached its highest stage since the piezometers were installed, fairly complete piezometer readings were obtained at all of the sites. Analyses of data obtained in the 1943 and 1950 high water are given in TM No. 3-424.

#### 1961 Piezometer Data

6. During the 1961 high water, piezometer readings were obtained at all of the piezometer sites except Cotton Bayou, La., where the head acting on the levee was relatively low. Readings from selected piezometers and concurrent river stages at each of the sites are plotted on odd-numbered plates E1 through E29. At Upper Francis, Lower Francis, Bolivar, and Eutaw, Miss., only two sets of readings were taken; one set




Fig. E1. Alluvial Valley of the Lower Mississippi River and locations of piezometer installations

was taken at about the crest of the high water, and one set about a week after the river crest. Readings at L'Argent and Hole-in-the-Wall, La., were taken about a week before the crest of the high water and again at about the crest. At all other sites, piezometer readings were taken at periodic intervals during the rise and fall of the river stage.

7. At each piezometer site, the principal piezometer line, perpendicular to the center line of the levee, was selected for analysis. The principal lines are identical with those selected for the analysis of the 1950 high-water data. The piezometer readings and hydraulic grade line for the condition of maximum river stage at each of these piezometer lines are shown in even-numbered plates E2 through E30.\* Piezometric data for other lines used in the initial analysis are also shown in some instances. At several of the piezometer sites, piezometers along the line selected for analysis were sluggish, indicated low readings as compared to other adjacent piezometers, or were completely inoperative. At Caruthersville, Mo., Stovall, Miss., and Hole-in-the Wall, La., the risers of piezometers located on the riverside of the levee were submerged during the 1961 high water. Those piezometers along the lines selected for analysis which were considered to be functioning improperly and those which were submerged during the 1961 high water are listed in table E1. It is recommended that in the near future the faulty piezometers be renovated or replaced, and the risers of those piezometers which were submerged in the 1961 high water be extended so that the piezometers can be read during the next major high water. Readings of the above-mentioned piezometers would greatly facilitate analyzing the data obtained during the next major high water.

#### Method of Analysis

8. When a levee is subjected to a differential hydrostatic head as a result of river stages being higher than the adjacent land, seepage enters the pervious substratum through the bed of the river, riverside borrow pits, and/or the riverside topstratum. The resulting artesian head

---

\* Legend for the generalized stratification shown in these plates is shown only in plate E2.


and hydraulic gradient in the sand stratum beneath the levee cause flow beneath and landward of the levee. The principal purposes of the piezometer installations along the Lower Mississippi River are to determine the hydraulic gradients beneath the levee and the distances to the effective source of seepage entry and exit during high-water periods. The effective source of seepage entry into the pervious stratum is defined as that vertical plane riverward of the levee where a hypothetical open seepage entry face, fully penetrating the pervious aquifer, with an impervious surface blanket between this plane and the levee, would produce the same flow and hydrostatic pressure beneath and landward of the levee as occur under the actual conditions riverward of the levee. It may also be defined as the vertical line through the point where the hydraulic grade line intersects the river stage elevation. The effective seepage exit is defined as that vertical plane landward of the levee where a hypothetical open drain face, with an impervious blanket between this plane and the landside levee toe, would result in the same hydrostatic pressure at the levee toe and the same amount of seepage passing beneath the levee as occur under actual conditions. It can also be defined as the intersection of the hydraulic grade line with the ground surface or tailwater elevation.

9. Analysis of the 1961 high-water data consisted primarily of determining the hydraulic grade line in the substratum sand, and the distance from the landside levee toe to the effective source of seepage entry and the effective seepage exit as the principal piezometer line of each site. The hydraulic grade line at the crest of the 1961 high water is plotted for the principal piezometer line of each site (for example, see plate E2). The distances from the landside toe of the levee (or berm) to the effective source of seepage ( $s$ ), and the effective seepage exit ( $x_3$ ) were determined from piezometers located beneath the levee, and berm (if present), using the following equations (see fig. E2 for nomenclature):

$$s = \ell_1 + \frac{H - h_1}{M} \quad (1)$$

$$x_3 = \frac{h_1}{M} - \ell_1 \quad (2)$$

where  $M$  is the slope of the hydraulic grade line. Where there were three or four piezometers beneath the levee, values of  $s$  and  $x_3$  were



### Notation

- $s$  = distance from landside toe of levee (or berm) to effective source of seepage entry  
 $x_1$  = effective length of blanket riverside of levee  
 $x_3$  = distance from landside toe of levee (or berm) to effective seepage exit  
 $L_2$  = base width of levee, and berm if present  
 $H$  = total net head on levee  
 $h_1, h_2$  = piezometric heads at two piezometers on a line perpendicular to the levee at distances  $l_1$  and  $l_2$ , respectively, from landside toe of levee  
 $M$  = slope of hydraulic grade line beneath levee  

$$= \frac{h_2 - h_1}{l_2 - l_1}$$

Fig. E2. Nomenclature for determination of  $s$  and  $x_3$  from piezometer readings

determined graphically. In the analysis of data for the 1950 high water, values of  $s$  and  $x_3$  were determined on selected days for rising river stages during the high-water period; these values were plotted versus river stage as shown in fig. E3 for piezometers at the Caruthersville site. From similar plots for each site, values of  $s$  and  $x_3$  were

extrapolated to project flood.\* The extrapolation of  $x_3$  to project flood was obtained by solving the following equation from the main report, using the conditions which were estimated to exist at project flood:

$$h_o = H \left( \frac{x_3}{s + x_3} \right) \quad (3)$$

where  $h_o$  is the excess head at the landside toe of the levee. The values of  $s$  and  $x_3$  extrapolated to project flood are shown in table E2, together with similar values determined for the 1950 and 1961 high water. The 1950 values of  $s$  and  $x_3$  shown in table E2 are the intersections of the curves of best fit through the data points and the maximum 1950 river stage. Values shown for 1961 are those determined for the maximum 1961 river stage. Also shown in table E2 are the net head on the levee  $H$ , and excess head at the landside toe of the levee (or berm)  $h_o$  for project flood, and for the 1950 and 1961 high waters. The values of  $H$  were considered to be the difference between the river stage and the average ground surface or tailwater elevation on the landside of the levee. Values of  $h_o$  are actual excess heads measured by piezometers near the landside toe of the levee or berm.

10. At several of the piezometer sites, the tailwater elevation behind the levee was not recorded when the piezometers were read. Without a record of tailwater, an accurate computation of effective seepage exit ( $x_3$ ) and excess head at the toe of the levee ( $h_o$ ) could not be made at these sites. It is recommended that during the next major high water the elevation of the tailwater (water in ditches behind the levee) be recorded at the same time that piezometers are read.

11. At all piezometer sites, the net head on the levee during the 1950 high water was higher than the head observed during the 1961 high water. The difference between the maximum net heads for the 1950 and 1961 high waters varied from 0.4 ft at Eutaw, Miss., to 7.1 ft at Kelson, La. No indications of excessive seepage or sand boils were reported for the

---

\* Project flood stages referred to in this report are those existing prior to 1956. A list of these stages for each piezometer site together with the current (1963) project flood stages adapted in 1956 is shown in table E3.

1961 high water. A discussion of the 1961 high-water data and a comparison of 1961 and 1950 high-water data at each piezometer site are presented in the following paragraphs.

#### Analysis of Data from Piezometer Sites

##### Caruthersville, Mo.

12. At piezometer line A, which is representative of conditions at Caruthersville, Mo., the maximum net head on the levee (H) during the 1961 high water was 8.9 ft compared to 9.4 ft in 1950. The hydraulic grade line for the maximum 1961 river stage is shown in plate E2. Also shown in this plate are piezometric data at line C and along the toe of the berm (line D). The 1961 data indicated that piezometer 4 was sluggish as compared with piezometers 5 and 6 (see plate E1), and the riser of piezometer 3 was submerged during the crest of the 1961 high water; therefore, only piezometers 5 and 6 were used to determine  $s$  and  $x_3$  at line A. Insufficient data precluded determination of the hydraulic grade line at line C.

13. The effective seepage entrance for the crest of the 1961 high water at line A was indicated to be 1100 ft from the landside toe of the levee, or just riverward of the abandoned riverside levee (see plate E2). In 1950 the computed source of seepage was 560 ft from the landside toe of the levee, or at about the deepest part of the riverside borrow pit. It is possible that since 1950 silting has occurred in the bottom of the riverside borrow pit, resulting in an increase in the distance to the effective seepage entrance ( $s$ ). The value of  $x_3$  computed for the 1961 high water was 480 ft, or about twice the value determined in 1950 (see fig. E3). The net head at the toe of the levee ( $h_o$ ) in 1961 (1.8 ft) was about the same as that observed in 1950 (2.0 ft).

##### Gammon, Ark.

14. At Gammon, Ark., line C was selected for determinations of  $s$  and  $x_3$  for the 1961 high water. The hydraulic grade line at line C for the crest of the 1961 high water is shown in plate E4. Values of  $s$  and  $x_3$  were determined graphically using data from piezometers C-3, -4, and -5 (see plate E3 for piezometer data). As seen in table






Fig. E3. Distance to effective seepage source and exit, Caruthersville, Mo.

E2 and fig. E4, the 1961 values of  $s$  and  $x_3$  were in good agreement with those values determined in 1950, indicating that conditions at Gammon, Ark., have not changed since the 1950 high water. The net head on the levee ( $H$ ) observed during the crest of the 1961 high water was 10.1 ft, as compared to an  $H$  of 11.9 ft observed in 1950. The head at the landside toe of the levee ( $h_0$ ) was slightly less in 1961 than the head observed




Fig. E4. Distance to effective seepage source and exit, Gammon, Ark.

during the 1950 high water (see table E2). The head at the toe ( $h_o$ ) in percent net head ( $H$ ) was about the same in 1961 as in 1950.

Commerce, Miss.

15. Piezometer line H was selected as representative of conditions at Commerce, Miss. As in previous high waters, piezometric data at Commerce indicated that the piezometric heads measured by piezometers with tips at greater depths in the sand aquifer were significantly greater than the head just beneath the topstratum (see plate E6). Values of  $s$  and  $x_3$  for the 1961 high water were determined graphically using data from piezometers H-14Y, -11Z, and -7Y located at middepth of the aquifer (see fig. E5 for piezometer data). As seen in table E2 and fig. E5, the distance to the effective seepage entrance in 1961 was about 400 ft less than that determined during the 1950 high water. This decrease in distance may have resulted from erosion of the bottom of the riverside borrow pit since 1950.




Fig. E5. Distance to effective seepage source and exit, Commerce, Miss.

16. At the crest of the 1961 high water, the net head on the levee at line H was 8.0 ft, as compared to a maximum net head of 9.2 ft observed in 1950. In 1961 the maximum head at the toe ( $h_c$ ) was 2.2 ft, the same as that observed in 1950. In general, the piezometric heads observed landside of the levee in 1961 were about the same as those observed in 1950. In 1961 the average tailwater just landside of the levee was at

about elevation 197.0, or about 0.5 ft less than the tailwater observed in 1950. This slight difference in tailwater resulted in a greater value of  $x_3$  computed for 1961 as compared to  $x_3$  computed for the 1950 high water (see fig. E5).

Trotters 51, Miss.

17. Line H was selected for determining  $s$  and  $x_3$ . The hydraulic grade line at line H is shown in plate E8. As seen in this plate, the reading of piezometer 2-X was low as compared to adjacent piezometers. Piezometric data shown in plate E7 indicated that the piezometer was sluggish; therefore, values of  $s$  and  $x_3$  were determined from piezometers 5-X and 4-X. As seen in fig. E6, the 1961 values of  $s$  and  $x_3$  are considerably less than similar values determined from the 1950 data. It is considered that the decrease in  $s$  may be the result of changes in conditions of the riverside borrow pits. The net head on the levee during the 1961 high water was 6.4 ft, as compared to 9.0 ft observed in 1950. At the crest of the 1961 high water,  $h_0$  was 1.2 ft as compared to 3.0 ft in 1950.




Fig. E6. Distance to effective seepage source and exit, Trotters 51, Miss.

Trotters 54, Miss.

18. The 1961 high-water data at Trotters 54, Miss., were previously analyzed and the results reported in WES TM 3-341, Control of Underseepage by Relief Wells, Trotters, Mississippi; Appendix G: Analysis of 1961 Well

Flow and Piezometric Data, July 1962. In the analysis of the data, values of  $s$  were computed for rising river stages at the three piezometer lines (lines M, R, and Q) perpendicular to the levee. The 1961 piezometer observations at Trotters are shown in plate E9; hydraulic grade lines for various river stages at line M are shown in plate E10. The average values of  $s$  for the three piezometer lines are plotted vs river stage in fig. E7, together with similar data for previous high-water periods. In




Fig. E7. Distance to effective seepage source, Trotters 54, Miss.

1961,  $s$  decreased with increasing river stages, but at a much slower rate than for previous high waters. The 1961 data indicated that  $s$  probably would not be less than the value of 900 ft selected for design of the well system.

19. The maximum net head on the levee ( $H$ ) observed in 1961 was 12.9 ft as compared to 13.8 ft observed in 1950. In 1950, piezometers were read when the relief well system was opened and when it was closed; in 1961 the wells remained open during the entire high water. The computed values of  $x_3$  and observed  $h_0$  in 1961 were therefore smaller than those values obtained with wells closed in the 1950 high water (see table E2). The ratio of  $h_0/H$  was 11 percent in 1961 as compared to 22 percent in 1950.

#### Stovall, Miss.

20. At Stovall, Miss., line B was selected for determining  $s$  and  $x_3$ . Data from selected piezometers at Stovall are shown in plate E11; the hydraulic grade line at line B for the 1961 high water is shown in plate E12. During the 1961 high water the readings of piezometer E-13 were lower than readings of adjacent piezometers and the riser of piezometer E-12 was clogged. Values of  $s$  and  $x_3$  were determined from readings of piezometers E-11 and -15. As shown in fig. E8 and table E2, values of  $s$  and  $x_3$  determined in 1961 were in good agreement with those values determined for the 1950 high water, indicating that conditions at




Fig. E8. Distance to effective seepage source and exit, Stovall, Miss.

Stovall have not changed appreciably since the 1950 high water. The maximum net head on the levee ( $H$ ) observed at line B in 1961 was 14.3 ft, as compared to a maximum net head of 14.9 ft observed in 1950. The observed excess head at the toe of the berm ( $h_0$ ) in 1961 (5.6 ft) was only slightly less than the head observed in 1950 (6.0 ft).

Farrell, Miss.

21. At Farrell, Miss., only one piezometer line (line A) was installed perpendicular to the levee. At line A, piezometers were installed immediately below the topstratum and also just below a clay seam about 25 ft below ground surface (see plate E14). In the analysis of 1950 high-water data, the sand stratum above the clay seam was designated the "upper aquifer," and the sand stratum below the clay seam was designated the "lower aquifer." The maximum net head on the levee in 1961 was 3.4 ft, which was one-half the maximum net head observed in 1950. Data from selected piezometers at Farrell are shown in plate E13. During the 1961 high water, the piezometers just below the topstratum were dry, indicating that no seepage occurred in the upper aquifer. The hydraulic grade line indicated by piezometers in the lower aquifer is shown in plate E14. The value of  $s$  computed from this grade line was 970 ft (see fig. E9). As seen in fig. E9, the latter value was in good agreement with the value of  $s$  (860 ft) computed for the 1950 high water. In 1961 the hydraulic grade line intersected the average ground




Fig. E9. Distance to effective seepage source and exit, Farrell, Miss.

surface at about the landside berm toe, indicating a value of zero for  $x_3$ . This would verify the trend observed during the 1950 high water (see plot of  $x_3$  vs river stage, fig. E9).

#### Upper Francis, Miss.

22. Piezometer line B was considered typical of conditions at Upper Francis, Miss. The hydraulic grade line at the maximum 1961 river stage at line B is shown in plate E16. As seen in this plate, piezometer B-1 indicated a low reading and was probably not functioning properly. Values of  $s$  and  $x_3$  were determined graphically from piezometers B-2, -3, and -4 (see plate E15 for piezometer data). As seen in fig. E10, the 1961 values of  $s$  were in good agreement with values obtained for the 1950 high water. During the 1961 high water, there was no excess head at the toe of the levee where the ground surface is at about elevation 161; however, piezometer data indicate that excess head of from 1 to 2 ft did exist landward of the levee where the ground surface is below elevation 160. In the analysis of the 1950 high water, values of  $x_3$  were computed on the assumption that the average ground surface landward of the levee was at elevation 160. Using this same assumption, a value of 50 ft was computed for  $x_3$  for the maximum 1961 river stage. Although this value is very small, it verifies the trend of increasing values of  $x_3$  with rising river stages observed for the 1950 high water (see plot of  $x_3$  vs river stage in fig. E10).




Fig. E10. Distance to effective seepage source and exit, Upper Francis, Miss.

### Lower Francis, Miss.

23. Line C was selected for determining values of  $s$  and  $x_3$  for Lower Francis, Miss. The hydraulic grade line at the crest of the 1961 high water at line C is shown in plate E18. Also shown is the hydraulic grade line at line E and the piezometric head along the levee toe (line H). The maximum net head on the levee in 1961 was 9.6 ft as compared to a net head of 13.6 observed in 1950. The excess head at the toe of the berm as measured by piezometer C-7 in 1961 was 1.5 ft as compared to an excess head of 1.7 ft observed in 1950. Values of  $s$  and  $x_3$  were computed for the 1961 data using piezometers C-4 and -6 (see plate E17 for piezometer data). As seen in fig. E11, the 1961 values of  $s$  and  $x_3$  were in good agreement with values determined in 1950, indicating that seepage conditions at Upper Francis have not changed since 1950.

### Bolivar, Miss.

24. Piezometer line D was considered representative of conditions at Bolivar, Miss. The hydraulic grade line at line D for the maximum 1961 river stage is shown in plate E20. The tip of piezometer D-1 was apparently clogged, and values of  $s$  and  $x_3$  were determined using data from piezometers D-2 and -3 (see plate E19 for piezometer data). The value of  $s$  in 1961 as shown in fig. E12 is in good agreement with values determined for the 1950 high water. At Bolivar, there are borrow pits directly behind the landside toe of the levee. During the 1961 high water, the water




Fig. E11. Distance to effective seepage source and exit, Lower Francis, Miss.





agreement with values computed for the 1950 high water. As the water level in the borrow pits behind the landside toe of the levee berm was not recorded during the 1961 high water, an accurate estimate of  $x_3$  could not be determined for the 1961 high-water data. In the analysis of the 1950 high-water data it was assumed that the average ground surface and tailwater landside of the levee were at elevation 135. Based on this same assumption, the maximum net head on the levee in 1961 was 5.8 ft as compared to 6.2 ft observed in 1950;  $h_o$  in 1961 was 2.0 ft as compared to 6.0 ft in 1950, and the computed  $x_3$  in 1961 was 260 ft. The latter value is considerably less than  $x_3$  values for the 1950 high water (see fig. E13).




Fig. E13. Distance to effective seepage source and exit, Eutaw, Miss.

#### L'Argent, La.

27. Only one piezometer line, line B, was installed perpendicular to the levee. Piezometer observations at line B, as shown in plate E23, were insufficient to establish an accurate hydraulic grade line. Further, as shown in plate E24, readings of piezometers B-1 and -3 were evidently in error. Piezometer B-1 indicated a reading at the same elevation as the river stage; this would mean, if correct, seepage entrance at the river-side toe of the levee. Piezometer B-3 indicated a piezometric head greater than the head at the toe of the levee. Because of the erratic data at L'Argent,  $s$  and  $x_3$  were not computed. It is recommended that all

piezometers along line B be flushed and pumped before the next high water.  
Hole-in-the-Wall, La.

28. Piezometer line B was considered representative of conditions at Hole-in-the-Wall, La. The hydraulic grade line at line B is shown in plate E26. At line B the risers of piezometers B-1 and -2 were submerged during the crest of the 1961 high water; therefore, only piezometers B-3, -4, -5, and -6 were used to determine the source of seepage entrance (see plate E25 for piezometer data). The values of  $s$  computed in 1961 were considerably greater than the values computed for the 1950 high water (see fig. E14). At the crest of the 1961 high water, the net head on the levee was only 5.4 ft. As seen in plate E26, no excess head developed landward of the levee during the 1961 high water, and therefore it is considered that artesian flow did not exist. Consequently, the values of  $s$  determined for 1961 probably are unreliable.




Fig. E14. Distance to effective seepage source and exit,  
 Hole-in-the-Wall, La.

Kelson, La.

29. At Kelson, La., a line of piezometers (line B) was installed beneath the levee to determine the hydrostatic pressures in the sandy silt stratum directly beneath the levee. The silty sand stratum is underlain by a thick stratum of clay and a stratum of silt, which in turn is underlain by pervious sand. The hydraulic grade line in the silty sand

stratum at the crest of the 1961 flood is shown in plate E28. From the piezometer data shown in plate E27, it appears that piezometer A-1 was not functioning properly and values of  $s$  were determined from piezometers A-2, -3, and -4. The value of  $s$  computed for 1961 is 240 ft, which agrees well with the values computed for the 1950 high water (see fig. E15) indicating that seepage continues to enter the silt stratum in the bottom of the borrow pit adjacent to the levee. There was no excess head landward of the levee during the 1961 high water; therefore, there is no value of  $x_3$  shown in fig. E15.




Fig. E15. Distance to effective seepage source and exit, Kelson, La.

#### Baton Rouge, La.

30. Piezometer line C was considered representative of conditions at Baton Rouge, La. The hydraulic grade line at the crest of the 1961 high water is shown in plate E30. The 1961 data indicated a very flat hydraulic grade line, as did the 1950 data. Values of  $s$  and  $x_3$  were determined graphically from the readings of piezometers P-21B, P-21C, P-45, and P-24 (see plate E29 for piezometer data). The 1961 value of  $s$  was considerably higher than the  $s$  computed for the 1950 high water at the same river stage. However, because of the flat hydraulic grade line the computed values of  $s$  for 1961 may not be accurate. The 1961 value of  $x_3$  was in good agreement with

values of  $x_3$  computed for the 1950 high water, as shown in fig. E16.




Fig. E16. Distance to effective seepage source and exit, Baton Rouge, La.

### Conclusions and Recommendations

#### Conclusions

31. The following conclusions are based on the data and studies presented in this report:
- The 1961 high water, which was the second major high water to have occurred at the majority of the piezometer sites since the piezometers were installed resulted in net heads on the levee only slightly lower than those produced in the 1950 high water. The difference between the maximum net heads for the 1950 and 1961 high waters varied from 0.4 ft at Eutaw, Miss., to 7.1 ft at Kelson, La. No indications of excessive seepage or sand boils were reported for the 1961 high water.
  - With some exceptions, the distances to the effective source of seepage entry ( $s$ ) in 1961 were generally in the same order of magnitude as those determined in 1950. At Caruthersville the distance increased by a factor of about 2, and at Baton Rouge the distance increased by a factor of 3; however, because of the flat hydraulic grade line at the latter site, the value of  $s$  computed for the 1961 high water may not be accurate. At Hole-in-the-Wall the value of  $s$  increased by a factor of 1.7; however, as a truly artesian flow did not exist beneath the levee in 1961, the value of  $s$  determined for 1961 was probably unreliable. At Commerce and Trotters 51 substantial reductions in the value of  $s$  were

noted and these reductions are probably due to increased scour in riverside borrow pits.

- c. Except at a few sites, the distances to the effective exit computed for the 1961 high water did not agree closely with values computed for the 1950 high-water data. The lack of agreement is attributed to faulty piezometers, uncertain tailwater elevations, and variations inherent in procedural technique which, as pointed out in the main report, may result in errors of as much as 20 percent.
- d. The maximum excess hydrostatic head at the toe of the levee or berm in 1961, expressed as a percentage of the net head acting on the levee, was generally about equal to or less than that observed in 1950.

#### Recommendations

32. It is recommended that:

- a. The existing piezometer systems be maintained and observed during significant high waters and the data analyzed as they become available.
- b. Faulty piezometers listed in table E1 be renovated or replaced and the risers of those piezometers which were submerged in the 1961 high water be extended so that the piezometers can be read during the next major high water.
- c. During the next major high water, the elevation of the tailwater (water in ditches behind the levee) be recorded at the same time that piezometers are read.

Table E1

Piezometers Functioning Improperly or Submerged During 1961 High Water

<u>Site</u>	<u>Piezometers Functioning Improperly</u>	<u>Piezometers with Risers Flooded</u>
Caruthersville, Mo.	4	3
Trotters 51, Miss.	H-2X	--
Stovall, Miss.	E-12, E-13	D-10
Upper Francis, Miss.	B-1	--
Bolivar, Miss.	D-1	--
Hole-in-the-Wall, La.	--	B-1, B-2
Kelson, La.	A-1	--

Table E2

Summary of 1950 and 1961 High-Water Data at Piezometer Sites

Site	Station	Line	H, ft		u, ft		x <sub>3</sub> , ft		h <sub>o</sub> , ft		h <sub>o</sub> /H %					
			Project Flood	1950	1961	Project Flood	1950	1961	Project Flood	1950	1961	1950	1961			
Caruthersville	26/0+00	A	19.2	9.4	8.9	480	560	1100	200	240	480	3.2	2.0	1.8	21	21
Gannon	138/26+00	C	25.2	11.9	10.1	980	980	1120	500	700	720	3.3	3.3	2.7	28	27
Commerce	23/10+75	H	22.7	9.2	8.0	1350	1500	1090	880	1,000	1,340	3.2	2.2	2.2	25	27
Trotters 51	52/22+00	H	23.7	9.0	6.4	900	1100	710	650	735	170	6.0	3.0	1.2	33	19
Trotters 54	54/14+05	M	27.7	13.8	12.9	950	1050	925	650	770	---	3.0	3.0	1.4*	22	11*
Stovall	77/38+00	B	29.8	14.9	14.3	800	800	675	750	800	870	9.8	6.0	5.6	44	39
Farrell	81/24+00	A**	24.1	6.8	3.4	550	580	--	120	140	---	2.4	2.4	---	28	--
Upper Francis	39+00	B	24.1	6.8	3.4	800	860	970	1,000	1,050	0	17.5	6.2	0	72	0
Lower Francis	130+00	C	25.0	8.3	5.8	1500	1520	1640	2,000	1,400	50	15.3	1.5	0	21	0
Belivar	2199+75	D	28.6	13.6	9.0	950	1010	935	200	250	320	3.8	1.7	1.5	13	17
Eutaw	2860+00	D	26.2	6.5	6.0	550	650	675	250	365	185	4.2	2.4	1.3	37	22
			28.1	6.2	5.8	1500	1600	1650	900	1,050	260	11.0	6.0	2.7	65	35
L'Argent	3542+33	B	31.0	16.4	13.4	3000	3150	††	4,200	3,000	††	14.9	14.9	††	35	--
Hole-in-the-Wall	3618+95	D	23.5	9.4	5.4	1150	1150	1900	120	0	0	1.9	1.2	0	13	0
Kelson	2700+71	B	21.7	16.7	9.6	250	250	240	20	50	0	8.9	4.6	0	28	0
Baton Rouge	94+42	C	23.0	17.4	11.6	800	800	2450	11,200	11,200	11,000	15.2	12.4	8.4	73	72

\* With relief wells on 50-ft centers flowing.

\*\* Upper aquifer

† Lower aquifer.

†† Insufficient data for computations.



Table E3

Comparison Between Elevations of Project Flood Flow Line  
in Main Report and Present (1956) Project Flood Flow  
Line for Lower Mississippi River Levees

<u>Piezometer Site</u>	<u>Station</u>	<u>Project Flood, El*</u>	
		<u>Prior to</u> <u>1956**</u>	<u>1956</u>
Caruthersville, Mo.	26/0+00	(287.2)	(283.8)
Gammon, Ark.	138/26+00	(244.2)	(342.5)
Commerce, Miss.	23/1C+75	(220.2)	(218.9)
Trotters 51, Miss.	52/22+00	(208.7)	(206.4)
Trotters 54, Miss.	54/1+05	(207.7)	(206.1)
Stovall, Miss.	77/38+00	(194.3)	(190.7)
Farrell, Miss.	81/24+00	(192.1)	(137.1)
Upper Francis, Miss.	39+00	185.0	182.2
Lower Francis, Miss.	130+00	182.6	181.3
Bolivar, Miss.	2199+75	167.2	163.7
Eutaw, Miss.	2860+00	161.1	157.6
L'Argent, La.	3542+33	90.0	86.6
Hole-in-the-Wall, La.	3618+95	89.5	86.1
Kelson, La.	2700+71	53.7	50.6
Baton Rouge, La.	94+42	48.0	45.2

\* Elevations in parentheses are in ft mgl; all other elevations are in ft msl.

\*\* Shown in main report.










PLATE E1













DATE	WELL	WATER LEVEL (FEET MSL)
10 MAY	W-1	218.5
10 MAY	W-2	218.5
10 MAY	W-3	218.5
10 MAY	W-4	218.5
10 MAY	W-5	218.5
10 MAY	W-6	218.5
10 MAY	W-7	218.5
10 MAY	W-8	218.5
10 MAY	W-9	218.5
10 MAY	W-10	218.5
10 MAY	W-11	218.5
10 MAY	W-12	218.5
10 MAY	W-13	218.5
10 MAY	W-14	218.5
10 MAY	W-15	218.5
10 MAY	W-16	218.5
10 MAY	W-17	218.5
10 MAY	W-18	218.5
10 MAY	W-19	218.5
10 MAY	W-20	218.5
10 MAY	W-21	218.5
10 MAY	W-22	218.5
10 MAY	W-23	218.5
10 MAY	W-24	218.5
10 MAY	W-25	218.5
10 MAY	W-26	218.5
10 MAY	W-27	218.5
10 MAY	W-28	218.5
10 MAY	W-29	218.5
10 MAY	W-30	218.5
10 MAY	W-31	218.5
10 MAY	W-32	218.5
10 MAY	W-33	218.5
10 MAY	W-34	218.5
10 MAY	W-35	218.5
10 MAY	W-36	218.5
10 MAY	W-37	218.5
10 MAY	W-38	218.5
10 MAY	W-39	218.5
10 MAY	W-40	218.5
10 MAY	W-41	218.5
10 MAY	W-42	218.5
10 MAY	W-43	218.5
10 MAY	W-44	218.5
10 MAY	W-45	218.5
10 MAY	W-46	218.5
10 MAY	W-47	218.5
10 MAY	W-48	218.5
10 MAY	W-49	218.5
10 MAY	W-50	218.5
10 MAY	W-51	218.5
10 MAY	W-52	218.5
10 MAY	W-53	218.5
10 MAY	W-54	218.5
10 MAY	W-55	218.5
10 MAY	W-56	218.5
10 MAY	W-57	218.5
10 MAY	W-58	218.5
10 MAY	W-59	218.5
10 MAY	W-60	218.5
10 MAY	W-61	218.5
10 MAY	W-62	218.5
10 MAY	W-63	218.5
10 MAY	W-64	218.5
10 MAY	W-65	218.5
10 MAY	W-66	218.5
10 MAY	W-67	218.5
10 MAY	W-68	218.5
10 MAY	W-69	218.5
10 MAY	W-70	218.5
10 MAY	W-71	218.5
10 MAY	W-72	218.5
10 MAY	W-73	218.5
10 MAY	W-74	218.5
10 MAY	W-75	218.5
10 MAY	W-76	218.5
10 MAY	W-77	218.5
10 MAY	W-78	218.5
10 MAY	W-79	218.5
10 MAY	W-80	218.5
10 MAY	W-81	218.5
10 MAY	W-82	218.5
10 MAY	W-83	218.5
10 MAY	W-84	218.5
10 MAY	W-85	218.5
10 MAY	W-86	218.5
10 MAY	W-87	218.5
10 MAY	W-88	218.5
10 MAY	W-89	218.5
10 MAY	W-90	218.5
10 MAY	W-91	218.5
10 MAY	W-92	218.5
10 MAY	W-93	218.5
10 MAY	W-94	218.5
10 MAY	W-95	218.5
10 MAY	W-96	218.5
10 MAY	W-97	218.5
10 MAY	W-98	218.5
10 MAY	W-99	218.5
10 MAY	W-100	218.5

PIEZOMETER OBSERVATIONS, 1961  
GAMMON, ARK.











PIEZOMETER OBSERVATIONS, 1961  
COMMERCE, MISS.

100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000







PIEZOMETER OBSERVATIONS, 1961  
TROTTERS 51, MISS.

0.0 0.1 0.2 0.3 0.4 0.5 0.6 0.7 0.8 0.9 1.0 1.1 1.2 1.3 1.4 1.5 1.6 1.7 1.8 1.9 2.0 2.1 2.2 2.3 2.4 2.5 2.6 2.7 2.8 2.9 3.0 3.1 3.2 3.3 3.4 3.5 3.6 3.7 3.8 3.9 4.0 4.1 4.2 4.3 4.4 4.5 4.6 4.7 4.8 4.9 5.0 5.1 5.2 5.3 5.4 5.5 5.6 5.7 5.8 5.9 6.0 6.1 6.2 6.3 6.4 6.5 6.6 6.7 6.8 6.9 7.0 7.1 7.2 7.3 7.4 7.5 7.6 7.7 7.8 7.9 8.0 8.1 8.2 8.3 8.4 8.5 8.6 8.7 8.8 8.9 9.0 9.1 9.2 9.3 9.4 9.5 9.6 9.7 9.8 9.9 10.0







HYDRAULIC GRADE LINE, 1961  
TROTTERS 51, MISS.




NOTE. M-3-X DESTROYED, M-4-W READS SAME AS M-5-W,  
M-12 READS SAME AS M-14



NOTE. 6, 7, AND 8 READ SAME AS M-6-X.







NOTE. PIEZOMETERS 4 AND 5 READ SAME AS M-15.




PIEZOMETER OBSERVATIONS, 1961  
TROTTERS 54, MISS.







DATE	CONCENTRATION	DATE	CONCENTRATION	DATE	CONCENTRATION	DATE	CONCENTRATION
MAY 15	100.0	MAY 25	100.0	MAY 15	100.0	MAY 25	100.0
MAY 16	100.0	MAY 26	100.0	MAY 16	100.0	MAY 26	100.0
MAY 17	100.0	MAY 27	100.0	MAY 17	100.0	MAY 27	100.0
MAY 18	100.0	MAY 28	100.0	MAY 18	100.0	MAY 28	100.0
MAY 19	100.0	MAY 29	100.0	MAY 19	100.0	MAY 29	100.0
MAY 20	100.0	MAY 30	100.0	MAY 20	100.0	MAY 30	100.0

PIEZOMETER OBSERVATIONS, 1961  
STOVALL, MISS.






HYDRAULIC GRADE LINE, 1961  
STOVALL, MISS.



DATE	TIME
A-1	17.7
B-2	16.4
B-3	18.0
B-7	17.5
B-9	17.8
D-9	16.1
B-10	17.9
B-4	16.4
B-6	16.2
B-11	17.2
D-12	16.4
E-13	16.6

PIEZOMETER OBSERVATIONS, 1961  
FARRELL, MISS.









PIEZ	GR E.	PIEZ	GR E.
A-1	162.5	B-7	156.9
B-1	153.5	B-8	156.1
B-2	163.0	C-2	160.6
B-3	170.9	C-3	160.6
B-4	161.4	C-4	161.3
B-5	160.4	C-5	157.9
B-6	158.4	C-6	157.9

PIEZOMETER OBSERVATIONS, 1961  
UPPER FRANCIS, MISS.










HYDRAULIC GRADE LINES, 1961  
UPPER FRANCIS, MISS.



PIEZ	ON E <sub>1</sub>	PIEZ	ON E <sub>2</sub>
A-1	154.3	C-8	154.3
B-1	154.3	C-9	153.8
C-1	154.3	C-10	153.4
C-2	154.3	C-11	153.5
C-3	154.3	C-12	153.8
C-4	154.3	C-13	154.6
C-5	154.3	C-14	152.2
C-6	154.3	C-15	154.3


PIEZOMETER OBSERVATIONS, 1961  
LOWER FRANCIS, MISS.








DATE	TIME	WATER	PIEZO
5/20	10:30	145.5	145.5
5/21	10:30	145.5	145.5
5/22	10:30	145.5	145.5
5/23	10:30	145.5	145.5
5/24	10:30	145.5	145.5
5/25	10:30	145.5	145.5
5/26	10:30	145.5	145.5
5/27	10:30	145.5	145.5
5/28	10:30	145.5	145.5
5/29	10:30	145.5	145.5
5/30	10:30	145.5	145.5
5/31	10:30	145.5	145.5
6/1	10:30	145.5	145.5
6/2	10:30	145.5	145.5
6/3	10:30	145.5	145.5
6/4	10:30	145.5	145.5
6/5	10:30	145.5	145.5

PIEZOMETER OBSERVATIONS, 1961  
BOLIVAR, MISS.















PIEZ	ORIG
A-1	13.5
B-1	67.6
B-2	40.6
B-3	56.3
B-4	44.5
B-5	44.5
C-1	63.3
C-2	44.7
C-3	44.6



PIEZOMETER OBSERVATIONS, 1961  
L'ARGENT, LA.










DATE	LINE A	LINE B	LINE C	LINE D
5/20	60.8	60.8	60.8	60.8
5/21	60.9	60.9	60.9	60.9
5/22	61.0	61.0	61.0	61.0
5/23	61.1	61.1	61.1	61.1
5/24	61.2	61.2	61.2	61.2
5/25	61.3	61.3	61.3	61.3
5/26	61.4	61.4	61.4	61.4
5/27	61.5	61.5	61.5	61.5
5/28	61.6	61.6	61.6	61.6
5/29	61.7	61.7	61.7	61.7
5/30	61.8	61.8	61.8	61.8
5/31	61.9	61.9	61.9	61.9
6/1	62.0	62.0	62.0	62.0
6/2	62.1	62.1	62.1	62.1
6/3	62.2	62.2	62.2	62.2
6/4	62.3	62.3	62.3	62.3
6/5	62.4	62.4	62.4	62.4





PIEZOMETER OBSERVATIONS, 1961  
HOLE-IN-THE-WALL, LA.



HYDRAULIC GRADE LINES, 1961  
HOLE-IN-THE-WALL, LA.







PIEZOMETER OBSERVATIONS, 1961				
BATON ROUGE, LA.				
PIEZOMETER	DATE	TIME	HEAD (ft)	REMARKS
P-1	MAY 15	0800	10.5	
P-1	MAY 15	1200	10.8	
P-1	MAY 15	1600	11.2	
P-1	MAY 15	2000	11.5	
P-1	MAY 16	0400	11.8	
P-1	MAY 16	0800	12.2	
P-1	MAY 16	1200	12.5	
P-1	MAY 16	1600	12.8	
P-1	MAY 16	2000	13.2	
P-1	MAY 17	0400	13.5	
P-1	MAY 17	0800	13.8	
P-1	MAY 17	1200	14.2	
P-1	MAY 17	1600	14.5	
P-1	MAY 17	2000	14.8	
P-1	MAY 18	0400	15.2	
P-1	MAY 18	0800	15.5	
P-1	MAY 18	1200	15.8	
P-1	MAY 18	1600	16.2	
P-1	MAY 18	2000	16.5	
P-1	MAY 19	0400	16.8	
P-1	MAY 19	0800	17.2	
P-1	MAY 19	1200	17.5	
P-1	MAY 19	1600	17.8	
P-1	MAY 19	2000	18.2	
P-1	MAY 20	0400	18.5	
P-1	MAY 20	0800	18.8	
P-1	MAY 20	1200	19.2	
P-1	MAY 20	1600	19.5	
P-1	MAY 20	2000	19.8	
P-1	MAY 21	0400	20.2	
P-1	MAY 21	0800	20.5	
P-1	MAY 21	1200	20.8	
P-1	MAY 21	1600	21.2	
P-1	MAY 21	2000	21.5	
P-1	MAY 22	0400	21.8	
P-1	MAY 22	0800	22.2	
P-1	MAY 22	1200	22.5	
P-1	MAY 22	1600	22.8	
P-1	MAY 22	2000	23.2	
P-1	MAY 23	0400	23.5	
P-1	MAY 23	0800	23.8	
P-1	MAY 23	1200	24.2	
P-1	MAY 23	1600	24.5	
P-1	MAY 23	2000	24.8	
P-1	MAY 24	0400	25.2	
P-1	MAY 24	0800	25.5	
P-1	MAY 24	1200	25.8	
P-1	MAY 24	1600	26.2	
P-1	MAY 24	2000	26.5	
P-1	MAY 25	0400	26.8	
P-1	MAY 25	0800	27.2	
P-1	MAY 25	1200	27.5	
P-1	MAY 25	1600	27.8	
P-1	MAY 25	2000	28.2	
P-1	MAY 26	0400	28.5	
P-1	MAY 26	0800	28.8	
P-1	MAY 26	1200	29.2	
P-1	MAY 26	1600	29.5	
P-1	MAY 26	2000	29.8	
P-1	MAY 27	0400	30.2	
P-1	MAY 27	0800	30.5	
P-1	MAY 27	1200	30.8	
P-1	MAY 27	1600	31.2	
P-1	MAY 27	2000	31.5	
P-1	MAY 28	0400	31.8	
P-1	MAY 28	0800	32.2	
P-1	MAY 28	1200	32.5	
P-1	MAY 28	1600	32.8	
P-1	MAY 28	2000	33.2	
P-1	MAY 29	0400	33.5	
P-1	MAY 29	0800	33.8	
P-1	MAY 29	1200	34.2	
P-1	MAY 29	1600	34.5	
P-1	MAY 29	2000	34.8	
P-1	MAY 30	0400	35.2	
P-1	MAY 30	0800	35.5	
P-1	MAY 30	1200	35.8	
P-1	MAY 30	1600	36.2	
P-1	MAY 30	2000	36.5	
P-1	MAY 31	0400	36.8	
P-1	MAY 31	0800	37.2	
P-1	MAY 31	1200	37.5	
P-1	MAY 31	1600	37.8	
P-1	MAY 31	2000	38.2	
P-1	JUN 1	0400	38.5	
P-1	JUN 1	0800	38.8	
P-1	JUN 1	1200	39.2	
P-1	JUN 1	1600	39.5	
P-1	JUN 1	2000	39.8	
P-1	JUN 2	0400	40.2	
P-1	JUN 2	0800	40.5	
P-1	JUN 2	1200	40.8	
P-1	JUN 2	1600	41.2	
P-1	JUN 2	2000	41.5	
P-1	JUN 3	0400	41.8	
P-1	JUN 3	0800	42.2	
P-1	JUN 3	1200	42.5	
P-1	JUN 3	1600	42.8	
P-1	JUN 3	2000	43.2	
P-1	JUN 4	0400	43.5	
P-1	JUN 4	0800	43.8	
P-1	JUN 4	1200	44.2	
P-1	JUN 4	1600	44.5	
P-1	JUN 4	2000	44.8	
P-1	JUN 5	0400	45.2	
P-1	JUN 5	0800	45.5	
P-1	JUN 5	1200	45.8	
P-1	JUN 5	1600	46.2	
P-1	JUN 5	2000	46.5	
P-1	JUN 6	0400	46.8	
P-1	JUN 6	0800	47.2	
P-1	JUN 6	1200	47.5	
P-1	JUN 6	1600	47.8	
P-1	JUN 6	2000	48.2	
P-1	JUN 7	0400	48.5	
P-1	JUN 7	0800	48.8	
P-1	JUN 7	1200	49.2	
P-1	JUN 7	1600	49.5	
P-1	JUN 7	2000	49.8	
P-1	JUN 8	0400	50.2	
P-1	JUN 8	0800	50.5	
P-1	JUN 8	1200	50.8	
P-1	JUN 8	1600	51.2	
P-1	JUN 8	2000	51.5	
P-1	JUN 9	0400	51.8	
P-1	JUN 9	0800	52.2	
P-1	JUN 9	1200	52.5	
P-1	JUN 9	1600	52.8	
P-1	JUN 9	2000	53.2	
P-1	JUN 10	0400	53.5	
P-1	JUN 10	0800	53.8	
P-1	JUN 10	1200	54.2	
P-1	JUN 10	1600	54.5	
P-1	JUN 10	2000	54.8	
P-1	JUN 11	0400	55.2	
P-1	JUN 11	0800	55.5	
P-1	JUN 11	1200	55.8	
P-1	JUN 11	1600	56.2	
P-1	JUN 11	2000	56.5	
P-1	JUN 12	0400	56.8	
P-1	JUN 12	0800	57.2	
P-1	JUN 12	1200	57.5	
P-1	JUN 12	1600	57.8	
P-1	JUN 12	2000	58.2	
P-1	JUN 13	0400	58.5	
P-1	JUN 13	0800	58.8	
P-1	JUN 13	1200	59.2	
P-1	JUN 13	1600	59.5	
P-1	JUN 13	2000	59.8	
P-1	JUN 14	0400	60.2	
P-1	JUN 14	0800	60.5	
P-1	JUN 14	1200	60.8	
P-1	JUN 14	1600	61.2	
P-1	JUN 14	2000	61.5	
P-1	JUN 15	0400	61.8	
P-1	JUN 15	0800	62.2	
P-1	JUN 15	1200	62.5	
P-1	JUN 15	1600	62.8	
P-1	JUN 15	2000	63.2	
P-1	JUN 16	0400	63.5	
P-1	JUN 16	0800	63.8	
P-1	JUN 16	1200	64.2	
P-1	JUN 16	1600	64.5	
P-1	JUN 16	2000	64.8	
P-1	JUN 17	0400	65.2	
P-1	JUN 17	0800	65.5	
P-1	JUN 17	1200	65.8	
P-1	JUN 17	1600	66.2	
P-1	JUN 17	2000	66.5	
P-1	JUN 18	0400	66.8	
P-1	JUN 18	0800	67.2	
P-1	JUN 18	1200	67.5	
P-1	JUN 18	1600	67.8	
P-1	JUN 18	2000	68.2	
P-1	JUN 19	0400	68.5	
P-1	JUN 19	0800	68.8	
P-1	JUN 19	1200	69.2	
P-1	JUN 19	1600	69.5	
P-1	JUN 19	2000	69.8	
P-1	JUN 20	0400	70.2	
P-1	JUN 20	0800	70.5	
P-1	JUN 20	1200	70.8	
P-1	JUN 20	1600	71.2	
P-1	JUN 20	2000	71.5	
P-1	JUN 21	0400	71.8	
P-1	JUN 21	0800	72.2	
P-1	JUN 21	1200	72.5	
P-1	JUN 21	1600	72.8	
P-1	JUN 21	2000	73.2	
P-1	JUN 22	0400	73.5	
P-1	JUN 22	0800	73.8	
P-1	JUN 22	1200	74.2	
P-1	JUN 22	1600	74.5	
P-1	JUN 22	2000	74.8	
P-1	JUN 23	0400	75.2	
P-1	JUN 23	0800	75.5	
P-1	JUN 23	1200	75.8	
P-1	JUN 23	1600	76.2	
P-1	JUN 23	2000	76.5	
P-1	JUN 24	0400	76.8	
P-1	JUN 24	0800	77.2	
P-1	JUN 24	1200	77.5	
P-1	JUN 24	1600	77.8	
P-1	JUN 24	2000	78.2	
P-1	JUN 25	0400	78.5	
P-1	JUN 25	0800	78.8	
P-1	JUN 25	1200	79.2	
P-1	JUN 25	1600	79.5	
P-1	JUN 25	2000	79.8	
P-1	JUN 26	0400	80.2	
P-1	JUN 26	0800	80.5	
P-1	JUN 26	1200	80.8	
P-1	JUN 26	1600	81.2	
P-1	JUN 26	2000	81.5	
P-1	JUN 27	0400	81.8	
P-1	JUN 27	0800	82.2	
P-1	JUN 27	1200	82.5	
P-1	JUN 27	1600	82.8	
P-1	JUN 27	2000	83.2	
P-1	JUN 28	0400	83.5	
P-1	JUN 28	0800	83.8	
P-1	JUN 28	1200	84.2	
P-1	JUN 28	1600	84.5	
P-1	JUN 28	2000	84.8	
P-1	JUN 29	0400	85.2	
P-1	JUN 29	0800	85.5	
P-1	JUN 29	1200	85.8	
P-1	JUN 29	1600	86.2	
P-1	JUN 29	2000	86.5	
P-1	JUN 30	0400	86.8	
P-1	JUN 30	0800	87.2	
P-1	JUN 30	1200	87.5	
P-1	JUN 30	1600	87.8	
P-1	JUN 30	2000	88.2	
P-1	JUN 31	0400	88.5	
P-1	JUN 31	0800	88.8	
P-1	JUN 31	1200	89.2	
P-1	JUN 31	1600	89.5	
P-1	JUN 31	2000	89.8	
P-1	JUL 1	0400	90.2	
P-1	JUL 1	0800	90.5	
P-1	JUL 1	1200	90.8	
P-1	JUL 1	1600	91.2	
P-1	JUL 1	2000	91.5	
P-1	JUL 2	0400	91.8	
P-1	JUL 2	0800	92.2	
P-1	JUL 2	1200	92.5	
P-1	JUL 2	1600	92.8	
P-1	JUL 2	2000	93.2	
P-1	JUL 3	0400	93.5	
P-1	JUL 3	0800	93.8	
P-1	JUL 3	1200	94.2	
P-1	JUL 3	1600	94.5	
P-1	JUL 3	2000	94.8	
P-1	JUL 4	0400	95.2	
P-1	JUL 4	0800	95.5	
P-1	JUL 4	1200	95.8	
P-1	JUL 4	1600	96.2	
P-1	JUL 4	2000	96.5	
P-1	JUL 5	0400	96.8	
P-1	JUL 5	0800	97.2	
P-1	JUL 5	1200	97.5	
P-1	JUL 5	1600	97.8	
P-1	JUL 5	2000	98.2	
P-1	JUL 6	0400	98.5	
P-1	JUL 6	0800	98.8	
P-1	JUL 6	1200	99.2	
P-1	JUL 6	1600	99.5	
P-1	JUL 6	2000	99.8	
P-1	JUL 7	0400	100.2	
P-1	JUL 7	0800	100.5	
P-1	JUL 7	1200	100.8	
P-1	JUL 7	1600	101.2	
P-1	JUL 7	2000	101.5	
P-1	JUL 8	0400	101.8	
P-1	JUL 8	0800	102.2	
P-1	JUL 8	1200	102.5	
P-1	JUL 8	1600	102.8	
P-1	JUL 8	2000	103.2	
P-1	JUL 9	0400	103.5	
P-1	JUL 9	0800	103.8	
P-1	JUL 9	1200	104.2	
P-1	JUL 9	1600	104.5	
P-1	JUL 9	2000	104.8	
P-1	JUL 10	0400	105.2	
P-1	JUL 10	0800	105.5	
P-1	JUL 10	1200	105.8	
P-1	JUL 10	1600	106.2	
P-1	JUL 10	2000	106.5	
P-1	JUL 11	0400	106.8	
P-1	JUL 11	0800	107.2	
P-1	JUL 11	1200	107.5	
P-1	JUL 11	1600	107.8	
P-1	JUL 11	2000	108.2	
P-1	JUL 12			

