AD-765 551

ORBIT DETERMINATION IN THE PRESENCE OF GRAVITY MODEL ERRORS

B. E. Schutz, et al

Texas University

Prepared for:

Air Force Office of Scientific Research

August 1972

DISTRIBUTED BY:

National Technical Information Service U. S. DEPARTMENT OF COMMERCE 5285 Port Royal Road, Springfield Va. 22151

Best Available Copy

AFOSR - TR - 73 - 1 4 3 9

ORBIT DETERMINATION IN THE PRESENCE

OF GRAVITY MODEL ERRORS

B. E. Schutz, B. D. Tapley, and P. E. Connolly The University of Texas at Austin



Approved for public release; distribution unlimited.

Reprod.ced by NATIONAL TECHNICAL INFORMATION SERVICE US Department of Commerce Springfield VA 22151

Symposium on Earth Gravity Models St. Louis, Missouri August 16-18, 1972

AD 76555]

ORBIT DETERMINATION IN THE PRESENCE OF GRAVITY MODEL ERRORS[#]

B. E. Schutz¹, B. D. Tapley², and P. E. Connolly³ The University of Texas at Austin

Abstract

The precise determination of a satellite's position is of prime importance in satellite geodesy and in the use of satellites in studying geodynamics. It is not possible, however, to obtain a precise estimate of the satellite's position if sufficiently large errors exist in the gravity model. In this investigation, the application of a dynamic model compensation method to the problem of estimating the motion of a near-earth satellite in the presence of gravity model errors is described. Based on numerical results obtained in a computer simulation, it is concluded that the algorithm will yield an accurate estimate of the state in the presence of gravity model errors. The effects of the observation type and accuracy, station location and observation batch size on the accuracy of the orbit determination procedure are considered. Finally, it is shown that in addition to an accurate estimate of the position and velocity, the method can be used to obtain an accurate estimate of the unmodeled acceleration components.

Assistant Professor, Department of Acrospace Engineering and Engineering Mechanics, The University of Texas at Austin

²Professor and Chairman, Department of Aerospace Engineering and Engineering Mechanics, The University of Texas at Austin

³Research Assistant, now assigned to Aerospace Defense Command, Laredo Air Force "Base, Laredo, Texas

[#]This investigation was supported by AFOSR Grant No. 72-2233.

DOCUMENT CONTROL DATA - À A D International activity of texas at Austin Dept of Acrospace Engineering & Engineering Mechanics Dept of Acrospace Engineering & Engineering Mechanics Dept of Acrospace Engineering & Engineering Mechanics Austin, Texas 78712 Austin, Texas 78712 Austin, Texas r8712 Austin, Texas r8712 Austexas r8722 Austin, Texas r8712 Austin, Texas r8712 Austin	Security Classification			
Iterative classification of links, but a station and and and a station of the station the station the station of the station of the station	DOCUMENT CONT	TROL DATA . R	L D	
ADMENTION ACTIVITY COMPARE WEAKING Dept of Actospace Engineering & Engineering Mechanics UNCLASSIFIED UNCLAS	(Security classification of title, body of abstract and indexing	ennotation musi be e	ntered when the	overall report is classified)
University of Texes at Austin Dept of Arcospace Engineering & Engineering Mechanics Austin, Texas 78712 Austin, Texas 78712 Austin, Texas 78712 Austin, Texas 78712 Austin, Texas 78712 ARCSAT DETERMINATION IN THE PRESENCE OF GRAVITY MOU'L ERRORS Control Present Automic Automic Automic Automic Automic Scientific Interim AutorNation Automic Automic Automic Automic AutorNation Automic Automic Automic Automic Automic AutorNation Automic Automic Automic Automic Automic AutorNation Automic Automic Automic Automic Automic Automic Automic AutorNation Automic Automi	I ORIGINATING ACTIVITY (Corporate author)		20. REPORT SE	CURITY CLASSIFICATION
Dept of Aerospace Engineering & Engineering Mechanics Austin, Texas 78712 Austin, Texas 78712 ORBHT DETERMINATION IN THE PRESENCE OF GRAVITY MOULL ERRORS - Ditentific Interim - AUTOMUT (Formation, adde motion data) Scientific Interim - AUTOMUT (Formation, adde motion data) - August 1972 - August 1972 - AFOSR 72-2233 - FRONT FORMATION FORMATION FORMATION FORMATION FORMATION - AFOSR 72-2233 - FRONT FORMATION FORMATION FORMATION - AFOSR 72-2233 - FRONT FORMATION FORMATION FORMATION - AFOSR 72-2233 - FRONT FORMATION FORMATION - AFOSR 72-233 - FRONT FORMATION - AFOSR 72-73 - 1 4 3 9 - CONTRACTON - AFOSR 72-73 - 1 4 3 9 - CONTRACT - AFOSR 72-73 - 1 4 3 9 -	University of Texas at Austin		UNCLAS	SIFIED
Austin, Texas 78712 A REFORM WITH A REFORM WITH NOTE (Type of regent and inclusive dates) S dentific Interim A CONTRACT OFFER of REAL TO A CONTRACT OFFER OF REAL TO A CONTRACT OFFER OFFE	Dept of Acrospace Engineering & Engineeri	ng Mechanics	28. GROUP	
AFFORTUNE ORBIT DETERMINATION IN THE PRESENCE OF GRAVITY MOLTL ERRORS • CELENTIVE MOTES (Proper and inclusive dates) Scientific Interim Scientific Interim • Autoconic (Proper and inclusive dates) Scientific Interim • Autoconic (Proper and inclusive dates) Scientific Interim • Autoconic (Proper and inclusive dates) B. E. Schutz B. D. Tapley P. E. Connolly * Accontic non operation AFOSR 72711 August 1972 * Accontactors chains no AFOSR 7272233 * Accontactors chains no * AFOSR 7373 PROCEDINCC * Superiment/on statters * Superiment/on statters </td <td>Austin, Texas 78712</td> <td>0</td> <td></td> <td></td>	Austin, Texas 78712	0		
ORBIT DETERMINATION IN THE PRESENCE OF GRAVITY MOLEL ERRORS - ORDENTIFY ROTTER (Provide direction) Scientific - AUTORNIC/First name, widdle indicat for name) B. D. Tapley P. F. Connolly - Account pairs August 1972 - Gentration of a state and contract activity - Gallou - AffOSR 72-2233 - Barbard - Gallou - AffOSR 72-73 - 1 4 3 9 - Contration of a provided activity Models, St. Louis, Missouri, 16-18 August 1972 - Air Force Office of Scientific Rsch (NM) 1400 Wilson Blvd Arlington, Virginia 22209 - Astract The precise determination of a satellite's position is of prime importance in satellite geodesy and in the use of satellites in studying geodynamics. It i	3 REPORT TITLE		L	
ORBIT DETERMINATION IN THE PRESENCE OF GRAVITY MODIL ERRORS • DETERMINATION IN THE PRESENCE OF GRAVITY MODIL. ERRORS • DETERMINATION IN THE PRESENCE OF GRAVITY MODIL. ERRORS • DETERMINATION IN THE PRESENCE OF GRAVITY MODIL. ERRORS • DETERMINATION IN THE PRESENCE OF GRAVITY MODIL. ERRORS • DETERMINATION ENTERNMENT B. E. Schutz B. D. Tapley P. E. Connolly * Account of the state of t				
A DECEMENT OF AN OTHER (Type of region and inclusion of Courter into the Court of the Court of Court of Court of the Court of Court of the Court of Court of the Court of Court of Court of the Court of Court of Court of the Court of Court of the Court of Court of the Court of Court of Court of Court of Court of Court of the Court of Co	ORBIT DETERMINATION IN THE PRESENCE OF CR	AVTTY MOLEL I	ERRORS	
 Distributive normal charge and malasize datase) Scientific Interim Scientific Interim Autoral (First mans, and in first, fail datase) B. E. Schutz B. D. Tapley F. E. Connolly A derail (First mans, and in first, fail datase) B. E. Schutz B. D. Tapley F. E. Connolly A derail (First mans, and in first, fail datase) August 1972 Actor and the first, fail datase) A derail (First mans, and in first, fail datase) A derail (First mans, and infinite fail datase) A derail (First mans, and fail fail datase) A derail (First mans, and fail fail datase) A derail (First mans, and fail datase) A dera				
Scientific Interim 1 Junch State Interim 2 Suppositum on Earth Gravity Models, St. Interime Interime Interime Interime Interime Interimetion 1 Junch State Interimetion of a satellite's position is of prime importance in satellite geodesy and in the use of satellites in studying geodynamics. It is not possible, however, to obtain a precise estimate of the satellite's position if sufficiently large errors exist in the gravity model. In this investigation, the application of a dynamic model compensation methat to the problem of estimating the motion of a mar-earth satellite in the presence of gravity model errors is described that the algorith will yield an accurate estimate of the state in the presence of gravity model errors is described that described and will be accuracy of the orbit determination procedure are considered. Finally, it is show that in addition to enaccuracy estimate of the state in the presence of gravity model errors. The effects of the observation type and accuracy, station location and observation batch size on the accuracy of the orbit	4. DESCRIPTIVE NOTES (Type of report and inclusive dates)			······································
B. E. Schutz B. D. Tapley P. F. Connolly August 1972 August 1972 * Contract on generic August 2072 * Contract on generic August 2072 * Contract on generic August 2072 * Contract on generic August 2072 * Contract on generic AFOSR 7-73 - 1439 * Contract on the image of estimate * Contract on generic * Contr *	Scientific Interim			
B. E. Schutz B. D. Tapley P. E. Connolly August 1972 t. Contract on Generation AFOSR 72-2233 t. sector no 9769 4 61102F 4 681304 AFOSR 72-223 t. sector no 9769 4 61102F 4 681304 AFOSR - TR - 73 - 1 4 3 9 TO DITINGUTION PARTMENT Approved for public release; distribution unlimited. T. Destingention of a satellite's position is of prime importance in satellite geodesy and in the use of satellites in studying geodynamics. It is not possible, however, to obtain a precise estimate of the satellite's position if sufficiently large errors exist in the gravity model. In this investigation, the application of a near-earth satellite in the presence of gravity model errors is described Difficiently large errors. The effects of the observation type and accuracy, station location and observation batch size on the accuracy of the orbit determination procedure are considered. Finally, it is shown that in addition to an accurate estimate of the position and velocity, the method can be used to obtain an accurate estimate of the unmodeled acceleration components.	S. AUTHOR(S) (First name, middle initial, last name)			· · · · · · · · · · · · · · · · · · ·
B. D. Tapley P. E. Connolly Argentation August 1972 40 4// Arostrater on Gamma Two AFOSR 72-2233 * PROSE 72-223 * PROSE 7200 <tr< td=""><td>B F Schutz</td><td></td><td></td><td></td></tr<>	B F Schutz			
5. 5. 14/14/2 F. C. Connolly August 1972 4. Yorki NO GFRACES (4. Yorki NO GFRACES (5. Yorki NO GFRACES </td <td></td> <td></td> <td></td> <td></td>				
P. L. CONDUTY 18. NO OF METS August 1972 40 % 18 August 1972 40 % 18 August 1972 18 18 August 1972 40 % 18 August 1972 18 18 * E- CONTRACTOR STATEMENT AFOSR 72-2233 18 * FRONCETOR STATEMENT AFOSR 72-2233 18 * 681304 AFOSR 73 - 14 39 19 * 681304 AFOSR - TR - 73 - 14 39 19 * 5000000000000000000000000000000000000	b. D. Tapley			
August 1972 40 4// 18 August 1972 40 4// 18 AFOSR 72-2233 • ONIGINATOR'S REPORT NUMBERS) * FROMET NO 9769 • OTHER REPORT NUMBERS) * 61102F • OTHER REPORT NUMBERS) * 681304 AFOSR 7-TR - 73 - 1439 * 0 OTHERSUTION STATEMENT AFOSE 7-TR - 73 - 1439 Approved for public release; distribution unlimited. AFOSE 7-TR - 73 - 1439 * 129PESMENT/** NOTE PROCEEDINCC Symposium on Earth Gravity Models, St. If spour wint duitary activity Louis, Missouri, 16-18 August 1972 Afr Force Office of Scientific Rsch (NM) 14.00 Wilson Blvd Arlington, Virginia 22209 ** Astract Ar Softward activity model errors is described The precise determination of a satellite's position is of prime importance in satellite geodesy and in the use of satellites in studying geodynamics. It is not possible, however, to obtain a precise estimate of the satellite's position if sufficiently large errors exist in the gravity model. In this investigation, the application of a dynamic model compensation methad to the problem of estimating the motion of a near-earth satellite in the presence of gravity model errors. The effects of the observation type and accuracy, station location and observation batch size on the accuracy of the orbit determination procedure are considered. Finally, it is shown that in addition to an accurate estimate of the position and velocity, the method can	A REPORT DATE	TA. TOTAL NO OF	PAGES	76. NO OF REFS
AFOSR 72-2233 • PROJECT NO 9769 • 61102F • 681304 AFOSR 72-2233 • PROJECT NO 9769 • 61102F • 681304 AFOSR 72-73 - 1 4 3 9 • ONLY AND STATEMENT Approved for public release; distribution unlimited. • Symposium on Earth Gravity Models, St. Louis, Missouri, 16-18 August 1972 The precise determination of a satellite's position is of prime importance in satellite geodesy and in the use of satellites in studying geodynamics. It is not possible, however, to obtain a precise estimate of the satellite's position if sufficiently large errors exist in the gravity model. In this investigation, the application of a dynamic model compensation methad to the problem of estimating the motion of a near-earth satellite in the presence of gravity model errors. The effects of the observation type and accuracy, station location and observation batch size on the accuracy of the orbit determination procedure are considered. Finally, it is shown that in addition to an accurate estimate of the unmodeled acceleration components.	August 1972	40	41	18
AFOSR 72-2233 • FROMET NO 9769 • 61102F • 681304 • 681304 • 681304 • 0 DIFER NEFORT NO(1) (Any other numbers that may be serified MISSIONT NO(1) (Any other numbers that may be serified Serified the algorithm will yield an accurate estimate of the state in the presence of gravity model errors. The effects of the observation type and accuracy, station location and observation batch size on the accuracy of the orbit determination procedure are considered. Finally, it is shown that in addition to an accurate estimate of the unmodeled acceleration components.	BE. CONTRACT OR GRANT NO	Se. ORIGINATOR'S	REPORT NUM	L
* FROZECT NO 9769 * 61102F * 661304 AFOSR - TR - 73 - 1439 * 681304 AFOSR - TR - 73 - 1439 * ONLYMENTY NOTE: PROCEEDINCC Symposium on Earth Gravity Models, St. Louis, Missouri, 16-18 August 1972 * Astract The precise determination of a satellite's position is of prime importance in satellite geodesy and in the use of satellites in studying geodynamics. It is not possible, however, to obtain a precise estimate of the satellite's position if sufficiently large errors exist in the gravity model. In this investigation, the application of a dynamic model compensation methal to the problem of estimating the motion of a near-earth satellite in the presence of gravity model errors is described that the algorithm will yield an accurate estimate of the sate in the presence of gravity model errors. The effects of the observation type and accuracy, station location and observation batch size on the accuracy of the orbit determination procedure are considered. Finally, it is shown that in addition to an accurate estimate of the unmodeled acceleration components.	AFOSR 72-2233			
 61102F 61102F 661304 AFOSR - TR - 73 - 1439 AFOSE - TR - 73 - 1439	6. PROJECT NO 9769			
 61102F 681304 AFOSR - TR - 73 - 1439 AFOST - TR - 73 - 1439 AFOSR - TR - 73 - 1439 AFOST - TR -				
Approved for public release; distribution unlimited. Approved for public release; distribution unlimited. Approved for public release; distribution unlimited. Descriment Gravity Models, St. Louis, Missouri, 16-18 August 1972 Air Force Office of Scientific Rsch (NM) 1400 Wilson Blvd Arlington, Virginia 22209 Arlington, Virginia 22209 Antington of a satellite's position is of prime importance in satellite geodesy and in the use of satellites in studying geodynamics. It is not possible, however, to obtain a precise estimate of the satellite's position if sufficiently large errors exist in the gravity model. In this investigation, the application of a dynamic model compensation methal to the problem of estimating the motior of a near-earth satellite in the presence of gravity model errors is described MMM Based on numerical results obtained in a computer simulation, it is concluded that the algorithm will yield an accurate estimate of the state in the presence of gravity model errors. The effects of the observation type and accuracy, station location and observation batch size on the accuracy of the orbit determination procedure are considered. Finally, it is shown that in addition to an accurate estimate of the position and velocity, the method can be used to obtain an accurate estimate of the unmodeled acceleration components.	6. 61102E	SA OTHER REPOR	T NO(3) (Any of	her numbers that may be essimed
AFOSR - TR - 73 - 1439 Approved for public release; distribution unlimited. Difference of Scientific Rsch (NM) House, Missouri, 16-18 August 1972 The precise determination of a satellite's position is of prime importance in satellite geodesy and in the use of satellites in studying geodynamics. It is not possible, however, to obtain a precise estimate of the satellite's position if sufficiently large errors exist in the gravity model. In this investigation, the application of a dynamic model compensation methad to the problem of estimating the motion of a near-earth satellite in the presence of gravity model errors is described MMM Based on numerical results obtained in a computer simulation, it is concluded that the algorithm will yield an accurate estimate of the state in the presence of gravity model errors. The effects of the observation type and accuracy, station location and observation batch size on the accuracy of the orbit determination procedure are considered. Finally, it is shown that in addition to an accurate estimate of the unmodeled acceleration components.	011021	this report)		
Approved for public release; distribution unlimited. TO DITABLE TO NOTES PROCEEDINCE Symposium on Earth Gravity Models, St. Louis, Missouri, 16-18 August 1972 The precise determination of a satellite's position is of prime importance in satellite geodesy and in the use of satellites in studying geodynamics. It is not possible, however, to obtain a precise estimate of the satellite's position if sufficiently large errors exist in the gravity model. In this investigation, the application of a dynamic model compensation methad to the problem of estimating the motion of a near-earth satellite in the presence of gravity model errors is described HAMM Based on numerical results obtained in a computer simulation, it is concluded that the algorithm will yield an accurate estimate of the state in the presence of gravity model errors. The effects of the observation type and accuracy, station location and observation batch size on the accuracy of the orbit determination procedure are considered. Finally, it is shown that in addition to an accurate estimate of the unmodeled acceleration components.	4 (0120)	AFOSR -	TR - 73	-1439
Approved for public release; distribution unlimited. Symposium on Earth Gravity Models, St. Louis, Missouri, 16-18 August 1972 The precise determination of a satellite's position is of prime importance in satellite geodesy and in the use of satellites in studying geodynamics. It is not possible, however, to obtain a precise estimate of the satellite's position if sufficiently large errors exist in the gravity model. In this investigation, the application of a dynamic model compensation method to the problem of estimating the motion of a near-earth satellite in the presence of gravity model errors is described EXME Based on numerical results obtained in a computer simulation, it is concluded that the algorithm will yield an accurate estimate of the state in the presence of gravity model errors. The effects of the observation type and accuracy, station location and observation batch size on the accuracy of the orbit determination procedure are considered. Finally, it is shown that in addition to an accurate estimate of the unmodeled acceleration components.	- 681304			1 - 0 0
The precise determination of a satellite's position is of prime importance in satellite geodesy and in the use of satellites in studying geodynamics. It is not possible, however, to obtain a precise estimate of the satellite's position if sufficiently large errors exist in the gravity model. In this investigation, the application of a dynamic model compensation method to the problem of estimating the motion of a near-earth satellite in the presence of gravity model errors is described that the algorithm will yield an accurate estimate of the state in the presence of gravity model errors. The effects of the observation type and accuracy, station location and observation batch size on the accuracy of the orbit determination procedure are considered. Finally, it is shown that in addition to an accurate estimate of the unmodeled acceleration components.	Symposium on Earth Gravity Models, St. Louis, Missouri, 16-18 August 1972	Air Force (1400 Wilson Arlington,	Office of Blvd Virginia	Scientific Rsch (NM) 22209
The precise determination of a satellite's position is of prime importance in satellite geodesy and in the use of satellites in studying geodynamics. It is not possible, however, to obtain a precise estimate of the satellite's position if sufficiently large errors exist in the gravity model. In this investigation, the application of a dynamic model compensation method to the problem of estimating the motion of a near-earth satellite in the presence of gravity model errors is described INEE Based on numerical results obtained in a computer simulation, it is concluded that the algorithm will yield an accurate estimate of the state in the presence of gravity model errors. The effects of the observation type and accuracy, station location and observation batch size on the accuracy of the orbit determination procedure are considered. Finally, it is shown that in addition to an accurate estimate of the position and velocity, the method can be used to obtain an accurate estimate of the unmodeled acceleration components.	13. ABSTRACT			
	The precise determination of a satellite's satellite geodesy and in the use of satell possible, however, to obtain a precise est sufficiently large errors exist in the gra application of a dynamic model compensation motion of a near-earth satellite in the pr MXMM Based on numerical results obtained of that the algorithm will yield an accurate gravity model errors. The effects of the location and observation batch size on the procedure are considered. Finally, it is estimate of the position and velocity, the estimate of the unmodeled acceleration com	s position is lites in stud timate of the avity model. on method to t resence of gr in a computer estimate of observation e accuracy of shown that i e method can mponents.	of prime ying geod satellit In this the problem avity mod simulati the state type and the orbi n additio be used t	importance in ynamics. It is not e's position if investigation, the m of estimating the el errors is described on, it is concluded in the presence of accuracy, station t determination n to an accurate o obtain an accurate

Security Classification

1 -

Introduction

With the recent improvements and refinements in the instruments used in the observations of near-earth satellites, measurements of range and range-rate with precision of less than one meter and one centimeter per second, respectively, are a reality. Such precise observations have potential for determination of the satellite's state, namely, position and velocity, to the precision necessary for geodesy and geodynamics studies.

A determination of the satellite's state commensurate with the observation accuracy using the classical batch processor (least squares) or the sequential filtering method is dependent on the accuracy of the tracking station locations and the model of the dynamical system. Such dependence on the model of the dynamical system is demonstrated by Smith, Kolenkiewicz, and Dunn (1971), Marsh and Douglas (1971), and Yionoulis, Heuring, and Guier (1972). Uncertainties in the geopotential, particularly resonant coefficients in some cases, are an important error source. Additional errors often occur in the atmospheric resistance modeling. The discrepancy between the true motion and the modeled motion often limit the usefulness of the orbit determination results, both from the point of view of using the estimates for navigation purposes as well as using them for scientific purposes.

The effect of gravity model errors on the accuracy of batch-type orbit determination methods was observed also in processing the Lunar Orbiter range-rate observations. Observation residuals were obtained which clearly showed a periodic variation with an amplitude larger than the observation noise. The work of Muller and Sjogren (1971) and Sjogren and Muller (1971) resulted in a mascon representation for the gravity anomalies.

A somewhat different approach was taken by Tapley and Ingram (1971) and Ingram and Tapley (1971) using a sequential estimation procedure which compensated for the model errors. In this approach, referred to as the Dynamic Model Compensation

(DMC) method, the model errors are assumed to consist of a time correlated component and a purely random component and are approximated by a first-order Gauss-Markov process. Application of the DMC method to the lunar orbit phase of the Apollo 10 and 11 spacecraft showed that (1) the DMC method obtained observation residuals within the observation noise level and (2) provided estimates of the acceleration due to the model error which could be correlated with the surface mass anomalies described by Sjogren and Muller (1971). Additional applications of the DMC method have been made by Tapley and Schutz (1972) to the problem of estimating unmodeled forces due to errors in the lunar potential. In addition, Connolly (1972) considered application of the method to the orbit determination problem of a near-earth satellite.

Other applications of statistical models have been explored by Shaw, Paul, and Henrikson (1969) for use in inertial navigation systems. Shaw <u>et al</u>. used statistical models for the vertical deflection from gravity anomaly models. More recently, Kasper (1971) and Jordan (1972) have utilized second-order Gauss-Markov processes to represent the gravity anomaly.

In this investigation, the question of how accurately both the state of the satellite and the acceleration due to model errors can be estimated for a nearearth satellite is considered. A near-earth orbit of 1000 km inclined at 42° is assumed for the study. In the investigation, computer simulation techniques were used to investigate the behavior of the DMC method as applied to the orbit determination problem of a near-earth satellite. In this study, the model errors were assumed to arise from an incomplete description of the geopotential. Two sets of simulated observations were generated, each resulting from a different method of <u>simulating</u> gravity model errors. It is shown that state estimates can be obtained which reduce the observation residuals to within the apriori observation accuracy and that the methods can be used to obtain an accurate estimate of

the accelerations due to gravity model error. The influence of observation accuracy, the magnitude of the model error, and the number of tracking stations on the accuracy with which the acceleration due to the model error can be estimated is discussed.

The Estimation Procedure

The equation: which describe the motion of an earth satellite can be expressed by the following system of first-order equations:

$$\dot{r} = v$$
, $\dot{v} = a_c + a_p + m(t)$ (1)

where r is a three-vector of position components, v is a three-vector of velocity components, a_c is the acceleration due to the central body, a_p is the modeled acceleration due to other sources, gravitational or otherwise, and m represents the acceleration due to incorrect modeling in a_c and a_p . The term m(t) will be referred to as the "unmodeled acceleration".

The three-vector m(t) represents the effects of all accelerations not accounted for in the mathematical model used to describe the motion of the satellite. In this discussion, m(t) is approximated as a first-order Gauss-Markov process, c(t), which satisfies the following vector differential equation

$$\dot{\varepsilon}(t) = B\varepsilon(t) + u(t)$$
 (2)

where u(t) is a three-vector of Gaussian noise whose components are assumed to be described by the statistics:

$$E[u(t)] = 0$$
, $E[u(t)u^{T}(\tau)] = q(t)\delta(t-\tau)$ (3)

where q(t) is a 3 x 3 positive definite matrix. The coefficient matrix B is defined by the components $B_{ij} = \frac{1}{T_i} \delta_{ij}$ where T_i , the time-correlation coefficients, are assumed to be unknown parameters whose values are to be determined during the estimation process. The state vector is then defined to be

 $\mathbf{X}^{\mathrm{T}} = [\mathbf{r}^{\mathrm{T}} : \mathbf{v}^{\mathrm{T}} : \mathbf{\varepsilon}^{\mathrm{T}} : \mathbf{T}^{\mathrm{T}}]$

Then the differential equations of state become

$$\dot{X} = \begin{bmatrix}
v \\
a_c + a_p + c \\
Bc + u \\
0
\end{bmatrix}$$
(4)

with the initial conditions $X(t_{0}) = X_{0}$.

In the following discussion, it is assumed that the observation noise, v_i , satisfies the following conditions:

$$E[v_i] = 0$$
, $E[v_i v_j^T] = R_i \delta_{ij}$, $E[v_i X_j^T] = 0$, (5)

where E[] is the expected value operator. Further, the observations are related to the state by the relation

$$y_{i} = G(x_{i}, t_{i}) + v_{i}$$
 (6)

where $G(X_{i},t)$ is some nonlinear function of the state.

The problem considered then is posed as follows: Given the relation for propagating the state, Eq. (4); the observation state relation, Eq. (6); a sequence of observations Y_i , i = 1, ..., k; the statistics on the state noise, Eq. (3); and the observation noise, Eq. (5), determine the best estimate of the state in the minimum variance sense, \hat{X}_k , at the time t_k . Under these conditions the estimate can be obtained using the following algorithm (Jazwinski, 1969):

$$\bar{\mathbf{X}}_{k} = \theta(\bar{\mathbf{X}}_{k-1}, t_{k-1}, t_{k})$$

$$\bar{\mathbf{P}}_{k} = \phi(t_{k}, t_{k-1})\mathbf{P}_{k-1} \phi^{T}(t_{k}, t_{k-1}) + \mathbf{Q}_{k-1}$$

$$\kappa_{k} = \bar{\mathbf{P}}_{k} H_{k}^{T}[\mathbf{H}_{k}\bar{\mathbf{P}}_{k}\mathbf{H}_{k}^{T} + \mathbf{R}_{k}]^{-1}$$

$$\hat{\mathbf{X}}_{k} = \bar{\mathbf{X}}_{k} + \kappa_{k}[\mathbf{Y}_{k} - \mathbf{G}(\bar{\mathbf{X}}_{k}, t_{k})]$$

$$\mathbf{P}_{k} = [\mathbf{I} - \kappa_{k}\mathbf{H}_{k}] \bar{\mathbf{P}}_{k}$$
(7)

where $H_k = [\partial G/\partial X_k]^*$, $\bar{X}_k = E[X_k | Y_1, ..., Y_{k-1}]$ and $\bar{X}_k = E[X_k | Y_1, ..., Y_k]$.

The covariance matrices \overline{P}_k and P_k are associated with the state estimates \overline{X}_k and \hat{X}_k , respectively. The state transition matrix, $\Psi(t_k, t_{k-1})$ satisfies the following differential equation

$$\dot{\Phi}(t, t_k) = A(t) \Phi(t, t_k); \Phi(t, t_k) = I$$
 (8)

where $A(t) = [\partial F/\partial X]^*$. The symbol $[]^*$ indicates that the quantity in the bracket is evaluated on the nominal solution, $\bar{X}(t) = \theta(\hat{X}_{k-1}, t_{k-1}, t), t_k \leq t$, that is, the solution obtained by integrating Eqs. (4) with the condition $X^*(t_{k-1}) = \hat{X}_{k-1}$ and $u^* = E[u(t)] = 0$. The algorithm given by Eqs. (7) and (8) is the extended form of the linear sequential estimator, or the Kalman-Bucy filter, as discussed by Jazwinski (1969). The covariance matrix P_k is associated with the best estimate of X_k based on k-observations while \bar{P}_k is the covariance matrix associated with the best estimate of x_k based on (k-1) observations.

It should be recalled that the estimate X_k , includes an estimate at the time, t_k , of the components of the position, the velocity, the unmodeled acceleration $\bar{\epsilon}(t)$ and the correlation coefficients, T_x , T_y , and T_z . The algorithm requires apriori or "initial" estimates of each of these quantities as well as the apriori covariance matrices, P_0 , Q_i , and R_i , associated with the initial state and with the state and the observation noise, respectively. The development of the algorithm and the computational procedure required to implement the algorithm are discussed in greater detail by Ingram (1971).

The following section describes the generation of the observations used in the estimation procedure and discusses the simulation of the gravity model errors. Generation of the Simulated Observations

The simulated observations are generated by the integration of the system of equations

where r_T is a three-vector of the true position components, v_T is a three-vector of the true velocity components, a_m represents the terms modeled in the estimation algorithm, and m represents the terms not directly included in the estimation differential equations. The term m represents a model error in the estimation procedure. To simulate model errors, two forms for m were used. First, m is assumed to represent the acceleration due to a point mass on the surface of the earth and close to the satellite's ground track. The term a_m includes all of the zonal harmonics up to the sixth degree as well as the tesseral and sectorial harmonics up to fourth-order and the lunar gravitational effect. In the second form, a_m includes J_2 and the lunar effect, whereas m contained the geopotential terms up to sixth degree in the zonal harmonics and all other terms to the fourth order.

 $\dot{\mathbf{r}}_{\mathrm{T}} = \mathbf{v}_{\mathrm{T}}$, $\dot{\mathbf{v}}_{\mathrm{T}} = \mathbf{a}_{\mathrm{m}} + \mathbf{m}$

Integration of Eq. (9) yields a solution for the motion of the satellite used in generating observations. The computer program ascertains which tracking stations can observe the satellite and an observation (either range, azimuth, elevation, range-rate or any combination) is computed. These observations are then corrupted by adding the quantity, $\sigma\lambda$, where σ is the standard deviation of the observation noise and λ is a Gaussian distributed random variable with zero mean.

The numerical integration is performed using the Runge-Kutta methods formulated by Fehlberg (1968). As implemented in the simulation program, two different order integrators can be used. For periods when the satellite cannot be seen by any of the tracking stations, the Runge-Kutta-Fehlberg 7(8) is used with a variable stepsize control. During periods in which observations are being generated, a fixed step is used to comply with a fixed observation interval.

8

(9)

This interval is normally small enough to allow use of a lower order integrator, namely, the Runge-Kutta-Fehlberg 4(5). If the observation interval results in a stepsize which is too large and the 4(5) is inadequate for maintaining accuracy, the 7(8) method can be used.

Data

The estimation program requires the numerical integration of Eq. (4) and Eq. (8), whereas the observation generation program requires the integration of Eq. (9). The state vector of Eq. (4) consists of 12 elements, the state transition matrix consists of 144 elements, and Eq. (8) consists of six elements. Eq. (8), $\dot{\phi}$, can, however, be reduced to a lower order by noting that a number of elements are zero.

The initial conditions for Eq. (4) and Eq. (9) used in the simulation are shown in Table I. A rectangular coordinate system is used in which X and Y are in the equatorial plane and Z is along the polar axis. The ground track of the satellite is shown in Fig. 1 where the semi-major axis of the satellite orbit is 7,507,000 meters, the eccentricity is .025, and the inclination is 41.2°. These orbital elements closely approximate those of the Beacon Explorer C (BE-C) spacecraft (Kolenkiewicz, 1972).

The assumed tracking station locations used in the simulations are shown in Table II. In general, the observations from horizon-to-horizon of the tracking station are used in the estimation process. However, several cases were examined in which a 25° elevation constraint was imposed. These results are discussed in a later section. The period of time during which each station can observe the satellite is shown also in Figure II. Although Figure II shows 15 stations, not all stations are used.

The geopotential coefficients used were given by Melbourne, <u>et al</u> (1968). Since these coefficients were being used to simulate a gravity model error, a more accurate set such as those determined by Gaposchkin and Lambeck (1970) was not required. In all cases, the initial covariance matrix, P, had the following form



where $\sigma_{\rm r}$ = 1000 meters; $\sigma_{\rm v}$ = 1 meter/sec; $\sigma_{\rm r}$ = .015 seconds; σ_{ξ} = .0001 meters/sec². In general, the initial value of ξ is taken to be zero unless otherwise stated. Results

Not only were two types of gravity model errors studied, but the effects of observation noise, station location, and number of stations were investigated. These results are discussed in the following. The gravity model error due to a point mass will be referred to as Case I and the second type discussed in preceding sections will be referred to as Case II. Furthermore, Case I is only considered in the 50 cm range observations study.

50-cm Range Observations

Both types of gravity model errors were used in the study with range observations in the noise level of 50 cm.

A. Case I

In the generation of the observations, a point mass of 3.64 x 10^{-5} times the mass of the earth was placed at 41°N latitude and 108°W longitude. The standard deviation in the state noise was .005 and the initial value assumed for the time correlation coefficient, T_i , i = 1, 2, 3, was 200 seconds. Figure 2 shows the result of estimating the acceleration due to the model error, or

unmodeled acceleration. In this figure, the smooth line represents the true value and the jagged line represents the estimate. Figs. 2a, 2b, and 2c represent the acceleration components in a rectangular coordinate system. Note that the estimate follows the true acceleration component and that the estimate has a mean which is close to the true value. Figs. 2d and 2e, show the trace of the state error covariance matrix and the true error norm plotted as a function of time. In Fig. 2d, for example, the smooth line represents the trace of P associated with the position components and the jagged line represents the true error norm. It is important to note that the state error covariance matrix bounds the true error. In this case, 12 tracking stations were used, although not all stations can observe the satellite simultaneously as shown in Table II. Those not used were Merritt Island, Arecibo, and Bermuda. Since the true error is within one meter from 5 to 20 minues, the (0-C)'s would also be within one meter.

B. Case II

The gravity model error was simulated using J_3 through J_6 and the tesseral and sectorial harmonics through order four. The same stations used in Case I were also used in this case. Figure 3a, 3b, and 3c show the acceleration estimate and the true acceleration. The standard deviation in the state noise was 0.000025. Again, the smooth line is the true and the jagged is the estimate. Although the estimate of the acceleration is not as good as in Case I, the state estimate is quite good, that is, within one meter. It should be noted that the acceleration error is approximately 100 times smaller than in the preceding case. The acceleration error in Case II is on the order of 5-8 milligals, as can be seen in Fig. 3. The (0-C)'s are shown in Fig. 4. Note that most of the points are within the 50 cm noise level of observation.

As a point of comparison the same case was run using the batch processor. The (0-C)'s are shown in Fig. 5. Note the periodic-type behavior with amplitude considerably above the noise level of the observation.

Figure 6 shows the results obtained by replacing the Santa Barbara, Las Vegas, and Albuquerque stations by ones at Merritt Island, Arecibo, and Bermuda. The influence of additional east coast stations was not significant except toward the end of the pass. It can be seen in Fig. 2d that the error begins a significant increase at approximately 20 minutes. Table II shows that at about 20 minutes there are four stations taking data and beginning at 24 minutes, only one station taking data. The error growth appears to be an effect of the number of stations. This effect will be discussed in a later section.

2. 1-cm Range Observations

Repeating the preceding Case II with $\sigma = 50$ cm replaced by $\sigma = 1$ cm yielded the results shown in Fig. 7. The tracking stations not used were Merritt Island, Arecibo, and Bermuda. It is apparent that by improving the observation accuracy, the estimate of the unmodeled acceleration is improved also. The upward trend of the covariance trace in Fig. 7d is again an effect of a single station observing the satellite. Note, however, that the true error is not increasing. Figure 8 illustrates the (0-C)'s for two of the stations, Goldstone and Goddard. Note that most of the residuals are within the 1-cm observation noise. For comparison, the same case was run in a batch processor. The (0-C)'s resulting from this case are shown in Fig. 9.

Since it is evident that the accuracy with which the unmodeled acceleration can be estimated is dependent on the observation accuracy, Case I was not run with 1-cm observations since 50-cm observations gave good estimates. The 1-cm observations would simply reduce the scatter in the estimate.

3. 2mm/sec Range-Rate Observations

The Case II discussed in the preceding section (2) was repeated using rangerate observations of 2 mm/sec accuracy. The results are shown in Fig. 10. The accuracy with which the unmodeled acceleration can be estimated is comparable to the J-cm range observations. The (0-C)'s behave as expected.

4. 25° Elevation Constraint

A case was run to examine the effect of a 25° elevation constraint on the 1-cm range observations. All observations yielding an elevation less than 25° were discarded. The observation interval used was .62 min = 1.2 sec. Again, Merritt Island, Arecibo, and Bermuda were not included. In this case, as can be seen in Table II, the first station which can see the satellite is San Francisco at approximately 3.6 minutes. Shortly thereafter, Santa Barbara acquires the satellite. Figure 11a shows that the acceleration estimate is poor until approximately 4 minutes at which time a third station acquires, namely, Goldstone. After this, the estimator yields good estimates. Thus, for the simulation, the horizon-to-horizon observations yield results representative of a more realistic case.

5. Effect of Number of Stations Claerving

The preceding case indicated the effect of the number of tracking stations which can observe the satellite. Figure 12 shows the results of using only three stations, namely, San Francisco, Ft. Davis, and Goddard. The observation accuracy is 1-cm in range, and the observations are taken from horizon-to-horizon. Note the radical change in the Y-component (Fig. 12b) when the third station is included at approximately 8 minutes. Even after the San Francisco station is lost at 16 minutes, the estimate remain:: quite good until the Ft. Davis station loses acquisition. Thus, this result shows that three stations can yield a good result while two stations may yield comparable or reasonable results. The question of what a single station can do with this method was not thoroughly investigated.

Summary

Based on the numerical results in the previous section, it can be concluded that the DMC method provides a significant improvement over the conventional batch method in estimating the state of a satellite in the presence of gravity model errors. The 50 cm range observations and 2 mm/sec range-rate observations are realistic while the 1 cm range observation will probably be available in the very mear future. Using these observation accuracies, it was shown in the previous section that the accuracy with which the unmodeled acceleration can be estimated depends on the observation accuracy and the magnitude of the acceleration due to the model error. Even when good acceleration estimates are not obtained, the state estimate yields (O-C)'s within the observation noise. The number of tracking stations which can observe the satellite influences the acceleration estimate. The results indicate that two or three stations yield good estimates at the 1-cm range noise level.

Further work is in progress to determine whether the second-order Gauss-Markov process would yield a significant improvement over the first-order process used in this paper. Additional investigation of the number of tracking stations required as well as the effect of tracking station location errors is underway. Consideration is also being given in the use of the acceleration estimates to improve the mathematical model of the geopotential.

15

References

- Connolly, P. E., "Orbit Determination for Artificial Satellites in the Presence of Errors in the Geopotential Model," Applied Mechanics Research Laboratory Report 1048, The University of Texas at Austin, 1972.
- Pehlberg, E., "Classical Fifth-, Sixth-, Seventh-, and Eighth-Order Runge-Kutta Formulas with Stepsize Control," NASA TR R-287, 1968.
- Gaposchkin, E. M., and Lambeck, K., "1969 Smithsonian Standard Earth (II)," SAO Special Report 315, 1970.
- Ingram, D. S., "Orbit Determination in the Presence of Unmodeled Accelerations," Applied Mechanics Research Laboratory Report 1022, 1971.
- Ingram, D. S., and Tapley, B. D., "Estimation of Unmodeled Forces on a Lunar Satellite," AAAS/AIAA Astrodynamics Specialist Conference, Paper No. 71-371, 1971.
- Jazwinski, A. H., Stochastic Processes and Filtering Theory, Academic Press, New York, 1969.
- Jordan, S. K., "Self-Consistent Statistical Models for the Gravity Anomaly, Vertical Deflections, and Undulation of the Geoid," Journal of Geophysical Research 77, 3660-3670, 1972.
- Kasper, J. F., Jr., "A Second-Order Markov Gravity Anomaly Model," <u>Journal of</u> <u>Geophysical Research</u>, 76, 7844-7849, 1971.
- Kolenkiewicz, R., Private Communicaton, 1972.
- Marsh, J. G. and Douglas, B. C., "Tests and Comparisons of Gravity Models," Celestial Mechanics, IV, 309-325, 1971.
- Melhourne, W. G., et. al., "Constants and Related Information for Astrodynamic Calculations, 1968," JPL TR 32-1306, 1968.
- Muller, P. M. and Gjogren, W. L., "Lunar Gravimetry and Mascons," <u>Applied Mechanics</u> Reviews, 955-959, 1971.
- Shaw, L., Paul, I., and Henrikson, P., "Statistical Models for the Vertical Deflection from Gravity-Annualy Models," Journal of Geophysical Research, 74, 4259-4265, 1969.
- Sjogren, W. L., and Muller, P. M., "Lunar Surface Mass Distribution From Dynamical Point Mass Solutions," The Moon II, 338-353, 1971.
- Smith, D. E., Kolenkiewicz, R., and Dunn, P. J., "Geodetic Studies by Laser Ranging to Satellites," Goddard Space Flight Center Report X-553-71-361, 1971.
- Tapley, B. D., and Ingram, D. S., "Orbit Determination in the Presence of Unmodeled Accelerations," incl. of the Second Symposium on Nonlinear Estimation Theory, San Diego, California, 1971.

Tapley, B. D., and Schutz, B. E., "Estimation of Unmodeled Forces on a Lunar Satellite," Paper to be presented at 23rd Congress of the IAF, Vienna, Austria, 1972.

Yionoulis, S. M., Heuring, F. T., and Guier, W. H., "A Geopotential Model (APL 5.0-1967) Determined from Satellite Doppler Data at Seven Inclinations," Journal of Geophysical Research 77, 3671-3677, 1972. Table I.

Initial Conditions (Meters and Meters/Sec.)

	TRUE	NOMINAL	DIFFERENCE (TRUE-NOMINAL)
×	-5385692.8	5385610.2	-82.6
¥	-3576430.5	3576222.4	-208.1
2	3549660.3	3549464.8	195.5
٠×	5014.492	5015.173	680
•>•	-4153.014	4153.526	.512
.2	3411.811	3411.019	.792





Table II

Simulation Tracking Station Locations and Coverage



.

Figure 1. Ground Track of Satellite



Case I Model Error



Figure 2. (Cont.)









Figure 3 (Cont.)







Figure 5. (0-C) For The Batch Processor





Figure 7. Case II Model Error, $\sigma_{
m o}$ = 1



Figure 7 (Cont.)



Figure 7 (Cont.)





Figure 9. (0-C) For the Batch Processor







Figure 10 (Cont.)







.

Figure 12 (Cont.)

c. Z Acceleration (meters/sec²)

