AD-768 768

EVALUATION OF TORSIONAL PROPERTIES OF SPRING MATERIALS

re searche en and she were the state of the state of the search of the state of the search of the search of the

Henry P. Swieskowski

Army Weapons Command Rock Llasd, Illinois

May 1973

白樹冷鎮。

ĊÅ.

ないで、というないというないというからい



National Technical Information Service U. S. DEPARTMENT OF COMMERCE 5285 Port Royal Road, Springfield Va. 22151

DISCLAIMER NOTICE

THIS DOCUMENT IS BEST QUALITY PRACTICABLE. THE COPY FURNISHED TO DTIC CONTAINED A SIGNIFICANT NUMBER OF PAGES WHICH DO NOT REPRODUCE LEGIBLY.

::

562111815	Rectify the general sector of the sector of		
(Security classification of title, body of abstract and	CONTROL DATA -	R&D be entered when the	overall report is classified;
CMDR, RICK Island Arsenal	Na managamba sa ka bistange sanawa na sa	24. REPORT S	ECURITY CLASSIFICATION assified
GEN Thomas J, Rodman Laborato	ry	25. GROUP	
REPORT TITLE			
EVALUATION OF TORSIONAL PROPERT	IES OF SPRING	G MATERIAL	3
I. DESCRIPTIVE NOTES (Typs of report and inclusive dates)	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		
5. AUTHOR(S) (Piret same, middle initial, last name)			
Henry P. Swieskowski			
May 1973	74. TOTAL NO	. OF PAGES	76. NO. OF NEFS
A. CONTRACT OR GRANT NO.	Re ORIGINAT	OR'S REPORT NUM	BER(3)
5. PROJECT NO.	R-	-RR-T-3-32-	.73
DA 1W562604A607			
AMS Code 552D.11.80700.0%	96. OTHER M this report)	PORT NO(S) (Any o	ther numbers that may be avergoed
C. DISTRIBUTION STATEMENT			
Approved for public release, di	stribution u	nlimited.	
- SUPPLEMENTARY NOTESCIAIS OF INVERSIONS IN	12. SPONSORI	NG HILIYARY ACTI	VITY .
this document may be t	Rock I	sland Arse	nal
SIUGIOG DE INICIVICIO.			
Torsional properties of various	spring mate	rials were	evaluated. All
materials tested were of Solid approximately 200 inch. Test s	circular cro specimens wer	ss section e twisted	with a diameter of a torsion test
equipped with an automatic reco	order by whic	h torque-a	ngular strain dia•
grams were plotted. Diagrams w	ere analyzed ai and elast	and measu ic limits.	rements made to The amount of in
determine values for propartion			
determine values for proportion crease to the proportional and	elastic limi	ts that re	sults from strain
determine values for proportion crease to the proportional and hardening was determined. The limit were also studied. Strai	elastic limi effects of s in hardening	ts that re hot peenin of the big	sults from strain g on the elastic h carbon steels
determine values for proportion crease to the proportional and hardening was determined. The limit were also studied. Strai had little effect on the propor	elastic limi effects of s in hardening rtional limit	ts that re hot peenin of the hig , but did	sults from strain g on the elastic h carbon steels produce a substan-
determine values for proportion crease to the proportional and hardening was determined. The limit were also studied. Strai had little effect on the propor tial increase in the elastic li	elastic limi effects of s in hardening ctional limit mit. The sh	ts that re hot peenin of the hig , but did ot peening	sults from strain g on the elastic h carbon steels produce a substan- operation had lii
determine values for proportion crease to the proportional and hardening was determined. The limit were also studied. Strai had little effect on the propor tial increase in the elastic li tle noticeable effect on the to torsional properties are presen	elastic limi effects of s in hardening rtional limit imit. The sh prsional prop ited and resu	ts that re hot peenin of the hig , but did ot peening erties. D lts discus	sults from strain g on the elastic h carbon steels produce a substan- operation had lij etailed tables of sed.
determine values for proportion crease to the proportional and hardening was determined. The limit were also studied. Strai had little effect on the propor tial increase in the elastic li tle noticeable effect on the to torsional properties are presen	elastic limi effects of s in hardening rtional limit imit. The sh orsional prop ited and resu	ts that re hot peenin of the hig , but did ot peening erties. D lts discus	sults from strain g on the elastic h carbon steels produce a substan- operation had lii etailed tables of sed.
determine values for proportion crease to the proportional and hardening was determined. The limit were also studied. Strai had little effect on the propor tial increase in the elastic li tle noticeable effect on the to torsional properties are presen	elastic limi effects of s in hardening rtional limit imit. The sh orsional prop ited and resu	ts that re hot peenin of the hig , but did ot peening erties. D lts discus	sults from strain g on the elastic h carbon steels produce a substan- operation had lii etailed tables of sed.
determine values for propartion crease to the proportional and hardening was determined. The limit were also studied. Strai had little effect on the propor tial increase in the elastic li tle noticeable effect on the to torsional properties are presen	elastic (1m) effects of s in hardening rtional limit imit. The sh prsional prop ited and resu	ts that re hot peenin of the hig , but did ot peening erties. D lts discus	sults from strain g on the elastic h carbon steels produce a substan- operation had lii etailed tables of sed.
determine values for proportion crease to the proportional and hardening was determined. The limit were also studied. Strai had little effect on the propor tial increase in the elastic li tle noticeable effect on the to torsional properties are presen	elastic limi effects of s in hardening rtional limit imit. The sh orsional prop ited and resu L TECHNICAL TION SERVICE	ts that re hot peenin of the hig , but did ot peening erties. D lts discus	sults from strain g on the elastic h carbon steels produce a substan- operation had lii etailed tables of sed.
determine values for proportion crease to the proportional and hardening was determined. The limit were also studied. Strai had little effect on the propor tial increase in the elastic li tle noticeable effect on the to torsional properties are presen	L TECHNICAL	ts that re hot peenin of the hig , but did ot peening erties. D lts discus	sults from strain g on the elastic h carbon steels produce a substan operation had li etailed tables of sed.
determine values for proportion crease to the proportional and hardening was determined. The limit were also studied. Strai had little effect on the propor tial increase in the elastic li tle noticeable effect on the to torsional properties are preser	elastic limi effects of s in hardening rtional limit imit. The sh prsional prop ited and resu L TECHNICAL TION SERVICE	ts that re hot peenin of the hig , but did ot peening erties. D lts discus	sults from strain g on the elastic h carbon steels produce a substan operation had li etailed tables of sed.
determine values for propartion crease to the proportional and hardening was determined. The limit were also studied. Strai had little effect on the propor tial increase in the elastic lit the noticeable effect on the to torsional properties are preser	elastic iimi effects of s in hardening rtional limit imit. The sh orsional prop ited and resu ited and resu ited and resu	ts that re hot peenin of the hig , but did ot peening erties. D lts discus Unclas	sults from strain g on the elastic h carbon steels produce a substan operation had li etailed tables of sed.

ч¥.

20-762768

`د

, ` , `

¢

ు భార

à

•

**

Unc	1	as	s i	fi	ed
-----	---	----	-----	----	----

۰*۲*

•

·, v

and the second of the second

そきすく し

6 .	KE WORDS		LIH	K . A	LIN	ĸ	LIN	KC
mahilayya	eren heren an anderen an		ROLE	WT	ROLE	W	ROLE	. W1
1.	Torsional Properties							
? .	Spring Wire							
}.	Proportional Limit							
\$.	Elastic Limit			-				
5.	Strain Hardening							
;.	Shot Peening							
	,							
			,					
						1		
				Υ.				
								•
				-	-			
	¢						, I	
		-	ļ		ĺ			
							Į	
				Í				
			·					
	an de fan de En de fan de f	0 (<i>c</i>)	Uncla	ssif	led	name (name)	manana	1047 <u>9</u> 64
		<i>µ</i> 0 -	,	Security	Classific	ation		

. .

DISPOSITION INSTRUCTIONS:

Destroy this report when it is no longer needed. Do not return it to the originator.

DISCLAIMER:

The findings of this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

			No.
- 733 - 73 - 7 - 7 - 7 - 7 - 7 - 7 - 7 - 7 - 7 - 7	AND Archer D.: Section	a no	
	/4531145HTTY CO	iES	
A		<u>UL</u>	

RESEARCH DIRECTORATE

GENERAL THOMAS J. RODMAN LABORATORY

ROCK ISLAND ARSENAL

ROCK ISLAND, ILLINOIS

TECHNICAL REPORT

R = RR = T = 3 = 32 = 73

EVALUATION OF TORSIONAL PROPERTIES OF SPRING MATERIALS

Henry P, Swieskowski

M., 1973

DA 1W562604A607

9

×

ţ

AMS Code 552D, 11.80700,01

Approved for public release, distribution unlimited.

هره بَنَ إِنَّ ا

ABSTRACT

5

Torsional properties of various spring materials were evaluated. All materials tested were of solid circular cross section with a diameter of approximately,200 inch. Test specimens were twisted on a torsion tester equipped with an automatic recorder by which torque-angular strain diagrams were Diagrams were analyzed and measurements made to deplotted. termine values for proportional and elastic limits. The amount of increase to the proportional and elastic limits that results from strain hardening was determined. The effects of shot peening on the elastic limit were also studied. Strain hardening of the high carbon steels had little effect on the proportional limit, but did produce a substantial increase in the elastic limit. The shot peening operation had little noticeable effect on the torsional properties. Detailed tables of torsional properties are presented and results discussed.

CONTENTS

٠,

	Page
Title Page	i
Abstract	ŤŤ
Table of Contents	iii
Objective :	1
Introduction	¹ 1
Discussion	1
Material	1
Testing Equipment and Procedures	2
Test Results	3
Material as Received, Not Shot Peened	3
Shot Peened Material	5
Bauschinger Effect Produced by Torque Reversal	6
Conclusions	7
Recommendations	7
Appendix	9
References	41
Distribution	4%
DD Form 1473 (Document Control Data - R & D)	46

OBJECTIVE

The objectives of this project were (1) to evaluate the torsional properties of various spring materials, (2) to determine the amount of increase to the proportional and elastic limits from strain hardening of the material and (3) to determine the effect on the torsional properties produced by shot peening of the material.

INTRODUCTION

The suitability of a material for helical compression and extension spring applications can best be decided by consideration of its torsional properties. The torsional elastic limit and yield point, rather than the tensile strength, provide more reliable criteria to determine the energy storing capacity of a spring, its resistance to permanent set, and the capacity for a satisfactory spring service life. This is true because the principal stress in a helical spring under compression is torsional, and the material behaves essentially as a straight bar twisted under torsion. The torsion moment, T, which produces the twist is the product of two factors, the load, P, acting along the axis of the helical spring and the effective moment arm, D/2, where D is the mean coil diameter. The formula for the torsional stress is obtained simply by the dividing of the torsion, which for round wire is $\pi d^3/16$; where d is the diameter of the wire.

and and a st

Torsional Stress,
$$S = \frac{PD}{2} = \frac{8PD}{\pi d^3}$$
 (1)

This formula is related to the one used for calculating the stress in torsion bar springs.

Torsional Stress,
$$S = \frac{16T}{\pi d^3}$$
 (2)

DISCUSSION

<u>Material</u>

Torsional properties of the following spring materials were measured in this study. All the material had solid circular cross sections.

<u>Material</u>	<u>Diameter</u> (inch)
Music Wire, QQ-W=470	。200
Hard Drawn, QQ-W-428, Type II	207
Chrome Vanadium, QQ-W-412, Comp. I	.207
Oil Tempered, 00-W-428, Type I	.200
Stainless Steel, 00-W-423, Comp. FS302	207
Stainless Steel, 00-W-423, Comp. FS316	187

Material was obtained from the supplier so that the diameters were as close to 200 inch as possible. Material was cut to 12 inches in length, this allowed 5.5 inches of gauge length specimen after the rod was secured into the locking chucks of the torsion tester. The application of right angle bends at the ends of the rod for anchoring purposes was unnecessary. The material was inserted in straight form directly into the gripping jaws of the chucks.

Testing Equipment and Procedures

The torsion tester used to measure the torsional properties is shown in Photograph 11-199-2086/AMC-72 in the Appendix. The tester consists of two major units, an indicating unit and a loading unit. The loading unit in turn is composed of two sep= arate parts, a weighing head and a power or load applying head. A torque arm which is permanently fixed within the weighing head transmits the torsional load to a load cell which directly converts the torque value to an electrical signal that is then displayed on the indicating unit. The power head is mounted on rollers and is free to travel on round rails to permit rapid lateral adjustment for varying specimen lengths, and automatic compensation for changes in specimens length during test. All loading was performed with the power head rotating in a counterclockwise direction.

The tester is equipped with a recorder by which the loadangular strain relationship of the specimen under test is automatically plotted. The torque load is plotted along the ordimate in terms of inch - pounds and the angular strain is shown along the abscissa in degrees. All testing was performed with a torque scale range of 0-500 inch - pounds, that is, each major division along the ordinate represents 10° inch - pounds. The strain magnification was selected so that each inch along the abscissa represents 10 degrees. The test speed both for loading and unloading was at 60 degrees per minute. The proportional limit and the elastic limit in torsion for each material were read directly from the load - strain curve. The proportional limit is that point on the load - strain diagram where the curve begins to depart from a straight line. Beyond the proportional limit, unit deformation begins to increase at a faster rate than does the unit stress. The elastic limit is that point on the load-strain curve where further deformation results in permanent set to the material.

Test Results

Material As Received, Not Shot Peened

The load-strain diagram of the initial loading that was applied to the music wire material is shown in Figure 1 in the Appendix, The measured proportional limit and elastic limit are respectively 150 inch-pounds and 205 inch-pounds. Note that a sizable difference exists between these two values; this is in contrast to the material loaded under tension where, generally, the proportional limit and the elastic limit practically coincide. The loading extends beyond the elastic limit and into the plastic range, as can be seen in Figure 1. The angular deflection of 25.5 degrees that occurred beyond the elastic limit resulted in a permanent set to the material. The slope of the unloading line is approximately equal to that of the elastic loading curve. The results of subsequent loadings that were made to the same piece of music wire are shown in Figures 2, 3, and 4. In each case loading was applied beyond the elastic limit and into the plastic region of the material. The proportional limit increased to 160 inch-pounds and the elastic limit. increased to 235 inch-pounds due to the effect of the strain hardening of the material (Figure 2). Further cold working had no effect on the proportional limit; however, it did increase the elastic limit slightly to 250 inch-pounds (Figures 3 and 4), Torsion testing of spring materials in this study has shown that little, if any, changes occurred in the physical properties after the fourth loading. The load-strain diagram of the music wire material torqued up to its elastic limit of 250 inch=pounds and then unloaded as shown in Figure 5. Note that the unloading line returned to the original position; no set occurred in the material since the elastic limit was not exceeded. Some energy dissipation occured in the loading and unloading cycle as repre-sented by the area between the two curves. This energy has been lost mainly in the form of internal friction within the rod.

Torsional properties of subsequent materials will be shown only at the following three important stages of loading; initial loading, fourth loading, and a complete cycle within the elastic range. The torsional properties of hard-drawn material QQ-W-428; Type II are represented in Figures 6, 7, and 8. Strain hardening had a slight effect on the proportional limit, i. e., its value was increased from 150 to 160 inch-pounds. However, strain hardening did have a profound effect on the elastic limit i. e., its value was increased 25 per cent, from 200 to 250 inch-pounds. The hard-drawn material can safely withstand a stress of 144,000 psi (250 in.-1b.) without incurring any permanent sec (Figure 8).

Torsional properties of chrome-vanadium material and its reaction to strain hardening are illustrated in Figures 9, 10, and 11. The proportional limit increased from 190 to 240 inch-pounds, and the elastic limit similarly in= creased from 225 to 275 inch-pounds.

A slight change occurred in the torsional properties of oil-tempered material. Strain hardening had no effect on the proportional limit; its value remained at 150 inchpounds throughout the testing (Figures 12 and 13). The elastic limit increased by 30 inch-pounds, from 190 to 220 inch-pounds.

The test results for stainless steel, FS302 and stainless steel, FS316 are shown in Figures 15 and 16, and in Figures 18 and 19, respectively. The proportional limit for the FS302 type increased from 100 to 140 inch-pounds, and its elastic limit increased from 155 to 200 inchpounds. The initial proportional and elastic limits for stainless steel, FS316 were 100 inch-pounds and 130 inchpounds. Each value was increased by 20 inch-pounds because of strain hardening to 120 and 150 inch-pounds.

The torsional properties of all the materials for convenient comparison are listed in Table 1 of the Appendix. Stress values shown on Table 1 were calculated with the use of Equation 2

Torsional stress, $S = \frac{16T}{\pi d^3}$ (2)

The most relevant value to spring design is the final elastic limit since the point at which a spring will commence to set and fail to support the applied load is determined by this value. The music wire and chrome=vana= dium materials have the highest elastic limits and are about equal (Table 1). The hard-drawn and oil-tempered materials which have comparable chemical compositions also have similar elastic properties. The stainless steels, FS302 and FS316, have approximately equal elastic strengths, which were the lowest of all measured values. The strain hardening of the high carbon steels had a greater influence on the elastic limit than on the proportional limit. This is particularly true for the oil tempered material whose proportional limit remained unchanged, but its elastic limit was increased by 30 inch-pounds because of the cold working. The following standard formula by which the torque-deflection relationship is expressed enables one to describe the test curves very closely up to the proportional limit of the material.

$$T = \frac{Gd^{4}\theta}{583 \cdot 6L} = \frac{11 \cdot 5 \times 10^{6} (207)^{4}\theta}{583 \cdot 6 (5 \cdot 5)}$$
(3)

T - Applied torque load, inch-pounds

G - Modulus of elasticity in torsion, pounds per square inch

d - Diameter of rod, inches

0 - Angular twist over gauge length, degrees

L = Gauge length, inches

For example, the measured and calculated torque-angular deflection values for the hard-drawn material (Figure 7) which has a proportional limit of 160 inch-pounds is as follows:

Deflection	<u>Measured Torque</u>	<u>Calculated Torque</u>
5 Deg,	35 In Lb -	33 InLb.
10	65	66
15	95	99
20	120	132
25	150	164
30	170	197
35	195	230

Shot-Peened Material

Six materials of the same type were also shot peened in accordance with the following procedure:

(1)	Type of shot material,	steel
(2)	Shot size,	.033 in.
(3)	Shot hardness,	R 45-50
(4)	Almen intensity,	.012×.016A

This procedure is the standard method practiced by the Arsenal Operations Directorate in the shot peening of production springs with wire diameters of .150-.500 inch. Load strain curves for the shot-peered material are given in Figures 21 to 26. For convenient comparison, each figure contains 2 curves, showing the initial loading and the final loading after the material has been fully strain hardened. The initial and final elastic limits for the as-received malerial and the shot-peened material together with the associated stress values are listed in Table 2 of the Appendix. The peening operation had little noticeable effect on the elastic limits. (Table 2). As a matter of fact, no changes occured in the elastic properties of the hard-drawn and oiltempered materials.

Bauschinger Effect Produced by Torque Reversal

The interesting effect caused by the reversing of the twisting moment is shown in Figure 27. The initial loading of the material is shown by curve OAB. The rod is then unloaded along curve BDO, then torqued in the opposite direction along curve OE, and then allowed to return to 0 torque. as shown by curve EF. The proportional and elastic finit. In the original loading direction are respectively 160 and 210 inch-pounds. However, these values decrease considerably when the bar is twisted in the opposite direction. Also, in the reversed direction, the proportional and elastic limits coincide at the value of 40 inch-pounds. This sharp decrease in physical properties is known as the Bauschinger effect and this effect is used to explain why spring manuals contain caution notes that torsion bars be loaded only in the same direction as that of the presetting torque.

The Bauschinger effect is produced by two factors. One is the nonuniformity of vielding in a polycrystalline metal. Because the crystals are oriented at random throughout the metal, they yield by different amounts so that on a microscopic scale the stress varies slightly from crystal to crystal. When the member is inloaded, it contracts until the average stress is zero. However, the crystals that yielded the least do not quite return to zero, these remain stressed in the original direction while those that yielded the most go beyond zero and are stressed in the opposite direction. Thus, microscopic residual stresses called Heyn stresses or textural stresses exist throughout the metal. Therefore, when the twisting moment is reversed, the crystals that already have residual stresses in that reversed direction will yield at a lesser stress level and the overall yield stress will be lower.

The effect observed in polycrystals cannot be attributed entirely to these residual stress, and the effect in single crystals cannot be explained by them. Another factor is the behavior of dislocations that can be explained as follows. When the material yields in the first direction. the dislocations move through the crystal structure until obstacles are encountered by which progress is slowed down or stopped entirely. As other dislocations approach, they also are slowed or stopped, and strain hardening takes place. When the load is removed, the elastic strains are recovered, but the dislocations still remain immobile and under some "train from having been crowded together behind the various obstacles. Consequently, they move more easily in the re= verse direction and at a lower than normal stress. This phenomenon enables one to explain the Baushinger effect in single crystals and, at least, part of that in polycrystals

CONCLUSIONS

1. Strain hardening had a minor effect on the proportional limits of the high-carbon steels that were tested. but did produce a noticeable effect on their elastic limits.

2. The formula $T = \underline{Gd^2\theta}_{583,6L}$ approximates the test results very closely up to the proportional limit of the matterial.

3. A sizable difference exists between the proportional and elastic limits in torsion; this is in contrast to the material loaded under tension, where generally these limits are approximately equal.

4. Music wire and chrome vanadium had the highest tor sional elastic limits of the six materials tested.

5. The shot-peening operation had little noticeable effect on the elastic limits of the material's. Evidently, the beneficial effects of shot peening can not be measured in terms of the elastic limit.

6. A torque-deflection diagram provides an excellent criterion for the determination of quality spring material.

RECOMMENDATIONS

I. Torsional properties should be considered in the evaluation of material for spring applications

2. Critical springs should be strain hardened by presetting to increase the elastic limit of the material.

3. Music wire and chrome-vanadium materials should be recommended generally for highly stressed applications because of their higher torsional elastic limits 4. Stainless steel materials should be recommended for only those areas that involve corrosive or high temperature environments.

の日本をないためであったとうとうとう

Ø

.

APPENDIX

				raye
Photogra	iph		Torsion Tester	11
igure	1	414	Initial Loading of Music-Wire Material	12
Figure	,2	-	Second Loading of Music-Wire Material	13
Figure	3	••	Third Loading of Music-Wire Material	14
Figure	4	-	Fourth Loading of Music-Wire Material	15
Figure	5	•	Final Loading of Music-Wire Material	16
Figure	6	84	Initial Loading of Hard-Drawn Material	17
Figutte	7	-	Fourth Loading of Hard-Drawn Material	18
Figure	8	-	Final Loading of Hard-Drawn Material	19
Figure	9	•	Initial Loading of Chrome-Vanadium Material	20
Figure 1	0	**	Fourth Loading of Chrome-Vanadium Material	21
Figure 1	1	8	Final Leading of Chrome-Vanadium Material	22
Figure 1	2		Initial Loading of Oil-Tempered-Material	23
Figure 1	3	•	Fourth Loading of Oil-Tempered-Material	24
Figure 1	4	•	Final Loading of Oil-Tempered-Material	25
Figure 1	5		Initial Loading of Stainless Steel FS302 Material	26
Figure 1	6	0	Fourth Loading of Stainless Steel FS302 Material	27
Figure 1	7	•	Final Loading of Stainless Steel FS302 Material	28
Figure 1	8	•	Initial Loading of Stainless Steel FS312 Material	29
Figure 1	9	*	Fourth Loading of Stainless Steel FS316 Material	30
Figure 2	20	-	Final Loading of Stainless Steel FS316 Material	31
Table 1		••	Torsional Properties of Materials	32
Figure 2	21	**	Loading of Shot-Peened Music-Wire Material	33

Figure	22	- Loading of Shot-Peened Hard-Drawn Material	34
Figure	23	- Loading of Shot-Peened Chrome-Vanadium Material	35
Figure	24	- Loading of Shot-Peaned Oil-Tempered Material	36
Figure	25	- Loading of Shot-Peened Stainless Steel FS302 Material	37
Figure	26	- Loading of Shot-Peened Stainless Steel FS316 Material	38
Table 2	2	- Torsional Properties of Shot-Peened Material	39
Figure	27	- Illustration of Bauschinger Effect	40

ß .





Ç



- Music Wire, QQ-W-470

Material



Material - Music Wire, QQ-W-470



15

FIGURE

¢

Material

Material - Music Wire, QQ-M-470

FIGURE 5

DIVIDE BY MAGNIFICATION RATIO



1.1

£...

į



Type II





Material



19

Material

Material - Chrome Vanadium, QQ-W-412 Comp. I

FIGURE 9

DIVIDE BY MAGNIFICATION RATIO





ş

\$

í

21

Material - Chrome Vanadium, QQ-W-412 Comp. I



FIGURE 11

DIVIDE BY MAGNIFICATION RATIO

11

STRAIN





FIGURE 12

DIVIDE BY MAGNIFICATION RATIO

÷

		N-12
	╋╏┹╈╄┹┪╘╼╈┇┨┇╅┇╊╊╞╞╈╂╍┇┧╛╪┯╍┪┪┪╗╔╖╎╕╧╺╶╽╴ ╪╋╋╞┿╪╪╪╪╪╪╪╪╪╪╪╪╪╪╪╪╪╪╪╪╪╪╪╪╪╪╪╪╪╪╪╪╪╪	GTH. 100
	╞╊╋╋╞┿╋┘╋╞┿┚┥╋┿╏┥╋╅┥┟┿╴╺╞╸┍┥╴╸╸ ┲┚┿┊┊┶╽┶╘┽┽╞┿┿╅┶┾╡╩╋╴┝╡┯╸╶┽╱┊┙┠╏╎╾╽┥┝┿╡ ╢╫┿╝╵┶┊╲╦┶╉╘┿┿╧╵╁┍╼┾╼┨┱╒┶┶╴┍┯╼╴╏┵╴╘┿┊┶┾┽	N THE N
	₩219 £28 £3 £23 £23 £45 £2 £3 £2 £2 £2 £2 £2 £2 £2 £2 £2 £2 £2 £2 £2	The Line Line Line Line Line Line Line Lin
		ER.
╴ ╴ ╴ ╴ ╴ ╴ ╴ 、 、 、 、 、 、 、 、 、 、 、 、 、	╺┝┫┙╞┥╞┝┨┶┥╡┑┝┤┾┝╴╞╶┝┿┥┥┢╕┈╵┶╺╎╴╵╸╽╴╿┍╸┙┥╡┼└┽┥ ┅┫┫┝┲╅╅┶┤┱╘┤┇┝╅╼╘╶╞┿╆╴┟╌╍╺╒╕┍╌╄╶╶╵╸╎╕┼╸╸ ╊┨┿┟┺┲┫┥┯┝┧┥┥┲╕╞╍┥╅┥╴╺╼┥┥┥╴╴╴╸	UMEI CATICATI
	┍╴╽╸┹╺╴┍╌╸┍╴┶╴╸┙╸┶╼╌┍╶╌┶╸┺╴╸╴╸┍╸┶╸╸╸╸┙╸╸╸╸╸ ┶╴┛╺╾╸╸╺┶╌╸╴╺ ┱╴╴╴╴╴╴╴╴╴╴╴╴╴╴╴╴╴╴╴╴╴	ST N ST N ALE GNIE
		TEC SIZ
		┫╫╪╋╪┿┿┿┿┿╋┫┝┾╌┑╡┲┧┶┫╎╽╍┯┾╽┿┿┿┿ ┨╫╪╼╺╅╋┲╞┝╅┫╽╕╡╴╘┍╴║╺┍╼┍╺╼╌╄╪┿ ┨╫╪╸┽╅╘╬╘┍┧┖╅╸┥┝┨╕┑╽╘┨╍╷╎┿┥╋╼╼╸
		╉┶ ┇╡╪╞╪╪╪╪ ╪╪╞╡ ╪┿┿┿┿┿╪╪╪╪╪╪╪╪╪╪╪╪╪╪╪╪╪╪╪╪╪╪╪╪╪╪╪╪╪
		7
<u>.</u>	$\mathbf{H}_{\mathbf{r}}$	
	╕╴┫┥┿╺┝┶┿┝┝┙┿┿╈╎┙┿┿┿┝╖╸╖╴╴┿┿┿┿┿┿╸╷╴╴ ┇╴╴╢╴╴┿┿┿┿┿┿┿┿┿┿┿┿┿┿┿┿┿┿┿┿┿┿┿┿┿┿┿┿┿┿┿	- 1 + 1
		• • • • • • • • • • • • • • • • • • •
# # * * * # * # # # # # * # * # * * * *		
		╡┇┇┹╅┇╺┑╸╹┥╎┧┖╏╏╷┥┎┚╴╺┿╎╽╧╹┍┿┱╼╴ ╴╴╴╴╴╴╴╴╴╴╴╴╴╴╴╴
		<u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u></u> <u>_</u>
		┫╧╺╾┥╼┝┱╡╡╡╏┇╷╵┊┶╡┶╕╕╕╺┍╮┽┷┶╺┽┙╴ ┠╍┱┯┲╘┲╧╧╡┿┙╡╢╕┠╕╄┱╡┼╡╴┍╎╷╵╸╡╸╴╴
A	2 Fine prove the prove	\$ \$ { • \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$
		да са става и с Тради и става и Посто и става и Посто и става и
00	ę	ę
	PERCENT OF SCALE RANGE	
FORWARD	QAO.I	BEVERSE

("

ç



Material - Oil Tempered, QQ-M-428 Type I



in a service of the service of the

Material - Oil Tempered, QQ-W-428 Type I

FIGURE 14

1105 JA

Material - Stainless Steel, QQ-W-423 Comp. FS302

`...)

ò

FIGURE 15

DIVIDE BY MAGNIFICATION RATIO

STRAIN

N. N.

لمبه ا	100 2 500 11	The state of the s								ПŢ
-										
ليتجيسون				tricure 15					+	11
ممنعه	80									111
_				+ + + + + + + + + + + + + + + + + + + +						Ħ
										1.
										П
										• •
										++
										14
										[]-
	40			27 TH - 10	· · · · · · · · · · · · · · · · · · ·					ŦŦ
	24	pants ough - Eith								T
1		TOO THE TR						+ · · · · · · · · · · · · · · · · · · ·		Π
39										[]]
N								* * *		Ţ
A۶	120							***	$\begin{array}{c} + + \\ + + \\ + \\ + \\ + \\ + \\ + \\ + \\ + $	T
1										
37							* * * * * * * * * *			+
٧:										П
DS										Т
						╸╺╴╼╴╼╴╼╸╺╴╺╴╸╸				- • •
10										
1					M REFOURTU					1
IN:		HIGH HURLING					H			-11
30	0.0		· · · · · · · · · · · · · · · · · · ·							Ŧ
้ม								· · · · · · · · · · · · · · · · · · ·		.
ЪЕ										H
(· • • · · · · · · · · · · · · · · · · ·	4 001								Ŧ
										Щ
	40						TECT NIMPE	antita di		
							ICAL NUMBER			
							DATE			
							SITEM . 3207	"GAUGE I ENG	GTH 5,5"	
	leo									
							SCALE RANG	JE 0 - 200	LD. 20	
									001-	
							MAGNIFICAL	NU		
	80							***	,	
							Maturial -	Stainless St	1-N-00-N-4	ő
						· · · · · · · · · · · · · · · · · · ·		Comp. FS20		y
							, 1 1 1 1 1 1 1 1 1 1 1			
	001				A INI					

সহ '

1148 1177

^

Ņ

0



FIGURE 16

DIVIDE BY MAGNIFICATION RATIO



27

Material - Stainless Steel, QQ-W-423 Comp. 302

FIGURE 17

DIVIDE BY MAGNIFICATION RATIO

STRAIN



٠,

Material - Stainless Steel, QQ-W-423 Comp. FS316

8 FIGURE

DIVIDE BY MAGNIFICATION RATIO

STRAIN



29

A DE LE D



- Sta less Stee¹ Cum, FS316

ПЛАМЯОЧ

80

ł Ħ

1 - i j - - - -

1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 +

ΠĪ

<u>1111</u>

田中

61, ganoia

• • - | • • • • • • • • • • • • • •

٠.

111

1

411

nr ur st

i- (

Eland

11-

-++++

<u>†</u>1†

. . . 1

1+

Lil

A

[n]t= 120 fn.

Proportional Li

++

111

4144

1

rt.

4-4 / 14 |

÷Η



PERCENT OF SCALE RANGE

REVERSE

80



20 FIGURE

DIVIDE BY MAGNIFICATION RATIO

STRAIN



Material	Music Wire	Hard Drawn	Chrome Vanadium	0il Tempered	Sta in less Stee l	Stainless Steel
	QQ-W-470	QQ-W-428	QQ-W-412	ÇQ-W-428	FS 302	FS 316
Wire Size, in.	.200	.207	.207	.200	.207	.187
Initial Proportional Limit, in. 1b	150	150	06 t	150	001	100
Final Proportional Limit, in. lb	160	160	240,	150	140	120
Initial Elastic Limit, in. 1b	205	200	225	180	155	130
Final Elastic Limit, in. lb	250	250	275	220	200	150
Stress ač Initial Elastic Limit, psi	131,000	115,000	129,000	115,000	89,000	101,000
Stress at Final Elastic Limit, psi	159,000	144,000	158,000	140,000	115,000	117,000
Stress Increase at Elastic Limit Due to Strain Hardening, psi	28,000	29,000	29,000	25,000	26,000	16,000

TABLE 1

Ŕ



ž

FIGURE 21

DIVIDE BY MAGNIFICATION RATIO

STRAIN

<u>ت</u> .	100:							

		╪╪ ┽┽ ┽┽ ┽┽ ┽ ┽ ┽			Cantor at 1			
••••		╡┥ ┽┥ ┽┥ ╋┿┿ ╋┿					- + + - + - + + + + + + + + + + + +	
تب								
~								╺╋╸╬╌┪╺┿┥┫╍┿╸╞╌┡╸╋╌┠╸╢╌╣╸╋╍╋┿╋┿╋╺╗┙╝╺╸╌┨╸┾╺╸┫╴╢╸╸╴╴╴
** *					htra sinharia		Thefe Time	
 E								
							-22-20-20-	
	0							
			LL-Curve-					
								╌╱╶ ┇╌┇╌┨╴┇┎╻┇╌╗╌╸╶┨╶╝╌╗╌╞╌╒╴╶╶╶╗╺┓╺┓╺┓╺┥╸┇╴╻╹╕╋╸┇╶╺┙╸╸ ╖┟╴┇╴┇╌╽╴┓╍┧╌╗╴╻╌┱╼╶┨╶┶╌╼┈┝╌╸╶╶┝╌╗╼╋╌╋╶╋╴╋╴╌╸┶╴╋╌╖╾┽╴╉╶╼╍╄╶╋╼╼╌┲
	* * * * * * * * *							╺┋┷┠╍┟╌┲╌┢╾╉╌┱╌╌╌┟╴┠╌╃╌╉╌╋╌┲╌┲╌┲╌┲╌╋╴╋╶╉╴╉╴╉╴╋╴╋╌┾┲┿╌┝╍┺╌┅┲┳╉┅┲
				またして				╼┿┿┿╼╼╼╈┅╲╌╋╌┿╌┿╼┶╸╼╶┾╌┾╶╸╺╼┝╌╾╺┥╸┝╍┝╍┝┿┺╍┿╍┷╺┿╵┿╴┿╴┍╴┍╴╴ ╼╸┿╶╾╼┻╋┙╌┺╍╋┿╬╌┺╴╴╴┾╴╴╸╺╺┝╸╸╺
-								
19								
N						<u>╋╼╼╼╋</u> ╋╋╋		
٨	2002			· · · · · · · · · · · · · · · · · · ·		╶ ╉╌┹╶╉╌╬╴╈╶╋╴┿╌┽╾╬╴╽		╺╸╺╸╺╸╸╸╸╸╸╸╸╸╸╸╸╸╸╸╸╸╸╸╴╴╴╴╴╴╸╺╴╸╸╸╸╸╸╸
H	+ + + +							
Ξ								╼╴┲╾┲╼┲╌┲╸╶╴┲╌┲╼┲╴┇╌┇╌┨╌╸┲╍┱╌┨╌╸╺╴╺╸┫╶╅╌┲╼┺┅╊╌┳╍╦╌╌┨╌╴┨
יר								╶╋╌╋╸┣╍╋╍╋╺╉╌╀╍╋╍╄╸╊╌╿╴╋╌╋╌┩╴╉╸┫╺╄╸┫╶╌┙┩╶┱╴╋╘┅┡┉┫╶┿╸╘╶┥╶┿╴
¥2		╶╴╸╸╸╸╸╸╸╸╸╸╸╸						┍┯┽╴╋╍╡╌╬╌╬╍╋╍╊╍╊╍┨╺╈╶╋╼╉╌┇╴╶╴╶╎╶┨╴╬╴╉╌╬╌╃╸╋╍╠╍┇╶┺╶╋╶╉╴╋
)S								
10								
								╈╸╗╌╋╸╋╍╊╶┲╍╋╺╋╍╋╸┨╍┸╴╋╴╋╍╋╌┓╵╣╶╊╍╋╺╋╶┫╴╋╺╋╌┫╴╋╺╋╍┨╴┚╸╋╶╋╶╋╶╋╴┨╶┯╸
11								╈╌┥╼╦┾╋╴╘╸╋╸┥╸╽╴┆╌╣╌╎╌┝╌┝╼╡╌┝╴╣╶┝╶┝╍┿┺╧╶┝╴╛╴
13								┥╌┥┙┥╺┙╸┙┙╌┥╸╽╺┥╸╡╶┙╴┽╴╴╸╸╸╸╺╺╺╺╸┥╸╸╸╸╸╸╸╸╴╴╴╴╴╴╴
25	20							
EF								
d	· · · · · · · · · · · · · · · · · · ·							╈╍┿╍┾╌╋╌╋╍┿╸╌┫╌╸┷╍╼╼╋╾┫╸╋╍┿╌╋╼┽╼┝╼╏╌┿╼╏╾┿╍┝╍╍┙┙┥╶┿╍┥╌┿╴┿╸
				* * + + + + + + + + + + + + + + + + + +				
								TEST NUMBER. Twenty One.
	+ + + + + + + + + + + + + + + + + + +							
	÷							DATE
								SITEDIA : 2007AUGE LENGTH 5 5"
	60							United to way and the second s
								SCALE RANGE 0-500 In. Ib.
 1			**					
				* 1 * * * * * *				MAGNIFICALIANT AND A MAGNIFICATION
	80							Waterial-Misic Mire. 00-V-42-470
<u>.</u>		· · · · · · · · · · · · · · · · · · ·	· · · · · · · · · · · · · · · · · · ·					
-	• • • •							. Shot. Peened
13								
2				* * * * * * *				
1								

۱ م

¢

ۍ ۲۹۰



Naterial - Hard Drawn, QQ-W-428 Type II, Shot Peened



<u>URAWRO</u>

٤.

REVERSE

QQ-W-412

Chrome Vanadium, I, Shot Peened

Ι,

Comp.

Material -

23



ДЯА WЯОЯ

REVERSE

QQ-W-428

Oil Tempered, Shot Peened

Material -Type I

24



Material - Stainless Steel, QQ-W-423 Comp. FS302, Shot Peened



1.12

. 2

, î

1.

ा •्र

FIGURE 26

2

DIVIDE BY MAGNIFICATION RATIO

Castate Reality

in a string

10.00

34 -

	╏╕┪╎╅╍┝┼┶╺┠╞╎╽┍╼╎┝┾ ┠┼┽┥┝╕╛┾┟┝╢┿┝╄╧┿╷╅┿	┶╏┷┶╸┶╌┥╸┝┥╘┙╸╸╸╸╸╸┝┶┪┥╏┧┿┇╺┝╌┿╘┍ ┿╏┍┪╿┇╼┑┊╕┙╽┥┾┽┾┼┙┽┽╏┅╼┍┝┯┰┲┿	5-2
			H of
	<mark>┟┍╞┲╪╋╴┇┇╒┲╸╏┇╶┇┇╞╴</mark> ╌╌┾	▖▖▖▖▖▖ ▖▖ ▖▖▖▖ ▖ ▖ ▖ ▖ ▖ ▖ ▖ ▖ ▖ ▖ ▖ ▖	
			S I H H H H
$\begin{bmatrix} 1 + 4 + 4 + 4 + 4 + 4 + 4 + 4 + 4 + 4 +$	┫╪┿╪┷╪╷╲╷╈╏╎╷╏┍╏╸ ╅┿┲╧╲╆╏┿┻	ا مراجعة لاحدة المحالية المراجع المراجع المراجع المراجع المحدي المحدية المراجع المراجع المحدية المراجع المراجع المراجع المراجع المراجع المراجع المراجع ا المراجع المراجع	ent jin ot j
		······································	
		╸┇╭┋╺╒┇┇╼┍╍┋╴┇┲┰╞╈┲╞╈╄╸┝┿╍╌╌┺╴╸╸┇┇╸╛╺ ╸┇╭┋╺╒┇┇╼┍╍┋╴┇┲┲╒╴	SER J87 Star
			UME RAN ICA'
			PLA PLA
		╎╴╵┛┓╸ _╋ ╅╎╎┱╕╪ <mark>┱┥╕╸┿╤┯┥╴┇┍╸╴</mark> ┿╌┯╋╒╴╴	IES DATI SIZE SIZE SIZE AG
		╸┇╺┟┶╌┝╺┊┾╸┥┪╷╍╸┵╼╋╋┧┿┷╏╎╄╸┡╋╡╸╕╖╎ ╸╶╶╶╶╶╶╴╴╴╴╴╸╸╴╴╸╸╸╸╸ ╸╏┆╧╘╞╡╡╸┥┨╌┦┽┯╼╄╍	
			┥╅╪╪┇╞┱┰╪┎╹┱╪╎╪╡╏╺┱╕╖╻╌┿╡┿╅┽┯ ┍╴╴┰╶╴╡╴╴
······································		┙╋┥╛╪┽┿╪╪╼╴╛┶┑╡┱┇╪╕╛╆╏╧╶╺╴╸╸╶╻ ┺╋┽┺╪┽╡╴┺┺┊┇┑╊┆┷╄╴╺┿┽┨╘╸┆┍┺╪╤┪╸╽┆	
		╸ ┑╴╸╸╸╸╸╸╸╸╸╸╸╴╴╴ ┓╴╸╸╴╴╴╴╴ ┓╴╸╴╴╴╴╴╴╴╴╴╴	, , , , , , , , , , , , , , , , , , ,
╴ <mark>╏┽╪┿╕╪╧╪╪╪╞┟┆╷╷┊</mark> ┇╞╪╺┾╸ ┠┿┿╅┾┉┿┾┊╒╏┍╕┑╤┍┍╸			╡┪╧╇┯┥┷┇╼╏┿┇┆╡┪╵╼╕╎╏╲┶┿┿┽╕╞┥╊╴ ┑╴┙╸╕╕┯┶┯╌╴╞┍╴┇╴╶┱╸╻╸┶╻┿┷╷╷╅╄╴
			Z
		┥┥╅╖╬╗╬╪╪╪╪╪ ╡╹╪┿┿┿╪╪╪╪╪╴╪╴ ╡╵╪┿┿┿╪╪╪╪╴	
		┿ <mark>╎┽┼┑</mark> ┥╎┆╼╺┾┽┿╶╼╺╺╸╸╸╸╸ ╕┝┽┼┪╾╗╸╎╷╸┍┽╴╸┍╴╸╸╸╸╸╸╸	
			Ω
		╈╏╪╪┿╪╪╪╪╪╪╪╪╪╪╪╪╪╪╪╪╪╪╪╪╪╪╪ ╡╏┇╶┚┇╪╬╅╈┉┇╬╅┇╤╴╌╌╪┿╪╪╪╶╖╎╴╴╸╶╵ ╡┇┇╴╴	
		• • • • • • • • • • • • • • • • • • •	
······································			
		1989 2	
			
			· · · · · · · · · · · · · · · · · · ·
9			
Sittitue 9.111.111		TELEVISION OF SCHEREN	
ляамяоя	. 391	DERCENT OF SCALE DAN	REVERSE

¢

1.5

ţ

ί

Red Property

heis a state of the

North Contraction

1.1.1

TABLE 2

			hand		Chrome		011		stainless		stainless	
Material	Music Wir	a	Drawn		Vanadium		Tempered		Steel		steel	
	QQ-W-470		QQ-W-428		QQ-W-412		QQ-W-428		FS 302		FS 316	
	Not Shot Peened	Shot Peened	Not Shot Peaned	Shot Peened	Not Shot	Shot Peened	Not Shot Peened	Shot Peened	Not Shot Peened	Shot Peened	Not Shot Peened	Shot Peened
Wire Size in.	.200	.200	.207	.207	.207	.207	.200	.200	.207	.207	.187	.187
Initial Elastic Limit, in. lb	205	210	2.06	200	225	230	180	180	155	160	130	130
Final Elastic Limit, in. lb	250	255	250	250	275	285	220	220	200	205	150	160
Stress at Initia: Elastic Limit, psi	131,000	134,000	115,000	115,000	129,000	132,000	115,000	115,000	000 68	92,000	101,000	101,000
Stress at Final Elastic Limit, psi	159,000	163,000	14.4,000	144,000	158,000	164,000	140,000	140,000	115,000	118,000	117,000	125,000

Materiai - Hard Drawn, QQ-W-428 Type II

FIGURE 27

DIVIDE BY MAGNIFICATION RATIO

STRAIN

(100	A DECK AND A DECK								
ב	しうちとしてしてい									
ک										
ł										
4	sand a second and a second sec									
1										
٨										
/		and and the second seco								
15										
Ä			and the second second second				the same of the same of the			
(
0		+ 1 + + + + + + + + + + + + + + + + + +	many manager (man and and							
ł										
								~~~~~		
	60									
									L'ELASTIC L	
									Tet	
			• • • • • • • • • • • • • • • • • • • •		the second secon	Construction of the second sec				
					Trade as a family and a second second					
							1.5.1.5.1.5.1.5.1			
E		* * * * * * *								
อ		In the second se			***		Manana and Manata			
N										
N	20-00									
/2	2						T + + + + + + + +			
ł		· · · · · · · · · · · · · · · · · · ·								
1										
3.										
י <b>ר</b> ור										
4: 4:				~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~			and a serie of the			
כ וי					- Cratic and the set					
S									<u>★ -                                   </u>	
Ċ		· · · · · · · · · · · · · · · · · · ·		* * - * - ' *				a mana to prove an		
), F										
0										
{		X	The sector best and the sector best							
11			A second se							
N										
3										
3	120-120			DUXXXXX	Site in the second					
ี่ช		and and a second and and								
E										
d			T + 1 + 1 + + + + T	1 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2						
			**** ***							
									•	
			* * *					TEST NUMBE	ER. JWEDLY SI	even
				• • • •				         		
								NATE '		
				1 - 6 - 4 - 4 - m - 4 - 4				crrniia≜20		
				1				ジューディーション		
										-
			******					SCALE RANG	SEVDUV-J.n.	
1										
Ξ								MAGNIFICATI	ON 1 inch	- 10 ⁰
S										
52	180									
1		· · · · · · · · · · · · · · · · · · ·				· · · · · · · · · · · · · · · · · · ·				
3	***		· · · · · · · · · · · ·	· · · · · · · · ·				•		:::::::::::::::::::::::::::::::::::::::
/								Material-	Hard Urawo.	828-W-00
13										
E									TVDe II	
ษ		€ <del>/ * * </del> * · · <del>* * * * *</del> * *	فسهسهسه فاسد الهسوس			<u> </u>				
			l							

, T

ó

¢

. پ

### REFERENCES

1

- 1. Eshbach, O. W., <u>Handbook of Engineering Fundamentals</u>, John Wiley & Sons, Inc., New York, New York, 1936.
- Richards, C. W., <u>Engineering Materials Science</u>, Wadsworth Publishing Company, Inc., San Francisco, California, 1961

è,