

~~DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED.~~

DR-99
NOVEMBER 1966
AD

801391

METEOROLOGICAL DATA REPORT
NIKE-HYDAC MK 12 STV (SR-038)
(20 September 1966)

BY
JOHN M. SHARPE

ATMOSPHERIC SCIENCES LABORATORY
WHITE SANDS MISSILE RANGE, NEW MEXICO

.....
E COM

UNITED STATES ARMY ELECTRONICS COMMAND

D D C
RECORDED
NOV 8 1966
C

METEOROLOGICAL DATA REPORT

NIKE-HYDAC MK 12 STV (SR-038)
(20 September 1966)

By

John M. Sharpe

DR-99

November 1966

DA Task IV650212A127-02

ATMOSPHERIC SCIENCES LABORATORY
WHITE SANDS MISSILE RANGE, NEW MEXICO

~~Distribution of this document is unlimited.~~

ABSTRACT

Meteorological data gathered for the launching of Nike-Hydac, MK 12 STV (SR-038) are presented for the Air Force Ballistic Missile Re-entry Systems Office, the General Electric Company and for ballistic studies. The data appear, along with calculated ballistic data, in tabular form.

CONTENTS

	PAGE
ABSTRACT -----	iii
INTRODUCTION -----	1
DISCUSSION -----	1
TABLES	
I. Theoretical Rocket Performance Values -----	2
II. Ballistic Factors -----	3
III. Anemometer Wind Speed and Direction -----	4
IV. Pilot-Balloon-Measured Wind Data -----	5
V. Rawinsonde-Measured Wind Data -----	7
VI. Computer-Calculated Upper Air Data (Release Time: 0615 MST) -----	8
VII. Computer-Calculated Upper Air Data (Release Time: 0955 MST) -----	16
VIII. Impact Prediction Data -----	24

DISCLAIMER NOTICE

THIS DOCUMENT IS BEST QUALITY PRACTICABLE. THE COPY FURNISHED TO DTIC CONTAINED A SIGNIFICANT NUMBER OF PAGES WHICH DO NOT REPRODUCE LEGIBLY.

*OR are
Blank-pgs.
that have
Been Removed*

**BEST
AVAILABLE COPY**

INTRODUCTION

Nike-Hydac, MX 12 STV (SR-038) was launched from Launch Complex 33, I-314, White Sands Missile Range (WSMR), New Mexico, at 0913 hours MST, 20 September 1966.

Meteorological data used in conjunction with theoretical calculations to predict rocket impact were collected by the Meteorological Support Division, Atmospheric Sciences Laboratory (ASL), WSMR, New Mexico. The Ballistic Meteorologists for this firing were John M. Sharpe and SFC Leon H. Allen.

DISCUSSION

Wind data for the first 216 feet above the Surface were obtained from a system composed of 5 Aerovanes mounted on a 200-foot tower and cabled to component indicators.

From 216 to 4,000 feet above the surface, wind data were obtained from double-theodolite-observed balloon ascents.

Temperature, pressure, and humidity data, along with upper wind data from 4,000 to 80,738 feet above the surface, were obtained from standard rawinsonde observations.

Mean wind component values in each ballistic zone were determined from vertical cross sections by the equal-area method.

Theoretical rocket performance values and ballistic factors as a function of altitude were provided by ASL, and are the basis for data appearing in Table VIII.

PAYLOAD		210	Pounds
CORIOLIS DISPLACEMENT	WEST	5.0	Miles
SECOND-STAGE IGNITION	TIME	20.2	Seconds
	ALTITUDE	35,975	Feet MSL
PEAK	TIME	236.2	Seconds
	ALTITUDE	723,966	Feet MSL
UNIT WIND EFFECT	RANGE	2.295	MILES/MPH
	CROSS	2.211	MILES/MPH
TOWER TILT EFFECT		14.2	MILES/Degree

TABLE I. THEORETICAL ROCKET PERFORMANCE VALUES
NIKE-HYDAC, MK 12 STV (SR-036)

LAYERS IN FEET ABOVE GROUND	BALLISTIC FACTORS.
11- 60	.138
60- 108	.094
108- 148	.059
148- 184	.043
184- 216	.031
216- 300	.066
300- 400	.058
400- 600	.080
600- 800	.060
800-1000	.050
1000-1400	.075
1400-2000	.069

LAYERS IN FEET ABOVE GROUND	BALLISTIC FACTORS
2000- 2500	.035
2500- 3000	.024
3000- 3500	.014
3500- 4000	.005
4000- 4315	-.001
4315- 9000	-.015
9000-15000	-.018
15000-21000	-.016
21000-26000	-.014
26000-31975	-.005
31975-34000	.070

LAYERS IN FEET ABOVE GROUND	BALLISTIC FACTORS
34000-36000	.033
36000-41000	.036
41000-46000	.013
46000-51000	.006
51000-56000	.004
56000-61000	.003
61000-66000	.002
66000-72738	.001
72738-76000	-.000
76000-86000	-.000
86000-96000	-.000

TABLE II. BALLISTIC FACTORS.
NIKE-HYDAG, MK 12 STV (SR-038)

AERO-VANE NO. *	MEAN WIND COMPONENTS IN MILES PER HOUR									
	1 0700 MST		2 0730 MST		3 0800 MST		4 0815 MST		5 0830 MST	
	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W
1	0.0	0.0	3.0N	1.0E	2.0N	1.0W	1.0S	1.0E	1.0S	1.0E
2	1.0N	0.0	4.0	1.0	2.0	1.0	0.0	1.0W	1.0	1.0
3	2.0	0.0	3.0	1.0	2.0	2.0	0.0	2.0	2.0	1.0
4	3.0	0.0	4.0	1.0	3.0	0.0	1.0N	0.0	2.0	1.0
5	4.0	0.0	3.0	0.0	0.0	0.0	1.0	3.0W	1.0	1.0

AERO-VANE NO. *	MEAN WIND COMPONENTS IN MILES PER HOUR									
	6 0840 MST		7 0850 MST		8 0856 MST		9 0913 MST		10 0919 MST	
	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W
1	5.0S	2.0E	7.0S	5.0E	6.0S	1.0W	5.0S	1.0E	5.0S	7.0E
2	3.0	3.0	8.0	3.0	5.0	1.0	4.0	0.0	6.0	6.0
3	5.0	5.0	7.0	2.0	6.0	1.0	4.0	1.0E	6.0	4.0
4	4.0	7.0	6.0	5.0	7.0	2.0E	3.0	3.0	6.0	9.0
5	1.0	1.0	4.0	5.0	5.0	1.0E	4.0	1.0	5.0	5.0

TABLE III. ANEMOMETER WIND SPEED AND DIRECTION
NIKE-HYDAC, MK 12 STV (SR-058)

* Heights corresponding to Aerovane Numbers: 1 = 35 Feet 3 = 128 Feet 5 = 200 Feet
2 = 88 feet 4 = 168 feet

LAYERS IN FEET ABOVE GROUND	MEAN WIND COMPONENTS IN MILES PER HOUR											
	1 0700 MST		2 0730 MST		3 0800 MST		4 0815 MST		5 0830 MST			
	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W		
216-300	3.5N	1.0E	3.0N	1.0E	0.5N	1.0E	1.0N	1.5W	1.5S	2.5E		
300-400	2.0	3.0	2.5	3.5	1.0	2.5	0.0	2.0E	1.5	5.0		
400-600	0.0	5.5	2.0	3.0	0.0	3.0	0.5S	3.0	1.0	6.5		
600-800	0.5S	6.0	2.0	2.0	1.0S	3.5	1.0	3.0	1.0	6.5		
800-1000	1.5	7.0	2.0S	3.0	2.5	4.0	2.5	5.0	1.5	7.0		
1000-1400	1.0	6.0	3.0	7.0	4.0	5.5	4.0	8.5	3.5	8.5		
1400-2000	2.0N	3.0	0.0	8.0	1.5	0.0	4.0	7.0	5.0	8.0		
2000-2500	1.5	3.0	1.0N	6.5	2.0	4.0E	2.5	4.0	4.0	5.0		
2500-3000	1.5S	3.5	2.5S	4.0	4.0	2.5	5.0	3.0	4.0	3.0		
3000-4000	6.5	1.0	9.0	2.5	2.5	2.0	6.0	3.0	7.5	2.0		

TABLE IV. PILOT-BALLOON-MEASURED WIND DATA
NIKE-HYDAC, MK 12 STV (SR-038)

LAYERS IN FEET ABOVE GROUND	MEAN WIND COMPONENTS IN KNOTS PER HOUR											
	6		7		8		1-TIME 0919 MST		MST			
	0810 MST		0850 MST		0957 MST		0919 MST		MST			
	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W		
216-300	3.08	2.58	4.08	5.08	5.08	3.58	7.08	6.58				
300-400	5.0	5.0	4.5	5.0	5.0	2.0	8.0	8.0				
400-600	5.5	6.5	5.0	5.0	5.0	3.0	8.0	7.0				
600-800	4.0	6.5	5.0	4.5	5.5	4.0	7.5	6.0				
800-1000	3.5	6.0	5.0	3.5	6.0	5.0	8.0	6.0				
1000-1400	4.0	4.0	5.5	4.0	6.0	8.0	7.5	5.5				
1400-2000	7.0	5.5	6.0	5.0	6.0	9.0	5.5	3.5				
2000-2500	7.0	5.0	6.5	4.5	6.0	6.0	6.0	3.0				
2500-3000	5.0	3.5	6.5	1.5	7.0	3.5	7.0	3.5				
3000-4000	6.5	3.0	7.0	2.0	10.0	3.5	8.5	4.0				

TABLE IV. PILOT-BALLOON-MEASURED WIND DATA (Cont)

NIKE-HYDRO, MK 12 STV (SR-038)

LAYERS IN FEET ABOVE GROUND	MEAN WIND COMPONENTS IN KNOTS					
	0615 MST		0915 MST		1215 MST	
	N-S	E-W	N-S	E-W	N-S	E-W
4000-4315	5.08	1.0E	8.08	0.0	0.0	
4315- 9000	6.0	2.0	3.0	4.0E		
9000-15000	6.0	3.5	6.0N	7.0		
15000-21000	8.5N	3.0W	6.0	0.0		
21000-26000	12.5	9.5	10.5	9.0W		
26000-31975	7.5	20.5	10.5	18.0		
31975-34000	0.0	31.0	9.5	26.0		
34000-36000	0.0	33.0	10.0	27.0		
36000-41000	6.5N	36.5	5.5	32.5		
41000-46000	10.0	28.0	10.0	20.0		
46000-51000	15.0	2.5	0.0	14.0		
51000-56000	1.58	8.0E	1.58	8.5E		
56000-61000	2.5N	14.0	9.0	16.0		
61000-66000	6.0	17.0	0.0	13.0		
66000-72738	4.0	23.5	3.0N	15.5		

TABLE V. RAWINSONDE-MEASURED WIND DATA
NIKE-HYDAC, MK 12 STV (SR-038)

STATION ALTITUDE 3989.0 FEET MSL
 20 SEPT.66 0615 HRS MST
 ASCENSION NO. 726

UPPER AIR DATA
 0890003902
 WHITE SANDS SITE
 TABLE VI

WSTM SITE COORDINATES
 E 488,580 FEET
 N 185,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		RELATIVE HUMIDITY PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA		INDEX OF REFRACTION
		AIR DEGREES CENTIGRADE	DEWPOINT CENTIGRADE				DIRECTION DEGREES(TN)	SPEED KNOTS	
3989.0	881.8	16.3	14.8	90.0	1053.9	664.8	0.	0.	1.000310
4000.0	881.5	16.4	14.8	89.5	1053.1	665.0	0.	0.0	1.000310
4500.0	866.0	19.3	14.4	72.8	1024.2	668.3	34.5	0.7	1.000301
5000.0	850.7	18.8	13.1	69.0	1008.4	667.6	68.3	1.5	1.000291
5500.0	835.7	18.3	11.7	65.2	992.9	666.8	102.1	2.2	1.000283
6000.0	821.0	17.8	10.4	61.4	977.5	666.1	135.8	2.9	1.000274
6500.0	806.6	17.3	8.9	57.6	962.4	665.4	158.6	4.3	1.000266
7000.0	792.4	16.8	7.4	53.8	947.6	664.6	174.0	6.0	1.000258
7500.0	778.4	16.3	6.3	51.4	932.8	663.9	181.4	6.9	1.000251
8000.0	764.6	15.7	6.2	53.0	917.9	663.4	187.6	7.4	1.000248
8500.0	751.0	14.9	6.0	55.7	904.1	662.4	191.2	6.8	1.000245
9000.0	737.5	13.5	6.0	60.4	892.1	660.8	189.3	5.9	1.000242
9500.0	724.2	12.1	5.8	65.2	880.4	659.2	181.2	4.7	1.000238
10000.0	711.2	10.7	5.5	69.9	868.8	657.6	165.3	4.3	1.000236
10500.0	698.4	9.3	5.1	74.6	857.4	656.0	145.0	4.5	1.000233
11000.0	685.8	7.8	1.6	65.0	847.3	653.9	129.2	4.8	1.000222
11500.0	673.2	6.6	0.8	66.4	835.5	652.4	115.4	5.2	1.000217
12000.0	660.8	5.4	-0.1	67.8	823.8	651.0	113.5	6.0	1.000213
12500.0	648.7	4.2	-1.5	66.3	812.2	649.5	115.3	7.0	1.000208
13000.0	636.6	3.3	-2.9	64.1	800.1	648.3	114.4	8.0	1.000203
13500.0	624.8	2.2	-2.2	72.9	788.2	647.1	113.1	9.0	1.000202
14000.0	613.1	1.2	-5.4	61.3	776.6	645.8	116.5	10.5	1.000194
14500.0	601.6	0.2	-9.1	49.7	765.3	644.4	119.2	11.7	1.000186
15000.0	590.3	-0.9	-9.5	52.1	754.0	643.1	119.3	11.4	1.000183
15500.0	579.1	-2.1	-9.5	56.8	742.9	641.7	123.1	10.4	1.000181
16000.0	568.2	-2.8	-13.7	43.1	731.2	640.7	130.9	8.6	1.000174
16500.0	557.3	-3.4	-20.5	25.5	719.2	639.8	146.9	6.1	1.000167
17000.0	546.7	-4.0	-31.2	10.0	707.4	639.0	165.8	3.5	1.000160
17500.0	536.3	-4.7	-16.1	40.7	695.1	638.4	202.6	2.7	1.000164
18000.0	526.0	-5.4	-28.0	15.1	684.0	637.3	240.1	2.4	1.000156

STATION ALTITUDE 3989.0 FEET MSL
 20 SEPT.66 0615 HRS MST
 ASCENSION NO. 726

UPPER AIR DATA
 0890003902
 WHITE SANDS SITE
 TABLE VI (Cont)

WSTM SITE COORDINATES
 E 488,580 FEET
 N 185,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		RELATIVE HUMIDITY PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA		INDEX OF REFRACTION
		AIR DEGREES	DEWPOINT CENTIGRADE				DIRECTION DEGREES(TN)	SPEED KNOTS	
18500.0	515.8	-6.3	-23.7	23.8	673.0	636.3	276.7	3.9	1.000155
19000.0	505.9	-7.1	-20.9	32.5	662.0	635.3	304.0	5.2	1.000154
19500.0	496.1	-8.0	-19.0	41.2	651.3	634.4	313.0	6.0	1.000152
20000.0	486.5	-9.0	-18.4	46.9	641.0	633.2	321.7	7.4	1.000151
20500.0	477.0	-9.9	-21.1	39.9	630.8	632.0	330.1	9.2	1.000147
21000.0	467.7	-10.8	-25.4	28.9	620.6	630.9	339.7	9.8	1.000142
21500.0	458.5	-11.6	-31.3	18.0	610.6	629.8	348.7	10.3	1.000138
22000.0	449.5	-12.5	-37.3	10.6	600.8	628.7	353.3	10.6	1.000135
22500.0	440.5	-13.7	-36.3	13.0	591.5	627.2	356.5	10.7	1.000133
23000.0	431.7	-14.9	-35.7	15.3	582.4	625.8	355.9	10.0	1.000131
23500.0	423.1	-16.1	-35.3	17.6	573.5	624.3	353.9	9.6	1.000129
24000.0	414.7	-17.3	-35.0	20.0	564.7	622.9	349.3	9.4	1.000128
24500.0	406.4	-18.5	-35.0	22.3	556.0	621.4	1.7	17.1	1.000126
25000.0	398.2	-19.6	-37.3	19.3	547.0	620.1	34.3	33.9	1.000123
25500.0	390.1	-20.5	-41.1	14.1	537.9	619.0	24.5	31.5	1.000121
26000.0	382.2	-21.4	-45.0	10.0	529.0	617.8	346.3	16.1	1.000118
26500.0	374.3	-22.5	-45.9	10.0	520.2	616.5	333.5	13.2	1.000116
27000.0	366.5	-23.5	-46.7	10.0	511.5	615.3	327.0	14.3	1.000114
27500.0	359.0	-24.5	-47.5	10.0	503.0	614.0	287.4	32.0	1.000113
28000.0	351.5	-25.6	-48.3	10.0	494.7	612.7	269.4	38.4	1.000111
28500.0	344.3	-26.6	-49.2	10.0	486.5	611.4	294.9	21.6	1.000109
29000.0	337.1	-27.6	-50.0	10.0	478.4	610.1	303.8	15.3	1.000107
29500.0	330.2	-28.7	-50.8	10.0	470.5	608.8	302.8	15.3	1.000105
30000.0	323.1	-30.0	-52.7	9.0**	462.8	607.2	301.3	16.1	1.000103
30500.0	316.1	-31.3	-54.8	8.0**	455.3	605.6	300.1	16.7	1.000102
31000.0	309.3	-32.6	-56.9	7.0**	447.9	603.9	299.8	16.8	1.000100
31500.0	302.6	-33.9	-59.1	6.0**	440.6	602.3	298.5	17.6	1.000098
32000.0	296.1	-35.2	-61.6	5.0**	433.5	600.7	296.3	19.0	1.000097
32500.0	289.7	-36.5	-64.2	4.0**	426.5	599.0	293.8	20.3	1.000095
33000.0	283.5	-37.8	-67.3	2.9**	419.6	597.4	291.2	21.6	1.000093

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL
 20 SEPT. 66 0615 HRS MST
 ASCENSION NO. 726

UPPER AIR DATA
 08900003902
 WHITE SANDS SITE
 TABLE VI (Cont)

WSTM SITE COORDINATES
 E 488,580 FEET
 N 185,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		RELATIVE HUMIDITY PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA		INDEX OF REFRACTION
		AIR DEGREES	DEWPOINT CENTIGRADE				DIRECTION DEGREES(TN)	SPEED KNOTS	
33500.0	277.3	-39.1	-71.2	1.9**	412.9	595.7	288.6	23.2	1.000092
34000.0	271.4	-40.4	-76.9	0.9**	406.2	594.0	285.9	24.7	1.000090
34500.0	265.5	-41.7	0.	0.	399.7	592.4	282.5	25.7	1.000089
35000.0	259.6	-42.9	0.	0.	392.7	590.9	280.2	26.6	1.000087
35500.0	253.8	-44.0	0.	0.	385.9	589.4	279.6	27.2	1.000086
36000.0	248.1	-45.2	0.	0.	379.2	587.9	277.7	28.7	1.000084
36500.0	242.5	-46.4	0.	0.	372.6	586.4	275.1	30.8	1.000083
37000.0	236.9	-47.4	0.	0.	365.6	585.1	274.2	32.1	1.000081
37500.0	231.5	-48.3	0.	0.	358.7	583.8	273.7	33.2	1.000080
38000.0	225.1	-49.3	0.	0.	352.0	582.5	273.0	34.5	1.000078
38500.0	220.9	-50.3	0.	0.	345.4	581.3	272.3	35.8	1.000077
39000.0	215.8	-51.3	0.	0.	338.9	580.0	273.5	36.3	1.000075
39500.0	210.8	-52.3	0.	0.	332.6	578.7	275.0	36.7	1.000074
40000.0	206.0	-53.3	0.	0.	326.3	577.4	276.3	37.6	1.000073
40500.0	201.2	-54.2	0.	0.	320.2	576.1	277.5	38.6	1.000071
41000.0	196.6	-55.2	0.	0.	314.3	574.8	279.5	38.5	1.000070
41500.0	192.0	-56.2	0.	0.	308.4	573.5	281.3	38.4	1.000069
42000.0	187.4	-57.3	0.	0.	302.5	572.0	282.5	38.3	1.000067
42500.0	182.8	-58.5	0.	0.	296.7	570.5	283.8	38.3	1.000066
43000.0	178.4	-59.6	0.	0.	291.1	569.1	285.3	38.5	1.000065
43500.0	174.1	-60.7	0.	0.	285.6	567.6	285.7	38.4	1.000064
44000.0	170.0	-61.8	0.	0.	280.2	566.1	285.7	38.1	1.000062
44500.0	165.9	-62.9	0.	0.	274.8	564.6	285.4	37.3	1.000061
45000.0	161.9	-64.0	0.	0.	269.7	563.1	285.0	36.3	1.000060
45500.0	158.0	-65.1	0.	0.	264.6	561.6	284.9	34.3	1.000059
46000.0	154.1	-65.2	0.	0.	258.2	561.5	284.1	32.5	1.000057
46500.0	150.3	-65.3	0.	0.	251.9	561.4	284.5	31.5	1.000056
47000.0	146.6	-66.3	0.	0.	246.9	560.0	285.3	30.3	1.000055
47500.0	142.9	-67.6	0.	0.	242.1	558.5	286.9	28.2	1.000054
48000.0	139.4	-68.5	0.	0.	237.3	557.0	288.4	26.2	1.000053

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

UPPER AIR DATA
 0890003902
 WHITE SANDS SITE
 TABLE VI (Cont)

STATION ALTITUDE 3989.0 FEET MSL
 20 SEPT.66 0615 HRS MST
 ASCENSION NO. 726

WSTM SITE COORDINATES
 E 488,580 FEET
 N 185,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		RELATIVE HUMIDITY PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA		INDEX OF REFRACTION
		AIR DEGREES	DEWPOINT CENTIGRADE				DIRECTION DEGREES(TN)	SPEED KNOTS	
48500.0	135.9	-69.5	0.	-0. **	232.5	555.7	289.4	24.6	1.000052
49000.0	132.5	-70.1	0.	-0. **	227.3	554.9	290.3	22.9	1.000051
49500.0	129.1	-70.7	0.	-0. **	222.2	554.0	291.2	21.3	1.000049
50000.0	125.8	-71.3	0.	-0. **	217.2	553.2	295.0	20.3	1.000048
50500.0	122.7	-71.9	0.	-0. **	212.3	552.4	302.0	20.1	1.000047
51000.0	119.6	-72.5	0.	-0. **	207.6	551.6	309.1	19.5	1.000046
51500.0	116.5	-73.2	0.	-0. **	203.0	550.6	316.3	18.6	1.000045
52000.0	113.5	-73.9	0.	-0. **	198.5	549.6	326.1	16.8	1.000044
52500.0	110.6	-73.8	0.	-0. **	193.3	549.8	338.2	14.2	1.000043
53000.0	107.8	-72.6	0.	-0. **	187.3	551.4	355.2	11.2	1.000042
53500.0	105.1	-71.5	0.	-0. **	181.5	553.0	16.0	7.8	1.000040
54000.0	102.4	-70.6	0.	-0. **	176.2	554.1	37.6	6.7	1.000039
54500.0	99.8	-70.9	0.	-0. **	171.9	553.8	59.5	6.8	1.000038
55000.0	97.3	-70.7	0.	-0. **	167.5	554.0	75.3	7.3	1.000037
55500.0	94.9	-69.6	0.	-0. **	162.4	555.5	90.1	8.0	1.000036
56000.0	92.5	-68.5	0.	-0. **	157.5	557.0	104.7	8.5	1.000035
56500.0	90.2	-67.4	0.	-0. **	152.7	558.5	118.1	9.0	1.000034
57000.0	88.0	-66.3	0.	-0. **	148.1	560.0	127.9	9.8	1.000033
57500.0	85.8	-65.3	0.	-0. **	143.8	561.4	130.6	10.2	1.000032
58000.0	83.7	-65.2	0.	-0. **	140.2	561.5	123.2	10.1	1.000031
58500.0	81.6	-65.1	0.	-0. **	136.7	561.6	112.9	10.2	1.000030
59000.0	79.6	-65.0	0.	-0. **	133.3	561.8	100.0	10.4	1.000030
59500.0	77.7	-64.9	0.	-0. **	129.9	561.9	92.4	11.0	1.000029
60000.0	75.8	-64.8	0.	-0. **	126.7	562.0	87.7	12.0	1.000028
60500.0	73.9	-64.7	0.	-0. **	123.5	562.2	84.0	11.5	1.000028
61000.0	72.1	-64.6	0.	-0. **	120.4	562.3	80.6	10.5	1.000027
61500.0	70.3	-64.1	0.	-0. **	117.3	562.9	78.2	11.1	1.000026
62000.0	68.7	-63.7	0.	-0. **	114.2	563.6	76.2	12.5	1.000025
62500.0	67.0	-63.2	0.	-0. **	111.2	564.2	75.6	14.2	1.000025
63000.0	65.4	-62.7	0.	-0. **	108.3	564.9	75.9	16.2	1.000024

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

UPPER AIR DATA
 0890003902
 WHITE SANDS SITE
 TABLE 71 (Cont)

STATION ALTITUDE 3989.0 FEET MSL
 20 SEPT. 66 0615 HRS MST
 ASCENSION NO. 726

WSTM SITE COORDINATES
 E 488,580 FEET
 N 185,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		RELATIVE HUMIDITY PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA		INDEX OF REFRACTION
		AIR DEGREES	DEWPOINT DEGREES				DIRECTION DEGREES (TN)	SPEED KNOTS	
63500.0	63.8	-62.2	0.	-0. **	105.4	565.5	77.2	17.4	1.000023
64000.0	62.3	-61.7	0.	-0. **	102.6	566.2	79.5	17.8	1.000023
64500.0	60.8	-61.2	0.	-0. **	99.9	566.9	79.5	17.7	1.000022
65000.0	59.3	-60.7	0.	-0. **	97.3	567.5	76.6	16.6	1.000022
65500.0	57.9	-60.2	0.	-0. **	94.8	568.1	71.5	15.7	1.000021
66000.0	56.5	-59.8	0.	-0. **	92.3	568.8	63.0	14.8	1.000021
66500.0	55.2	-59.3	0.	-0. **	89.9	569.4	57.3	14.5	1.000020
67000.0	53.8	-58.8	0.	-0. **	87.5	570.1	56.0	15.1	1.000019
67500.0	52.5	-58.3	0.	-0. **	85.2	570.7	56.9	15.2	1.000019
68000.0	51.3	-57.8	0.	-0. **	83.0	571.4	61.3	14.5	1.000018
68500.0	50.0	-57.3	0.	-0. **	80.8	572.0	68.5	13.9	1.000018
69000.0	48.8	-56.8	0.	-0. **	78.7	572.7	80.5	13.4	1.000018
69500.0	47.7	-56.5	0.	-0. **	76.7	573.1	90.3	13.2	1.000017
70000.0	46.6	-56.5	0.	-0. **	74.9	573.1	95.8	13.3	1.000017
70500.0	45.5	-56.5	0.	-0. **	73.1	573.1	99.2	13.5	1.000016
71000.0	44.4	-56.5	0.	-0. **	71.4	573.1	97.9	14.0	1.000016
71500.0	43.3	-56.5	0.	-0. **	69.7	573.1	95.6	14.5	1.000016
72000.0	42.3	-56.5	0.	-0. **	68.1	573.1	91.0	14.8	1.000015
72500.0	41.3	-56.5	0.	-0. **	66.4	573.1	86.1	15.4	1.000015
73000.0	40.3	-56.5	0.	-0. **	64.9	573.1	80.4	16.7	1.000014
73500.0	39.4	-56.5	0.	-0. **	63.4	573.1	75.4	17.9	1.000014
74000.0	38.5	-56.1	0.	-0. **	61.8	573.6	73.8	18.5	1.000014
74500.0	37.6	-55.4	0.	-0. **	60.1	574.5	72.3	19.1	1.000013
75000.0	36.7	-54.8	0.	-0. **	58.5	575.4	75.7	20.5	1.000013
75500.0	35.8	-54.1	0.	-0. **	57.0	576.3	79.3	21.8	1.000013
76000.0	35.0	-53.4	0.	-0. **	55.5	577.2	83.0	21.4	1.000012
76500.0	34.2	-52.8	0.	-0. **	54.0	578.1	86.7	20.0	1.000012
77000.0	33.4	-52.6	0.	-0. **	52.7	578.3	90.1	18.7	1.000012
77500.0	32.6	-52.5	0.	-0. **	51.5	578.4	92.9	17.5	1.000011
78000.0	31.9	-52.4	0.	-0. **	50.3	578.5	95.4	16.2	1.000011

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL
 20 SEPT.66 0615 HRS MST
 ASCENSION NO. 726

UPPER AIR DATA
 0090003902
 WHITE SANDS SITE
 TABLE VI (Cont)

WSTM SITE COORDINATES
 E 488,580 FEET
 N 185,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		RELATIVE HUMIDITY PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND		WIND DATA		INDEX OF REFRACTION
		AIR DEGREES	DEWPOINT CENTIGRADE			KNOTS	KNOTS	DIRECTION DEGREES(TN)	SPEED KNOTS	
78500.0	31.1	-52.4	0.	-0. **	49.1	578.6	37.6	14.4	1.000011	
79000.0	30.4	-52.3	0.	-0. **	48.0	578.6	79.8	12.5	1.000011	
79500.0	29.7	-52.3	0.	-0. **	46.9	578.7	75.0	12.1	1.000010	
80000.0	29.0	-52.2	0.	-0. **	45.8	578.8	71.3	12.2	1.000010	
80500.0	28.4	-51.7	0.	-0. **	44.6	579.5	68.1	12.6	1.000010	
81000.0	27.7	-51.2	0.	-0. **	43.5	580.1	65.7	13.4	1.000010	
81500.0	27.1	-50.6	0.	-0. **	42.4	580.8	63.3	14.2	1.000009	
82000.0	26.5	-50.1	0.	-0. **	41.3	581.5	64.2	14.8	1.000009	
82500.0	25.9	-49.6	0.	-0. **	40.3	582.2	65.9	15.4	1.000009	
83000.0	25.3	-49.1	0.	-0. **	39.3	582.9	67.6	15.9	1.000009	
83500.0	24.7	-48.5	0.	-0. **	38.3	583.6	68.6	16.4	1.000009	
84000.0	24.1	-48.0	0.	-0. **	37.4	584.2	69.6	16.9	1.000008	
84500.0	23.6	-47.5	0.	-0. **	36.4	584.9	71.0	17.3	1.000008	
85000.0	23.0	-47.0	0.	-0. **	35.5	585.6	73.8	17.0	1.000008	
85500.0	22.5	-46.4	0.	-0. **	34.6	586.3	76.5	16.7	1.000008	
86000.0	22.0	-45.9	0.	-0. **	33.7	587.0	80.9	15.9	1.000008	
86500.0	21.5	-45.9	0.	-0. **	33.0	587.0	87.0	14.6	1.000007	
87000.0	21.0	-45.9	0.	-0. **	32.2	587.0	93.0	13.3	1.000007	
87500.0	20.6	-45.9	0.	-0. **	31.5	587.0	96.8	12.5	1.000007	
88000.0	20.1	-45.9	0.	-0. **	30.8	587.0	99.6	12.0	1.000007	
88500.0	19.6	-45.9	0.	-0. **	30.1	587.0	102.5	11.4	1.000007	
89000.0	19.2	-45.9	0.	-0. **	29.4	587.0	105.3	10.6	1.000007	
89500.0	18.8	-45.9	0.	-0. **	28.8	587.0	108.1	9.7	1.000006	
90000.0	18.4	-45.9	0.	-0. **	28.1	587.0	109.7	8.9	1.000006	
90500.0	17.9	-45.9	0.	-0. **	27.5	587.0	102.5	8.7	1.000006	
91000.0	17.5	-45.9	0.	-0. **	26.9	587.0	95.2	8.6	1.000006	
91500.0	17.1	-45.9	0.	-0. **	26.3	587.0	87.8	8.3	1.000006	
92000.0	16.8	-45.9	0.	-0. **	25.7	587.0	80.0	7.7	1.000006	
92500.0	16.4	-45.9	0.	-0. **	25.1	587.0	72.3	7.1	1.000006	
93000.0	16.0	-45.9	0.	-0. **	24.6	587.0	64.3	6.8	1.000005	

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

UPPER AIR DATA
0890003902
WHITE SANDS SITE
TABLE VI (Cont)

STATION ALTITUDE 3989.0 FEET MSL
20 SEPT.66 0615 HRS MST
ASCENSION NO. 726

WSM SITE COORDINATES
E 488,580 FEET
N 135,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	AIR TEMPERATURE DEGREES CENTIGRADE	RELATIVE HUMIDITY PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DIRECTION DEGREES (TND)	WIND SPEED KNOTS	INDEX OF REFRACTION
93500.0	15.7	-45.5	-0. **	24.0	587.4	55.7	7.4	1.000005
94000.0	15.3	-45.2	-0. **	23.4	587.9	47.1	8.0	1.000005
94500.0	15.0	-44.8	-0. **	22.9	588.4	38.4	8.6	1.000005
95000.0	14.7	-44.4	-0. **	22.3	588.9	33.1	9.3	1.000005
95500.0	14.3	-44.1	-0. **	21.8	589.3	30.4	10.2	1.000005
96000.0	14.0	-43.7	-0. **	21.3	589.8	27.6	11.0	1.000005
96500.0	13.7	-43.3	-0. **	20.8	590.3	24.9	11.9	1.000005
97000.0	13.4	-43.0	-0. **	20.3	590.8	23.3	12.7	1.000005
97500.0	13.1	-42.6	-0. **	19.8	591.2	24.1	13.6	1.000004
98000.0	12.8	-42.2	-0. **	19.4	591.7	24.8	14.5	1.000004
98500.0	12.6	-41.8	-0. **	18.9	592.2	25.6	15.4	1.000004
99000.0	12.3	-41.5	-0. **	18.5	592.7	26.4	16.3	1.000004
99500.0	12.0	-41.1	-0. **	18.0	593.1	27.8	16.9	1.000004
100000.0	11.8	-40.7	-0. **	17.6	593.6	29.2	17.5	1.000004
100500.0	11.5	-40.4	-0. **	17.2	594.1	30.5	18.2	1.000004
101000.0	11.2	-40.0	-0. **	16.8	594.6	31.9	18.8	1.000004
101500.0	11.0	-39.6	-0. **	16.4	595.0	32.4	19.4	1.000004
102000.0	10.8	-39.3	-0. **	16.0	595.5	32.8	20.0	1.000004
102500.0	10.5	-38.9	-0. **	15.6	596.0	33.2	20.6	1.000003
103000.0	10.3	-38.5	-0. **	15.3	596.4	33.6	21.2	1.000003
103500.0	10.1	-38.1	-0. **	14.9	596.9	34.6	21.2	1.000003
104000.0	9.8	-37.8	-0. **	14.6	597.4	35.8	20.9	1.000003
104500.0	9.6	-37.4	-0. **	14.2	597.9	37.1	20.6	1.000003
105000.0	9.4	-37.0	-0. **	13.9	598.3	38.3	20.3	1.000003
105500.0	9.2	-36.7	-0. **	13.6	598.8	41.0	20.2	1.000003
106000.0	9.0	-36.3	-0. **	13.3	599.3	45.4	20.6	1.000003
106500.0	8.8	-35.9	-0. **	12.9	599.7	49.8	20.9	1.000003
107000.0	8.6	-35.6	-0. **	12.6	600.2	54.1	21.2	1.000003
107500.0	8.4	-35.2	-0. **	12.3	600.7	59.3	21.2	1.000003
108000.0	8.2	-34.8	-0. **	12.1	601.1	66.8	20.3	1.000003

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL
 20 SEPT.66 0615 HRS MST
 ASCENSION NO. 726

UPPER AIR DATA
 0890003902
 WHITE SANDS SITE
 TABLE VI (Cont)

WSTM SITE COORDINATES
 E 488,580 FEET
 N 185,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE AIR DEGREES CENTIGRADE	RELATIVE HUMIDITY PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA		INDEX OF REFRACTION
						DIRECTION DEGREES(TN)	SPEED KNOTS	
108500.0	8.1	-34.4	-0. **	11.8	601.6	74.3	19.4	1.000003
109000.0	7.9	-34.2	-0. **	11.5	601.9	81.8	18.4	1.000003
109500.0	7.7	-34.1	-0. **	11.3	602.0	89.4	17.5	1.000003
110000.0	7.6	-34.0	-0. **	11.0	602.1	97.1	17.1	1.000002
110500.0	7.4	-33.9	-0. **	10.8	602.2	104.8	16.8	1.000002
111000.0	7.2	-33.9	-0. **	10.5	602.3	112.5	16.4	1.000002
111500.0	7.1	-33.8	-0. **	10.3	602.5	120.2	16.1	1.000002
112000.0	6.9	-33.7	-0. **	10.1	602.6			1.000002
112500.0	6.8	-33.6	-0. **	9.9	602.7			1.000002
113000.0	6.6	-33.5	-0. **	9.7	602.8			1.000002
113500.0	6.5	-33.4	-0. **	9.5	603.0			1.000002
114000.0	6.4	-33.3	-0. **	9.2	603.1			1.000002
114500.0	6.2	-33.2	-0. **	9.0	603.2			1.000002
115000.0	6.1	-33.1	-0. **	8.9	603.3			1.000002

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

UPPER AIR DATA
0890003903
WHITE SANDS SITE
TABLE VII

STATION ALTITUDE 3989.0 FEET MSL
20 SEPT.66 0955 HRS MST
ASCENSION NO. 728

MSTM SITE COORDINATES
E 488,580 FEET
N 185,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE AIR DEGREES	TEMPERATURE DEWPOINT DEGREES	RELATIVE HUMIDITY PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA		INDEX OF REFRACTION
							DIRECTION DEGREES(TN)	SPEED KNOTS	
3989.0	883.1	26.4	15.9	52.0	1019.3	676.3	120.0	5.1	1.000303
4000.0	882.8	26.3	15.7	51.7	1019.3	676.4	120.1	5.1	1.000302
4500.0	867.5	23.0	9.9	43.3	1015.1	671.9	126.8	5.6	1.000279
5000.0	852.3	21.7	9.9	46.9	1001.7	670.4	133.5	6.2	1.000276
5500.0	837.5	20.4	9.8	50.4	988.5	669.0	140.1	6.8	1.000274
6000.0	822.8	19.1	9.6	54.0	975.6	667.5	146.8	7.4	1.000270
6500.0	808.4	17.8	9.4	57.6	962.9	666.0	153.4	8.0	1.000267
7000.0	794.2	16.3	9.1	62.1	951.0	664.2	168.2	7.3	1.000264
7500.0	780.1	14.3	8.6	68.4	940.4	662.0	185.2	6.1	1.000261
8000.0	766.2	13.6	6.7	62.9	926.5	660.9	187.1	5.8	1.000252
8500.0	752.5	13.6	4.5	54.1	910.5	660.7	190.3	4.9	1.000242
9000.0	739.0	12.8	4.4	56.2	896.5	659.9	188.3	3.8	1.000238
9500.0	725.7	12.1	4.2	58.3	882.8	659.0	169.3	2.8	1.000235
10000.0	712.6	10.7	3.6	61.3	871.0	657.4	143.7	2.5	1.000231
10500.0	699.7	9.0	2.8	64.8	860.5	655.4	118.7	2.7	1.000227
11000.0	687.0	7.9	1.6	64.4	848.5	654.0	99.3	3.8	1.000222
11500.0	674.5	7.5	-0.2	58.1	834.4	653.5	92.4	4.9	1.000215
12000.0	662.0	6.3	-1.0	59.5	822.9	651.9	90.5	6.1	1.000211
12500.0	649.9	5.0	-1.9	61.0	811.5	650.4	95.1	7.4	1.000207
13000.0	637.9	3.7	-2.8	62.5	800.4	648.9	100.4	8.6	1.000203
13500.0	626.1	2.9	-9.6	39.2	788.6	647.6	106.4	9.6	1.000190
14000.0	614.3	1.8	-11.0	38.0	777.1	646.2	112.1	9.8	1.000186
14500.0	602.8	0.6	-11.4	40.3	765.9	644.8	117.0	9.2	1.000184
15000.0	591.5	-0.5	-11.8	42.5	754.8	643.4	119.7	6.6	1.000181
15500.0	580.4	-0.8	-10.4	25.0	741.8	642.9	98.0	3.5	1.000173
16000.0	569.4	-1.5	-21.1	20.9	729.8	642.0	62.7	0.9	1.000168
16500.0	558.5	-2.4	-21.3	22.1	718.3	640.9	6.4	3.6	1.000166
17000.0	547.9	-3.4	-21.5	23.2	707.0	639.8	344.6	5.8	1.000163
17500.0	537.5	-4.3	-21.7	24.4	696.0	638.7	354.3	7.5	1.000161
18000.0	527.2	-5.2	-22.0	25.5	685.1	637.6	358.1	8.5	1.000158

STATION ALTITUDE 3989.0 FEET MSL
 20 SEPT.66
 ASCENSION NO. 728

UPPER AIR DATA
 0890003903
 WHITE SANDS SITE
 TABLE VII (Cont)

WSTM SITE COORDINATES
 E 485,580 FEET
 N 1/5,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		RELATIVE HUMIDITY PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA		INDEX OF REFRACTION
		AIR DEGREES	DEWPOINT CENTIGRADE				DIRECTION DEGREES(TN)	SPEED KNOTS	
18500.0	517.1	-6.9	-18.2	40.4	676.0	535.7	0.8	9.1	1.000158
19000.0	507.1	-8.0	-21.4	33.5	685.8	634.3	3.2	8.8	1.000154
19500.0	497.3	-9.1	-21.4	36.2	655.6	633.0	7.6	7.8	1.000152
20000.0	487.6	-10.1	-18.8	49.2	645.1	631.8	13.5	6.4	1.000151
20500.0	478.0	-10.8	-24.0	33.1	634.4	630.9	24.8	6.2	1.000146
21000.0	468.6	-11.6	-27.2	26.3	623.9	629.9	32.0	5.8	1.000143
21500.0	459.4	-12.3	-31.1	19.4	613.5	629.0	35.1	5.1	1.000139
22000.0	450.4	-13.2	-32.6	18.0	603.5	627.9	25.7	4.2	1.000137
22500.0	441.4	-14.2	-31.4	21.9	593.7	626.7	9.7	3.2	1.000135
23000.0	432.7	-15.2	-30.6	25.8	584.2	625.5	341.5	2.3	1.000133
23500.0	424.0	-16.2	-31.6	25.5	574.7	624.3	325.2	2.9	1.000131
24000.0	415.5	-17.2	-33.4	23.2	565.4	623.1	315.2	4.9	1.000128
24500.0	407.2	-18.1	-35.2	21.0	556.2	621.9	317.4	7.3	1.000125
25000.0	399.0	-19.0	-37.3	18.3	546.9	620.8	319.5	9.9	1.000123
25500.0	390.9	-19.3	-41.0	12.8	536.4	620.5	321.4	12.5	1.000120
26000.0	382.5	-20.0	-43.8	10.1	527.0	619.6	317.7	14.5	1.000118
26500.0	375.0	-21.2	-44.7	10.2	518.5	618.1	323.6	14.9	1.000116
27000.0	367.3	-22.4	-45.5	10.3	510.2	616.7	310.0	15.3	1.000114
27500.0	359.7	-23.5	-46.3	10.4	502.1	615.2	308.5	15.8	1.000112
28000.0	352.3	-24.7	-47.2	10.5	494.0	613.8	308.3	15.5	1.000111
28500.0	345.0	-25.9	-48.0	10.7	486.2	612.3	309.8	16.2	1.000109
29000.0	337.9	-27.1	-48.9	10.8	478.4	610.8	311.2	16.7	1.000107
29500.0	331.0	-28.2	-49.7	10.9	470.8	609.4	311.7	17.0	1.000105
30000.0	324.1	-29.5	-51.0	10.6**	463.3	607.9	309.5	17.8	1.000104
30500.0	317.1	-30.8	-53.5	9.0**	455.9	606.2	303.8	17.9	1.000102
31000.0	310.3	-32.1	-56.1	7.4**	448.6	604.5	300.1	18.8	1.000100
31500.0	303.7	-33.4	-59.1	5.7**	441.4	602.9	297.8	19.5	1.000098
32000.0	297.2	-34.8	-62.6	4.1**	434.3	601.4	296.9	20.1	1.000097
32500.0	290.8	-36.1	-67.2	2.5**	427.4	599.5	296.4	21.0	1.000095
33000.0	284.6	-37.4	-74.9	0.9**	420.6	597.8	297.1		1.000094

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL
 20 SEPT.66 0955 HRS MST
 ASCENSION NO. 728

UPPER AIR DATA
 0890003903
 WHITE SANDS SITE
 (ABIE VIT (Cont))

WSTM SITE COORDINATES
 E 488.500 FEET
 N 185.043 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	AIR TEMPERATURE DEGREES CENTIGRADE	RELATIVE HUMIDITY PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DIRECTION DEGREES(TN)	WIND SPEED KNOTS	INDEX OF REFRACTION
33500.0	278.4	-38.7	-0.0	413.6	596.3	297.1	21.8	1.000092
34000.0	272.2	-39.7	-0.0	406.3	594.9	295.6	22.7	1.000090
34500.0	266.2	-40.8	-0.0	399.1	593.5	293.9	23.8	1.000089
35000.0	260.2	-41.9	-0.0	392.1	592.1	292.0	24.9	1.000087
35500.0	254.5	-43.0	-0.0	385.2	590.7	290.8	26.8	1.000086
36000.0	248.8	-44.1	-0.0	378.4	589.4	289.7	28.9	1.000084
36500.0	243.3	-45.1	-0.0	371.8	588.0	289.8	28.9	1.000083
37000.0	237.9	-46.2	-0.0	365.2	586.6	289.9	29.0	1.000081
37500.0	232.4	-47.3	-0.0	358.4	585.2	289.8	29.3	1.000080
38000.0	226.9	-48.3	-0.0	351.6	583.9	289.2	29.4	1.000078
38500.0	221.6	-49.3	-0.0	344.9	582.5	288.1	29.2	1.000077
39000.0	216.4	-50.4	-0.0	338.4	581.2	286.6	30.2	1.000075
39500.0	211.3	-51.4	-0.0	332.0	579.8	284.8	31.7	1.000074
40000.0	206.3	-52.4	-0.0	325.7	578.5	283.9	33.1	1.000073
40500.0	201.5	-53.5	-0.0	319.6	577.1	283.3	34.4	1.000071
41000.0	196.8	-54.5	-0.0	313.5	575.8	283.7	34.6	1.000070
41500.0	192.1	-55.5	-0.0	307.6	574.4	284.3	34.8	1.000069
42000.0	187.6	-56.6	-0.0	301.8	573.0	285.2	34.7	1.000067
42500.0	183.2	-57.6	-0.0	296.2	571.7	285.9	34.4	1.000066
43000.0	178.9	-58.6	-0.0	290.6	570.3	286.3	33.8	1.000065
43500.0	174.7	-59.7	-0.0	285.2	568.9	286.6	33.4	1.000064
44000.0	170.6	-60.7	-0.0	279.8	567.5	286.9	33.3	1.000062
44500.0	166.6	-61.7	-0.0	274.6	566.2	287.1	33.2	1.000061
45000.0	162.7	-62.8	-0.0	259.5	564.8	287.1	33.0	1.000060
45500.0	158.8	-63.8	-0.0	264.3	563.4	287.9	33.4	1.000059
46000.0	154.9	-64.7	-0.0	258.8	562.2	289.1	33.9	1.000058
46500.0	151.0	-65.5	-0.0	253.4	561.0	290.3	33.4	1.000056
47000.0	147.2	-66.4	-0.0	248.2	559.8	291.6	32.4	1.000055
47500.0	143.6	-67.3	-0.0	243.0	558.6	292.9	31.6	1.000054
48000.0	140.0	-68.2	-0.0	238.0	557.4	294.2	30.8	1.000053

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL
 20 SEPT. 66 0955 HRS MST
 ASCENSION NO. 728

UPPER AIR DATA
 0800003903
 WHITE SANDS SITE
 TABLE VLT. (Cont.)

WSTM SITE COORDINATES
 E 488,580 FEET
 N 185,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		RELATIVE HUMIDITY PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA		INDEX OF REFRACTION
		AIR DEGREES	DEWPOINT CENTIGRADE				DIRECTION DEGREES(TN)	SPEED KNOTS	
48500.0	136.5	-69.1	0.	**	233.1	556.2	294.1	29.5	1.000052
49000.0	133.1	-70.0	0.	**	228.3	555.0	293.5	28.0	1.000051
49500.0	129.8	-70.9	0.	**	223.6	553.8	293.4	26.7	1.000050
50000.0	126.5	-71.8	0.	**	218.9	552.5	293.3	25.5	1.000049
50500.0	123.4	-72.4	0.	**	214.2	551.6	296.5	23.2	1.000048
51000.0	120.3	-72.1	0.	**	208.4	552.1	300.1	20.7	1.000046
51500.0	117.2	-71.8	0.	**	202.8	552.5	306.1	17.0	1.000045
52000.0	114.2	-71.5	0.	**	197.4	552.9	312.6	13.1	1.000044
52500.0	111.4	-71.2	0.	**	192.1	553.3	309.6	9.8	1.000043
53000.0	108.5	-70.9	0.	**	187.0	553.8	302.3	6.8	1.000042
53500.0	105.8	-70.6	0.	**	182.0	554.2	279.6	4.9	1.000041
54000.0	103.1	-70.3	0.	**	177.1	554.6	245.2	4.0	1.000039
54500.0	100.5	-70.0	0.	**	172.3	555.0	209.8	4.0	1.000038
55000.0	98.0	-69.5	0.	**	167.7	555.6	173.7	4.9	1.000037
55500.0	95.6	-69.1	0.	**	163.2	556.3	147.3	6.2	1.000036
56000.0	93.3	-68.6	0.	**	158.8	556.9	128.5	7.7	1.000035
56500.0	91.0	-68.1	0.	**	154.6	557.5	116.8	8.5	1.000034
57000.0	88.7	-67.7	0.	**	150.4	558.2	110.6	8.8	1.000033
57500.0	86.5	-67.2	0.	**	146.4	558.8	101.9	9.0	1.000033
58000.0	84.4	-66.7	0.	**	142.5	559.5	90.1	9.0	1.000032
58500.0	82.3	-66.2	0.	**	138.7	560.1	79.8	9.4	1.000031
59000.0	80.3	-65.8	0.	**	135.0	560.7	74.0	11.2	1.000030
59500.0	78.3	-65.3	0.	**	131.3	561.4	60.3	13.0	1.000029
60000.0	76.4	-64.8	0.	**	127.8	562.0	71.9	15.5	1.000028
60500.0	74.5	-64.4	0.	**	124.4	562.6	75.5	18.1	1.000028
61000.0	72.7	-63.9	0.	**	121.1	563.2	77.4	18.8	1.000027
61500.0	70.9	-63.4	0.	**	117.8	563.9	78.7	19.0	1.000026
62000.0	69.2	-63.0	0.	**	114.7	564.5	82.3	19.3	1.000026
62500.0	67.5	-62.5	0.	**	111.6	565.1	89.2	19.5	1.000025
63000.0	65.8	-62.0	0.	**	108.6	565.8	96.1	19.8	1.000024

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL
 20 SEPT. 66 0955 HRS MST
 ASCENSION NO. 728

UPPER AIR DATA
 0890003903
 WHITE SANDS SITE
 TABLE VII (Cont)

WSTN SITE COORDINATES
 E 488,500 FEET
 N 185,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		RELATIVE HUMIDITY PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND		WIND DATA		INDEX OF REFRACTION
		AIR DEGREES CENTIGRADE	DEWPOINT CENTIGRADE			SPEED KNOTS	SOUND KNOTS	DIRECTION DEGREES(TN)	SPEED KNOTS	
63500.0	64.2	-61.6	0.	-0. **	105.7	566.4	101.0	18.2	1.000024	
64000.0	62.6	-61.1	0.	-0. **	102.9	567.0	105.9	16.7	1.000023	
64500.0	61.1	-60.6	0.	-0. **	100.1	567.6	109.0	14.7	1.000022	
65000.0	59.6	-60.3	0.	-0. **	97.6	568.1	111.2	12.6	1.000022	
65500.0	58.2	-60.0	0.	-0. **	95.2	568.5	108.0	10.8	1.000021	
66000.0	56.9	-59.7	0.	-0. **	92.8	568.9	96.8	9.4	1.000021	
66500.0	55.5	-59.4	0.	-0. **	90.5	569.3	87.1	8.6	1.000020	
67000.0	54.2	-59.1	0.	-0. **	88.2	569.7	82.1	9.9	1.000020	
67500.0	52.9	-58.8	0.	-0. **	86.0	570.1	77.6	11.2	1.000019	
68000.0	51.7	-58.5	0.	-0. **	83.9	570.5	84.4	12.6	1.000019	
68500.0	50.5	-58.2	0.	-0. **	81.8	570.9	91.1	14.1	1.000018	
69000.0	49.3	-57.9	0.	-0. **	79.8	571.3	89.0	14.5	1.000018	
69500.0	48.1	-57.6	0.	-0. **	77.8	571.7	85.3	14.7	1.000017	
70000.0	47.0	-57.3	0.	-0. **	75.8	572.1	81.8	14.9	1.000017	
70500.0	45.9	-57.0	0.	-0. **	73.9	572.5	78.6	15.0	1.000016	
71000.0	44.8	-56.7	0.	-0. **	72.1	572.9	75.4	15.2	1.000016	
71500.0	43.7	-56.4	0.	-0. **	70.3	573.3	72.9	16.0	1.000016	
72000.0	42.7	-56.1	0.	-0. **	68.5	573.7	70.5	16.9	1.000015	
72500.0	41.7	-55.8	0.	-0. **	66.8	574.1	69.7	17.5	1.000015	
73000.0	40.7	-55.5	0.	-0. **	65.2	574.5	72.8	17.5	1.000014	
73500.0	39.8	-55.2	0.	-0. **	63.5	574.9	75.9	17.5	1.000014	
74000.0	38.8	-54.9	0.	-0. **	62.0	575.3	78.3	17.7	1.000014	
74500.0	37.9	-54.6	0.	-0. **	60.4	575.7	80.6	17.9	1.000013	
75000.0	37.0	-54.2	0.	-0. **	58.9	576.1	83.0	18.0	1.000013	
75500.0	36.1	-53.9	0.	-0. **	57.4	576.5	85.8	18.2	1.000013	
76000.0	35.3	-53.6	0.	-0. **	56.0	576.9	88.7	18.3	1.000012	
76500.0	34.5	-53.3	0.	-0. **	54.6	577.3	91.2	17.8	1.000012	
77000.0	33.6	-53.0	0.	-0. **	53.2	577.7	93.4	16.7	1.000012	
77500.0	32.8	-52.7	0.	-0. **	51.9	578.1	95.6	15.7	1.000012	
78000.0	32.1	-52.4	0.	-0. **	50.6	578.5	93.0	14.9	1.000011	

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL
 20 SEPT.66 0955 HRS MST
 ASCENSION NO. 728

UPPER AIR DATA
 OS90003903
 WHITE SANDS SITE
 TABLE VII (Cont)

WSTM SITE COORDINATES
 E 488°580 FEET
 N 185°045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		RELATIVE HUMIDITY PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA		INDEX OF REFRACTION
		AIR DEGREES CENTIGRADE	DEWPOINT CENTIGRADE				DIRECTION DEGREES(TN)	SPEED KNOTS	
78500.0	31.3	-51.8	0.	-0. **	49.3	579.3	90.0	14.2	1.000011
79000.0	30.6	-51.2	0.	-0. **	48.1	580.1	87.1	13.5	1.000011
79500.0	29.9	-50.6	0.	-0. **	46.9	580.9	84.7	13.2	1.000010
80000.0	29.2	-50.0	0.	-0. **	45.7	581.6	82.2	12.8	1.000010
80500.0	28.6	-49.4	0.	-0. **	44.5	582.4	80.9	12.8	1.000010
81000.0	27.9	-48.8	0.	-0. **	43.4	583.2	80.3	13.1	1.000010
81500.0	27.3	-48.2	0.	-0. **	42.3	584.0	79.8	13.3	1.000009
82000.0	26.7	-47.6	0.	-0. **	41.2	584.8	80.1	13.4	1.000009
82500.0	26.1	-47.0	0.	-0. **	40.1	585.6	80.4	13.4	1.000009
83000.0	25.5	-47.1	0.	-0. **	39.2	585.5	80.6	13.4	1.000009
83500.0	24.9	-47.2	0.	-0. **	38.4	585.3	80.0	13.6	1.000009
84000.0	24.3	-47.4	0.	-0. **	37.5	585.0	79.5	13.7	1.000008
84500.0	23.8	-47.6	0.	-0. **	36.7	584.8	80.2	14.2	1.000008
85000.0	23.2	-47.8	0.	-0. **	35.9	584.6	82.5	14.9	1.000008
85500.0	22.7	-47.9	0.	-0. **	35.1	584.3	84.8	15.6	1.000008
86000.0	22.2	-48.1	0.	-0. **	34.4	584.1	86.7	15.9	1.000008
86500.0	21.7	-48.3	0.	-0. **	33.6	583.9	88.4	15.8	1.000007
87000.0	21.2	-48.5	0.	-0. **	32.9	583.7	90.1	15.8	1.000007
87500.0	20.7	-48.6	0.	-0. **	32.1	583.4	91.7	15.7	1.000007
88000.0	20.2	-48.8	0.	-0. **	31.4	583.2	93.3	15.6	1.000007
88500.0	19.8	-49.0	0.	-0. **	30.7	583.0	94.9	15.6	1.000007
89000.0	19.3	-49.2	0.	-0. **	30.1	582.7	96.4	15.5	1.000007
89500.0	18.9	-49.2	0.	-0. **	29.4	582.7	95.7	14.4	1.000007
90000.0	18.5	-48.7	0.	-0. **	28.7	583.4	94.7	13.2	1.000006
90500.0	18.1	-48.1	0.	-0. **	28.0	584.1	93.7	11.9	1.000006
91000.0	17.7	-47.6	0.	-0. **	27.3	584.8	91.1	11.3	1.000006
91500.0	17.3	-47.1	0.	-0. **	26.6	585.4	87.1	11.2	1.000006
92000.0	16.9	-46.6	0.	-0. **	26.0	586.1	83.1	11.1	1.000006
92500.0	16.5	-46.1	0.	-0. **	25.3	586.8	79.0	11.0	1.000006
93000.0	16.1	-45.5	0.	-0. **	24.7	587.4	74.0	11.3	1.000005

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

UPPER AIR DATA
0890003903
WHITE SANDS SITE
TABLE VII (Cont)

STATION ALTITUDE 3989.0 FEET MSL
20 SEPT. 66 0955 HRS MST
ASCENSION NO. 728

WSTH SITE COORDINATES
E 488,500 FEET
N 165,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE AIR DEGREES CENTIGRADE	RELATIVE HUMIDITY PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA		INDEX OF REFRACTION
						DIRECTION DEGREES (TN)	SPEED KNOTS	
93500.0	15.8	-45.0	-0. **	24.1	588.1	69.0	11.5	1.000005
94000.0	15.4	-44.5	-0. **	23.5	588.8	64.0	11.8	1.000005
94500.0	15.1	-44.0	-0. **	22.9	589.4	60.3	12.8	1.000005
95000.0	14.7	-43.5	-0. **	22.4	590.1	57.0	14.1	1.000005
95500.0	14.4	-43.0	-0. **	21.8	590.8	53.7	19.3	1.000005
96000.0	14.1	-42.4	-0. **	21.3	591.4	51.4	26.4	1.000005
96500.0	13.8	-41.9	-0. **	20.8	592.1	51.0	17.1	1.000005
97000.0	13.5	-41.4	-0. **	20.2	592.8	50.5	17.8	1.000005
97500.0	13.2	-40.9	-0. **	19.7	593.4	50.0	18.6	1.000004
98000.0	12.9	-40.6	-0. **	19.3	593.7	53.6	18.1	1.000004
98500.0	12.6	-40.7	-0. **	18.9	593.6	57.2	17.7	1.000004
99000.0	12.3	-40.8	-0. **	18.5	593.5	60.8	17.3	1.000004
99500.0	12.0	-41.0	-0. **	18.1	593.3	63.8	17.0	1.000004
100000.0	11.8	-41.1	-0. **	17.7	593.2	66.5	17.0	1.000004
100500.0	11.5	-41.2	-0. **	17.3	593.1	69.1	16.9	1.000004
101000.0	11.3	-41.3	-0. **	16.9	592.9	72.6	16.9	1.000004
101500.0	11.0	-41.4	-0. **	16.6	592.8	81.3	17.3	1.000004
102000.0	10.8	-41.5	-0. **	16.2	592.7	90.1	17.7	1.000004
102500.0	10.5	-41.6	-0. **	15.9	592.6	98.8	18.1	1.000004
103000.0	10.3	-41.7	-0. **	15.5	592.4	105.0	18.5	1.000003
103500.0	10.1	-41.8	-0. **	15.2	592.3	110.1	18.9	1.000003
104000.0	9.9	-41.6	-0. **	14.8	592.5	115.1	19.3	1.000003
104500.0	9.6	-41.4	-0. **	14.5	592.8	119.8	19.6	1.000003
105000.0	9.4	-41.1	-0. **	14.2	593.1	120.5	19.7	1.000003
105500.0	9.2	-40.9	-0. **	13.8	593.4	121.2	19.7	1.000003
106000.0	9.0	-40.6	-0. **	13.5	593.8	121.9	19.7	1.000003
106500.0	8.8	-40.4	-0. **	13.2	594.1	123.6	19.8	1.000003
107000.0	8.6	-40.1	-0. **	12.9	594.4	128.3	20.0	1.000003
107500.0	8.4	-39.9	-0. **	12.6	594.7	132.9	20.2	1.000003
108000.0	8.3	-39.6	-0. **	12.3	595.0	137.5	20.4	1.000003

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

UPPER AIR DATA
 0890003903
 WHITE SANDS SITE
 TABLE VII (Cont)

STATION ALTITUDE 3989.0 FEET MSL
 20 SEPT.66 0955 HRS MST
 ASCENSION NO. 728

WSTM SITE COORDINATES
 E 488,580 FEET
 N 185,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		RELATIVE HUMIDITY PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA		INDEX OF REFRACTION
		AIR DEGREES	DEWPOINT CENTIGRADE				DIRECTION DEGREES(TN)	SPEED KNOTS	
108500.0	8.1	-39.4	0.	-0. **	12.0	595.4			1.000003
109000.0	7.9	-39.1	0.	-0. **	11.8	595.7			1.000003
109500.0	7.7	-38.8	0.	-0. **	11.5	596.0			1.000003
110000.0	7.6	-38.6	0.	-0. **	11.2	596.3			1.000002
110500.0	7.4	-38.3	0.	-0. **	11.0	596.7			1.000002
111000.0	7.2	-38.1	0.	-0. **	10.7	597.0			1.000002
111500.0	7.1	-37.8	0.	-0. **	10.5	597.3			1.000002

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

RELEASE TIME (MST)	SECOND-STAGE IMPACT DISPLACEMENT IN MILES DUE TO WIND										AZI- MUTH (DEG- REES)	THEORETICAL IMPACT FROM LAUNCHER (IN MILES)		
	RAWIN- SCXIDE	FIBAL	11-216 FT		216-4000 FT		4000-9600 FT		TOTAL			RANGE	N-S	E-W
			N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W				
0615	0700	1.0N	0.0	4.7N	5.1E	0.8N	12.0W	2.3N	6.9W	355.4	100.5	100.2N	8.1W	
0615	0730	2.8N	0.7E	0.2N	4.8E	0.8N	12.0W	3.8N	6.5W	355.7	102.0	101.7N	7.7W	
0615	0800	1.5N	0.8W	1.6N	3.4E	0.8N	12.0W	4.0N	9.4W	354.1	102.5	101.9N	10.6W	
0615	0815	0.1N	0.4W	2.3S	4.7E	0.8N	12.0W	1.4S	7.6W	354.8	97.7	96.5N	8.8W	
0615	0830	1.1S	0.7E	3.1S	7.2E	0.8N	12.0W	3.3S	4.1W	356.8	94.7	94.6N	5.3W	
0615	0840	3.3S	2.7E	5.9S	3.7E	0.8N	12.0W	8.3S	5.6W	355.7	89.9	89.6N	6.3W	
0615	0850	5.7S	3.3E	6.3S	5.3E	0.8N	12.0W	11.2S	3.4W	357.0	86.8	86.7N	4.6W	
0615	0857	4.7S	0.4W	6.8S	5.7E	0.8N	12.0W	10.7S	6.6W	354.9	87.6	87.2N	7.8W	
0955	0919	3.5S	0.8E	8.8S	6.8E	2.5N	10.8W	9.8S	3.2W	357.1	88.2	88.1N	4.4W	

*

*Post Shoot Winds

	AZIMUTH (DEG- REES)	MILES FROM LAUNCHER		
		RANGE	N-S	E-W
LAUNCHER SETTING (ELEVATION 83.1 DEGREES QE)	002.2	98.0	97.9N	3.8E
NO WIND IMPACT	359.7	97.9	97.9N	1.2W
PREDICTED IMPACT	357.6	69.6	69.6N	2.9W
ACTUAL IMPACT	344.5	97.5	94.0N	26.1W
PREDICTED BOOSTER IMPACT	002.0	1.4	1.4N	0.0
ACTUAL BOOSTER IMPACT	N/A	N/A	N/A	N/A

TABLE VIII. IMPACT PREDICTION DATA
NIKE-HYDAC, MK 1.2 STV (SR-038)

UNCLASSIFIED

Security Classification

DOCUMENT CONTROL DATA - R&D		
<i>(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)</i>		
1. ORIGINATING ACTIVITY (Corporate author)		2a. REPORT SECURITY CLASSIFICATION
U. S. Army Electronics Command Fort Monmouth, New Jersey		UNCLASSIFIED
		2b. GROUP
3. REPORT TITLE		
METEOROLOGICAL DATA REPORT, NIKE-HYDAC MK 12 STV (SR-038)		
4. DESCRIPTIVE NOTES (Type of report and inclusive dates)		
5. AUTHOR(S) (Last name, first name, initial)		
SHARPE, John M		
6. REPORT DATE	7a. TOTAL NO. OF PAGES	7b. NO. OF REFS
November 1966	24	None
8a. CONTRACT OR GRANT NO.	9a. ORIGINATOR'S REPORT NUMBER(S)	
b. PROJECT NO.	DR-09	
c. DA Task IV650212A127-02	9b. OTHER REPORT NO(S) (Any other numbers that may be assigned to this report)	
d.		
10. AVAILABILITY/LIMITATION NOTICES		
Distribution of this document is unlimited.		
11. SUPPLEMENTARY NOTES	12. SPONSORING MILITARY ACTIVITY	
	U. S. Army Electronics Command Atmospheric Sciences Laboratory White Sands Missile Range, New Mexico	
13. ABSTRACT		
Meteorological data gathered for the launching of Nike-Hydac, MK 12 STV (SR-038) are presented for the Air Force Ballistic Missile Re-entry Systems Office, the General Electric Company and for ballistic studies. The data appear, along with calculated ballistic data, in tabular form.		

DD FORM 1473
1 JAN 64

UNCLASSIFIED

Security Classification

Security Classification

KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
1. Ballistics 2. Meteorology 3. MINT						

INSTRUCTIONS

1. **ORIGINATING ACTIVITY:** Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (corporate author) issuing the report.

2a. **REPORT SECURITY CLASSIFICATION:** Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. **GROUP:** Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. **REPORT TITLE:** Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. **DESCRIPTIVE NOTES:** If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. **AUTHOR(S):** Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. **REPORT DATE:** Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.

7a. **TOTAL NUMBER OF PAGES:** The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. **NUMBER OF REFERENCES:** Enter the total number of references cited in the report.

8a. **CONTRACT OR GRANT NUMBER:** If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. **PROJECT NUMBER:** Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. **ORIGINATOR'S REPORT NUMBER(S):** Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. **OTHER REPORT NUMBER(S):** If the report has been assigned any other report numbers (either by the originator or by the sponsor), also enter this number(s).

10. **AVAILABILITY/LIMITATION NOTICES:** Enter any limitations on further dissemination of the report, other than those imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. **SUPPLEMENTARY NOTES:** Use for additional explanatory notes.

12. **SPONSORING MILITARY ACTIVITY:** Enter the name of the departmental project office or laboratory sponsoring (paying for) the research and development. Include address.

13. **ABSTRACT:** Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. **KEY WORDS:** Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.

UNCLASSIFIED

Security Classification