

DR-103
NOVEMBER 1966

AD

802595

METEOROLOGICAL DATA REPORT

NIKE-HYDAC STV (SR-040)
(4 October 1966)

BY

LEN E. CARTER

ATMOSPHERIC SCIENCES LABORATORY
WHITE SANDS MISSILE RANGE, NEW MEXICO

.....
ECOM

UNITED STATES ARMY ELECTRONICS COMMAND

DDC
RECORDED
NOV 29 1966
C

ABSTRACT

Meteorological data gathered for the launching of Nike-Hydec STV (SR-040) are presented for the Ballistic Systems Division, U. S. Air Force, Avco Corporation, and for ballistic studies. The data appear, along with calculated ballistic data, in tabular form.

CONTENTS

	PAGE
ABSTRACT -----	111
INTRODUCTION -----	1
DISCUSSION -----	1
TABLES	
I. Theoretical Rocket Performance Values -----	2
II. Ballistic Factors -----	3
III. Anemometer Wind Speed and Direction -----	4
IV. Pilot-Balloon-Measured Wind Data -----	5
V. Rawinsonde Measured Wind Data -----	7
VI. Computer-Calculated Upper Air Data (Release Time: 0500 MST) -----	8
VII. Computer-Calculated Upper Air Data (Release Time: 0800 MST) -----	15
VIII. Impact Prediction Data -----	22

DISCLAIMER NOTICE

THIS DOCUMENT IS BEST QUALITY PRACTICABLE. THE COPY FURNISHED TO DTIC CONTAINED A SIGNIFICANT NUMBER OF PAGES WHICH DO NOT REPRODUCE LEGIBLY.

OR ARE
Blank pgs.
that have
Been Removed

**BEST
AVAILABLE COPY**

INTRODUCTION

Nike-Hydac STV (SR-010) was launched from Launch Complex 33, L-311, White Sands Missile Range (WSMR), New Mexico, at 0802 hours MST, 4 October 1966.

Meteorological data used in conjunction with theoretical calculations to predict rocket impact were collected by the Meteorological Support Division, Atmospheric Sciences Laboratory (ASL), WSMR, New Mexico. The Ballistics Meteorologists for this firing were Len E. Carter and Gordon L. Dunaway.

DISCUSSION

Wind data for the first 216 feet above the surface were obtained from a system composed of 5 Aerovanes mounted on a 200-foot tower and cabled to 5 component wind indicators.

From 216 to 4,000 feet above the surface, wind data were obtained from double-theodolite-observed balloon ascents.

Temperature, pressure, and humidity data, along with upper wind data from 4,000 to 73,497 feet above the surface, were obtained from standard rawinsonde observations.

Mean wind component values in each ballistic zone were determined from vertical cross sections by the equal-area method.

Theoretical rocket performance values and ballistic factors as a function of altitude were provided by ASL, and are the basis for data appearing in Table VIII.

PAYLOAD		233	Pounds
CORIOLIS DISPLACEMENT	WEST	4.9	Miles
	EAST	20.2	Seconds
SECOND-STAGE IGNITION	ALTITUDE	36,673	Feet MSL
	TIME	236.2	Seconds
PEAK	ALTITUDE	718,586	Feet MSL
			Miles/HR
UNIT WIND EFFECT		2,575	Miles/HR
			Miles/HR
TOWER TILT EFFECT		14.08	Miles/Degree

TABLE I. THEORETICAL ROCKET PERFORMANCE VALUES
NIKE-HYDAC STV (SR-040)

LAYERS IN FEET ABOVE GROUND	BALLISTIC FACTORS
15000-21000	-.0104
21000-26000	-.0072
26000-32617	-.0057
32617-34000	.0113
34000-36000	.0315
36000-41000	.0343
41000-46000	.0126
46000-52000	.0055
52000-56000	.0035
56000-61000	.0024
61000-66000	.0019
66000-72197	.0009

LAYERS IN FEET ABOVE GROUND	BALLISTIC FACTORS
800- 1000	.0432
1000- 1400	.0703
1400- 2000	.0563
2000- 2500	.0899
2500- 3000	.0166
3000- 3500	.0803
3500- 4000	.0041
4000- 4263	-.0067
4263- 9000	-.0109
9000-15000	-.0124

LAYERS IN FEET ABOVE GROUND	BALLISTIC FACTORS
00- 11	.0000
11- 60	.1482
60-108	.1028
108-148	.0671
148-184	.0544
184-216	.0315
216-300	.0835
300-400	.0681
400-600	.0727
600-800	.0503

TABLE II. BALLISTIC FACTORS
NIKE-HYDAC STV (SR-040)

AERO-VANE NO. *	MEAN WIND COMPONENTS IN MILES PER HOUR							
	1 0600 MST		2 0630 MST		3 0700 MST		4 0720 MST	
	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W
1	6.0N	0.0	7.0N	2.0E	8.0N	1.0E	14.0N	3.0E
2	8.0	0.0	10.0	2.0	9.0	1.0	15.0	5.0
3	9.0	0.0	11.0	1.0	9.5	1.5	15.0	5.0
4	10.0	0.0	12.0	0.0	10.0	2.0	15.0	5.0
5	12.0	0.0	13.0	0.0	11.0	0.0	18.0	2.0

AERO-VANE NO. *	MEAN WIND COMPONENTS IN MILES PER HOUR							
	5 0735 MST		6 0742 MST		7 0750 MST		8 0802 MST	
	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W
1	10.0N	3.0E	10.0N	1.0E	12.0N	2.0E	12.0E	3.0E
2	12.0	4.0	12.0	1.0	14.0	3.0	14.0	2.0
3	12.5	4.0	12.5	1.5	13.0	3.0	15.0	3.0
4	13.0	4.0	13.0	2.0	12.0	3.0	17.0	4.0
5	14.0	2.0	12.0	2.0	13.0	2.0	17.0	1.0

TABLE III. AIRCRAFT WIND SPEED AND DIRECTION
NIKE-HIDAG STV (SR-9)(0)

* Heights corresponding to Aerovane Numbers: 1 = 35 Feet 2 = 125 Feet 3 = 200 Feet
4 = 65 Feet 5 = 165 Feet

LAYERS IN FEET ABOVE GROUND	MEAN WIND COMPONENTS IN MILES PER HOUR											
	1 0600 MST		2 0630 MST		3 0700 MST		4 0720 MST		MST		MST	
	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W
216-300	13.0N	0.5W	16.0N	0.0	14.5N	0.0	18.0N	1.0E	1.0E			
300-400	16.0	2.0	17.0	0.5E	17.0	0.0	18.0	1.0	1.0			
400-600	18.0	1.0	20.0	1.0	19.0	0.5E	20.5	1.0	1.0			
600-800	21.5	0.5E	22.0	1.0	20.0	1.5	20.0	1.5	1.5			
800-1000	23.0	1.0	22.0	1.0	19.0	2.0	20.0	1.5	1.5			
1000-1400	22.0	1.0	20.0	0.5	16.0	1.0	19.0	1.0	1.0			
1400-2000	19.5	1.5	15.0	1.5	15.0	2.0	16.5	2.5	2.5			
2000-2500	16.5	5.5	11.0	4.6	11.0	4.0	10.0	2.5	2.5			
2500-3000	13.0	8.0	6.0	6.5	2.0	5.0	7.0	3.5	3.5			
3000-3500	6.5	8.0	3.0	9.0	0.0	5.5	3.0	5.0	5.0			
3500-4000	0.0	7.0	0.08	10.5	6.58	10.0	11.58	10.0	10.0			

TABLE IV. FILLOT-BALLOON-MEASURED WIND DATA
NIXE-HYDAS BTY (SR-010)

LAYERS IN FEET ABOVE GROUND	MEAN WIND COMPONENTS IN MILES PER HOUR											
	5 0735 MST		6 0742 MST		7 0750 MST		8 0802 MST		MST		MST	
	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W
216-300	15.0N	2.5E	13.0N	0.0	15.5N	2.0E	17.5N	1.5E	17.5N	2.0E	19.5N	1.5E
300-400	17.5	3.0	18.0	3.0E	18.0	2.5	19.5	2.0	19.5	2.5	21.5	2.0
400-600	20.0	3.0	20.5	4.0	20.5	3.0	21.5	3.0	21.5	3.0	22.0	3.0
600-800	21.5	2.5	23.5	3.0	22.0	2.5	22.0	3.5	22.0	2.5	22.0	3.5
800-1000	21.5	2.0	23.5	2.0	21.0	3.0	21.0	3.5	21.0	3.0	21.0	2.0
1000-1400	19.0	1.0	21.5	2.0	18.0	3.0	18.0	2.0	18.0	3.0	18.0	4.0
1400-2000	17.0	1.5	16.5	3.0	15.0	3.0	15.0	4.0	15.0	4.5	12.0	4.5
2000-2500	13.5	3.0	8.0	5.5	14.0	4.5	14.0	5.5	14.0	4.5	11.0	5.5
2500-3000	5.0	5.0	4.5	7.0	8.0	5.0	8.0	7.5	8.0	5.0	5.0	7.5
3000-3500	2.0	7.0	2.5S	6.0	3.5	5.5	3.5	5.5	3.5	5.5	5.0	7.5
3500-4000	1.0S	10.5	7.0	7.0	3.0S	7.0	3.0S	0.5S	3.0S	7.0	0.5S	0.5

TABLE IV. PILOT-BALLOON-MEASURED WIND DATA (Cont)

NIKE-HYDAC SIX (SR-010)

LAYERS IN FEET ABOVE GROUND	MEAN WIND COMPONENTS IN KNOTS					
	1 0500 MST			2 0800 MST		
	N-S	E-W	N-S	E-W	N-S	E-W
4000-4263	1.5S	10.5E	4.5S	8.0E		
4263-9000	15.0	5.5	12.0	7.0		
9000-15000	30.5	5.5W	30.5	5.5W		
15000-21000	40.0	23.0	39.0	22.5		
21000-26000	57.0	33.0	53.0	21.0		
26000-32647	68.0	39.0	54.0	31.0		
32647-34000	68.0	57.0	55.0	46.0		
34000-36000	67.0	56.0	57.0	48.0		
36000-41000	63.0	53.0	47.0	39.0		
41000-46000	47.0	39.0	41.5	34.5		
46000-51000	36.5	31.0	36.0	30.0		
51000-56000	9.5	26.0	33.5	28.0		
56000-61000	8.0N	4.5	29.5	17.0		
61000-66000	7.5S	13.0	20.5	7.5		
66000-73497	5.5	9.5	8.5	7.0		

TABLE V. RAWINSONDE-MEASURED WIND DATA
NIKE-HYDAC STV (SR-040)

UPPER AIR DATA
 008300302
 WHITE SANDS SITE
 TABLE VI

STATION ALTITUDE 3989.0 FEET MSL
 4 OCT. 66
 ASCENSION NO. 763

WSTM SITE COORDINATES
 E 488,580 FEET
 N 185,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE AIR DEGREES CENTIGRADE	REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA		INDEX OF REFRACTION
						DIRECTION DEGREES (M)	SPEED KNOTS	
3989.0	877.0	12.0	80.0	1066.4	659.1	360.0	2.9	1.000282
4000.0	876.7	12.1	79.6	1065.7	659.2	0.1	3.0	1.000290
4500.0	861.0	15.0	64.0	1036.0	662.6	5.3	4.6	1.000281
5000.0	845.7	16.6	59.9	1011.7	664.5	10.6	6.3	1.000277
5500.0	830.6	15.9	59.5	996.5	663.6	15.8	8.0	1.000271
6000.0	815.8	15.1	59.1	981.6	662.6	21.0	9.7	1.000265
6500.0	801.3	14.3	58.7	966.9	661.7	34.7	9.4	1.000259
7000.0	787.0	13.5	58.4	952.4	660.7	53.9	7.7	1.000254
7500.0	773.0	12.7	58.2	938.3	659.7	90.8	8.3	1.000249
8000.0	759.1	11.1	60.4	926.8	657.8	108.2	9.4	1.000244
8500.0	745.3	10.1	62.3	913.2	656.6	122.7	11.0	1.000240
9000.0	731.7	9.1	64.2	899.8	653.4	136.0	12.4	1.000236
9500.0	718.4	8.1	66.0	886.7	654.2	146.7	13.4	1.000232
10000.0	705.3	7.1	67.9	873.8	653.0	158.6	14.4	1.000228
10500.0	692.4	5.9	76.0	861.3	651.7	171.5	15.5	1.000226
11000.0	679.7	4.5	92.1	849.3	650.2	179.3	16.6	1.000227
11500.0	667.1	3.8	94.9	835.5	649.5	185.7	17.7	1.000224
12000.0	654.8	3.2	97.7	821.9	648.7	188.9	19.6	1.000220
12500.0	642.6	2.1	97.1	810.0	647.3	191.0	21.2	1.000215
13000.0	630.5	0.6	93.4	799.6	645.4	191.6	22.3	1.000208
13500.0	618.7	-0.9	89.7	789.2	643.5	191.4	23.9	1.000202
14000.0	607.1	-2.3	85.1	778.9	641.6	191.0	25.7	1.000196
14500.0	595.5	-3.7	77.4	768.2	639.9	190.9	27.3	1.000190
15000.0	584.2	-4.8	64.8	757.1	638.4	191.3	29.0	1.000183
15500.0	573.0	-5.0	36.4	743.6	638.0	193.8	31.0	1.000174
16000.0	562.0	-5.5	34.3	731.0	637.3	196.6	33.1	1.000170
16500.0	551.2	-6.1	32.2	718.6	636.5	199.5	35.4	1.000167
17000.0	540.5	-7.1	31.5	707.2	635.4	202.2	37.2	1.000164
17500.0	530.0	-8.1	31.0	696.1	634.2	204.8	38.4	1.000161
18000.0	519.6	-9.1	30.4	685.2	632.9	207.0	39.2	1.000158

STATION ALTITUDE 3989.0 FEET MSL
 4 OCT. 66 0500 HRS MST
 ASCENSION NO. 763

UPPER AIR DATA
 0083003902
 WHITE SANDS SITE
 TABLE VI (Cont)

WSM SITE COORDINATES
 E 488,580 FEET
 N 185,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA DIRECTION DEGREES(TN)	SPEED KNOTS	INDEX OF REFRACTION
		AIR DEGREES	DEWPOINT CENTIGRADE						
18500.0	509.5	-10.1	-24.5	29.9	674.5	631.7	209.0	39.9	1.000155
19000.0	499.6	-11.1	-25.6	29.4	663.9	630.5	210.1	40.2	1.000152
19500.0	489.9	-11.9	-26.6	28.6	653.0	629.5	210.8	40.4	1.000149
20000.0	480.2	-12.2	-27.3	27.4	640.9	629.1	211.0	40.9	1.000146
20500.0	470.8	-12.5	-28.1	26.2	629.1	628.7	211.0	41.5	1.000144
21000.0	461.5	-13.5	-28.6	26.9	618.9	627.6	209.8	42.3	1.000141
21500.0	452.3	-14.6	-29.2	28.0	609.2	626.3	208.8	43.1	1.000139
22000.0	443.3	-15.7	-30.0	28.5	599.8	624.8	209.1	44.1	1.000136
22500.0	434.5	-16.9	-30.9	29.0	590.6	623.4	209.4	45.1	1.000134
23000.0	425.6	-18.1	-31.8	29.1	581.1	622.0	209.4	46.4	1.000132
23500.0	416.9	-19.2	-32.8	29.3	571.8	620.6	209.6	47.8	1.000130
24000.0	408.4	-20.3	-33.7	29.4	562.7	619.2	210.5	49.6	1.000127
24500.0	400.1	-21.5	-34.7	29.5	553.7	617.8	211.1	51.4	1.000125
25000.0	391.9	-22.6	-35.7	29.7	544.9	616.4	211.1	53.0	1.000123
25500.0	384.0	-23.8	-36.6	29.8	536.3	615.0	210.3	55.5	1.000121
26000.0	376.1	-24.9	-37.6	29.9	527.7	613.6	208.8	58.8	1.000119
26500.0	368.4	-25.5	-38.1	30.0	518.2	612.8	206.8	62.0	1.000117
27000.0	360.8	-25.5	-38.1	30.0	507.4	612.8	204.6	65.1	1.000114
27500.0	353.2	-26.5	-38.9	30.1	498.7	611.6	203.3	67.8	1.000112
28000.0	345.7	-27.5	-39.9	30.3	490.4	610.3	202.1	70.5	1.000110
28500.0	338.5	-28.6	-40.8	30.4	482.1	609.0	202.8	71.7	1.000108
29000.0	331.3	-29.7	-41.7	30.5	474.1	607.6	203.5	72.5	1.000107
29500.0	324.4	-30.8	-42.6	30.7	466.2	606.3	204.1	70.8	1.000105
30000.0	317.5	-31.8	-43.5	30.8	458.4	604.9	204.7	69.8	1.000103
30500.0	310.9	-32.9	-44.4	31.0	450.7	603.6	205.4	69.9	1.000101
31000.0	304.2	-33.6	-45.1	30.9	442.4	602.7	206.3	69.4	1.000099
31500.0	297.7	-34.2	-45.7	30.7	434.0	601.9	207.3	68.2	1.000097
32000.0	291.3	-34.8	-46.3	30.5	425.7	601.2	208.7	69.5	1.000095
32500.0	285.0	-35.3	-46.8	30.3	417.5	600.5	210.3	71.7	1.000094
33000.0	278.9	-35.9	-47.4	30.1	409.5	599.8	211.3	75.4	1.000092

UPPER AIR DATA
0083003902
WHITE SANDS SITE
TABLE VI (Cont)

STATION ALTITUDE 3989.0 FEET MSL
4 OCT. 66 0500 HRS MST
ASCENSION NO. 763

MSTM SITE COORDINATES
E 488,680 FEET
N 105,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA		INDEX OF REFRACTION
		AIR DEGREES	DEWPOINT CENTIGRADE				DIRECTION DEGREES (M)	SPEED KNOTS	
33500.0	272.8	-36.8	-48.2	30.0	402.2	598.6	212.2	79.4	1.0000090
34000.0	266.9	-38.0	-49.3	30.0	395.4	597.1	213.3	81.4	1.0000089
34500.0	261.1	-39.1	-51.3	26.5**	388.6	595.7	214.3	83.2	1.0000087
35000.0	255.3	-40.0	-54.7	19.4**	381.6	594.5	215.9	84.0	1.0000085
35500.0	249.7	-41.0	-59.1	12.4**	374.7	593.3	217.3	84.8	1.0000084
36000.0	244.2	-42.0	-66.1	5.4**	368.0	592.1	218.7	85.5	1.0000082
36500.0	238.7	-43.0	0.	-0. **	361.4	590.7	219.5	87.3	1.0000080
37000.0	233.3	-44.3	0.	-0. **	355.2	589.0	219.7	90.0	1.0000079
37500.0	227.9	-45.7	0.	-0. **	349.1	587.3	219.6	92.1	1.0000078
38000.0	222.7	-47.0	0.	-0. **	343.2	585.5	219.4	94.0	1.0000076
38500.0	217.7	-48.3	0.	-0. **	337.3	583.8	219.5	92.9	1.0000075
39000.0	212.7	-49.7	0.	-0. **	331.6	582.1	219.6	91.3	1.0000074
39500.0	207.8	-51.0	0.	-0. **	326.0	580.3	219.9	90.1	1.0000073
40000.0	203.1	-52.4	0.	-0. **	320.5	578.6	220.2	88.8	1.0000071
40500.0	198.4	-53.7	0.	-0. **	315.0	576.8	220.9	87.1	1.0000070
41000.0	193.9	-55.0	0.	-0. **	309.7	575.1	221.6	85.3	1.0000069
41500.0	189.3	-56.1	0.	-0. **	303.9	573.6	222.1	83.1	1.0000068
42000.0	184.8	-57.3	0.	-0. **	298.2	572.1	222.6	82.0	1.0000066
42500.0	180.4	-58.4	0.	-0. **	292.6	570.6	222.4	79.1	1.0000065
43000.0	176.1	-59.5	0.	-0. **	287.1	569.1	222.2	77.3	1.0000064
43500.0	171.9	-60.6	0.	-0. **	281.8	567.6	222.4	75.6	1.0000063
44000.0	167.8	-61.7	0.	-0. **	276.5	566.2	222.6	73.7	1.0000062
44500.0	163.7	-61.9	0.	-0. **	270.0	565.0	223.5	71.5	1.0000060
45000.0	159.7	-62.0	0.	-0. **	263.6	563.9	224.5	68.6	1.0000059
45500.0	155.9	-62.2	0.	-0. **	257.5	563.5	225.5	65.5	1.0000057
46000.0	152.1	-63.0	0.	-0. **	252.1	564.5	225.2	62.6	1.0000056
46500.0	148.4	-63.8	0.	-0. **	246.9	563.4	224.7	59.8	1.0000055
47000.0	144.7	-64.5	0.	-0. **	241.7	562.4	223.5	57.8	1.0000054
47500.0	141.2	-64.8	0.	-0. **	236.1	562.0	222.4	55.7	1.0000053
48000.0	137.7	-65.0	0.	-0. **	230.5	561.8	222.0	54.2	1.0000051

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

UPPER AIR DATA
 0083003902
 WHITE SANDS SITE
 TABLE VT (Cont)

STATION ALTITUDE 3989.0 FEET MSL
 4 OCT. 66
 0500 HRS MST
 ASCENSION NU. 763

WSTM SITE COORDINATES
 E 488,580 FEET
 N 185,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		REL. HUM. PERCENT	DENSITY GR/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA		INDEX OF REFRACTION
		AIR DEGREES	DEWPOINT CENTIGRADE				DIRECTION DEGREES(TND)	SPEED KNOTS	
48500.0	134.3	-65.1	0.	**	225.0	561.6	221.6	52.7	1.000050
49000.0	131.0	-65.3	0.	**	219.6	561.4	221.9	51.8	1.000049
49500.0	127.8	-65.4	0.	**	214.4	561.2	222.2	50.9	1.000048
50000.0	124.7	-65.6	0.	**	209.2	561.0	221.4	50.5	1.000047
50500.0	121.6	-65.9	0.	**	204.4	560.6	220.6	50.0	1.000046
51000.0	118.5	-66.3	0.	**	199.7	560.0	219.0	49.6	1.000044
51500.0	115.6	-66.7	0.	**	195.1	559.5	217.5	49.2	1.000043
52000.0	112.7	-67.1	0.	**	190.6	559.0	216.1	49.0	1.000042
52500.0	109.9	-67.5	0.	**	186.2	558.5	214.9	49.1	1.000041
53000.0	107.2	-67.8	0.	**	181.9	557.9	214.1	49.6	1.000040
53500.0	104.5	-68.2	0.	**	177.7	557.4	214.0	48.8	1.000040
54000.0	101.9	-68.6	0.	**	173.6	556.9	214.4	47.0	1.000039
54500.0	99.4	-69.0	0.	**	169.6	556.3	214.1	43.8	1.000038
55000.0	96.9	-69.4	0.	**	165.7	555.8	218.8	39.8	1.000037
55500.0	94.5	-69.7	0.	**	161.8	555.4	223.5	34.7	1.000036
56000.0	92.1	-69.6	0.	**	157.7	555.5	230.3	28.6	1.000035
56500.0	89.8	-69.6	0.	**	153.7	555.6	238.6	23.3	1.000034
57000.0	87.6	-69.5	0.	**	149.8	555.6	249.4	19.4	1.000033
57500.0	85.4	-69.5	0.	**	146.0	555.7	258.1	16.3	1.000033
58000.0	83.2	-69.4	0.	**	142.3	555.8	261.1	14.7	1.000032
58500.0	81.1	-68.3	0.	**	138.0	557.3	261.1	13.4	1.000031
59000.0	79.1	-65.8	0.	**	133.0	560.7	254.0	12.8	1.000030
59500.0	77.2	-63.2	0.	**	128.1	564.1	247.0	12.4	1.000029
60000.0	75.3	-63.0	0.	**	124.9	564.4	240.3	12.2	1.000028
60500.0	73.5	-63.1	0.	**	121.9	564.4	238.2	10.6	1.000027
61000.0	71.7	-63.1	0.	**	118.9	564.3	243.3	7.0	1.000026
61500.0	69.9	-63.1	0.	**	116.0	564.3	269.0	4.3	1.000026
62000.0	68.2	-63.2	0.	**	113.2	564.2	322.2	2.9	1.000025
62500.0	66.6	-63.2	0.	**	110.5	564.2	359.8	2.7	1.000025
63000.0	65.0	-63.3	0.	**	107.8	564.1	18.7	4.1	1.000024

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL
 4 OCT. 66 0500 HRS MST
 ASCENSION NO. 763

UPPER AIR DATA
 0083003902
 WHITE SANDS SITE
 TABLE VI (Cont)

WSTN SITE COORDINATES
 E 489,580 FEET
 N 185,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	AIR TEMPERATURE DEGREES CENTIGRADE	REL. HUM. PERCENT	DENSITY GH/CUBIC METER	SPEED OF SOUND KNOTS	WIND DIRECTION DEGREES (TNS)	SPEED KNOTS	INDEX OF REFRACTION
63500.0	63.4	-63.3	-0.0	105.2	564.1	29.2	4.5	1.000023
64000.0	61.8	-63.3	-0.0	102.7	564.0	30.8	3.9	1.000023
64500.0	60.3	-63.4	-0.0	100.2	564.0	31.9	3.3	1.000022
65000.0	58.9	-63.3	-0.0	97.8	564.0	32.5	2.6	1.000022
65500.0	57.5	-62.7	-0.0	95.1	564.8	34.5	1.8	1.000021
66000.0	56.1	-62.1	-0.0	92.6	565.6	256.6	0.9	1.000021
66500.0	54.7	-62.5	-0.0	90.1	566.5	215.8	0.9	1.000020
67000.0	53.4	-60.9	-0.0	87.7	567.3	214.7	1.8	1.000020
67500.0	52.2	-60.3	-0.0	85.4	568.1	214.2	5.3	1.000019
68000.0	50.9	-59.7	-0.0	83.1	568.9	214.1	10.8	1.000018
68500.0	49.7	-59.1	-0.0	80.9	569.7	214.1	13.4	1.000018
69000.0	48.5	-58.5	-0.0	78.7	570.5	214.1	14.0	1.000018
69500.0	47.3	-57.8	-0.0	76.6	571.3	219.0	13.5	1.000017
70000.0	46.2	-57.2	-0.0	74.6	572.2	227.2	12.3	1.000017
70500.0	45.1	-56.6	-0.0	72.6	573.0	237.3	10.6	1.000016
71000.0	44.0	-56.0	-0.0	70.6	573.8	248.6	8.7	1.000016
71500.0	43.0	-55.9	-0.0	68.9	573.9	272.3	8.2	1.000015
72000.0	42.0	-55.8	-0.0	67.3	574.1	303.4	8.6	1.000015
72500.0	41.0	-55.7	-0.0	65.7	574.2	318.2	8.9	1.000015
73000.0	40.0	-55.6	-0.0	64.1	574.3	294.2	9.2	1.000014
73500.0	39.1	-55.5	-0.0	62.6	574.5	270.1	9.4	1.000014
74000.0	38.2	-55.4	-0.0	61.1	574.6	253.4	11.0	1.000014
74500.0	37.3	-55.3	-0.0	59.6	574.7	244.1	13.6	1.000013
75000.0	36.4	-55.2	-0.0	58.2	574.9	234.8	16.7	1.000013
75500.0	35.6	-55.1	-0.0	56.8	575.0	229.7	17.9	1.000012
76000.0	34.7	-55.0	-0.0	55.5	575.1	227.9	17.9	1.000012
76500.0	33.9	-54.9	-0.0	54.1	575.3	226.0	17.9	1.000012
77000.0	33.1	-54.8	-0.0	52.8	575.4	224.4	17.4	1.000012
77500.0	32.3	-54.7	-0.0	51.6	575.5	222.9	16.5	1.000011
78000.0	31.6	-54.6	-0.0	50.4	575.7	221.4	15.6	1.000011

12

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3969.0 FEET MSL
 4 OCT. 66 0500 HRS MST
 ASCENSION NO. 763
 UPPER AIR DATA
 U083003902
 WHITE SANDS SITE
 TABLE VI (Cont)

WSTM SITE COORDINATES
 E 488,580 FEET
 N 185,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND		WIND DATA		INDEX OF REFRACTION
		AIR DEGREES CENTIGRADE	DEWPOINT			KNITS	KNITS	DIRECTION DEGREES(TN)	SPEED KNOTS	
78500.0	30.8	-54.3	0.	-0.	49.1	576.0	221.1	15.1	1.000011	
79000.0	30.1	-53.5	0.	-0.	47.8	577.1	221.3	14.8	1.000011	
79500.0	29.4	-52.7	0.	-0.	46.5	578.1	221.5	14.5	1.000010	
80000.0	28.8	-52.1	0.	-0.	45.3	578.9	219.8	17.6	1.000010	
80500.0	28.1	-52.0	0.	-0.	44.3	579.1	217.6	21.8	1.000010	
81000.0	27.4	-51.8	0.	-0.	43.2	579.3	215.3	26.1	1.000010	
81500.0	26.8	-51.6	0.	-0.	42.2	579.6	214.8	28.9	1.000009	
82000.0	26.2	-51.4	0.	-0.	41.2	579.8	214.8	31.2	1.000009	
82500.0	25.6	-51.2	0.	-0.	40.2	580.1	214.8	33.6	1.000009	
83000.0	25.0	-51.0	0.	-0.	39.2	580.3	214.8	24.8	1.000009	
83500.0	24.4	-50.9	0.	-0.	38.3	580.5	214.8	14.5	1.000009	
84000.0	23.9	-50.7	0.	-0.	37.4	580.8	206.4	5.6	1.000008	
84500.0	23.3	-50.5	0.	-0.	36.5	581.0	140.1	6.6	1.000008	
85000.0	22.8	-50.3	0.	-0.	35.7	581.2	73.9	7.6	1.000008	
85500.0	22.3	-50.1	0.	-0.	34.8	581.5	34.8	9.3	1.000008	
86000.0	21.8	-50.0	0.	-0.	34.0	581.7	34.8	11.9	1.000008	
86500.0	21.3	-49.8	0.	-0.	33.2	581.9	34.8	14.5	1.000007	
87000.0	20.8	-49.6	0.	-0.	32.4	582.2	349.0	13.1	1.000007	
87500.0	20.3	-49.4	0.	-0.	31.6	582.4	282.7	9.8	1.000007	
88000.0	19.8	-49.2	0.	-0.	30.9	582.7	216.5	6.6	1.000007	
88500.0	19.4	-49.1	0.	-0.	30.1	582.9	214.8	8.1	1.000007	
89000.0	18.9	-48.9	0.	-0.	29.4	583.1	214.8	9.8	1.000007	
89500.0	18.5	-48.8	0.	-0.	28.8	583.2	230.9	10.8	1.000006	
90000.0	18.1	-48.8	0.	-0.	28.1	583.3	296.4	9.8	1.000006	
90500.0	17.7	-48.7	0.	-0.	27.4	583.4	2.0	8.7	1.000006	
91000.0	17.3	-48.6	0.	-0.	26.8	583.5	34.8	7.6	1.000006	
91500.0	16.9	-48.6	0.	-0.	26.2	583.5	34.8	6.5	1.000006	
92000.0	16.5	-48.5	0.	-0.	25.6	583.6	34.8	5.3	1.000006	
92500.0	16.1	-48.4	0.	-0.	25.0	583.7	34.8	4.8	1.000006	
93000.0	15.8	-48.4	0.	-0.	24.4	583.8	34.8	4.6	1.000005	

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

UPPER AIR DATA
0083003902
WHITE SANDS SITE
TABLE VI (Cont)

STATION ALTITUDE 3989.0 FEET MSL
4 OCT. 66 0500 HRS MST
ASCENSION NO. 763

MSTM SITE COORDINATES
E 488,580 FEET
N 185,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA		INDEX OF REFRACTION
		AIR DEGREES CENTIGRADE	DEWPOINT CENTIGRADE				DIRECTION DEGREES(TN)	SPEED KNOTS	
93500.0	15.4	-48.5	0.	**	23.9	583.9	34.4	6.4	1.000005
94000.0	15.1	-48.2	0.	**	23.3	584.0	328.8	5.0	1.000005
94500.0	14.7	-48.2	0.	**	22.8	584.1	263.3	5.7	1.000005
95000.0	14.4	-48.1	0.	**	22.3	584.1	199.6	6.5	1.000005
95500.0	14.1	-48.0	0.	**	21.8	584.2	140.9	7.5	1.000005
96000.0	13.7	-48.0	0.	**	21.3	584.3	82.3	8.6	1.000005
96500.0	13.4	-47.9	0.	**	20.8	584.4	63.8	8.0	1.000005
97000.0	13.1	-47.8	0.	**	20.3	584.5	75.9	6.2	1.000005
97500.0	12.8	-47.4	0.	**	19.8	585.0	88.0	4.3	1.000004
98000.0	12.5	-46.8	0.	**	19.3	585.8	76.6	5.9	1.000004
98500.0	12.3	-46.2	0.	**	18.8	586.5	65.0	7.5	1.000004
99000.0	12.0	-45.6	0.	**	18.4	587.3	54.4	8.2	1.000004
99500.0	11.7	-45.0	0.	**	17.9	588.1	44.7	8.1	1.000004
100000.0	11.5	-44.4	0.	**	17.5	588.9	35.1	8.0	1.000004
100500.0	11.2	-43.8	0.	**	17.0	589.6	34.6	10.1	1.000004
101000.0	11.0	-43.2	0.	**	16.6	590.4	34.6	12.4	1.000004
101500.0	10.7	-42.6	0.	**	16.2	591.2			1.000004
102000.0	10.5	-42.0	0.	**	15.8	591.9			1.000004
102500.0	10.2	-41.4	0.	**	15.4	592.7			1.000003
103000.0	10.0	-40.8	0.	**	15.0	593.5			1.000003
103500.0	9.8	-41.7	0.	**	14.7	592.3			1.000003

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL
 4 OCT. 66 0800 HRS MST
 ASCENSION NU. 704

UPPER AIR DATA
 0083003903
 WHITE SANDS SITE
 TABLE VII

WSTM SITE COORDINATES
 E 488,580 FEET
 N 185,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA		INDEX OF REFRACTION
		AIR DEGREES CENTIGRADE	DEMPUNT CENTIGRADE				DIRECTION DEGREES(TN)	SPEED KNOTS	
3989.0	878.5	17.7	8.1	53.0	1047.5	665.6	30.0	9.9	1.000282
4000.0	878.2	17.7	8.0	52.9	1047.2	665.6	30.0	9.9	1.000281
4500.0	862.6	16.9	6.0	48.6	1032.1	664.5	29.6	10.0	1.000272
5000.0	847.4	17.0	5.9	47.6	1013.3	664.6	29.1	10.0	1.000267
5500.0	832.3	16.8	5.5	47.1	996.3	664.3	28.7	10.0	1.000263
6000.0	817.5	15.8	4.7	47.4	981.7	663.2	28.2	10.1	1.000257
6500.0	803.0	14.9	4.0	47.6	967.4	662.2	42.6	9.2	1.000253
7000.0	788.7	14.0	3.2	47.9	953.4	661.1	70.5	7.4	1.000248
7500.0	774.6	13.0	2.5	48.6	939.7	659.9	98.1	7.9	1.000243
8000.0	760.6	12.0	1.8	49.9	926.3	658.6	125.5	9.3	1.000239
8500.0	746.9	10.9	1.2	51.1	913.1	657.3	138.7	10.9	1.000235
9000.0	733.4	9.8	0.5	52.3	900.1	656.0	149.5	12.6	1.000231
9500.0	720.1	8.1	2.5	67.7	888.6	654.3	154.5	13.3	1.000233
10000.0	706.9	6.8	1.3	68.0	876.8	652.6	159.3	14.0	1.000228
10500.0	694.0	5.4	-0.0	68.0	865.2	650.9	162.4	14.1	1.000223
11000.0	681.2	4.7	1.8	81.4	851.0	650.3	165.7	14.2	1.000224
11500.0	668.5	3.8	2.0	88.1	837.8	649.3	170.8	14.5	1.000222
12000.0	656.1	2.5	-0.1	82.6	826.2	647.7	175.8	14.7	1.000214
12500.0	643.8	1.3	-2.2	77.1	814.8	646.1	180.1	16.3	1.000208
13000.0	631.8	0.1	-4.4	71.6	803.5	644.5	184.0	18.1	1.000201
13500.0	619.9	-1.0	-6.2	68.3	791.9	643.1	185.4	20.9	1.000196
14000.0	608.2	-2.0	-6.9	69.3	779.8	641.8	186.1	23.9	1.000192
14500.0	596.6	-3.1	-7.7	70.2	768.0	640.6	185.9	27.1	1.000189
15000.0	585.3	-4.1	-8.5	71.2	756.3	639.4	188.2	29.7	1.000185
15500.0	574.2	-5.2	-9.6	71.5	745.3	637.9	192.4	31.7	1.000182
16000.0	563.1	-7.4	-15.2	54.0	737.3	635.2	196.5	33.4	1.000174
16500.0	552.2	-6.3	-23.2	24.9	720.5	636.3	200.7	35.0	1.000166
17000.0	541.5	-7.0	-24.1	24.4	708.4	635.4	204.4	36.3	1.000162
17500.0	530.9	-7.8	-24.9	23.9	696.6	634.5	207.5	37.5	1.000160
18000.0	520.6	-8.5	-25.8	23.5	684.9	633.6	207.9	38.3	1.000157

UPPER AIR DATA
0083003903
WHITE SANDS SITE
TABLE VII (Cont)

STATION ALTITUDE 3989.0 FEET MSL
4 OCT. 66 0800 HRS MST
ASCENSION NO. 764

WSTH SITE COORDINATES
E 488.500 FEET
N 185.045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	AIR TEMPERATURE DEGREES CENTIGRADE	REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	DIRECTION DEGREES (TN)	WIND DATA SPEED KNOTS	INDEX OF REFRACTION
18500.0	510.4	-9.2	23.0	673.5	652.7	208.1	39.2	1.000154
19000.0	500.5	-10.0	22.5	662.2	651.9	208.1	40.2	1.000151
19500.0	490.8	-10.7	22.0	651.2	651.0	208.1	41.1	1.000148
20000.0	481.2	-11.4	21.6	640.3	650.1	208.1	41.9	1.000146
20500.0	471.8	-12.2	21.1	629.6	629.2	208.0	42.7	1.000143
21000.0	462.4	-13.2	21.2	619.4	628.0	207.9	43.5	1.000141
21500.0	453.1	-14.2	21.4	609.5	626.7	208.2	43.7	1.000138
22000.0	444.0	-15.3	21.6	599.8	625.4	208.7	43.6	1.000136
22500.0	435.1	-16.4	21.8	590.2	624.0	209.6	44.2	1.000134
23000.0	426.4	-17.5	22.0	580.8	622.7	210.6	45.0	1.000131
23500.0	417.8	-18.5	22.2	571.5	621.4	211.2	46.4	1.000129
24000.0	409.4	-19.6	22.5	562.4	620.1	211.8	48.0	1.000127
24500.0	401.2	-20.7	22.7	553.5	618.8	210.8	50.0	1.000125
25000.0	393.1	-21.7	22.9	544.7	617.5	209.4	53.5	1.000123
25500.0	385.2	-22.6	23.0	535.5	616.4	207.3	57.0	1.000121
26000.0	377.2	-23.2	23.0	525.8	615.6	205.0	60.7	1.000118
26500.0	369.5	-23.9	23.0	516.3	614.8	203.1	63.7	1.000116
27000.0	361.9	-24.5	23.0	507.0	614.0	201.6	66.2	1.000114
27500.0	354.4	-25.2	23.0	497.9	613.2	200.7	68.3	1.000112
28000.0	347.0	-26.2	23.0	489.5	612.0	200.3	70.2	1.000110
28500.0	339.7	-27.2	23.0	481.2	610.7	200.1	70.3	1.000108
29000.0	332.6	-28.2	23.0	473.1	609.4	200.1	68.4	1.000106
29500.0	325.7	-29.3	23.0	465.1	608.1	200.2	66.4	1.000104
30000.0	318.8	-30.3	23.0	457.3	606.9	200.7	64.4	1.000103
30500.0	312.1	-30.1	23.0	447.4	607.1	201.3	63.3	1.000100
31000.0	305.5	-30.6	23.0	438.8	606.4	202.6	67.7	1.000098
31500.0	299.0	-31.9	23.0	431.6	604.9	204.1	71.4	1.000097
32000.0	292.6	-33.1	23.0	424.6	603.3	206.9	67.3	1.000095
32500.0	286.3	-34.3	23.0	417.6	601.8	209.7	63.4	1.000094
33000.0	280.2	-35.5	23.0	410.8	600.2	212.3	61.3	1.000092

UPPER AIR DATA
0083003903
WHITE SANDS SITE
TABLE VII (Cont)

STATION ALTITUDE 3989.0 FEET MSL
4 OCT. 66
ASCENSION NO. 764

WSTM SITE COORDINATES
E 488,580 FEET
N 185,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE AIR DEGREES	TEMPERATURE DEWPOINT CENTIGRADE	REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DIRECTION DEGREES(TN)	WIND SPEED KNOTS	INDEX OF REFRACTION
33500.0	274.2	-36.7	-50.9	21.8**	403.9	598.8	215.2	59.2	1.000090
34000.0	268.2	-37.6	-53.5	17.6**	396.7	597.6	219.4	50.9	1.000089
34500.0	262.3	-38.5	-56.4	13.5**	389.5	596.4	221.6	48.3	1.000087
35000.0	256.5	-39.5	-60.1	9.4**	382.5	595.2	221.2	51.6	1.000085
35500.0	250.9	-40.4	-65.2	5.2**	375.7	594.0	221.1	59.1	1.000084
36000.0	245.4	-41.4	-76.5	1.1**	368.9	592.8	221.0	67.8	1.000082
36500.0	239.9	-42.5	0.	0.	362.4	591.3	221.2	70.4	1.000081
37000.0	234.4	-43.7	0.	0.	356.0	589.8	221.5	72.5	1.000079
37500.0	229.0	-45.0	0.	0.	349.7	588.2	221.6	73.6	1.000078
38000.0	223.8	-46.2	0.	0.	343.6	586.6	221.6	74.0	1.000077
38500.0	218.7	-47.5	0.	0.	337.6	585.0	221.6	74.1	1.000075
39000.0	213.7	-48.7	0.	0.	331.7	583.4	221.9	70.3	1.000074
39500.0	208.8	-49.9	0.	0.	325.9	581.7	221.4	66.4	1.000073
40000.0	204.0	-51.2	0.	0.	320.2	580.1	221.1	63.6	1.000071
40500.0	199.3	-52.4	0.	0.	314.6	578.5	220.9	61.1	1.000070
41000.0	194.8	-53.7	0.	0.	309.2	576.9	220.3	60.0	1.000069
41500.0	190.3	-54.9	0.	0.	303.8	575.3	219.8	59.2	1.000068
42000.0	185.0	-56.1	0.	0.	298.6	573.6	219.3	61.0	1.000066
42500.0	181.6	-57.4	0.	0.	293.3	572.0	218.9	63.7	1.000065
43000.0	177.3	-58.6	0.	0.	288.0	570.3	219.5	64.2	1.000064
43500.0	173.0	-59.5	0.	0.	282.2	569.1	220.4	63.6	1.000063
44000.0	168.8	-60.0	0.	0.	276.0	568.4	221.2	64.1	1.000061
44500.0	164.7	-60.5	0.	0.	269.9	567.8	221.9	65.0	1.000060
45000.0	160.7	-61.1	0.	0.	264.0	567.1	222.2	61.7	1.000059
45500.0	156.3	-61.6	0.	0.	258.1	566.4	222.4	56.2	1.000057
46000.0	152.9	-62.1	0.	0.	252.5	565.7	221.9	53.5	1.000056
46500.0	149.2	-62.6	0.	0.	246.9	565.0	220.8	52.7	1.000055
47000.0	145.6	-63.1	0.	0.	241.5	564.4	219.3	51.6	1.000054
47500.0	142.0	-63.6	0.	0.	236.1	563.7	217.5	50.1	1.000053
48000.0	138.6	-64.1	0.	0.	230.9	563.0	216.2	49.4	1.000051

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE HAS BEEN USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL
 4 OCT. 66 0800 HRS MST
 ASCENSION NO. 764

UPPER AIR DATA
 0083003903
 WHITE SANDS SITE
 TABLE VII (cont)

MSM SITE COORDINATES
 E 488,580 FEET
 N 185,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA		INDEX OF REFRACTION
		AIR DEGREES	DEWPOINT CENTIGRADE				DIRECTION DEGREES (TN)	SPEED KNOTS	
48500.0	135.2	-64.6	0.	-0.	225.8	562.3	215.7	49.8	1.000080
49000.0	131.9	-65.1	0.	-0.	220.9	561.6	215.2	50.2	1.000049
49500.0	128.7	-65.6	0.	-0.	216.0	560.9	215.6	50.4	1.000048
50000.0	125.5	-66.1	0.	-0.	211.3	560.2	214.1	50.6	1.000047
50500.0	122.5	-66.6	0.	-0.	206.6	559.4	213.6	50.4	1.000046
51000.0	119.5	-67.1	0.	-0.	202.1	558.9	213.1	50.2	1.000045
51500.0	116.5	-67.5	0.	-0.	197.5	558.3	212.5	49.5	1.000044
52000.0	113.6	-67.8	0.	-0.	192.8	558.0	212.0	48.9	1.000043
52500.0	110.8	-68.1	0.	-0.	188.3	557.6	212.0	47.9	1.000042
53000.0	108.0	-68.4	0.	-0.	183.8	557.2	212.1	46.9	1.000041
53500.0	105.3	-68.7	0.	-0.	179.5	556.8	214.4	46.6	1.000040
54000.0	102.7	-68.1	0.	-0.	174.0	557.5	217.3	46.6	1.000039
54500.0	100.2	-67.5	0.	-0.	169.7	558.4	220.7	46.6	1.000038
55000.0	97.7	-66.9	0.	-0.	165.0	559.2	224.5	46.8	1.000037
55500.0	95.3	-66.2	0.	-0.	160.4	560.1	227.2	46.8	1.000036
56000.0	92.9	-66.5	0.	-0.	156.6	559.8	228.3	46.7	1.000035
56500.0	90.6	-67.7	0.	-0.	153.6	558.2	228.7	46.4	1.000034
57000.0	88.4	-68.2	0.	-0.	150.2	557.4	226.9	45.3	1.000033
57500.0	86.2	-67.3	0.	-0.	145.8	558.7	224.9	44.3	1.000032
58000.0	84.1	-66.3	0.	-0.	141.6	560.0	221.0	43.8	1.000032
58500.0	82.0	-65.3	0.	-0.	137.5	561.3	217.1	43.2	1.000031
59000.0	80.0	-64.4	0.	-0.	133.4	562.6	215.3	43.5	1.000030
59500.0	78.0	-63.4	0.	-0.	129.6	563.9	213.8	43.7	1.000029
60000.0	76.1	-62.9	0.	-0.	126.1	564.7	212.9	46.6	1.000028
60500.0	74.2	-62.8	0.	-0.	123.0	564.8	212.1	45.4	1.000027
61000.0	72.4	-62.7	0.	-0.	119.8	564.9	211.9	45.6	1.000027
61500.0	70.7	-62.6	0.	-0.	117.0	565.0	211.9	45.6	1.000026
62000.0	69.0	-62.5	0.	-0.	114.1	565.1	211.9	41.5	1.000025
62500.0	67.3	-62.4	0.	-0.	111.3	565.2	211.9	33.5	1.000025
63000.0	65.7	-62.3	0.	-0.	108.5	565.4	211.9	27.4	1.000024

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 5989.0 FEET MSL
 4 OCT. 66 0800 HRS MSL
 ASCENSION NO. 764

UPPER AIR DATA
 0083003903
 WHITE SANDS SITE
 TABLE VII (Cont)

WSTM SITE COORDINATES
 E 488°580 FEET
 N 185°045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA DIRECTION DEGREES (TN)	SPEED KNOTS	INDEX OF REFRACTION
		AIR DEGREES CENTIGRADE	DEWPOINT CENTIGRADE						
63500.0	64.1	-61.9	0.	-0.	105.7	566.0	211.9	26.1	1.000024
64000.0	62.6	-61.2	0.	-0.	102.6	566.9	211.9	24.7	1.000023
64500.0	61.1	-60.4	0.	-0.	100.0	567.9	211.9	24.5	1.000022
65000.0	59.6	-59.7	0.	-0.	97.3	568.9	211.9	24.2	1.000022
65500.0	58.2	-59.0	0.	-0.	94.7	569.8	211.9	23.2	1.000021
66000.0	56.8	-58.3	0.	-0.	92.1	570.8	211.9	22.5	1.000021
66500.0	55.4	-57.5	0.	-0.	89.6	571.7	211.9	20.8	1.000020
67000.0	54.1	-56.8	0.	-0.	87.2	572.7	211.9	19.1	1.000019
67500.0	52.8	-56.2	0.	-0.	84.8	573.5	212.2	18.6	1.000019
68000.0	51.6	-56.1	0.	-0.	82.8	573.6	213.4	15.3	1.000018
68500.0	50.4	-56.1	0.	-0.	80.8	573.7	214.5	12.0	1.000018
69000.0	49.2	-56.0	0.	-0.	78.9	573.7	216.2	29.1	1.000018
69500.0	48.0	-56.0	0.	-0.	77.1	573.8	217.9	26.4	1.000017
70000.0	46.9	-55.9	0.	-0.	75.2	573.9	219.6	22.6	1.000017
70500.0	45.8	-55.9	0.	-0.	73.4	573.9	221.2	20.4	1.000016
71000.0	44.7	-55.8	0.	-0.	71.7	574.0	222.8	17.3	1.000016
71500.0	43.7	-55.6	0.	-0.	69.9	574.3	223.2	15.0	1.000016
72000.0	42.6	-55.1	0.	-0.	68.1	575.0	221.4	14.4	1.000015
72500.0	41.7	-54.5	0.	-0.	66.4	575.7	219.7	13.8	1.000015
73000.0	40.7	-54.0	0.	-0.	64.7	575.5	217.6	12.9	1.000014
73500.0	39.7	-53.4	0.	-0.	63.0	577.2	215.2	11.8	1.000014
74000.0	38.8	-53.0	0.	-0.	61.4	577.8	212.9	10.8	1.000014
74500.0	37.9	-52.9	0.	-0.	60.0	577.9	212.8	10.1	1.000013
75000.0	37.0	-52.8	0.	-0.	58.6	578.0	212.1	9.7	1.000013
75500.0	36.2	-52.8	0.	-0.	57.2	578.1	212.1	9.2	1.000013
76000.0	35.3	-52.7	0.	-0.	55.9	578.2	212.1	11.0	1.000012
76500.0	34.5	-52.6	0.	-0.	54.5	578.3	212.1	13.4	1.000012
77000.0	33.7	-52.5	0.	-0.	53.3	578.4	212.1	15.8	1.000012
77500.0	33.0	-52.4	0.	-0.	52.0	578.5	212.1	17.4	1.000012
78000.0	32.2	-52.4	0.	-0.	50.8	578.6	212.1	18.9	1.000011

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION**

UPPER AIR DATA
0083003903
WHITE SANDS SITE
TABLE VII (Cont)

STATION ALTITUDE 3989.0 FEET MSL
4 OCT. 66 0800 HRS MST
ASCENSION NO. 764

WSM SITE COORDINATES
E 489,580 FEET
N 185,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE AIR DEGREES CENTIGRADE	REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DIRECTION DEGREES TRUE	WIND SPEED KNOTS	INDEX OF REFRACTION
78500.0	31.4	-52.3	**	49.6	576.7	212.1	20.3	1.000011
79000.0	30.7	-52.2	**	48.4	578.0	212.1	20.5	1.000011
79500.0	30.0	-52.1	**	47.3	579.9	212.1	20.4	1.000011
80000.0	29.3	-52.1	**	46.2	579.0	212.1	18.4	1.000010
80500.0	28.6	-52.0	**	45.1	579.1	212.1	11.6	1.000010
81000.0	28.0	-51.9	**	44.1	579.2	212.1	4.9	1.000010
81500.0	27.3	-51.8	**	43.0	579.3	212.1	2.4	1.000010
82000.0	26.7	-51.7	**	42.0	579.4	212.1	2.9	1.000009
82500.0	26.1	-51.7	**	41.0	579.5	212.1	3.5	1.000009
83000.0	25.5	-51.6	**	40.1	579.6	161.6	3.7	1.000009
83500.0	24.9	-51.5	**	39.1	579.7	97.6	3.9	1.000009
84000.0	24.3	-51.4	**	38.2	579.8	33.6	4.0	1.000009
84500.0	23.8	-51.4	**	37.3	579.9	32.1	4.4	1.000008
85000.0	23.2	-51.3	**	36.5	580.0	32.1	4.9	1.000008
85500.0	22.7	-51.2	**	35.6	580.1	32.1	5.4	1.000008
86000.0	22.2	-51.1	**	34.8	580.2	32.1	6.5	1.000008
86500.0	21.6	-50.6	**	33.9	580.9	32.1	7.7	1.000008
87000.0	21.2	-49.8	**	33.0	581.9	32.1	8.6	1.000007
87500.0	20.7	-49.0	**	32.1	582.9	32.1	8.7	1.000007
88000.0	20.2	-48.3	**	31.3	583.9	32.1	8.9	1.000007
88500.0	19.7	-47.5	**	30.5	584.9	15.0	8.3	1.000007
89000.0	19.3	-46.7	**	29.7	585.9	314.1	6.0	1.000007
89500.0	18.9	-46.2	**	29.0	586.6	253.2	3.7	1.000006
90000.0	18.4	-46.0	**	28.3	586.8	231.7	2.3	1.000006
90500.0	18.0	-45.9	**	27.6	587.0	291.9	2.7	1.000006
91000.0	17.6	-45.8	**	27.0	587.2	352.2	3.0	1.000006
91500.0	17.2	-45.6	**	26.4	587.3	32.1	3.0	1.000006
92000.0	16.9	-45.5	**	25.8	587.5	32.1	2.3	1.000006
92500.0	16.5	-45.4	**	25.2	587.7	32.1	1.5	1.000006
93000.0	16.1	-45.2	**	24.6	587.8	11.3	0.9	1.000005

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL
 4 OCT. 66 0800 HRS MST
 ASCENSION NO. 764

UPPER AIR DATA
 0083003903
 WHITE SANDS SITE
 TABLE VII (Cont)

WSTM SITE COORDINATES
 E 488,580 FEET
 N 185,043 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE AIR DEGREES CENTIGRADE	REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA		INDEX OF REFRACTION
						DIRECTION DEGREES(TN)	SPEED KNOTS	
93500.0	15.8	-45.1	-0.	24.1	588.0	311.1	0.7	1.000005
94000.0	15.4	-45.0	-0.	23.5	588.2	250.9	0.5	1.000005
94500.0	15.1	-44.9	-0.	23.0	588.3	212.1	1.2	1.000005
95000.0	14.7	-44.7	-0.	22.5	588.5	212.1	3.5	1.000005
95500.0	14.4	-44.6	-0.	21.9	588.7	212.1	5.8	1.000005
96000.0	14.1	-44.5	-0.	21.4	588.8	212.1	7.8	1.000005
96500.0	13.8	-44.3	-0.	21.0	589.0	212.1	9.1	1.000005
97000.0	13.5	-44.2	-0.	20.5	589.2	212.1	10.5	1.000005
97500.0	13.2	-44.1	-0.	20.0	589.4	212.1	11.0	1.000004
98000.0	12.9	-43.9	-0.	19.6	589.5	212.1	9.8	1.000004
98500.0	12.6	-43.8	-0.	19.1	589.7	212.1	8.5	1.000004
99000.0	12.3	-43.7	-0.	18.7	589.9	212.1	7.2	1.000004
99500.0	12.0	-43.5	-0.	18.2	590.0	212.1	6.2	1.000004
100000.0	11.8	-43.4	-0.	17.8	590.2	212.1	5.3	1.000004
100500.0	11.5	-43.3	-0.	17.4	590.4	212.1	4.4	1.000004
101000.0	11.2	-43.1	-0.	17.0	590.5	212.1		1.000004
101500.0	11.0	-43.0	-0.	16.6	590.7			1.000004
102000.0	10.7	-42.9	-0.	16.3	590.9			1.000004
102500.0	10.5	-42.7	-0.	15.9	591.0			1.000004
103000.0	10.3	-42.6	-0.	15.5	591.2			1.000003
103500.0	10.0	-42.5	-0.	15.2	591.4			1.000003
104000.0	9.8	-42.4	-0.	14.8	591.5			1.000003
104500.0	9.6	-42.2	-0.	14.5	591.7			1.000003

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

RELEASE TIME (MST)	SECOND-STAGE IMPACT DISPLACEMENT IN MILES DUE TO WIND												AZI- MUTH (DEG- REES)	THEORETICAL IMPACT FROM LAUNCHER (IN MILES)			
	11-21.6 FT						4000-73497 FT							TOTAL	RANGE	N-S	E-W
	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W					
RAMIN- SONDE	FIBAL																
0500	0600	6.3N	0.0	23.1N	2.3E	18.6S	18.4W	12.6N	16.1W	353.7	66.5	66.1N	7.3W				
0500	0630	10.0N	1.5E	22.5N	2.0E	18.6S	18.4W	13.2N	14.9W	354.9	67.5	67.2N	6.1W				
0500	0700	8.8N	1.2E	20.3N	1.9E	18.6S	18.4W	10.5N	15.3W	352.4	64.4	63.8N	8.5W				
0500	0720	14.9N	4.0E	22.4N	2.2E	18.6S	18.4W	18.7N	12.2W	357.3	72.1	72.0N	3.4W				
0500	0735	12.1N	3.6E	22.6N	3.5E	18.6S	18.4W	16.1N	11.3W	357.5	69.4	69.1N	2.5W				
0500	0742	11.9N	1.3E	22.6N	3.8E	18.6S	18.4W	15.9N	13.3W	356.3	69.4	69.2N	4.5W				
0500	0750	13.3N	2.7E	22.5N	3.8E	18.6S	18.4W	17.2N	11.9W	357.5	70.6	70.5N	3.1W				
0500	0803	14.7N	2.8E	24.6N	3.9E	18.6S	18.4W	20.7N	12.7W	357.7	74.1	74.0N	2.9W				
0800	0802	14.7N	2.8E	24.6N	3.9E	13.5S	13.6W	25.8N	6.9W	001.4	79.1	79.1N	1.9E				

AZIMUTH (DEG- REES)	MILES FROM LAUNCHER		
	RANGE	N-S	E-W
014.0	54.9	53.3N	13.7E
009.4	54.0	53.3N	8.8E
357.6	70.0	69.9N	2.9W
357.8	66.6	66.5N	2.5W
014.0	0.8	0.8N	0.2E
N/A	N/A	N/A	N/A

LAUNCHER SETTING (ELEVATION 86.1 DEGREES QE)
NO WIND IMPACT
PREDICTED SECOND-STAGE IMPACT
SECOND-STAGE IMPACT, RADAR TRACK
PREDICTED BOOSTER IMPACT
ACTUAL BOOSTER IMPACT

TABLE VIII. IMPACT PREDICTION DATA
NIKE-HYDAC 3TV (SR-010)

UNCLASSIFIED

Security Classification

DOCUMENT CONTROL DATA - RAD

Security classification of this, title of document and indexing classification must be entered when the source report is classified

1. ORIGINATING ACTIVITY (Corporate name)		2a. REPORT SECURITY CLASSIFICATION	
U. S. Army Electronics Command Fort Monmouth, New Jersey		UNCLASSIFIED	
		2b. GROUP	
3. REPORT TITLE			
METEOROLOGICAL DATA REPORT, NIKE-HYDAC STV (SR-040)			
4. DESCRIPTIVE NOTES (Type of report and inclusive dates)			
5. AUTHOR(S) (Last name, first name, initial)			
CARTER, Len E.			
6. REPORT DATE		7a. TOTAL NO. OF PAGES	7b. NO. OF REFS
November 1966		22	None
8a. CONTRACT OR GRANT NO.	9a. ORIGINATOR'S REPORT NUMBER(S)		
	DR-103		
8b. PROJECT NO.	9b. OTHER REPORT NO(S) (Any other numbers that may be assigned to the report)		
c. DA Task IV650212A127-02			
z.			
10. AVAILABILITY/LIMITATION NOTICES			
Dist. of this document is unlimited.			
11. SUPPLEMENTARY NOTES		12. SPONSORING MILITARY ACTIVITY	
		U. S. Army Electronics Command Atmospheric Sciences Laboratory White Sands Missile Range, New Mexico	
13. ABSTRACT			
<p>Meteorological data gathered for the launching of Nike-Hydac STV (SR-040) are presented for the Ballistic Systems Division, U. S. Air Force, Avco Corporation and for ballistic studies. The data appear, along with calculated ballistic data, in tabular form.</p>			

KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
1. Ballistics						
2. Meteorology						
3. Wind						

INSTRUCTIONS

1. **ORIGINATING ACTIVITY:** Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (corporate address) issuing the report.
- 2a. **REPORT SECURITY CLASSIFICATION:** Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.
- 2b. **GROUP:** Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.
3. **REPORT TITLE:** Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parentheses immediately following the title.
4. **DESCRIPTIVE NOTES:** If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.
5. **AUTHOR(S):** Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.
6. **REPORT DATE:** Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.
- 7a. **TOTAL NUMBER OF PAGES:** The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.
- 7b. **NUMBER OF REFERENCES:** Enter the total number of references cited in the report.
- 8a. **CONTRACT OR GRANT NUMBER:** If appropriate, enter the applicable number of the contract or grant under which the report was written.
- 8b, 8c, & 8d. **PROJECT NUMBER:** Enter the appropriate military department identification, such as project number, subproject number, system number, task number, etc.
- 9a. **ORIGINATOR'S REPORT NUMBER:** Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.
- 9b. **OTHER REPORT NUMBER:** If the report has been assigned any other report numbers (either by the originator or by the sponsor), also enter this number(s).

10. **AVAILABILITY/LIMITATION NOTICES:** Enter any limitations on further dissemination of the report, other than those imposed by security classification, using standard statements such as:
 - (1) "Qualified requesters may obtain copies of this report from DDC."
 - (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
 - (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
 - (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
 - (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. **SUPPLEMENTARY NOTES:** Use for additional explanatory notes.
12. **SPONSORING MILITARY ACTIVITY:** Enter the name of the departmental project office or laboratory sponsoring (paying for) the research and development. Include address.
13. **ABSTRACT:** Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C) or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. **KEY WORDS:** Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical content. The assignment of links, rules, and weights is optional.