

UNCLASSIFIED

AD NUMBER

AD811154

LIMITATION CHANGES

TO:

Approved for public release; distribution is unlimited.

FROM:

Distribution authorized to U.S. Gov't. agencies and their contractors; Critical Technology; APR 1967. Other requests shall be referred to Air Force Rocket Propulsion Laboratory, Attn: RPPR/STINFO, Edwards, CA 93523. This document contains export-controlled technical data.

AUTHORITY

AFRPL ltr, 27 Oct 1971

THIS PAGE IS UNCLASSIFIED

AFRPL-TR-67-83

811154

**STUDY OF HEAT TRANSFER CHARACTERISTICS
OF HOT-GAS IGNITERS**


Third Quarterly Progress Report for Period Ending
15 March 1967

J. A. Wrubel

Rocketdyne, A Division of North American Aviation, Inc.,
6633 Canoga Avenue, Canoga Park, California

TECHNICAL REPORT AFRPL-TR-67-83

April 1967



This document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of AFRPL (RPPR/STINFO), Edwards, California 93523.

Air Force Rocket Propulsion Laboratory
Research and Technology Division
Edwards, California
Air Force Systems Command
United States Air Force

NOTICES

When U.S. Government drawings, specifications, or other data are used for any purpose other than a definitely related Government procurement operation, the Government thereby incurs no responsibility nor any obligation whatsoever, and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise, or in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

The information in this study was generated under the sponsorship of the Air Force Rocket Propulsion Laboratory, Research and Technology Division, Edwards Air Force Base, California, which is part of the Air Force Systems Command, United States Air Force.

AFRPL-TR-67-83

STUDY OF HEAT TRANSFER CHARACTERISTICS
OF HOT-GAS IGNITERS

Third Quarterly Progress Report for Period Ending
15 March 1967

J. A. Wrubel

Rocketdyne, A Division of North American Aviation, Inc.,
6633 Canoga Avenue, Canoga Park, California

April 1967

This document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of AFRPL (RPPR/STINFO), Edwards, California 93523.

Air Force Rocket Propulsion Laboratory
Research and Technology Division
Edwards, California
Air Force Systems Command
United States Air Force

FOREWORD

This technical report presents the effort conducted during the third quarter under a contract entitled "Study of Heat Transfer Characteristics of Hot-Gas Igniters." The study was conducted by the Research Division of Rocketdyne, a Division of North American Aviation, Inc. The third quarter effort, conducted during the period 16 December to 15 March 1967, was authorized by the USAF Rocket Propulsion Laboratory under Contract AF04(611)-11613. The Air Force Project Monitor is 1/Lt. C. E. Payne, RPMC.

This report has been assigned the Rocketdyne Report No. R-6856-3.

Publication of this report does not constitute Air Force approval of the report's findings or conclusions. It is published only for the exchange and stimulation of ideas.

CHARLES COOKE
Division Chief,
Solid Rocket Division

ABSTRACT

This program is concerned with determining the convective heat transfer characteristics of pyrogen igniters in both the aft-end and head-end configurations for three-pointed star and conocyl motor grains. Heat transfer modeling tests utilizing thin-plate calorimetric techniques are being conducted to evaluate the heat transfer distribution. The third quarter effort reported herein was directed toward completion of the model heat transfer tests, preparation of the model heat transfer data for machine computation, initiation of demonstration motor build-up, continuance of the head-end and aft-end fluid dynamic analysis, completion of a description of the "HOTGAS" computer program, and initiation of that portion of data reduction requiring machine computation.

CONTENTS

Foreword	ii
Abstract	iii
Summary	1
Introduction	2
Experimental Equipment	6
Experimental Operations	8
Data Analysis	9
"Hotgas" Computer Program	9
Data Reduction	18
Analytical Studies	20
Future Effort	21
Nomenclature	22
References	23

SUMMARY

During the third quarter of the "Study of the Heat Transfer Characteristics of Hot-Gas Igniters," major effort was directed toward completion of model heat transfer tests, test data analysis, demonstration motor build-up, and head-end and aft-end fluid dynamic analysis. The planned total of 90 model heat transfer tests were completed and the test data organized and tabulated. A description of the "HOTGAS" computer program was prepared to facilitate the assembly of the model heat transfer data for machine computations. These required computer runs were initiated toward the end of the period. Demonstration motor build-up is near completion. Fabrication of test section components is approximately 90 percent complete while test stand build-up is 50 percent complete. A literature survey in support of the head-end and aft-end fluid dynamic analysis was concluded. Review and analysis of the gathered material is continuing.

Demonstration motor build-up will be completed at the beginning of the fourth quarter. Shortly thereafter motor testing will commence. Data analysis and correlation will be completed toward the middle of the next quarter and the fluid dynamic analysis will be completed near the end of the next quarter. The demonstration motor firings will be conducted according to the testing schedule established during the first quarter.

INTRODUCTION

A 12-month program entitled "Study of Heat Transfer Characteristics of Hot-Gas Igniters," was initiated by the Rocketdyne Research Division under Contract AF04(611)-11613 on 16 June 1966. The objective of this study is to develop relationships which predict convective heat transfer from a hot-gas igniter to a solid propellant grain and to demonstrate that such relationships permit a quantitative prediction of the ignition delay. These relationships, based on a comprehensive testing program, will be derived for typical head-end and aft-end, hot-gas igniters for practical solid propellant grain designs, i.e., stars and conocyls. The testing program consists of: (1) a critical test to investigate a transient boundary layer mechanism, (2) schlieren tests to gain a fundamental understanding of the interaction of fluid dynamics upon the heat transfer from hot-gas igniters, (3) model heat transfer tests to determine the influence of geometric changes of solid propellant grain ports and position of the igniter nozzle on the heat transfer to the propellant surface, and (4) demonstration motor firings to determine the applicability of the developed relations to an actual propellant system.

Frequently, solid propellant rocket motors are ignited by hot-gas sources such as smaller burning solid propellant charges (pyrogen igniters) or pyrotechnic grains which exhaust their combustion products into the main combustion chamber through convergent or convergent-divergent nozzles located in either the head-end or aft-end of the motor. Historically, the design of hot-gas igniters evolved from empirical approximations developed by motor manufacturers based upon massive testing programs involving many different motor systems. Current refinements of available approximations still result in more costly hot-gas igniter design than would be necessary if generalized design principles were available. Because the pre-ignition period in hot-gas ignition largely involves a convective heat transfer process, a program under Contract AF04(611)-9884, entitled "A Study of the Heat Transfer Characteristics of Hot-Gas Ignition," (Ref. 1)

was conducted. This program developed generalized correlations and analytical procedures on a substantial theoretical and experimental basis that could define particular simple hot-gas ignition system requirements. The use of modeling techniques facilitated the gathering of pertinent information in a rapid and inexpensive manner.

Current ignition research programs are progressing significantly toward the elevation of ignition system design from an art to a science. Relationships correlating heat flux, pressure, and ignition delay have been developed for some rubber-base propellants under Contract AF04(611)-9701, entitled "Ignition of Solid Propellant Motors Under Vacuum," (Ref. 2). Of fundamental importance in the practical utilization of the preceding information is knowledge of the characteristics and mechanisms of the heat delivery from the igniter gas to the propellant surface. This was developed for cylindrical geometry in Ref. 1. The extension of the previously developed modeling techniques and procedures to more complex geometries (i.e., star and conocyl configurations), coupled with the data for a particular propellant from Ref. 2, should allow, for the first time, the scientific tailoring of an igniter to a specific solid propellant motor without recourse to empirical rules.

During the first quarter effort on the "Study of Heat Transfer Characteristics of Hot-Gas Igniters," (Ref. 3), major effort was directed toward reactivation of the hot-gas heater, design of test section components, procurement of materials, hardware fabrication, the computer program changeover, and test planning. Reactivation of the hot-gas heater eliminated the problem of oxide deposition on test section hardware, allowed far more rapid changeover of test section thermocouple instrumentation, and increased the response rate of the gaseous nitrogen pressure regulator. Test stand modifications were completed, and the checkout of the apparatus and design approaches was successful. All test section designs were completed. Fabrication was completed for: components for the critical experiment, components for the schlieren test, the optimum expansion ratio model igniter nozzles, and components for long-lead-time items for the demonstration motor firings. A tentative test matrix that included a total of 115 tests was formulated.

During the second quarter (Ref. 4), major effort was directed toward fabrication of the test sections for the model heat transfer experiments, procurement of the propellant grains for the demonstration motor test series, the conducting of a majority of the tests for the experimental phase of the program, completion of the computer program changeover, and test data analysis.

The model heat transfer test sections consist of star port and conocyl port grain configurations incorporating a rational change of geometric variables, i.e., star point angle, cone angle, cone spacing, and cross-sectional area. Eight test sections (five star and three conocyl) were fabricated.

A subcontract was let to the United Technology Center for the loading of UTP 3001 solid propellant into Rocketdyne-supplied hardware. The eight demonstration motor cartridges ordered consisted of three cylindrical port, four star port, and one solid port grain configurations.

The high gas temperature critical experiment and schlieren test series were concluded. The model heat transfer experiments were approximately two-thirds completed with 57 of a planned 90 tests accomplished. The computer program changeover was completed with the successful run of a trial case.

Test data analysis was completed for the high gas temperature critical experiment and schlieren tests. The critical experiment demonstrated that the heat transfer coefficient remained constant as a function of time when a high driving temperature potential was present. A letter was sent to those named on the final report distribution list of Contract AFO4(611)-9884, alerting them to this significant result. A general qualitative analysis of the schlieren tests which establishes the flow field created by head-end and aft-end, hot-gas igniters is presented in Ref. 4.

During the third quarter effort, described in detail in this report, the following tasks were accomplished: completion of the model heat transfer tests, preparation of the model heat transfer data for machine computation, initiation of build-up for the demonstration motor firings, continuance of the head-end and aft-end fluid dynamic analysis, completion of a description of the "HOTGAS" computer program; and initiation of that portion of data reduction requiring machine computation.

EXPERIMENTAL EQUIPMENT

A complete description of the hot gaseous nitrogen supply system and associated subsystems, located in Pit 2 of the Combustion and Heat Transfer Laboratory, Santa Susana Field Laboratory, is contained in AFRPL 65-158, the final report under Contract AF04(611)-9884. This test facility and applicable test section hardware fabricated previously are being utilized in the current program and, because their description has been presented previously, only modifications to the existing apparatus and newly designed equipment will be reported.

The design drawings of the demonstration motor case, head closure, window retainer, and exhaust nozzles were prepared early in the quarter. All other components necessary for a demonstration motor assembly were taken from an existing Rocketdyne solid propellant evaluation motor. The windowed demonstration motor case allows the use of a 12-inch-long propellant grain with an outside diameter of 6 inches. The 8.25 by 1.75 inch centered window section will enable observation of the ignition location for all of the various test conditions. Pressure instrumentation (high-response Photocon and medium-response Wiancko transducers) and the pyrogen igniter will be mounted in the forward closure of the demonstration motor. When testing in the aft-end mode, a plug will be inserted in the head-end pyrogen igniter port. To fulfill the required test configurations for this series, four ATJ graphite nozzle throat inserts were designed. Dimensions were established to be consistent with configurations that were tested during model heat transfer experiments except that the divergence half-angle for the nominal 4-inch-diameter nozzles was changed from 15 to 7 degrees.

Fabrication of the demonstration motor inert parts is near completion. The head closure was constructed and the ATJ graphite throat inserts were received from a vendor. Machining of the window retainer and demonstration motor case is 90 percent complete. Holes must still be drilled and tapped in these two parts. It is anticipated that fabrication will be completed early during the next quarter.

The UTP 3001 solid propellant grains were received from the United Technology Center. Longitudinal slots were cut through the grain web to allow photographic observation of ignition in the motor grain port. Plexiglas spacers were bonded into the slots and inert propellant was applied to sharp edges to inhibit spurious ignition at these locations. This completed propellant grain build-up.

Test stand build-up is approximately 50 percent complete. The electrical and instrumentation system which includes two Photocon lines, two Wiancko lines, igniter fire circuit, hydraulic cylinder actuation circuit, motion picture camera power lines, and timer circuit has been installed. Also, the actuator system has been assembled. Early next quarter, the actuator system and demonstration motor assembly will be installed in the auxiliary pad at the Combustion and Heat Transfer Laboratory. This will complete the effort on fabrication and build-up of experimental equipment for this contract.

EXPERIMENTAL OPERATIONS

During the third quarter, model heat transfer testing was completed. The planned total of 90 tests utilizing star port and conocyl port test sections in both the aft-end and head-end igniter configuration was accomplished. The test series included 55 head-end tests (35 star port and 20 conocyl port) and 35 aft-end tests (22 star port and 13 conocyl port). Test configurations were as shown in Ref. 3 , but the firing order was changed to reduce the number of physical changes between tests. The final test series, demonstration motor firings, will be accomplished during the fourth quarter.

DATA ANALYSIS

During the third quarter, a description of the "HOTGAS" computer program was written, test data reduction of the model heat transfer experiments continued, and preliminary analysis enabling the prediction of the ignition location and ignition delay for the demonstration motor firings was accomplished.

A general discussion of the computational process used in heat transfer data reduction was presented in Ref. 4. For continuity, some of that material is repeated in the following description of the "HOTGAS" computer program.

"HOTGAS" COMPUTER PROGRAM

Input

The input data for the HOTGAS computer program are received from two sources. The primary data are the Beckman 210 transient test data. The raw test data are scaled into temperature units (F) by Rocketdyne's 2T825 scaling program. This scaling program is run simultaneously with the HOTGAS reduction program and it feeds the data directly via the TRANS subroutine. The secondary input consists of constant values, option controls, and title heads. This is read in via input data cards. The input list and format is shown in Table 1.

Output

The printed output consists of time, gas-side and outside wall temperatures, heat fluxes, and gas temperatures.

A Stromberg-Carlson 4020 cathode ray tube (CRT) plots the calculated data on 9 inch by 9 inch graphs. Five types of graphs are available: (1) gas-side and outside wall temperatures vs time, (2) heat flux vs time,

TABLE 1

FORTRAN FIXED 10 DIGIT DECIMAL DATA

DECK NO. DATA		PROGRAMMER	DATE	PAGE	of	JOB NO.
NUMBER		IDENTIFICATION	DESCRIPTION DO NOT KEY PUNCH			
1	99.8		SIGNAL TO START CASE			
13						
25						
37						
49						
61						
1			TITLE HEAD LABELS CRT'S (BOTTOM LINE)			
13						
25						
37						
49						
61						
1	STAND		STAND NUMBER			
13						
25			RUN DATE			
37						
49			TITLE HEAD (SECOND LINE)			
61						
1						
13						
25						
37						
1			TITLE HEAD (FIRST LINE)			
13						
25						
37						
49						
61						

TABLE 1
(Continued)

DECK NO. DATA		PROGRAMMER	DATE	PAGE 2 of	JOB NO.
NUMBER	VECTOR LOCATION	IDENTIFICATION	DESCRIPTION	DO NOT KEY PUNCH	
1	0.01		C_1	$k = C_1 + C_2 \left(\frac{T_{w1} + T_{w2}}{2} \right)$	
13	0.02		C_2	THERMAL CONDUCTIVITY OF WALL MATERIAL (BTU/IN-SEC-°F)	
25	0.03		B_1		
37	0.04		B_2	$C_{p_{gas}} = B_1 + B_2 T_{gas} + B_3 T_{gas}^2 + B_4 T_{gas}^3$ (BTU/LB-°F)	
49	0.05	73	B_3		
61	0.06	5	B_4		
1	0.07		AREA	{ IF (-) WELL READ INDENTURE AREAS FROM A (251) TO A (300) IF (+) WILL ACCEPT VALUE AS CONSTANT AREA [IN ²] }	
13	0.08		D	D - DIAMETER OF TEST SECTION (in.)	
25	0.09		WD	WD - \dot{m} = WEIGHT FLOW RATE (lbm/SEC)	
37	0.10		WDA	$WDA \approx \rho \left(\frac{W}{W_0} \right)^2$ USED IN $\% \Delta C_{p_{gas}}$	
49	0.11	73		NUMBER OF DATA POINTS TO AVERAGE	
61	0.12	6	HTLOSS	IF (-) NO HEAT LOSS CORRECTION OF T_{gas} IF (+) HEAT LOSS CONSIDERED	
1	0.13		S	S - TEST SECTION WALL THICKNESS (in.)	
13	0.14		D_1	$C_p = D_1 + D_2 \left(\frac{T_{w1} + T_{w2}}{2} \right)$ SPECIFIC HEAT OF WALL MATERIAL (BTU/LB-°F)	
25	0.15		D_2		
37	0.16		GAS TEMP	{ IF (-) WILL CHECK A (201) FOR TC IDENTIFICATION IF (+) WILL ACCEPT VALUE AS CONSTANT TEMP (°F) }	
49	0.17	73	NRUN	NRUN - RUN NUMBER	
61	0.18	7	OPTAPE	IF (-) NO MAGNETIC TAPE OUTPUT IF (+) WILL STORE h, TIME, ΔT ON TAPE	
1	0.19		NCHAN	NCHAN - NUMBER OF CHANNELS REQUESTED IN PRIMARY LIST	
13	0.20		N	N - READS EVERY NEW TEMP, USE 1.0	
25	0.21		M	M - SAMPLE REDUCTION FACTOR IF $\Delta T > 1.0$, WILL CAUSE	
37	0.22		X/D	X/D LIMIT ON H X/D PLOT, BOUNDED (X/D) MAX	
49	0.23	73	H	H LIMIT ON H X/D PLOT	
61	0.24	8			

114-C-17 VELLUM

TABLE 1
(Continued)

DECK NO. DATA		PROGRAMMER	DATE	PAGE 3 of	JOB NO.
NUMBER	VECTOR LOCATION	IDENTIFICATION	DESCRIPTION DO NOT KEY PUNCH		
6.0	0.25		SECTION TO USE		
	0.26		SLICE TO USE		
	0.27		LOGICAL TAPE UNIT OF DATA TAPE		
	0.28				
	0.29				
	0.30				
	0.31				
	0.32				
	0.33				
	0.34				
	0.35				
	0.36				
	1.51				
	1.52				
	1.53				
	1.54				
	1.55				
	1.56				
	2.01				
	2.02				
	2.03				
	2.04				
	2.05				
	2.06				

IF (-) NO PLOTS AT ALL.
CROPT (IF (+)) WILL CHECK FOLLOWING OPTIONS

T, t, T₂ vs. Time Plot

Q/A vs. Time Plot

H vs. Time Plot

H vs. X/D Plot

PRIMARY LIST OF PARAMETERS THAT WILL BE FULLY EVALUATED. GIVE THE POSITION NUMBER ACCORDING TO THE ORDER OF SCALING.

THIS LIST CONTINUES TO LOCATION A(200) AND ADDITION CARDS PERMITTED.

GAS TEMP TC IF A(12) IS NEG. GIVE POSITION NUMBER OF CHANNEL PER SCALING ORDER.

SECONDARY LIST OF PARAMETERS TO BE EVALUATED TO TEMPS ONLY. LIST PER POSITION NUMBER. THIS LIST CONTINUES TO LOCATION A(240), ADDITIONAL CARDS PERMITTED.

TABLE 1
(Continued)

CHECK NO. DATA PROGRAMMER		DATE	PAGE	of	JOB NO.
NUMBER		IDENTIFICATION	DESCRIPTION DO NOT KEY PUNCH		
1	999		END OF CASE		
13					
25					
37					
49					
61					
1		240			
13	*		END OF JOB		
25					
37					
49					
61					
1		99900000			
13					
25					
37					
49					
61					
1					
13					
25					
37					
49					
61					
1					
13					
25					
37					
49					
61					

114-C-17 VELLUM

TABLE 1
(Concluded)

DECK NO. DATA		PROGRAMMER	DATE	PAGE 4 of	JOB NO.
NUMBER	VECTOR Location	IDENTIFICATION	DESCRIPTION	DO NOT KEY PUNCH	
1	2.5.1		AREAS - IF A(7) IS NEG., LIST INDIVIDUAL AREAS (in ²)		
13	2.5.2		HERE, IN SAME ORDER AS PRIMARY		
25	2.5.3		LIST. THIS LIST CONTINUES TO A(300),		
37	2.5.4		ADDITIONAL CARDS PERMITTED. IF A(7)		
49	2.5.5	73	IS POS.(+) OR MEAT LOSS NOT CONSIDERED		
61	2.5.6	1.60	LEAVE THIS LIST BLANK.		
1	3.0.1		X LOCATIONS OF TC'S FOR H ₂ O PLOT. THIS		
13	3.0.2		LIST CONTINUES TO A(350), ADDITIONAL		
25	3.0.3		CARDS PERMITTED. BE SURE THAT THE		
37	3.0.4		ORDER OF THIS LIST CORRESPONDS		
49	3.0.5	73	TO THE ORDER OF THE PRIMARY LIST.		
61	3.0.6	1.80	IF NO H ₂ O PLOT, LEAVE THIS BLANK.		
1	3.5.1		I.D. LIST FOR PRIMARY PARAMETERS. ANY		
13	3.5.2		IDENTIFICATION NUMBER FOR LABELING		
25	3.5.3		PARAMETERS. MAINTAIN CORRESPONDING		
37	3.5.4		ORDER TO PRIMARY LIST. THIS LIST		
49	3.5.5	73	CONTINUES TO A(400), ADDITIONAL		
61	3.5.6	2.00	CARDS PERMITTED.		
1	4.0.1		I.D. FOR GAS TEMP T.C.		
13	4.0.2		I.D. LIST FOR SECONDARY PARAMETERS.		
25	4.0.3		MAINTAIN CORRESPONDING ORDER TO		
37	4.0.4		SECONDARY LIST. THIS LIST CONTINUES		
49	4.0.5	73	TO A(490), ADDITIONAL CARDS PERMITTED		
61	4.0.6	2.20			

114-C-17 VELLUM

(3) heat transfer coefficient vs time, (4) heat transfer coefficient vs x/D position with time being the changing parameter, and (5) gas temperature vs time. These five graphs are controlled by option variables that are read-in on data cards. If the corresponding option value is positive (+), plot; if negative (-), no plot. There is also an option to store the calculated heat transfer coefficients with the corresponding times and x/D positions on magnetic tape. The data are labeled by a run number and a title head that is read-in on the data cards.

Computations

The HOTGAS computer program is a revision of another heat transfer data reduction computer program (7T109). The revisions consist principally of conversion from Fortran IV to Fortran H and expansion of the program for versatility. The basic calculating methods remain unchanged.

The time base used in the program is calculated. The initial time is obtained from the Beckman scaled data tape, and the Δt is calculated from

$$t = t_i + \Delta t$$

$$\Delta t = \frac{(t_f - t_o) \text{ Number of points averaged}}{\text{Total number of points}}$$

There may be some ambient data points recorded on the run tape prior to the start of the test. To conserve computer execution time, these points are overlooked and only the points taken during the test are reduced. The program checks the first three data channels at the start of each run for a 1 F rise in temperature. If a rise is found, the data point following is also checked to confirm that the rise is not a system "blip". After the data point is confirmed, the start time (t_i) is recorded. If no rise in temperature is found in the three data channels, t_i will be taken as the first point encountered in the data set.

The temperatures read-in from the scaled data tape are from thermocouples attached to the outside walls of the heat transfer test section. The individual outside wall temperatures are averaged in groups of n points (n specified by the input data A_{11}). TEMP2 (T_{W2}) is the arithmetic mean of two consecutive averaged groups.

The number of data points to be evaluated can be reduced by assigning a value greater than 1.0 to the sample reduction factor (A_{21}). This would cause the program to skip $m-1$ groups of data points.

The calculated gas-side wall temperatures corresponding to measured outside-wall temperatures are obtained from the solution of two simultaneous equations:

$$T_{W1} = T_{W2} + \frac{(q/A) \zeta}{2k}$$

where k is the thermal conductivity of the wall material, described by a linear function of the mean wall temperature.

$$k = C_1 + C_2 \frac{(T_{W1} + T_{W2})}{2}$$

The solution of the combined expression takes the form:

$$T_{W1} = \frac{-2C_1 + \sqrt{4C_1^2 + 4C_2(C_2T_2^2 + 2C_1T_2 + q/A \zeta)}}{2C_2}$$

where

$$C_1 = A_1$$

$$C_2 = A_2 \quad (\text{Read-in values})$$

$$\zeta = A_{13}$$

The gas temperature may be read-in as a constant, or assigned a thermocouple that measured T_{gas} .

The calculation of the heat flux was based on the following differential heat balance for a relatively thin, highly conductive wall, subject to a heat flux on the front face and insulated on the back face:

$$(q/A)_{N,t} = \rho c_p \zeta \left(\frac{dT_{W2}}{dt} \right)_{N,t}$$

The program is written for test sections with constant wall thickness (ζ) and so the product $\rho \zeta$ is replaced by a constant weight per unit area (W/A). Also, because there are a finite number of data points, the differential dT_{W2}/dt becomes $\Delta T_{W2}/\Delta t$ and the heat flux expression is reduced to:

$$(q/A)_{N,t} = \frac{W}{A} c_p \left(\frac{\Delta T_{W2}}{\Delta t} \right)_{N,t}$$

where specific heat of the wall material is defined as a linear function:

$$c_p = c_1 + c_2 \left(\frac{T_1 + T_2}{2} \right)_{N,t}$$

where

$$c_1 = A_{14} \quad (\text{Read-in values})$$

$$c_2 = A_{15}$$

Finally, the local instantaneous values of the heat transfer coefficients ($h_{N,t}$) for the transfer of heat from the hot nitrogen gas to the test section wall are computed from the following Newtonian convection equation which includes a correction for the bulk temperature drop of the hot nitrogen gas as it flows through the test section and loses heat to the wall:

$$h_{N,t} = \frac{(q/A)_{N,t}}{\left[T_{gi}(t) - \sum_{N=1}^N \frac{(q/A)_{N,t} A}{\dot{m} C_{pg}} \right] - (T_{W1})_{N,t}}$$

where the specific heat of the gas is:

$$C_{pg} = B_1 + B_2 T_3 + B_3 T_3^2 + B_4 T_3^3$$

B_1, B_2, B_3 , and B_4 are read-in values

There is an option to neglect heat loss if desired, and the expression reduces to:

$$h_{N,t} = \frac{(q/A)_{N,t}}{T_{gi}(t) - (T_{W1})_{N,t}}$$

DATA REDUCTION

Data reduction continued for the model heat transfer experiments. All data from the Brown and Datarite recorders were reduced and tabulated. Gas temperature data were extracted from the Brush recordings of the thermocouple outputs (on-line analog charts of the digitized data). This enabled calculation of the average mass flowrates for the individual tests. All necessary input data were prepared for the machine computations which utilize thermocouple output data in the generation of heat transfer data. Some delay has been encountered with the general usage Beckman transient data unpacking program, TRANS. This hampered data reduction during the major portion of the quarter. The elimination of the problem near the end of the period allowed a full-scale checkout of the entire data reduction system with actual test data, but did not allow ample time for the generation of heat transfer information from the test data. The bulk of the test data reduction will be accomplished near the beginning of the next quarter.

The impingement points and the ignition delays for the individual demonstration motor firings were calculated.

The ignition delay was based on the published master ignition curve for UTP 3001 propellant (Ref. 2). The test section pressure was estimated from Ref. 1 and the unpublished results of this program. The peak heat flux was based on data from the critical experiment.

ANALYTICAL STUDIES

The head-end and aft-end fluid dynamic studies are continuing. Literature is being reviewed to gain additional insight into the fluid dynamic/heat transfer phenomena occurring in these two ignition situations. For example, selected reports gathered for the following general areas include: closely related programs (Ref. 5 through 13); flow over rearward facing steps with and without heat transfer (Ref. 14 through 16); analysis of free and confined jets (Ref. 17); flow in entry regions of tubes (Ref. 18); separated flow in rectangular cavities (Ref. 19); flow in noncircular cross sections with and without heat transfer (Ref. 20); and approximations and techniques utilized in boundary layer calculations (Ref. 21 through 23).

A literature search in support of these studies was completed. The search was restricted to existing material available in the libraries of all North American Aviation divisions. Pertinent books and reports that had not been previously gathered have been requested and will be received at the beginning of the next quarter. The search indicated that a large quantity of related information is available in the open literature. Whether this information is directly applicable to the subject study will be evaluated during the next quarter when a consistent analysis will be formulated and correlations will be established.

FUTURE EFFORT

The testing program is currently 1 month ahead of schedule. Major effort during the fourth quarter will be directed toward data analysis and correlation of the model heat transfer experiments. Demonstration motor firings will be conducted near the middle of the period.

NOMENCLATURE

C_p	=	specific heat of the wall material (Btu/lb-F)
C_{pg}	=	specific heat of the gas at constant pressure (Btu/lb-F)
h	=	heat transfer coefficient (Btu/in. ² -sec-F)
\dot{m}	=	gas flowrate (lb/sec)
q/A	=	heat flux (Btu/in. ² -sec)
t	=	time (seconds)
T_{gi}	=	gas temperature (F)
T_{W1}	=	test section inside wall temperature (F)
T_{W2}	=	test section outside wall temperature (F)
W/A	=	weight per unit surface area (lb/in. ²)
ρ	=	density (lb/in. ³)
ζ	=	test section wall thickness (inches)
k	=	thermal conductivity of the wall material (Btu/in.-sec-F)

Subscripts

g	=	gas
i	=	initial
N	=	axial station number
t	=	time

REFERENCES

1. Carlson, L. W. and J. D. Seader: A Study of the Heat Transfer Characteristics of Hot Gas Ignition: Final Report, Contract AF04(611)-9884, Research Division of Rocketdyne, a Division of North American Aviation, Inc., Canoga Park, California, June 1965.
2. Beyer, R. B., R. Anderson, R. O. MacLaren, and W. J. Corcoran: Ignition of Solid-Propellant Motors Under Vacuum: Final Report, Contract AF04(611)-9701, United Technology Center, Sunnyvale, California, 8 April 1965.
3. Carlson, L. W. and J. A. Wrubel: Study of Heat Transfer Characteristics of Hot Gas Igniters, First Quarterly Report, Contract AF04(611)-11613, Research Division of Rocketdyne, a Division of North American Aviation, Inc., Canoga Park, California, September 1966.
4. Wrubel, J. A.: Study of Heat Transfer Characteristics of Hot Gas Igniters, Second Quarterly Report, Contract AF04(611)-11613, Research Division of Rocketdyne, a Division of North American Aviation, Inc., Canoga Park, California, December 1966.
5. Allan, D. S., E. K. Bastress, and K. A. Smith: "Heat-Transfer Processes During Ignition of Solid Propellant Rockets," J. Spacecraft, Vol. 4, No. 1, pp 95-100, January 1967.
6. Grant, E. H., Jr., R. W. Lancaster, J. Wenograd, and M. Summerfield: "A Study of the Ignition of Solid Propellants in a Small Rocket Motor," AIAA Preprint No. 64-153, presented at AIAA Solid Propellant Rocket Conference, Palo Alto, California, 29-31 January 1964.
7. Mullis, B., J. C. Burgess, R. S. Channapragada, and A. C. Keathley: Heat Transfer Studies of Solid Rocket Igniters, Final Technical Report, Contract NAS7-302, United Technology Center, Sunnyvale, California, 24 September 1965.
8. Jensen, G. E., D. A. Cose, R. S. Brown, R. Anderson, R. O. MacLaren, and W. J. Corcoran: Studies in Ignition and Flame Propagation of Solid Propellants, Final Report, Contract NAS7-329, United Technology Center, Sunnyvale, California, June 1966.

9. Brown, R. S., G. E. Jensen, R. Anderson, R. O. MacLaren, and W. J. Corcoran: Investigation of Fundamental Hypergolic Ignition Phenomena Under Dynamic Flow Environments, Final Report, Contract NAS7-156, United Technology Center, Sunnyvale, California, 25 February 1965.
10. Brown, R. S., T. K. Wirrick, and R. Anderson: "Theory of Ignition and Ignition Propagation of Solid Propellants in a Flow Environment," AIAA Preprint No. 64-157, presented at AIAA Solid Propellant Rocket Conference, Palo Alto, California, 29-31 January 1964.
11. Anderson, R., R. S. Brown, and L. J. Shannon: "Ignition Theory of Solid Propellants," AIAA Preprint No. 64-156, presented at AIAA Solid Propellant Rocket Conference, Palo Alto, California, 29-31 January 1964.
12. Plumley, A. G.: "Development of an Analytical Model to Determine Aft-End Igniter Design Parameters," Technical Paper 136 SRP, Aerojet General Corp., Sacramento, California, March 1964.
13. Salmi, R. J.: "Compressed-Air Model Investigation of Solid Rocket Overpressures Due to Interference from Aft-End Ignition Rocket," NASA Technical Note NASA-TN-D-3537, National Aeronautics and Space Administration, Washington, D.C., August 1966.
14. Djodjodihardjo, R. H. and J. F. Thorpe: "Fully Developed Luminar Flow in a Stepped Rectangular Channel," ASME Paper No. 66-APM-6, contributed by the Applied Mechanics Division for publication (without presentation) in the Journal of Applied Mechanics.
15. Chow, W. L. and H. H. Korst; "Influence on Base Pressures by Heat and Mass Additions," ARS Journal, pp 1094-1095, July 1962.
16. Scherberg, M. G. and H. E. Smith: "Experimental Study of the Flow Structure and Heat Transfer for a Pearward Facing Step in Supersonic Flow," Israel Journal of Technology, Vol. 4, No. 1, 1966 pp 55-62 Proc. VIII Israel Annual Conference of Aviation and Astronautics, February 1966.
17. Vick, A. R., E. H. Andrews, Jr., J. S. Dennard, and C. B. Craidon: "Comparisons of Experimental Free-Set Boundaries with Theoretical Results Obtained with the Method of Characteristics," NASA Technical Note NASA-TN-D-2327, National Aeronautics and Space Administration, Washington, D.C., June 1964.

18. Romanenko, P. N. and N. V. Krylova: "A Study of the Effects of Inlet Conditions on Heat Transfer in the Entry Region of a Tube," *International Chemical Engineering*, Vol. 4, No. 4, pp 587-593, October 1964.
19. Haugen, R. L. and A. M. Dhanak: "Momentum Transfer in Turbulent Separated Flow Past a Rectangular Cavity," ASME Paper No. 66-APM-Q, Contributed by the Applied Mechanics Division for publication (without presentation) in the *Journal of Applied Mechanics*.
20. Carlson, L. W. and T. F. Irvine: "Fully Developed Pressure Drop in Triangular Shaped Duets," *Journal of Heat Transfer*, November 1961.
21. Orszag, S. A. and M. D. Kruskal: "Theory of Turbulence," *Physical Review Letters*, Vol. 16, No. 11, pp 441-444, 14 March 1966.
22. Rotta, J. C.: "Recent Developments in Calculation Methods for Turbulent Boundary Layers with Pressure Gradients and Heat Transfer," ASME Paper No. 66-APM-F, contributed by the Applied Mechanics Division for publication (without presentation) in the *Journal of Applied Mechanics*.
23. Baum, F.: "Effects of Initial Profile in the Laminar Mixing Layer," EOS Research Note No. 30, Electro-Optical Systems, Inc., Pasadena, California, November 1965.

UNCLASSIFIED

Security Classification

DOCUMENT CONTROL DATA - R&D		
(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)		
1. ORIGINATING ACTIVITY (Corporate author) Rocketdyne, a Division of North American Aviation, Inc., 6633 Canoga Avenue, Canoga Park, California 91304		2a. REPORT SECURITY CLASSIFICATION UNCLASSIFIED 2b. GROUP
3. REPORT TITLE STUDY OF HEAT TRANSFER CHARACTERISTICS OF HOT-GAS IGNITERS		
4. DESCRIPTIVE NOTES (Type of report and inclusive dates) Third Quarterly Report (16 December 1966 through 15 March 1967)		
5. AUTHOR(S) (Last name, first name, initial) Wrubel, J. A.		
6. REPORT DATE April 1967	7a. TOTAL NO. OF PAGES 29	7b. NO. OF REFS 23
8a. CONTRACT OR GRANT NO. AF04(611)-11613 b. PROJECT NO. 3059 c. BPSN 623059 d.	9a. ORIGINATOR'S REPORT NUMBER(S) R-6856-3 9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report) AFRPL-TR-67-83	
10. AVAILABILITY/LIMITATION NOTICES This document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of AFRPL:(RPPR/STINFO), Edwards, California 93523.		
11. SUPPLEMENTARY NOTES		12. SPONSORING MILITARY ACTIVITY Air Force Rocket Propulsion Laboratory Research and Technology Division Edwards, California
13. ABSTRACT This program is concerned with determining the convective heat transfer characteristics of pyrogen igniters in both the aft-end and head-end configurations for three-pointed star and conocyl motor grains. Heat transfer modeling tests using thin-plate calorimetric techniques are being used to evaluate the heat transfer distributions. The third quarter effort reported herein was directed toward completion of the model heat transfer tests, preparation of the model heat transfer data for machine computation, initiation of build-up for the demonstration motor firings, continuance of the head-end and aft-end fluid dynamic analysis, completion of a description of the "HOTGAS" computer program, and initiation of that portion of data reduction requiring machine computation.		

DD FORM 1 JAN 64 1473

UNCLASSIFIED
Security Classification

UNCLASSIFIED

Security Classification

14. KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
Solid Propellant Ignition Pyrogen Heat Transfer Modeling						

INSTRUCTIONS

1. **ORIGINATING ACTIVITY:** Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (corporate author) issuing the report.

2a. **REPORT SECURITY CLASSIFICATION:** Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. **GROUP:** Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. **REPORT TITLE:** Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parentheses immediately following the title.

4. **DESCRIPTIVE NOTES:** If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. **AUTHOR(S):** Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. **REPORT DATE:** Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.

7a. **TOTAL NUMBER OF PAGES:** The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. **NUMBER OF REFERENCES:** Enter the total number of references cited in the report.

8a. **CONTRACT OR GRANT NUMBER:** If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. **PROJECT NUMBER:** Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. **ORIGINATOR'S REPORT NUMBER(S):** Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. **OTHER REPORT NUMBER(S):** If the report has been assigned any other report numbers (either by the originator or by the sponsor), also enter this number(s).

10. **AVAILABILITY/LIMITATION NOTICES:** Enter any limitations on further dissemination of the report, other than those

imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. **SUPPLEMENTARY NOTES:** Use for additional explanatory notes.

12. **SPONSORING MILITARY ACTIVITY:** Enter the name of the departmental project office or laboratory sponsoring (paying for) the research and development. Include address.

13. **ABSTRACT:** Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. **KEY WORDS:** Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.

UNCLASSIFIED

Security Classification