

UNCLASSIFIED

AD NUMBER
AD829246
NEW LIMITATION CHANGE
TO Approved for public release, distribution unlimited
FROM Distribution authorized to U.S. Gov't. agencies and their contractors; Critical Technology; JUN 1958. Other requests shall be referred to Space and Missile Systems Organization, Attn: SMSD, Los Angeles, CA 90045.
AUTHORITY
Space and Missile Systems Organization [USAF] ltr dtd 28 Feb 1972

THIS PAGE IS UNCLASSIFIED

AD829246

50

REPORT NO. 7A1425


ASTRONAUTICS

PRESSURE RELIEF

VALVE NO. 7-0334

EVALUATION TEST OF

T
to s
each
gov
with
Ho S
Att



This document is subject to special export controls and each copy is controlled to foreign government officials. Distribution is limited to those personnel who have been approved of: Hq. SMC-10, W.A., Cr. 90045 Attn: SMS

This document has been approved for public release and sale; its distribution is unlimited.

RECEIVED

JUL 9 '58

ASTRONAUTICS
TECHNICAL
LIBRARY

DDC
RECEIVED
APR 3 1968
B

Reproduced by
NATIONAL TECHNICAL
INFORMATION SERVICE
U S Department of Commerce
Springfield VA 22151

CONVAIR

A DIVISION OF GENERAL DYNAMICS CORPORATION
SAN DIEGO

14

AD829246



CONVAIR
A DIVISION OF GENERAL DYNAMICS CORPORATION
ASTRONAUTICS

REPORT 7A1425
DATE 19 June 1958
MODEL Astronautics
NO. OF PAGES 12

REPORT NO. 7A1425
ASTRONAUTICS
PRESSURE RELIEF
VALVE NO. 7-0334
EVALUATION TEST OF

This document is subject to special export controls and each time it is furnished to a foreign government, contractor or national organization, it is made only with prior approval of: HQ SASSO, LA., Ca. 90045
Attn: SMSD

PREPARED BY D. T. Kuczon
D. T. Kuczon
CHECKED BY J. L. Parr
J. L. Parr
CHECKED BY F. J. Lukas
F. J. Lukas
Group Engineer-Mechanical

GROUP Components Test Lab
APPROVED BY R. S. Campbell
R. S. Campbell, Jr.
Test Lab Group Eng
APPROVED BY R. S. Campbell
R. S. Campbell
Chief of Test Labs

Requested by: P. A. Bergin

REVISIONS

NO.	DATE	BY	CHANGE	PAGES AFFECTED

TABLE OF CONTENTS

<u>SUBJECT</u>	<u>PAGE NO.</u>
Object	2
Conclusion	2
Description of Specimen	2
Test Procedure	2 -3
Discussion of Results	4 -5
Tables, Curves and Photographs	6 - 12
<u>PHOTOGRAPHS</u>	
Short Circuit Test	
Sealed Position	11
Open Position	12

1.0 OBJECT:

1.1 The purpose of this test was to evaluate the performance of the 7-03340-1 Pressure Relief Valve which is used on Range Safety Command Battery Canisters.

2.0 CONCLUSIONS:

2.1 The dry relief valve and the electrolyte soaked relief valve maintained differential pressures of 3.2 psid and 8.7 psid, respectively, at an altitude equivalent to 1 millimeter of mercury. No evidence of electrolyte or short circuits were found after the altitude tests. During the short circuit test, the battery canister without a pressure relief valve burst at 340 psig. No rise in pressure occurred during the short circuit test of the battery container equipped with a safety relief valve.

3.0 DESCRIPTION OF SPECIMEN:

3.1 The specimens were two 7-03340-1 Pressure Relief Valves. The spring loaded valves were set for approximately 5 psid.

4.0 TEST PROCEDURE:

4.1 The test setup consisted of the following components:

- a) Range Safety Command Batteries Serial No. 48311-3 and 9.
- b) Statham Pressure Transducers No. 6389; range 0 to 1000 psig, and No. 3974; range 0 to 100 psia.
- c) Helicoid Pressure Gages Serial No. 438; range 0 to 600 psi and Serial No. 406; range 0 to 300 psi.
- d) Twenty-eight volt battery pack.
- e) Continuous Duty Contactor - SPST - Serial No. 168171.
- f) Miscellaneous pipe fittings and valves.
- g) C.E.C. Recording Oscillographs Serial No. 283DE3 and 29025.
- h) Weston D.C. Volt Meter.
- i) BEMCO Environmental Chamber Model FA-100-45.


4.2 The pressure transducer and bleed valve arrangement is shown in Figure 4. The altitude test transducer mounted in test position was calibrated from 5.8 psia to 19.7 psia using the altitude chamber for the range below atmospheric pressure and nitrogen gas above atmospheric pressure. The low range calibration was performed with the pressure relief valve held open to allow the transducer to respond to the chamber pressure.

4.0 TEST PROCEDURE: (Continued)

- 4.3 The pressure relief valve used for the first altitude test was dry. With the relief valve in place and the batteries fully charged, battery canister No. 4831-1-3 was pressurized to 1 millimeter of mercury within 10 minutes. After this condition was attained, the chamber pressure was returned to ambient pressure. The canister pressure was allowed to reach ambient pressure slowly by opening the bleed valve gradually. After ambient pressure was attained, the canister was opened to check for evidence of electrolyte and short circuits.
- 4.4 The above procedure (Paragraph 4.3) was used for the altitude test of the electrolyte soaked relief valve. The relief valve and battery canister used in this test were the same as those used in the first altitude test.
- 4.5 The pressure transducer for the short circuit tests was calibrated from 0 to 300 psig. before mounting on the battery canister. The bleed valve and transducer arrangement was then mounted on the battery canister as shown in Figure 4.
- 4.6 The first short circuit test was performed on battery canister No. 4831-1-3 without a pressure relief valve. After the canister was pressurized to 3 psig, the batteries were shorted at the contactor switch which was remotely operated behind a protection shield. A record of the canister pressure during the test was made on C.E.C. recording equipment.
- 4.7 The above procedure, Paragraph 4.6, was used for the second short circuit test using the electrolyte soaked relief valve on battery canister No. 9.

5.0 DISCUSSION OF RESULTS:

- 5.1 The graphic results of the canister pressure variation for the altitude tests are shown in Figure 1.
- 5.2 The altitude chamber attained 1 millimeter of mercury after seven minutes of operation for the dry relief valve altitude test. During this time, the battery canister pressure dropped at a varying rate directly related to the rate of chamber depressurization. After 1 mm of mercury was reached, the canister continued to lose pressure for nine minutes. The lowest pressure attained within the test specimen, before the altitude chamber was repressurized, was 6.6 inches of mercury or 3.2 psia. This continuous pressure drop after 1 millimeter of mercury was reached was probably caused by leakage at the relief valve seal since the canister pressure remained constant when the chamber pressure was increased. The canister pressure remained at 6.6 inches of mercury during chamber pressurization. The canister was allowed to return to ambient pressure within 40 seconds.
- 5.3 Inspection of the canister after the altitude test showed no evidence of electrolyte or short circuits.
- 5.4 The chamber attained 1 millimeter of mercury after seven minutes of operation for the altitude test of the electrolyte soaked relief valve. During this time the canister pressure drop varied according to the rate of chamber depressurization. The canister pressure reached a low of 10.0 millimeters of mercury or 8.7 psia during the depressurization period and remained at this pressure during chamber repressurization. The canister was allowed to return to ambient pressure within 50 seconds.
- 5.5 Inspection of the canister after the test showed no evidence of electrolyte or short circuits.
- 5.6 The electrolyte soaked relief valve attained a higher differential pressure than the dry relief valve and remained at this pressure until the canister was repressurized. This variation in differential pressures at 1 millimeter of mercury indicates that the electrolyte caused the relief valve to maintain a tighter seal than the dry relief valve.
- 5.7 The electrolyte caused the relief valve to corrode to the extent that several days after the test, it was no longer functional.



5.0 DISCUSSION OF RESULTS: (Continued)

- 5.8 The original internal leads from the batteries to the cannon plug burned out during the first short circuit test. Doubling the number of leads was necessary in order to discharge the battery for the test. Pictures of the battery canisters after the short circuit tests in the sealed and open positions are shown in Figures 4 and 5, respectively.
- 5.9 The graphic results of the pressure build-up in the battery canister without the relief valve are shown in Figures 2 and 3. The batteries discharged rapidly causing the canister pressure to increase to a bursting point of 340 psig within 59.5 seconds. A small pressure drop occurred at 59.2 seconds which was probably caused by a small leak in the canister seal. The canister lid was forced open at a screw fastener as shown in Figure 4. Electrolyte was sprayed from the canister after the lid opened. The internal damage is shown in Figure 5.
- 5.10 The addition of the electrolyte soaked relief valve in the second short circuit test relieved the pressure during the discharge period. The relief valve maintained a constant pressure in the battery canister of 3 psig for the entire test. Electrolyte was sprayed through the relief valve during the test. Internal damage to the batteries and canister is shown in Figure 5.

6.0 DATA BOOK REFERENCE:

- 6.1 The data from which this report was prepared are recorded in Astronautics Engineering Test Laboratory Note Book No. 7193.

ALTITUDE TEST
 of
 RANGE SAFETY COMMAND BATTERY
 RELIEF VALVE

TABLE I

BATTERY CANISTER EQUIPPED
WITH DRY RELIEF VALVE

TIME SEC.	PRESS. IN HG.
0	36.1
2	33.8
5	30.9
8	28.3
10	27.0
14	24.8
18	22.9
22	21.3
26	20.0
33	18.0
48	15.0
95	11.1
110	10.6
150	9.6
190	9.0
230	8.6
340	8.0
440	7.8
560	7.1
680	6.9
840	6.6
891	6.6
894	6.8
895	8.8
896	10.6
898	14.0
899	15.4
900	17.9
902	19.5
904	21.7
906	22.5
908	24.9
910	26.0
914	27.4
918	28.2
920	28.5
926	29.9

TABLE II

BATTERY CANISTER EQUIPPED WITH
ELECTROLYTE SOAKED RELIEF VALVE

TIME SEC.	PRESS. IN HG.
0.0	36.1
3.0	33.3
6.0	31.1
9.0	28.2
11.0	27.0
15.0	24.8
19.0	23.3
20.0	22.5
23.0	21.4
28.0	19.7
34.0	18.0
42.0	16.3
46.0	15.5
62.0	13.3
100.0	11.0
120.0	10.5
150.0	10.1
170.0	10.0
300.0	10.0
400.0	10.0
500.0	10.0
513.0	10.2
515.0	10.5
519.8	12.1
520.0	13.8
520.3	14.8
520.5	16.3
521.0	17.6
530.0	18.6
534.0	21.0
540.0	23.7
546.0	25.5
552.0	26.7
556.0	27.3
559.8	28.2
560.5	29.9

SHORT CIRCUIT TEST
 of
 RANGE SAFETY COMMAND BATTERY
 RELIEF VALVE

TABLE III

BATTERY CANISTER WITHOUT
 SAFETY PRESSURE RELIEF VALVE

TIME SEC.	PRESS. PSI.	TIME SEC.	PRESS. PSI.	TIME SEC.	PRESS. PSI.
0	3	47.0	186	59.50	149
5.0	3	48.0	194	59.51	111
8.5	7	49.0	202	59.52	83
11.0	10	50.0	212	59.53	68
13.0	13	51.0	220	59.54	55
15.0	16	52.0	228	59.55	45
17.0	20	53.0	238	59.56	42
20.0	22	54.0	246	59.57	36
25.0	30	55.0	257	59.58	33
30.0	42	56.0	269	59.59	29
35.0	59	57.0	283	59.60	28
38.0	77	58.0	296	59.65	17
40.0	96	59.0	311	59.70	12
41.0	107	59.20	313	59.80	4
42.0	119	59.21	305	59.90	3
43.0	133	59.22	306	60.00	1
44.0	148	59.30	306	60.50	1
45.0	162	59.40	308	61.50	0
46.0	175	59.49	333		

VIBRAMENT
K&E VIBRATION & PAPER CO.
10310 THE MENCH
3201-11G






Fig. 1
B5-01-3
3-10-3




O.F.K.
3-10-58
Fig 2

ARMY RESEARCH OFFICE
 DURHAM, N.C. 27706
 REPORT NO. 3201-11G

DIVISION OF THE ARMY
ENGINEERING CENTER
FORT MONMOUTH, NEW JERSEY



OPK
-10-58
Fig. 3




PREPARED D. T. Kuczon
CHECKED R. G. Camp, Jr.
REVISED

PAGE 0
REPORT NO. 7A1425
MODEL 7

PHOTO INDEX

<u>FIGURE NUMBER</u>	<u>PHOTO NUMBER</u>	<u>PAGE NUMBER</u>
4	10232A	11
5	10233A	12



SPECIMEN - B
WITH RELIEF VALVE

SHORT CIRCUIT TEST
RANGE SAFETY COMMAND
BATTERIES

SEALED POSITION

SPECIMEN - A
WITHOUT RELIEF VALVE

Fig. 4




Fig. 5