

UNCLASSIFIED

AD NUMBER
AD844659
NEW LIMITATION CHANGE
TO Approved for public release, distribution unlimited
FROM Distribution authorized to U.S. Gov't. agencies and their contractors; Administrative/Operational Use; NOV 1968. Other requests shall be referred to the U. S. Army Electronics Command, Fort Monmouth, New Jersey.
AUTHORITY
st-a usaec notice, 13 Sep 1971

THIS PAGE IS UNCLASSIFIED

DR-373
November 1968

AD

THIS DOCUMENT IS SUBJECT TO SPECIAL EXPORT CONTROLS AND EACH TRANSMITTAL TO FOREIGN GOVERNMENTS OR FOREIGN NATIONALS MAY BE MADE ONLY WITH PRIOR APPROVAL OF ATMOSPHERIC SCIENCES RESEARCH OFFICE, WHITE SANDS MISSILE RANGE, NEW MEXICO. 88002

AD 844659

METEOROLOGICAL DATA REPORT


NIRE-HYDAC 9.5-68-4-604
(17 October 1968)

BY

HAROLD M. RICHART

AND

LEN E. CARVER



ATMOSPHERIC SCIENCES RESEARCH OFFICE
WHITE SANDS MISSILE RANGE, NEW MEXICO

ECOM

UNITED STATES ARMY ELECTRONICS COMMAND

METEOROLOGICAL DATA REPORT

NIKE-HYDAC 9.5-68-4-604
(17 October 1968)

By

Harold M. Richart

And

Len E. Carter

DR-373

November 1968

DA Task 1T665702D127-02

ATMOSPHERIC SCIENCES RESEARCH OFFICE
WHITE SANDS MISSILE RANGE, NEW MEXICO

This document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of Atmospheric Sciences Research Office, White Sands Missile Range, New Mexico. 88002

ABSTRACT

Meteorological data gathered for the launching of Nike-Hydac 9.4-68-4-604 are presented for the Defense Atomic Support Agency, Sub-task 905, and for ballistic studies. The data appear, along with calculated ballistic data, in tabular form.

CONTENTS

	PAGE
ABSTRACT	iii
INTRODUCTION	1
DISCUSSION	1
TABLES	
I. Theoretical Rocket Performance Values	2
II. Ballistic Factors	3
III. Anemometer Wind Speed and Direction	4
IV. Pilot-Balloon-Measured Wind Data	5
V. Rawinsonde-Measured Wind Data	7
VI. Significant Level Data (Release Time: 1230 MDT)	8
VII. Upper Air Data (Release Time: 1230 MDT)	9
VIII. Mandatory Levels (Release Time: 1230 MDT)	16
IX. Significant Level Data (Release Time: 1500 MDT)	17
X. Upper Air Data (Release Time: 1500 MDT)	18
XI. Mandatory Levels (Release Time: 1500 MDT)	26
XII. Impact Prediction Data	27

INTRODUCTION

Nike-Hydrac 9.5-68-4-604 was launched from Launch Complex 33, X-361, White Sands Missile Range (WSMR), New Mexico, at 1530 hours MDT, 17 October 1968.

Meteorological data used in conjunction with theoretical calculations to predict rocket impact were collected by the Meteorological Support Technical Area, Atmospheric Sciences Research Office, WSMR, New Mexico. The Ballistics Meteorologists for this firing were Harold M. Richart and Len E. Carter.

DISCUSSION

Wind data for the first 216 feet above the surface were obtained from a system composed of five Aerovanes mounted on a 200-foot tower and cabled to component indicators.

From 216 to 4,000 feet above the surface, wind data were obtained from T-9 Radar-tracked balloon ascents.

Temperature, pressure, and humidity data, along with upper wind data from 4,000 to 100,000 feet above the surface, were obtained from standard rawinsonde observations.

Mean wind component values in each ballistic zone were determined from vertical cross sections by the equal-area method.

Theoretical rocket performance values and ballistic factors as a function of altitude were provided by Atmospheric Sciences Research Office and are the basis for data appearing in Table I.

PAYLOAD		400	Pounds
CORIOUS DISPLACEMENT	WEST	2.5	Miles
SECOND-STAGE IGNITION	TIME	20.2	Seconds
	ALTITUDE	35,040	Feet MSL
PEAK	TIME	185	Seconds
	ALTITUDE	438,259	Feet MSL
UNIT WIND EFFECT	HEAD	1.7053	Miles/MPH
	CROSS	1.7707	Miles/MPH
	TAIL	1.7053	Miles/MPH
TOWER TILT EFFECT		8.77	Miles/Degree

TABLE I. THEORETICAL ROCKET PERFORMANCE VALUES
NIKE-HYDAC 9.5-68-4-604

LAYERS IN FEET ABOVE GROUND	BALLISTIC FACTORS	LAYERS IN FEET ABOVE GROUND	BALLISTIC FACTORS	LAYERS IN FEET ABOVE GROUND	BALLISTIC FACTORS
11-60	.1617	800-1000	.0325	15000-20000	-.0096
60-108	.0960	1000-1400	.0516	20000-25000	-.0068
108-148	.0639	14000-2000	.0503	25000-31040	-.0069
148-184	.0535	2000-2500	.0276	31040-36000	.1055
184-216	.0377	2500-3000	.0178	36000-41000	.0321
216-300	.0792	3000-3500	.0057	41000-46000	.0126
300-400	.0666	3500-4130	.0040	46000-51000	.0078
400-600	.0752	4130-10000	-.0135	51000-56000	.0067
600-800	.0542	10000-15000	-.0106	56000-64400	.0053

TABLE II. BALLISTIC FACTORS
NIKE-HYDAC 9.5-68-4-604

AERO-VANE NO. *	MEAN WIND COMPONENTS IN MILES PER HOUR											
	1 1330 MDT		2 1400 MDT		3 1430 MDT		4 1445 MDT		5 1500 MDT			
	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W		
1	6.0N	5.0E	8.0N	0.0	5.0N	5.0E	6.0N	2.0E	3.0N	4.0E		
2	6.0	5.0	8.0	0.0	5.0	6.0	6.0	2.0	4.0	6.0		
3	6.0	5.0	8.0	2.0E	7.0	7.0	10.0	2.0	4.0	4.0		
4	6.0	5.0	9.0	2.0	5.0	8.0	6.0	0.0	4.0	6.0		
5	6.0	5.0	9.0	2.0	8.0	8.0	6.0	0.0	4.0	6.0		

AERO-VANE NO. *	MEAN WIND COMPONENTS IN MILES PER HOUR							
	6 1510 MDT		7 1520 MDT		8 1531 MDT			
	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W
1	2.0N	4.0E	2.0N	0.0	5.0N	0.0		
2	2.0	6.0	3.0	2.0E	4.0	1.0E		
3	3.0	5.0	4.0	4.0	4.0	2.0		
4	2.0	4.0	4.0	4.0	5.0	1.0		
5	2.0	4.0	4.0	4.0	5.0	1.0		

TABLE III. ANEMOMETER WIND SPEED AND DIRECTION
NIKE-HYDAC 9.5-68-4-604

* Heights corresponding to Aerovane Numbers: 1 = 35 Feet 3 = 128 Feet 5 = 200 Feet
2 = 88 Feet 4 = 168 Feet

LAYERS IN FEET ABOVE GROUND	MEAN WIND COMPONENTS IN MILES PER HOUR									
	1 1330 MDT		2 1400 MDT		3 1430 MDT		4 1445 MDT		5 1500 MDT	
	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W
216- 300	3.5N	2.5E	4.0N	1.0E	8.0N	5.0E	5.5N	1.0E	4.0N	5.5E
300- 400	4.0	3.0	4.5	0.0	7.5	4.5	5.0	3.5	4.0	5.0
400- 600	4.5	3.0	5.0	1.5E	7.5	3.5	3.0	5.5	4.0	4.5
600- 800	4.0	2.5	5.0	2.5	8.5	2.0	2.5	5.0	4.0	4.0
800-1000	6.5	3.0	3.0	1.5	9.0	1.0W	1.0	6.5	6.0	4.0
1000-1400	5.5	3.0	3.5	0.5W	10.0	0.5	6.5	6.0	5.0	3.5
1400-2000	5.5	3.0	5.0	1.5E	9.0	1.0	9.5	1.0	4.0	3.0
2000-2500	4.0	2.5	4.5	0.0	8.5	1.5	5.5	4.5	7.0	3.5
2500-3000	4.5	1.5	1.0	2.0E	8.0	1.5	6.0	2.5	8.5	1.5
3000-3500	4.5	0.0	0.5S	3.5	5.5	1.5	5.5	4.0	8.5	2.0W
3500-4000	2.5	1.5W	0.5N	1.0	6.5	4.0	4.5	7.0	6.0	3.5

TABLE IV. PILOT-BALLOON-MEASURED WIND DATA
NIKE-HYDAC 9.5-68-4-604

LAYERS IN FEET ABOVE GROUND	MEAN WIND COMPONENTS IN MILES PER HOUR											
	6 1510 MDT		7 1520 MDT		8 1531 MDT							
	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W
216- 300	2.0N	4.0E	4.0N	4.0E	5.0N	2.0E						
300- 400	4.5	2.5	4.0	5.5	6.0	4.5						
400- 600	7.0	3.5	4.5	6.5	9.0	4.0						
600- 800	7.0	1.0	3.5	7.0	6.0	4.0						
800-1000	4.5	5.5	4.0	6.0	3.0	3.5						
1000-1400	5.0	5.0	3.0	6.5	2.0	3.0						
1400-2000	8.0	2.0	6.0	6.5	5.0	2.0						
2000-2500	11.5	2.0	10.0	4.5	5.0	0.5W						
2500-3000	8.5	0.5	11.0	1.5	6.0	1.0						
3000-3500	3.5	0.0	9.0	1.0W	5.5	2.0						
3500-4000	2.5	0.5W	6.0	6.0	4.5	1.0						

TABLE IV. PILOT-BALLOON-MEASURED WIND DATA (CONT)
 NIKK-HYDAG 9, 5-65-4-604

LAYERS IN FEET ABOVE GROUND	MEAN WIND COMPONENTS IN KNOTS					
	1 1230 MDT		2 1500 MDT			
	N-S	E-W	N-S	E-W	N-E	E-W
4130-10000	4.5N	12.0W	2.5N	14.0W		
10000-15000	3.5	20.5	0.5	14.5		
15000-20000	5.0	28.5	5.0	29.5		
20000-25000	13.0	35.5	31.0	36.5		
25000-31040	13.5	36.5	20.5	35.5		
31040-36000	29.0	34.5	36.5	31.0		
36000-41000	14.5	39.5	7.0	40.5		
41000-46000	19.0	33.0	12.5	35.0		
46000-51000	0.0	30.0	0.0	33.0		
51000-56000	3.58	18.5	0.0	28.0		
56000-64400	5.5	9.5	0.0	15.0		

TABLE V. RAWINSONDE-MEASURED WIND DATA.
NIKS-HYDAC 9.4-68-4-674

STATION ALTITUDE 3987.00 FEET MSL
 17 OCT. 68
 ASCENSION NO. 848

SIGNIFICANT LEVEL DATA
 0731003902
 WHITL SANDS SITE

WSTM SITE COORDINATES
 400580.000000000
 105045.000000000

TABLE VI

PRESSURE MILLIBARS	GEOMETRIC ALTITUDE MSL FEET	TEMPERATURE AIR DEGREES CENTIGRADE	TEMPERATURE DEW POINT CENTIGRADE	REL. HUM. PERCENT
882.1	3989.0	17.3	-0.8	16.0
877.0	4309.5	14.4	-9.0	19.0
811.0	6296.6	8.4	-11.0	24.0
759.0	8076.2	3.1	-19.1	25.0
693.0	10499.9	6.0	-18.2	18.0
659.0	11840.1	3.0	-20.4	16.0
686.0	19809.2	-13.0	-29.9	23.0
352.0	27509.4	-31.3	-47.0	20.0
331.0	28930.9	-34.5	-49.8	22.0
281.0	32615.5	-44.0	0.	**
252.0	35017.2	-48.0	0.	**
206.0	39402.8	-50.1	0.	**
201.0	39932.3	-49.6	0.	**
195.0	40580.7	-53.2	0.	**
172.0	43236.8	-54.5	0.	**
134.0	48398.7	-63.4	0.	**
118.0	50983.0	-62.0	0.	**
107.0	52955.3	-67.0	0.	**
104.0	53524.6	-64.9	0.	**
102.0	53913.0	-67.4	0.	**
84.0	57791.7	-64.4	0.	**
82.0	58279.6	-62.0	0.	**
77.0	59563.7	-62.0	0.	**
69.0	61625.3	-57.8	0.	**
43.0	71716.5	-55.9	0.	**
30.0	79368.4	-51.2	0.	**
27.0	81631.9	-51.5	0.	**
11.0	101314.2	-42.3	0.	**
9.6	104352.0	-44.2	0.	**
8.8	106299.7	-41.0	0.	**

** RELATIVE HUMIDITY NOT SUPPLIED. ZERO VALUE ASSUMED FOR COMPUTATIONS.

NOT REPRODUCIBLE

STATION ALTITUDE 3989.00 FEET MSL
 17 OCT. 68 1230 HRS MDT
 ASCENSION NO. 848

UPPER AIR DATA
 0731003902
 WHITE SANDS SITE

WSTM SITE COORDINATES
 488580.00FEET E
 185045.00FEET N

TABLE VII

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA		INDEX OF REFRACTION
		AIR DEGREES	DEWPOINT CENTIGRADE				DIRECTION DEGREES(TN)	SPEED KNOTS	
3989.0	882.1	17.3	-8.8	16.0	1056.7	664.0	360.0	9.9	1.000250
4000.0	881.8	17.2	-8.8	16.1	1056.7	663.9	360.0	9.9	1.000250
4500.0	866.0	13.8	-9.1	19.5	1050.0	660.1	358.3	9.4	1.000248
5000.0	850.3	12.3	-9.6	20.7	1036.4	658.3	356.7	9.0	1.000245
5500.0	834.9	10.8	-10.1	22.0	1023.1	656.6	355.1	8.5	1.000241
6000.0	819.8	9.3	-10.7	23.3	1010.0	654.8	353.5	8.1	1.000238
6500.0	804.9	7.8	-11.5	24.1	997.0	653.0	351.8	7.6	1.000234
7000.0	790.0	6.3	-12.6	24.4	983.9	651.3	350.2	7.2	1.000230
7500.0	775.5	4.8	-13.8	24.7	971.0	649.5	331.4	6.8	1.000227
8000.0	761.2	3.3	-14.9	25.0	958.3	647.8	311.0	6.6	1.000223
8500.0	747.0	3.3	-15.5	23.8	940.8	647.7	296.3	9.5	1.000219
9000.0	733.1	3.4	-16.1	22.3	922.7	647.9	284.8	12.5	1.000214
9500.0	719.5	3.6	-16.8	20.9	904.9	648.1	282.7	15.7	1.000210
10000.0	706.1	3.8	-17.5	19.4	887.6	648.3	283.3	18.2	1.000205
10500.0	693.0	4.0	-18.2	18.0	870.5	648.5	286.3	20.3	1.000201
11000.0	680.1	3.6	-19.0	17.3	855.5	648.0	288.9	21.0	1.000197
11500.0	667.5	3.3	-19.9	16.5	840.8	647.6	291.4	21.3	1.000194
12000.0	654.9	2.7	-20.6	16.1	826.7	646.9	289.4	21.3	1.000190
12500.0	642.4	1.7	-21.1	16.6	813.8	645.7	286.6	21.2	1.000187
13000.0	630.1	0.7	-21.6	17.0	801.2	644.5	281.9	21.3	1.000184
13500.0	618.0	-0.3	-22.2	17.5	788.7	643.3	277.2	21.4	1.000181
14000.0	606.1	-1.3	-22.7	17.9	776.5	642.2	273.8	22.0	1.000178
14500.0	594.5	-2.3	-23.3	18.3	764.4	641.0	271.8	22.5	1.000175
15000.0	583.1	-3.3	-23.9	18.8	752.5	639.8	274.1	22.9	1.000172
15500.0	571.9	-4.3	-24.5	19.2	740.9	638.6	276.6	23.6	1.000169
16000.0	560.9	-5.4	-25.1	19.7	729.4	637.4	279.2	24.7	1.000167
16500.0	550.2	-6.4	-25.7	20.1	718.1	636.2	280.9	25.9	1.000164
17000.0	539.6	-7.4	-26.3	20.5	707.0	635.0	282.3	27.1	1.000161
17500.0	529.3	-8.4	-26.9	21.0	696.1	633.8	282.1	28.4	1.000159
18000.0	519.1	-9.4	-27.5	21.4	685.4	632.6	282.0	29.7	1.000156

NOV 1968

NOT REPRODUCIBLE

STATION ALTITUDE 3989.00 FEET MSL
 17 OCT. 68
 ASCENSION NO. 848

UPPER AIR DATA
 0731003902
 WHITE SANDS SITE

WSTM SITE COORDINATES
 488580.00 FEET E
 185045.00 FEET N

TABLE VII (Cont)

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE AIR DEGREES CENTIGRADE	REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA DIRECTION DEGREES (TN)	SPEED KNOTS	INDEX OF REFRACTION
18500.0	509.2	-10.4	21.9	674.8	631.3	282.9	30.6	1.000154
19000.0	489.4	-11.4	22.3	654.4	630.1	283.7	31.4	1.000151
19500.0	489.8	-12.4	22.7	654.2	628.9	283.5	32.3	1.000149
20000.0	480.2	-13.5	22.9	644.0	627.6	283.5	33.2	1.000146
20500.0	470.4	-14.6	22.7	633.7	626.2	284.4	34.2	1.000144
21000.0	460.7	-15.8	22.5	623.6	624.7	285.6	35.3	1.000141
21500.0	451.3	-17.0	22.3	613.7	623.3	287.9	36.2	1.000139
22000.0	442.1	-18.2	22.1	604.0	621.8	290.4	37.2	1.000136
22500.0	433.0	-19.4	22.0	594.4	620.3	293.7	38.8	1.000134
23000.0	424.2	-20.6	21.8	585.0	618.9	296.6	40.2	1.000132
23500.0	415.5	-21.8	21.6	575.8	617.4	298.2	40.7	1.000130
24000.0	407.0	-23.0	21.4	566.7	616.0	298.7	41.2	1.000127
24500.0	398.7	-24.1	21.2	557.7	614.5	297.3	41.6	1.000125
25000.0	390.5	-25.3	21.0	548.9	613.0	294.9	42.5	1.000123
25500.0	382.5	-26.5	20.8	540.3	611.5	292.1	43.7	1.000121
26000.0	374.7	-27.7	20.6	531.8	610.1	290.2	42.6	1.000119
26500.0	367.0	-28.9	20.4	523.5	608.6	288.7	41.4	1.000117
27000.0	359.5	-30.1	20.2	515.3	607.1	288.6	40.0	1.000115
27500.0	352.1	-31.3	20.0	507.2	605.6	288.9	38.4	1.000114
28000.0	344.6	-32.7	20.7	499.4	603.8	289.7	36.3	1.000112
28500.0	337.2	-34.2	21.4	491.7	601.9	290.4	35.7	1.000110
29000.0	330.0	-35.7	21.6**	484.1	600.1	291.1	36.2	1.000108
29500.0	322.7	-36.8	18.6**	475.8	598.6	291.0	37.3	1.000106
30000.0	315.6	-38.0	15.6**	467.6	597.2	290.7	38.7	1.000104
30500.0	308.7	-39.1	12.6**	459.6	595.7	289.7	39.5	1.000103
31000.0	301.9	-40.3	9.6**	451.7	594.2	288.4	40.3	1.000101
31500.0	295.3	-41.4	6.7**	444.0	592.7	288.5	40.8	1.000099
32000.0	288.8	-42.6	3.7**	436.4	591.3	289.1	41.3	1.000097
32500.0	282.4	-43.7	0.7**	429.0	589.8	292.2	41.5	1.000096
33000.0	276.1	-44.2	-0. **	420.2	587.2	297.7	41.2	1.000094

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

UPPER AIR DATA
0731003902
WHITE SANDS SITE

STATION ALTITUDE 3989.00 FEET MSL
17 OCT. 68
ASCENSION NO. 848

1230 HRS MDT

TABLE VII (Cont)

WSTM SITE COORDINATES
408580.00FEET E
185045.00FEET N

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA		INDEX OF REFRACTION
		AIR DEGREES	DEWPOINT CENTIGRADE				DIRECTION DEGREES(TN)	SPEED KNOTS	
33500.0	270.0	-44.4	0.	-0.	411.1	589.0	303.3	41.8	1.000092
34000.0	263.9	-44.6	0.	-0.	402.3	588.7	309.1	43.6	1.000090
34500.0	258.0	-44.8	0.	-0.	393.6	588.4	313.7	45.1	1.000088
35000.0	252.2	-45.0	0.	-0.	385.1	588.2	315.6	46.1	1.000086
35500.0	246.5	-45.6	0.	-0.	377.3	587.4	315.5	46.4	1.000084
36000.0	240.9	-46.1	0.	-0.	369.7	586.7	309.5	45.2	1.000082
36500.0	235.4	-46.7	0.	-0.	362.2	585.9	303.1	43.9	1.000081
37000.0	230.1	-47.3	0.	-0.	354.9	585.2	293.9	42.3	1.000079
37500.0	224.8	-47.9	0.	-0.	347.7	584.4	284.8	40.6	1.000077
38000.0	219.7	-48.5	0.	-0.	340.7	583.7	279.2	40.7	1.000076
38500.0	214.7	-49.1	0.	-0.	333.8	582.9	269.7	41.0	1.000074
39000.0	209.8	-49.6	0.	-0.	327.1	582.1	266.2	41.1	1.000073
39500.0	205.1	-50.0	0.	-0.	320.2	581.7	264.1	41.1	1.000071
40000.0	200.4	-50.0	0.	-0.	312.8	581.7	266.1	41.2	1.000070
40500.0	195.7	-52.8	0.	-0.	309.4	578.1	271.2	41.4	1.000069
41000.0	191.2	-53.4	0.	-0.	303.1	577.2	276.3	41.6	1.000068
41500.0	186.7	-53.6	0.	-0.	296.4	576.9	281.4	41.9	1.000066
42000.0	182.4	-53.9	0.	-0.	289.8	576.6	286.4	42.2	1.000065
42500.0	178.1	-54.1	0.	-0.	283.3	576.2	291.7	42.0	1.000063
43000.0	173.9	-54.4	0.	-0.	277.0	575.9	297.1	41.9	1.000062
43500.0	169.8	-55.0	0.	-0.	271.2	575.2	299.9	40.3	1.000060
44000.0	165.8	-55.8	0.	-0.	265.7	574.0	302.0	38.5	1.000059
44500.0	161.8	-56.7	0.	-0.	260.4	572.9	302.1	36.5	1.000058
45000.0	157.9	-57.5	0.	-0.	255.2	571.8	300.6	34.4	1.000057
45500.0	154.2	-58.4	0.	-0.	250.1	570.6	296.5	32.7	1.000056
46000.0	150.5	-59.3	0.	-0.	245.1	569.5	288.9	31.7	1.000055
46500.0	146.9	-60.1	0.	-0.	240.2	568.3	281.6	30.8	1.000053
47000.0	143.4	-61.0	0.	-0.	235.5	567.2	276.5	31.3	1.000052
47500.0	140.0	-61.9	0.	-0.	230.8	566.0	271.5	31.8	1.000051
48000.0	136.6	-62.7	0.	-0.	226.2	564.9	269.3	32.1	1.000050

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

UPPER AIR DATA
0731003902
WHITE SANDS SITE

STATION ALTITUDE 3989.00 FEET MSL
17 OCT. 68
ASCENSION NO. 848

WSTM SITE COORDINATES
485480.00 FEET E
185045.00 FEET N

TABLE VII (Cont)

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA		INDEX OF REFRACTION
		AIR DEGREES	DEWPOINT CENTIGRADE				DIRECTION DEGREES(TN)	SPEED KNOTS	
48500.0	133.3	-63.3	0.	-0.	221.4	564.0	269.7	32.1	1.000049
49000.0	130.1	-63.1	0.	-0.	215.8	564.4	270.2	32.1	1.000048
49500.0	126.9	-62.8	0.	-0.	210.2	564.7	273.7	30.5	1.000047
50000.0	123.8	-62.5	0.	-0.	204.9	565.1	277.2	28.9	1.000046
50500.0	120.8	-62.3	0.	-0.	199.6	565.5	282.4	26.5	1.000044
51000.0	117.9	-62.0	0.	-0.	194.6	565.7	288.4	23.8	1.000043
51500.0	115.0	-63.3	0.	-0.	191.0	564.0	286.4	22.5	1.000043
52000.0	112.2	-64.6	0.	-0.	187.4	562.3	272.1	23.6	1.000042
52500.0	109.4	-65.8	0.	-0.	183.9	560.6	258.1	24.6	1.000041
53000.0	106.8	-66.8	0.	-0.	180.3	559.3	256.8	24.0	1.000040
53500.0	104.1	-65.0	0.	-0.	174.3	561.3	255.5	23.3	1.000039
54000.0	101.6	-67.4	0.	-0.	171.9	558.6	253.5	24.0	1.000038
54500.0	99.0	-67.1	0.	-0.	167.5	558.9	250.7	25.8	1.000037
55000.0	96.6	-66.8	0.	-0.	163.1	559.3	248.0	27.7	1.000036
55500.0	94.2	-66.6	0.	-0.	158.9	559.6	254.2	22.9	1.000035
56000.0	91.9	-66.3	0.	-0.	154.8	560.0	260.4	18.1	1.000034
56500.0	89.6	-66.1	0.	-0.	150.8	560.3	263.0	15.2	1.000034
57000.0	87.4	-65.8	0.	-0.	146.9	560.7	259.9	15.2	1.000033
57500.0	85.2	-65.6	0.	-0.	143.1	561.0	256.8	15.1	1.000032
58000.0	83.1	-63.9	0.	-0.	138.5	563.2	251.7	14.9	1.000031
58500.0	81.1	-62.0	0.	-0.	133.9	565.8	245.8	14.7	1.000030
59000.0	79.2	-62.0	0.	-0.	130.6	565.8	239.9	14.5	1.000029
59500.0	77.2	-62.0	0.	-0.	127.5	565.8	242.5	14.4	1.000028
60000.0	75.4	-61.2	0.	-0.	123.9	566.9	245.2	14.2	1.000028
60500.0	73.6	-60.3	0.	-0.	120.4	568.1	246.7	13.6	1.000027
61000.0	71.8	-59.3	0.	-0.	117.0	569.4	244.0	11.6	1.000026
61500.0	70.1	-58.4	0.	-0.	113.7	570.6	241.3	9.6	1.000025
62000.0	68.4	-57.8	0.	-0.	110.7	571.5	241.4	7.9	1.000025
62500.0	66.8	-57.7	0.	-0.	108.0	571.6	244.5	6.4	1.000024
63000.0	65.2	-57.6	0.	-0.	105.4	571.7	247.6	4.9	1.000023

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

UPPER AIR DATA
 0731003902
 WHITE SANDS SITE

STATION ALTITUDE 3989.00 FEET MSL
 17 OCT. 68 1230 HRS MDT
 ASCENSION NO. 848

WSTM SITE COORDINATES
 488580.00FEET E
 185045.00FEET N

TABLE VII (Cont)

GEOMETRIC ALTYITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	DIRECTION DEGREES(TN)	WIND DATA		INDEX OF REFRACTION
		AIR DEGREES CENTIGRADE	DEWPOINT CENTIGRADE					SPEED KNOTS	SPEED KNOTS	
63500.0	63.7	-57.5	0.	-0. **	102.9	571.8	241.7	4.8	1.000023	
64000.0	62.2	-57.4	0.	-0. **	100.4	572.0	232.0	5.4	1.000022	
64500.0	60.7	-57.3	0.	-0. **	98.0	572.1	222.3	5.9	1.000022	
65000.0	59.3	-57.2	0.	-0. **	95.6	572.2	225.5	7.0	1.000021	
65500.0	57.9	-57.1	0.	-0. **	93.3	572.3	230.5	8.1	1.000021	
66000.0	56.5	-57.0	0.	-0. **	91.1	572.5	235.5	9.3	1.000020	
66500.0	55.2	-56.9	0.	-0. **	88.9	572.6	236.9	8.8	1.000020	
67000.0	53.9	-56.8	0.	-0. **	86.8	572.7	236.8	7.8	1.000019	
67500.0	52.6	-56.7	0.	-0. **	84.7	572.9	236.8	6.8	1.000019	
68000.0	51.4	-56.6	0.	-0. **	82.6	573.0	238.2	6.0	1.000018	
68500.0	50.1	-56.5	0.	-0. **	80.7	573.1	243.7	5.8	1.000018	
69000.0	49.0	-56.4	0.	-0. **	78.7	573.2	249.2	5.7	1.000018	
69500.0	47.8	-56.3	0.	-0. **	76.8	573.4	254.8	5.5	1.000017	
70000.0	46.7	-56.2	0.	-0. **	75.0	573.5	253.7	4.6	1.000017	
70500.0	45.6	-56.1	0.	-0. **	73.2	573.6	251.0	3.4	1.000016	
71000.0	44.5	-56.0	0.	-0. **	71.4	573.7	248.3	2.2	1.000016	
71500.0	43.4	-55.9	0.	-0. **	69.7	573.9	247.3	1.8	1.000016	
72000.0	42.4	-55.7	0.	-0. **	68.0	574.2	249.7	3.0	1.000015	
72500.0	41.4	-55.4	0.	-0. **	66.3	574.6	252.1	4.1	1.000015	
73000.0	40.5	-55.1	0.	-0. **	64.7	575.0	254.5	5.3	1.000014	
73500.0	39.5	-54.8	0.	-0. **	63.1	575.4	208.7	4.7	1.000014	
74000.0	38.6	-54.5	0.	-0. **	61.5	575.8	158.7	4.1	1.000014	
74500.0	37.7	-54.2	0.	-0. **	60.0	576.2	108.7	3.4	1.000013	
75000.0	36.8	-53.9	0.	-0. **	58.5	576.6	87.2	3.4	1.000013	
75500.0	36.0	-53.6	0.	-0. **	57.1	577.0	86.4	2.7	1.000013	
76000.0	35.2	-53.3	0.	-0. **	55.7	577.4	81.5	3.9	1.000012	
76500.0	34.3	-53.0	0.	-0. **	54.3	577.8	80.7	4.8	1.000012	
77000.0	33.5	-52.7	0.	-0. **	53.0	578.2	84.3	6.9	1.000012	
77500.0	32.8	-52.3	0.	-0. **	51.7	578.6	87.8	9.0	1.000012	
78000.0	32.0	-52.0	0.	-0. **	50.4	579.0	91.4	10.9	1.000011	

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

UPPER AIR DATA
 0731003902
 WHITE SANDS SITE
 TABLE VII (Cont)

STATION ALTITUDE 3989.00 FEET MSL
 17 OCT. 68
 ASCENSION NO. 848
 1230 HPS MDT

WSTM SITE COORDINATES
 488580.00 FEET E
 185045.00 FEET N

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE AIR DEGREES CENTIGRADE	REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA		INDEX OF REFRACTION
						DIRECTION DEGREES(TN)	SPEED KNOTS	
78500.0	31.3	-51.7	-0. **	49.2	579.4	95.8	9.8	1.000011
79000.0	30.5	-51.4	-0. **	48.0	579.8	100.2	8.6	1.000011
79500.0	29.8	-51.2	-0. **	46.8	580.1	104.6	7.4	1.000010
80000.0	29.1	-51.3	-0. **	45.7	580.0	112.2	6.8	1.000010
80500.0	28.5	-51.3	-0. **	44.7	579.9	120.9	6.3	1.000010
81000.0	27.8	-51.4	-0. **	43.7	579.8	129.6	5.9	1.000010
81500.0	27.2	-51.5	-0. **	42.7	579.7	132.8	5.4	1.000010
82000.0	26.6	-51.3	-0. **	41.7	579.9	128.6	4.8	1.000009
82500.0	26.0	-51.1	-0. **	40.7	580.2	124.5	4.2	1.000009
83000.0	25.4	-50.9	-0. **	39.8	580.5	120.3	3.6	1.000009
83500.0	24.8	-50.6	-0. **	38.8	580.8	90.2	2.8	1.000009
84000.0	24.2	-50.4	-0. **	37.9	581.1	60.1	2.1	1.000008
84500.0	23.7	-50.2	-0. **	37.0	581.5	29.9	1.3	1.000008
85000.0	23.2	-49.9	-0. **	36.1	581.8	15.5	1.3	1.000008
85500.0	22.6	-49.7	-0. **	35.3	582.1	19.7	2.0	1.000008
86000.0	22.1	-49.5	-0. **	34.5	582.4	24.0	2.8	1.000008
86500.0	21.6	-49.2	-0. **	33.6	582.7	28.3	3.6	1.000007
87000.0	21.1	-49.0	-0. **	32.9	583.0	10.5	3.2	1.000007
87500.0	20.7	-48.8	-0. **	32.1	583.3	350.3	2.7	1.000007
88000.0	20.2	-48.5	-0. **	31.3	583.6	330.0	2.1	1.000007
88500.0	19.7	-48.3	-0. **	30.6	583.9	329.9	2.0	1.000007
89000.0	19.3	-48.1	-0. **	29.9	584.2	8.7	2.8	1.000007
89500.0	18.9	-47.8	-0. **	29.2	584.5	47.4	3.6	1.000006
90000.0	18.4	-47.6	-0. **	28.5	584.8	86.2	4.4	1.000006
90500.0	18.0	-47.4	-0. **	27.8	585.1	97.0	4.6	1.000006
91000.0	17.6	-47.1	-0. **	27.1	585.4	100.2	4.5	1.000006
91500.0	17.2	-46.9	-0. **	26.5	585.7	103.4	4.5	1.000006
92000.0	16.8	-46.7	-0. **	25.9	586.0	106.4	4.6	1.000006
92500.0	16.4	-46.4	-0. **	25.3	586.3	108.7	5.1	1.000006
93000.0	16.1	-46.2	-0. **	24.7	586.6	111.0	5.6	1.000005

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.00 FEET MSL
 17 OCT. 68 1230 HRS MDT
 ASCENSION NO. 848

UPPER AIR DATA
 0731003902
 WHITE SANDS SITE

WSTM SITE COORDINATES
 488500.00FEET E
 185045.00FEET N

TABLE VII (Cont)

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE AIR DEGREES	TEMPERATURE DEWPOINT DEGREES	REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA		INDEX OF REFRACTION
							DIRECTION DEGREES(TM)	SPEED KNOTS	
93500.0	15.7	-46.0	0.	-0. **	24.1	586.9	113.3	6.1	1.000005
94000.0	15.4	-45.7	0.	-0. **	23.5	587.2	122.0	6.1	1.000005
94500.0	15.0	-45.5	0.	-0. **	23.0	587.5	133.9	6.0	1.000005
95000.0	14.7	-45.3	0.	-0. **	22.4	587.8	145.8	5.9	1.000005
95500.0	14.3	-45.0	0.	-0. **	21.9	588.1	156.6	5.8	1.000005
96000.0	14.0	-44.8	0.	-0. **	21.4	588.4	159.4	6.2	1.000005
96500.0	13.7	-44.6	0.	-0. **	20.9	588.7	162.1	6.6	1.000005
97000.0	13.4	-44.3	0.	-0. **	20.4	589.0	164.9	7.0	1.000005
97500.0	13.1	-44.1	0.	-0. **	19.9	589.3	171.0	7.1	1.000004
98000.0	12.8	-43.8	0.	-0. **	19.4	589.6	179.8	7.1	1.000004
98500.0	12.5	-43.6	0.	-0. **	19.0	589.9	186.6	7.1	1.000004
99000.0	12.2	-43.4	0.	-0. **	18.5	590.2	197.4	7.1	1.000004
99500.0	11.9	-43.1	0.	-0. **	18.1	590.5	202.9	7.3	1.000004
100000.0	11.7	-42.9	0.	-0. **	17.7	590.8	208.4	7.4	1.000004
100500.0	11.4	-42.7	0.	-0. **	17.3	591.1	213.8	7.6	1.000004
101000.0	11.2	-42.4	0.	-0. **	16.9	591.4	218.2	8.0	1.000004
101500.0	10.9	-42.4	0.	-0. **	16.5	591.5	221.2	8.8	1.000004
102000.0	10.7	-42.7	0.	-0. **	16.1	591.1	224.2	9.6	1.000004
102500.0	10.4	-43.0	0.	-0. **	15.8	590.7	227.2	10.5	1.000004
103000.0	10.2	-43.4	0.	-0. **	15.5	590.3			1.000003
103500.0	10.0	-43.7	0.	-0. **	15.1	589.9			1.000003
104000.0	9.8	-44.0	0.	-0. **	14.8	589.5			1.000003
104500.0	9.5	-44.0	0.	-0. **	14.5	589.5			1.000003
105000.0	9.3	-43.1	0.	-0. **	14.1	590.5			1.000003
105500.0	9.1	-42.3	0.	-0. **	13.8	591.6			1.000003
106000.0	8.9	-41.5	0.	-0. **	13.4	592.6			1.000003

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

NOT REPRODUCIBLE

STATION ALTITUDE 3989.00 FEET MSL
 17 OCT. 68
 ASCENSION NO. 848

MANDATORY LEVELS
 0731003902
 WHITE SANDS SITE

WSTM SITE COORDINATES
 488580.00 FEET E
 185045.00 FEET N

TABLE VIII

PRESSURE GEOPOTENTIAL		TEMPERATURE		REL. HUM.	WIND DATA	
MILLIBARS	FEET	AIR DEGREES	DEWPOINT CENTIGRADE	PERCENT	DIRECTION DEGREES(TN)	SPEED KNOTS
850.0	5013.	12.3	-9.6	21.	356.7	9.0
800.0	6663.	7.3	-11.9	24.	351.3	7.9
750.0	8389.	3.2	-15.4	24.	299.4	8.9
700.0	10225.	3.9	-17.8	19.	284.7	19.2
650.0	12196.	2.3	-20.8	16.	288.3	21.3
600.0	14309.	-1.9	-23.0	18.	271.7	22.4
550.0	16551.	-6.4	-25.7	20.	281.1	26.0
500.0	18973.	-11.3	-28.8	22.	283.7	31.4
450.0	21596.	-17.2	-33.8	22.	288.5	36.4
400.0	24456.	-24.0	-40.1	21.	297.3	41.6
350.0	27605.	-31.7	-47.2	20.	289.1	37.8
300.0	31112.	-40.6	-61.5	9.**	288.1	40.5
250.0	35131.	-45.2	0.	-0.**	316.4	46.4
200.0	39961.	-50.2	0.	-0.**	266.5	41.2
175.0	42781.	-54.3	0.	-0.**	295.7	41.9
150.0	45988.	-59.4	0.	-0.**	287.6	31.5
125.0	49687.	-62.6	0.	-0.**	275.9	29.5
100.0	54161.	-67.2	0.	-0.**	251.8	25.1
80.0	58613.	-62.0	0.	-0.**	242.5	14.6
70.0	61339.	-58.4	0.	-0.**	241.2	9.5
60.0	64533.	-57.2	0.	-0.**	222.8	6.4
50.0	68322.	-56.5	0.	-0.**	244.2	5.8
40.0	72980.	-55.0	0.	-0.**	235.1	5.1
30.0	79064.	-51.2	0.	-0.**	103.4	7.8
25.0	82952.	-50.7	0.	-0.**	103.3	3.2
20.0	87746.	-48.4	0.	-0.**	325.3	2.0
15.0	94000.	-45.5	0.	-0.**	132.1	6.0
10.0	102941.	-43.6	0.	-0.**		

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.00 FEET MSL
 17 OCT. 68
 ASCENSION NO. 849

SIGNIFICANT LEVEL DATA
 0731003903
 WHITE SANDS SITE

WSTM SITE COORDINATES
 480580.00 FEET E.
 185045.00 FEET N

TABLE IX

PRESSURE GEOMETRIC ALTITUDE		TEMPERATURE	REL. HUM.
MILLIBARS	MSL FEET	AIR DEGREE	PERCENT
		DEGREES	
		CENTIGRADE	
879.7	3989.0	19.3	18.0
861.0	4589.9	15.0	23.0
732.0	9011.9	4.6	31.0
699.0	10248.2	5.9	13.0
688.0	10675.3	7.0	12.0
550.0	16570.5	-6.3	20.0
517.0	18152.9	-9.1	33.0
409.0	23981.0	-20.9	25.0
364.0	26773.5	-28.2	25.0
320.0	29766.1	-36.1	23.0
278.0	32930.7	-43.6	-0. **
246.0	35634.7	-44.1	-0. **
192.0	40997.9	-53.5	-0. **
174.0	43079.9	-54.5	-0. **
137.0	48029.8	-62.8	-0. **
119.0	50870.8	-65.8	-0. **
112.0	52091.2	-63.7	-0. **
99.0	54558.2	-68.6	-0. **
60.0	64691.5	-58.9	-0. **
20.0	88011.0	-48.5	-0. **
11.5	100091.8	-47.4	-0. **
7.7	109041.8	-39.1	-0. **

** RELATIVE HUMIDITY NOT SUPPLIED. ZERO VALUE ASSUMED FOR COMPUTATIONS.

UPPER AIR DATA
0731003903
WHITE SANDS SITE

STATION ALTITUDE 3989.00 FEET MSL
17 OCT. 68
ASCENSION NO. 849
1500 HRS MDT

WSTM SITE COORDINATES
48580.00FEET E
185045.00FEET N

TABIX X

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE AIR DEGREES	DEWPOINT CENTIGRADE	REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	DIRECTION DEGREES(TM)	WIND DATA SPEED KNOTS	INDEX OF REFRACTION
3989.0	879.7	19.3	-5.6	18.0	1046.2	666.5	360.0	5.1	1.000251
4000.0	879.4	19.2	-5.6	18.1	1046.1	666.4	0.2	5.1	1.000251
4500.0	863.8	15.6	-5.9	22.3	1040.3	662.3	7.5	5.2	1.000250
5000.0	848.1	14.0	-6.4	23.7	1027.3	660.4	14.8	5.4	1.000246
5500.0	832.7	12.8	-6.9	24.6	1012.9	659.0	22.1	5.6	1.000243
6000.0	817.6	11.6	-7.5	25.6	998.7	657.6	29.4	5.7	1.000239
6500.0	802.7	10.4	-8.1	26.5	984.7	656.2	36.7	5.9	1.000235
7000.0	788.1	9.2	-8.7	27.4	970.9	654.8	28.9	4.5	1.000231
7500.0	773.8	8.0	-9.3	28.3	957.4	653.4	18.2	2.9	1.000228
8000.0	759.7	6.8	-9.9	29.2	944.1	652.0	347.9	3.7	1.000224
8500.0	745.9	5.6	-10.6	30.1	930.9	650.6	300.6	6.6	1.000221
9000.0	732.3	4.4	-11.3	31.0	918.0	649.2	279.8	10.4	1.000217
9500.0	718.8	5.0	-14.0	23.9	899.4	649.7	279.5	15.0	1.000211
10000.0	705.5	5.6	-17.9	16.6	881.1	650.4	285.7	16.1	1.000204
10500.0	692.5	6.5	-20.5	12.4	862.1	651.4	293.5	16.2	1.000198
11000.0	679.6	6.3	-20.7	12.4	846.8	651.1	303.3	15.2	1.000194
11500.0	666.8	5.1	-21.0	13.1	834.3	649.8	309.6	14.4	1.000191
12000.0	654.2	4.0	-21.3	13.8	821.9	648.5	314.6	13.5	1.000189
12500.0	641.9	2.9	-21.7	14.5	809.8	647.1	310.7	13.8	1.000186
13000.0	629.9	1.8	-22.1	15.2	797.8	645.8	305.6	14.4	1.000183
13500.0	618.0	0.6	-22.5	15.8	786.0	644.5	295.9	15.8	1.000180
14000.0	606.4	-0.5	-23.0	16.5	774.4	643.1	287.5	17.6	1.000177
14500.0	595.0	-1.6	-23.4	17.2	763.0	641.8	281.7	20.2	1.000175
15000.0	583.8	-2.8	-23.9	17.9	751.8	640.5	278.2	22.7	1.000172
15500.0	572.8	-3.9	-24.5	18.5	740.8	639.1	277.4	25.1	1.000169
16000.0	562.0	-5.0	-25.0	19.2	729.9	637.8	276.9	26.8	1.000167
16500.0	551.5	-6.1	-25.6	19.9	719.2	636.4	276.6	28.1	1.000164
17000.0	540.8	-7.1	-24.5	23.5	707.8	635.4	278.5	29.2	1.000162
17500.0	530.4	-7.9	-23.5	27.6	696.3	634.3	280.8	30.1	1.000160
18000.0	520.1	-8.8	-22.7	31.7	685.1	633.3	282.4	31.2	1.000158

UPPER AIR DATA
 0731003903
 WHITE SANDS SITE

STATION ALTITUDE 3989.00 FEET MSL
 17 OCT. 68 1500 HRS MDT
 ASCENSION NO. 849

WSTM SIVE COORDINATES
 488580.00FEET E
 185045.00FEET N

TABLE X (Cont)

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		REL. NUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA DIRECTION DEGREES(TN)	SPEED KNOTS	INDEX OF REFRACTION
		AIR DEGREES	DEWPOINT CENTIGRADE						
18500.0	509.8	-9.8	-23.3	32.5	674.1	632.1	284.3	32.4	1.000155
19000.0	499.7	-10.8	-24.4	31.8	653.2	630.9	287.3	34.3	1.000152
19500.0	489.7	-11.8	-25.6	31.2	652.6	629.6	289.9	36.0	1.000150
20000.0	480.0	-12.8	-26.7	30.5	642.1	628.4	292.1	37.5	1.000147
20500.0	470.4	-13.9	-27.9	29.8	631.8	627.2	294.9	38.9	1.000144
21000.0	461.1	-14.9	-29.0	29.1	621.7	625.9	297.9	40.4	1.000142
21500.0	451.9	-15.9	-30.2	28.4	611.7	624.7	300.1	41.8	1.000139
22000.0	442.9	-16.9	-31.3	27.7	602.0	623.4	302.2	43.3	1.000137
22500.0	434.1	-17.9	-32.4	27.0	592.3	622.2	302.7	43.6	1.000134
23000.0	425.5	-18.9	-33.6	26.3	582.9	621.0	303.0	43.8	1.000132
23500.0	417.0	-19.9	-34.8	25.7	573.6	619.7	301.2	43.5	1.000130
24000.0	408.7	-20.9	-35.9	25.0	564.4	618.4	299.2	43.1	1.000127
24500.0	400.2	-22.3	-37.0	25.0	555.7	616.8	296.6	42.1	1.000125
25000.0	392.0	-23.6	-38.2	25.0	547.1	615.2	294.1	42.0	1.000123
25500.0	383.9	-24.9	-39.3	25.0	538.6	613.6	291.7	43.0	1.000121
26000.0	375.9	-26.2	-40.5	25.0	530.3	612.0	289.3	43.5	1.000119
26500.0	368.2	-27.5	-41.6	25.0	522.1	610.3	287.1	43.5	1.000117
27000.0	360.5	-28.8	-42.8	24.8	513.9	608.7	285.9	42.7	1.000115
27500.0	352.8	-30.1	-44.1	24.5	505.7	607.1	285.9	41.4	1.000113
28000.0	345.3	-31.4	-45.4	24.2	497.6	605.4	287.6	39.2	1.000112
28500.0	337.9	-32.8	-46.7	23.8	489.7	603.7	292.5	40.1	1.000110
29000.0	330.7	-34.1	-47.9	23.5	482.0	602.1	298.0	40.7	1.000108
29500.0	323.7	-35.4	-49.2	23.2	474.3	600.4	304.2	40.5	1.000106
30000.0	316.7	-36.7	-51.0	21.3**	466.5	598.8	308.8	41.8	1.000104
30500.0	309.7	-37.8	-53.0	17.7**	458.6	597.3	312.9	43.5	1.000102
31000.0	302.9	-39.0	-56.5	14.0**	450.8	595.8	316.0	44.7	1.000101
31500.0	296.3	-40.2	-59.9	10.4**	443.1	594.3	317.9	46.4	1.000099
32000.0	289.7	-41.4	-64.1	6.8**	435.6	592.8	318.1	48.7	1.000097
32500.0	283.4	-42.6	-70.4	3.1**	428.2	591.3	318.4	50.7	1.000095
33000.0	277.1	-43.6	0.	-0.4**	420.7	589.9	319.1	51.8	1.000094

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

NOT REPRODUCIBLE

STATION ALTITUDE 3989.00 FEET MSL
 17 OCT. 68
 ASCENSION NO. 849

UPPER AIR DATA
 0731003903
 WHITE SANDS SITE

WSTN SITE COORDINATES
 498980.00 FEET E
 105045.00 FEET N

TADLR X (Cont)

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	AIR TEMPERATURE DEGREES CENTIGRADE	REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DIRECTION DEGREES(TYP)	WIND SPEED KNOTS	INDEX OF REFRACTION
33500.0	270.9	-43.7	0.0	411.4	589.8	319.7	52.6	1.000092
34000.0	264.9	-43.8	0.0	402.4	589.7	320.6	51.1	1.000090
34500.0	259.0	-43.9	0.0	393.5	589.6	320.5	49.3	1.000088
35000.0	253.2	-44.0	0.0	384.5	589.5	317.0	46.5	1.000086
35500.0	247.5	-44.1	0.0	376.4	589.3	313.7	43.7	1.000084
36000.0	241.9	-44.7	0.0	369.0	588.5	310.8	41.3	1.000082
36500.0	236.4	-45.6	0.0	361.9	587.3	305.8	39.6	1.000081
37000.0	231.0	-46.5	0.0	355.0	586.2	296.3	39.1	1.000079
37500.0	225.7	-47.4	0.0	348.3	585.1	288.1	39.1	1.000078
38000.0	220.5	-48.2	0.0	341.6	583.9	282.9	39.9	1.000076
38500.0	215.5	-49.1	0.0	335.1	582.8	277.7	40.9	1.000075
39000.0	210.6	-50.0	0.0	328.8	581.7	272.6	43.0	1.000074
39500.0	205.8	-50.9	0.0	322.5	580.5	267.5	45.2	1.000072
40000.0	201.1	-51.8	0.0	316.4	579.4	267.9	45.3	1.000070
40500.0	196.5	-52.6	0.0	310.4	578.2	269.9	44.7	1.000069
41000.0	192.0	-53.5	0.0	304.5	577.1	273.5	43.8	1.000068
41500.0	187.5	-53.7	0.0	297.7	576.8	278.9	42.6	1.000066
42000.0	183.1	-54.0	0.0	291.1	576.4	284.2	41.6	1.000065
42500.0	178.8	-54.2	0.0	284.6	576.1	289.4	41.2	1.000063
43000.0	174.7	-54.5	0.0	278.3	575.8	293.9	40.8	1.000062
43500.0	170.5	-55.2	0.0	272.6	574.8	295.2	40.7	1.000061
44000.0	166.4	-56.0	0.0	257.1	573.7	296.5	40.6	1.000059
44500.0	162.5	-56.9	0.0	251.7	572.6	293.7	40.2	1.000058
45000.0	158.6	-57.7	0.0	256.5	571.5	294.7	39.7	1.000057
45500.0	154.8	-58.6	0.0	251.3	570.4	292.2	38.6	1.000056
46000.0	151.1	-59.4	0.0	246.3	569.3	287.9	36.8	1.000055
46500.0	147.5	-60.2	0.0	241.4	568.2	283.2	35.1	1.000054
47000.0	144.0	-61.1	0.0	236.6	567.0	276.3	33.2	1.000053
47500.0	140.6	-61.9	0.0	231.8	565.9	269.4	31.4	1.000052
48000.0	137.2	-62.7	0.0	227.2	564.8	265.3	32.4	1.000051

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

UPPER AIR DATA
 0731003903
 WHITE SANDS SITE

STATION ALTITUDE 3989.00 FEET MSL
 17 OCT. 68 1500 HRS MDT
 ASCENSION NO. 849

MSTN SITE COORDINATES
 488580.00FEET E
 185045.00FEET N

TABLE X (Cont)

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	AIR TEMPERATURE DEGREES CENTIGRADE	REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	DIRECTION DEGREES(TN)	WIND DATA SPEED KNOTS	INDEX OF REFRACTION
48500.0	133.8	-63.3	0.0	222.2	564.1	261.3	33.6	1.000049
49000.0	130.6	-63.8	0.0	217.3	563.4	262.0	34.3	1.000048
49500.0	127.4	-64.4	0.0	212.5	562.6	264.8	34.6	1.000047
50000.0	124.3	-64.9	0.0	207.9	561.9	267.9	35.3	1.000046
50500.0	121.2	-65.4	0.0	203.3	561.2	271.5	36.4	1.000045
51000.0	118.2	-65.6	0.0	198.5	561.0	274.9	37.4	1.000044
51500.0	115.3	-64.7	0.0	192.8	562.2	275.6	35.8	1.000043
52000.0	112.5	-63.9	0.0	187.3	563.3	276.2	34.1	1.000042
52500.0	109.7	-64.5	0.0	183.2	562.4	274.4	33.5	1.000041
53000.0	107.0	-65.5	0.0	179.6	561.1	271.7	33.3	1.000040
53500.0	104.4	-66.5	0.0	176.0	559.7	270.4	32.9	1.000039
54000.0	101.8	-67.5	0.0	172.5	558.4	271.2	32.3	1.000038
54500.0	99.3	-68.5	0.0	169.0	557.1	272.0	31.6	1.000038
55000.0	96.9	-68.2	0.0	164.6	557.5	271.7	30.7	1.000037
55500.0	94.5	-67.7	0.0	160.3	558.1	271.4	29.7	1.000036
56000.0	92.2	-67.2	0.0	156.0	558.8	270.7	28.3	1.000035
56500.0	89.9	-66.7	0.0	151.8	559.4	269.0	26.0	1.000034
57000.0	87.7	-66.3	0.0	147.8	560.1	267.3	23.6	1.000033
57500.0	85.6	-65.8	0.0	143.8	560.7	263.6	21.7	1.000032
58000.0	83.5	-65.3	0.0	140.0	561.4	258.0	20.1	1.000031
58500.0	81.5	-64.8	0.0	136.3	562.0	252.4	18.6	1.000030
59000.0	79.5	-64.3	0.0	132.6	562.7	250.8	18.8	1.000030
59500.0	77.5	-63.9	0.0	129.1	563.3	249.4	19.1	1.000029
60000.0	75.7	-63.4	0.0	125.7	563.9	245.7	16.5	1.000028
60500.0	73.8	-62.9	0.0	122.3	564.6	241.1	12.9	1.000027
61000.0	72.0	-62.4	0.0	119.1	565.2	241.5	10.2	1.000027
61500.0	70.3	-62.0	0.0	115.9	565.9	245.1	8.4	1.000026
62000.0	68.5	-61.5	0.0	112.8	566.5	248.7	6.3	1.000025
62500.0	66.9	-61.0	0.0	109.8	567.1	252.5	4.1	1.000024
63000.0	65.2	-60.5	0.0	106.9	567.8	256.3	1.8	1.000024

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.00 FEET MSL
 17 OCT. 68
 ASCENSION NO. 849

UPPER AIR DATA
 0731003903
 WHITE SANDS SITE

WSTM SITE COORDINATES
 48580.00FEET E
 185045.00FEET N

TABLR X (Cont)

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA		INDEX OF REFRACTION
		AIR DEGREES CENTIGRADE	DEWPOINT CENTIGRADE				DIRECTION DEGREES(TM)	SPEED KNOTS	
63500.0	63.6	-60.0	0.	-0.	104.0	568.4	266.7	3.8	1.000023
64000.0	62.1	-59.6	0.	-0.	101.3	569.1	276.4	5.9	1.000023
64500.0	60.6	-59.1	0.	-0.	98.6	569.7	279.3	7.7	1.000022
65000.0	59.1	-58.8	0.	-0.	96.1	570.1	272.0	9.3	1.000021
65500.0	57.8	-58.5	0.	-0.	93.8	570.4	264.8	10.8	1.000021
66000.0	56.4	-58.3	0.	-0.	91.5	570.7	263.4	9.8	1.000020
66500.0	55.1	-58.1	0.	-0.	89.3	571.0	263.6	8.2	1.000020
67000.0	53.8	-57.9	0.	-0.	87.1	571.3	264.8	6.6	1.000019
67500.0	52.6	-57.6	0.	-0.	85.0	571.6	274.7	4.9	1.000019
68000.0	51.3	-57.4	0.	-0.	82.8	571.9	284.5	3.2	1.000018
68500.0	50.1	-57.2	0.	-0.	80.6	572.2	309.4	2.7	1.000018
69000.0	49.0	-57.0	0.	-0.	78.9	572.5	356.9	3.8	1.000018
69500.0	47.8	-56.8	0.	-0.	77.0	572.8	44.4	4.9	1.000017
70000.0	46.7	-56.5	0.	-0.	75.2	573.1	65.1	5.0	1.000017
70500.0	45.6	-56.3	0.	-0.	73.3	573.4	73.7	4.7	1.000016
71000.0	44.6	-56.1	0.	-0.	71.5	573.7	82.2	4.3	1.000016
71500.0	43.5	-55.9	0.	-0.	69.8	574.0	92.6	4.8	1.000016
72000.0	42.5	-55.6	0.	-0.	68.1	574.3	103.0	5.3	1.000015
72500.0	41.5	-55.4	0.	-0.	66.5	574.6	110.4	5.6	1.000015
73000.0	40.6	-55.2	0.	-0.	64.8	574.9	110.4	5.8	1.000014
73500.0	39.6	-55.0	0.	-0.	63.3	575.1	110.5	5.9	1.000014
74000.0	38.7	-54.7	0.	-0.	61.7	575.4	108.9	6.3	1.000014
74500.0	37.8	-54.5	0.	-0.	60.2	575.7	99.4	6.8	1.000013
75000.0	36.9	-54.3	0.	-0.	58.8	576.0	93.0	7.2	1.000013
75500.0	36.1	-54.1	0.	-0.	57.3	576.3	86.9	7.4	1.000013
76000.0	35.2	-53.9	0.	-0.	56.0	576.6	80.7	7.6	1.000012
76500.0	34.4	-53.6	0.	-0.	54.6	576.9	83.7	8.6	1.000012
77000.0	33.6	-53.4	0.	-0.	53.3	577.2	90.0	9.9	1.000012
77500.0	32.8	-53.2	0.	-0.	52.0	577.5	95.1	10.8	1.000012
78000.0	32.1	-53.0	0.	-0.	50.7	577.8	96.2	9.9	1.000011

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.00 FEET MSL
 17 OCT. 68 1500 HRS MDT
 ASCENSION NO. 849

JPPER AIR DATA
 0731003903
 WHITE SANDS SITE

UPPER AIR DATA
 0731003903
 WHITE SANDS SITE

488580.00FEET E
 185045.00FEET N

TABLE X (Cont)

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SQ.IND KNOTS	DIRECTION DEGREES(TN)	WIND DATA SPEED KNOTS	INDEX OF REFRACTION
		AIR DEGREES	DEWPOINT CENTIGRADE						
78500.0	31.3	-52.7	0.	**	49.5	578.1	97.3	9.0	1.000011
79000.0	30.6	-52.5	0.	**	48.3	578.4	103.9	8.0	1.000011
79500.0	29.9	-52.3	0.	**	47.1	578.7	112.5	7.1	1.000010
80000.0	29.2	-52.1	0.	**	46.0	579.0	123.8	6.0	1.000010
80500.0	28.5	-51.8	0.	**	44.9	579.2	153.3	4.6	1.000010
81000.0	27.8	-51.6	0.	**	43.8	579.5	182.8	3.2	1.000010
81500.0	27.2	-51.4	0.	**	42.7	579.8	209.0	2.0	1.000010
82000.0	26.5	-51.2	0.	**	41.7	580.1	214.5	2.1	1.000009
82500.0	25.9	-51.0	0.	**	40.7	580.4	220.0	2.1	1.000009
83000.0	25.3	-50.7	0.	**	39.7	580.7	225.5	2.2	1.000009
83500.0	24.7	-50.5	0.	**	38.7	581.0	235.4	2.1	1.000009
84000.0	24.2	-50.3	0.	**	37.8	581.3	245.9	2.1	1.000008
84500.0	23.6	-50.1	0.	**	36.9	581.6	256.5	2.0	1.000008
85000.0	23.0	-49.8	0.	**	36.0	581.9	258.1	2.1	1.000008
85500.0	22.5	-49.6	0.	**	35.1	582.2	253.7	2.4	1.000008
86000.0	22.0	-49.4	0.	**	34.2	582.4	249.3	2.7	1.000008
86500.0	21.5	-49.2	0.	**	33.4	582.7	238.8	2.8	1.000007
87000.0	21.0	-49.0	0.	**	32.6	583.0	216.0	2.6	1.000007
87500.0	20.5	-48.7	0.	**	31.8	583.3	193.2	2.4	1.000007
88000.0	20.0	-48.5	0.	**	31.0	583.6	170.5	2.3	1.000007
88500.0	19.6	-48.5	0.	**	30.3	583.7	152.4	3.0	1.000007
89000.0	19.1	-48.4	0.	**	29.6	583.7	134.2	3.7	1.000007
89500.0	18.7	-48.4	0.	**	29.0	583.8	116.1	4.4	1.000006
90000.0	18.3	-48.3	0.	**	28.3	583.8	108.0	5.6	1.000006
90500.0	17.8	-48.3	0.	**	27.6	583.9	104.3	6.9	1.000006
91000.0	17.4	-48.2	0.	**	27.0	584.0	100.6	8.3	1.000006
91500.0	17.0	-48.2	0.	**	26.4	584.0	99.4	8.7	1.000006
92000.0	16.7	-48.1	0.	**	25.8	584.1	103.0	7.4	1.000006
92500.0	16.3	-48.1	0.	**	25.2	584.1	106.7	6.1	1.000006
93000.0	15.9	-48.0	0.	**	24.6	584.2	110.3	4.8	1.000005

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.00 FEET MSL
 17 OCT. 68 1500 HRS MDT
 ASCENSION NO. 849

UPPER AIR DATA
 0731003903
 WHITE SANDS SITE

WSTW SITE COORDINATES
 48°58.00 FEET E
 105°04.50 FEET N

TABLE X (CONT)

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DIRECTION DEGREES (TN)	WIND DATA SPEED KNOTS	INDEX OF REFRACTION
		AIR DEGREES	DEWPOINT CENTIGRADE						
93500.0	15.6	-48.0	0.	-0.	24.1	584.3	137.2	4.5	1.000005
94000.0	15.2	-48.0	0.	-0.	23.5	584.3	164.7	4.3	1.000005
94500.0	14.9	-47.9	0.	-0.	23.0	584.4	192.3	4.0	1.000005
95000.0	14.5	-47.9	0.	-0.	22.5	584.4	207.8	4.3	1.000005
95500.0	14.2	-47.8	0.	-0.	21.9	584.5	213.8	5.0	1.000005
96000.0	13.9	-47.8	0.	-0.	21.4	584.6	219.9	5.8	1.000005
96500.0	13.6	-47.7	0.	-0.	21.0	584.6	226.0	6.5	1.000005
97000.0	13.2	-47.7	0.	-0.	20.5	584.7	221.5	6.9	1.000005
97500.0	12.9	-47.6	0.	-0.	20.0	584.7	216.9	7.3	1.000004
98000.0	12.7	-47.6	0.	-0.	19.6	584.8	212.2	7.6	1.000004
98500.0	12.4	-47.5	0.	-0.	19.1	584.9	208.5	8.1	1.000004
99000.0	12.1	-47.5	0.	-0.	18.7	584.9	207.0	8.9	1.000004
99500.0	11.8	-47.5	0.	-0.	18.2	585.0	205.4	9.7	1.000004
100000.0	11.5	-47.4	0.	-0.	17.8	585.0	203.9	10.5	1.000004
100500.0	11.3	-47.0	0.	-0.	17.4	585.5	207.7	11.5	1.000004
101000.0	11.0	-46.6	0.	-0.	17.0	586.1	215.2	12.6	1.000004
101500.0	10.8	-46.1	0.	-0.	16.6	586.7	222.7	13.8	1.000004
102000.0	10.6	-45.6	0.	-0.	16.2	587.3	230.2	14.9	1.000004
102500.0	10.3	-45.2	0.	-0.	15.8	587.9	233.1	16.1	1.000004
103000.0	10.1	-44.7	0.	-0.	15.4	588.5	235.2	17.3	1.000003
103500.0	9.9	-44.2	0.	-0.	15.0	589.1	237.4	18.4	1.000003
104000.0	9.7	-43.8	0.	-0.	14.7	589.7	239.6	19.6	1.000003
104500.0	9.4	-43.3	0.	-0.	14.3	590.3	243.1	21.2	1.000003
105000.0	9.2	-42.8	0.	-0.	14.0	590.9	246.6	22.8	1.000003
105500.0	9.0	-42.4	0.	-0.	13.6	591.5	250.1	24.4	1.000003
106000.0	8.8	-41.9	0.	-0.	13.3	592.1			1.000003
106500.0	8.6	-41.5	0.	-0.	13.0	592.7			1.000003
107000.0	8.4	-41.0	0.	-0.	12.7	593.3			1.000003
107500.0	8.3	-40.5	0.	-0.	12.4	593.9			1.000003
108000.0	8.1	-40.1	0.	-0.	12.1	594.5			1.000003

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

NOT REPRODUCIBLE

STATION ALTITUDE 3989.00 FEET MSL
 17 OCT. 68
 ASCENSION NO. 849

UPPER AIR DATA
 0731003903
 WHITE SANDS SITE

WSTM SITE COORDINATES
 488580.00FEET E
 185045.00FEET N

TABLE X (Cont)

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND		WIND DATA		INDEX OF REFRACTION
		AIR DEGREES	DEWPOINT CENTIGRADE			KNOTS	KNOTS	DIRECTION DEGREES(TN)	SPEED KNOTS	
108500.0	7.9	-39.6	0.	-0. **	11.8	595.1				1.000003
109000.0	7.7	-39.1	0.	-0. **	11.5	595.6				1.000003

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.00 FEET MSL
 17 OCT. 68
 ASCENSION NO. 849

MANDATORY LEVELS
 0731003903
 WHITE SANDS SITE

MSM SITE COORDINATES
 48990.00FEET E
 185045.00FEET N

TABLE XI

PRESSURE MILLIBARS	GEOPOTENTIAL FEET	AIR TEMPERATURE DEGREES CENTIGRADE	TEMPERATURE DEWPOINT CENTIGRADE	REL. HUM. PERCENT	WIND DATA		
					DIRECTION DEGREES(TN)	SPEED KNOTS	SPEED KNOTS
850.0	4945.	14.2	-6.3	24.	14.0	5.4	5.4
800.0	6610.	10.2	-8.2	27.	37.1	5.8	5.8
750.0	8357.	8.0	-10.4	30.	313.8	5.8	5.8
700.0	10204.	5.9	-20.0	14.	288.3	16.5	16.5
650.0	12190.	3.6	-21.4	14.	313.3	13.6	13.6
600.0	14302.	-1.1	-23.2	17.	283.9	15.2	15.2
550.0	16556.	-6.3	-25.7	20.	276.6	23.3	23.3
500.0	18982.	-10.8	-24.4	32.	287.3	34.3	34.3
450.0	21613.	-16.1	-30.4	28.	300.7	42.2	42.2
400.0	24490.	-22.3	-37.1	25.	296.5	42.1	42.1
350.0	27656.	-30.6	-44.6	24.	286.5	40.5	40.5
300.0	31181.	-39.5	-57.9	12.**	317.5	45.3	45.3
250.0	35215.	-44.0	0.	-0.**	315.1	44.9	44.9
200.0	40049.	-52.0	0.	-0.**	268.4	45.1	45.1
175.0	42866.	-54.4	0.	-0.**	293.8	40.9	40.9
150.0	46069.	-59.7	0.	-0.**	286.4	36.2	36.2
125.0	49759.	-64.8	0.	-0.**	267.0	35.0	35.0
100.0	54213.	-68.2	0.	-0.**	271.8	31.8	31.8
80.0	58641.	-64.5	0.	-0.**	251.3	18.6	18.6
70.0	61336.	-61.9	0.	-0.**	245.2	8.3	8.3
60.0	64488.	-58.9	0.	-0.**	276.6	8.3	8.3
50.0	68257.	-57.2	0.	-0.**	307.5	2.6	2.6
40.0	72911.	-55.1	0.	-0.**	110.5	5.8	5.8
30.0	78977.	-52.3	0.	-0.**	108.7	7.5	7.5
25.0	82861.	-50.6	0.	-0.**	228.9	2.2	2.2
20.0	87656.	-48.5	0.	-0.**	169.6	2.3	2.3
15.0	93875.	-47.9	0.	-0.**	181.2	4.1	4.1
10.0	102684.	-44.5	0.	-0.**	236.1	17.7	17.7

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

RELEASE TIME (MDT)	SECOND-STAGE IMPACT DISPLACEMENT IN MIL'S DUE TO WIND												AZI- MUTH (DEG- REES)	THEORETICAL IMPACT FROM LAUNCHER (IN MILES)				
	15-216 FT				216-4000 FT				4000-64400 FT					RANGE	N-S	E-W		
	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W	TOTAL							
RAWIN- SONDE	PIBAL																	
1230	1330	4.2N	3.7E	6.7N	4.6E	6.8N	9.3W	9.3W	17.7N	1.0W	49.2	49.2N	0.7W					
1230	1400	5.8N	0.6E	6.8N	1.9E	6.8N	9.3W	9.3W	19.4N	6.8W	51.3	50.9N	6.5W					
1230	1430	4.0N	4.5E	6.5N	2.2E	6.8N	9.3W	9.3W	17.3N	2.6W	48.9	48.8N	2.3W					
1230	1445	4.7N	1.1E	3.8N	3.2E	6.8N	9.3W	9.3W	15.3N	5.0W	47.0	46.8N	4.7W					
1230	1500	3.2N	3.9E	3.8N	3.3E	6.8N	9.3W	9.3W	13.8N	2.1W	45.3	45.3N	1.8W					
1230	1510	1.5N	3.4E	4.7N	2.5E	6.8N	9.3W	9.3W	13.0N	3.4W	44.6	44.5N	3.1N					
1230	1520	2.1N	1.4E	3.9N	4.5E	6.8N	9.3W	9.3W	12.8N	3.4W	44.4	44.3N	3.1W					
1230	1531	3.3N	0.6E	4.4N	2.2E	6.8N	9.3W	9.3W	14.5N	6.5W	46.4	46.0N	6.2W					
1500	1531	3.3N	0.6E	4.4N	2.2E	7.4N	9.0W	9.0W	15.1N	6.2W	47.0	46.6N	5.9W					

	AZI- MUTH (DEG- REES)	MILES FROM LAUNCHER		
		RANGE	N-S	E-W
LAUNCHER SETTING (ELEVATION 86.4 DEGREES QE)	005.0	31.6	31.5N	2.8E
NO WIND IMPACT	000.5	31.5	31.5N	0.3E
PREDICTED SECOND-STAGE IMPACT	057.0	44.7	44.6N	2.3W
SECOND-STAGE IMPACT, RADAR TRACK	353.2	42.9	42.6N	5.5W
PREDICTED BOOSTER IMPACT	026.0	1.4	1.3N	0.6E
ACTUAL BOOSTER IMPACT	N/A	N/A	N/A	N/A

TABLE XII. IMPACT PREDICTION DATA
NIKE-HYDAC 9.5-68-4-604

UNCLASSIFIED

Security Classification

DOCUMENT CONTROL DATA - R & D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY (Corporate effort) U. S. Army Electronics Command Ft. Monmouth, New Jersey		2. REPORT SECURITY CLASSIFICATION UNCLASSIFIED	
3. REPORT TITLE METEOROLOGICAL DATA REPORT, NIKE-HYDAC 9.5-68-4-604		3A. GROUP	
4. DESCRIPTIVE NOTES (Type of report and inclusive dates)			
5. AUTHOR(S) (First name, middle initial, last name) Harold M. Richart and Len E. Carter			
6. REPORT DATE November 1968		7A. TOTAL NO. OF PAGES 34	7B. NO. OF REFS NONE
8A. CONTRACT OR GRANT NO. a. PROJECT NO. c. DA Task 1T665702D127-02 d.		8B. ORIGINATOR'S REPORT NUMBER(S) DR-373	
9. OTHER REPORT NUMER (Any other numbers that may be assigned this report)			
10. DISTRIBUTION STATEMENT This document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of Atmospheric Sciences Research Office, White Sands Missile Range, New Mexico.			
11. SUPPLEMENTARY NOTES		12. SPONSORING MILITARY ACTIVITY U. S. Army Electronics Command Atmospheric Sciences Research Office White Sands Missile Range, New Mexico	
13. ABSTRACT Meteorological data gathered for the launching of Nike-Hydac 9.5-68-4-604 are presented for the Defense Atomic Support Agency, Sub-task 905, and for ballistic studies. The data appear, along with calculated ballistic data, in tabular form.			

DD FORM 1473
1 NOV 68

REPLACES DD FORM 1473, 1 JAN 64, WHICH IS OBSOLETE FOR ARMY USE.

UNCLASSIFIED

Security Classification

UNCLASSIFIED

Security Classification

14. KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
1. Ballistics						
2. Meteorology						
3. Wind						

UNCLASSIFIED

Security Classification