

UNCLASSIFIED

AD NUMBER
AD849115
NEW LIMITATION CHANGE
TO Approved for public release, distribution unlimited
FROM Distribution: Further dissemination only as directed by Administrative/Operational use; Commanding Officer, Office Of Naval Research Branch Office, FPO New York 09510; 6 Mar 1969 or higher DoD authority.
AUTHORITY
ONRL ltr, 8 Jun 1971.

THIS PAGE IS UNCLASSIFIED

AD849115



OFFICE OF NAVAL RESEARCH

BRANCH
OFFICE
LONDON
ENGLAND

THIS REPORT IS ISSUED
FOR INFORMATION PURPOSES
ON THE UNDERSTANDING
THAT IT IS NOT A PART OF
THE SCIENTIFIC LITERATURE
AND WILL NOT BE CITED
ABSTRACTED OR REPRINTED


ONR LONDON MEMORANDUM

M-4-69

V/STOL HEAD UP DISPLAY WORK AT
ROYAL AIRCRAFT ESTABLISHMENT, FARNBOROUGH

LIEUTENANT COMMANDER F. P. MARTIN, USN

6 MARCH, 1969



UNITED STATES OF AMERICA

THIS DOCUMENT IS SUBJECT TO SPECIAL EXPORT CONTROLS AND EACH TRANSMITTAL TO FOREIGN
GOVERNMENTS OR FOREIGN NATIONALS MAY BE MADE ONLY WITH PRIOR APPROVAL OF THE
COMMANDING OFFICER, OFFICE OF NAVAL RESEARCH BRANCH OFFICE, BOX 39, FPO NEW YORK 09510

V/STOL HEAD UP DISPLAY WORK
AT RAE, FARNBOROUGH

With the current world interest running high in V/STOL aircraft of all kinds, work in filling the vacuum that has always existed for these aircraft (helicopters, for example) with regard to instrumentation is beginning to pick up also. That's great, since helicopter pilots right up to the present time have had to make do with the same instrumentation that was developed eons ago for fixed wing use. Many of these instruments just are not adequate when flying low and very slow--nor were they designed to be. For example, the airspeed indicator in most aircraft is not reliable prior to reaching 30 knots. In a fixed wing aircraft that always operates from runways or even aircraft carriers, lovely, but V/STOL aircraft and helicopters--look in SEA today--spend a great deal of their time operating near or below 30 knots. Indeed, this may be the most important portion of the mission in the case of an air-sea rescue craft.

At any rate, helicopter pilots are tired of leftovers, and V/STOL pilots will want the top of the line. Ask any US Marine N.A.

At RAE, Farnborough, Dave Walters, Les Mayhew and their cohorts are about to begin evaluation of Head up Displays which could eventually be used for the Hawker-Siddeley Harrier. The display will be flown in one of the last prototype Kestrels. Flights are scheduled to begin in late March or early April.

The Harrier already has a display being built for it by Specto Avionics, Feltham, UK. What RAE is doing though, is trying a new approach to try to determine what pilots would like to be told. The question is, would they like to be told what is necessary to be done and how to do it? Or, would they prefer to have a choice of the method of accomplishment, if such choice exists?

Specifically, in the case of V/STOL aircraft, there is a difference in the control responses when wing-borne from that when jet-borne. Pull back the stick when wing-borne, airspeed decreases, altitude increases, while the same control movement when fully jet-borne produces a nose up attitude, but leads to rearward motion and generally a loss of altitude--assuming constant power is maintained.

Somewhere along the approach path of the V/STOL aircraft which is making a transition from wing-borne to jet-borne flight, this control transition also occurs.

In designing a head up display for V/STOL aircraft, two approaches were considered by the RAE avionics department. The basic HUD symbology from which work began is shown in Figure 1. The first modification to the basic display of Figure 1 is called (by RAE) the Control Director Display and includes the addition of the director dot, the throttle T and the nozzle symbol. These are shown on the display in Figure 2. The eyes are guided to the director dot by the lines arranged in a triangle with the dot at the apex. The short lines remain parallel to the horizon symbol. The dot shows required stick movements for altitude control. The "T" indicator is driven in a vertical sense only and corresponds with fore and aft movements of the throttle lever. The third symbol, "<", is also driven only in the vertical sense and corresponds to movements of the nozzle control lever. Ideally, the pilot maintains the horizontal bar of the "T" and the point of the "<" on the horizontal extensions of the aircraft symbol. In Figure 2, the actions required by the pilot are:

1. move stick forward and starboard (director dot)
2. move throttle aft to decrease power (T)
3. move nozzle control lever forward to accelerate (<)

Inputs to the controls are based on control laws which will give the pilot proper instructions wherever he is on the approach flight path.

The Guidance Display is shown in Figure 3. Two symbols are added to the basic display of Figure 1, namely dot with guide lines, and a trapezium shape associated with the landing area. Here, the dot indicates to the pilot, whether wing or jet-borne, that he is required to control aircraft height. It does not, however, tell him how to achieve this. The trapezium shape is used to control forward speed and therefore fore and aft acceleration. The trapezium normally remains out of sight in the upper portion of the display until the approach to a landing pad is begun. It requires inputs to stabilize it with respect to the landing pad. After the approach has begun and speed is reduced to say 150 kT, as the range from pad to aircraft drops, the symbol (trapezium) moves from the top of the display toward the center directing the pilot to begin deceleration. Again, it does not tell him how to decelerate. By matching deceleration with the display (trapezium) demands, and height with dot demands, the pilot should arrive over the pad at whatever preselected altitude he has chosen at which time the trapezium will be in the center (i.e. aircraft symbol centered on trapezium) and the height dot would be inside the aircraft symbol.


I have flown both of these displays on the RAE V/STOL Simulator and prefer the Control Director Display. However, at the time, the visual simulation portion was out of commission and I didn't get a fair test. I'll remedy this soon.



F. P. MARTIN
LCDR, USN

DISTRIBUTION:

CNO, 703, 2 cys
ONR Washington, 400B2, 461
STIC (N)
USDAO, London
S&T Unit Frankfurt
ICAF
CINCUSNAVEUR
HQ USMC (OP-522) (OP-93)
NASC (AIR 340D)
CNO (OP-72) (OP-50B)
NADC (SYIL-1)
NASC (533)
NATC (Flight Test)
DDR&E (CAPT Anderson)
DDC (20 cys)



- | | |
|----------------|-----------------|
| 1 AIR SPEED. | 7 ADD. SCALE. |
| 2 HEADING. | 8 RANGE CIRCLE. |
| 3 SLIP LIMITS. | 9 EVENT MARKER. |
| 4 A/C SYMBOL. | 10 SLIP BUBBLE |
| 5 HEIGHT. | 11 V.S.I. |
| 6 PITCH BAR. | 12 HORIZON. |

Fig. 1 Basic form of head-up display.




Fig. 2 Control director display.




Fig. 3 Guidance display.

Security Classification

DOCUMENT CONTROL DATA - R&D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY (Corporate author) Office of Naval Research, Branch Office London, England		2a. REPORT SECURITY CLASSIFICATION	
		2b. GROUP	
3. REPORT TITLE V/STOL HEAD UP DISPLAY WORK AT ROYAL AIRCRAFT ESTABLISHMENT, FARNBOROUGH			
4. DESCRIPTIVE NOTES (Type of report and inclusive dates) N.A.			
5. AUTHOR(S) (Last name, first name, initial) MARTIN, FRANK P.			
6. REPORT DATE 6 MARCH 1969		7a. TOTAL NO. OF PAGES 3	7b. NO. OF WORDS figures: 3
8a. CONTRACT OR GRANT NO. N.A.		9a. ORIGINATOR'S REPORT NUMBER(S) ONRL M-4-69	
b. PROJECT NO. N.A.		9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)	
c.		N.A.	
d.			
10. AVAILABILITY/LIMITATION NOTICES This document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of the Office of Naval Research, Branch Office, Box 39 FPO New York 09510			
11. SUPPLEMENTARY NOTES N.A.		12. SPONSORING MILITARY ACTIVITY N.A.	
13. ABSTRACT This report covers some of the new work being done at RAE Farnborough on Head-up Displays for V/STOL aircraft. Testing of displays discussed will begin at RAE in April 1969 using a Kestrel aircraft.			

UNCLASSIFIED

Security Classification

14. KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
V/STOL Head-up Display Harrier wing-borne jet-borne control law instrumentation						

INSTRUCTIONS

1. **ORIGINATING ACTIVITY:** Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (*corporate author*) issuing the report.

2a. **REPORT SECURITY CLASSIFICATION:** Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. **GROUP:** Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. **REPORT TITLE:** Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parentheses immediately following the title.

4. **DESCRIPTIVE NOTES:** If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. **AUTHOR(S):** Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. **REPORT DATE:** Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.

7a. **TOTAL NUMBER OF PAGES:** The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. **NUMBER OF REFERENCES:** Enter the total number of references cited in the report.

8a. **CONTRACT OR GRANT NUMBER:** If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. **PROJECT NUMBER:** Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. **ORIGINATOR'S REPORT NUMBER(S):** Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. **OTHER REPORT NUMBER(S):** If the report has been assigned any other report numbers (*either by the originator or by the sponsor*), also enter this number(s).

10. **AVAILABILITY/LIMITATION NOTICES:** Enter any limitations on further dissemination of the report, other than those

imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. **SUPPLEMENTARY NOTES:** Use for additional explanatory notes.

12. **SPONSORING MILITARY ACTIVITY:** Enter the name of the departmental project office or laboratory sponsoring (paying for) the research and development. Include address.

13. **ABSTRACT:** Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. **KEY WORDS:** Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, roles, and weights is optional.

UNCLASSIFIED