

UNCLASSIFIED

AD NUMBER

AD867944

LIMITATION CHANGES

TO:

Approved for public release; distribution is unlimited.

FROM:

Distribution authorized to U.S. Gov't. agencies and their contractors;
Administrative/Operational Use; 07 APR 1970.
Other requests shall be referred to Naval Air Development Center, Warminster, PA.

AUTHORITY

NADC ltr 5 Oct 1971

THIS PAGE IS UNCLASSIFIED

AD-867944

LIBRARY
TECHNICAL REPORT SECTION
NAVAL POSTGRADUATE SCHOOL
MONTEREY, CALIFORNIA 93940

NAVAL AIR DEVELOPMENT CENTER

Johnsville, Warminster, Pennsylvania

Report No. NADC-AE-7007

7 Apr 1970

NEW PLAN FOR
INTEGRATED AVIONICS SYSTEM ARCHITECTURE

TECHNICAL NOTE
AIRTASK NO. A36533/202/70F15224601
Work Unit No. 3

This document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of COMNAVAIRDEVCEM or COMNAVAIRSYSCOM (AIR-6022).



NOTICES

PRODUCT ENDORSEMENT - The discussion or instructions concerning commercial products herein do not constitute an endorsement by the Government nor do they convey or imply the license or right to use such products.

U0131595

Title: New Plan for Integrated Avionics System Architecture.

AD Number: AD0867944

Corporate Author: NAVAL AIR DEVELOPMENT CENTER WARMINSTER PA AERO-ELECTRONIC TECHNOLOGY DEPT

Personal Author: Power, J B Stein, H B

Report Date: April 07, 1970

Media: 11 Page(s)

Distribution Code: 01 - APPROVED FOR PUBLIC RELEASE

Report Classification: Unclassified

Source Code: 245702

From the collection:

Technical Reports



DEPARTMENT OF THE NAVY
 NAVAL AIR DEVELOPMENT CENTER
 JOHNSVILLE
 WARMINSTER, PA. 18974

Aero-Electronic Technology Department

REPORT NO. NADC-AE-7007

7 Apr 1970

NEW PLAN FOR
 INTEGRATED AVIONICS SYSTEM ARCHITECTURE

TECHNICAL NOTE
 AIRTASK NO. A36533/202/70F15224601
 Work Unit No. 3

Naval avionics development is pushing toward integration of electronic systems, notably in the areas of communications, navigation, and identification. However, present day avionics systems are wired-together conglomerates of "black boxes." A new concept is now introduced for the total integration of all the avionics systems through time-shared functions program-controlled to suit the mission profile. The programmer-communication link for these functions and the internal systems communications will be through the MINCOMS multiplexing concept. Microelectronic circuitry will be configured into a "slabular" form.

Reported by:


J. B. Power, H. B. Stein
 J. B. Power H. B. Stein
 Command and Control Division

Approved by:

E. C. Johnson
 E. C. Johnson, Superintendent
 Command and Control Division

D. W. Mackiernan
 D. W. Mackiernan
 Technical Director

This document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of COMNAVAIRDEVCCEN or COMNAVAIRSYSCOM (AIR-6022).



I N T R O D U C T I O N

The architectural plan for assembling a naval avionics system has been to wire together a conglomerate of electronic "black boxes."

In the early 1950's, a concept was launched to integrate a communications, navigation, and identification (CNI) subsystem by assembling all black boxes into one rack or case. The developed subsystems bear the designation, AN/ASQ-().

More recent advances have been made in the integration of avionics systems with the development of the Integrated Helicopter Avionic System (IHAS) and the Integrated Light Attack Avionics System (ILASS). However, a step backwards from the integrated concept has been taken in the electronics architecture of recent Navy aircraft, specifically the P-3C and the S-3A, which revert to the conglomerate concept. The S-3A will, however, have multiplexing interconnecting the communication subsystem.

This technical note introduces a new concept developed by the Naval Air Development Center for the total integration of all the avionics systems in the airplane.

S Y S T E M C O N C E P T

The Integrated Avionics System Architecture (IASA) concept is visualized for a fully integrated aircraft avionics system. It contains individual functional components, such as r-f and i-f amplifiers, frequency control synthesizers, audio amplifiers, detectors, and displays. These functional components are time-shared and interconnected through a central programmer control device. The central programmer controls the functions automatically, placing them in their preprogrammed configurations. Integrated antenna systems for uhf communications, navigation, identification, and electronic warfare detection are used and time-shared, receiving their instructions from the central programmer.

The Multiple Interior Communications System (MINCOMS) (a multiplexing concept and technique developed by NAVAIRDEVGEN to provide simultaneous signal flow and communications between avionics functions and crew members over twisted pair or coaxial cables) will provide the "highway" for the flow of the programmer digital instructions, as well as all other signals, digital and analog. Power switching and control, timing references, frequencies, computer control, in-flight performance monitoring (IFPM), functional fault diagnosis to replaceable levels, display signal flow, sensor signals, engine health sensor signals, airfoil control, weapons stores status and control, and other system functions are interconnected through the MINCOMS system.






Diagram of the NAVAIRDEVCON Integrated Avionics System Architecture (IASA) Concept

The use of large-scale integrated circuit techniques and other foreseeable state-of-the-art microelectronics technology are used in the construction of the system. Integrated control panels provide the crew members with access to the computer, programmer, and equipment functions. The concept will provide a Navy aircraft with electronics architecture constructed as functional "slabs" using microelectronics techniques and mounted along the airframe, rather than the "black box" concept. Cooling and interconnections are channeled about the airframe and are an integral part of the airframe.



"BLACK BOX" ARCHITECTURE

INTEGRATED "SLAB" ARCHITECTURE

Conceptual Illustration of Integrated "Slabular" Architecture

A D V A N T A G E S

The use of the IASA concept for the construction of future aircraft electronics systems affords the advantages that have been the goals in many subsystem concepts. The system becomes adaptable to changes in the tactical environment by programming the central programmer to reconfigure the functional "slabs" to the required situation. Aircraft maintenance aboard a carrier can be facilitated by using continuous monitoring and reporting of system performance, and identification of system failures. This knowledge can be used to replace modules or functional elements during aircraft turnaround time. Operators and maintenance personnel will not have to be as highly skilled, and fewer will be needed. If a failure were to occur during a flight, the programmer will select alternate paths automatically to continue system operation.

The MINCOMS "highway" will provide low level, solid state control of all internal and external communications, both man-to-machine and machine-to-machine, including the processing, distribution, and display of all sensor information; all electric power generation and distribution within the aircraft; as well as integration of aircraft flight instruments, cockpit displays, monitoring engine performance systems, and the status displays and control of the weapons systems.

Additionally, MINCOMS and functional units with microminiature electronics have high inherent reliability, and can be replaced quickly when necessary. They thus eliminate the extremely time consuming and costly fault tracing, wire replacement, and multipin connector replacement inherent in today's multiconductor "hand-wired" cable systems.

In summary, IASA will:

1. increase flexibility, expansion capability, compatibility, and reliability of all avionics systems;
2. increase probability of mission accomplishment;
3. reduce size and weight requirements; and
4. decrease maintenance, aircraft down time, and life time cost.

A P P L I C A T I O N

The 1975-85 era aircraft for such future airborne weapon systems as the Air-to-Air Weapons Control System (AAWCS) and the Airborne Tactical Control System (ATCS), are excellent candidates for full application of the IASA concept. The heart of the concept is a control programmer, and

full use can be made of the functional computer, known as the Advanced Avionics Digital Computer (AADC).

Integrated antennas could be used for the subsystems, and the AADC through MINCOMS would control these subsystems, placing them in their respective functions at the appropriate time. The data gathered through these subsystems, plus other data such as weapons status, engine performance, and electronics subsystem status, could be displayed on integrated, flat plate, display panels. The aircraft electrical system could be controlled through a newly proposed Advanced Aircraft Electric System concept, reference (a). The airfoil control could be accomplished through digital information, and might be performed through the AADC or manual control.

C O N C L U S I O N S

The ever increasing sophistication of Navy aircraft to meet defense requirements places an equivalent burden upon research and development to meet minimum size, weight, and maintenance demands with maximum performance and reliability. The NAVAIRDEVCON Integrated Avionics System Architecture concept is considered to be an important step toward these goals.

R E F E R E N C E S

The following documents are applicable to the IASA concept or have supplied ideas during the formulation of the plan.

- (a) NAVAIRSYSCOM, Nov 1969; Proposed Technical Approaches for Advanced Aircraft Electric Systems; PTA 71-421.
- (b) NAVAIRSYSCOM, 30 Jun 1968; Proposed Technical Approaches for Multiple Interior Communications System (MINCOMS); PTA 70-602.
- (c) Barney, L. W., Kearney, J. J., and Kilgore, J. R.; 16 Mar 1968; Sharing Common Circuits or Sub-System (SCCORSS) in Avionics System (U); RCA Report No. CR67-566-1 (CONF), Contract No. N00014-67-C-0375.
- (d) Ask, H., Games, J., and Stone, D.; AF-APL Symposium 24-26 Jun 1969; Impact of Multiplexing Engine/Aircraft Instrumentation and Control Signals, HSER 5374; Hamilton Standard Division of United Aircraft Corporation.
- (e) Kilgore, J. R., and Barney, L. W., 30 Dec 1966; Multiplexing Guidelines and Standards for Interior Avionics Systems; RCA, Contract No. N00014-66-C-0137.
- (f) Final Report, Multiplexing Guidelines and Standards for Interior Avionics Systems, 30 Dec 1966, RCA, Contract No. N00014-66-C-0137.
- (g) The Wired City; 1980, A Report for the President's Telecommunications Task Force; 1 Jun 1968.
- (h) SST General Purpose Multiplexer System Study; Volume I, (A Study for the Boeing Company); 27 Dec 1968; North American Rockwell Corporation, Autonetics Division.
- (i) Final Design Report for the SST Multiplexer; HSER 5280, Volume I, Book I and II; 31 Dec 1968; (a Study for the Boeing Company), Hamilton Standard Division of United Aircraft.
- (j) Davis, H. I.; Military Avionics - How Much Integration?; Astronautics and Aeronautics, Jun 1967; pp 46-54.
- (k) Parks, M. S.; The Story of Microelectronics -- First, Second and Future Generations; 1966, Publication No. P3-75/317; North American Aviation Autonetics Division.

DOCUMENT CONTROL DATA - R & D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY (Corporate author) AERO-ELECTRONIC TECHNOLOGY DEPARTMENT NAVAL AIR DEVELOPMENT CENTER WARMINSTER, PENNSYLVANIA 18974		2a. REPORT SECURITY CLASSIFICATION UNCLASSIFIED	
		2b. GROUP	
3. REPORT TITLE NEW PLAN FOR INTEGRATED AVIONICS SYSTEM ARCHITECTURE			
4. DESCRIPTIVE NOTES (Type of report and inclusive dates) TECHNICAL NOTE			
5. AUTHOR(S) (First name, middle initial, last name) J. B. POWER H. B. STEIN			
6. REPORT DATE	7a. TOTAL NO. OF PAGES 9	7b. NO. OF REFS 11	
8a. CONTRACT OR GRANT NO.	9a. ORIGINATOR'S REPORT NUMBER(S) NADC-AE-7007		
b. PROJECT NO. AIRTASK NO. A36533/202/70F15224601			
c. WORK UNIT NO. 3	9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)		
d.			
10. DISTRIBUTION STATEMENT THIS DOCUMENT IS SUBJECT TO SPECIAL EXPORT CONTROLS AND EACH TRANSMITTAL TO FOREIGN GOVERNMENTS OR FOREIGN NATIONALS MAY BE MADE ONLY WITH PRIOR APPROVAL OF COMNAVAIRDEVCCEN OR COMNAVAIRSYSCOM (AIR-6022).			
11. SUPPLEMENTARY NOTES		12. SPONSORING MILITARY ACTIVITY NAVAL AIR SYSTEMS COMMAND DEPARTMENT OF THE NAVY	
13. ABSTRACT Naval avionics development is pushing toward integration of electronic systems, notably in the areas of communications, navigation, and identification. However, present day avionics systems are wired-together conglomerates of "black boxes." A new concept is now introduced for the total integration of all the avionics systems through time-shared functions program-controlled to suit the mission profile. The programmer communication link for these functions and the internal systems communications will be through the MINCOMS multiplexing concept. Microelectronic circuitry will be configured into a "slabular" form.			

14. KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
INTEGRATED AVIONICS SLABULAR ARCHITECTURE NEW CONCEPT						