

UNCLASSIFIED

AD NUMBER
AD868927
NEW LIMITATION CHANGE
TO Approved for public release, distribution unlimited
FROM Distribution authorized to U.S. Gov't. agencies and their contractors; Critical Technology; Jan 1970. Other requests shall be referred to Commander, Air Force Weapons Lab., Kirtland AFB, OH.
AUTHORITY
AFWL ltr dtd 30 Nov 1971

THIS PAGE IS UNCLASSIFIED

AFWL-TR-69-161

AFWL-TR-
69-161

AD 868927



COMPUTERIZED ANATOMICAL MODEL MAN


Paul G. Kase

Martin Marietta Corporation
Denver, Colorado 80201
Contract F29601-69-C-0052

TECHNICAL REPORT NO. AFWL-TR-69-161

January 1970

AIR FORCE WEAPONS LABORATORY
Air Force Systems Command
Kirtland Air Force Base
New Mexico



This document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of AFWL (WLBB), Kirtland AFB, NM, 87117.

164

AIR FORCE WEAPONS LABORATORY
Air Force Systems Command
Kirtland Air Force Base
New Mexico

24

WHITE SECTION, AVAILABILITY CODES:

0000 0001 0002 0003 0004 0005 0006 0007 0008 0009 0010 0011 0012 0013 0014 0015 0016 0017 0018 0019 0020 0021 0022 0023 0024 0025 0026 0027 0028 0029 0030 0031 0032 0033 0034 0035 0036 0037 0038 0039 0040 0041 0042 0043 0044 0045 0046 0047 0048 0049 0050 0051 0052 0053 0054 0055 0056 0057 0058 0059 0060 0061 0062 0063 0064 0065 0066 0067 0068 0069 0070 0071 0072 0073 0074 0075 0076 0077 0078 0079 0080 0081 0082 0083 0084 0085 0086 0087 0088 0089 0090 0091 0092 0093 0094 0095 0096 0097 0098 0099 0100 0101 0102 0103 0104 0105 0106 0107 0108 0109 0110 0111 0112 0113 0114 0115 0116 0117 0118 0119 0120 0121 0122 0123 0124 0125 0126 0127 0128 0129 0130 0131 0132 0133 0134 0135 0136 0137 0138 0139 0140 0141 0142 0143 0144 0145 0146 0147 0148 0149 0150 0151 0152 0153 0154 0155 0156 0157 0158 0159 0160 0161 0162 0163 0164 0165 0166 0167 0168 0169 0170 0171 0172 0173 0174 0175 0176 0177 0178 0179 0180 0181 0182 0183 0184 0185 0186 0187 0188 0189 0190 0191 0192 0193 0194 0195 0196 0197 0198 0199 0200 0201 0202 0203 0204 0205 0206 0207 0208 0209 0210 0211 0212 0213 0214 0215 0216 0217 0218 0219 0220 0221 0222 0223 0224 0225 0226 0227 0228 0229 0230 0231 0232 0233 0234 0235 0236 0237 0238 0239 0240 0241 0242 0243 0244 0245 0246 0247 0248 0249 0250 0251 0252 0253 0254 0255 0256 0257 0258 0259 0260 0261 0262 0263 0264 0265 0266 0267 0268 0269 0270 0271 0272 0273 0274 0275 0276 0277 0278 0279 0280 0281 0282 0283 0284 0285 0286 0287 0288 0289 0290 0291 0292 0293 0294 0295 0296 0297 0298 0299 0300 0301 0302 0303 0304 0305 0306 0307 0308 0309 0310 0311 0312 0313 0314 0315 0316 0317 0318 0319 0320 0321 0322 0323 0324 0325 0326 0327 0328 0329 0330 0331 0332 0333 0334 0335 0336 0337 0338 0339 0340 0341 0342 0343 0344 0345 0346 0347 0348 0349 0350 0351 0352 0353 0354 0355 0356 0357 0358 0359 0360 0361 0362 0363 0364 0365 0366 0367 0368 0369 0370 0371 0372 0373 0374 0375 0376 0377 0378 0379 0380 0381 0382 0383 0384 0385 0386 0387 0388 0389 0390 0391 0392 0393 0394 0395 0396 0397 0398 0399 0400 0401 0402 0403 0404 0405 0406 0407 0408 0409 0410 0411 0412 0413 0414 0415 0416 0417 0418 0419 0420 0421 0422 0423 0424 0425 0426 0427 0428 0429 0430 0431 0432 0433 0434 0435 0436 0437 0438 0439 0440 0441 0442 0443 0444 0445 0446 0447 0448 0449 0450 0451 0452 0453 0454 0455 0456 0457 0458 0459 0460 0461 0462 0463 0464 0465 0466 0467 0468 0469 0470 0471 0472 0473 0474 0475 0476 0477 0478 0479 0480 0481 0482 0483 0484 0485 0486 0487 0488 0489 0490 0491 0492 0493 0494 0495 0496 0497 0498 0499 0500 0501 0502 0503 0504 0505 0506 0507 0508 0509 0510 0511 0512 0513 0514 0515 0516 0517 0518 0519 0520 0521 0522 0523 0524 0525 0526 0527 0528 0529 0530 0531 0532 0533 0534 0535 0536 0537 0538 0539 0540 0541 0542 0543 0544 0545 0546 0547 0548 0549 0550 0551 0552 0553 0554 0555 0556 0557 0558 0559 0560 0561 0562 0563 0564 0565 0566 0567 0568 0569 0570 0571 0572 0573 0574 0575 0576 0577 0578 0579 0580 0581 0582 0583 0584 0585 0586 0587 0588 0589 0590 0591 0592 0593 0594 0595 0596 0597 0598 0599 0600 0601 0602 0603 0604 0605 0606 0607 0608 0609 0610 0611 0612 0613 0614 0615 0616 0617 0618 0619 0620 0621 0622 0623 0624 0625 0626 0627 0628 0629 0630 0631 0632 0633 0634 0635 0636 0637 0638 0639 0640 0641 0642 0643 0644 0645 0646 0647 0648 0649 0650 0651 0652 0653 0654 0655 0656 0657 0658 0659 0660 0661 0662 0663 0664 0665 0666 0667 0668 0669 0670 0671 0672 0673 0674 0675 0676 0677 0678 0679 0680 0681 0682 0683 0684 0685 0686 0687 0688 0689 0690 0691 0692 0693 0694 0695 0696 0697 0698 0699 0700 0701 0702 0703 0704 0705 0706 0707 0708 0709 0710 0711 0712 0713 0714 0715 0716 0717 0718 0719 0720 0721 0722 0723 0724 0725 0726 0727 0728 0729 0730 0731 0732 0733 0734 0735 0736 0737 0738 0739 0740 0741 0742 0743 0744 0745 0746 0747 0748 0749 0750 0751 0752 0753 0754 0755 0756 0757 0758 0759 0760 0761 0762 0763 0764 0765 0766 0767 0768 0769 0770 0771 0772 0773 0774 0775 0776 0777 0778 0779 0780 0781 0782 0783 0784 0785 0786 0787 0788 0789 0790 0791 0792 0793 0794 0795 0796 0797 0798 0799 0800 0801 0802 0803 0804 0805 0806 0807 0808 0809 0810 0811 0812 0813 0814

When U. S. Government drawings, specifications, or other data are used for any purpose other than a definitely related Government procurement operation, the Government thereby incurs no responsibility nor any obligation whatsoever, and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise, as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

This report is made available for study with the understanding that proprietary interests in and relating thereto will not be impaired. In case of apparent conflict or any other questions between the Government's rights and those of others, notify the Judge Advocate, Air Force Systems Command, Andrews Air Force Base, Washington, D. C. 20331.

DO NOT RETURN THIS COPY. RETAIN OR DESTROY.

AFWL-TR-69-161

COMPUTERIZED ANATOMICAL MODEL MAN

Paul G. Kase

Martin Marietta Corporation
Denver, Colorado 80201
Contract F29601-69-C-0052

TECHNICAL REPORT NO. AFWL-TR-69-161

This document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of AFWL (WLBB), Kirtland AFB, NM, 87117. Distribution is limited because of the technology discussed in the report.

FOREWORD


This research was prepared by the Martin Marietta Corporation, Denver, Colorado, under Contract F29601-69-C-0052. The research was performed under Program Element 62401F, Project 5877, Task 01, and was funded by the Manned Spacecraft Center, Houston, Texas, of the National Aeronautics and Space Administration.


Inclusive dates of research were February through October 1969. The report was submitted 17 November 1969 by the Air Force Weapons Laboratory Project Officers, Captain James A. Dibiase and Captain Roger S. Case, Jr. (WLBB).


Information in this report is embargoed under the Department of State ITIARs. This report may be released to foreign governments by departments or agencies of the US Government subject to approval of AFWL (WLBB), Kirtland AFB, NM, 87117.

The important contributions of the following persons to the success of this study are gratefully acknowledged: Mr. George Moschinsky, Artist, for the illustrations; Senior Engineers John E. Braly, Thomas J. Sullivan, and Adolph M. Spamer for the model design; Mrs. Lois M. Ryan, Associate Engineer, for MEVDP adaptation and operation; Leonard J. Caranna, M. D., and James D. Gatts, M. D., Medical Consultants; Edward Karnes, Ph.D., subject for anatomical measurements; and Mr. Alva Hardy of NASA Manned Spacecraft Center, Houston, Texas, for his computer graphics checking of the model.

This technical report has been reviewed and is approved.


JAMES A. DIBIASE
Captain, USAF
Project Officer


DEAN E. EWING
Major, USAF
Chief, Bioenvironmental Branch


WARREN J. HARE
Colonel, USAF
Chief, Biophysics Division

ABSTRACT

(Distribution Limitation Statement No. 2)

The Computerized Anatomical Model Man is a detailed representation of the radiation transport properties of the human body. It is to be used for computation of the areal density distribution at specified locations in the body. This information is applicable to dose calculations in natural, weapon, reactor, and other radiation environments. The model has two configurations--standing and seated. Over 2200 individual geometrical shapes have been used to depict the external conformation, the skeleton, and the principal organs. The exterior dimensions are those of the 50th percentile Air Force man; the skeleton and organs were scaled from life-size models to conform to the exterior. The model includes variations of material density and fractional composition by weight due to the principal chemical elements contained in muscle, bone, bone marrow, and organ tissue. The model is compatible with the North American Rockwell Modified Elemental Volume Dose Program. This has been demonstrated by solution of sample problems employing both configurations of the model with the North American Rockwell Program on the CDC 6600 digital computer at the Air Force Weapons Laboratory.

This page intentionally left blank.

CONTENTS

<u>Section</u>		<u>Page</u>
I	OBJECTIVES OF THE MODEL MAN	1
	Introduction	1
	Model Requirements	2
II	MODEL DEVELOPMENT	4
	Reference Illustrations	4
	Geometrical Representation	14
	Chemical Composition and Density	22
III	DESCRIPTION OF THE MODEL	30
	Shield Identification and Location	30
	Geometrical Shapes	34
	Materials	34
	Weights	38
IV	MODEL DEMONSTRATION	45
	Dose Points	45
	Sample Problems	45
V	RESULTS AND RECOMMENDATIONS	47
	Summary of Results	47
	Recommendations	47
	APPENDIXES	
	I Illustrations	49
	II Listing of Card Decks for the Model	117
	Card Formats	117
	Card Listing	121
	III Listing of Sample Problem Results	123
	Description of Problem	123
	Problem Listing	123

CONTENTS (cont'd)

<u>Section</u>	<u>Page</u>
REFERENCES	139
BIBLIOGRAPHY	141

ILLUSTRATIONS

<u>Figure</u>		<u>Page</u>
1	Body Link-Joint and Coordinate Systems	5
2	Exterior of the Standing Man	7
3	Exterior of the Seated Man	8
4	Plastic Model Skeleton	10
5	Assorted Human Bones	11
6	Skeleton Within Standing Man	12
7	Skeleton Within Seated Man	13
8	Plastic Model Torso, Assembled	15
9	Plastic Model Torso, Disassembled	16
10	Organs in Torso, Front View	17
11	Organs in Torso, Right Side View	18
12	Geometrical Shapes Compatible with MEVDP	19
13	Example of Sectoring Code Worksheet	21
14	Lockheed LSVC-4 Computer Drawing of the Eye	23
15	MEVDP Computer Drawing of the Eye	24
16	Sections of Human Bones	27
17	Shield Identification Numbers Assigned to the Standing Man	31
18	Shield Identification Numbers Assigned to the Seated Man	32
19	Composite Shields in the Muscle Portion, Standing Man	143
20	Composite Shields in the Muscle Portion, Seated Man	144
21	Composite Shields in the Skeleton, Standing Man	145
22	Composite Shields in the Skeleton, Seated Man	146
23	Errors of the Volume Calculation	40
24	Time and Accuracy Analysis of the Brain Volume Calculation	41

ILLUSTRATIONS (cont'd)

<u>Figure</u>		<u>Page</u>
25	Locations of Body Sections	50
26(A)	Vertical Section of Head, Normal to X-Axis at X = 2.7 Inches	51
27(B)	Vertical Section of Head, Normal to Y-Axis at Eye Pupil, Y = 1.25 Inches	52
28(C)	Vertical Section of Head, Normal to Y-Axis at Center	53
29	Horizontal Sections of Head, Torso, Leg, and Foot	
	(1) Head, Z = 3.3 Inches	54
	(2) Head, Z = 4.3 Inches	54
	(3) Head, Z = 5.7 Inches	55
	(4) Head, Z = 7.0 Inches	55
	(5) Head, Z = 8.1 Inches	56
	(6) Neck, Z = 9.0 Inches	56
	(7) Neck, Z = 10.4 Inches	57
	(8) Shoulder, Z = 12.0 Inches	57
	(9) Chest, Z = 15.0 Inches	58
	(10) Chest, Z = 19.0 Inches	59
	(11) Abdomen, Z = 26.0 Inches	60
	(12) Abdomen, Z = 32.0 Inches	61
	(13) Abdomen, Z = 34.0 Inches	62
	(14) Thighs and Genitals, Z = 36.5 Inches	63
	(15) Thigh, Z = 40.0 Inches	64
	(16) Upper Leg, Z = 45.5 Inches	64
	(17) Leg Above Knee, Z = 49.0 Inches	65
	(18) Knee, Z = 51.0 Inches	65
	(19) Leg Below Knee, Z = 53.0 Inches	66
	(20) Lower Leg, Z = 57.0 Inches	66

ILLUSTRATIONS (cont'd)

<u>Figure</u>		<u>Page</u>
	(21) Leg Above Ankle, Z = 64.0 Inches	67
	(22) Ankle, Z = 66.0 Inches	67
30	Sections of Foot	
	(23) Horizontal, Z = 68.0 Inches	68
	(24) Vertical, X = 4.0 Inches	68
	(25) Vertical, X = 6.0 Inches	68
31	Horizontal Sections of Arm and Genitals	
	(26) Upper Arm at Shoulder, Z = 17.0 Inches	69
	(27) Upper Arm, Z = 20.0 Inches	69
	(28) Arm Above Elbow, Z = 25.0 Inches	70
	(29) Elbow, Z = 26.5 Inches	70
	(30) Arm Below Elbow, Z = 28.5 Inches	71
	(31) Lower Arm, Z = 33.0 Inches	71
	(32) Wrist, Z = 35.7 Inches	72
	(33) Hand at Root of Thumb, Z = 38.0 Inches	72
	(34) Hand and Thumb, Z = 39.6 Inches	73
	(35) Genitals, Z = 38.0 Inches	73
	(36) Upper Leg, Seated, X = 4.0 Inches	74
	(37) Upper Leg, Seated, X = 13.7 Inches	74
32	Spinal Column	75
33	Pelvic Girdle	76
34	Eye Location	77
35	Central Nervous System, Brain and Spinal Cord	
	a. Front View	78
	b. Right Side View	79

ILLUSTRATIONS (cont'd)

<u>Figure</u>		<u>Page</u>
36	Thyroid	
	a. Front View	80
	b. Right Side View	81
	c. Horizontal Section, Z = 11.5 Inches	82
37	Main Circulatory System	
	a. Front View	83
	b. Right Side View	84
38	Sections of the Heart and Blood Vessels	
	(1) Horizontal, Z = 16.3 Inches	85
	(2) Horizontal, Z = 18.5 Inches	85
	(3) Vertical, Normal to Y-Axis at Center	86
	(4) Vertical, Normal to X-Axis, X = 1.0 Inches	87
	(5) Vertical, Normal to X-Axis, X = 2.0 Inches	87
39	Head with Nasal and Oral Passages, Esophagus, and Trachea	
	a. Vertical Section Normal to Y-Axis at Center	88
	b. Vertical Section Normal to X-Axis, X = 2.7 Inches	89
40	Views of Lungs	
	a. Front View	90
	b. Right Side View	91
41	Horizontal Sections of the Lungs	
	(1) Z = 15.3 Inches	92
	(2) Z = 18.5 Inches	93
42	Views of Liver and Gall Bladder	
	a. Front View	94
	b. Right Side View	95

ILLUSTRATIONS (cont'd)

<u>Figure</u>		<u>Page</u>
43	Sections of Liver and Gall Bladder	
	(1) Horizontal, Z = 22.3 Inches	96
	(2) Vertical, Normal to Y-Axis, Y = 1.8 Inches	97
	(3) Vertical, Normal to X-Axis, X = 0.0 Inches	97
44	Views of the Spleen	
	a. Front View	98
	b. Right Side View	99
45	Transverse Section of the Spleen (1)	100
46	Views of the Kidney and Adrenal Glands	
	a. Front View	101
	b. Right Side View	102
47	Horizontal Section of the Kidneys, Z = 26.0 Inches (1)	103
48	Views of the Bladder	
	a. Front View	104
	b. Right Side View	105
49	Vertical Section of the Bladder, Normal to the X-Axis, X = 0.3 Inches (1)	106
50	Views of the Gastrointestinal Tract	
	a. Front View	107
	b. Right Side View	108
51	Views of the Pancreas	
	a. Front View	109
	b. Right Side View	110
52	Sections of the Pancreas	
	(1) Transverse	111
	(2) Vertical, Normal to the Y-Axis at the Center	111

ILLUSTRATIONS (cont'd)

<u>Figure</u>		<u>Page</u>
53	Sections of the Stomach and Intestines	
	(1) Horizontal, Z = 23.0 Inches	112
	(2) Vertical, Normal to the Y-Axis, Y = 2.5 Inches	113
	(3) Horizontal, Z = 26.2 Inches	114
	(4) Horizontal, Z = 29.0 Inches	115
	(5) Horizontal, Z = 32.3 Inches	116
54	Portion of Card Deck Listing	122
55	Listing of Sample Problem	
	a. Listing of Computerized Anatomical Model Man	126
	b. Listing (concl)	127
	c. Listing of Astronaut Geometry	128
	d. Summary of Transformations to Detector Point Coordinate System	129
	e. Ray Orientation Data	130
	f. Ray Orientation Data (concl), Range-Energy Coefficients, and Areal Density Function	131
	g. Areal Density Function (concl) and Least Squares Analysis	132
	h. Least Squares Analysis (cont)	133
	i. Least Squares Analysis (concl)	134
	j. ORDER Printout	135
	k. ORDER Printout (concl) and Sorted Areal Densities	136
	l. Sorted Areal Densities (cont)	137
	m. Sorted Areal Densities (concl)	138

TABLES

<u>Table</u>		<u>Page</u>
I	Dimensions of 50th Percentile Air Force Man	9
II	Distribution of Marrow in the Adult Human Skeleton	26
III	Shield Identification Summary	33
IV	Summary of Shields Employed in the Model Man	35
V	Summary of Geometrical Shapes Employed in the Model Man	36
VI	Material Code Table	37
VII	Summary of Model Man Weight	42
VIII	Comparison of Model and Actual Organ Weights	43
IX	Dose Point Locations Within the Model Man	46
X	Data Requirements, First Card of Set	118
XI	Data Requirements, Second and Succeeding Cards of Set	120

This page intentionally left blank.

SECTION I

OBJECTIVES OF THE MODEL MAN

1. INTRODUCTION

The growth of manned space flight has brought new emphasis to the problem of evaluating the effects of radiation on man. Though space flight has had considerable public attention, man may be exposed to various radiation sources other than the natural radiation of space. These sources include weapons, reactors, X-ray generators and radioisotopes. Exposure may occur during combat or in laboratory, industrial, or medical situations, as well as in space. There is a need common to all of these situations. That need is to be able to predict accurately the radiation arriving from the radiation source at a specified location in the body.

Before the advent of space flight, except for wartime or accidents, scrupulous efforts had been made to minimize the exposure of man to radiation. Now, manned missions in space involve planned endurance of radiation so that lengthy missions, such as Apollo Applications (AAP), the large space station, or planetary exploration, can be practical in view of other considerations such as weight.

The trend of manned space flight is shown by the Mercury, Gemini, and Apollo programs. During Mercury the doses were measured in mrad. Warren et al.⁽¹⁾ summarize the radiation doses measured during the Gemini program and those anticipated in the Apollo command and service module (CSM). The largest dose reported so far during the U.S. manned space program occurred during the Gemini X flight when doses on the order of 0.8 rad were measured at the astronauts' chests. The Apollo lunar missions occur during a period of maximum solar flare activity. If one of the more intense solar flares of the last solar cycle were repeated, for instance, that of 12 November 1960, the skin dose within the CSM could be 200 rad. The maximum radiation dose levels acceptable to the AAP are higher. For example, Berry⁽²⁾ has published a maximum operational dose of 300 rad at a depth of 0.1 mm in the skin for 60-day missions. This dose has been derived from a daily dose limit of 5 rad.

The maximum operational dose is an emergency limit. It could result in harmful inflight response in terms of crew safety and postflight response of delayed radiation injury.

Tentative plans for future AAP missions and for interplanetary exploration show the possibility of individuals remaining in orbit for a year or longer. The AAP mission analysis indicates that the skin and eye doses absorbed during an extended mission might exceed currently accepted allowables.

As the limits of the acceptable radiation dose are approached, the need for precise dose calculation is evident. First, a dose calculation with a simple model of man could indicate arrival at a radiation dose limit when, in fact, this has not occurred. Both the configuration of the spacecraft and the presence of the astronaut have profound effects on the radiation dose. As self-shielding by the body could make an apparently unacceptable mission tolerable, this effect should be considered in the planning of missions where radiation might be a limiting factor. Second, more detailed calculations of radiation doses in man are needed because the larger doses anticipated during long missions could exceed the injury thresholds of specific sensitive organs before reaching the maximum operation dose limits specified by sources such as Berry. Several of the critical dose levels are indicated in a report by Helvey *et al.* (3) For instance, microscopically detectable changes in the germinal epithelium occur near 25 rad. A dose of 150 rad to the gonads may produce temporary subfertility or sterility. A complete analysis of the radiation dose in hypersensitive regions would account for significant modification of the dose due to self-shielding by the body, and thereby either establish confidence in the safety of the astronaut or determine positively that the mission would cause excessive local doses.

Prior to initiation of this study, a detailed model of the radiation transport properties of man, including the effects of the skeleton and organs, had not been available. It is hoped that the Computerized Anatomical Model Man will be a standard for calculation of radiation doses from space and other sources.

2. MODEL REQUIREMENTS

It is common practice to use large digital computers to process the tremendous number of calculations necessary to evaluate complex shielding configurations. The North American Rockwell Modified Elemental Volume Dose Program (MEVDP) is one of several programs for this purpose. (4) This program is operational at both the Air Force Weapons Laboratory and the NASA Manned Spacecraft Center, Houston. The Computerized Anatomical Model Man is completely compatible with MEVDP and should therefore have considerable utilization.

To interface with MEVDP, the Computerized Anatomical Model Man conforms to two principal requirements. First, the geometrical configuration of the model has been established with combinations of the geometrical shapes recognized by MEVDP. These shapes are the hexahedron - a figure comprised of six planar surfaces: right circular cylinder; sphere; hemisphere; right circular cone, truncated right circular cone, and the ellipsoid - truncated by two or fewer parallel planes. Second, the two punched card decks that represent the standing and seated positions of the man are in the format required for operation with MEVDP. In addition to geometrical data, these cards contain the identity of the shield - a four-digit number, a three-digit number identifying the shield material, the material density, and a number indicating the number of individual shields comprising a composite shield. The details of all of these interface requirements are discussed in Section II, Model Development.

The Computerized Anatomical Model Man depicts the radiation transport properties of the 50th percentile Air Force man. The dimensions and medical information incorporated in the model have been taken in large part from a bibliography furnished by the Air Force Weapons Laboratory at the start of this study. The bibliography is included in this report. This information has been supplemented by literature searches conducted by two medical consultants and by measurements of both living subjects and anatomical models. In order to achieve a complete model of the radiation transport properties of man, the exterior conformation, the skeleton, and the organs are depicted. The objectives of the model development included 0.1-inch accuracy of component location and 0.1-inch accuracy of geometrical data input to the computer. The weight of the model man is within 10% of the weight of the 50th percentile Air Force man. The study objectives also included representation of the man with 500 to 1000 individual shield geometries. However, it was necessary to use over 2200 geometrical shapes to achieve the desired accuracy.

Best Available Copy

SECTION II

MODEL DEVELOPMENT

1. REFERENCE ILLUSTRATIONS

a. Coordinate and Drawing Systems

All illustrations and computer data are referred to a right-hand, orthogonal 3-axis (XYZ) system defined as follows. The origin of the system is at the top of the head in the left/right plane of symmetry. The Z-axis is vertical and positive down so that the clavicular and transpelvic links of the body joints are intersected as shown in Figure 1. The X-axis is in a horizontal plane pointed forward. The positive Y-axis is directed to the right. With this coordinate system, change from a standing to a seated position entails movement of only the limbs. The head and torso are always in the same position with respect to this coordinate system.

The illustrations made during this study were the master source of dimensions for all numerical data entered on the computer card deck. To ensure consistency, the artist drew each illustration 1/2 life size on a 1/2-inch grid. The origin of all measurements is the origin of the coordinate system. An objective of the study was to locate all components within 0.1 inch of the coordinate system. With the grid chosen, each square represents 1 inch. Dimensions scaled from these drawings are considered accurate to within ± 0.01 inch.

b. External Conformation of the Man

The exterior dimensions of the Computerized Anatomical Model Man are principally the 50th percentile Air Force man established by Hertzberg, Daniels and Churchill.⁽⁵⁾ This survey reports body size data for 132 measurements of over 4000 Air Force flying personnel. Though more recent documents were included in the government furnished bibliography, this survey was usually the principal source for these documents. Furthermore, Hertzberg measured many more individuals than any of the other investigators. Since the principal objective of the Hertzberg survey was to obtain data for the design of skin-tight flying garments, his information is not always appropriate for design of a model man.




Figure 1 Body Link-Joint and Coordinate Systems

The artist resolved inconsistencies in the Hertzberg data and supplemented the data where necessary with measurements of a living subject who closely approximated the 50th percentile Air Force man. A medical consultant assisted in obtaining these measurements. The artist combined the Hertzberg data, the supplementary measurements, and his experience to produce the exterior layout of the standing man shown in reduced size on Figure 2. Figure 3 shows the differences in appearance of the limbs and genitals of the man when seated.

Symbols and numbers on Figures 2 and 3 show where the Hertzberg data and the illustrations coincide. Table I gives the results of the Hertzberg survey for the 50th percentile man. The numbers on the figures and the numbers in the table are identical. Symbols are also used in Table I to indicate whether the data was used in preparing the illustrations. The reader is referred to the Hertzberg paper for explanation of any measurement nomenclature not clarified by reference to Figures 2 and 3.

c. Skeleton

The bibliography and literature search by the medical consultants provided qualitative or pictorial information describing the skeleton and its location within the body, but specific dimensions for an average man were not available. Therefore, the artist referred to a life-size plastic model skeleton and an assorted set of human bones that had been purchased from the Clay-Adams Scientific Company, New York, and was subsequently borrowed from the Research and Development Division, Martin Marietta Corporation, while preparing the layouts of the skeleton. Figure 4 is a photograph of the skeleton. The assorted bones are shown in Figure 5. The artist referred to Morton⁽⁶⁾, Eycleshymer⁽⁷⁾, and Grant⁽⁸⁾, and was advised by the medical consultants in scaling the model skeleton and developing its conformation within the outline of the 50th percentile Air Force man. The results are shown in Figure 6, the standing position; and in Figure 7, the seated position.

In addition to these front and side views, the artist drew sections of the skeleton at numerous locations. These drawings are presented in Appendix I - Illustrations.

Best Available Copy




Figure 2 Exterior of the Standing Man




Figure 3 Exterior of the Seated Man

Table I. Dimensions of the 50th Percentile Air Force Man

Designation	Dimension	Used X,Y,Z (in.)
Weight	161.9	---
Body Lengths		
1. Weight (lb)	161.9	---
2. Stature	69.1	Z = 69.1
3. Nasal root height	65.0	Z = 6.1
4. Eye (internal canthus) height	64.7	Z = 4.4
5. Tragon height	64.0	Z = 5.1
6. Cervical height	59.2	Z = 9.9
7. Shoulder (acromial) height	56.6	Z = 12.5
8. Suprasternal height	56.3	Z = 12.8
9. Nipple height	50.4	Z = 18.7
10. Substernal height	48.7	Z = 20.4
11. Elbow height (radiale height)	43.5	Z = 25.6
12. Waist height	42.1	Z = 27.0
13. Pelvic height	36.5	Z = 35.5
14. Wrist height (stylion height)	33.6	Z = 36.3
15. Crotch height (lineum)	32.8	Z = 37.5
16. Gluteal furrow height	31.6	Z = 39.1
17. Kneecap (metacarpale III) height	29.0	Z = 48.9
18. Kneecap (metacarpale III) height	29.2	Z = 48.9
19. Sitting height	16.0	
20. Eye (internal canthus) height, -S	11.5	
21. Shoulder (acromial) height, -S	23.3	
22. Waist height, -S	9.3	
23. Elbow rest height, -S	9.1	
24. Thigh clearance height, -S	5.6	
25. Knee height, -S	21.7	Z = 21.7
26. Popliteal height, -S	17.0	Z = 17.0
27. Buttock-knee length	23.6	
28. Buttock-leg length	42.7	
29. Shoulder-elbow length	18.1	Z = 18.1
30. Forearm-hand length	16.9	Z = 16.9
31. Span	20.8	
32. Arm reach from wall	16.6	
33. Maximum reach from wall	18.6	
34. Functional reach	12.3	
Body Breadths and Thicknesses		
35. Elbow-to-elbow breadth	17.2	ZY = 17.2
36. Hip breadth, -S	13.9	ZY = 13.9
37. Kneecap-knee breadth, -S	7.9	
38. Biacromial diameter	15.8	ZY = 15.8
39. Shoulder breadth (biacromial dia)	17.9	
40. Chest breadth	12.0	ZY = 10.8
41. Waist breadth	10.6	
42. Hip breadth	13.2	ZX = 9.15
43. Chest depth	9.0	ZX = 7.9
44. Waist depth	7.9	
45. Buttock depth	8.8	

Designation	Dimension	Used X,Y,Z (in.)
Circumferential and Body Surface Measurements		
46. Neck circumference	14.9	
47. Shoulder circumference	45.1	
48. Chest circumference	38.7	
49. Waist circumference	31.7	
50. Buttock circumference	37.7	
51. Thigh circumference	22.4	
52. Lower thigh circumference	17.3	
53. Calf circumference	14.4	
54. Ankle circumference	8.9	
55. Scye circumference	18.0	
56. Axillary arm circumference	12.4	
57. Biceps circumference-Y	12.8	
58. Elbow circumference-Y	12.2	
59. Lower arm circumference-Y	11.5	
60. Wrist circumference	6.8	
61. Sleeve length	19.8	
62. Sleeve length (spine-to-wrist)	31.7	
63. Anterior neck length	3.4	
64. Posterior neck length	3.6	
65. Shoulder length	6.8	
66. Waist back	17.7	Z = 17.7
67. Waist front	15.2	
68. Gluteal arc	11.7	
69. Crotch length	28.2	
70. Vertical trunk circumference	64.8	
71. Interscye	19.6	
72. Interscye maximum	22.9	
73. Buttock circumference, -S	41.5	
74. Knee circumference, -S	15.4	
The Foot		
75. Foot length	10.5	ZX = 10.5
76. Instep length	7.6	
77. Foot breadth	3.78	
78. Heel breadth	2.63	
79. Ball breadth	2.95	
80. Medial malleolus height	3.5	
81. Lateral malleolus height	2.7	
82. Ball of foot circumference	9.6	
The Hand		
83. Hand length	7.5	Z = 7.5
84. Palm length	4.24	Z = 4.2
85. Hand breadth at thumb	4.08	ZX = 3.90
86. Hand breadth at metacarpale	3.49	ZX = 3.35
87. Thickness at metacarpale III	1.17	
88. First phalanx III length	2.67	
89. Finger diameter III	0.85	
90. Grip diameter (inside)	1.81	
91. Grip diameter (outside)	4.09	
92. Flat circumference	11.6	

Designation	Dimension	Used X,Y,Z (in.)
The Head and Face		
93. Head length	7.7	ZX = 7.9
94. Head breadth	6.05	ZY = 6.1
95. Minimum frontal diameter	4.35	ZX = 4.35
96. Maximum frontal diameter	4.72	ZX = 4.72
97. Biygonomic diameter	5.54	ZY = 5.54
98. Bigonial diameter	4.3	ZY = 4.3
99. Bitrignon diameter	5.6	ZY = 5.6
100. Interocular diameter	1.25	ZY = 1.25
101. Biocular diameter	3.78	ZY = 3.78
102. Interpupillary distance	2.49	ZY = 2.49
103. Nose length	2.00	Z = 2.00
104. Nose breadth	1.31	ZY = 1.38
105. Nasal root breadth	0.61	ZY = 0.61
106. Nose protrusion	0.90	ZX = 0.90
107. Philtrum length	0.76	Z = 0.67
108. Menton-subnasal length	2.62	Z = 2.60
109. Menton-erinion length	7.4	
110. Lip-to-lip distance	0.63	Z = 0.73
111. Lip length (bichelion diameter)	2.02	ZY = 2.00
112. Ear length	2.47	Z = 2.50
113. Ear breadth	1.44	ZX = 1.20
114. Ear length above tragon	1.17	Z = 1.47
115. Ear protrusion	0.83	ZY = 0.60
116. Head height (tragon to vertex)	5.1	Z = 5.10
117. Menton projection	1.9	
118. External canthus to wall	6.8	ZX = 6.8
119. Nasal root to wall	7.8	ZX = 7.8
120. Tragon to wall	4.0	ZX = 4.2
121. Larynx to wall	6.9	
122. Head circumference	22.5	ZX = 6.72
123. Sagittal arc	15.1	
124. Bitrignon-coronal arc	13.8	
125. Minimum frontal arc	5.4	
126. Bitrignon-minimum frontal arc	12.0	
127. Bitrignon-erinion arc	13.1	
128. Bitrignon-menton arc	12.8	
129. Bitrignon-submandibular arc	12.1	
130. Bitrignon-subnasal arc	11.4	
131. Bitrignon-posterior arc	10.7	
132. Bitrignon-inion arc	11.6	

Note: S - Seated; P - Flexed.
All dimensions in inches except where noted.




Figure 4 Plastic Model Skelton




Figure 5 Assorted Human Bones




Figure 6 Skeleton Within Standing Man




Figure 7 Skeleton Within Seated Man

d. Organs

The dimensional data available for organs was, as in the case of the skeleton, inadequate. Accordingly, the artist followed the same procedure used to develop the illustrations for the skeleton. In addition to the references cited for the skeleton, he also referred to Frohse⁽¹¹⁾ and Armstrong⁽¹²⁾ during this phase. Another Clay Adams visual aid, the life-size model torso shown assembled in Figure 8 and disassembled in Figure 9, was borrowed for the preparation of these illustrations. The resulting layouts of the organs in the torso are shown in front and right side views on Figures 10 and 11, respectively. Views and sections of the individual organs are presented in Appendix I - Illustrations.

2. GEOMETRICAL REPRESENTATION

a. Input Required for the MEVDP

All geometrical data describing the Computerized Anatomical Model Man have been prepared in a punched card format compatible with the MEVDP. The punched card formats are explained in detail in Appendix II - Listing of Card Decks for Model. The types of geometrical shapes incorporated in MEVDP are shown in Figure 12. The number and symbols shown with the individual figures are locations, radii, and angles required by MEVDP. These shapes may be used individually as solids or may be combined in mixtures of up to 10 solids and voids to form composite shields. The voids are used only within composites to modify the shapes of the solids and thus to describe very complex shapes with a limited number of simple geometries. This capability was used extensively in the geometrical development of the model.

In addition to the geometrical data, the input to MEVDP includes the following:

- Shield identification;
- Shield type;
- Material identification;
- Material density;
- Number of shields within a composite.

Further explanation of all these inputs appears in Section III - Description of Model, and Appendix II - Listing of Card Decks for Model.




Figure 8 Plastic Model Torso, Assembled




Figure 9 Plastic Model Torso, Disassembled




Figure 1: Organs in Torso: Front View







Figure 1. Organs in Torii, Right Side View




a. Hexahedron




b. Cylinder




c. Sphere




d. Hemisphere



e. Cone



f. Truncated Cone



g. Ellipsoid

Figure 12 Geometrical Shapes Compatible with MEVDP

b. Design Procedure

Development of the geometrical representation entailed four steps. First, the external conformation was modeled. Next, the skeleton was designed independently of the exterior. Then, the skeleton and exterior were integrated. This procedure frequently involved modification of portions of both the exterior and the skeleton so that the combined shield configurations would be compatible with the allowable number of shields in a composite. As indicated earlier, MEVDP allows a mixture of 10 shields in a composite. However, the shield serial number system used in this study permits only 9 shields in a composite. (This number system is described in Section III - Description of Model). The final step of the development was modeling of the organs. No modification was involved during this step because the organs naturally fit within previously designed cavities of the skeleton and abdomen.

Simplifications of the design were made in several places in the interest of developing a model of reasonable size. On the exterior, all hair was ignored. In the case of the skeleton, the skull was simplified by not modeling the nasal septum, the zygomatic arches (or cheekbones), the mastoid processes, or the inner ear. The rib cage was simplified by assuming that the entire structure is a thin shell. The outline of the rib cage is correct, but the region between the ribs is bone, not tissue. Generally, the organs have their proper shape. However, the chest and abdominal cavities are completely filled with organ tissue. Fluids in which several organs float and supporting tissues and muscle have not been modeled. These simplifications are thought not to seriously affect the precision of the model, yet the number of shields in the model is several hundred fewer because of them.

The procedures in each step of the geometrical representation were identical. First, the geometric shapes forming the man were inferred by inspection of the illustrations the artist had made. Then, the numerical data required by MEVDP to define these geometries were read from the illustrations. This information was punched on data cards and also entered on Sectoring Code Worksheets, such as shown in Figure 13. These worksheets summarize all data requirements for MEVDP and were completed for the total of 3156 shields comprising the standing and seated versions of the model man.

02847

SECTORING CODE WORK SHEET

MDC - 06 - 8288 - 01 (3-69)

SHIELD SERIAL NUMBER			SHIELD TYPE	+	
			-		
MATERIAL CODE NUMBER			CHEMICAL COMPOSITION		
OCTANT NUMBER			DENSITY (GM/CM ³)		
CYL RADIUS (IN) OR CONE HALF ANGLE (RAD)					
	SPHERE (2)	1	X (IN)	Y (IN)	Z (IN)
	HEMISPHERE (2)				
	CYLINDER (2)	2			
	CONE (2)				
	TRUNCATED CONE (3) (TRUNCATION PT.)	3			
	SIMPLE ELLIPSOID (4)	4			
	TRUNCATED ELLIPSOID (5 OR 6) (TRUNCATION PT.)	5			
		6			
	HEXAHEDRON (8)	7			
		8			
REMARKS:					

Figure 13 Example of Sectoring Code Worksheet

The model was checked by inspection of the card decks, matching of the data on the worksheets to both the illustrations and to the punched cards, and with two computer graphics programs. A version of MEVDP used by NASA Manned Spacecraft Center, Houston with the UNIVAC 1108 digital computer, has a CRT plotting routine that allows visual checking of the shielding geometry. Unfortunately, this version is incompatible with the Martin Marietta CDC 6500 digital computer. Therefore, the model was first checked in-house using the Lockheed LSVDC-4 Geometry Test Program to eliminate the obvious errors. Figure 14 is a drawing of the eye made by this program. The final visual checking of the model was done at the NASA Manned Spacecraft Center with MEVDP. Figure 15 is also the eye, but drawn by means of the MEVDP. Due to the intensive in-house checking prior to the final checks at NASA, only a few corrections were necessary.


3. CHEMICAL COMPOSITION AND DENSITY

a. Collection of Information

The penetration of radiation incident on the body to a dose point within is affected by both the chemical composition and the density of all intervening materials. A precise radiation transport model of man should therefore account for variations of these properties in skin, muscle, bone, bone marrow, fat, and the various organ tissues. The medical consultants were assigned the task of collecting and organizing information on the density of human tissues, and their fractional composition by weight of the principal chemical elements. The consultants reviewed the documents suggested by the government furnished bibliography and Long⁽⁹⁾, Spector⁽¹⁰⁾, Altman⁽¹³⁾, and Glasser⁽¹⁴⁾, as well. Of these sources, Long was most complete.

Unfortunately all of the chemical composition data examined during the study was inadequate for radiation transport analysis. In every case, the portions by chemical element did not total 100%. The better information accounted for only 70 to 80% of the constituents. The difficulty is related to the manner in which the information is obtained and documented. Frequently, the data is for dry tissue with no indication of how much water might have been present. In other cases, water content is shown, but the remainder is described as ash of undefined composition. In addition, there is no indication of how the ash was obtained or what chemical processes might have occurred during reduction of the tissue to ash. As a consequence, the losses of carbon, oxygen, and nitrogen could not be established.

Best Available Copy



Symbol Table	Material No.	Density (gm/cm ³)	Volume	Name
A	3	1.058	7	Aft Sclera
.	3	1.058	3	Aft Vitreous Humor
C	3	1.058	8	Forward Sclera
2	3	1.058	4	Forward Vitreous Humor
E	3	1.058	6	Cornea
+	3	1.058	2	Aft Lens
G	3	1.058	1	Forward Lens
H	3	1.058	5	Forward Aqueous Humor

Figure 14 Lockheed LSVDC-4 Computer Drawing of the Eye




Figure 15 MEVDP Computer Drawing of the Eye

Because of these and other inadequacies in the chemical composition data, it was necessary to use approximations for the composition and density of organ and skeleton tissues. However, the geometrical models are complete. Improved data for chemical composition and density may readily be substituted in the future.

b. Organ Tissue

The medical consultants have formulated the radiation transport properties of a typical soft organ from the information gathered during the study. The typical density is that of blood, 1.058 gm/cm^3 . The chemical composition is as follows:

Hydrogen	0.0980	Phosphorous	0.0030
Carbon	0.1450	Sulfur	0.0018
Nitrogen	0.0380	Potassium	0.0026
Oxygen	0.7070	Calcium	0.0009
Sodium	0.0015	Chlorine	<u>0.0020</u>
Magnesium	0.0002	Total	1.0000

These properties are used in all organs of this model.

e. Skeleton

Red blood cells are produced in the red marrow of the skeleton. Radiation reaching the blood formation centers could disrupt this production. Accordingly, the medical consultants have identified the distribution of red marrow in the human skeleton. This information is presented in Table II. The composition of bone marrow is similar to fat.

In order to plan the geometrical representation of the blood forming organs in the model, several of the larger human bones shown in Figure 5 were sawed into longitudinal and transverse sections. The artist illustrated these sections as shown by Figure 16. It is observed that the human bone is a very efficient shell structure reinforced internally with spongy material. As a consequence, the hard, dense material is concentrated in a very thin layer on the outside of the bone and the bulk of the interior is marrow. Description of the bone geometry separately from the marrow geometry would have added several hundred shields to an already large model. It was therefore decided that the radiation transport properties of the skeleton would be simulated adequately by combining the compositions and densities of bone and bone marrow, thus making a simpler geometric representation.

Table II. Distribution of Marrow in the Adult Human Skeleton

A. Distribution of Total Marrow, Red and Yellow, in Man.
Total Marrow is 1600 to 3700 grams (3.53 to 8.15 lb),
or 3.4 to 5.9% Body Weight.

Region/bones	Percent of Total	Subtotal	Total
Upper Limbs:			100.00
Humeri	5.98		
Ulnae	1.38		
Radii	1.34		
Wrists and hands	2.74	11.44	
Lower Limbs:			
Femorae	17.07		
Tibiae	10.93		
Fibulae	1.54		
Patellae	0.82		
Ankles and feet	8.43	38.79	
Ribs and Trunk:			
1-4 ribs	2.08		
5-8 ribs	3.36		
9-12 ribs	1.90		
Scapulae	2.38		
Clavicles	0.76		
Sternum	1.38		
Pelvis	16.29	28.15	
Spinal Column			
Cervical vertebrae	1.78		
Dorsal vertebrae	7.29		
Lumbar vertebrae	5.61	14.68	
Skull			
Cranium	6.34		
Mandible	0.60	6.94	

B. Distribution of Red Marrow (Blood Cell Producing).
Red Marrow is 50% of Total in a 40 Year Old Male.

Bone	Percent of red marrow	Average weight (gm)	Total weight (gm)
Skull - cranium and mandible	13.1	136.6	1045.7
Humeri, scapulae, clavicles	8.3	86.7	
Sternum	2.2	23.4	
Ribs	7.9	82.6	
Vertebrae	28.5	297.8	
Pelvis	40.0	418.6	




Figure 16 Sections of Human Bones

The properties of skeleton material were derived analytically using the following procedure. First, the geometrical model of the skeleton was developed by reference to the illustrations that had been prepared by the artist. The volume of this model was calculated next. Long⁽⁹⁾ and Morgan⁽¹⁵⁾ assign a total weight of 10 kilograms (22.046 lb) to the skeleton. Applying a calculated skeleton volume of 407.15 cu. in., the average density of the skeleton is 1.499 gm/cm³. The density of bone is 1.75 gm/cm³, that of marrow, 0.918 gm/cm³, according to Long⁽⁹⁾ and Spector⁽¹⁰⁾. Their distribution in the skeleton is given by Long⁽⁹⁾ as 70% and 30%, respectively. The composition of bone according to Berger⁽¹⁶⁾ is as follows:

<u>Chemical Element</u>	<u>Fraction by Weight</u>
Hydrogen	0.064
Carbon	0.278
Nitrogen	0.027
Oxygen	0.410
Magnesium	0.002
Phosphorous	0.070
Sulfur	0.002
Calcium	<u>0.147</u>
Total	1.000

The chemical composition of bone marrow according to Dr. Gatts, one of our medical consultants, is as follows:

<u>Chemical Element</u>	<u>Fraction by Weight</u>
Hydrogen	0.122
Carbon	0.761
Oxygen	<u>0.117</u>
Total	1.000

The calculated fractions by weight of bone and marrow in the skeleton were applied to these compositions to derive the following average composition of the skeleton;

<u>Chemical Element</u>	<u>Fraction by Weight</u>
Hydrogen	0.082
Carbon	0.423
Nitrogen	0.019
Oxygen	0.322
Magnesium	0.001
Phosphorous	0.049
Sulfur	0.001
Calcium	0.103
Total	<u>1.000</u>

SECTION III

DESCRIPTION OF THE MODEL

1. SHIELD IDENTIFICATION AND LOCATION

A 4-digit number system has been used to identify and locate all geometrical shapes employed in the model. The digits are allocated as follows:

- 1st and 2nd - body segment;
- 3rd - shield within the body segment;
- 4th - shield sequence within a composite shield.

If the shield is not a composite, the 4th digit is zero. Because of this rule, a composite may contain only 9 shields. Although a composite may contain more than one solid, if the solids do not overlap, it was convenient for the purposes of this study to allow only one solid shield in a composite. This simplified the weight analysis presented at the end of this section.

Groups of shield identification numbers have been assigned to the principal regions of the body. These assignments are shown in Figures 17 and 18 for the standing and seated positions, respectively. Within the body regions, the sequence is from back to front, right to left, and top to bottom. Also, major elements within the body region are sequenced in groups - muscle, skeleton, and organ. The distribution of shield identification numbers among body regions is summarized in Table III.

The locations of the composite shields of the model man both in the standing and seated positions are shown in Figures 19, 20, 21, and 22. The apportionment of muscle is shown on Figures 19 and 20; the composite shields of the skeleton are shown on Figures 21 and 22. The allocation of identification numbers to the individual organs is shown with the illustration of the organs in Appendix I - Illustrations.

Best Available Copy





Figure 17 Shield Identification Numbers Assigned to the Standing Man



Note: Segment numbering same as standing man except where noted.

Figure 13 Shield Identification Numbers Assigned to the Seated Man

Table III. Shield Identification Summary

Model Position	Body Region	Shield Identification Number Assignments			
		Entire Region	Muscle Tissue	Skeleton	Organs
Common to both standing & seated configurations	Torso	--	1011 to 2222	2721 to 3030	3150 to 3494
	Head	3711 to 5394	3711 to 4635	4641 to 5035	5041 to 5394
	Right Arm	--	5511 to 5526	5751 to 5780	--
	Left Arm	--	6011 to 6026	6251 to 6280	--
Unique to standing configuration	Genitals	0001 to 0084	0001 to 0084	--	(Incl in Torso)
	Torso	--	2231 to 2643	3041 to 3120	3511 to 3540
	Right Arm	--	5531 to 5740	5791 to 5944	--
	Left Arm	--	6031 to 6240	6291 to 6444	--
	Right Leg	7511 to 8027	7511 to 7748	7750 to 8027	--
Unique to seated configuration	Left Leg	8111 to 8627	8111 to 8348	8350 to 8627	--
	Genitals	--	--	--	(Incl in Torso)
	Torso	--	2651 to 2713	3131 to 3142	3551 to 3580
	Right Arm	6511 to 6884	6511 to 5730	5740 to 6884	--
	Left Arm	7011 to 7384	7011 to 7230	7240 to 7384	--
	Right Leg	8711 to 9170	8711 to 8938	8940 to 9170	--
	Left Leg	9311 to 9770	9311 to 9538	8540 to 9770	--

Best Available Copy

2. GEOMETRICAL SHAPES

The quantities of composite and individual shields employed in the Computerized Anatomical Model Man are summarized in Table IV. It is noted that there are 557 composite shields, representing 2518 individual geometrical shapes in the standing model and 504 composite shields representing 2271 individual geometrical shapes in the seated model. There are 336 composite shields and 1633 individual geometrical shapes common to both the standing and seated positions.

Of the seven geometries compatible with MEVDP, the ellipsoid is most useful for describing the human shape. The hexahedron was frequently used for creating cavities within other shapes or for truncating unwanted portions of the curved geometries. Of the other shapes, the truncated cone, the sphere, and the cylinder had varying, but considerably less, frequency of use. The hemisphere and the simple cone were never used in this model. The frequency of use of all shapes for the model man is summarized in Table V.

3. MATERIALS

Due to the difficulty experienced in gathering chemical composition data suitable for precise radiation transport calculations, the list of materials employed in the model is brief. Table VI shows the chemical compositions and densities assigned to the materials associated with this model. Of the ten materials shown, water and tissue, Morgan,⁽¹⁵⁾ were not actually employed in the model. The data for these two materials are presented for comparative purposes.

It is noted that all of the tissues listed in Table VI have very high hydrogen and oxygen contents. It is well known that the specific gravity of the entire human body is very nearly equal to that of water. Applying the techniques of Berger,⁽¹⁶⁾ it is seen in the following table that the principal radiation transport properties of water and all tissues except bone are similar.

<u>Material</u>	<u>Atomic weight/atomic number</u>	<u>Adjusted mean excitation energy (electron volts)</u>
Water	1.802	65.2
Tissue	1.904	65.7
Organ	1.825	66.7
Muscle	1.818	66.2
Bone	1.886	85.2
Bone Marrow	1.787	58.1
Skeleton	1.854	75.4

Table IV. Summary of Shields Employed in the Model Man

Body region	Composite shields	Individual geometrical shapes
Common to both standing and seated configurations:		
Head	153	772
Torso	171	803
Upper Limbs	<u>12</u>	<u>58</u>
Subtotal	336	1633
Unique to standing configuration:		
Genitals	9	27
Torso	50	284
Upper limbs	68	200
Lower limbs	<u>94</u>	<u>374</u>
Subtotal	221	885
Complete standing configuration	557	2518
Unique to seated configuration:		
Torso	12	62
Upper limbs	70	214
Lower limbs	<u>86</u>	<u>362</u>
Subtotal	168	638
Complete seated configuration	504	2271

Table V. Summary of Geometrical Shapes Employed in the Model Man

Body region	Hexahedron	Cylinder	Sphere	Truncated cone	Truncated ellipsoids		
					Not	Singly	Doubly
Common to both standing and seated configurations: Head Torso Upper Limbs Subtotal	308	1	20	17	26	246	154
	339	39	4	93	3	33	292
	<u>58</u>	<u>0</u>	<u>0</u>	<u>0</u>	<u>0</u>	<u>0</u>	<u>0</u>
	705	40	24	110	29	279	446
Unique to standing configuration: Genitals Torso Upper limbs Lower limbs Subtotal	7	0	0	0	7	4	9
	43	54	6	70	2	23	86
	144	0	0	4	0	18	34
	<u>306</u>	<u>0</u>	<u>0</u>	<u>12</u>	<u>12</u>	<u>18</u>	<u>26</u>
	500	54	6	86	21	63	155
Complete standing configuration	1205	94	30	196	50	342	601
Unique to seated configuration: Torso Upper limbs Lower limbs Subtotal	32	0	6	0	2	9	13
	142	0	0	4	0	36	32
	<u>278</u>	<u>0</u>	<u>0</u>	<u>8</u>	<u>28</u>	<u>18</u>	<u>30</u>
	452	0	6	12	30	63	75
Complete seated configuration	1157	40	30	122	59	342	521
Total utilization	1657	94	36	208	80	405	676

Table VI. Material Code Table

Chemical element	Fractional composition by weight									
	Code No.									
	1	2	3	4	5	6	7	8	9	10
	Name									
Void	Lung	Organ	Intestine	Muscle	Bone	Marrow (rat)	Skeleton	Tissue	Water	
Density (gm/cm ³)										
0.000	0.257	0.058	0.451	1.060	1.75	0.918	1.499	1.000	1.000	1.000
Hydrogen (H)	0.0986	0.0980	0.0980	0.1020	0.064	0.122	0.082	0.1030	0.1119	0.1119
Carbon (C)	0.150	0.1450	0.1450	0.1230	0.278	0.761	0.423	0.1660	---	---
Nitrogen (N)	0.0380	0.0380	0.0380	0.0350	0.027	---	0.019	0.0300	---	---
Oxygen (O)	0.7070	0.7070	0.7070	0.7290	0.410	0.117	0.322	0.6100	0.8881	0.8881
Sodium (Na)	0.0015	0.0015	0.0015	0.0018	---	---	---	0.0015	---	---
Magnesium (Mg)	0.0002	0.0002	0.0002	0.0002	0.002	---	0.001	0.0005	---	---
Phosphorus (P)	0.0030	0.0030	0.0030	0.0020	0.070	---	0.049	0.0100	---	---
Sulfur (S)	0.0018	0.0018	0.0018	0.0050	0.002	---	0.001	0.0025	---	---
Potassium (K)	0.0026	0.0026	0.0026	0.0030	---	---	---	0.0020	---	---
Calcium (Ca)	0.0009	0.0009	0.0009	0.0009	0.147	---	0.103	0.0015	---	---
Chlorine (Cl)	0.0020	0.0020	0.0020	---	---	---	---	0.0015	---	---
Reference		Caranna		Berger (16)	Berger (16)	Gutts		Morgan (15)		

Because the skeleton is only about 14.3% of the adult body weight, only small errors should result from approximating the body with Morgan's version of an all tissue man. However, when better chemical composition and density data become available, the model may easily be updated for more precise analyses.

4. WEIGHT

One of the objectives of this study was to develop a model of the radiation transport properties of man that would weigh within 10% of the 50th percentile Air Force man. Since each of the two model configurations, standing and seated, is comprised of over 500 composite shields, representing over 2200 interacting geometrical shapes, it was necessary to automate the weight calculation. This was done by modification of MEVDP in the following manner.

MEVDP in its usual configuration divides space into a selected number of solid angles originating at the dose point. Then, rays are generated from the origin along the central axes of the solid angles. Whenever a ray intercepts an individual or a composite shield, the length of its track through the shield is calculated. These lengths are summed along each ray in terms of an equivalent material to form the areal density function used for dose calculations. To calculate weight, the same basic equations were used with different logic. First, in the cases of solid shields not in composites, the volumes and weights were calculated exactly with the standard formulas for the geometrical shapes compatible with MEVDP. In the cases where the shield element was a composite, a mock dose point was located at the center of the only solid shield assigned to the composite according to the rules adopted for this study. Then, the MEVDP equations were used to establish solid angles and rays at the dose point and to calculate the ray's track through the solid as modified by the voids included in the composite.

Simple modifications to the MEVDP provided the data for the following equation:

$$\Delta V_n = 1/3 (r_{2n}^3 - r_{1n}^3) (\phi_{2n} - \phi_{1n}) [\cos \theta_{1n} - \cos \theta_{2n}]$$

where

ΔV_n is the incremental volume associated with ray "n"

r_{2n} and r_{1n} are the distances from the dose point to the outer and inner surfaces, respectively, of the solid surface, as modified by adjoining voids

ϕ_{2n} , ϕ_{1n} , θ_{1n} and θ_{2n} are the angular limits of the solid angle element associated with ray "n" (Reference 4)

The volume of each composite was obtained by summing the incremental volumes over all rays. The weight was then the product of this volume and the density assigned to the composite. The mock dose point was relocated for each new composite. The preceding equation is exact for spheres and hemispheres and for ellipsoids whose semi-axes are allowed in the limit to become equal. As would be expected, the equation loses accuracy for shapes that are pointed or have corners, such as cones, cylinders and hexahedrons. Therefore, a study was made of the accuracy of the volume integration as a function of the number of rays selected for each type of geometrical shape for simple composites of one solid and one or more voids. The errors with respect to known, exact volumes are shown in Figure 23. Since the objective of the weight analysis was to reproduce the weight of the Air Force man within 10%, an error within a simple composite of 1% or less was considered satisfactory. Figure 23 indicates that 512 rays will limit the error to 1% in most cases.

Finally, a study was made of the effect of number of rays on the total volume of a group of composites and the time required to perform the calculation with the CDC 6500 digital computer. This analysis was done with the brain, which comprises 17 composites including a total of 59 geometrical shapes, mostly truncated ellipsoids. The results are shown in Figure 24. It would be expected that as the number of rays is increased, the volume would become asymptotic. This was generally true except for the sudden jog between 435 and 512 rays which was attributed to the solid angle distribution assuming a more favorable orientation with respect to the axes of the geometrical shapes in this region. As the result of this analysis, all volume and weight reported in this document are based on 512 rays. This number results in a volume little different from that obtained with many more rays and costs a reasonable amount in computation time.

The weight of the 50th percentile Air Force man is 161.9 pounds. The weight of the standing model man is 155.6 pounds. The seated model weighs 150.7 pounds. The errors in these weights are 3.9% and 6.9%, relative to the weight of the Air Force man. The calculated weights of the model man are summarized in Table VII. It is noted that the technique used to formulate the average chemical composition of the skeleton has forced its weight to be correct. The weights of individual organs are compared to weights of organs adapted from Morgan⁽¹⁵⁾ and Sunderman⁽¹⁷⁾ in Table VIII.




Figure 23 Errors of the Volume Calculation




Figure 24 Time and Accuracy Analysis of the Brain Volume Calculation

Table VII. Summary of Model Man Weight

Body region	Tissue	Skeleton	Organ
Common to both standing and seated configurations:			
Head	4.5794	1.6986	2.6029
Torso	28.1042	11.4023	17.1606
Upper Limbs	<u>0.7331</u>	<u>0.7629</u>	<u>---</u>
Subtotal	33.4167	13.8638	19.7635
Unique to standing configuration:			
Genitals	0.2008	---	0.0832
Torso	17.6378	0.9590	1.5785
Upper limbs	15.8166	1.5300	---
Lower limbs	<u>44.9349</u>	<u>5.6899</u>	<u>---</u>
Subtotal	78.5901	8.1789	1.6617
Complete standing configuration:			
Total, each material	109.6839	22.0427	21.4252
Grand total	155.5530		
% error in grand total	3.92		
Unique to seated configuration:			
Genitals	---	---	0.0832
Torso	9.4900	0.2412	1.4915
Upper limbs	14.4615	1.5605	---
Lower limbs	<u>49.5862</u>	<u>6.6231</u>	<u>---</u>
Subtotal	73.5377	8.4248	1.5747
Complete seated configuration:			
Total, each material	104.6315	22.2886	21.3382
Grand total	150.6595		
% error in grand total	6.94		
Note: 50th percentile Air Force man weighs 161.9 lb.			

Best Available Copy

Table VIII. Comparison of Model and Actual Organ Weights.

Organs (weights in lb)	Model man (standing)	Morgan ⁽¹⁵⁾	Sunderman ⁽¹⁷⁾		
			Minimum	Maximum	Average
Eyes (both)	0.0834	0.0661			
Teeth	0.0123	0.0441			
Brain	2.5073	3.3069	2.4251	3.7479	3.0865
Spinal cord	0.2107	0.0661	---	---	0.0595
Thyroid	0.0279	0.0441	0.0661	0.1543	0.0882
Heart and adjoining vessels	3.3455	0.6614	0.5952	0.7937	0.6614
Lungs (both)	2.2046	2.2046	1.5102	2.3148	1.8188
Liver	2.9203	3.7479	3.3069	3.9683	3.6376
Spleen	0.2047	0.3307	---	---	0.3417
Kidneys and adrenal glands	1.1588	0.6614	0.5335	0.9964	0.7164
Bladder	0.4571	0.3307	---	---	---
Pancreas	0.2014	0.1543	0.1323	0.2976	0.2425
Stomach	1.1306	} 8.0138	---	---	---
Intestines	6.8775		---	---	---
Testicles (both)	0.0832	0.0882	0.0882	0.1190	0.1102
Total	21.4252	19.7203			
<u>Note:</u> Organs of the Model Man are assumed to be filled with blood, food, feces, or urine as appropriate.					

Best Available Copy

It is noted that the weights of the model organs are generally somewhat greater than those given in the reference. Part of this discrepancy is attributed to the modeling technique. The organs were assumed to entirely fill the cavities in the skull, rib cage, and abdomen. Actually, this is not true because the organs are cushioned by fluids and supported by various tissues and muscles. These details were not modeled in the interest of keeping the number of geometrical shapes used in the model to a reasonable number. Another possible source of discrepancy between the weights of the model organs and actual organs may be due to preparation of the actual organs. The references do not indicate whether blood and other fluids normally within the living organs were drained prior to weighing. It is suspected that unless the donors were frozen immediately after death, the organs were drained. Since the model assumes the entire volume of the organ to be occupied by tissue and fluids having a uniform density equal to that of blood, it would be expected that the model organs should be heavier than organs without the normal fluid content they had while living.

Best Available Copy

SECTION IV
MODEL DEMONSTRATION

1. DOSE POINTS

Compatibility of the Computerized Anatomical Model Man with MEVDP was demonstrated by operation of the two systems together on the CDC 6600 digital computer at the Air Force Weapons Laboratory. In preparation for this demonstration, the locations of numerous dose points were identified. These locations are given in Table IX. It is noted that except for the gonads and femur the dose point locations are the same in the standing and seated configurations.

2. SAMPLE PROBLEMS

Demonstration of the model at the Air Force Weapons Laboratory entailed solution of shielding thickness problems for six dose points chosen from Table IX. Both standing and seated configurations were used. The model was input to MEVDP from both punched cards and magnetic tape. The demonstration conditions were as follows:

<u>Problem no.</u>	<u>Dose point</u>	<u>Model configuration</u>	<u>Input source</u>	<u>No. of rays</u>	<u>Computer time (sec)</u>
1	Heart	Seated	Tape	512	420.813
2	Intestines	Seated	Tape	512	445.660
3	Hypothalamus	Seated	Cards	512	502.227
4	Heart	Standing	Tape	512	430.500
5	Intestines	Seated	Tape	200	211.876
6	Hypothalamus	Standing	Cards	512	615.913

A partial listing of the result of problem number 1 is presented in Appendix III - Listing of Sample Problem Results.

Best Available

Table IX. Dose Point Locations Within the Model Man

Dose point	Coordinates (in.)		
	X	Y	Z
Inner ear:			
Right, at drum	-0.03	2.04	5.00
Right, at cochlear nerve	-0.23	1.68	4.75
Hypothalamus at center of mass	0.90	0.00	4.10
Lungs at center of mass:			
Right	0.36	2.48	18.00
Left	0.36	-2.82	17.61
Heart at center of mass	1.71	0.14	17.60
Kidneys at center of mass:			
Right	-0.90	2.53	25.80
Left	-1.10	-2.53	24.65
Pancreas at center of mass	1.50	-0.81	24.45
Gonads at center of mass:			
Right testicle, standing	2.25	0.55	38.25
Left testicle, standing	2.25	-0.55	38.50
Right testicle, seated	4.74	0.55	36.84
Left testicle, seated	4.95	-0.55	36.97
Bone marrow channels:			
Sternum at center	3.26	0.00	15.62
Right femur at center, standing	1.60	4.33	43.38
Right femur at center, seated	9.13	4.33	33.80
Eyes:			
Right at center of lens	3.393	1.245	4.30
Right, retina at optic nerve	2.278	1.245	4.30
Intestines at center of mass	1.80	-0.20	28.95
Spleen at center of mass	-1.18	-3.37	23.4
Brain at center of mass	-0.30	0.00	3.43
<u>Note:</u> Ears and eyes are located symmetrically with respect to the XZ plane.			

Best Available Copy

SECTION V

RESULTS AND RECOMMENDATIONS

1. SUMMARY OF RESULTS

This study has produced a Computerized Anatomical Model Man in both standing and seated configurations. The model depicts a 50th percentile Air Force man and comprises over 2200 geometrical shapes representing his external conformation, skeleton, and major organs. The quantity of geometrical shapes used in this model compares to 968 shapes used in an existing model of the Apollo Command and Service Module and 1038 in a model of the Apollo Lunar Module. Despite the number of geometrical shapes employed in this model, it was necessary to make compromises to achieve a model man of reasonable size yet sufficient geometrical accuracy.

Due to inadequacies in the data available to this study, the chemical compositions and densities assigned to the parts of the model do not represent the radiation transport properties of man precisely. However, since the greatest part of living human tissue is similar to water in both composition and density, these inadequacies may not be significant. The model is so constructed that better information may easily be substituted.

The compatibility of the Computerized Anatomical Model Man with an existing radiation shielding program, MEVDP, has been demonstrated. Since this computer program is operational at the Air Force Weapons Laboratory, the NASA Manned Spacecraft Center, Houston, North American Rockwell Corporation, and other government and industrial centers as well, the model should have considerable utilization.

2. RECOMMENDATIONS

Studies should be made using the model in one or several fixed environments to determine the sensitivity of doses calculated at various locations to the chemical composition and density of muscle tissue, skeleton, and organs. These doses should also be compared to doses calculated at the same locations using a uniform tissue composition such as that suggested by Morgan.⁽¹⁵⁾ If it is discovered that important differences in the doses result, additional research into man's composition and density would be indicated to update this part of the model.

Best Available Copy

It is noted that the Computerized Anatomical Model Man is nude. Omitting clothing results in a conservative dose calculation. However, credit should be taken for a spacesuit in studies of extra-vehicular activity.

Some broadening of the geometrical capability of MEVDP would be desirable. If the cones, truncated cones, and cylinders had elliptical sections rather than circular sections they would be more useful. MEVDP uses only convex shapes, that is, all solid material is on the interior. Concave shapes, or the ability to use the exteriors of the convex shapes as voids, would also have been useful.

Best Available Copy

APPENDIX I

ILLUSTRATIONS

To facilitate the modeling of the 50th percentile Air Force man's exterior, skeleton, and organs, the artist prepared numerous sectional drawings of the entire man and views of individual organs and bones that are obscured in the complete drawings. These illustrations were used to infer the geometrical shapes that would best simulate the man.

The locations of the body sections are shown on Figures 3 and 25. The numerical scales on each drawing that follows locate the section in the main man coordinate system. Figures 26 through 31 show the location of the skeleton within the external conformation of the body. Views of the spinal column and pelvis are presented in Figures 32 and 33, respectively.

The remaining figures include front and right side views of the main organ systems -- nervous, circulatory, and gastrointestinal, views of individual organs, and sections of these organs. The locations of the organs are shown in Figures 10 and 11; the locations of organ sections are shown on the appropriate views. The composite identification numbers associated with these organs are also indicated as well as the shapes of the primary solid volumes of the components. The effects of voids that in many cases cause large changes in the final appearance of the shield are not shown. The location of the eye in the head is shown in Figure 34. The dimensions of the eye in the model are based on Gullstrand's schematic eye as cited by Southall⁽¹⁸⁾. All other organ dimensions are the result of scaling the anatomical models to the dimensions of the 50th percentile Air Force man. The central nervous system -- brain and spinal cord, is shown in Figure 35; the thyroid in Figure 36. The main circulatory system is shown in right side and front views in Figure 37. Horizontal and vertical sections of the heart and adjoining blood vessels are shown in Figure 38. Figure 39 presents the nasal and oral passages of the head, the esophagus and the trachea. The lungs and their sections are shown in Figures 40 and 41. These organs are followed by the liver and gall bladder, in Figures 46 and 47; and the bladder, Figures 48 and 49. The gastrointestinal tract is shown in Figure 50. Views and sections of the pancreas appear in Figures 51 and 52. Finally sections of the stomach, small and large intestines are presented in Figure 53.

Best Available Copy




Figure 25 Locations of Body Sections




Figure 26 (A) Vertical Section of head, Normal to X-Axis at $X = 2.7$ inches




Figure 27 (B) Vertical Section of Head, Normal to Y-Axis at eye Pupil $Y = 1.25$ inches




Figure 28 (C) Vertical Section of Head, Normal to Y-Axis at Center




Figure 29 Horizontal Sections of Head, Torso, Leg and Foot




Figure 29 (cont)




Figure 29 (cont)




Figure 29 (cont)




Figure 29 (cont)




Figure 29 (cont)




Figure 29 (cont)




Figure 29 (cont)




Figure 19 (cont)




Figure 25 (cont)




Figure 29 (cont)




Figure 29 (cont)




Figure 29 (cont)







Figure 29 (concl)



23) Horizontal, Z = 68.0 inches



24) Vertical, X = 40 inches



25) Vertical, X = 6.0 inches

Figure 30 Sections of Foot




Figure 31 Horizontal Sections of Arm and Genitals




Figure 31 (cont)




Figure 31 (cont)




Figure 31 (cont)





Figure 31 (cont)




Figure 31 (concl)




Figure 32 Spinal Column




Figure 33 Pelvic Girdle




Figure 34 Eye Location






Figure 35 Central Nervous System, Brain and Spinal Cord




b. Right Side View

Figure 35 (cont.)




a. Front View

Figure 36 Thyroid



b. Right Side View

Figure 36 (cont)



1) Horizontal Section, $Z = 11.5$ inches

Figure 36 (concl)





Figure 37 Main Circulatory System



b. Right Side View

Figure 37 (cont.)




Figure 38 Sections of the Heart and Blood Vessels




Figure 38 (cont)






Figure 38 (concl)




a. Vertical Section Normal to Y-Axis at the Center

Figure 39 Head with Nasal and Oral Passages, Esophagus, and Trachea




b. Vertical Section Normal to X-Axis at $X = 2.7$ inches

Figure 39 (concl)



a. Front View

Figure 40 Views of Lungs



b. Right Side View

Figure 40 (concl)




Figure 41 Horizontal Sections of the Lungs






Figure 41 (concl)



a. Front View

Figure 42 Views of Liver and Gall Bladder



b. Right Side View

Figure 42 (concl)




Figure 43 Sections of Liver and Gall Bladder







Figure 43 (concl)



a. Front View

Figure 44 Views of the Spleen



b. Right Side View
Figure 44 (concl)






Figure 45 Transverse Section of the Spleen, 1)



a. Front View

Figure 46 Views of the Kidney and Adrenal Glands



b. Right Side View

Figure 46 (concl)






Figure 47 Horizontal Section of the Kidneys, $Z = 26.0$ inches, 1)



a. Front View

Figure 48 Views of the Bladder



b. Right Side View
Figure 48 (concl)




Figure 49 Vertical Section of the Bladder, Normal to the X-Axis,
X = 0.3 inches, 1)






Figure 50: Views of the Gastrointestinal Tract




B. Right Side View

Figure 50 (concl)



a. Front View

Figure 51 Views of the Pancreas



b. Right Side View
Figure 51 (concl)




Figure 52 Sections of the Pancreas




Figure 53 Sections of the Stomach and Intestines




Figure 53 (cont)





Figure 53 (cont)






Figure 53 (concl)

APPENDIX II

LISTING OF CARD DECKS FOR THE MODEL

1. CARD FORMATS

The partial listing that follows is for the Computerized Anatomical Model Man only. None of the other input necessary for running MEVDP is shown.

It is noted that only two types of card formats are used. The first type contains a mixture of identification, material, and dimensional data. The second type contains only the XYZ locations of the points indicated in Figure 12, 2 points per card. Depending on the geometrical shape under consideration, up to 4 cards of the second type are required. A set of first and second type cards is used to describe each geometrical shape of the model.

The requirements for the first data card are given in Table X. The entries on this card include the following:

- 1) Shield Serial Number - The 4-digit shield identification system was explained in Section III, Description of the Model. The data is in integer form.
- 2) Shield Type - Each of the seven compatible geometrical shapes is identified as a solid by an odd integer, or as a void by an even integer, according to the tabulation.

<u>Type of Shield</u>	<u>Void</u>	<u>Solid</u>
Hexahedron	0	1
Cylinder	2	3
Sphere	4	5
Hemisphere	6	7
Cone	8	9
Truncated cone	10	11
Ellipsoid	12	13

The first shield of a composite is always a solid. In this model only one solid is used in a composite. The second and succeeding shields in the composite are always voids.

Best Available Copy

Table X. Data Requirements, First Card of Set

Columns	1	2 - 5	6, 7	8 - 10	11 - 20	21 - 30	31 - 35	36 - 40	76 - 79	80
	Blank	Shield serial no.	Shield type	Material code	Cylinder radius (in.) or cone half-angle (radians)	Density of material (gm/cm^3)	No. of coordinates for ellipsoids	No. of shields in composite	Shield serial no.	Card no.
		A	A	A	B C	B	A D	A E	A F	

A - Integer, right-adjusted, see Appendix II.

B - Left-adjusted with decimal, not exponential format.

C - Columns 11 through 20 are left blank for hexahedrons, spheres, hemispheres, and ellipsoids.

D - Blank if shield is not an ellipsoid; if the shield is an ellipsoid, see Appendix II.

E - Equal to one if shield is not part of a composite; if a composite, enter the total number on the first card of the first shield. Leave this column blank for the remaining shields.

F - This is for identification only. It is ignored during processing.

Best Available Copy

- 3) Material Code - The chemical composition of the material is defined by an integer of up to 3 digits. The code numbers for the Computerized Anatomical Model Man are given in Table VI.
- 4) Cylinder Radius or Cone Half Angle - These dimensions are shown in Figure 12. The data is entered in decimal, not exponential format.
- 5) Density of Material - The material densities are associated with the material code numbers of the model in Table VI. These data are entered in decimal format only.
- 6) Number of Coordinates for Ellipsoids - This entry is an integer, selected as appropriate from the following list:
 - 4 Nontruncated
 - +5 Single truncation with lower portion eliminated with respect to Z_E axis (See Table XI)
 - 5 Single truncation with upper portion eliminated with respect to $+Z_E$ axis (See Table XI)
 - 6 Double truncation.
- 7) Number of Shields in Composite - If the shield is not a composite, the entry is the integer 1; if the shield is a composite, the appropriate integer, 2 through 9, is entered on the first data card for the composite. There is no entry on the remaining card sets of the composite.
- 8) Shield Serial Number and Card Number - This information appears on every data card. It is for identification only and is ignored by the computer during processing of a problem.

The requirements for the second, and subsequent cards if needed, of a shield data set are shown in Table XI. The required number of cards of this type are summarized below:

<u>Geometrical Shape</u>	<u>Number of Type 2 Cards</u>
Hexahedron	4
Cylinder	1
Sphere	1
Hemisphere	1
Cone	1
Truncated cone	2
Ellipsoid	2 or 3

Best Available Copy


Table XI. Data Requirements, Second and Succeeding Cards of Set

Hexahedrons, Type 0 (Void), 1 (Solid)


8 Points Required, Ordered as Shown

Column	1-10	11-20	21-30	31-40	41-50	51-60	76-79	80
Card 2	X ₁	Y ₁	Z ₁	X ₂	Y ₂	Z ₂	Same as Card 1	2
Card 3	X ₃	Y ₃	Z ₃	X ₄	Y ₄	Z ₄		3
Card 4	X ₅	Y ₅	Z ₅	X ₆	Y ₆	Z ₆		4
Card 5	X ₇	Y ₇	Z ₇	X ₈	Y ₈	Z ₈		5


Left-adjusted, decimal format




Cylinder, Type 2 (void),
Type 3 (solid)



Sphere, Type 4 (void),
Type 5 (solid)



Hemisphere, Type 6 (void),
Type 7 (solid)




Cone, Type 8 (Void), Type 9 (Solid)

2 Points Required, Ordered as Shown

Column	1-10	11-20	21-30	31-40	41-50	51-60	76-79	80
Card 2	X ₁	Y ₁	Z ₁	X ₂	Y ₂	Z ₂	Same as Card 1	2


Left-adjusted, decimal format



Truncated Cone, Type 10 (Void), 11 (Solid)

3 Points Required, Ordered as Shown

Column	1-10	11-20	21-30	31-40	41-50	51-60	76-79	80
Card 2	X ₁	Y ₁	Z ₁	X ₂	Y ₂	Z ₂	Same as Card 1	2
Card 3	X ₃	Y ₃	Z ₃					3




Ellipsoid, Type 12 (Void), 13 (Solid)

4, 5, or 6 Points Required (See Appendix II)

Column	1-10	11-20	21-30	31-40	41-50	51-60	76-79	80
Card 2	X ₁	Y ₁	Z ₁	X ₂	Y ₂	Z ₂	Same as Card 1	2
Card 3	X ₃	Y ₃	Z ₃	X ₄	Y ₄	Z ₄		3
Card 4 (Sing. v Truncated)	X ₅ or X ₆	Y ₅ or Y ₆	Z ₅ or Z ₆					4
Card 5 (Doubly Truncated)	X ₅	Y ₅	Z ₅	X ₆	Y ₆	Z ₆		4

Left-adjusted, decimal format



Best Available Copy

2. CARD LISTING

The first page of a listing of the punched card deck that describes the Computerized Anatomical Model Man follows (Figure 54). The complete card listing of all shields requires 222 pages. The combined common, standing, and seated portions of the model are contained on 13,743 cards, or 7 boxes.

Best Available Copy

371113 5		1.0600000	5	3		
-3.62492	0.	2.48958	0.		2.83084	2.48958
0.	0.	0.	0.		0.	2.48958
0.	0.	1.32000				
3712 0 5		0.				
0.	-3.50000	9.00000	0.		3.50000	9.00000
0.	-3.50000	-1.00000	0.		3.50000	-1.00000
9.00000	3.50000	-1.00000	5.00000		-3.50000	-1.00000
5.00000	3.50000	9.00000	5.00000		-3.50000	9.00000
371312 5		0.				
-2.74809	0.	1.51296	0.		2.00783	1.51296
0.	0.	.35000	0.		0.	1.51296
0.	0.	1.32000				
372113 5		1.0600000	5	3		
3.09515	0.	1.40075	0.		-2.50316	1.40075
0.	0.	0.	0.		0.	1.40075
0.	0.	1.32000				
3722 0 5		0.				
-5.00000	-3.50000	9.00000	-5.00000		3.50000	9.00000
-5.00000	-3.50000	-1.00000	-5.00000		3.50000	-1.00000
0.	3.50000	-1.00000	0.		-3.50000	-1.00000
0.	3.50000	9.00000	0.		-3.50000	9.00000
372312 5		0.				
2.71763	0.	1.62180	0.		-2.03822	1.62180
0.	0.	.35000	0.		0.	1.62180
0.	0.	1.32000				
373113 5		1.0600000	6	3		
-3.87931	0.	3.31468	0.		2.96534	3.31468
0.	0.	-2.1387	0.		0.	3.31468
0.	0.	1.32000	0.		0.	2.70000
3732 0 5		0.				
0.	-3.50000	9.00000	0.		3.50000	9.00000
0.	-3.50000	-1.00000	0.		3.50000	-1.00000
9.00000	3.50000	-1.00000	5.00000		-3.50000	-1.00000
5.00000	3.50000	9.00000	5.00000		-3.50000	9.00000
373312 5		0.				
-3.55733	0.	3.65623	0.		2.59280	3.65623
0.	0.	.04984	0.		0.	3.65623
0.	0.	1.32000	0.		0.	2.70000
374113 5		1.0600000	6	3		
6.31270	0.	16.22460	0.		-4.77541	16.22460
0.	0.	-86765	0.		0.	16.22460
0.	0.	1.32000	0.		0.	2.70000
3742 0 5		0.				
-5.00000	-3.50000	9.00000	-5.00000		3.50000	9.00000
-5.00000	-3.50000	-1.00000	-5.00000		3.50000	-1.00000
0.	3.50000	-1.00000	0.		-3.50000	-1.00000
0.	3.50000	9.00000	0.		-3.50000	9.00000
374312 5		0.				
3.85004	0.	4.99025	0.		-2.80615	4.99025
0.	0.	-.05216	0.		0.	4.99025
0.	0.	1.32000	0.		0.	2.70000

37111
 37112
 37113
 37114
 37121
 37122
 37123
 37124
 37125
 37131
 37132
 37133
 37134
 37211
 37212
 37213
 37214
 37221
 37222
 37223
 37224
 37225
 37231
 37232
 37233
 37234
 37311
 37312
 37313
 37314
 37321
 37322
 37323
 37324
 37325
 37331
 37332
 37333
 37334
 37411
 37412
 37413
 37414
 37421
 37422
 37423
 37424
 37425
 37431
 37432
 37433
 37434

Figure 54 Portion of Card Deck Listing

APPENDIX III

LISTING OF SAMPLE PROBLEM RESULTS

1. DESCRIPTION OF PROBLEM

The demonstration of the model at the Air Force Weapons Laboratory entailed the solution of six sample problems. The results of problem number 1 are presented in this appendix. The conditions of this problem were as follows:

Dose Point - Heart

X = 1.71 in.

Y = 0.14

Z = 17.60

Model configuration - Seated

Input source - Magnetic tape

Number of rays - 512

Time required for
execution - 420.813 sec

2. PROBLEM LISTING

Since the complete printout of the sample problem required 305 pages, only typical pages are reproduced in this document.

The first pages of the problem printout are a listing of the geometrical data. These data are in 2 groups. In the usual MEVDP problem, the first group describes the spacecraft. In the case of the sample problem, this group is a listing of the computerized anatomical model man. Figures 55a and 55b are the first and last pages of this listing, respectively. It is noted that except for the headings, this listing repeats the card deck listing, shown earlier as Figure 54. The complete listing used 162 pages to reproduce the information contained on the 9920 cards that depict the seated configuration. The second group of geometrical data is usually a listing of a less complex model of an astronaut that is contained in MEVDP. As shown by Figure 55c, this feature of the program was not needed for the sample calculation.

Best Available

The first step of the problem execution entails checking the geometrical data and sorting the shields into octants relative to a coordinate system originating at the dose point. The result of this step is shown by Figure 55d which gives the location of the dose point; the total number of shields in the spacecraft, e.g., the computerized anatomical model man; the allocation of shields to octants; and the time required to accomplish transformation of the geometrical data from the main coordinate system to the detector coordinate system. Note that any shield intersecting one of the three principal planes of the detector coordinate system is assigned to octant 9.

The next pages of the printout show the orientation of rays originating at the detector location within a region of space also centered at the detector. Each ray is located by a pair of angles, THETA and PHI, relative to the detector coordinate system. The ranges of THETA and PHI used for the sample problem include all of the space surrounding the detector. However, the region of space may be restricted if desired. The printout includes the identification numbers of the 512 rays used; the angles THETA and PHI; and the direction cosines of the ray -- ALPHA, BETA, and GAMMA -- referred to the X, Y, and Z axes, respectively, of the detector coordinate system. This printout runs for 8½ pages. The first page is shown on Figure 55e, and the last page on Figure 55f.

The problem execution then proceeds to creation of the areal density function. This function describes the distribution of all materials and geometrical volumes comprising the shielding configuration in the equivalent total weight per unit area of a standard material (aluminum) intercepted by each ray. For heavy charged particles, it is assumed that the range-energy relationship is expressed in each material, including the standard, by the expression,

$$R = \delta E^\eta$$

The values of DELTA, δ , and ETA, η , used for solution of the sample problem are tabulated in the middle region of Figure 55f. It is noted that appropriate names were used, but that the range-energy coefficients are for aluminum in all cases. The time required to execute this part of the problem follows on the printout which concludes with the areal density computed for each ray. This printout begins on Figure 55f and ends on Figure 55g.

Best Available Copy

The next phase of the problem execution entails least-squares empirical fitting of the areal density distribution data. The results of this analysis begin on Figure 55g and end on Figure 55i. The maximum areal density to be included in this part of the analysis is designated XMAX -- 10.0 gm/cm^2 . All 97 values of the areal density less than or equal to XMAX are then listed in ascending order of thickness. The curve has been fit in 3 sections. The printouts at the bottom of Figure 55g and the top of Figure 55h show part of the analysis of the first section. The analyses of the second and third sections are shown on Figures 55h and 55i.

The next pages of the problem printout beginning on Figure 55j and ending on Figure 55k, show the output of the subroutine ORDER of MEVDP. Each of the 56 pages of this section shows the ray number, the identity of each of several path numbers associated with the ray, the distance from the origin at the detector to the outermost point of the path, the contribution of the particular path to the total areal density along the ray, and the material along the path.

The final pages of the sample problem show the preceding data reordered by ray in ascending order, and the paths ordered from outermost to that closest to the detector. The only external organs are the eyes. The remainder of the exterior of the model man is muscle tissue. Accordingly the first path for the vast majority of the rays is always muscle. Since the detector has been located within an organ (the heart) for the sample problem, the last path is always through organ material. The intervening paths along any ray depend on the ray's orientation, and include varying numbers of paths through muscle, skeleton, and organ tissues. The execution of the sample problem requires 73 pages.

RECORD NO.

CONTENTS

1	371113	5	1.0600000	5	3		
2	-3.62492	0.	2.48958	0.		2.43084	2.48958
3	0.	0.	0.	0.		0.	2.48958
4	0.	0.	1.32000				
5	3712 0	5	0.				
6	0.	-3.50000	9.00000	0.		3.50000	9.00000
7	0.	-3.50000	-1.00000	0.		3.50000	-1.00000
8	5.00000	3.50000	-1.00000	5.00000		-3.50000	-1.00000
9	5.00000	3.50000	9.00000	5.00000		-3.50000	9.00000
10	371312	5	0.	5			
11	-2.74809	0.	1.51296	0.		2.00783	1.51296
12	0.	0.	.35000	0.		0.	1.51296
13	0.	0.	1.32000				
14	372113	5	1.0600000	5	3		
15	3.09515	0.	1.40075	0.		-2.50316	1.40075
16	0.	0.	0.	0.		0.	1.40075
17	0.	0.	1.32000				
18	3722 0	5	0.				
19	-5.00000	-3.50000	9.00000	-5.00000		3.50000	9.00000
20	-5.00000	-3.50000	-1.00000	-5.00000		3.50000	-1.00000
21	0.	3.50000	-1.00000	0.		-3.50000	-1.00000
22	0.	3.50000	9.00000	0.		-3.50000	9.00000
23	372312	5	0.	5			
24	2.71763	0.	1.62180	0.		-2.03822	1.62180
25	0.	0.	.35000	0.		0.	1.62180
26	0.	0.	1.32000				
27	373113	5	1.0600000	6	3		
28	-3.87931	0.	3.31468	0.		2.96534	3.31468
29	0.	0.	-2.1387	0.		0.	3.31468
30	0.	0.	1.32000	0.		0.	2.70000
31	3732 0	5	0.				
32	0.	-3.50000	9.00000	0.		3.50000	9.00000
33	0.	-3.50000	-1.00000	0.		3.50000	-1.00000
34	5.00000	3.50000	-1.00000	5.00000		-3.50000	-1.00000
35	5.00000	3.50000	9.00000	5.00000		-3.50000	9.00000
36	373312	5	0.	6			
37	-3.55733	0.	3.65623	0.		2.59280	3.65623
38	0.	0.	.04984	0.		0.	3.65623
39	0.	0.	1.32000	0.		0.	2.70000
40	374113	5	1.0600000	6	3		
41	6.31270	0.	16.22460	0.		-4.77541	16.22460
42	0.	0.	-.86765	0.		0.	16.22460
43	0.	0.	1.32000	0.		0.	2.70000
44	3742 0	5	0.				
45	-5.00000	-3.50000	9.00000	-5.00000		3.50000	9.00000
46	-5.00000	-3.50000	-1.00000	-5.00000		3.50000	-1.00000
47	0.	3.50000	-1.00000	0.		-3.50000	-1.00000
48	0.	3.50000	9.00000	0.		-3.50000	9.00000
49	374312	5	0.	6			
50	3.85004	0.	4.99025	0.		-2.80615	4.99025
51	0.	0.	-.05216	0.		0.	4.99025
52	0.	0.	1.32000	0.		0.	2.70000
53	375113	5	1.0600000	6	3		
54	-3.95000	0.	4.10000	0.		3.02500	4.10000
55	0.	0.	-1.40228	0.		0.	4.10000
56	0.	0.	2.70000	0.		0.	4.10000

a. Listing of Computerized Anatomical Model Man

Figure 55 Listing of Sample Problem

9915	14.33000	-3.50000	54.67220	14.29000	-3.50000	54.69870
9916	9770 1 8		1.5070000	1		
9917	14.60000	-2.73000	53.11000	14.80000	-2.53000	52.40000
9918	15.24000	-2.67540	52.05000	14.53000	-2.56100	52.05000
9919	16.53000	-3.80000	52.05000	15.20000	-3.80000	52.05000
9920	16.80000	-3.88000	52.40000	14.60000	-3.88000	53.11000

b. Listing of Computerized Anatomical Model Man (concl)

Figure 55 (cont)

SIMULATED ASTRONAUT GEOMETRY

RECORD NO.	CONTENTS
1	NO ASTRONAUTS THIS RUN

c. Listing of Astronaut Geometry

Figure 55 (cont)

DETECTOR POINT COORDINATES

$1.71000000E+00$ $1.40000000E-01$ $1.76000000E+01$

NO. VOLUMES OF SPACECRAFT = 2271 NO. DESCRIBING ASTRONAUTS = 0

NO. SHIELDS IN OCTANT

58	1
50	2
53	3
31	4
54	5
192	6
42	7
192	8
1599	9

TRANSFORMATION TIME= .57 MIN

d. Summary of Transformations to Detector Point Coordinate System

Figure 55 (cont)

Best Available Copy

MODEL MAN SITTING

MACROSCOPIC SOLID ANGLE 1

PHI 0. 3.6000000E+02 AND THETA 0.

1.80000000E+02

RAY DIRECTION COSINES
SYSTEMATIC SELECTION FROM CENTER OF EQUAL SOLID ANGLES

	THETA (DEG)	PHI (DEG)	COS (ALPHA)	COS (BETA)	COS (GAMMA)
1	1.44775148E+01	5.62500000E+00	2.48796222E-01	2.45042487E-02	9.68245826E-01
2	1.44775148E+01	1.68750000E+01	2.39235123E-01	7.25711800E-02	9.68245826E-01
3	1.44775148E+01	2.81250000E+01	2.20480353E-01	1.17849202E-01	9.68245826E-01
4	1.44775148E+01	3.93750000E+01	1.93252647E-01	1.58598345E-01	9.68245826E-01
5	1.44775148E+01	5.06250000E+01	1.58598350E-01	1.93252642E-01	9.68245826E-01
6	1.44775148E+01	6.18750000E+01	1.17849204E-01	2.20480350E-01	9.68245826E-01
7	1.44775148E+01	7.31250000E+01	7.25711864E-02	2.39235121E-01	9.68245826E-01
8	1.44775148E+01	8.43750000E+01	2.45042493E-02	2.48796222E-01	9.68245826E-01
9	1.44775148E+01	9.56250000E+01	-2.45042482E-02	2.44796223E-01	9.68245826E-01
10	1.44775148E+01	1.06875000E+02	-7.25711736E-02	2.39235125E-01	9.68245826E-01
11	1.44775148E+01	1.18125000E+02	-1.17849196E-01	2.20480356E-01	9.68245826E-01
12	1.44775148E+01	1.29375000E+02	-1.58598336E-01	1.93252651E-01	9.68245826E-01
13	1.44775148E+01	1.40625000E+02	-1.93252634E-01	1.58598355E-01	9.68245826E-01
14	1.44775148E+01	1.51875000E+02	-2.20480347E-01	1.17849213E-01	9.68245826E-01
15	1.44775148E+01	1.63125000E+02	-2.39235118E-01	7.25711928E-02	9.68245826E-01
16	1.44775148E+01	1.74375000E+02	-2.48796221E-01	2.45043020E-02	9.68245826E-01
17	1.44775148E+01	1.85625000E+02	-2.48796224E-01	-2.45042753E-02	9.68245826E-01
18	1.44775148E+01	1.96875000E+02	-2.39235127E-01	-7.25711671E-02	9.68245826E-01
19	1.44775148E+01	2.08125000E+02	-2.20480354E-01	-1.17849190E-01	9.68245826E-01
20	1.44775148E+01	2.19375000E+02	-1.93252655E-01	-1.58598334E-01	9.68245826E-01
21	1.44775148E+01	2.30625000E+02	-1.58598342E-01	-1.93252634E-01	9.68245826E-01
22	1.44775148E+01	2.41875000E+02	-1.17849210E-01	-2.20480344E-01	9.68245826E-01
23	1.44775148E+01	2.53125000E+02	-7.25711992E-02	-2.39235118E-01	9.68245826E-01
24	1.44775148E+01	2.64375000E+02	-2.45043027E-02	-2.48796220E-01	9.68245826E-01
25	1.44775148E+01	2.75625000E+02	2.45042487E-02	-2.48796224E-01	9.68245826E-01
26	1.44775148E+01	2.86875000E+02	7.25711607E-02	-2.39235129E-01	9.68245826E-01
27	1.44775148E+01	2.98125000E+02	1.17849184E-01	-2.20480363E-01	9.68245826E-01
28	1.44775148E+01	3.09375000E+02	1.58598320E-01	-1.93252659E-01	9.68245826E-01
29	1.44775148E+01	3.20625000E+02	1.93252634E-01	-1.58598365E-01	9.68245826E-01
30	1.44775148E+01	3.31875000E+02	2.20480345E-01	-1.17849225E-01	9.68245826E-01
31	1.44775148E+01	3.43125000E+02	2.39235114E-01	-7.25712056E-02	9.68245826E-01
32	1.44775148E+01	3.54375000E+02	2.48796220E-01	-2.45043153E-02	9.68245826E-01
33	3.51823238E+01	5.62500000E+00	5.73405723E-01	5.64755331E-02	8.17322699E-01
34	3.51823238E+01	1.68750000E+01	5.51370061E-01	1.67256276E-01	8.17322699E-01
35	3.51823238E+01	2.81250000E+01	5.08145551E-01	2.71609455E-01	8.17322699E-01
36	3.51823238E+01	3.93750000E+01	4.45393310E-01	3.65524835E-01	8.17322699E-01
37	3.51823238E+01	5.06250000E+01	3.65524847E-01	4.45393301E-01	8.17322699E-01
38	3.51823238E+01	6.18750000E+01	2.71609464E-01	5.08145552E-01	8.17322699E-01
39	3.51823238E+01	7.31250000E+01	1.67256271E-01	5.51370056E-01	8.17322699E-01
40	3.51823238E+01	8.43750000E+01	5.64755485E-02	5.73405719E-01	8.17322699E-01
41	3.51823238E+01	9.56250000E+01	-5.64755475E-02	5.73405722E-01	8.17322699E-01
42	3.51823238E+01	1.06875000E+02	-1.67256262E-01	5.51370065E-01	8.17322699E-01
43	3.51823238E+01	1.18125000E+02	-2.71609441E-01	5.08145567E-01	8.17322699E-01
44	3.51823238E+01	1.29375000E+02	-3.65524843E-01	4.45393320E-01	8.17322699E-01
45	3.51823238E+01	1.40625000E+02	-4.45393291E-01	3.65524859E-01	8.17322699E-01
46	3.51823238E+01	1.51875000E+02	-5.08145545E-01	2.71609482E-01	8.17322699E-01
47	3.51823238E+01	1.63125000E+02	-5.51370052E-01	1.67256306E-01	8.17322699E-01
48	3.51823238E+01	1.74375000E+02	-5.73405717E-01	5.64755636E-02	8.17322699E-01

Ray Orientation Data

Figure 55 (cont)

Best Available Copy

483	1.65522487E+02	2.81250000E+01	2.20480368E-01	1.17849210E-01	-9.68245822E-01
484	1.65522487E+02	3.93750000E+01	1.93252660E-01	1.58598355E-01	-9.68245822E-01
485	1.65522487E+02	5.06250000E+01	1.58598361E-01	1.93252656E-01	-9.68245822E-01
486	1.65522487E+02	6.18750000E+01	1.17849214E-01	2.20480365E-01	-9.68245822E-01
487	1.65522487E+02	7.31250000E+01	7.25711913E-02	2.39235138E-01	-9.68245822E-01
488	1.65522487E+02	8.43750000E+01	2.45042970E-02	2.48796238E-01	-9.68245822E-01
489	1.65522487E+02	9.56250000E+01	-2.45042837E-02	2.48796240E-01	-9.68245822E-01
490	1.65522487E+02	1.06875000E+02	-7.25711785E-02	2.39235141E-01	-9.68245822E-01
491	1.65522487E+02	1.18125000E+02	-1.17849204E-01	2.20480371E-01	-9.68245822E-01
492	1.65522487E+02	1.29375000E+02	-1.58598350E-01	1.93252664E-01	-9.68245822E-01
493	1.65522487E+02	1.40625000E+02	-1.93252651E-01	1.58598366E-01	-9.68245822E-01
494	1.65522487E+02	1.51875000E+02	-2.20480365E-01	1.17849221E-01	-9.68245822E-01
495	1.65522487E+02	1.63125000E+02	-2.39235136E-01	7.25711977E-02	-9.68245822E-01
496	1.65522487E+02	1.74375000E+02	-2.48796239E-01	2.45043037E-02	-9.68245822E-01
497	1.65522487E+02	1.85625000E+02	-2.48796240E-01	-2.45042770E-02	-9.68245822E-01
498	1.65522487E+02	1.96875000E+02	-2.39235143E-01	-7.25711708E-02	-9.68245822E-01
499	1.65522487E+02	2.08125000E+02	-2.20480374E-01	-1.17849198E-01	-9.68245822E-01
500	1.65522487E+02	2.19375000E+02	-1.93252668E-01	-1.58598345E-01	-9.68245822E-01
501	1.65522487E+02	2.30625000E+02	-1.58598371E-01	-1.93252647E-01	-9.68245822E-01
502	1.65522487E+02	2.41875000E+02	-1.17849227E-01	-2.20480358E-01	-9.68245822E-01
503	1.65522487E+02	2.53125000E+02	-7.25712041E-02	-2.39235134E-01	-9.68245822E-01
504	1.65522487E+02	2.64375000E+02	-2.45043103E-02	-2.48796237E-01	-9.68245822E-01
505	1.65522487E+02	2.75625000E+02	-2.45042703E-02	-2.48796241E-01	-9.68245822E-01
506	1.65522487E+02	2.86875000E+02	7.25711654E-02	-2.39235145E-01	-9.68245822E-01
507	1.65522487E+02	2.98125000E+02	1.17849192E-01	-2.20480377E-01	-9.68245822E-01
508	1.65522487E+02	3.09375000E+02	1.58598340E-01	-1.93252673E-01	-9.68245822E-01
509	1.65522487E+02	3.20625000E+02	1.93252643E-01	-1.58598376E-01	-9.68245822E-01
510	1.65522487E+02	3.31875000E+02	2.20480355E-01	-1.17849233E-01	-9.68245822E-01
511	1.65522487E+02	3.43125000E+02	2.39235132E-01	-7.25712105E-02	-9.68245822E-01
512	1.65522487E+02	3.54375000E+02	2.48796237E-01	-2.45043170E-02	-9.68245822E-01

NO. SOLID ANGLES IN ELEMENT SUBTENDED SOLID ANGLE PER RAY
512 2.45436914E-02

DELTA STD = 3.03056000E-05	ETA STD = 1.75079000E-02	ALUMINUM
DELTA(1) = 3.03056000E-05	ETA(1) = 1.75079000E-02	ALUMINUM
DELTA(2) = 3.03056000E-05	ETA(2) = 1.75079000E-02	LUNG
DELTA(3) = 3.03056000E-05	ETA(3) = 1.75079000E-02	ORGAN
DELTA(4) = 3.03056000E-05	ETA(4) = 1.75079000E-02	INTESTINE
DELTA(5) = 3.03056000E-05	ETA(5) = 1.75079000E-02	MUSCLE
DELTA(6) = 3.03056000E-05	ETA(6) = 1.75079000E-02	BONE
DELTA(7) = 3.03056000E-05	ETA(7) = 1.75079000E-02	ALUMINUM
DELTA(8) = 3.03056000E-05	ETA(8) = 1.75079000E-02	SKELETON

TRACK TIME = 4.54 MIN

512 AREAL DENSITY FUNCTIONS (GM/SQ.CM.)

1	4.28923355E+01	4.75015642E+01	4.98693370E+01	5.29928812E+01	6.90817461E+01	6.13871895E+01
7	5.58550470E+01	5.52605168E+01	5.62755053E+01	6.01294309E+01	6.18105249E+01	6.26512805E+01
13	5.79251578E+01	5.82580969E+01	6.41689338E+01	7.06720974E+01	7.17758533E+01	6.92693622E+01
19	5.81049195E+01	5.75976724E+01	5.95140206E+01	6.00359839E+01	5.98163148E+01	5.47800374E+01
25	5.46516974E+01	5.57167594E+01	5.70788319E+01	6.95912762E+01	6.02417853E+01	5.02439335E+01
31	4.71331500E+01	4.06577650E+01	2.96201204E+01	5.09860077E+01	2.75711286E+01	1.80032197E+01
37	1.79167020E+01	1.93144091E+01	2.57078585E+01	2.88253525E+01	3.03413911E+01	2.88762937E+01

f. Ray Orientation Data (concl), Range-Energy Coefficients, and
Areal Density Function

Figure 55 (cont)

Best Available Copy

415	9.59370920E+00	9.13471142E+00	1.03207644E+01	1.04313685E+01	1.04721666E+01	1.10301670E+01
421	1.17407077E+01	1.24797314E+01	1.32925544E+01	1.54142467E+01	1.76690742E+01	1.80529112E+01
427	1.76497303E+01	1.6944380E+01	1.49023274E+01	1.31868971E+01	1.23193202E+01	1.43672297E+01
433	1.73727074E+01	1.47433254E+01	1.24345060E+01	1.38074026E+01	1.59214712E+01	1.69528654E+01
439	1.79019200E+01	1.75400140E+01	1.57445417E+01	1.29072974E+01	1.22100343E+01	1.19305397E+01
445	1.11403825E+01	1.0740054E+01	1.04949514E+01	1.03425470E+01	1.12995856E+01	1.12982000E+01
451	1.1245144E+01	1.11400777E+01	1.11042493E+01	1.15439370E+01	1.28110014E+01	1.45254341E+01
457	1.66739477E+01	1.75401697E+01	1.68371942E+01	1.51448001E+01	1.44212523E+01	1.50493862E+01
463	1.55887005E+01	1.91445647E+01	1.98541742E+01	1.79414654E+01	1.42387107E+01	1.40544341E+01
469	1.38582308E+01	1.40473688E+01	1.61152438E+01	1.55023465E+01	1.41310073E+01	1.27113714E+01
475	1.15084527E+01	1.08254051E+01	1.09978143E+01	1.11282422E+01	1.12210693E+01	1.12700145E+01
481	1.13304441E+01	1.15431293E+01	1.20437545E+01	1.27216770E+01	1.36204214E+01	1.47260645E+01
487	1.58797915E+01	1.70454354E+01	2.02444470E+01	2.14223444E+01	2.79941455E+01	4.01942241E+01
493	4.31274344E+01	4.82470825E+01	4.70807424E+01	6.03971417E+01	4.01723920E+01	5.74411100E+01
499	4.69132009E+01	4.57743317E+01	4.04471819E+01	3.88078735E+01	2.59042205E+01	1.94051564E+01
505	1.81149341E+01	1.47492264E+01	1.44350100E+01	1.30819545E+01	1.23244060E+01	1.17733645E+01
511	1.14245172E+01	1.21942091E+01				

XMAX = 1.0000000E+01 TAU = 8.0000000E+00 DELR = 1.0500000E-02

97 WEIGHTED VALUES OF THICKNESS

8.80813742E+00	8.80813766E+00	8.80813772E+00	8.80813820E+00	8.80813949E+00
8.80814241E+00	8.80814824E+00	8.80815766E+00	8.80817227E+00	8.80819372E+00
8.80822345E+00	8.80824474E+00	8.80831849E+00	8.80838823E+00	8.80847610E+00
8.80852828E+00	8.80871895E+00	8.80888054E+00	8.80907368E+00	8.80930224E+00
8.80957029E+00	8.80988216E+00	8.81024237E+00	8.81045567E+00	8.81112705E+00
8.81164171E+00	8.81224507E+00	8.81294278E+00	8.81370072E+00	8.81454497E+00
8.81548186E+00	8.81651793E+00	8.81765995E+00	8.81891493E+00	8.82029007E+00
8.82170242E+00	8.82343087E+00	8.82521211E+00	8.82714448E+00	8.82923695E+00
8.83140752E+00	8.83393523E+00	8.83655914E+00	8.83937863E+00	8.84240323E+00
8.84544277E+00	8.84910735E+00	8.85280733E+00	8.85675334E+00	8.86095631E+00
8.86542746E+00	8.87017834E+00	8.87522080E+00	8.88056708E+00	8.88622977E+00
8.89222144E+00	8.89855673E+00	8.90524831E+00	8.91231097E+00	8.91975941E+00
8.92749778E+00	8.93587746E+00	8.94458014E+00	8.95373501E+00	8.96336044E+00
8.97347729E+00	8.98410514E+00	8.99526644E+00	9.00698479E+00	9.01928532E+00
9.03210513E+00	9.04574352E+00	9.05996227E+00	9.07448813E+00	9.09055322E+00
9.10700571E+00	9.12429046E+00	9.14245908E+00	9.16157354E+00	9.18169856E+00
9.20291245E+00	9.22531497E+00	9.24499813E+00	9.27406436E+00	9.30071036E+00
9.32909710E+00	9.35945567E+00	9.39207814E+00	9.42734721E+00	9.46578187E+00
9.50811741E+00	9.55544033E+00	9.60941843E+00	9.67395914E+00	9.75440541E+00
9.89271199E+00	1.00000000E+01			

CURVE FIT OF SECTION 1

THICKNESS	DISTRIBUTION	CURVE FIT PT.
8.80813762E+00	1.95312500E-03	1.70739549E-03
8.80813766E+00	1.95312500E-03	1.70739756E-03
8.80813772E+00	1.95312500E-03	1.70740011E-03
8.80813820E+00	1.95312500E-03	1.70742218E-03
8.80813949E+00	1.95312500E-03	1.70748533E-03
8.80814241E+00	1.95312500E-03	1.70762348E-03
8.80814824E+00	1.95312500E-03	1.70788054E-03
8.80815766E+00	1.95312500E-03	1.70831064E-03
8.80817227E+00	1.95312500E-03	1.70897812E-03

Best Available Copy

9.04574352E+00	1.17187500E-02	1.25587717E-02
9.05996227E+00	1.36718750E-02	1.32081373E-02
9.07488613E+00	1.36718750E-02	1.38897044E-02
9.09055322E+00	1.36718750E-02	1.46052151E-02
9.10700571E+00	1.36718750E-02	1.53565942E-02
9.12429046E+00	1.56250000E-02	1.61459826E-02
9.14245998E+00	1.75781250E-02	1.69757783E-02
9.16157354E+00	1.75781250E-02	1.78486876E-02
9.18169856E+00	2.14843750E-02	1.87677900E-02
9.19874207E+00	2.21328584E-02	1.90894646E-02

2 COEFFICIENTS

-4.00557097E-01 4.56696420E-02

CURVE FIT OF SECTION 2

THICKNESS	DISTRIBUTION	CURVE FIT PT.
9.18874207E+00	2.21328584E-02	1.95434392E-02
9.20291245E+00	2.34375000E-02	2.06690913E-02
9.22530497E+00	2.34375000E-02	2.24478849E-02
9.24498132E+00	2.53906250E-02	2.43286624E-02
9.27406636E+00	2.53906250E-02	2.63213422E-02
9.30071036E+00	2.53906250E-02	2.84378608E-02
9.32909710E+00	2.73437500E-02	3.06928178E-02
9.35945567E+00	2.92968750E-02	3.31044110E-02
9.39207814E+00	3.51562500E-02	3.56958408E-02
9.42734721E+00	3.90625000E-02	3.84975090E-02
9.46578187E+00	4.10156250E-02	4.15506418E-02
9.50811761E+00	4.68750000E-02	4.49136653E-02
9.55546033E+00	4.88281250E-02	4.86744274E-02
9.58579265E+00	5.32036707E-02	5.10839351E-02

2 COEFFICIENTS

-7.10382412E-01 7.94369725E-02

CURVE FIT OF SECTION 3

THICKNESS	DISTRIBUTION	CURVE FIT PT.
9.58579265E+00	5.32036707E-02	5.40470543E-02
9.60961843E+00	5.66406250E-02	5.55866365E-02
9.67395918E+00	6.05468750E-02	5.97442281E-02
9.75640581E+00	6.44531250E-02	6.50717909E-02
9.89270199E+00	7.22656250E-02	7.38790215E-02
1.00000000E+01	8.20312500E-02	8.08124395E-02

2 COEFFICIENTS

h. Least Squares Analysis (cont)

Figure 55 (cont)

Best Available Copy

-5.65370807E-01

6.46183247E-02

GEOMDS TIME = .01 MIN

EXECUTION TIME FOR ESPOSE IS 4.57 MIN

i. Least Squares Analysis (concl)

Figure 55 (cont)

NO. PATHS IS 3455 OF TOTAL 3455

RAY NO. PATH NO. DISTANCE TO (CM.) PATH THROUGH (GM./SQ.CM.) MATERIAL NO.

495	1	4.34023617E+01	7.36637773E-01	5
496	1	4.40000322E+01	9.49056676E-01	5
497	1	4.41202044E+01	8.59951277E-01	5
498	1	4.37850844E+01	1.14020841E+00	5
499	1	4.29729645E+01	2.81475675E-01	5
499	1	4.11456456E+01	1.12189053E+00	5
494	1	4.21049712E+01	1.97819089E+00	5
495	2	4.27074244E+01	7.11862975E-01	5
498	2	4.27074244E+01	9.32972077E-02	5
499	2	4.27074204E+01	1.46565028E+00	5
500	1	4.14181335E+01	2.32281107E+00	5
501	1	3.93058113E+01	2.31666263E-01	5
492	1	3.71503444E+01	1.93985936E+00	5
493	2	3.90872593E+01	1.56783082E+00	5
501	2	3.90872543E+01	2.86603518E+00	5
502	1	3.64841138E+01	7.16547226E-01	5
492	2	3.54146300E+01	4.17105642E+00	5
493	3	3.27596649E+01	1.35670348E+00	5
494	2	3.19350197E+01	3.76669505E-01	5
500	2	3.21354976E+01	6.95176070E-01	5
501	3	3.37455340E+01	1.97781893E+00	5
502	2	3.58081259E+01	2.71073002E+00	5
502	3	3.32508334E+01	2.43357290E+00	5
512	1	3.13719238E+01	8.40266393E-01	5
512	2	3.04958289E+01	7.82989332E-02	5
492	3	3.14796711E+01	4.33906324E+00	5
493	4	3.14796711E+01	4.36570572E+00	5
494	3	3.14796711E+01	4.36570572E+00	5
495	3	3.09618862E+01	3.81685379E+00	5
496	2	3.06785028E+01	3.51644732E+00	5
497	2	3.07174059E+01	3.19306216E+00	5
498	3	3.07739186E+01	3.61760806E+00	5
499	3	3.13428688E+01	4.22069524E+00	5
500	3	3.14796711E+01	4.36570572E+00	5
501	4	3.14796711E+01	4.33906703E+00	5
502	4	3.09550099E+01	6.51859481E-01	5
489	1	3.25189732E+01	3.27458137E-02	5
490	1	3.28917665E+01	3.03169544E-02	5
504	1	3.25189734E+01	3.27458404E-02	5
489	2	3.25189732E+01	3.27458137E-02	5
503	1	3.28917647E+01	3.03169369E-02	5
504	2	3.25189734E+01	3.27458404E-02	5
493	5	2.78070428E+01	4.72719728E-01	5
494	4	2.78070428E+01	4.72719728E-01	5
495	4	2.78070428E+01	4.72719728E-01	5
496	3	2.78070428E+01	4.72719728E-01	5
497	3	2.78070428E+01	4.72719728E-01	5
498	4	2.78070428E+01	4.72719728E-01	5
499	4	2.78070428E+01	4.72719728E-01	5
500	4	2.78070428E+01	4.72719728E-01	5
501	5	2.78070428E+01	1.85863105E-01	5
493	6	2.78070428E+01	4.72719728E-01	5
494	5	2.78070428E+01	4.72719728E-01	5
495	5	2.78070428E+01	4.72719728E-01	5
499	5	2.78070428E+01	4.72719728E-01	5
500	5	2.78070428E+01	4.72719728E-01	5

j. ORDER Printout

Figure 55 (cont)

33	7	5.32528053E+01	2.02774726E+00	5
33	8	5.43098940E+01	7.86591008E-01	5
34	9	4.73870601E+01	2.54330708E+00	5
35	6	5.40838925E+01	9.64751144E+00	5
33	9	5.43866332E+01	8.13414053E-02	5
34	10	5.89081001E+01	6.60469836E-02	5
33	10	5.95127186E+01	3.17007719E+00	5
34	11	5.95127186E+01	6.40895507E-01	5
33	11	6.64736871E+01	7.37862663E+00	5
34	12	6.31078711E+01	3.81086171E+00	5
34	13	9.74834672E+01	1.78943300E+00	5
34	14	4.95902921E+01	1.00310115E-01	5
33	12	5.35678290E+01	3.33925160E-01	5
34	15	5.20098179E+01	4.90011375E+00	5
34	16	5.89457917E+01	6.07224392E+00	5
34	17	6.61899246E+01	3.26694092E+00	5
34	18	6.87451141E+01	4.04343594E-01	5
34	19	7.09044144E+01	2.28886043E+00	5
10	17	4.48585311E+01	3.16265761E+00	8
34	20	5.20098179E+01	3.64622536E+00	8
34	21	5.31172597E+01	1.66891475E+00	8
34	22	6.83636579E+01	3.27581009E+00	8
22	16	5.24639377E+01	1.35215079E+00	5
23	17	5.22699173E+01	1.70059076E+00	5
24	17	5.22073820E+01	2.57740935E+00	5
25	14	5.23422271E+01	4.53088866E+00	5
26	13	5.26703053E+01	8.06565261E+00	5
27	12	5.27809150E+01	1.26023310E+01	5
28	13	5.27809150E+01	1.73021648E+01	5
29	11	5.27809150E+01	1.67604108E+01	5
30	6	5.27809150E+01	1.58403985E+01	5
31	7	5.26073876E+01	1.41274841E+01	5
32	7	4.99850740E+01	8.44845406E+00	5
62	7	4.95983390E+01	5.33489311E+00	5
62	8	5.51189766E+01	9.28007920E-01	5
63	8	4.74921122E+01	2.37024437E+00	5
63	9	5.90612219E+01	6.46942348E-02	5
63	10	5.95127186E+01	4.78586582E-01	5
64	9	5.95127186E+01	1.42759062E+00	5
63	11	6.30574311E+01	3.75739534E+00	5
64	10	6.41564027E+01	4.9220521E+00	5
63	12	9.74859599E+01	1.13482215E+00	5
62	9	5.42434974E+01	4.92384793E+00	5
63	13	5.21028574E+01	4.88738994E+00	5
63	14	5.90001895E+01	6.23590583E+00	5
63	15	6.83294182E+01	5.58830631E+00	5
63	16	6.87909808E+01	4.52959873E-01	5
63	17	7.19401301E+01	3.33809828E+00	5
23	18	4.49585311E+01	1.39536863E+00	8
63	18	5.31172594E+01	1.52870392E+00	8
63	19	6.83636601E+01	5.16025478E-02	8

AREAL DENSITIES, SORTED ACCORDING TO RAY NO. AND DISTANCE

RAY NO.	PATH NO.	DISTANCE TO (CM.)	PATH THROUGH (GM./SQ.CM.)	MAT. NO.	MAT. NAME
---------	----------	-------------------	---------------------------	----------	-----------

1	1	5.10132767E+01	1.08547788E+01	5	MUSCLE
---	---	----------------	----------------	---	--------

k. ORDER Printout (concl) and Sorted Areal Densities

Figure 55 (cont)

Best Available Copy

	2	3.02599386E+01	3.15621051E+00	5	MUSCLE
	3	2.72823815E+01	5.56140853E+00	5	MUSCLE
	4	2.20357697E+01	2.78070427E+00	5	MUSCLE
	5	1.94124638E+01	4.48782908E-01	5	MUSCLE
	6	1.89890836E+01	1.20416233E+01	3	ORGAN
	7	7.60758715E+00	8.04882720E+00	3	ORGAN
2	1	5.27809150E+01	1.50069546E+01	5	MUSCLE
	2	3.06916240E+01	3.61379702E+00	5	MUSCLE
	3	2.72823815E+01	5.56140853E+00	5	MUSCLE
	4	2.20357697E+01	2.78070427E+00	5	MUSCLE
	5	1.94124638E+01	1.65960332E-01	5	MUSCLE
	6	1.92558974E+01	1.23239122E+01	3	ORGAN
	7	7.60758715E+00	8.04882720E+00	3	ORGAN
3	1	5.27809150E+01	1.63028718E+01	5	MUSCLE
	2	3.17031039E+01	4.68596579E+00	5	MUSCLE
	3	2.72823815E+01	5.56140853E+00	5	MUSCLE
	4	2.20357697E+01	2.78070427E+00	5	MUSCLE
	5	1.94124638E+01	1.24895594E+01	3	ORGAN
	6	7.60758715E+00	8.04882720E+00	3	ORGAN
4	1	5.27809150E+01	1.70826024E+01	5	MUSCLE
	2	3.28060444E+01	2.93674160E-01	5	MUSCLE
	3	3.28060444E+01	2.93674160E-01	5	MUSCLE
	4	3.28060444E+01	2.93674160E-01	5	MUSCLE
	5	3.28060444E+01	2.93674160E-01	5	MUSCLE
	6	3.28060444E+01	2.93674160E-01	5	MUSCLE
	7	3.25289933E+01	5.56140853E+00	5	MUSCLE
	8	2.72823815E+01	5.56140853E+00	5	MUSCLE
	9	2.20357697E+01	2.78070427E+00	5	MUSCLE
	10	1.94124638E+01	1.24895594E+01	3	ORGAN
	11	7.60758715E+00	8.04882720E+00	3	ORGAN
5	1	5.27809150E+01	1.75256057E+01	5	MUSCLE
	2	3.55883052E+01	1.94481621E+00	4	INTESTINE
	3	3.53911473E+01	3.03388324E+00	5	MUSCLE
	4	3.53911473E+01	3.03388324E+00	5	MUSCLE
	5	3.53911473E+01	3.03388324E+00	5	MUSCLE
	6	3.53911473E+01	3.03388324E+00	5	MUSCLE
	7	3.53911473E+01	3.03388324E+00	5	MUSCLE
	8	3.25289933E+01	5.56140853E+00	5	MUSCLE
	9	2.72823815E+01	5.56140853E+00	5	MUSCLE
	10	2.20357697E+01	2.78070427E+00	5	MUSCLE
	11	1.94124638E+01	1.24895594E+01	3	ORGAN
	12	7.60758715E+00	8.04882720E+00	3	ORGAN
6	1	5.27809150E+01	1.40214729E+01	5	MUSCLE
	2	3.95531103E+01	4.03220372E-01	4	INTESTINE
	3	3.73850780E+01	3.09646759E+00	4	INTESTINE
	4	3.64223142E+01	3.97419050E-01	5	MUSCLE
	5	3.60473906E+01	1.14585555E-01	5	MUSCLE
	6	3.59392910E+01	3.61491555E+00	5	MUSCLE
	7	3.59392910E+01	3.61491555E+00	5	MUSCLE
	8	3.59392910E+01	3.61491555E+00	5	MUSCLE
	9	3.59392910E+01	3.61491555E+00	5	MUSCLE
	10	3.59392910E+01	3.61491555E+00	5	MUSCLE

1. Sorted Areal Densities (cont)

Figure 55 (cont)

	8	4.98428126E+00	5.27336957E+00	3	ORGAN
507	1	1.44589556E+01	2.81190607E-01	5	MUSCLE
	2	1.41936909E+01	3.62788882E+00	5	MUSCLE
	3	1.07711543E+01	1.65314172E+00	8	SKELETON
	4	9.67417903E+00	4.23574365E-01	2	LUNG
	5	7.60796261E+00	2.77555488E+00	3	ORGAN
	6	4.98428126E+00	5.27336957E+00	3	ORGAN
508	1	1.37250028E+01	2.92128452E-01	5	MUSCLE
	2	1.34494099E+01	3.30057857E+00	5	MUSCLE
	3	1.03356466E+01	1.68292806E+00	8	SKELETON
	4	9.21891599E+00	4.67989705E-01	2	LUNG
	5	6.93603939E+00	2.06496010E+00	3	ORGAN
	6	4.98428126E+00	5.27336957E+00	3	ORGAN
509	1	1.31235546E+01	3.03949244E-01	5	MUSCLE
	2	1.28368100E+01	3.03619459E+00	5	MUSCLE
	3	9.97247553E+00	1.68943738E+00	8	SKELETON
	4	8.85141556E+00	4.97424906E-01	2	LUNG
	5	6.42495260E+00	1.52423028E+00	3	ORGAN
	6	4.98428126E+00	5.27336957E+00	3	ORGAN
510	1	1.26672228E+01	3.13146662E-01	5	MUSCLE
	2	1.23718015E+01	2.84205365E+00	5	MUSCLE
	3	9.69061877E+00	1.68438920E+00	8	SKELETON
	4	8.57290462E+00	5.13428223E-01	2	LUNG
	5	6.06838070E+00	1.14697721E+00	3	ORGAN
	6	4.98428126E+00	5.27336957E+00	3	ORGAN
511	1	1.23596979E+01	3.19328188E-01	5	MUSCLE
	2	1.20593483E+01	2.71829590E+00	5	MUSCLE
	3	9.49495819E+00	1.67654090E+00	8	SKELETON
	4	8.38245593E+00	5.17976168E-01	2	LUNG
	5	5.95574292E+00	9.22006436E-01	3	ORGAN
	6	4.98428126E+00	5.27336957E+00	3	ORGAN
512	1	3.13719238E+01	8.40266393E-01	5	MUSCLE
	2	3.08958289E+01	7.82949332E-02	5	MUSCLE
	3	1.22007493E+01	3.19089051E-01	5	MUSCLE
	4	1.18997219E+01	2.56272169E+00	5	MUSCLE
	5	9.38772027E+00	1.67158670E+00	8	SKELETON
	6	8.27850548E+00	5.12478954E-01	2	LUNG
	7	5.77860814E+00	8.40397841E-01	3	ORGAN
	8	4.98428126E+00	5.27336957E+00	3	ORGAN

m. Sorted Areal Densities (concl)

Best Available Copy

Figure 55 (concl)

REFERENCES

1. C. S. Warren, J. C. Lill, R. G. Richmond, and W. G. Davis: "Radiation Dosimetry on the Gemini and Apollo Missions." Journal of Spacecraft and Rockets, Volume 5, No. 2, February 1968, p 207-210.
2. C. A. Berry: Radiation Dose Levels for Apollo Crew Members, Apollo Applications Program. U.S. Government Memorandum, 10 February 1967.
3. W. Helvey, C. Martell, J. Peters, G. Rosenthal, F. Benjamin, and G. Albright: Biomedical and Human Factor Requirements for a Manned Earth Orbiting Station. RAC 1781A (ARD-FR-63-144A). Republic Aviation Corporation, Farmingdale, Long Island, New York, Revised 3 January 1964.
4. B. Liley and S. C. Hamilton, Modified Elemental Dose Program (EVDP). AFWL-TR-69-68. North American Rockwell Corporation, Los Angeles, California, August 1969.
5. H. T. E. Hertzberg, G. J. Daniels, and E. Churchill: Anthropometry of Flying Personnel - 1950. WADC-TR-52-321 (AD 47953), Wright Air Development Center, Dayton, Ohio, September 1954.
6. D. J. Morton: Manual of Human Cross Section Anatomy. Williams and Wilkins Company, Baltimore, Maryland, 1944.
7. A. C. Eycleshymer and D. M. Shoemaker: A Cross Section Anatomy. D. Appleton and Company, New York, New York, 1923.
8. J. C. B. Grant: An Atlas of Anatomy (Volumes I and II), Williams and Wilkins Company, Baltimore, Maryland, 1943.
9. C. Long, Editor: Biochemists' Handbook. D. Van Nostrand Company, Inc., Princeton, New Jersey. 1968.
10. W. S. Spector, Editor: Handbook of Biological Data. W. B. Saunders Company, Philadelphia, Pennsylvania, 1956.
11. F. Frohse, M. Brodel, and L. Schlossberg: Atlas of Human Anatomy. Barnes and Nobel, Inc., New York, New York, 1967.
12. K. F. Armstrong and D. J. Kidd: Atlas of Male Anatomy. Bailliere, Tindall and Cassell, London, England, 1967.

13. P. I. Altman and D. S. Dittmer, Editors: Biology Data Book. Federated American Society of Experimental Biologists, Washington, D.C. 1964.
14. O. Glasser: Medical Physics. The Year Book Publishers, Inc., 1947.
15. K. Z. Morgan, Editor: "Report of ICRP Committee II on Permissible Dose for Internal Radiation (1959)", Health Physics, Volume 3. Pergamon Press, Inc., New York, New York, June 1960.
16. M. J. Berger and S. M. Seltzer: Tables of Energy Losses and Ranges of Electrons and Positrons. NASA SP-3012, National Bureau of Standards, Washington, D.C., 1964.
17. W. F. Sunderman and F. Barner: Normal Values in Clinical Medicine. W. B. Saunders Company, Philadelphia, Pennsylvania, 1949.
18. Southall: Physiological Optics. Dover Publishing Company, New York, New York, 1961.

BIBLIOGRAPHY

- Anson, B. J.: Morris' Human Anatomy; (12th Ed). McGraw Hill Book Company, New York, New York, 1966.
- Appleton, A. B.: W. J. Hamilton, and G. Simon: Surface and Radiological Anatomy; Williams and Wilkins Company, Baltimore, Maryland, 1946.
- Brozek, J.: Human Body Composition; Pergamon Press, Inc., Oxford, England, 1965
- Churchill, E., and G. S. Daniels: Nomographs of Head Measurements. WADC-TR-53-14 (AD-16748), Wright Air Development Center, Dayton, Ohio, May 1953.
- Diem, K.: Documenta Geigy - Scientific Tables; (6th Ed), Geigy Pharmaceuticals, Ardsley, New York.
- Eycleshymer, A. C., and D. M. Shoemaker: A Cross-Section Anatomy; D. Appleton and Company, New York, New York, 1923.
- Hanavan, E. P.: A Mathematical Model of the Human Body: AMRL-TP-64-102 (AD-608463), Aerospace Medical Research Laboratories, Dayton, Ohio, October 1964.
- Hansen, R., D. Y. Cornog, and H. L. Zoh: Annotated Bibliography of Applied Physical Anthropology in Human Engineering: WADC-TR-56-30 (AD-155622), Wright Air Development Center, Dayton, Ohio, May 1958.
- Hertzberg, H. T. E., G. S. Daniels and E. Churchill: Anthropometry of Flying Personnel - 1950. WADC-TR-52-321 (AD-47953), Wright Air Development Center, Dayton, Ohio, September 1954.
- Leffler, J. M.: Shielded Primary Proton Spectra and Dose Formulas; Inter-Office letter, North American Rockwell Corporation, Los Angeles, Calif., 20 August 1962.
- Liley, B., S. C. Hamilton, and J. D. Fletcher: Numerical Model Representing the Geometrical Shielding of the Lunar Module; SD 68-798, Space Division North American Rockwell Corporation, Los Angeles, California, Sept. 1968.

Moore, F. D., et al: The Body Cell Mass; W. B. Saunders Company, Philadelphia, Pennsylvania.

Morgan, K. Z., Editor: "Report of ICRP Committee II on Permissible Dose for Internal Radiation (1959)", Health Physics, Volume 3, Pergamon Press, Inc., New York, New York, June 1960.

Morton, D. J.: Manual of Human Cross Section Anatomy; Williams and Wilkins Company, Baltimore, Maryland, 1944.

McConville, J. T., M. Alexander, and S. M. Velsey: Anthropometric Data in Three Dimensional Form: Development and Fabrication of USAF Height - Weight - Manikins: AMRL-TDR-63-55 (AD-411556), Aerospace Medical Research Laboratories, Dayton, Ohio, June 1963.

McKenzie, S. K.: An Annotated Bibliography of USAF Physical Anthropology for the Period 1946 to 1968. (9th Ed.) Anthropology Branch, Aerospace Medical Research Laboratories, Dayton, Ohio.

Report of the International Commission on Radiobiological Units and Measurements (ICRU), NBS Handbook No. 62, National Bureau of Standards, Washington, D. C., 1956.

Roebuck, J. A.: Development of Mathematical Models and Computer Program for Workspace Design and Analysis. PTP-13100, Space Division, North American Rockwell Corporation, Los Angeles, California.

Roebuck, J. A.: Models of Musculo-Skeletal Mechanics: Engineering Course 230B, University of California, Los Angeles, California.

Steinheimer, R. M.: "Range-Energy Relations for Protons in Various Substances," Physical Review, Volume 118, Number 4, May 1960, P. 1046.

The Autopsy. Armed Forces Institute of Pathology, Washington, D. C., 1951.

Topping, P. C., and J. A. Roebuck: Computer Program for NASA Anthropometry File and Report (Program No. AFB152B), PTP-13100 Space Division, North American Rockwell Corporation, Los Angeles, California.


Truex, R. C., and C. E. Kellner: Detailed Atlas of the Head and Neck; Oxford University Press, New York, New York, 1948.

Legend:

Composite Numbers

0 = single shield

X = multiple shields ($2 \leq x \leq 9$)







Figure 19 Composite Shields in the Muscle Portion, Standing Man

A

Legend:
Composite Numbers
0 = single shield
X = multiple shields ($2 \leq X \leq 9$)






Figure 20 Composite Shields in the Muscle Portion, Seated Man

B


A

Legend:

Composite Numbers

0 = single shield

X = multiple shields ($2 \leq x \leq 9$)







Figure 21 Composite Shields in the Skeleton, Standing Man

A

Legend:
 Composite Numbers
 0 = single shield
 X = multiple shields ($2 \leq x \leq 9$)






Figure 22 Composite Shields in the Skeleton, Seated Man

UNCLASSIFIED

Security Classification

DOCUMENT CONTROL DATA - R & D		
(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)		
1. ORIGINATING ACTIVITY (Corporate author)		2a. REPORT SECURITY CLASSIFICATION
Martin Marietta Corporation Denver, Colorado 80201		UNCLASSIFIED
3. REPORT TITLE		2b. GROUP
COMPUTERIZED ANATOMICAL MODEL MAN		
4. DESCRIPTIVE NOTES (Type of report and inclusive dates)		
7 February-7 October 1969		
5. AUTHOR(S) (First name, middle initial, last name)		
Paul G. Kase		
6. REPORT DATE	7a. TOTAL NO. OF PAGES	7b. NO. OF REFS
January 1970	160	18
8a. CONTRACT OR GRANT NO.	9a. ORIGINATOR'S REPORT NUMBER(S)	
F29601-69-C-0052	AFWL-TR-69-161	
b. PROJECT NO.	9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)	
5877	Contractor's Report No.: MCR-69-409	
c. Task No.		
01		
10. DISTRIBUTION STATEMENT This document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of AFWL (WLBB), KAFB, NM, 87117. Distribution is limited because of the technology discussed in the report.		
11. SUPPLEMENTARY NOTES		12. SPONSORING MILITARY ACTIVITY
		AFWL (WLBB) Kirtland AFB, NM 87117
13. ABSTRACT		
(Distribution Limitation Statement No. 2)		
The Computerized Anatomical Model Man is a detailed representation of the radiation transport properties of the human body. It is to be used for computation of the areal density distribution at specified locations in the body. This information is applicable to dose calculations in natural, weapon, reactor, and other radiation environments. The model has two configurations--standing and seated. Over 2200 individual geometrical shapes have been used to depict the external conformation, the skeleton, and the principal organs. The exterior dimensions are those of the 50th percentile Air Force man; the skeleton and organs were scaled from life-size models to conform to the exterior. The model includes variations of material density and fractional composition by weight due to the principal chemical elements contained in muscle, bone, bone marrow, and organ tissue. The model is compatible with the North American Rockwell Modified Elemental Volume Dose Program. This has been demonstrated by solution of sample problems employing both configurations of the model with the North American Rockwell Program on the CDC 6600 digital computer at the Air Force Weapons Laboratory.		

DD FORM 1473

REPLACES DD FORM 1473, 1 JAN 64, WHICH IS OBSOLETE FOR ARMY USE.

UNCLASSIFIED
Security Classification

UNCLASSIFIED
Security Classification

14. KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
Radiobiology Space radiation Spacecraft shielding Dose Depth dose Radiation hazards Radiation transport in man						

UNCLASSIFIED
Security Classification