## **REPORT DOCUMENTATION PAGE**

#### Form Approved OMB NO. 0704-0188

I. REPORT DATE (DD-MM-YYYY)       2. REPORT TYPE New Reprint       3. DATES COVERED (From - To)         A. TITLE AND SUBTITLE       See CONTRACT NUMBER         Concepts, performance review, and prospects of table-top, few- cycle optical parametric chirped-pulse amplification       See CONTRACT NUMBER         6. AUTHORS       See CONTRACT NUMBER         6. AUTHORS       See PROJECT NUMBER         6. AUTHORS       See TASK NUMBER         6. AUTHORS       See TASK NUMBER         6. AUTHOR S       See TASK NUMBER         7. PERFORMING ORGANIZATION NAMES AND ADDRESSES       See TASK NUMBER         0. SPONSORING/MONTORING AGENCY NAME(S) AND ADDRESSES       8. PERFORMING ORGANIZATION REPORT         0. SPONSORING/MONTORING AGENCY NAME(S) AND ADDRESS       10. SPONSOR/MONITOR'S ACRONYM(S)         (ES)       9727-PH-MUR 88       10. SPONSOR/MONITOR'S ACRONYM(S)         12. DISTRIBUTION AVAILBILITY STATEMENT       Approved for public release: distribution is unlimited.       11. SPONSOR/MONITOR'S REPORT         13. SUPFLEMENTARY NOTES       The views, opinions andfor findings contained in this report are those of the author(s) and should not contrued as an official Department of the Army postion, policy or decision, unless so designated by other documentation.         14. ABSTRACT       More than 20 years after the first presentation of optical parametric chirped-pulse amplification (OPCPA), the technology has matured as a powerful technique to produce high-intensity, few-cyc	The public rep searching exist regarding this Headquarters Respondents s of information if PLEASE DO N	orting burden for th ing data sources, g burden estimate o Services, Directora hould be aware tha i th does not display OT RETURN YOUF	nis collection of in jathering and mair or any other aspe- te for Information t notwithstanding a a currently valid OI R FORM TO THE A	formation is estimated to avera itaining the data needed, and o ct of this collection of informa Operations and Reports, 12 ny other provision of law, no pe MB control number. BOVE ADDRESS.	age 1 hour pe completing and tion, including 15 Jefferson 1 rson shall be s	response, reviewing t suggesstic avis Highv ubject to ar	, including the time for reviewing instructions, the collection of information. Send comments ons for reducing this burden, to Washington way, Suite 1204, Arlington VA, 22202-4302. ny oenalty for failing to comply with a collection			
New Reprint         -           4. TITLE AND SUBTITLE Concepts. performance review, and prospects of table-top, few- cycle optical parametric chirped-pulse amplification         5a. CONTRACT NUMBER W911NF-11-1-0297           5b. GRANT NUMBER         5b. GRANT NUMBER           6. AUTHORS         6. AUTHORS           Andreas Vaupel, Nathan Bodnar, Benjamin Webb, Lawrence Shah, Martin Richardson         5c. PROGRAM ELEMENT NUMBER           5c. TASK NUMBER         5c. TASK NUMBER           7. PERFORMING ORGANIZATION NAMES AND ADDRESSES         8. PERFORMING ORGANIZATION REPORT NUMBER           12201 Research Parkway, Suite 501         5c. TASK NUMBER           01ado, FL         32826 - 3246           9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS         10. SPONSOR/MONITOR'S ACRONYM(S) ARO           12.0 SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS         11. SPONSOR/MONITOR'S ACRONYM(S) ARO           12.0 SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS         11. SPONSOR/MONITOR'S ACRONYM(S) ARO           13. SUPPLEMENTARY NOTES         11. SPONSOR/MONITOR'S ACRONYM(S) ARO           13. SUPPLEMENTARY NOTES         11. SPONSOR/MONITOR'S ACRONYM(S) ARO           13. SUPPLEMENTARY NOTES         59727-PH-MUR,88           12. DISTRIBUTION AVAILBELTLY STATEMENT         59727-PH-MUR,88           13. SUPPLEMENTARY NOTES         50. Jord and seignated by other documentation.           14. ABSTRACT	1. REPORT	DATE (DD-MM-	YYYY)	2. REPORT TYPE		3. D.	3. DATES COVERED (From - To)			
4. TITLE AND SUBTITIE Concepts, performance review, and prospects of table-top, few- cycle optical parametric chirped-pulse amplification  5a. CONTRACT NUMBER  5b. GRANT NUMBER  5b. GRANT NUMBER  5c. PROGRAM ELEMENT NUMBER  611103  6. AUTHORS  Andreas Vaupel, Nathan Bodnar, Benjamin Webb, Lawrence Shah, Martin Richardson  6. AUTHORS  Andreas Vaupel, Nathan Bodnar, Benjamin Webb, Lawrence Shah, Martin Richardson  7. PERFORMING ORGANIZATION NAMES AND ADDRESSES University of Central Florida 12201 Research Parkway, Suite 501  7. Orlando, FL  9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS  (ES)  10. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS  10. SPONSOR/MONITOR'S ACRONYM(S)  ARD  11. SPONSOR/MONITOR'S REPORT NUMBER  12. DISTRIBUTION AVAILIBILITY STATEMENT Approved for public release, distribution is unlimited.  13. SUPPLEMENTARY NOTES  14. ABSTRACT  14. ABSTRACT  14. ABSTRACT  15. SUBJECT THEMS  16. SPECURITY CLASSIFICATION OF:  15. SUBJECT THEMS  16. SECURITY CLASSIFICATION OF:  15. SUBJECT THEMS  10. SPONSORING (OPCPA), the telenication of optical parametric chirped-pulse amplification.  16. SECURITY CLASSIFICATION OF:  15. SUBJECT THEMS  16. SECURITY CLASSIFICATION OF:  15. SUBJECT THEMS  16. SECURITY CLASSIFICATION OF:  17. LIMITATION OF  15. NUMBER  19. AMSTRACT  10. SPONSORIAL PERSONSIBLE PERSON  10. SPONSORIAL PERSONSIBLE PERSON  11. SPONSOR/MONTOR'S REPORT  12. SIDTRIBUTION AVAILIBILITY STATEMENT  13. SUBPLEMENTARY NOTES  14. ABSTRACT  15. SUBJECT THEMS  16. SECURITY CLASSIFICATION OF:  15. SUBJECT THEMS  17. LIMITATION OF  15. SUBJECT THEMS  17. LIMITATION OF  15. NUMBER  19. AMSTRACT  19. BASTRACT  10. SPONSORIAL PUBLE NUMBER  19. NAME OF RESPONSIBLE PERSON  19. TELEPHONE NUMBER  19. TELEPHONE NUMBER  19. NAME OF RESPONSIBLE PERSON  19. TELEPHONE NUMBER  19. THEEPHONE NUMBER				New Reprint			-			
Concepts, performance review, and prospects of table-top, few- cycle optical parametric chirped-pulse amplification       W911NF-11-1-0297         sc. PROGRAM ELEMENT NUMBER       5b. GRANT NUMBER         6. AUTHORS       611103         Andreas Vaupel, Nathan Bodnar, Benjamin Webb, Lawrence Shah, Martin Richardson       5d. PROJECT NUMBER         7. PERFORMING ORGANIZATION NAMES AND ADDRESSES       5f. WORK UNIT NUMBER         University of Central Florida       5f. WORK UNIT NUMBER         12201 Research Parkway, Suite 501       NUMBER         Orlando, FL       32826 - 3246         9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS       10. SPONSOR/MONITOR'S ACRONYM(S)         (ES)       ARO         U.S. Army Research Office       11. SPONSOR/MONITOR'S ACRONYM(S)         P.O. Box 12211       SP727-PH-MUR.88         Research Traingle Park, NC 27709-2211       59727-PH-MUR.88         13. SUPPL EMENTARY NOTES       The views, opinions and/or findings contained in this report are those of the author(s) and should not contrued as an official Department of the Army position, policy or decision, unless so designated by other documentation.         14. ABSTRACT       More than 20 years after the first presentation of optical parametric chirped-pulse amplification (OPCPA), the technology has matured as a powerful technique to produce high-intensity, few-cycle, and ultrashort laser pulses. The output characteristics of these systems cover a wide range of center wavelengths, pulse amplification- bra	4. TITLE A	ND SUBTITLE			5a. CC	NTRACT	NUMBER			
cycle optical parametric chirped-pulse amplification       5b. GRANT NUMBER         5c. PROGRAM ELEMENT NUMBER       5c. PROGRAM ELEMENT NUMBER         6. AUTHORS       5d. PROJECT TRUMBER         Andreas Vaupel, Nathan Bodnar, Benjamin Webb, Lawrence Shah, Martin Richardson       5d. PROJECT TRUMBER         5r. WORK UNIT NUMBER       5c. TASK NUMBER         7. PERFORMING ORGANIZATION NAMES AND ADDRESSES University of Central Florida 12201 Research Parkway, Suite 501       8. PERFORMING ORGANIZATION REPORT NUMBER         0rlando, FL       32826 - 3246       NUMBER         9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS (ES)       10. SPONSOR/MONITOR'S ACRONYM(S) ARO         12. DISTRIBUTION AVALLIBILITY STATEMENT Approved for public release; distribution is unlimited.       11. SPONSOR/MONITOR'S REPORT NUMBER(S) and should not contrued as an official Department of the Army position, policy or decision, unless so designated by other documentation.         14. ABSTRACT       More than 20 years after the first presentation of optical parametric chirped-pulse amplification (OPCPA), the technology has matured as a powerful technique to produce high-intensity, few-eycle, and ultrashort laser pulses. The outrent record performance of table-top, few-cycle OPCPA systems are 16 TW peak power and 22 W average power, which show that OPCPA is able to directly compete with Trisaphire chirped-pulse amplification.         15. SUBJECT TERMS       11. LIMITATION OF ABSTRACT UU       12. LIMITATION OF ABSTRACT UU       15. NUMBER <td>Concepts, p</td> <td>performance re</td> <td>eview, and pro</td> <td>spects of table-top, few</td> <td>- W911</td> <td colspan="3">1NF-11-1-0297</td>	Concepts, p	performance re	eview, and pro	spects of table-top, few	- W911	1NF-11-1-0297				
Sc. PROGRAM FLEMENT NUMBER         6. AUTHORS         Andreas Vaupel, Nathan Bodnar, Benjamin Webb, Lawrence Shah, Martin Richardson         5. TASK NUMBER         1201 Research Parkway, Suite 501         Orlando, FL         3. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS         (B)         10. SPONSOR/MONITOR'S ACRONYM(S)         (RS)         11. SPONSOR/MONITOR'S ACRONYM(S)         ARO         12. DISTRIBUTION AVAILIBILITY STATEMENT         Approved for public release; distribution is unlimited.         13. SUPPLEMENTARY NOTES         The view, opinions and/or findings contained in this report are those of the author(s) and should not contrued as an official Department of the Army position, policy or decision, unless so designated by other documentation.         14. ABSTRACT         More than 20 years after the first presentation of optical parametric chirped-pulse amplification (OPCPA), the technology has matured as a powerful technique to produce high-intensity, few-cycle, and ultrashort laser pulses.         The output characteristics of these systems cover a wide range of center wavelengths, pulse energies, and average power,	cycle optic	al parametric c	chirped-pulse	amplification	5b. GF	ANT NU	MBER			
6. AUTHORS       Adreas Vaupel, Nathan Bodnar, Benjamin Webb, Lawrence Shah, Martin Richardson       5d. PROJECT NUMBER         5e. TASK NUMBER       5e. TASK NUMBER         7. PERFORMING ORGANIZATION NAMES AND ADDRESSES       5f. WORK UNIT NUMBER         12001 Research Parkway, Suite 501       5f. WORK UNIT NUMBER         0rlando, FL       32826 -3246         9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS       8. PERFORMING ORGANIZATION REPORT NUMBER         0. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS       10. SPONSOR/MONITOR'S ACRONYM(S) ARO         (FS)       11. SPONSOR/MONITOR'S ACRONYM(S) ARO         12.01STRIBUTION AVAILIBILITY STATEMENT       NUMBER         Approved for public release; distribution is unlimited.       13. SUPPLEMENTARY MONTES         The views, opinions and/or findings contained in this report are those of the author(s) and should not contrued as an official Department of the Army position, policy or decision, unless so designated by other documentation.         14. ABSTRACT       ABSTRACT         More than 20 years after the first presentation of optical parametric chirped-pulse amplification (OPCPA), the technology has matured as a powerful technique to produce high-intensity, few-cycle, and ultrashort laser pulses. The output characteristics of these systems cover a wide range of center wavelengths, pulse energies, and average powers. Which show that OPCPA is sable to directly complet with Tisapplire chirped-pulse amplification-         15. SUBJECT TERMS       17. LIMITATION OF <td< td=""><td></td><td></td><td></td><td></td><td>5c. PR</td><td colspan="3">ROGRAM ELEMENT NUMBER</td></td<>					5c. PR	ROGRAM ELEMENT NUMBER				
6. AUTHORS       Andreas Vaupel, Nathan Bodnar, Benjamin Webb, Lawrence Shah, Martin Richardson       5d. PROJECT NUMBER         5e. TASK NUMBER       5e. TASK NUMBER         7. PERFORMING ORGANIZATION NAMES AND ADDRESSES       5f. WORK UNIT NUMBER         7. PERFORMING ORGANIZATION NAMES AND ADDRESSES       8. PERFORMING ORGANIZATION REPORT         University of Central Florida       32826 -3246         9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS       10. SPONSOR/MONITOR'S ACRONYM(S)         (ES)       X.S. Army Research Office         9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS       10. SPONSOR/MONITOR'S ACRONYM(S)         Research Triangle Park, NC 27709-2211       11. SPONSOR/MONITOR'S REPORT         NUMBER(S)       59727-PH-MUR.88         12. DISTRIBUTION AVAILIBILITY STATEMENT       ARO         Approved for public release; distribution is unlimited.       51. SUPPLEMENTARY NOTES         The views, opinions and/or findings contained in this report are those of the author(s) and should not contrued as an official Department of the Army position, policy or decision, unless so designated by other documentation.         14. ABSTRACT       More than 20 years after the first presentation of optical parametric chirped-pulse amplification (OPCPA), the technology has matured as a powerful technique to produce high-intensity, few-cycle, and ultrashort laser pulses. The output characteristics of these systems cover a wide range of center wavelengths, pulse emergies, and average powers. The current record performan		611					03			
Andreas Vaupel, Nathan Bodnar, Benjamin Webb, Lawrence Shah, Martin Richardson  5c. TASK NUMBER  5c. TASK N	6. AUTHOR	RS			5d. PR	OJECT NUMBER				
Martin Richardson       Se. TASK NUMBER         5f. WORK UNIT NUMBER         7. PERFORMING ORGANIZATION NAMES AND ADDRESSES         University of Central Florida         12201 Research Parkway, Suite 501         Orlando, FL       32826 - 3246         9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS         (ES)         U.S. Army Research Office         P. D. Dax 12211         Research Trangle Park, NC 27709-2211         Supproved for public release; distribution is unlimited.         13. SUPPLEMENTARY NOTES         The views, opinions and/or findings contained in this report are those of the author(s) and should not contrued as an official Department of the Army position, policy or decision, unless so designated by other documentation.         14. ABSTRACT         More than 20 years after the first presentation of optical parametric chirped-pulse amplification (OPCPA), the technology has matured as a powerful technique to produce high-intensity, few-cycle, and ultrashort laser pulses.         14. ABSTRACT         More than 20 years after the first presentation of optical parametric chirped-pulse amplification (OPCPA), the technology has matured as a powerful technique to produce high-intensity, few-cycle, and ultrashort laser pulses.         15. SUBJECT TERMS         ultrafast laser amplifiers; solid-state laser, optical parametric chirped-pulse amplification.         15. SUBJECT TERMS         ultrafast laser amplifiers; las	Andreas Va	upel, Nathan Boo	dnar, Benjamin V	Vebb, Lawrence Shah,						
5f. WORK UNIT NUMBER         7. PERFORMING ORGANIZATION NAMES AND ADDRESSES       8. PERFORMING ORGANIZATION REPORT         University of Central Florida       NUMBER         12201 Research Parkway, Suite 501       10. SPONSOR/MONITOR'S ACRONYM(S)         Orlando, FL       32826 - 3246         9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS       10. SPONSOR/MONITOR'S ACRONYM(S)         (ES)       10. SPONSOR/MONITOR'S ACRONYM(S)         U.S. Army Research Office       11. SPONSOR/MONITOR'S REPORT         P.O. Box 12211       59727-PH-MUR.88         Research Triangle Park, NC 27709-2211       59727-PH-MUR.88         12. DISTRIBUTION AVAILIBILITY STATEMENT       Approved for public release; distribution is unlimited.         13. SUPPLEMENTARY NOTES       The views, opinions and/or findings contained in this report are those of the author(s) and should not contrued as an official Department of the Army position, policy or decision, unless so designated by other documentation.         14. ABSTRACT       More than 20 years after the first presentation of optical parametric chirped-pulse amplification (OPCPA), the technology has matured as a powerful technique to produce high-intensity, few-cycle, and ultrashort laser pulses. The output characteristics of these systems cover a wide range of center wavelengths, pulse energies, and average powers. The current record performance of table-top, few-cycle OPCPA systems are 16 TW peak power and 22 W average power, which show that OPCPA is able to directly competer with Ti: sapphire chirped-pulse amplification.	Martin Rich	hardson	, J	, , ,	5e. TA	SK NUMI	BER			
7. PERFORMING ORGANIZATION NAMES AND ADDRESSES       8. PERFORMING ORGANIZATION REPORT         University of Central Florida       32826 -3246         12201 Research Parkway, Suite 501       NUMBER         Orlando, FL       32826 -3246         9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS       10. SPONSOR/MONITOR'S ACRONYM(S)         (ES)       11. SPONSOR/MONITOR'S REPORT         V.S. Army Research Office       11. SPONSOR/MONITOR'S REPORT         P.O. Box 12211       NUMBER(S)         Research Triangle Park, NC 27709-2211       59727-PH-MUR.88         12. DISTRIBUTION AVAILIBILITY STATEMENT       NUMBER(S)         Approved for public release; distribution is unlimited.       59727-PH-MUR.88         13. SUPPLEMENTARY NOTES       The views, opinions and/or findings contained in this report are those of the author(s) and should not contrued as an official Department of the Army position, policy or decision, unless so designated by other documentation.         14. ABSTRACT       More than 20 years after the first presentation of optical parametric chirped-pulse amplification (OPCPA), the technology has matured as a powerful technique to produce high-intensity, few-cycle, and ultrashort laser pulses.         The output characteristics of these systems cover a wide range of center wavelengths, pulse energies, and average powers. The current record performance of table-top, few-cycle OPCPA systems are 16 TW peak power and 22 W average power, which show that OPCPA is able to directry compete with Ti:sapphire chirped-pulse amplificati					5f. WC	ORK UNIT NUMBER				
Orlando, FL       32826 - 3246         9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS (ES)       10. SPONSOR/MONITOR'S ACRONYM(S) ARO         U.S. Army Research Office P.O. Box 12211 Research Triangle Park, NC 27709-2211       11. SPONSOR/MONITOR'S REPORT NUMBER(S) 59727-PH-MUR.88         12. DISTRIBUTION AVAILIBILITY STATEMENT Approved for public release; distribution is unlimited.       59727-PH-MUR.88         13. SUPPLEMENTARY NOTES The views, opinions and/or findings contained in this report are those of the author(s) and should not contrued as an official Department of the Army position, policy or decision, unless so designated by other documentation.         14. ABSTRACT More than 20 years after the first presentation of optical parametric chirped-pulse amplification (OPCPA), the technology has matured as a powerful technique to produce high-intensity, few-cycle, and ultrashort laser pulses. The output characteristics of these systems cover a wide range of center wavelengths, pulse energies, and average powers. The current record performance of table-top, few-cycle OPCPA systems are 16 TW peak power and 22 W average power, which show that OPCPA is able to directly compete with Ti:sapphire chirped-pulse amplification- teced enterement of current of current of current strice lawnees for intensity and the surgent the average for intensity of average for intensity and average for intensities and average for	7. PERFORMING ORGANIZATION NAMES AND ADDRESSES University of Central Florida 12201 Research Parkway, Suite 501					8. PERFORMING ORGANIZATION REPORT NUMBER				
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS (ES)       10. SPONSOR/MONITOR'S ACRONYM(S) ARO         U.S. Army Research Office P.O. Box 12211 Research Triangle Park, NC 27709-2211       11. SPONSOR/MONITOR'S REPORT NUMBER(S) 59727-PH-MUR.88         12. DISTRIBUTION AVAILIBILITY STATEMENT Approved for public release; distribution is unlimited.       59727-PH-MUR.88         13. SUPPLEMENTARY NOTES The views, opinions and/or findings contained in this report are those of the author(s) and should not contrued as an official Department of the Army position, policy or decision, unless so designated by other documentation.         14. ABSTRACT More than 20 years after the first presentation of optical parametric chirped-pulse amplification (OPCPA), the technology has matured as a powerful technique to produce high-intensity, few-cycle, and ultrashort laser pulses. The output characteristics of these systems cover a wide range of center wavelengths, pulse energies, and average powers. The current record performance of table-top, few-cycle OPCPA systems are 16 TW peak power and 22 W average power, which show that OPCPA is able to directly compete with Ti:sapphire chirped-pulse amplification- these devices are activated as a potential and as the output the successity of th	Orlando, FI	-	3282	6 -3246						
U.S. Army Research Office P.O. Box 12211 Research Triangle Park, NC 27709-2211       11. SPONSOR/MONITOR'S REPORT NUMBER(S) 59727-PH-MUR.88         12. DISTRIBUTION AVAILIBILITY STATEMENT Approved for public release; distribution is unlimited.       59727-PH-MUR.88         13. SUPPLEMENTARY NOTES The views, opinions and/or findings contained in this report are those of the author(s) and should not contrued as an official Department of the Army position, policy or decision, unless so designated by other documentation.         14. ABSTRACT More than 20 years after the first presentation of optical parametric chirped-pulse amplification (OPCPA), the technology has matured as a powerful technique to produce high-intensity, few-cycle, and ultrashort laser pulses. The output characteristics of these systems cover a wide range of center wavelengths, pulse energies, and average powers. The current record performance of table-top, few-cycle OPCPA systems are 16 TW peak power and 22 W average power, which show that OPCPA is able to directly compete with Ti:sapphire chirped-pulse amplification.         15. SUBJECT TERMS ultrafiast laser amplifiers; solid-state laser; optical parametric chirped-pulse amplification.       15. NUMBER Martin Richardson         16. SECURITY CLASSIFICATION OF: a. REPORT UU       17. LIMITATION OF ABSTRACT UU       15. NUMBER VU       19a. NAME OF RESPONSIBLE PERSON Martin Richardson         19b. TELEPHONE NUMBER 407-823-6819       19a. NAME OF RESPONSIBLE PERSON       19b. TELEPHONE NUMBER 407-823-6819	9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS       10. SPONSOR/MONITOR'S ACRONYM(S)         (ES)       ARO						NSOR/MONITOR'S ACRONYM(S)			
Research Triangle Park, NC 27709-2211         59727-PH-MUR.88         12. DISTRIBUTION AVAILIBILITY STATEMENT         Approved for public release; distribution is unlimited.         13. SUPPLEMENTARY NOTES         The views, opinions and/or findings contained in this report are those of the author(s) and should not contrued as an official Department of the Army position, policy or decision, unless so designated by other documentation.         14. ABSTRACT         More than 20 years after the first presentation of optical parametric chirped-pulse amplification (OPCPA), the technology has matured as a powerful technique to produce high-intensity, few-cycle, and ultrashort laser pulses. The output characteristics of these systems cover a wide range of center wavelengths, pulse energies, and average powers. The current record performance of table-top, few-cycle OPCPA systems are 16 TW peak power and 22 W average power, which show that OPCPA is able to directly compete with Ti:sapphire chirped-pulse amplification-hered outputs are amplifiers; solid-state laser; optical parametric chirped-pulse amplification.         16. SECURITY CLASSIFICATION OF: UU         UU       UI       17. LIMITATION OF ABSTRACT       15. NUMBER       19a. NAME OF RESPONSIBLE PERSON         Matrin Richardson         UU       15. NUMBER       19a. NAME OF RESPONSIBLE PERSON         Matrin Richardson	U.S. Army Research Office P.O. Box 12211					11. SPONSOR/MONITOR'S REPORT NUMBER(S)				
12. DISTRIBUTION AVAILIBILITY STATEMENT         Approved for public release; distribution is unlimited.         13. SUPPLEMENTARY NOTES         The views, opinions and/or findings contained in this report are those of the author(s) and should not contrued as an official Department of the Army position, policy or decision, unless so designated by other documentation.         14. ABSTRACT         More than 20 years after the first presentation of optical parametric chirped-pulse amplification (OPCPA), the technology has matured as a powerful technique to produce high-intensity, few-cycle, and ultrashort laser pulses. The output characteristics of these systems cover a wide range of center wavelengths, pulse energies, and average powers. The current record performance of table-top, few-cycle OPCPA systems are 16 TW peak power and 22 W average power, which show that OPCPA is able to directly compete with Ti:sapphire chirped-pulse amplification-top devices antical pulses. Here, we review the conserve of OPCPA and preserve the current the current the current for intense antical pulses. Here, we review the conserve of OPCPA and preserve the current the current the current the current the current the current for intense antical pulses. Here, we review the conserve of OPCPA and preserve the current to current the current the current the current the current to current to current the current to current to current the current to current the current to current	Research Triangle Park, NC 27709-2211					59727-PH-MUR.88				
Approved for public release; distribution is unlimited.         13. SUPPLEMENTARY NOTES         The views, opinions and/or findings contained in this report are those of the author(s) and should not contrued as an official Department of the Army position, policy or decision, unless so designated by other documentation.         14. ABSTRACT         More than 20 years after the first presentation of optical parametric chirped-pulse amplification (OPCPA), the technology has matured as a powerful technique to produce high-intensity, few-cycle, and ultrashort laser pulses. The output characteristics of these systems cover a wide range of center wavelengths, pulse energies, and average powers. The current record performance of table-top, few-cycle OPCPA systems are 16 TW peak power and 22 W average power, which show that OPCPA is able to directly compete with Ti:sapphire chirped-pulse amplification-the automs for intense partical pulses. Here, we exclude the current record performance of table-top, the resonance of ODCPA and present the current 15. SUBJECT TERMS         16. SECURITY CLASSIFICATION OF:       17. LIMITATION OF       15. NUMBER       19a. NAME OF RESPONSIBLE PERSON         16. SECURITY CLASSIFICATION OF:       UU       UU       15. NUMBER       19a. NAME OF RESPONSIBLE PERSON         17. LIMITATION OF       UU       UU       UU       15. NUMBER       19b. TELEPHONE NUMBER         407-823-6819       UU       UU       UU       07-823-6819       07-823-6819	12. DISTRIE	BUTION AVAIL	IBILITY STATE	EMENT	ı					
13. SUPPLEMENTARY NOTES         The views, opinions and/or findings contained in this report are those of the author(s) and should not contrued as an official Department of the Army position, policy or decision, unless so designated by other documentation.         14. ABSTRACT         More than 20 years after the first presentation of optical parametric chirped-pulse amplification (OPCPA), the technology has matured as a powerful technique to produce high-intensity, few-cycle, and ultrashort laser pulses. The output characteristics of these systems cover a wide range of center wavelengths, pulse energies, and average powers. The current record performance of table-top, few-cycle OPCPA systems are 16 TW peak power and 22 W average power, which show that OPCPA is able to directly compete with Ti:sapphire chirped-pulse amplification-head sustaines for intense antical pulses. Use survive the concentre of OPCPA and present the current to a survey of the average power, which show that OPCPA is able to directly compete with Ti:sapphire chirped-pulse amplification-head sustaines for intense antical pulses. Use survive the concentre of OPCPA and present the current to a survey of the concentre of OPCPA and present the current to a survey.         16. SECURITY CLASSIFICATION OF:       17. LIMITATION OF       18. NAME OF RESPONSIBLE PERSON         a. REPORT       b. ABSTRACT       c. THIS PAGE       UU       UU       19a. NAME OF RESPONSIBLE PERSON         19b. TELEPHONE NUMBER       UU       UU       UU       19b. TELEPHONE NUMBER       19b. TELEPHONE NUMBER	Approved for	r public release; c	listribution is un	limited.						
14. ABSTRACT         More than 20 years after the first presentation of optical parametric chirped-pulse amplification (OPCPA), the technology has matured as a powerful technique to produce high-intensity, few-cycle, and ultrashort laser pulses. The output characteristics of these systems cover a wide range of center wavelengths, pulse energies, and average powers. The current record performance of table-top, few-cycle OPCPA systems are 16 TW peak power and 22 W average power, which show that OPCPA is able to directly compete with Ti:sapphire chirped-pulse amplification-         15. SUBJECT TERMS       Interact energies; solid-state laser; optical parametric chirped-pulse amplification.         16. SECURITY CLASSIFICATION OF:       17. LIMITATION OF         a. REPORT       b. ABSTRACT         UU       UU         UU       UU         UU       UU	13. SUPPLE The views, o of the Army	EMENTARY NO pinions and/or fir position, policy c	TES ndings contained or decision, unles	in this report are those of th s so designated by other doc	e author(s) and a sumentation.	d should	not contrued as an official Department			
15. SOBJECT TERMIS         ultrafast laser amplifiers; laser amplifiers; solid-state laser; optical parametric chirped-pulse amplification.         16. SECURITY CLASSIFICATION OF:       17. LIMITATION OF         a. REPORT       b. ABSTRACT       c. THIS PAGE         UU       UU       UU         UU       UU       UU	14. ABSTRA More than technology The output powers. Th average po	ACT 20 years after has matured a characteristics the current recon- wer, which sho	the first presents a powerful the s of these system rd performance tow that OPCP	ntation of optical param technique to produce his ems cover a wide range e of table-top, few-cycl A is able to directly con	etric chirp gh-intensity of center v e OPCPA npete with	d-pulse , few-cy vaveleng ystems a Ti:sappl	amplification (OPCPA), the vcle, and ultrashort laser pulses. ths, pulse energies, and average are 16 TW peak power and 22 W hire chirped-pulse amplification-			
16. SECURITY CLASSIFICATION OF:17. LIMITATION OF15. NUMBER19a. NAME OF RESPONSIBLE PERSONa. REPORTb. ABSTRACTc. THIS PAGEABSTRACTOF PAGESMartin RichardsonUUUUUUUU19b. TELEPHONE NUMBER407-823-6819	15. SUBJE0 ultrafast lase	ultrafast laser amplifiers; laser amplifiers; solid-state laser; optical parametric chirped-pulse amplification.								
UU UU UU UU UU UU UU 407-823-6819	16. SECURI	TY CLASSIFIC	ATION OF:	17. LIMITATION OF	15. NUMB OF PAGES	ER 19a. Mart	NAME OF RESPONSIBLE PERSON			
	UU	UU	UU	UU		19b. 407-	TELEPHONE NUMBER -823-6819			

#### **Report Title**

Concepts, performance review, and prospects of table-top, few-cycle optical parametric chirped-pulse amplification

#### ABSTRACT

More than 20 years after the first presentation of optical parametric chirped-pulse amplification (OPCPA), the technology has matured as a powerful technique to produce high-intensity, few-cycle, and ultrashort laser pulses. The output characteristics of these systems cover a wide range of center wavelengths, pulse energies, and average powers. The current record performance of table-top, few-cycle OPCPA systems are 16 TW peak power and 22 W average power, which show that OPCPA is able to directly compete with Ti:sapphire chirped-pulse amplification-based systems as source for intense optical pulses. Here, we review the concepts of OPCPA and present the current state-of-the art performance level for several systems reported in the literature. To date, the performance of these systems is most generally limited by the employed pump laser. Thus, we present a comprehensive review on the recent progress in high-energy, high-average-power, picosecond laser systems, which provide improved performance relative to OPCPA pump lasers employed to date. From here, the impact of these novel pump lasers on table-top, few-cycle OPCPA systems are discussed.

### REPORT DOCUMENTATION PAGE (SF298) (Continuation Sheet)

Continuation for Block 13

ARO Report Number 59727.88-PH-MUR Concepts, performance review, and prospects o...

Block 13: Supplementary Note

© 2013 . Published in Optical Engineering, Vol. Ed. 0 53, (5) (2013), (, (5). DoD Components reserve a royalty-free, nonexclusive and irrevocable right to reproduce, publish, or otherwise use the work for Federal purposes, and to authroize others to do so (DODGARS §32.36). The views, opinions and/or findings contained in this report are those of the author(s) and should not be construed as an official Department of the Army position, policy or decision, unless so designated by other documentation.

Approved for public release; distribution is unlimited.

# Optical Engineering

SPIEDigitalLibrary.org/oe

# Concepts, performance review, and prospects of table-top, few-cycle optical parametric chirped-pulse amplification

Andreas Vaupel Nathan Bodnar Benjamin Webb Lawrence Shah Martin Richardson



# Concepts, performance review, and prospects of table-top, few-cycle optical parametric chirped-pulse amplification

Andreas Vaupel,\* Nathan Bodnar, Benjamin Webb, Lawrence Shah, and Martin Richardson

University of Central Florida, CREOL-The College of Optics and Photonics, Townes Laser Institute, 4000 Central Florida Boulevard, Orlando, Florida 32816

**Abstract.** More than 20 years after the first presentation of optical parametric chirped-pulse amplification (OPCPA), the technology has matured as a powerful technique to produce high-intensity, few-cycle, and ultrashort laser pulses. The output characteristics of these systems cover a wide range of center wavelengths, pulse energies, and average powers. The current record performance of table-top, few-cycle OPCPA systems are 16 TW peak power and 22 W average power, which show that OPCPA is able to directly compete with Ti:sapphire chirped-pulse amplification-based systems as source for intense optical pulses. Here, we review the concepts of OPCPA and present the current state-of-the art performance level for several systems reported in the literature. To date, the performance of these systems is most generally limited by the employed pump laser. Thus, we present a comprehensive review on the recent progress in high-energy, high-average-power, picosecond laser systems, which provide improved performance relative to OPCPA pump lasers employed to date. From here, the impact of these novel pump lasers on table-top, few-cycle OPCPA is detailed and the prospects for next-generation OPCPA systems are discussed. © *The Authors. Published by SPIE under a Creative Commons Attribution 3.0 Unported License. Distribution or reproduction of this work in whole or in part requires full attribution of the original publication, including its DOI.* [DOI: 10.1117/1.0E.53.5.051507]

Keywords: ultrafast laser amplifiers; laser amplifiers; solid-state laser; optical parametric chirped-pulse amplification.

Paper 131120SS received Jul. 24, 2013; revised manuscript received Oct. 16, 2013; accepted for publication Nov. 18, 2013; published online Dec. 31, 2013.

#### 1 Introduction

Ultrafast laser amplification was revolutionized in 1985 when chirped-pulse amplification (CPA) was introduced.<sup>1</sup> In CPA, the low-energy sub-1-ps pulses from an ultrafast oscillator are stretched in time to several hundred picoseconds or few nanoseconds. The energy of these pulses is increased in consecutive amplifier stages to the millijoule-(mJ) or even joule-level, while the peak power remains below the threshold of optical damage and pulse distortion in the amplifiers. After amplification, these pulses are recompressed to almost the original pulse duration, allowing to obtain ultrafast pulses with terawatt (TW) peak powers.<sup>2</sup> Countless major and minor improvements on Ti:sapphirebased CPA have been reported over the last three decades. To date, table-top, high-peak-power systems exceeding 100 TW operate in laboratories around the world and are commercially available. As a result, Ti:sapphire-based CPA systems are currently the dominant driving lasers for ultrafast, high-intensity experiments.

Further increases in performance have been challenging due to two effects. First, the amplification bandwidth of Ti:sapphire systems is limited to ~75 nm (FWHM) centered at 800 nm, and gain narrowing associated with amplification over several orders of magnitude further narrows the obtainable bandwidth. Thus, this effect must be compensated for in order to obtain sub-35-fs pulse duration from TW-scale systems. Spectral filtering techniques can be employed to enable compressed pulse durations as short as 15 to 30 fs depending on the level of amplification.<sup>3</sup> On the other hand, nonlinear propagation methods can be utilized to convert a portion of the output of these CPA systems to durations in the few-cycle pulse regime. Such schemes, including spectral broadening in hollow-core fibers<sup>4–6</sup> and filamentation-based self-compression,<sup>7–9</sup> have been employed to shorten the pulses to quasi-single-cycle duration with up to several mJ-level pulse energies resulting in peak powers at the 1 TW-level. The second limiting effect in Ti:sapphire CPA systems prohibits the output average power to be scaled beyond 30 to 40 W with cryogenically cooled amplifier stages.<sup>10</sup> Compensation of thermal effects and beam distortions become increasingly challenging at this performance level. High repetition rate systems have been presented operating with high average power, such as a system providing 26 W compressed with duration of >50 fs.<sup>11</sup>

Extending the concept of CPA, the method optical parametric chirped-pulse amplification (OPCPA) was first presented in 1992.<sup>12</sup> Similar to CPA, an ultrashort pulse is first stretched in time, amplified, and recompressed. In contrast to CPA, in which amplification is based on stimulated emission, OPCPA transfers energy from a pump beam to a seed beam in an optical parametric amplifier (OPA). The amplification bandwidth can span almost one octave supporting sub-10-fs pulse durations in the visible spectrum. These pulses are referred to as optical few-cycle pulses since their durations approach the duration of an optical cycle (2.66 fs at 800 nm wavelength). In contrast to traditional amplification via stimulated emission in pumped laser crystals, no energy is directly stored during the amplification process in the nonlinear material due to the instantaneous nature of the OPA process, thereby mitigating typical thermal effects and beam distortions, thereby facilitating power and

<sup>\*</sup>Address all correspondence to: Andreas Vaupel, E-mail: vaupel@creol.ucf.edu

energy scaling of the OPA systems. The pulses from tabletop OPCPA systems have been compressed to the few-cycle regime, with the nominal current record durations of 5.0 fs (1.7 cycles) at 0.88  $\mu$ m,<sup>13</sup> 10.5 fs (1.5 cycles) at 2.1  $\mu$ m,<sup>14</sup> 67 fs (6.3 cycles) at 3.2  $\mu$ m,<sup>15</sup> and 83 fs (6.4 cycles) at 3.9  $\mu$ m.<sup>16</sup> As will be discussed later, table-top OPCPA systems are primarily limited in terms of pulse energy and average power by the employed pump laser; however, onset of parasitic effects have been reported and will be discussed in Sec. 2.4. The records in terms of peak power [16 TW (Ref. 17)] and average power [22 W (Ref. 13)] indicate that the OPCPA method has matured to a performance level comparable to Ti:sapphire-based CPA systems, with the advantage of shorter pulse durations and wavelength tunability from the visible to mid-IR range.

Here, we give a detailed review of the current performance level and the prospects of table-top, few-cycle OPCPA systems based upon recent developments in table-top, high-energy, high-average-power picosecond laser systems. References 18, 19, and 20 provide excellent overviews on the traditional OPCPA architecture, while the OPA process itself has been reviewed comprehensively in Ref. 21, and essential parameters based on simulations for visible OPCPA based upon beta barium borate (β-BaB2O4; commonly referred to as BBO) crystals are presented in Ref. 22. Since the focus in this article is on the recent developments in table-top, few-cycle OPCPA, we intentionally disregard large-scale, petawatt- (PW) level OPCPA laser systems. A few example articles for further reading on PW-scale OPCPA systems include a prospective view in Ref. 23 and a presentation of a full system providing 300 TW in Ref. 24, while Refs. 25, 26, and 27 describe relevant PWlevel OPCPA designs.

#### 2 Table-Top, Few-Cycle OPCPA Systems

Several relevant concepts and trends in OPCPA are reviewed in the following sections, starting with an overview on the early pioneering work toward the generation of few-cycle pulses via OPA and OPCPA. The second section introduces the advantages, challenges, and limitations of few-cycle OPCPA, followed by a section highlighting the record performance levels demonstrated to date. The section concludes with a detailed discussion of the performance of representative OPCPA systems and their pump lasers.

#### **2.1** Pioneering Few-Cycle Optical Parametric Amplification

The OPCPA method was first presented in 1992 by Dubietis et al. with a system incorporating a stretcher, an OPA stage, and a compressor, resulting in energetic 70-fs pulses.<sup>12</sup> This development was followed rapidly with ground-breaking investigations toward the generation of intense few-cycle pulses. The pioneering work of Gale et al. in 1995 resulted in the presentation of the shortest pulse duration from a laser oscillator at this time with 13 fs and nanojoule-level pulse energy.<sup>28</sup> The authors also demonstrated the tunability of the sub-20-fs pulses from the megahertz optical parametric oscillator over a range from 590 to 666 nm center wavelength (see also Ref. 29). Hereafter, several groups investigated few-cycle OPA systems based upon BBO pumped by Ti:sapphire CPA systems enabling the generation of intense sub-10-fs pulses with wide tunability. In 1998, Nisoli et al.

employed two OPA stages in collinear configuration to generate 10-µJ-level pulses with 14.5 fs in the near-IR (center wavelength of 1.5  $\mu$ m),<sup>30</sup> and Cerullo et al. used a noncollinear configuration to generate visible sub-8-fs pulses with 2  $\mu$ J energy and bandwidth ranging from 510 to 800 nm.<sup>31</sup> In the same period, Wilhelm et al.<sup>32</sup> in 1997 and Riedle et al.<sup>33</sup> in 2000 reported 10-µJ-level, sub-20-fs pulses tunable from 470 to 750 nm and 870 to 1500 nm, respectively. Shirakawa et al. reported in 1998 on a compact noncollinear optical parametric amplification (NOPA) system amplifying pulses with 5  $\mu$ J pulse energy and 6.2 fs duration at 630 nm or 8.4 fs at 1.1  $\mu$ m, respectively,<sup>34</sup> and Kobayashi and Shirakawa presented in 2000 sub-5-fs pulses.<sup>35</sup> Further improvements on the latter system by Baltuška et al. in 2002 including an ultrashort, white-light, seed pulse and an adaptive pulse compressor enabled the generation of sub-4-fs pulses with 0.5  $\mu$ J pulse energy.<sup>3</sup> Since most of these pioneering few-cycle OPA implementations were driven by Ti:sapphire-based CPA systems with mJ-level pulse energy and kilohertz repetition rate, the generated few-cycle pulses were limited to the 100  $\mu$ J and 0.1 W average power-level. However, the impressive results in the late 1990s demonstrated the potential of energetic few-cycle pulses from OPA (Ref. 21) and lead to the development of few-cycle OPCPA systems driven by a variety of laser technologies, as shown in Sec. 2.6.

#### 2.2 Optical Parametric Chirped-Pulse Amplification

NOPA is capable of supporting the amplification of an almost-octave spanning bandwidth. Several parameters are critical in this process: nonlinear medium, phase-matching conditions, input angle, wavelengths, crystal thickness, and pump intensity. A schematic of the geometry is shown in Fig. 1(a) and a photograph of a laboratory implementation is shown in Fig. 1(b).

The most-commonly used OPCPA architecture for fewcycle pulses in the visible is based on BBO as nonlinear material. This approach has been used to generate the current record performances in terms of peak power and average power. Here, the pump wavelength ranges typically from 343 to 532 nm, depending on the pump lasers. The typical amplification bandwidth ranges from <725 to >1050 nm when pumped at 532 nm wavelength and 3 to 5 mm crystal lengths are employed.<sup>37</sup> This bandwidth supports a transform-limited duration of <8 fs or less than three optical cycles.<sup>38</sup> Additionally, octave-spanning bandwidth to support quasi-single-cycle pulses can be obtained by pumping consecutive OPA stages with different wavelengths. This is most easily done with different harmonics of the fundamental pump laser, i.e., 532 and 355 nm for Nd:YAG-based pumps or 515 and 343 nm for Yb-based pumps. This concept was introduced in 2010 with mJ-level pulses<sup>39</sup> and experimentally verified in a different setup in 2012 with microjoule-level pulse energies and compressed to 4.6-fs duration.4

The key parameters determining the parametric gain are the used pump intensity and the length of the crystal. Figure 2(a) shows example calculations for the parametric gain following the assumptions in Ref. 21 for BBO as nonlinear material. Pump intensities from 10 to 100 GW/cm<sup>2</sup> and crystal lengths from 1 to 5 mm are presented. It can be seen that a large parametric gain in excess of  $10^6$  can



**Fig. 1** (a) Schematic of the noncollinear optical parametric amplification (NOPA) geometry showing the geometry for pump, signal, and idler beam. (b) Laboratory picture of an optical parametric amplifier (OPA) setup with the green pump beam visible aligned through a BBO crystal.<sup>37</sup>



**Fig. 2** (a) Calculated parametric gain in dependence of the interaction length and the pump intensity. (b) Scaled<sup>44</sup> damage threshold<sup>45,46</sup> of BBO in the femtosecond to nanosecond range.

be obtained in these configurations. Experimentally, high parametric gains of  $10^3$  (Ref. 17),  $10^4$  (Ref. 41), or even  $10^6$  (Ref. 42) are typically employed in the first OPA stage of OPCPA systems, while a parametric gain of up to  $10^8$  has been experimentally demonstrated from a femtosecond OPA stage.<sup>43</sup> Figure 2(b) shows the scaled damage threshold in BBO based on the empirical squared root scaling law of the damage threshold with pulse duration<sup>44</sup> and values found in the literature.<sup>45,46</sup> It can be seen that sub-100-ps pulses are necessary to avoid damage and enable pump intensities of 10 GW/cm<sup>2</sup> and above.

On the other hand, it is well known that employing a shorter crystal has the benefit to relax requirements on the wave-vector mismatch for the OPA process. BBO crystals of several lengths have been utilized in the literature: for example, a single 1-mm-long BBO crystal for the amplification of sub-4-fs pulses<sup>36</sup> and two 2-mm-long crystals for the amplification of 5.0-fs pulses to  $87-\mu$ J pulse energy.<sup>41</sup> A combination of a 3-mm- and a 5-mm-long crystal has been used to amplify 5.7-fs pulses to  $3-\mu J$  pulse energy<sup>47</sup> and two 5-mm-long crystals to amplify 7.9-fs pulses to 130-mJ pulse energy.<sup>17</sup> In general, shorter crystals enable a wider phase-matching bandwidth and allow OPA stages to support almost-octave spanning bandwidths. In order to obtain the same gain from shorter crystals, higher pump intensities must be employed. A trend from reported OPCPA systems can be found in the utilization of short picosecond pump pulses, enabled by the recent developments in

Yb-based CPA laser technology providing high-energy, high-average-power pumps with 0.5- to 1-ps duration.

The energy transfer efficiency in OPCPA from pump to signal pulse is typically on the order of 10 to 15% and dependent on the amplified bandwidth. Generating the record table-top, few-cycle OPCPA pulse energy of 130 mJ required a pump pulse energy of 1.0 J at 532 nm wavelength,<sup>17</sup> and the record average power of 22 W required a pump laser with 120 W average power at 515 nm wavelength.<sup>13</sup> For OPCPA at 2.1 µm center wavelength, the current record efficiency is 6.7% with an amplified pulse energy of 0.74 mJ pumped by 11 mJ pulse energy at 1053 nm wavelength.<sup>48</sup> It is interesting to note that OPCPA compared to Ti:sapphire-based CPA is, in general, less efficient in terms of pump to signal conversion since Ti:sapphire systems operate with conversion efficiencies of 30 to 40%.<sup>49</sup> In addition, it is worth noting that the required lasers to pump Ti:sapphire are typically commercially available, Nd-based, master oscillator power amplifiers (MOPA) providing high energetic nanosecond pulses (5 to 10 ns). In contrast, OPCPA requires extremely stable picosecond pump lasers with high peak power. The performance of such pump lasers is the primary limitation upon scaling of pulse energy and/or average power in OPCPA systems.

#### 2.3 Traditional OPCPA Architecture

The amplification via OPCPA of few-cycle pulses typically follows the laser architecture<sup>21,23</sup> as shown in Fig. 3 and described in the following. The front-end of the OPCPA



**Fig. 3** Traditional optical parametric chirped pulse amplification (OPCPA) architecture in the visible based upon a sub-5-fs oscillator, a pulse stretcher, the broadband amplification in the OPA, and a compressor to retrieve almost the original pulse duration. The pump beam is typically derived from the front-end oscillator to ensure optical synchronization and utilizes in the pump beam generation multiple amplification stages resulting in a high-energetic picosecond pump pulse.

architecture is typically a mode-locked, octave-spanning Ti:sapphire oscillator covering the required amplification bandwidth.<sup>50</sup> However, a few OPCPA systems have been reported that utilize nonlinear spectral broadening of pulses from either a Ti:sapphire oscillator<sup>13,40</sup> or a Ti:sapphire-based CPA system<sup>17</sup> to seed the OPA. For center wavelengths different from the visible Ti:sapphire bandwidth, nonlinear frequency conversion based upon the octave-spanning Ti: sapphire bandwidth, typically via difference frequency generation (DFG)<sup>51,52</sup> or OPA,<sup>16</sup> has been employed to provide the seed pulses at various center wavelengths such as in the mid-IR. In addition, OPCPA systems seeded by stable white light filamentation in bulk material, such as a YAG plate generated by a portion of the typical sub-1-ps pump laser, have been reported.<sup>53–55</sup>

Pulse stretching for sub-10-fs pulses in the visible can be achieved with a grism stretcher, based on a combination of grating and prism pairs, an acousto-optical programmable dispersive filter (AOPDF) for phase fine-adjustments and compression in bulk glass compressor. This method has been shown to allow complete dispersion compensation over >300 nm bandwidth in the visible supporting sub-10-fs pulses<sup>56,57</sup> and has been numerically extended for sub-5-fs pulses.<sup>58</sup> For wavelengths in the IR, dispersive glasses can be utilized to up or down chirp the pulse and ultrashort pulse shapers such as AOPDF are commercially available.<sup>14,51</sup> Dispersion management becomes increasingly challenging for wavelengths >4  $\mu$ m and mainly grating/ grism pairs are used without adaptive shaping.<sup>59</sup>

In the traditional OPCPA architecture shown in Fig. 3, the pump laser is typically optically or electronically synchronized to the frond-end oscillator. The timing jitter requirement at the OPA stage ranges from sub-picosecond to 10 ps depending on the employed pulse durations, pulse shapes, and output stability requirements. The electronic synchronization has been presented for 60 ps pump pulse durations.<sup>60</sup> The optical synchronization is commonly preferred since its performance is typically better than the minimum requirement.<sup>61</sup> A jitter of several 100 fs from a pump scheme with sub-1-ps pulse duration has been reported as significant and was actively stabilized, since it otherwise induces fluctuations on the parametric gain, bandwidth, and center wavelength.<sup>62</sup> Recently, an investigation has shown that the obtainable carrier-envelope phase (CEP) stability also depends on the pump-to-signal timing jitter and a CEP-stabilization with 86 mrad has been realized associated with a residual pump-to-signal timing jitter of  $18 \pm 4$  fs with  $\sim 500$  fs pump pulse duration.<sup>6</sup>



**Fig. 4** The colored bars represent the few-cycle OPCPA bandwidth of reported systems for few different crystals, pump wavelengths, and phase matching condition. The gray bars represent the typical transparency range of the employed crystals. Note that the tuning range of the mentioned OPA stages can be larger than the indicated OPCPA bandwidths and extremely wide OPA tuning ranges covering the visible<sup>55</sup> to near-IR<sup>65</sup> and mid-IR<sup>66</sup> have been reported.

#### 2.4 Visible to Mid-IR Few-Cycle Pulses

A major advantage of OPCPA compared to its main competitor, the Ti:sapphire-based CPA, is the possibility to operate at center wavelengths spanning the near-IR to the mid-IR. This is achieved by the choice of a nonlinear crystal, pump wavelength, as well as phase-matching geometry. Several OPCPA systems have been presented operating with few-cycle durations covering almost continuously the spectrum from the visible ( $0.6 \mu m$ ) to the mid-IR ( $8 \mu m$ ), which are summarized in Fig. 4. The transparency ranges of the employed nonlinear crystals are given, which were found via the freely available software package SNLO (AS-Photonics, LLC, Albuquerque, New Mexico).<sup>64</sup>

A few crystal and wavelength combinations are detailed in the following. An OPCPA system has been presented in 2011, using MgO:PPLN (periodically poled lithium niobate) pumped at 1049 nm as well as a BBO crystal pumped at 1030 nm, providing parametric amplification from 1.8 to 2.5  $\mu$ m centered at 2.1  $\mu$ m.<sup>15,51</sup> After compression, this produced few-cycle pulses with 0.85 mJ pulse energy at 1 kHz with 32 fs duration (4.5 optical cycles). A comparable system has been presented pumped at 1053 nm with 49 ps using PPLN and BBO crystals.<sup>48</sup> This system operates with 15.7 fs duration (2 optical cycles) at 2.1  $\mu$ m center wavelength and 0.74 mJ energy. Further in the IR, a system has been presented operating at 3.2  $\mu$ m with 67 fs duration (6.3 optical cycles) and generating 3.8  $\mu$ J pulse energy at 100 kHz.<sup>15</sup> A system operating at 3.9  $\mu$ m was presented in 2011, which used KTA (Potassium Titanyl Arsenate, KTiOAsO4) crystals and produced pulses with 83 fs duration (7 optical cycles) and 8 mJ energy corresponding to 90 GW peak power.<sup>16</sup> The longest-wavelength OPCPA presented to date provided amplification from 4.1 to 7.9  $\mu$ m centered at 6  $\mu$ m.<sup>5</sup>

#### **2.5** Current Performance Level of Table-Top, Few-Cycle OPCPA

The performance of the reported OPCPA systems are listed in Table 1 and graphically represented in Fig. 5 with the year

Ref	Pulse energy	Average power	Pulse duration	Peak power	Center wavelength	Pump technology	Pump duration
38	90 mJ	0.9 W	10 fs	9.0 TW	0.8 <i>µ</i> m	Flashlamp	60 ps
60	16 mJ	0.47 W	7.6 fs	2.1 TW	0.8 <i>µ</i> m	Flashlamp	60 ps
65	200 <i>µ</i> J	0.2 W	15 fs	13 GW	1.5 μm	Ti:sapphire	50 fs
69	1.5 mJ	1.5 W	6.4 fs	230 GW	0.8 <i>µ</i> m	Ti:sapphire	100 ps
67	2.7 mJ	2.7 W	5.5 fs	490 GW	0.8 <i>µ</i> m	Ti:sapphire	75 ps
52	1.2 <i>μ</i> J	0.12 W	96 fs	13 MW	3.2 μm	DPSS	15 ps
42	220 <i>µ</i> J	0.22 W	23 fs	9.6 GW	2.2 μm	DPSS	12 ps
48	740 μJ	0.74 W	15.7 fs	47 GW	2.1 <i>µ</i> m	DPSS	49 ps
17	0.13 J	1.3 W	7.9 fs	16 TW	0.805 <i>µ</i> m	Flashlamp	78 ps
15	3.8 <i>μ</i> J	0.38 W	67 fs	56 MW	3.2 <i>µ</i> m	DPSS	8 ps
53	0.4 <i>μ</i> J	0.42 W	9.7 fs	43 MW	0.8 <i>µ</i> m	Fiber	0.42 ps
70	74 μJ	7.1 W	8.0 fs	9.3 GW	0.8 <i>µ</i> m	Fiber	0.78 ps
71	1.3 <i>μ</i> J	0.19 W	8.8 fs	150 MW	0.8 <i>µ</i> m	Thin-disk	1.6 ps
47	3 <i>µ</i> J	0.43 W	5.7 fs	530 MW	0.85 <i>µ</i> m	Thin-disk	1.6 ps
51	850 μJ	0.85 W	32 fs	27 GW	2.1 μm	Cryo SS	12 ps
41	87 μJ	2.61 W	5.4 fs	16 GW	0.8 <i>µ</i> m	Fiber	0.70 ps
16	8 mJ	0.16 W	83 fs	96 GW	3.9 <i>µ</i> m	Flashlamp	70 ps
13	22 μJ	22 W	5.0 fs	4.4 GW	0.88 <i>µ</i> m	Fiber	0.50 ps
14	1.2 mJ	3.6 W	10.5 fs	114 GW	2.1 <i>u</i> m	Thin-disk	1.6 ps

Table 1 List of selected optical parametric chirped pulse amplification (OPCPA) systems reported in the literature, which are graphically illustrated in Fig. 5. See Table 2 for the list of acronyms.



Fig. 5 Graphical overview of the performance of reported OPCPA systems. A color code is employed to emphasize the impact of the pump laser technology on the overall OPCPA performance. See Table 1 for the list of references and Table 2 for the list of acronyms.

of publication noted (see Table 2 for list of acronyms). All of these systems operate with few-cycle pulse duration with center wavelengths ranging from 0.8 to 3.9  $\mu$ m. A few outstanding record table-top OPCPA systems are listed in the following. The highest OPCPA peak power presented to date is 16 TW corresponding to 130 mJ and 7.9 fs duration with a contrast of  $10^{-12}$  for  $\pm 30$  ps.<sup>17</sup> The record pulse energy for repetition rates around 1 kHz is 2.7 mJ with 5.5 fs pulse duration corresponding to a peak power of 490 GW.<sup>67</sup> The highest average power was reported in Ref. 13 with 22 W at 1 MHz repetition rate and a nominal pulse duration of 5.0 fs corresponding to 1.7 optical cycles. Similar to other OPCPA publications with durations of 5.5 fs (Ref. 67) and 5.7 fs (Ref. 47), the reported central pulse of 5 to 6 fs duration is surrounded by side pulses, which potentially degrade pulse contrast and affect usability for high pulse intensity experiments.68

Even shorter pulse durations have been reported recently, employing different pump wavelengths in multiple OPA stages. This method enabled the generation of a waveform with a 4.6 fs duration, where two consecutive OPA stages pumped by the second harmonic generation (SHG) and third harmonic generation of the pump beam, respectively, resulted in an amplified bandwidth covering from 430 to

Table 2 List of acronyms and definitions.

Acronym	Definition
Flashlamp	Based upon flashlamp-pumped amplifiers
Ti:sapphire	Based upon Ti:sapphire-based amplifiers
DPSS	Based upon diode-pumped solid-state amplifiers
Fiber	Based upon Yb-doped fiber-based amplifiers
Thin-disk	Based upon Yb:YAG thin-disk amplifiers
Cryo SS	Based upon cryogenically cooled Yb-based solid-state amplifiers
MOPA	A system in master oscillator power amplifier configuration
CPA	A system in chirped-pulse amplification configuratior

1300 nm (-40 dB).<sup>40</sup> In a similar scheme, two separate OPCPA systems have been employed (covering a bandwidth from 0.75 to 1.1  $\mu$ m and 1.9 to 2.5  $\mu$ m) to synthesize a waveform with a central region of 0.8 cycles (FWHM) corresponding to 2.1 fs.<sup>72</sup> In contrast to these OPCPA systems with quasi-single-cycle pulses, visible sub-10-fs (Ref. 17) and near-IR sub-20-fs pulses<sup>42,48</sup> can provide a more uniform spectrum, with potentially increased temporal contrast in the femto- to picosecond range. The shortest duration reported from OPA itself is 4.0 fs at a 600 nm center wavelength corresponding to 2.0 optical cycles.<sup>36</sup> The lowest number of cycles reported is 1.5 at a center wavelength of 2.1  $\mu$ m.<sup>14</sup> Most of the record OPCPA performances were achieved when operated in the visible spectrum based upon BBO as a nonlinear medium.

Figure 5 employs a color code that relates the OPCPA performance to the utilized pump laser technology. It can be seen that high pulse energies, exceeding the 10 mJ-level, have only been achieved when pump lasers were employed based on flashlamp-pumped solid-state amplifiers. On the other hand, the highest average power regime demonstrations have utilized fiber and thin-disk pump lasers. For the range in between, several pump technologies have been employed providing comparable performance.

The reported OPCPA systems cover a wide parameter range due to the advantages of OPA and the absences of any stored energy in the nonlinear material (besides the parasitic effects discussed later in this paragraph). The latter is in contrast to traditional laser amplification based upon stimulated emission, in which a high amount of energy can be stored in the amplification medium resulting in thermally induced beam distortions, such as thermal lensing. For OPCPA, it seems that the performance is currently still scalable in terms of pulse energy and average power and that OPCPA is primarily limited by the performance of the employed pump lasers. It has been found recently that parasitic effects in the nonlinear crystal can lead to heat accumulation in the OPA stage of a high-averagepower system. In this context, the most dominate parasitic effect in BBO-based visible NOPA, as shown experimentally in Ref. 73, results from absorption of the idler beam. This is due to the limited transparency range, which covers in a 1cm-long BBO crystal the range from 0.2 to 2.6 µm for the 0.5 transmittance level, while the linear absorption value at 2.55  $\mu$ m is significant at 0.5 cm<sup>-1</sup>.<sup>74</sup> Thus, for visible NOPA covering the range from 625 to 950 nm, pumped at 515 nm and with generated idler beam ranging from 1.1 to 2.9  $\mu$ m, the nonvanishing absorption in BBO can become a limiting factor for further power scaling beyond the current level. In addition, the non-negligible linear absorption across the transparency range (for example, in BBO of 0.01 cm<sup>-1</sup> at 0.532 nm or 0.001 cm<sup>-1</sup> at 1.0  $\mu$ m)<sup>74</sup> or multiphoton absorption results in additional heat accumulation. This heat-affected zone in the OPA stage can impact the phase-matching condition and induce thermal lensing or potentially fracture/damage the OPA material. These novel thermally induced effects in OPA are under investigation in many research laboratories around the world. We expect several approaches to mitigate thermal effects in OPAs emerging from this research.

#### 2.6 Experimentally Demonstrated Pump Laser Schemes

Over the last seven years, several radically different pump laser schemes have been implemented as OPCPA pump lasers. Here, we review the progress of these laser systems and the influence on the OPCPA output performance. The performances of the pump lasers of the OPCPA systems from Fig. 5 are listed in Table 3 and graphically shown in Fig. 6 (see Table 2 for list of acronyms). The latter shows the pulse energy and average power of the employed pump lasers relative to the year of publication.

Several trends can be extracted from Fig. 6: It can be seen that the highest pulse energy has been achieved utilizing flashlamp-pumped solid-state amplifiers. Based on the performance shown in Fig. 6, flashlamp-pumped amplifiers are the only OPCPA-proven technology in this context that result in pump pulse energies >100 mJ, with a record energy of 1.5 J with 15 W average power. The pulse provided by the system had 110 ps duration corresponding to 14 GW



**Fig. 6** Performance of OPCPA pump lasers in terms of pulse energy and average power against the year of publication. The pump laser systems are differentiated by color code corresponding to their laser technology. See Table 3 for the list of references and Table 2 for the list of acronyms.

peak power at 1064 nm center wavelength.<sup>17</sup> This pump laser generated the current record performance in terms of pulse energy and peak power for table-top OPCPA systems with an output of 130 mJ and 16 TW, respectively. Other systems have been presented for OPCPA pumping, such as a 250mJ pulse energy system with 70 ps duration at 20 Hz repetition rate<sup>16</sup> and a system providing 160-mJ, 60-ps pulses at 30 Hz.<sup>60</sup> It can be seen that high pulse energy is achieved with this technology, but the corresponding average power is limited to the 20 W-level.

On the other side, the highest average power was demonstrated with a fiber-based pump laser system. This system operated at a repetition rate of 1 MHz providing 200 W average power and 200  $\mu$ J pulse energy at 1030 nm center wavelength with 0.47 ps duration before SHG to 515 nm to pump an OPCPA system.<sup>13</sup> This pump laser enabled the record OPCPA average power performance of 22 W with a peak power of 4.4 GW.<sup>13</sup>

Several systems have been presented providing both high pulse energy as well as high average power. The earliest systems were based on narrow-band, picosecond pump systems providing 10 mJ-level pulse energies at kilohertz repetition rate. In 2007, such a pump system based on Ti:sapphire amplifiers provided 4 and 10 mJ at 400 nm with ~70 ps duration.<sup>69</sup> A Nd:YLF regenerative and multistage amplifiers were used to generate 11 mJ at 1 kHz repetition rate with 49 ps duration.<sup>48</sup> A similar system of Nd:YLF regenerative and multipass amplifier was used to generate 7 mJ pulse energy with 110 ps duration, which was compressed to 12 ps and 4.5 mJ.<sup>42</sup> A commercial mode-locked Nd:YVO<sub>4</sub> system (Lumera Laser GmbH, Germany) producing 10 W at 100 kHz with 0.1 mJ pulse energy and 8.7 ps duration was the OPCPA pump laser in Ref. 52.

More recently, Yb-based CPA systems have been introduced as OPCPA pumps allowing significant increases in average power due to their superior thermal handling compared to Nd-based systems and reduction in pulse duration via CPA. A cryogenically cooled solid-state system has been used as OPCPA pump based on a Yb:YAG regenerative amplifier operating at 1 kHz, 13 mJ, 15 ps, 13 W.<sup>51</sup> A Yb:YAG thin-disk system has been used as a pump with 20 mJ at 1030 nm and 3 kHz, 1.6 ps duration.<sup>14</sup> The performance benefits of Ybbased CPA systems are highlighted in Sec. 3.3.

#### 3 Recent Developments on Picosecond, High-Energy, and High-Average-Power Lasers

This section reviews the recent progress in relevant laser technologies that will impact the performance of the OPCPA systems in the near future. The pump laser systems mentioned in Sec. 2.5 are listed in Table 3 and graphically shown in Fig. 7(a) in terms of pulse energy and average power. Similarly, the performances of several recently reported laser systems are listed in Table 4 and graphically shown in Fig. 7(b) (see Table 2 for list of acronyms). These two figures are placed next to one another in order to directly compare the performance of pump lasers that have been employed for OPCPA with that of recently reported picosecond laser systems. In addition, trends are identified in this chapter for the recently reported systems and the direct impact on the performance of OPCPA systems in the near future is discussed.



**Fig. 7** (a) Performances of the pump lasers of reported OPCPA systems in terms of pulse energy and average power. (b) Performance of recently demonstrated high-energy, high-average-power picosecond laser system. The laser systems are differentiated by color code corresponding to their laser technology. See Tables 3 and 4 for the list of references and Table 2 for the list of acronyms.

Ref.	Laser technology	Scheme	Pulse energy	Average power	Pulse duration	Peak power
38	Flashlamp	MOPA	1.15 J	11.5 W	110 ps	10 GW
60	Flashlamp	MOPA	250 mJ	7.5 W	85 ps	2.9 GW
65	Ti:sapphire	CPA	1.5 mJ	1.5 W	50 fs	30 GW
69	Ti:sapphire	MOPA	21 mJ	21 W	141 ps	150 MW
67	Ti:sapphire	MOPA	29 mJ	29 W	106 ps	273 MW
52	DPSS	MOPA	65 <i>µ</i> J	6.5 W	15 ps	4.3 MW
42	DPSS	MOPA	4.5 mJ	4.5 W	12 ps	380 MW
48	DPSS	MOPA	11 mJ	11 W	49 ps	225 MW
17	Flashlamp	MOPA	1.5 J	15 W	110 ps	14 GW
15	DPSS	MOPA	400 <i>µ</i> J	40 W	12 ps	33 MW
53	Fiber	CPA	9 <i>µ</i> J	9 W	420 fs	21 MW
70	Fiber	CPA	500 μJ	49 W	1.1 ps	460 MW
71	Thin-disk	CPA	40 <i>µ</i> J	5.7 W	1.56 ps	25 MW
47	Thin-disk	CPA	27 μJ	3.85 W	2.3 ps	12 MW
51	Cryo SS	CPA	16.5 mJ	16.5 W	12 ps	1.4 GW
41	Fiber	CPA	890 <i>µ</i> J	26.8 W	990 fs	900 MW
16	Flashlamp	MOPA	250 mJ	5 W	70 ps	3.6 GW
13	Fiber	CPA	120 <i>µ</i> J	120 W	500 fs	240 MW
14	Thin-disk	CPA	20 mJ	60 W	1.6 ps	12.5 GW

 Table 3
 List of the performances of the pump lasers employed in reported OPCPA systems (Fig. 5), which are graphically illustrated in Figs. 6 and

 7. See Table 2 for the list of acronyms.

#### **3.1** Flashlamp-Pumped and Diode-Pumped Solid-State MOPA Systems

The highest pulse energies from OPCPA systems have been reported when employing flashlamp-pumped solid-state amplifiers. The technology utilizes large-aperture Nd:YAG rods with large amounts of stored energy to reach joulelevel pulse energies with repetition rates of 30 Hz and lower. Based on the comparison here, no other laser technology has been used to obtain higher pulse energies. Since this technology offers compact optical setup, it is the most common path for the generation of ultrahigh-energy pulses and moderate average powers. Thus, the current record OPCPA peak power of 16 TW was enabled by flashlamppumped amplifiers in the pump beam generation. Higher average powers are generally prohibited by the low efficiency of flashlamp pumping and the associated demands on the high-voltage power supplies/switching electronics. As a consequence, this mature technology has been generally limited to 10 W-level average powers but with ultrahigh pulse energies at the joule-level.

A compromise between pulse energy and average power can be realized with diode-pumped solid-state amplifiers, such as Nd:YAG or Nd:YVO<sub>4</sub>. In this case, the average powers are sufficiently high that thermally induced lensing and depolarization must be compensated. A system has been demonstrated operating at 1 kHz with Nd:YAG amplifiers producing an output energy of 40 mJ, 48 ps duration and a corresponding average power of 40 W.<sup>94</sup> At higher repetition rates, a system has been presented operating with 33.7 W and 20 kHz with ~220 ps pulse duration corresponding to 7 MW peak power.<sup>103</sup> Another system has been demonstrated based on Nd: YVO<sub>4</sub> slab amplifier with 0.6 mJ pulse energy and 12 ps duration corresponding to an average/peak power between 46 W/38 MW and 30 W/50 MW.<sup>95</sup> All of these systems offer high performance with compact footprint due to the MOPA architecture.

#### 3.2 Yb:YAG Thin-Disk and Yb:Fiber CPA Systems

Compared to Nd-based amplifiers, the quantum defect is  $\sim 10\%$  in Yb:YAG whereas it is  $\sim 25\%$  in Nd:YAG, resulting in higher optical-to-optical efficiency and lower thermal load at comparable operational power. Several novel laser/amplifier configurations have been developed to reduce the thermal distortions. The thin-disk approach is one example in which a Yb:YAG crystal with few hundred micrometers thickness and few millimeters diameter is utilized. This heat removal scheme minimizes thermally induced beam distortions without the need for complex compensation. Extraction of up to 25 mJ at 3 kHz repetition rate with 1.6 ps duration

Ref.	Laser technology	Scheme	Pulse energy	Average power	Pulse duration	Peak power
75	DPSS	MOPA	130 <i>µ</i> J	5.3 W	19 ps	7 MW
76	DPSS	MOPA	123 <i>µ</i> J	12 W	6.8 ps	18 MW
77	Cryo SS	MOPA	3.7 μJ	287 W	5.5 ps	670 kW
78	Cryo SS	CPA	300 <i>µ</i> J	6 W	195 fs	1.5 GW
79	Thin-disk	CPA	25 mJ	75 W	1.6 ps	15 GW
80	Thin-disk	CPA	300 mJ	3 W	2 ps	150 GW
81	Cryo SS	MOPA	15 μJ	760 W	12 ps	1.2 MW
82	Cryo SS	CPA	6.5 mJ	13 W	15 ps	433 MW
83	DPSS	MOPA	3 mJ	30 W	25 ps	118 MW
84	DPSS slab	CPA	5.5 μJ	1.1 kW	610 fs	9 MW
85	Fiber	CPA	3.1 <i>µ</i> J	3.1 W	140 fs	22 MW
86	Fiber	CPA	11 <i>µ</i> J	830 W	0.64 fs	12 MW
87	Cryo SS	CPA	100 mJ	10 W	5 ps	20 GW
88	Cryo SS	CPA	12 mJ	60 W	1.6 ps	7.5 GW
89	DPSS	CPA	27 mJ	2.7 W	560 fs	48 GW
90	DPSS ceramic	CPA	130 mJ	1.3 W	450 fs	290 GW
91	DPSS	MOPA	1.8 mJ	8.8 W	28 ps	62 MW
92	DPSS	CPA	200 mJ	2 W	900 fs	222 GW
93	DPSS	MOPA	500 μJ	5 W	85 ps	5.8 MW
94	DPSS	MOPA	40 mJ	40 W	48 ps	833 MW
54	DPSS slab	CPA	20 mJ	250 W	830 fs	24 GW
95	DPSS slab	MOPA	600 <i>µ</i> J	30 W	12 ps	50 MW
96	Fiber	CPA	3 mJ	30 W	470 fs	6.4 GW
97	Fiber	CPA	2.2 mJ	11 W	500 fs	4.4 GW
98	Cryo SS	CPA	11 mJ	106 W	865 fs	12.3 GW
99	Cryo SS	CPA	1 J	100 W	5 ps	200 GW
100	DPSS	CPA	40 <i>µ</i> J	8 W	180 fs	220 MW
101	Fiber	CPA	3 <i>µ</i> J	3 W	50 fs	60 MW
102	Flashlamp	MOPA	300 ml	3 W	141 ps	2 1 GW

 Table 4
 List of the performances of high-energy, high-average-power picosecond laser systems reported over the last years, which satisfy the performance requirements to pump OPCPA. These systems are graphically illustrated in Fig. 7. See Table 2 for the list of acronyms.

has been presented.<sup>92</sup> However, due to the small thickness of the disk, the scheme has to overcome low pump absorption and low small signal gain (on occasion <1.1) with a high number of passes for pump and signal, such as 20 passes of the pump and 300 bounces in the case of regenerative amplifier reported in Ref. 92. A 15-pass amplifier was presented based on a thin-disk to amplify a 10-Hz burst of 80 pulses at 100 kHz repetition rate with 25 mJ per pulse.<sup>104</sup>

Recent progress in large-pitch photonic crystal fibers has allowed the increase of pulse energy in fiber amplifier systems to impressive levels. CPA systems based on such fibers have been already used as OPCPA pump with up to 200 W average power resulting in the current record OPCPA average power.<sup>13</sup> A similar performance has been shown from a system providing up to 830 W average and 10.6  $\mu$ J pulse energy with sub-picosecond pulse duration.<sup>86</sup> For higher

pulse energies, a similar fiber system has been employed to generate 2.2 mJ pulse energy with sub-ps duration<sup>97</sup> and 3 mJ when beam combining is utilized.<sup>96</sup> Thus, fiber amplifier based systems offer high average power performance in highly stable and compact architectures.

#### 3.3 Yb-Based Cryogenically Cooled Solid-State and Slab Systems

Several relevant properties of Yb:YAG improve when operating at cryogenic temperatures. The level scheme becomes an almost four-level minimizing reabsorption, the stimulated cross-section improves by  $\sim$ 5, while the thermal conductivity increases 2.5 to 4 times depending on the dopant level.<sup>81</sup> However, the emission linewidth and thus, the amplification bandwidths of these systems reduce to typically <1 nm, corresponding to a transform-limited pulse duration of  $\sim 5$  ps. A few cryogenically cooled systems have been presented, such as a system generating 287 W average power with 5.5 ps duration pulses corresponding to 3.7  $\mu$ J pulse energy. Another system has been reported based on cryogenically cooled, thick-disk, Yb:YAG producing up to 100 mJ at 100 Hz with a compressed duration of 5 ps.<sup>87</sup> The performance of the system has been further scaled to generate an output of 1 J pulse energy with 5 ps duration corresponding to 100 W average power.99 A system with a double- and single-pass amplifier was presented based on multiple thick Yb:YAG disks generating up to 15.2  $\mu$ J pulse energy with 760 W average power and 12 ps duration.<sup>81</sup>

Another scheme to reduce thermally induced aberrations is a slab amplifier. The beam multipasses through the slab offering lower thermal aberration compared to rod-type designs, high small signal gain as well as a compact design. One such system based on a Yb: YAG slab generated 0.64 ps pulses with up to 1.1 kW average power at 20 MHz corresponding to a peak power of 80 MW.<sup>84</sup> At 12.5 kHz repetition rate, a similar amplifier scheme has been used to generate 20 mJ pulse energy with 0.83 ps after postcompression corresponding to an average power of 250 W.<sup>54</sup>

#### 3.4 Trends and Impact for Few-Cycle OPCPA

The mentioned laser technologies are employed with a wide range of output parameters. Figure 7 shows the performance in terms of pulse energy and average power for some potential pump systems in contrast to those already employed for OPCPA pumping. It can be seen that novel laser technologies offer an order of magnitude improvement in average power relative to the performance employed to pump OPCPA systems to date. Although many of these new systems have not been characterized for the strict OPCPA requirements in terms of low noise, fluctuations, and jitter, the implementation of higher-average-power pump lasers is within reach.

A few notable pump lasers have been presented. For example, if the cryogenically cooled, Yb:YAG, thick-disk amplifier producing 1 J pulses with 5 ps duration<sup>99</sup> were employed as an OPCPA pump, few-cycle pulses could be generated with 100 mJ at 100 Hz corresponding to 10 W average power. Similarly, if the Yb:YAG slab amplifier producing 0.83 ps pulses with 20 mJ energy<sup>54</sup> were employed, an OPCPA output of 2 mJ at 12.5 kHz could be obtained. As a consequence, we expect to see a sharp increase of available pump power in the next years, enabling OPCPA with energies from 1 to 100 mJ and repetition rate from 100 Hz to 10 kHz outperforming Ti:sapphire-based CPA systems.

#### 4 Summary and Outlook

In this article, we have reviewed the concepts behind tabletop, few-cycle OPCPA as well as the current performance level obtained in research laboratories around the world. The current performance level of table-top OPCPA is primarily limited by the performance of the employed pump laser. Today, the OPCPA method has reached a performance level comparable to Ti:sapphire-based CPA technology with multi-10 TW peak power, mJ-level pulse energy at several kilohertz repetition rate, or ultra-high repetition rates with >20 W average power. Although thermal effects have been observed in the OPA, this is not yet a significant limit on average power scaling.

We also have presented an overview of recently reported high-energy, high-average-power, picosecond laser systems. Several promising laser systems have been presented, producing >100 W average power with high pulse energy and picosecond pulse duration. Thus, it seems feasible to obtain in the near future few-cycle pulses with multi-mJlevel energy in the visible, near-IR, or mid-IR via OPCPA at the 10 W average power level.

#### References

- D. Strickland and G. Mourou, "Compression of amplified chirped optical pulses," *Opt. Commun.* 55(6), 447–449 (1985).
   P. Maine et al., "Generation of ultrahigh peak power pulses by chirped pulse amplification," *IEEE J. Quantum Electron.* 24(2), 398–403 1988)
- 3. T. Tanabe et al., "Compensation for a transfer function of a regenerative amplifier to generate accurately shaped ultrashort pulses in both the amplitude and phase," *IEEE J. Sel. Topics Quantum Electron.* **10**(1), 221–228 (2004).
- 4. M. Nisoli et al., "A novel-high energy pulse compression system: generation of multigigawatt sub-5-fs pulses," Appl. Phys. B 65(2), 189-196 (1997).
- 5. T. Brabec and F. Krausz, "Intense few-cycle laser fields: frontiers of nonlinear optics," *Rev. Mod. Phys.* **72**(2), 545–591 (2000). S. Bohman et al., "Generation of 5.0 fs, 5.0 mJ pulses at 1 kHz
- using hollow-fiber pulse compression," Opt. Lett. 35(11), 1887-1889 (2010)
- 7. C. P. Hauri et al., "Generation of intense, carrier-envelope phaselocked few-cycle laser pulses through filamentation," Appl. Phys. B 79(6), 673-677 (2004)
- 8. G. Stibenz, N. Zhavoronkov, and G. Steinmeyer, "Self-compression of millijoule pulses to 7.8 fs duration in a white-light filament," Opt. Lett. **31**(2), 274–276 (2006).
- A. Mysyrowicz, A. Couairon, and U. Keller, "Self-compression of optical laser pulses by filamentation," *New J. Phys.* **10**(2), 025023 (2008).
- 10. I. Matsushima, H. Yashiro, and T. Tomie, "10 kHz 54 W Ti:sapphire regenerative amplifier as a pumping laser of a laser-plasma x-ray source," *Proc. SPIE* **7022**, 70220M (2008).
- 11. I. Matsushima, H. Yashiro, and T. Tomie, "10 kHz 40 W Ti:sapphire regenerative ring amplifier," Opt. Lett. 31(13), 2066-2068 (2006).
- 12. A. Dubietis, G. Jonušauskas, and A. Piskarskas, "Powerful femtosecond pulse generation by chirped and stretched pulse parametric amplification in BBO crystal," *Opt. Commun.* **88**(4-6), 437-440 (1992)
- (1992).
  13. J. Rothhardt et al., "Octave-spanning OPCPA system delivering CEP-stable few-cycle pulses and 22 W of average power at 1 MHz repetition rate," *Opt. Express* 20(10), 10870–10878 (2012).
  14. Y. Deng et al., "Carrier-envelope-phase-stable, 1.2 mJ, 1.5 cycle laser pulses at 2.1 μm," *Opt. Lett.* 37(23), 4973–4975 (2012).
  15. O. Chalus et al., "Six-cycle mid-infrared source with 3.8 μJ at 100 kHz," *Opt. Lett.* 35(19), 3204–3206 (2010).
  16. G. Andriukaitis et al., "90 GW peak power few-cycle mid-infrared pulses from an optical parametric amplifier," *Opt. Lett.* 36(15), 2755–2757 (2011).

- 2755-2757 (2011).
- 17. D. Herrmann et al., "Generation of sub-three-cycle, 16 TW light pulses by using noncollinear optical parametric chirped-pulse amplification," *Opt. Lett.* **34**(16), 2459–2461 (2009). 18. R. Butkus et al., "Progress in chirped pulse optical parametric ampli-
- fiers," Appl. Phys. B 79(6), 693-700 (2004).

- 19. A. Dubietis, R. Butkus, and A. P. Piskarskas, "Trends in chirped pulse optical parametric amplification," *IEEE J. Sel. Topics Quantum* Electron. 12(2), 163-172 (2006)
- 20. S. Witte and K. S. E. Eikema, "Ultrafast optical parametric chirpedpulse amplification," IEEE J. Sel. Topics Quantum Electron. 18(1), 296–307 (2012).
- 21. G. Cerullo and S. De Silvestri, "Ultrafast optical parametric ampli-
- fiers," *Rev. Sci. Instrum.* 74(1), 1–18 (2003).
  22. S. Witte et al., "Numerical simulations for performance optimization of a few-cycle terawatt NOPCPA system," *Appl. Phys. B* 87(4), 677–684 (2007).
- 23. I. N. Ross et al., "The prospects for ultrashort pulse duration and ultrahigh intensity using optical parametric chirped pulse amplifiers," *Opt. Commun.* 144(1–3), 125–133 (1997).
  24. O. V. Chekhlov et al., "35 J broadband femtosecond optical parametric
- chirped pulse amplification system," Opt. Lett. 31(24), 3665-3667 (2006).
- I. N. Ross et al., "Analysis and optimization of optical parametric chirped pulse amplification," J. Opt. Soc. Am. B 19(12), 2945–2956 (2002).
- 26. C. N. Danson et al., "Vulcan petawatt: design, operation and interactions at 5 × 10<sup>20</sup> W cm<sup>-2</sup>," *Laser Part. Beams* 23(1), 87–93 (2005).
  27. O. Novák et al., "Design of a petawatt optical parametric chirped pulse
- amplification upgrade of the kilojoule iodine laser PALS," Laser Part. Beams 31(02), 211-218 (2013).
- 6. M. Gale et al., "Sub-20-fs tunable pulses in the visible from an 82-MHz optical parametric oscillator," *Opt. Lett.* **20**(14), 1562–1564 28. (1995)
- 29. G. M. Gale, F. Hache, and M. Cavallari, "Broad-bandwidth parametric amplification in the visible: femtosecond experiments and simulations," IEEE J. Sel. Topics Quantum Electron. 4(2), 224-229 (1998).
- M. Nisoli et al., "Parametric generation of high-energy 14.5-fs light pulses at 1.5 µm," *Opt. Lett.* 23(8), 630–632 (1998).
   G. Cerullo et al., "Sub-8-fs pulses from an ultrabroadband optical parametric amplifier in the visible," *Opt. Lett.* 23(16), 1283–1285 (1998).
   T. Wilhelm, J. Piel, and E. Riedle, "Sub-20-fs pulses tunable across the visible form a blue nummed since a pass a parametrized parametric para
- T. Wilhelm, J. Piel, and E. Riedle, "Sub-20-fs pulses tunable across the visible from a blue-pumped single-pass noncollinear parametric converter," *Opt. Lett.* 22(19), 1494-1496 (1997).
   E. Riedle et al., "Generation of 10 to 50 fs pulses tunable through all of the visible and the NIR," *Appl. Phys. B* 71(3), 457-465 (2000).
   A. Shirakawa, I. Sakane, and T. Kobayashi, "Pulse-front-matched opti-cal parametric amplification for sub-10-fs pulse generation tunable in the visible and near infrared," *Opt. Lett.* 23(16), 1292-1294 (1998).
   T. Kobayashi and A. Shirakawa, "Tunable visible and near-infrared pulse generator in a 5 fs regime," *Appl. Phys. B* 70(1), 239-246 (2000).
   A. Baltuška, T. Fuji, and T. Kobayashi, "Visible pulse compression to 4 fs by optical parametric amplification and programmable dispersion

- 4 fs by optical parametric amplification and programmable dispersion control," Opt. Lett. 27(5), 306-308 (2002).
- M. Hemmer, A. Vaupel, and M. Richardson, "Current status of the 37. HERACLES, a millijoule level, multi kHz, few-cycle, and CEP stab-lized OPCPA system," in *Conf. on Lasers and Electro-Optics and* Quantum Electronics and Laser Science, pp. 1-2, Optical Society of America (2010).
- F. Tavella, A. Marcinkevicius, and F. Krausz, "90 mJ parametric chirped pulse amplification of 10 fs pulses," *Opt. Express* 14(26),
- 12822–12827 (2006).
  39. D. Herrmann et al., "Approaching the full octave: noncollinear optical parametric chirped pulse amplification with two-color pumping," *Opt. Express* 18(18), 18752–18762 (2010).
- 40. A. Harth et al., "Two-color pumped OPCPA system emitting spectra spanning 1.5 octaves from VIS to NIR," *Opt. Express* 20(3), 3076– 3081 (2012).
- 41. S. Hädrich et al., "High-repetition-rate sub-5-fs pulses with 12 GW peak power from fiber-amplifier-pumped optical parametric chirped-pulse amplification," *Opt. Lett.* **36**(3), 313–315 (2011).
- 42. J. Moses et al., "Highly stable ultrabroadband mid-IR optical parametric chirped-pulse amplifier optimized for superfluorescence suppres-V. Krylov et al., "Efficient noncollinear parametric amplification of
- V. Krylov et al., "Efficient noncollinear parametric amplification of weak femtosecond pulses in the visible and near-infrared spectral range," *Opt. Lett.* 23(2), 100–102 (1998).
   B. C. Stuart et al., "Nanosecond-to-femtosecond laser-induced break-down in dielectrics," *Phys. Rev. B* 53(4), 1749–1761 (1996).
   H. Nakatani et al., "Laser-induced damage in beta-barium metaborate," *Appl. Phys. Lett.* 53(26), 2587 (1988).
   C. Chen et al., "New nonlinear-optical crystal: LiB3O5," *J. Opt. Soc. Am. B.* 6(A) 616–621 (1989).

- Am. B 6(4), 616–621 (1989). 47. M. Schultze et al., "Multi- $\mu$ J, CEP-stabilized, two-cycle pulses from
- an OPCPA system with up to 500 kHz repetition rate," *Opt. Express* **18**(26), 27291–27297 (2010).
- 48. X. Gu et al., "Generation of carrier-envelope-phase-stable 2-cycle 740-μJ pulses at 2.1-μm carrier wavelength," *Opt. Express* 17(1), 62–69 (2009).
  49. S. Backus et al., "High power ultrafast lasers," *Rev. Sci. Instrum.* 69(3),
- 1207–1223 (1998).
- R. Ell et al., "Generation of 5-fs pulses and octave-spanning spectra directly from a Ti:sapphire laser," *Opt. Lett.* 26(6), 373–375 (2001).

- 51. K.-H. Hong et al., "High-energy, phase-stable, ultrabroadband kHz OPCPA at 2.1 μm pumped by a picosecond cryogenic Yb:YAG laser," *Opt. Express* **19**(16), 15538–15548 (2011).
- 52. O. Chalus et al., "Mid-IR short-pulse OPCPA with micro-joule energy at 100 kHz," Opt. Express 17(5), 3587-3594 (2009).
- 53. M. Emons et al., "Sub-10-fs pulses from a MHz-NOPA with pulse energies of 0.4 μJ," *Opt. Express* 18(2), 1191–1196 (2010).
  54. M. Schulz et al., "Yb:YAG Innoslab amplifier: efficient high repetition
- 54. M. Schubzeera, "10:1740 humoinds and amplified: encloted high repetition in a subpicosecond pumping system for optical parametric chirped pulse amplification," *Opt. Lett.* **36**(13), 2456–2458 (2011).
  55. C. Homann et al., "Octave wide tunable UV-pumped NOPA: pulses down to 20 fs at 0.5 MHz repetition rate," *Opt. Express* **16**(8), The subpicore of the sub
- 5746-5756 (2008).
- 56. D. M. Gaudiosi et al., "Multi-kilohertz repetition rate Ti:sapphire amplifier based on down-chirped pulse amplification," Opt. Express 14(20), 9277–9283 (2006). 57. F. Tavella et al., "Dispersion management for a sub-10-fs, 10 TW opti-
- cal parametric chirped-pulse amplifier," *Opt. Lett.* **32**(15), 2227–2229 (2007).
- 58. T. H. Dou et al., "Dispersion control with reflection grisms of an ultrabroadband spectrum approaching a full octave," Opt. Express 18(26), 27900-27909 (2010).
- 59. S. Alisauskas et al., "Micro-joule octave spanning pulses at 6  $\mu$ m from a hybrid femtosecond OPA," in *Lasers, Sources, and Related Photonic Devices*, Paper AM1A.6, Optical Society of America (2012). 60. S. Witte et al., "A source of 2 terawatt, 2.7 cycle laser pulses based
- on noncollinear optical parametric chirped pulse amplification,' Opt. Express 14(18), 8168-8177 (2006).
- C. Y. Teisset et al., "Soliton-based pump-seed synchronization for few-cycle OPCPA," *Opt. Express* 13(17), 6550–6557 (2005).
   S. Klingebiel et al., "Experimental and theoretical investigation of for the synchronization of the
- timing jitter inside a stretcher-compressor setup," *Opt. Express* 20(4), 3443–3455 (2012).
  63. S. Hädrich et al., "Improving carrier-envelope phase stability in optical
- b. Thatter et al., "Indicate the entry of phase stability in optical parametric chirped-pulse amplifiers by control of timing jitter," *Opt. Lett.* **37**(23), 4910–4912 (2012). AS-Photonics, "SNLO," http://www.as-photonics.com/ (1 July 2013). C. Vozzi et al., "High-energy, few-optical-cycle pulses at 1.5  $\mu$ m with passive carrier-envelope phase stabilization," *Opt. Express* **14**(21), 1450–1260.

- 66. G. Cirmi et al., "Carrier-envelope phase stable, few-optical-cycle pulses tunable from visible to near IR," *J. Opt. Soc. Am. B* 25(7), B62 (2008).
- 67. S. Adachi et al., "5-fs, multi-mJ, CEP-locked parametric chirped-pulse amplifier pumped by a 450-nm source at 1 kHz," *Opt. Express* **16**(19), 8168–8177 (2008).
- 68. J. M. Mikhailova et al., "Ultra-high-contrast few-cycle pulses for multipetawatt-class laser technology," Opt. Lett. 36(16), 3145-3147  $(201\bar{1})$
- (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  (2011).
  <
- more than 1 microJ of pulse energy," Opt. Express 18(3), 2836-2841 (2010).
- S. Huang et al., "High-energy pulse synthesis with sub-cycle wave-form control for strong-field physics," *Nat. Photonics* 5(8), 475– 479 (2011)
- J. Rothhardt et al., "Thermal effects in high average power optical parametric amplifiers," *Opt. Lett.* 38(5), 763–765 (2013).
   D. N. Nikogosyan, *Nonlinear Optical Crystals: A Complete Survey*,
- Chapter 2, Springer Science+Business Media, Inc., New York (2005).
   75. M. Siebold et al., "A high-average-power diode-pumped Nd:YVO<sub>4</sub> regenerative laser amplifier for picosecond-pulses," *Appl. Phys. B* 78(3-4), 287-290 (2004).
- 76. J. Kleinbauer, R. Knappe, and R. Wallenstein, "13-W picosecond Nd:YVO4 regenerative amplifier with 200-kHz repetition rate, *Appl. Phys. B* **81**(2–3), 163–166 (2005). 77. K.-H. Hong et al., "Generation of 287 W, 5.5 ps pulses at 78 MHz
- repetition rate from a cryogenically cooled Yb:YAG amplifier seeded by a fiber chirped-pulse amplification system," Opt. Lett. 33(21), 24473–2475 (2008).
- A. Pugźlys et al., "Multi-mJ, 200-fs, cw-pumped, cryogenically cooled, Yb, Na:CaF<sub>2</sub> amplifier," *Opt. Lett.* 34(13), 2075–2077 (2009)
- 79. T. Metzger et al., "High-repetition-rate picosecond pump laser based In McDirect et al., "High repetition rate prosecond pump near based on a Yb:YAG disk amplifier for optical parametric amplification," *Opt. Lett.* 34(14), 2123–2125 (2009).
   J. Tümmler et al., "High-repetition-rate chirped-pulse-amplification thin-disk laser system with joule-level pulse energy," *Opt. Lett.* 34(9),
- 1378-1380 (2009).
- 81. D. C. Brown et al., "High sustained average power cw and ultrafast Yb:YAG near-diffraction-limited cryogenic solid-state laser," Opt. Express 18(24), 24770-24792 (2010).

- K.-H. Hong et al., "High-energy, kHz-repetition-rate, ps cryogenic Yb:YAG chirped-pulse amplifier," *Opt. Lett.* 35(11), 1752–1754 (2010).
- J. Fu et al., "Picosecond laser system with 30-W average power via cavity dumping and amplifying," *Laser Phys.* 21(6), 1042–1046 (2011).
   P. Russbueldt et al., "Compact diode-pumped 1.1 kW Yb:YAG Innoslab femtosecond amplifier," *Opt. Lett.* 35(24), 4169–4171 (2010).
   H. Kalaycioglu et al., "Microjoule-energy, 1 MHz repetition rate for a few formula for a set of the set of the
- pulses from all-fiber-integrated nonlinear chirped-pulse amplifier,' *Opt. Lett.* **35**(7), 959–961 (2010). 86. T. Eidam et al., "Femtosecond fiber CPA system emitting 830 W aver-
- age output power," *Opt. Lett.* **35**(2), 94–96 (2010). 87. A. H. Curtis et al., "Demonstration of a compact 100 Hz, 0.1 J, diode-
- pumped picosecond laser," *Opt. Lett.* **36**(11), 2164–2166 (2011). 88. D. A. Rand et al., "Picosecond pulses from a cryogenically cooled,
- composite amplifier using Yb:YAG and Yb:GSAG," Opt. Lett. 36(3), 340-342 (2011).
- B. D. N. Papadopoulos et al., "Broadband high-energy diode-pumped Yb:KYW multipass amplifier," *Opt. Lett.* 36(19), 3816–3818 (2011).
   M. Suzuki et al., "Hundred mJ, sub-picoseconds, high temporal con-trast OPCPA/Yb:YAG ceramic thin disk hybrid laser system," *Appl.* Phys. B 105(2), 181-184 (2011).
- H. Lin et al., "High-power picosecond regenerative amplifier based on CW diode side-pumped Nd:YAG with high beam quality," *Chinese* Opt. Lett. 9(8), 081404 (2011).
- S. Klingebiel et al., "High energy picosecond Yb:YAG CPA system 92 at 10 Hz repetition rate for pumping optical parametric amplifiers,' pt. Express 19(6), 5357–5363 (2011).
- 93. M. Hemmer et al., "OPCPA pump laser based on a regenerative amplifier with volume Bragg grating spectral filtering," Appl. Phys. B 106(3), 599-603 (2012)
- 94. K. Michailovas, V. Smilgevicius, and A. Michailovas, "Kilohertz rate K. Michailovas, V. Smilgevicius, and A. Michailovas, "Kilonertz rate picosecond pulses amplifier for pumping of OPCPA system," in *Lasers, Sources, and Related Photonic Devices*, Paper AW4A3, Optical Society of America (2012).
   C. Heese et al., "High-energy picosecond Nd: YVO<sub>4</sub> slab amplifier for OPCPA pumping," *Appl. Phys. B* 103(1), 5–8 (2011).
   A. Klenke et al., "Coherently-combined two channel femtosecond
- fiber CPA system producing 3 mJ pulse energy," Opt. Express 19(24), 24280-24285 (2011).
- T. E. Gidam et al., "Fiber chirped-pulse amplification system emitting 3.8 GW peak power," *Opt. Express* 19(1), 255–260 (2011).
   D. E. Miller et al., "Sub-picosecond pulses at 100 W average power
- from a Yb: YLF chirped-pulse amplification system," Opt. Lett. 37(13), 2700-2702 (2012).
- 99. B. A. Reagan et al., "Demonstration of a 100 Hz repetition rate gainsaturated diode-pumped table-top soft x-ray laser," Opt. Lett. 37(17),
- 3624–3626 (2012). 100. G. H. Kim et al., "High average-power ultrafast CPA Yb:KYW laser system with dual-slab amplifier," Opt. Express 20(4), 3434-3442 (2012).
- 101. L. Daniault et al., "High peak-power stretcher-free femtosecond fiber amplifier using passive spatio-temporal coherent combining," *Opt. Express* 20(19), 21627–21634 (2012).
  102. J. Adamonis et al., "High-energy Nd:YAG-amplification system for OPCPA pumping," *Quantum Electron.* 42(7), 567–574 (2012).

- 103. M. Lührmann et al., "High energy cw-diode pumped Nd: YVO4 regenerative amplifier with efficient second harmonic generation," *Opt. Express* **17**(25), 22761–22766 (2009). 104. M. Schulz et al., "Pulsed operation of a high average power Yb:YAG
- thin-disk multipass amplifier," Opt. Express 20(5), 5038-5043 (2012).

Andreas Vaupel received the degrees diploma-physicist in 2008 from the Philipps University Marburg, Germany, and MS (optics) from the University of Central Florida in 2009. Currently, he is a graduate research assistant in CREOL at the University of Central Florida and expected to receive a PhD (optics) in 2013. He developed OPCPA and picosecond laser systems. As a visiting student at the University Bordeaux 1, France, he worked on high-power OPCPA systems and fiber-based lasers.

Nathan Bodnar received a BS degree (electrical engineering) and a MS degree (optics) from the University of Central Florida in 2010 and 2013, respectively. He is currently working as a graduate research assistant on his PhD degree in electrical engineering at the University of Central Florida. His research topics include novel methods in ultrafast laser development and EUV target control systems. He has extensive experience with the CEP stabilization of fewcycle OPCPA systems.

Benjamin Webb received a BS degree (electrical engineering) from Lamar University in 2009 and a MS degree (optics) from the University of Central Florida in 2011. He is currently a graduate research assistant in CREOL at the University of Central Florida. In 2013, he was awarded a graduate research excellence fellowship from the University of Central Florida. He works in the development of highpower ultrafast lasers using optical parametric chirped pulse amplification (OPCPA).

Lawrence Shah received his MS and PhD degrees (optical physics) from the University of Central Florida in 1999 and 2001, respectively. He has over 10 years experience in solid-state and fiber lasers, has been awarded seven patents and has authored many peer-reviewed publications. He leads the laser development efforts within LPL on Tm:fiber lasers, and Yb:thin-disk lasers. He also advises on the development of OPCPA lasers for the generation of high-intensity quasisingle-cycle optical pulses.

Martin Richardson graduated from Imperial College, London, (physics) and received a PhD (photon physics) from London University. Thereafter, he worked at the National Research Council Laboratories in Ottawa and joined the University of Rochester in 1980. In 1990, he established the LPL in CREOL at the University of Central Florida. He has held visiting scientific positions, published over 400 scientific articles in professional scientific journals, and presented numerous invited and plenary talks.