

AD-A024383

Pitman

AD

USADAC TECHNICAL LIBRARY
 eltaub
 5 0712 01016823 4

FA-TR-76021

ADA024383

REDUCTION OF TARGET DETECTABILITY BY
LASER PROTECTIVE MATERIALS.

TECHNICAL
LIBRARY

April 1976

Approved for public release; distribution unlimited.



Pitman-Dunn Laboratory

U.S. ARMY ARMAMENT COMMAND
FRANKFORD ARSENAL
PHILADELPHIA, PENNSYLVANIA 19137

DISPOSITION INSTRUCTIONS


Destroy this report when it is no longer needed. Do not return it to the originator.

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER FA-TR-76021	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) REDUCTION OF TARGET DETECTABILITY BY LASER PROTECTIVE MATERIALS		5. TYPE OF REPORT & PERIOD COVERED Technical Research Report
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) DR. GERALD C. HOLST		8. CONTRACT OR GRANT NUMBER(s)
9. PERFORMING ORGANIZATION NAME AND ADDRESS FRANKFORD ARSENAL ATTN: SARFA-PDS-P PHILADELPHIA, PA 19137		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS AMCMS CODE: 611102.11.H46. F1.00 DA PROJECT: 1T161102AH46
11. CONTROLLING OFFICE NAME AND ADDRESS USA ECOM FT. MONMOUTH NJ 07703		12. REPORT DATE APRIL 1976
		13. NUMBER OF PAGES 24
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		15. SECURITY CLASS. (of this report) UNCLASSIFIED
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Laser Safety Laser Goggles Anti-Laser Goggles Target Detectability Laser Protection		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) Target detectability has been measured as a function of target size and luminance levels. The reduction of detectability by laser safety goggles (American Optical Model 585 and Glendale Optical Model LGS-R) has been determined for achromatic targets. The effects of target color rendition are considered. Luminous transmission appears to be the most important parameter for detection. Blue targets, either natural or rendered blue by protective materials, require more contrast for detection.		

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)



SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

TABLE OF CONTENTS

	<u>PAGE</u>
INTRODUCTION.....	3
THEORY.....	3
EXPERIMENTAL.....	8
RESULTS.....	10
DISCUSSION.....	10
SUMMARY.....	16
REFERENCES.....	17
DISTRIBUTION.....	19

LIST OF TABLES

TABLE

1. Relative Values of B_1	8
2. Relationship Between Various Luminance Levels Used.....	9

LIST OF ILLUSTRATIONS

FIGURE

1. Chromatic Difference of Focus (from Reference 3).....	4
2. Relative Responses of the Three Neural Color Opponent Processes. The Positive Values Indicate an Increased Firing Rate of the Neurons. A Negative Value Indicates a Decreased Firing Rate Relative to the Resting (Spontaneous) Firing Rate.....	6
3. Spectral Transmission of the American Optical Model 585 Ruby Goggle and the Glendale Optical Model LGS-R Ruby Goggle.....	7
4. Schematic of Experimental Setup.....	9

LIST OF ILLUSTRATIONS (Cont'd)

<u>FIGURE</u>	<u>PAGE</u>
5. Target-Background Contrast Required for 50% Probability of Detection as a Function of Range and Target Diameter d with Background Luminance of 1700 FT-L.....	11
6. Target-Background Contrast Required for 50% Probability of Detection as a Function of Range and Target Diameter d with Background Luminance of 500 FT-L.....	11
7. Target-Background Contrast Required for 50% Probability of Detection as a Function of Range and Target Diameter d with Background Luminance of 106 FT-L.....	12
8. Target-Background Contrast Required for 50% Probability of Detection as a Function of Range and Target Diameter d with Background Luminance of 56 FT-L.....	12
9. Target-Background Contrast Required for 50% Probability of Detection as a Function of Range and Target Diameter d with Background Luminance of 12 FT-L.....	13
10. Target-Background Contrast Required for 50% Probability of Detection as a Function of Range and Target Diameter d with Background Luminance of 3.2 FT-L.....	13
11. Target-Background Contrast Required for 50% Probability of Detection as a Function of Range and Target Diameter d with Background Luminance of 0.67 FT-L.....	14
12. Target-Background Contrast Required for 50% Probability of Detection as a Function of Range and Target Diameter d with Background Luminance of 0.35 FT-L.....	14
13. Target-Background Contrast Required for 50% Probability of Detection as a Function of Background Intensity for a Target Subtending 6.6 Minutes of Arc.....	15

INTRODUCTION

An ideal laser protection material will provide the required optical density at the laser wavelength and be transparent at all other wavelengths. Practical bulk absorbers are broad band absorbers which greatly reduce the transparency. The degree of transparency is specified by the luminous transmission which is the integrated effect of the spectral transmission on the standard photopic observer. The luminous transmission is a useful figure for neutral density filters which uniformly reduce the intensity of a scene. It does not describe the spectral characteristics of the material and therefore is perhaps a misleading parameter for laser protective materials. It does not relate how visual functions such as color discrimination, intensity discrimination, detection and identification may be affected.

A "quality factor" or "figure of merit" has been used to assess the perceived image of infrared systems¹ and photographic pictures². The factor combines the image sharpness and system background noise with the eye's ability to resolve images. The factor is extremely useful for black and white displays where the eye detects luminance changes only. With colored images the eye will detect differences in color even if the luminance is constant. The quality factors used by Synder¹ or Granger² must then be expanded to include color contrast.

Although there are many ways to formulate a quality factor, the present study examines a method of combining luminous transmission with the detectability of low contrast targets.

The present study examines how detectability of low contrast targets is affected by two popular ruby laser protectors (American Optical Corp., Model 585; and Glendale Optical Co., Model LGS-R). In order to study the effect of color rendition only, neutral density filters were used to equate the luminous transmission of the two goggles. Theoretical considerations of how these goggles might perform is given. To obtain the effects of protective materials on detectability, the contrast required for the detection of various achromatic targets was measured. The targets consisted of fourteen gratings which subtended visual angles from 2.26 minutes per line pair up to 68.4 minutes per line pair.

THEORY

Contrast sensitivity functions depend upon, (a) the optical modulation transfer function of the eye responsible for image formation on the retina, (b) retinal topology, and (c) higher neural interactions. We will consider each in turn.

The primary chromatic aberration of the eye is longitudinal chromatic aberration. When viewing white light, the eye optimally focuses on one wavelength and all other wavelengths are more or less out of focus. As shown in Figure 1, this optimal focus is about 575 nm.³ Optimal focusing leads to maximum visual acuity. The focus difference in the red (from 575 nm to 700 nm) is small. However in the blue (400 nm to 500 nm) the difference is large. Clearly, blue targets in a normal environment (i.e., if white light controls the focus) will be somewhat out of focus and thereby more difficult to recognize.




Figure 1. Chromatic Difference of Focus (from Reference 3).

If a relatively narrow spectral band of illumination is used one might suppose the eye focuses roughly in the center of that band. Since the eye exhibits lower acuity in the blue we may assume that the eye will always attempt for maximum focus and thereby focus at wavelengths close to 575 nm rather than in the center. For the laser safety goggles under consideration, one appears blue and the other green. The maximum transmission for LGS-R occurs at 475 nm whereas it is 520 nm for A0585. From purely chromatic aberration considerations we might assume that detection would be poor when using the LGS-R goggle.

However, in monochromatic light, except in the deep blue the eye is able to focus properly if corrective lenses are used.⁴ But Porkorny,

et al.⁵ has shown that even with corrective lenses visual acuity is lower in the blue (465 nm) which he attributes to complex retinal and neural factors.

Green⁶ has shown that for equal luminance targets, short wavelength (blue) targets require higher contrast to be detected. This he attributed to the fact that there are few blue cones in the retina.

Granger carries this one step farther into the neural processing of the eye. He⁷ has shown that the neural yellow-blue system is less efficient in detection than the neural red-green system. In contrast, Farnsworth⁸ has shown that for detection of small targets, the eye suffers small-field tritanopia. This means that the yellow-blue system is unimportant at threshold. Furthermore Judd and Eastman⁹ state that the effect of the R-G system is reduced by a factor of 10 at threshold. Thus the W-B1 system is the most important system. To account for the increased contrast required in the blue region of the spectrum, Judd and Eastman show that the inherent chromatic aberrations of the eye account for 82% of the difference in detectability. The approach of Judd and Eastman's allows one to calculate the visibility of targets from the spectral content of the target and background but does not include the effect of target size.

All researchers arrive at the same end point: blue targets require higher contrast for detection. It is a combination of, (a) inherent aberrations, (b) neural processing that causes the yellow-blue system to be either ineffective or inefficient, and (c) lack of blue cones.

Although many methods may be used to calculate a "quality factor", we will follow Granger's⁷ approach. The data presented is insufficient to justify this quality factor as the only unique approach. But the calculations will demonstrate the rationale involved.

The eye's neural system appears to follow a color opponent system.¹⁰ The chromatic responses, white-black, red-green and yellow-blue systems, are related to the CIE tristimulus values by,

$$W-B1 = Y$$

$$R-G = X-Y$$

$$Y-B = 0.4X - 0.4Z$$

Note that the W-B1 system is identical to the CIE photopic observer (Figure 2).

If different colored low contrast images excite the W-B1 system equally, then according to Granger, the image whose spectral component excites the R-G system maximally will have the highest probability of detection. Any image whose spectral components excite the Y-B system maximally will have a smaller probability of detection.




Figure 2. Relative Responses of the Three Neural Color Opponent Processes. The Positive Values Indicate an Increased Firing Rate of the Neurons. A Negative Value Indicates a Decreased Firing Rate Relative to the Resting (Spontaneous) Firing Rate.

The relationship between contrast sensitivity and luminous transmission is not fully understood. However Granger and Heurtley¹¹ proposed a color image quality factor which correlated with subjectively perceived quality assessment of color images. This factor is represented as,

$$Q = \sum_i C_{fi} B_i W_i$$

where,

$$B_i = \sum_{\lambda} T_{\lambda} S_{\lambda} R_{\lambda i} \Delta\lambda$$

and, T_{λ} is the transmission of the material at wavelength λ ,

S_{λ} is the source intensity,

$R_{\lambda i}$ is the color opponent system,

W_i is a weighting factor,

C_{fi} is contrast sensitivity of each system for each spatial frequency f .

B_1 , B_2 , and B_3 represent the contribution from the R-G, Y-B, and W-B1 systems. When B is normalized, the luminous transmission is obtained.

i.e.,

$$LT = \bar{B}_3 = \frac{\sum_{\lambda} T_{\lambda} S_{\lambda} R_{\lambda 3} \Delta \lambda}{\sum_{\lambda} S_{\lambda} R_{\lambda 3} \Delta \lambda}$$

The weighting factor relates how the color opponents systems should be added together. The exact values of W_i and C_{fi} are not known for the three systems.

To determine these unknowns two ruby laser protective materials (American Optical 585 and Glendale LGS-R) and a neutral density filter were chosen. The spectral transmission is shown in Figure 3. A neutral density filter of 0.4 units of density was placed in front of the American Optical Model 585 goggles so that it would have the same luminous transmission as the Glendale Optical LGS-R goggle. A second neutral density filter was also chosen to have the same luminous transmission so that the effect of uniform attenuation could be measured. Unless otherwise stated all tests and calculations were performed with the 0.4 ND filter in front of the A0585 goggle. Using a light source whose color temperature was 3200°K the relative values of B_i were calculated. The results are tabulated in Table 1.




Figure 3. Spectral Transmission of the American Optical Model 585 Ruby Goggle and the Glendale Optical Model LGS-R Ruby Goggle.

Table 1. Relative Values of B_1 .

Goggle	B_1 (R-G)	B_2 (Y-B)	B_3 (W-B1)
A0585	-43	-30	+92
LGS-R	-46	+14	+92
ND	+14	+21	+92

As seen in Table 1, these materials have one nice property. Namely since B_1 is the same for both A0585 and LGS-R then any difference in contrast sensitivity can be attributed to the Y-B system.

EXPERIMENTAL

To determine C_{fi} and W_i , threshold of detection of various gratings of different spatial frequencies were obtained using four subjects. The experimental setup is shown in Figure 4. The subject could adjust the neutral density wedge about his own threshold. He would simply increase the density until the grating faded into the background and then reverse the wedge until the grating just appeared on the screen. By using a potentiometer attached to the wedge, the optical density of the wedge could be followed on a strip chart recorder. The system was calibrated so that the wedge setting was related to the contrast. The contrast is defined as target luminance divided by the background luminance. Each grating was presented vertically and for about one minute. In this time, the subject made about 10 excursions about his threshold. Threshold is defined as the average value of the excursions. This threshold corresponds to a 50% probability of detection. Using Blackwell's average probability curve¹² the minimum to maximum excursion corresponded to a probability of 15%-85% for two observers and 25-75% for the other two observers. Fourteen gratings which subtended visual angles from 2.26 minutes per line pair to 68.4 minutes per line pair were used. The intensity of the screen was varied from 0.35 foot lamberts to 1700 foot lamberts. These light levels corresponding to known levels of illumination are shown in Table 2.




Figure 4. Schematic of Experimental Setup.

Table 2. Relationship Between Various Luminance Levels Used.

<u>Log Foot Lamberts</u>	<u>Horizon Sky Luminances</u>	<u>Visual System</u>
-6	absolute threshold	Scotopic Rods
-5	overcast starlight	
-4	starlight	
-3	quarter moon	
-2	full moon	
-1	deep twilight	Mixed
0	twilight	
1	very dark day	Photopic: Cones
2	overcast sky	
3	full daylight	
4		
5		
6		

THIS STUDY

RESULTS

The contrast sensitivity C_{f1} obtained is the usual "J-shaped" curve.¹³ However the hook of the J is caused by the experimental procedure. Hoekstra, et al.¹⁴ have shown that the threshold depends upon the number of cycles in the stimulus when less than 8 complete cycles are present for the 2.1 degree circular screen, this translates to 16 minutes per line pair. Therefore rather than report experimental artifact, only the data below 16 minutes per line pair is presented. Using Johnson's¹⁵ criterion for target detection (i.e., 50% probability of detection corresponds to detection of one line pair) the data has been converted from minutes per line pair to angular width. The contrast required for detection for the three goggles are shown in Figures 5-12. The range R is obtained by multiplying the abscissa by the diameter of the target d. For example if the target diameter is 1 meter then the abscissa is the range in meters. The ordinate is the contrast required for a 50% probability of detection.

DISCUSSION

In all cases except the lowest intensity (0.35 and 0.67 FT-L) and the highest intensity (1700 FT-L) targets viewed through the Glendale LGS-R require more contrast than the A0585 or neutral density filter. Scanning across the graphs, it can be seen that as luminance decreases, the contrast required increases. This contrast difference is much greater than the differences among the three materials at a fixed intensity level. Both the A0585 and neutral density provide about equal performance even though $\Delta B_1 = 57$ and $\Delta B_2 = 51$. It would appear then that the weighting factors are such that B_1 and B_2 cancel. Thus the quality factor may have a form such as,

$$Q = a(B_1 - B_2) + bB_3$$

Then,

$$Q = -13a + 92b \text{ for A0585}$$

$$Q = -60a + 92b \text{ for LGS-R}$$

$$Q = -7a + 92b \text{ for ND}$$

Since the luminous level has such a large effect on the contrast, $b \gg a$. From the A0585 and LGS-R curves, the difference in contrast can be attributed to $\Delta B_2 = 44$. Thus we find that the Y-B system has a poorer contrast response than the R-G system. This is consistent with Granger's findings.




Figure 5. Target-Background Contrast Required for 50% Probability of Detection as a Function of Range and Target Diameter d with Background Luminance of 1700 FT-L.




Figure 6. Target-Background Contrast Required for 50% Probability of Detection as a Function of Range and Target Diameter d with Background Luminance of 500 FT-L.




Figure 7. Target-Background Contrast Required for 50% Probability of Detection as a Function of Range and Target Diameter d with Background Luminance of 106 FT-L.




Figure 8. Target-Background Contrast Required for 50% Probability of Detection as a Function of Range and Target Diameter d with Background Luminance of 56 FT-L.




Figure 9. Target-Background Contrast Required for 50% Probability of Detection as a Function of Range and Target Diameter d with Background Luminance of 12 FT-L.




Figure 10. Target-Background Contrast Required for 50% Probability of Detection as a Function of Range and Target Diameter d with Background Luminance of 3.2 FT-L.




Figure 11. Target-Background Contrast Required for 50% Probability of Detection as a Function of Range and Target Diameter d with a Background Luminance of 0.67 FT-L.




Figure 12. Target-Background Contrast Required for 50% Probability of Detection as a Function of Range and Target Diameter d with a Background Luminance of 0.35 FT-L.




Figure 13. Target-Background Contrast Required for 50% Probability of Detection as a Function of Background Intensity for a Target Subtending 6.6 Minutes of Arc.

Although Granger and Heurtley's formulation does fit the experimental data, the data does not permit the ability to distinguish between a color opponent theory and inherent aberrations. Nor does the data suggest that this quality factor is unique.

The light intensities for representative sky luminances are shown in Table 2. The light intensities listed are those for the luminance of the screen. The actual intensity reaching the eye is reduced by the luminous transmission of the material ($LT \approx 10\%$). For the low intensities both rods and cones are functioning. The rods allow only achromatic vision. The protective materials were matched for equal photopic luminous transmission. Thus at the lower intensities (0.35 and 0.67 FT-L) the luminous intensity is no longer equal.

At the high intensities, there is no difference in detection capability. This is evident in Figure 13 where the data has been replotted as a function of intensity for a fixed visual angle. Simply stated, for high intensities, the contrast required for detection is independent of the intensity. At low intensities the LGS-R goggle requires 40% more contrast when compared to the neutral density or A0585 with equal luminous transmission. Apparently the Glendale LGS-R goggle, has no deleterious effect on detection threshold at high intensities. The shape of Figure 13 is identical to those obtained by Blackwell.¹²

Because these are static tests, there is no way of predicting how vision will be degraded in a dynamic case such as in searching or tracking.

These tests were performed on color normal subjects. Each subject had or was corrected for standard visual acuity (20/20). Since approximately 5% of the population is color blind, it is of interest to study the effect of laser protective materials on this segment of the population. One color blind individual was available for these tests. Initial testing on the Farnsworth-Munsell 100 Hue Test indicated that he was a strong deutan. When wearing the LGS-R, his color discrimination axis appeared to shift from that of a deutan to that of a protan. On the grating tests, the variability was so high that the data could not be used.

Two long-term adaptation tests were performed. The LGS-R goggle was worn for three hours. The pre- and post-results on the target detection tests were identical.

SUMMARY

1. Luminous transmission appears to be the most important parameter in detecting achromatic low contrast targets.

2. Blue targets, either natural or rendered blue by protective material, require more contrast for detection. In particular, under conditions of overcast daylight or darker, the LGS-R goggles require 40% more contrast than the A0585 with reduced transmission. Since the standard A0585 has a much higher luminance transmission, it will provide greater detection ranges than the LGS-R.

3. Laser protective materials will not degrade detection capability for high intensity targets.

4. Long term (three hours) adaptation does not change detection ability.

5. The need for a quality factor is more evident when detecting real targets (i.e., colored targets on colored background). The approach used in this study required further investigation before a definitive quality factor can be employed.

REFERENCES

1. H. L. Snyder, "Perception of Displayed Information", edited by L. Biberman, Plenum Press (1973).
2. E. Granger and K. Cupery, "An Optical Merit Function (SQF) Which Correlates with Subjective Image Judgements", Photographic Sci. and Eng. 15, 221 (1972).
3. G. Wald and D. R. Griffin, "The Change in Refractive Power of the Human Eye in Dim and Bright Light", J. Optical Soc. Am. 37, 321 (1947).
4. Y. Le Grand, "Light, Colour and Vision", (Translated by R. Hunt, J. Walsh and F. Hunt), J. Wiley (1957).
5. J. Porkorny, Ch. H. Graham and R. N. Lanson, "Effect of Wavelength on Foveal Grating Acuity", J. Optical Soc. Am. 58, 1410 (1968).
6. D. Green, "The Contrast Sensitivity of the Colour Mechanisms of the Human Eye", J. Physiol. 196, 415 (1968).
7. E. Granger, private communication.
8. D. Farnsworth, "Tritanomalous Vision as a Threshold Function", Farbe 4, 185 (1955).
9. D. Judd and A. Eastman, "Prediction of Target Visibility from the Colors of Target and Surround", Illuminating Engineering 66, 256 (1971).
10. Hurvich and Jameson's theory can be found in many vision books. See for example, "Vision and Visual Perception", C. Graham, editor, John Wiley (1965).
11. E. Granger and J. Heurtley, "Specification of Color Image Quality", J. Optical Soc. Am. 63, 1301 (1973)(Abstract WK 15).
12. H. R. Blackwell, "Contrast Thresholds of the Human Eye", J. Optical Soc. Am. 36, 624 (1946).
13. Numerous studies on contrast sensitivity have been performed. See for example, F. L. VanNes and M. A. Bonman, "Spatial Modulation Transfer in the Human Eye", J. Optical Soc. Am. 57, 401 (1967).

14. J. Hoekstra, D. P. Van Der Goot, G. Van Den Brink and F. A. Bilsen, "The Influence of the Number of Cycles Upon the Visual Contrast Threshold for Spatial Sine Wave Patterns", Vision Research 14, 365 (1974).
15. J. Johnson, "Analysis of Image Forming Systems", in Image Intensifier Symposium, Ft. Belvoir, Virginia, October 1958, AD 220160.

DISTRIBUTION

Commander
US Army Materiel, Development &
Readiness Command
5001 Eisenhower Avenue
Alexandria, VA 22333

- 1 Attn: AMCDL,
Mr. N. Klein
- 1 Attn: AMCDL,
Mr. J. Bender
- 1 Attn: DRCDE,
- 1 Attn: DRCDE-PT,
Mr. T. Shumacher
- 1 Attn: DRCDE-TP
Mr. P. Chernoff
- 1 Attn: DRCDE-FW
Mr. R. Cory
- 1 Attn: DRCDE-MT,
Mr. E. Sedlak
- 1 Attn: DRCDE-T,
Mr. R. Zentner
- 1 Attn: DRCDE-PE,
Mr. T. Jasczcult
- 1 Attn: DRCDE-G,
LTC M. Illseman

Commander
US Army Missile Command
Redstone Arsenal, AL 35809

- 1 Attn: DRSMI-RR,
Dr. G. Miller
- 1 Attn: DRSMI-RR,
LT, J. Hammond
- 1 Attn: DRSMI-R,
Dr. J. McDaniel
- 1 Attn: DRSMI-REI,
Mr. John Asbell

Commander
Aberdeen Proving Ground
Aberdeen, MD 21005

- 1 Attn: AMSTE-SA-E,
Mr. J. Bialo
- 1 Attn: STEAP-DS-TF
- 1 Attn: AMXHE-SYS,
Mr. G. Horley
- 1 Attn: AMXBR-TD,
Dr. R. Eichelberger
- 1 Attn: AMXSY-GS,
Mr. C. Odom
- 1 Attn: AMXSY-D,
Dr. J. Sperrazza

Commander
US Army Armament Command
Rock Island, IL 61201

- 1 Attn: DRSAR, CG
Commanding General
- 1 Attn: DRSAR-RDT,
Mr. J. Tuekeltaub
- 1 Attn: DRSAR-RDT,
Mr. W. Beyth
- 1 Attn: DRSAR-RD,
Mr. J. Brinkman
- 1 Attn: DRSAR-RVE,
Mr. E. Vaughan
- 1 Attn: DRSAR-RDT,
Dr. R. L. Moore
- 1 Attn: DRSAR-RD,
Director

DISTRIBUTION (Cont'd)

Commander
US Army Dugway Proving Ground
Attn: STEDP-TL, Technical Library
Dugway, UT 84022

Commander
White Sands Missile Range
White Sands, NM 88002

1 Attn: AMSEL-W-MJ,
LTC R. Coon

1 Attn: AMSEL-WL-ML,
Mr. J. Bert

1 Attn: STEWS-ID-A,
Mr. G. Galos

Commander
US Army Electronic Proving Ground
Attn: STEEP-T-B1
Ft. Huachuca, AZ 85613

Commander
Yuma Proving Ground
Attn: STEYP-AD, Technical Library
Yuma, AZ 85364

Commander
US Army Tropic Test Center
Attn: STETC-MO
APO, New York 09827

Commander
US Army Field Artillery School
Ft. Sill, OK 73503

1 Attn: Director of Combat &
Training Developments

1 Attn: Doctrine Division

1 Attn: Artillery Support Div.

1 Attn: Studies Division

Commander
US Army Tank Automotive Command
Attn: AMSTA-Z, Mr. R. McGregor
Warren, MI 48090

Commander
Combat Systems Group (CACDA)
Ft. Leavenworth, KS 66027

1 Attn: Terminal Homing Task Force,
COL De Shazo

1 Attn: Technical Director,
Dr. L. Follis

1 Attn: LTC J. Gower

Commander
Training & Doctrine Command
Ft. Belvoir, VA 22060

1 Attn: ATCD-CS-F,
LTC Davis

1 Attn: ATCD-CS-I,
LTC Griminger

Commander
USACDC, Infantry Agency
Ft. Benning, GA 31905

1 Attn: CDCINA-S,
MAJ Gibbs

1 Attn: CDCINA-S,
MAJ Binkewicz

1 Attn: CDCINA-CM,
MAJ McDonald

Commander
Edgewood Arsenal
Attn: SAREA-DE-MM, Mr. D. Anderson
SAREA-AEHA, Mr. David Sliney
Aberdeen Proving Ground, MD 21010

Commander
US Army Materials & Mechanics
Research Center
Attn: AMXMR-D, Mr. R. Fitzpatrick
Watertown, MA 02172

DISTRIBUTION (Cont'd)

Commander
Harry Diamond Laboratories
2800 Powder Mill Road
Adelphia, MD 20783

1 Attn: AMXDO-TIB

1 Attn: AMXDO-RCB,
Mr. H. Gibson

1 Attn: AMXDO-RCB,
Dr. T. Gleason

Commander
US Army Research Office-Durham
Box CM, Duke Station
Attn: Dr. R. J. Lontz
Durham, NC 27706

Commander
US Army Natick Research &
Development Command
Attn: AMXRE-PDR, Dr. E. Healy
Natick, MA 07160

Commander
US Army Electronics Command
Night Vision Laboratory
Attn: AMSEL-NV-VL, Mr. W. Lyttle
Ft. Belvoir, VA 22060

Commander
Naval Missile Center
Pt. Mugu, CA 93042

1 Attn: Mr. J. Kearney

1 Attn: Mr. Mark, Code 5351

1 Attn: Mr. Stephenson, Code 5351

Commander
Naval Research Laboratory
Washington, D.C. 20390

1 Attn: Dr. Anderson, Code 6550

1 Attn: Dr. A. Schindler, Code 6330

Commander
Wright-Patterson AF Base
Attn: AFAL/WRW, Mr. A. R. Torres
Dayton, OH 45433

Commander
Air Force Armament Laboratories
Attn: DLOS
Eglin AFB, FL 32542

Commander
USASA/ODCSRND
Arlington Hall Station
Attn: Mr. Abercrombie
Arlington, VA 22212

Commander
US Army Combat Developments
Experimentation Command
Ft. Ord, CA 93941

1 Attn: CDCEC-PPA-PA,
CPT Macia

1 Attn: CDCEC-EX-E,
Project Officer

1 Attn: CECEC-EX-E,
MAJ F. Isgrig

Commander
US Army Armament Command
Attn: AMCPM-CAWS, COL Post
Rock Island Arsenal, IL 61201

Commander
Ft. Hood
Attn: MASSTER, MAJ Alexander
Killeen, TX 76544

Office of Naval Research
Branch Office, London
Attn: ONRL, Dr. J. Bateman
Box 39
FPO, New York 09510

DISTRIBUTION (Cont'd)

Commander
US Army Electronics Command
Ft. Monmouth, NJ 07703

1 Attn: AMSEL-KL-DT,
Mr. B. Louis

2 Attn: AMSEL-CT-L,
Dr. R. Buser

1 Attn: AMSEL-CT-L,
Mr. V. DeMonte

1 Attn: AMSEL-CT-L,
Mr. M. Mirachi

US Army Foreign Science &
Technology Center
Attn: AMXST-BS (Stop 196)
Munitions Bldg.
Washington, DC 20315

President
US Army Armor & Engineering Board
Attn: STEBB-CV
Ft. Knox, KY 40121

Atmospheric Science Laboratory
USAECOM
White Sands Missile Range
White Sands, New Mexico 88002

1 Attn: SELWS-E,
Mr. M. Diamond

1 Attn: AMSEL-BL-MS,
Mr. R. B. Gomez

Director Electronic Warfare
Electronic Warfare Laboratory
Ft. Monmouth, NJ 07703

1 Attn: AMSEL-WL-D,
Mr. J. Charlton

1 Attn: AMSEL-WL-D,
Mr. C. Hardin

US Army Research Office
Room 1A881, Pentagon
Washington, DC 20301

1 Attn: DARD-ARS-PP,
MAJ A. Mullin

1 Attn: DARD-ARS-PP,
Dr. J. I. Bryant

1 Attn: DARD-ARS-PP,
Dr. R. Watson

Office of the Deputy Assistant
Commander for Combat Developments
and Training
Ft. Knox, KY 40121

1 Attn: ATSAR-CD-S,
COL Davis

1 Attn: ATSAR-CD-M,
COL Bradley

Advisory Group on Electron Devices
Attn: Secretary Working Group
on Lasers
201 Varick Street
New York, NY 10014

Mr. Douglas Beatty
ODDR&E, Air Warfare
Pentagon
Room 3E1047
Washington, DC 20301

LTC Robert D. Resley
HQDA (DARD-ART)
Pentagon
Room 3D358
Washington, DC 20301

LTC B. Krawetz
Office of Ass't Secty Defense
Intelligence Office
Pentagon, Room 3C200
Washington, DC 20301

DISTRIBUTION (Cont'd)

Department of the Air Force
Air Force Avionics Laboratory
(AFSC)
Wright-Patterson AFB, PH 45433

1 Attn: Mr. R. Firsdon

1 Attn: ASD/RWT

Air Force Weapons Laboratory
Kirtland Air Force Base
Attn: CPT M. Kemp, Bldg. 497
Albuquerque, NM 87116

Director, Eustis Directorate
US Army Air Mobility R&D
Laboratory
Attn: SAVDL-EU-SS, Mr. J. Ladd
Ft. Eustis, VA 23604

Division of Non-Ionizing Radiation
Letterman Army Institute of Res.
Presidio of San Francisco
Attn: Dr. Harry Zwick
San Francisco, CA 94129

Mr. Thomas Siolek
Gordon & Breach Science
Publishers
One Park Avenue
New York, NY 10016

Dr. David Robbins
Psychology Department
Ohio Wesleyan University
Delaware, O 43015

LTC F. Palermo
Pentagon
Attn: DARD-DD-M-F,
Room 3C367
Washington, DC 20301

Dr. R. E. Schwartz
Pentagon
Attn: ODDR&E/TWP, Rm. 3E1025
(Land Warfare)
Washington, DC 20301

Dr. John Porter
Pentagon, ODDR&E/EW&R
Room 3D139
Washington, DC 20301

LTC Guest
HQ, USAF, Pentagon
Attn: AF/RDP, Rm. 4D274
Washington, DC 20301

COL Richard McLean
Weapons System Evaluation Group
400 Army/Navy Dirve
Arlington, VA 22202

Mr. F. Reed, Product Manager
Aircraft Survivability Equipment
P.O. Box 209
St. Louis, MO 63166

MG S. Meyer
Commander
Attn: MASSTER
Ft. Hood, TX 76544

Mr. Everett Richey
School of Aerospace Medicine
Brooks Air Force Base
San Antonio, TX 78235

Advanced Research Projects Agency
Architect Building
1400 Wilson Boulevard
Arlington, VA 22209


1 Attn: Dr. E. Gerry

1 Attn: Dr. P. Clark

DISTRIBUTION (Cont'd)

Dr. M. P. Pastel Scientific Advisor-TRADOC Attn: ATDC-SI Ft. Monroe, VA 23651	Frankford Arsenal: 1 Attn: AOA-M/107-B 1 Attn: TD/107-1
Assistant Director Engineering Technology Pentagon Attn: ODDR&E, Rm. 3E1060 Mr. J. Persch Washington, DC 20301	1 Attn: PD/64-4 1 Attn: PDR/64-4 1 Attn: PDS/64-4
Defense Documentation Center (12) Cameron Station Alexandria, VA 22314	6 Attn: PDS-P/65-1 Dr. G. Holst 1 Attn: PDC/64-3 1 Attn: FC/110-1 1 Attn: FCD-O/201-2 Mr. S. C. Novak 1 Attn: FI/107-B 1 Attn: PA/107-2 1 Attn: QA/235-3 1 Attn: FCD-O/202-1 Mr. J. Walls, Jr. 1 Attn: FCA-W/110-2 Mr. W. Sipple 3 Attn: TSP-L/51-2 1 - Reference Copy 1 - Circulation Copy 1 - Tech Rpts Editing

Printing & Reproduction Division
FRANKFORD ARSENAL
Date Printed:



DEPARTMENT OF THE ARMY
FRANKFORD ARSENAL
PHILADELPHIA, PA. 19137

—
OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE \$300

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DoD-314

